



Polars cheat sheet



General

Install

```
pip install polars
```



Import

```
import polars as pl
```

Creating/reading DataFrames

Create DataFrame

nrs	names	random	groups
1	"foo"	0.3	"A"
2	"ham"	0.7	"A"
3	"spam"	0.1	"B"
null	"egg"	0.9	"C"
5	null	0.6	"B"

```
df = pl.DataFrame(  
    {  
        "nrs": [1, 2, 3, None, 5],  
        "names": ["foo", "ham", "spam", "egg", None],  
        "random": [0.3, 0.7, 0.1, 0.9, 0.6],  
        "groups": ["A", "A", "B", "C", "B"],  
    }  
)
```

Read CSV

```
df = pl.read_csv("https://j.mp/iris.csv",  
    has_header=True)
```

Read parquet

```
df = pl.read_parquet("path.parquet")
```

Expressions

Polars expressions can be performed in sequence. This improves readability of code.

```
df \  
    .filter(pl.col("nrs") < 4) \  
    .groupby("groups") \  
    .agg(  
        pl \  
        .all() \  
        .sum()  
    )
```

by Franz Diebold (diebold.io)

Subset Observations - rows



Filter: Extract rows that meet logical criteria.

```
df.filter(pl.col("random") > 0.5)  
df.filter(  
    (pl.col("groups") == "B")  
    & (pl.col("random") > 0.5)  
)
```

Sample

```
# Randomly select fraction of rows.  
df.sample(frac=0.5)  
  
# Randomly select n rows.  
df.sample(n=2)
```

Select first and last rows

```
# Select first n rows  
df.head(n=2)  
  
# Select last n rows.  
df.tail(n=2)
```

Subset Variables - columns



Select multiple columns with specific names

```
df.select(["nrs", "names"])
```

Select columns whose name matches regex

```
df.select(pl.col("^n.*$"))
```

Subsets - rows and columns



Select rows 2-4

```
df[2:4, :]
```

Select columns in positions 1 and 3 (first column is 0)


```
df[:, [1, 3]]
```

Reshaping Data – Change layout, sorting, renaming



Append rows of DataFrames

```
pl.concat([df, df2])
```



Append columns of DataFrames

```
pl.concat([df, df3], how="horizontal")
```



Gather columns into rows

```
df.melt(  
    id_vars="nrs",  
    value_vars=["names", "groups"]  
)
```



Spread rows into columns

```
df.pivot(values="nrs", index="groups",  
    columns="names")
```

Order rows by values of a column

```
# low to high  
df.sort("random")  
  
# high to low  
df.sort("random", reverse=True)
```

Rename the columns of a DataFrame

```
df.rename({"nrs": "idx"})
```

Drop columns from DataFrame

```
df.drop(["names", "random"])
```

Summarize Data

Count number of rows with each unique value of variable

```
df["groups"].value_counts()
```

of rows in DataFrame


```
len(df)  
# or  
df.height
```

Tuple of # of rows, # of columns in DataFrame

```
df.shape
```

of distinct values in a column

```
df["groups"].n_unique()
```



Basic descriptive and statistics for each column

```
df.describe()
```

Aggregation functions

```
df.select(  
    [  
        # Sum values  
        pl.sum("random").alias("sum"),  
  
        # Minimum value  
        pl.min("random").alias("min"),  
  
        # Maximum value  
        pl.max("random").alias("max"),  
        # or  
        pl.col("random").max().alias("other_max"),  
  
        # Standard deviation  
        pl.std("random").alias("std dev"),  
  
        # Variance  
        pl.var("random").alias("variance"),  
  
        # Median  
        pl.median("random").alias("median"),  
  
        # Mean  
        pl.mean("random").alias("mean"),  
  
        # Quantile  
        pl.quantile("random", 0.75) \  
        .alias("quantile_0.75"),  
        # or  
        pl.col("random").quantile(0.75) \  
        .alias("other_quantile_0.75"),  
    ]  
)
```