








LED Downlight DLS1

-  IP65
-  Class II
-  AC220-240V
-  Recessed Ceiling
-  Highly recyclable
-  50k Hours Lifetime
-  Dimming Optional: DALI, Phase Cut & 1/0-10V



Product Features:

- ✓ Delivers exceptional luminous efficiency, providing bright illumination while minimizing energy consumption, resulting in cost savings and environmental benefits.
- ✓ Constructed with a durable die-cast aluminum body, ensuring robustness and longevity in outdoor and industrial environments, with excellent heat dissipation properties for optimal performance.
- ✓ Incorporates Surface Mounted Device (SMD) technology, Known for its reliability, efficiency, and consistent light output, ensuring uniform illumination and reduced maintenance requirements.
- ✓ Features an IP65 rating, providing complete protection against dust and water, making it suitable for both dry and wet area installations.
- ✓ With its high efficacy and advanced LED technology, the downlight offers exceptional energy efficiency, helping to lower electricity bills and reduce carbon footprint.
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80.




Product Specifications:

- ✓ Housing: Die-Cast Aluminum
- ✓ Diffuser: Opal Polycarbonate
- ✓ Outstanding Temp: 0~45°C
- ✓ Delivered Lumen Output: 120lm/W
- ✓ Color Render Index > 80
- ✓ Power Factor > 0.9

Model Selection

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)DxH
DLS1-009	9 W	1080 lm	125	145x75
DLS1-017	17 W	2040 lm	125	145x75
DLS1-020	20 W	2400 lm	160	190x95
DLS1-025	25 W	3000 lm	200	230x105
DLS1-030	30 W	3600 lm	200	230x105

Selectable Options

CCT	Beam Angle	Housing
 3000K	 100°	<input type="checkbox"/> White
 4000K		
<input type="checkbox"/> 6500K		

