



Luck-i-flip

Time limit: 1000 ms
Memory limit: 256 MB

In Sierra island there is a famous game called **Luck-i-flip**. To place a bet, each participant fills a row of length n with 0 s and 1 s, representing the two sides of a coin. The bets are public to prevent multiple participants from placing the same bet.

On the day of the event, the president of the Sierra Cultural Association flips a coin n times and the winner is the participant with the most correct coin side guesses. In case of a tie, the association keeps the jackpot.

Sara does not like to gamble but she is interested in the fact that this game is not solely reliant on luck. Not every bet offers the same chances of winning. In particular, she wants to know what are the odds of winning for the worst bet on the public ledger.

For that, Sara should count how many different draws will give the prize to the worst bet. Can you help her?

Take, for example, the three bets 001 , 110 and 101 :

- for the bet 001 the winning draws are 000 , 001 and 011
- for the bet 110 the winning draws are 010 and 110
- for the bet 101 the only winning draw is 101

In this case, the worst bet is 101 and the number of different winning draws for the worst bet is 1.

Standard input

The first line is the number of bets, b in the public ledger, followed by a bet in each line.

Standard output

The output is the minimum number, m , of winning draws for the worst bet.

Constraints and notes

- $n \leq 22$
- $b \leq 100$
- $m \leq 20$

Input	Output	Explanation
<div>2 00 11</div>	<div>1</div>	<div>There are two bets, 00 and 11 . There are four possible draws of length 2: 00 , 01 , 10 , 11 . If the draw is 00 , then the winning bet would be 00 . If the draw is 11 the winning bet would be 11 . But if the draw is 01 or 10 then both bets failed one coin side and lose the jackpot. For each bet, there is only 1 draw leading it to the prize. So the answer is the minimum</div>
Input	Output	Explanation