[Emacs Speaks Statistics] Reference Card for S and R

updated for ESS 5.3.0

August 28, 2006 — as of November 16, 2006

- 1. Nota Bene: S is the language, R is one dialect!
- 2. This is a list of the more widely used key shortcuts. Many more are available, and most are accessible from the Emacs Menus such as iESS, ESS, etc.

Interacting with the S process

For use in a process buffer '*R*' (inferior-ess-mode):

| $\langle \text{RET} \rangle$ | Send a command |
|------------------------------|--------------------------------|
| $\langle \text{TAB} \rangle$ | Complete S object name |
| C-c C-c | Break |
| C-g | interrupt Emacs' waiting for S |
| C-a / C-e | Beginning / End of command |
| C-c C-u | Delete this command |
| C-c C-w | Delete last word |

Command history (part of Menu 'In/Out')

| Command | mistory (part of Menu 111/out) |
|---------------------------------|-----------------------------------|
| M-p | Previous command |
| M-n | Next command |
| C-c C-l | List command history (& choose!) |
| C-c M-r | Previous similar command |
| C-c M-s | Next similar command |
| $C-c\langle \text{RET} \rangle$ | Copy current input |
| C-c C-r | Top of last output |
| C-c C-o | Delete last output |
| Hot keys | |
| C-c C-v | Help for S object |
| C-c C-1 | Load source file (+ error check!) |
| C-c C-x | List objects |
| C-c C-s | Display search list |
| C-c C-a | Attach a directory |
| C-c C-d | Edit an object (dump to file) |
| $\overline{\text{Others}}$ | |
| C-c ' | Jump to error after C-c C-l |
| | |

Inside S Transcripts (I + O)

Quit from S

Kill the S process

C-c C-q

C-c C-z

Inside ESS transcript buffers, (*.Rout files):

| $\langle \text{RET} \rangle$ | Send and Move |
|------------------------------|--------------------------------------|
| C-c $C-n$ | Next prompt |
| C-c C-p | Previous prompt |
| C-c C-w | Clean Region (\mapsto input only) |

Editing S source

For use in ess-mode edit buffers, (*.R files):

| $\langle \text{TAB} \rangle$ | Indent this line |
|------------------------------|-------------------------------------|
| $C-c\langle TAB \rangle$ | Complete S object name |
| $M-\langle TAB \rangle$ | Complete file- / path- name |
| M-C-a | Beginning of function |
| М-С-е | End of function |
| M-C-q | Indent this expression (use at '{') |
| M-C-h | Mark this function |

| Evaluation | commands (Prefix C-u: $in/visibly$) |
|-----------------------------|--|
| C-c C-1 | Load this buffer – detect errors! |
| C-c $C-n$ | Step through code – line by line |
| C-c C-e | Evaluate an expression |
| C-c C-j | Evaluate this line |
| С-с М-ј | Evaluate this line and go |
| M-C-x | Evaluate this function |
| C-c C-f | Evaluate this function |
| C-c M-f | Evaluate this function and go |
| C-c C-p | Evaluate this paragraph and step |
| C-c C-c | Evaluate this para. or function \mathcal{E} step |
| C-c C-r | Evaluate this region |
| C-c M-r | Evaluate this region and go |
| C-c C-b | Evaluate this buffer |
| C-c M-b | Evaluate this buffer and go |
| $\underline{\text{Others}}$ | |
| C-c C-v | Help for S object |
| C-c C-d | "dump" – Edit another object |
| C-c C-z | Return to S process (at prompt) |
| | |

At SfS, or activated by M-x ess-add-MM-keys insert function() definition outline

Reading help files

For use in '*help[R](...)*' help buffers:

| SPC | Next page |
|-----|-------------------------------------|
| DEL | Previous page |
| b | Previous page ('back') |
| / | Search forwards |
| n | Next section |
| p | Previous section |
| S | Skip ('jump') to a named section |
| s e | ${ m e.g.,\ skip\ to\ "Examples:"}$ |
| 1 | Evaluate one 'Example' line |
| r | Evaluate current region |
| h | Help on another object |
| ? | Help for this mode |
| q | Return to S process ('quit) |
| x | Kill this buffer and return ('exit) |