API

SDMX 3.0 API

Operations

Search

GET Data Availability Query

GET **Data Query**

GET Metadata Query [by Metadataflow]

GET Metadata Query [by Metadatasets]

GET Metadata Query [by Structure]

GET Structure Query [Structure Type, Agency, Resource, Version, Item]

GET Structure Query [Structure Type, Agency, Resource, Version]

GET Structure Query [Structure Type, Agency, Resource]

GET Structure Query [Structure Type, Agency]

GET Structure Query [Structure Type]

SDMX 3.0 API

View changelog

Download definition Select definition type

SDMX version 3.0 introduces new features, improvements and changes to the information model, structural metadata artifacts, and data queries. Learn more about SDMX 3.0 changes here.

The IMF API allows developers to build applications and integrate IMF data. You can use the IMF APIs to import economic and financial data from databases available on http://data.imf.org/ into your data systems or applications. For additional information on working with the API, refer to the Help here. For questions, contact datahelp@imf.org.

Data Query

Data queries allow **retrieving statistical data**.

Entire datasets can be retrieved or individual observations, or anything in between, using filters on dimensions (including time), attributes and/or measures.

All data matching a query can be retrieved or only the data that has changed since the last time the same query was performed.

Using the *includeHistory* parameter, it is also possible to retrieve previous versions of the data.

Last but not least, the data retrieved can be packaged in different ways (as time series, cross-sections or as a table), in a variety of formats (JSON, XML, CSV, etc.).

Endpoint:

Tags: Data queries

GET https://api.imf.org/external/sdmx/3.0/data/{context}/{agencyID}/{resource
[?c][&updatedAfter][&firstNObservations][&lastNObservations]
[&dimensionAtObservation][&attributes][&measures]
[&includeHistory][&asOf]

Try this operation

Request

Request parameters

Name	In	Required	Type	Descr

context	template	true	string	The co for da retriev possib contex be sel using
agencyID	template	true	array	The maint of the artefa Multip values be sel by usi as a separa can be as sho to sele availal maint
resourceID	template	true	array	The ar ID(s). Multip values be sel by usi as a separa can be as sho to sele availal artefa
version	template	true	array	The versio the ar

Multip
values
be sel
by usi
as a
separa
can be
as sho
to sele
availal
artefa

+ can
used t
retriev
latest
versio

~ can
used t
retriev
latest
versio
regard
of its s
(stable
draft,

key	template	true	array	The combi of dimer values identif series slices cube (examp `D.USD` Multip values possib Wildca are suppo using (`D.*.E`
c	query	false	object	Filter by compo value c[FREQ Multip values suppo In add opera may b used: **Op** eq ne

				Op lt le gt ge co nc sw ew Opera appea prefix compo value(are separa from i : (e.g. c[TIM 01+le 12).
updatedAf...	query	false	string	Forma date-t (as da time i RFC33 The la time t query

				perfor by the If this param used, return messa should includ dimer values the da that h chang since t point i (upda and revisic
firstNObse...	query	false	integer	The maxin numb obser to be return each c match series, startir from t first obser
lastNObse...	query	false	integer	The maxin numb obser to be return each c match series, counti back f the m

				recent obser
dimension...	query	false	string	This param allows client indica the da shoul packa the se The op are: • •

attributes	query	false	array	The attribu be ret For examp is pos to inst the we servic return only (i attribu
measures	query	false	array	The measu be ret
includeHis...	query	false	boolean	This attribu allows retriev previo versio the da they w disser in the (*histor timelir* functi
asOf	query	false	string	Forma date-t (as da time i

RFC33
Retrie
resou
it was
suppli
point
(aka ti
travel)

Response: 200 OK

OK

Table Schema Content type application/json

Data-context-agencyID-resourceID-version-key-Get200ApplicationJsonResponse

default

default (json)


```
{
    "data": {
        "dataSets": [{
            "action": "Information",
            "series": {
                "0:0:0:0:0:0": {
                    "attributes": [null],
                    "observations": {
                        "0": ["-803260893.854749", 0, null],
                        "1": ["-755969273.743017", 0, null]
                    }
                }
            },
            "structure": 0
        }],
```

```
            "structures": [{
                "annotations": [],
                "attributes": {
                    "dataSet": [{
                        "id": "COMMENT",
                        "isMandatory": false,
                        "relationship": {
                            "dataflow": {}
                        },
                        "roles": [],
                        "values": []
                    }, {
                        "id": "BASE_PER",
                        "isMandatory": false,
                        "relationship": {
                            "dataflow": {}
                        },
                        "roles": [],
                        "values": []
                    }],
                    "observation": [{
                        "id": "UNIT_MULT",
                        "isMandatory": false,
                        "relationship": {
                            "observation": {}
                        },
                        "roles": [],
                        "values": [{
                            "id": "6"
                        }, {
                            "id": "0"
                        }]
                    }, {
                        "id": "OBS_STATUS",
                        "isMandatory": false,
                        "relationship": {
                            "observation": {}
                        },
                        "roles": [],
                        "values": []
                    }],
                    "series": [{
                        "id": "TIME_FORMAT",
                        "isMandatory": false,
                        "relationship": {
                            "dimensions": ["DATA_DOMAIN", "REF_AREA"
```

```
                    },
                    "roles": [],
                    "values": []
                }]
            },
            "dataSets": [0],
            "dimensions": {
                "observation": [{
                    "id": "TIME_PERIOD",
                    "keyPosition": 6,
                    "values": [{
                        "value": "2011"
                    }, {
                        "value": "2012"
                    }]
                }],
                "series": [{
                    "id": "DATA_DOMAIN",
                    "keyPosition": 0,
                    "roles": [],
                    "values": [{
                        "id": "BOP6"
                    }]
                }, {
                    "id": "REF_AREA",
                    "keyPosition": 1,
                    "roles": [],
                    "values": [{
                        "id": "1C_355"
                    }]
                }]
            },
            "links": [{
                "title": "Dataflow",
                "urn": "urn:sdmx:org.sdmx.infomodel.datastructur
            }, {
                "title": "DataStructureDefinition",
                "urn": "urn:sdmx:org.sdmx.infomodel.datastructur
            }],
            "measures": {
                "observation": [{
                    "id": "OBS_VALUE",
                    "roles": []
                }]
            }
        }]
```

```
    },
    "meta": {}
}
```


Definitions

Powered by Azure API Management.

Name	Description
Data-context-agencyID-resourceID-version-key-Get200ApplicationJsonResponse	

Data-context-agencyID-resourceID-version-key-Get200ApplicationJsonResponse

Table Schema

Data-context-agencyID-resourceID-version-key-Get200ApplicationJsonResponse