API

SDMX 3.0 API

Operations

Search

GET Data Availability Query

GET Data Query

GET Metadata Query [by Metadataflow]

GET Metadata Query [by Metadatasets]

GET Metadata Query [by Structure]

GET Structure Query [Structure Type, Agency, Resource, Version, Item]

GET Structure Query [Structure Type, Agency, Resource, Version]

GET Structure Query [Structure Type, Agency, Resource]

GET Structure Query [Structure Type, Agency]

GET Structure Query [Structure Type]

SDMX 3.0 API

View changelog

Download definition Select definition type

SDMX version 3.0 introduces new features, improvements and changes to the information model, structural metadata artifacts, and data queries. Learn more about SDMX 3.0 changes here.

The IMF API allows developers to build applications and integrate IMF data. You can use the IMF APIs to import economic and financial data from databases available on http://data.imf.org/ into your data systems or applications. For additional information on working with the API, refer to the Help here. For questions, contact datahelp@imf.org.

Structure Query [Structure Type, Agency, Resource, Version, Item]

'Item queries extend structure queries by allowing to retrieve items in item schemes such as particular codes in a codelist.'

Endpoint:

Tags: Structure queries

GET https://api.imf.org/external/sdmx/3.0/structure/{structureType}/{agencyID
[?detail][&references][&asOf]

Try this operation

Request

Request parameters

Name	In	Required	Type	Descr
structureT...	template	true	string	The ty struct metac (e.g. codeli datafl etc.)
agencyID	template	true	array	The maint

				of the artefa Multip values be sel by usi as a separa can be as sho to sele availal maint
resourceID	template	true	array	The ar ID(s). Multip values be sel by usi as a separa can be as sho to sele availal artefa
version	template	true	array	The versio the ar Multip values be sel by usi as a separa can be as sho to sele availal artefa

				+ can used t retriev latest versio ~ can used t retriev latest versio regarc of its s (stable draft,
itemID	template	true	array	The id item t return Multip values possib * can used a shortc select items.
detail	query	false	string	This attribu specif desire amou inform to be return For examp is pos to inst the we servic return basic inform about

maint
artefa
id, age
id, ver
and n
Most
notab
items
item
schem
not be
return
(for
examp
will no
return
codes
code l
query)

Possib
values

`full` -
availal
inform
for all
return
artefa
shoul
return
Return
exten
codeli
to be
resolv
includ
inherit
codes,
must
includ
Codeli
prope
the
inherit
codeli
must l
resolv
they s

not be
return
secon
as
separa
codeli

`allst`
all ret
artefa
should
return
stubs,
only
contai
identif
inform
and th
artefa
name.

`refer`
- same
full wi
excep
that
refere
artefa
should
return
only a
stubs,
only
contai
identif
inform
and th
artefa
name.

`allco`
all ret
artefa
should
return
compl
stubs,
only
contai

identif
inform
the
artefa
name,
descri
and
annot

`refer`
- same
full wi
excep
that
refere
artefa
shoul
return
compl
stubs,
only
contai
identif
inform
the
artefa
name,
descri
and
annot

`refer`
- same
full wi
excep
that
refere
item
schem
shoul
includ
items
by the
artefa
be ret

`raw` - s
as full
the

				excep that th return exten codeli not re and m includ Codeli prope and if refere codeli desce are to return then t includ all inh codeli
references	query	false	array	This attribu instru web s to retu not) th artefa refere by the artefa be ret (for examp the co lists a conce used b data struct definit match the qu as wel the ar that u match artefa

exam
the
datafl
that u
data
struct
definit
match
the qu

Possib
values

none -
refere
will be
return

paren
the ar
that u
artefa
match
the qu

paren
- the
artefa
that u
artefa
match
the qu
as wel
the ar
refere
by the
artefa

ances
the ar
that u
artefa
match
the qu
up to
level

child
artefa
refere

				by the artefa be ret `desce` - refer of refere up to level, also b return `all` - t combi of paren and desce In add a conc type o resou may a used (examp `refer`
asOf	query	false	string	Forma date-t (as da time i RFC33 Retrie resou it was suppli point i (aka ti travel)

Request headers

Name	Required	Type	Descriptio
Accept	false	string	Specifies th output forı `applicati` (the defaul indicates th output forı a json.

Response: 200 OK

OK

Table Schema Content type application/json

Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationJsonResponse

default

default (json)


```
{
    "data": {
        "codeLists": [{
            "agencyID": "SDMX",
            "annotations": [{
                "id": "origin",
                "text": null,
                "title": null,
                "type": null,
                "value": "INTEGRATION"
            }, {
```

```
                "id": "isFinal",
                "text": null,
                "title": null,
                "type": null,
                "value": null
            }, {
                "id": "lastUpdatedAt",
                "text": null,
                "title": null,
                "type": null,
                "value": "2023-02-21T07:31:30Z"
            }],
            "codes": [{
                "annotations": [],
                "description": "To be used for data collected or
                "descriptions": {
                    "en": "To be used for data collected or diss
                },
                "id": "A",
                "name": "Annual",
                "names": {
                    "en": "Annual"
                }
            }],
            "description": "This code list provides a set of val
            "descriptions": {
                "en": "This code list provides a set of values i
            },
            "id": "CL_FREQ",
            "isPartial": true,
            "links": [{
                "rel": "self",
                "type": "codelist",
                "urn": "urn:sdmx:org.sdmx.infomodel.codelist.Coc
            }],
            "name": "Frequency",
            "names": {
                "en": "Frequency"
            },
            "version": "2.0"
        }]
    },
    "meta": {
        "contentLanguages": ["en"],
        "id": "IDREF9418",
        "prepared": "2023-08-17T12:34:35Z",
```

```
        "schema": "https://raw.githubusercontent.com/sdmx-twg/sc
        "sender": {
            "id": "unknown"
        },
        "test": false
    }
}
```


Definitions

Name	Description
Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationJsonResponse	
Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationXmlResponse	

Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationJsonResponse

Table Schema

Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationJsonResponse

Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationXmlResponse

Table Schema

Powered by Azure API Management.

Structure-structureType-agencyID-resourceID-version-itemID-Get200ApplicationXmlResponse