API

SDMX 3.0 API

Operations

Search

GET Data Availability Query

GET Data Query

GET Metadata Query [by Metadataflow]

GET Metadata Query [by Metadatasets]

GET Metadata Query [by Structure]

GET Structure Query [Structure Type, Agency, Resource, Version, Item]

GET Structure Query [Structure Type, Agency, Resource, Version]

GET Structure Query [Structure Type, Agency, Resource]

GET Structure Query [Structure Type, Agency]

GET Structure Query [Structure Type]

SDMX 3.0 API

View changelog

Download definition Select definition type

SDMX version 3.0 introduces new features, improvements and changes to the information model, structural metadata artifacts, and data queries. Learn more about SDMX 3.0 changes here.

The IMF API allows developers to build applications and integrate IMF data. You can use the IMF APIs to import economic and financial data from databases available on http://data.imf.org/ into your data systems or applications. For additional information on working with the API, refer to the Help here. For questions, contact datahelp@imf.org.

Structure Query [Structure Type, Agency, Resource, Version]

Structure queries when no item is specified. The item is equivalent to "*".

Structure queries in SDMX allow you to retrieve structural metadata at various levels of granularity, from all structural metadata available in the source to a single code from a particular version of a particular codelist maintained by a particular agency.

Endpoint:

Tags: Structure queries

GET https://api.imf.org/external/sdmx/3.0/structure/{structureType}/{agencyID
[?detail][&references][&asOf]

Try this operation

Request

Request parameters

Name	In	Required	Type	Descr
structureT...	template	true	string	The ty struct metac (e.g. codeli datafl etc.)

agencyID	template	true	array	The maint of the artefa Multip values be sel by usi as a separa can be as sho to sele availal maint
resourceID	template	true	array	The ar ID(s). Multip values be sel by usi as a separa can be as sho to sele availal artefa
version	template	true	array	The versio the ar Multip values be sel by usi as a separa can be as sho to sele

				availal artefa + can used t retriev latest versio ~ can used t retriev latest versio regarc of its s (stable draft,
detail	query	false	string	This attribu specif desire amou inform to be return For examp is pos to inst the we servic return basic inform about maint artefa id, age id, ver and na Most notab items item schem not be

return
(for
examp
will no
return
codes
code l
query)

Possib
values

`full` -
availal
inform
for all
return
artefa
should
return
Return
exten
codeli
to be
resolv
includ
inherit
codes,
must r
includ
Codeli
prope
the
inherit
codeli
must l
resolv
they s
not be
return
secon
as
separa
codeli

`allst`
all retu
artefa
should

return
stubs,
only
contai
identif
inform
and th
artefa
name.

`refer`
- same
full wi
excep
that
refere
artefa
shoul
return
only a
stubs,
only
contai
identif
inform
and th
artefa
name.

`allco`
all ret
artefa
shoul
return
compl
stubs,
only
contai
identif
inform
the
artefa
name,
descri
and
annot

`refer`
- same

full wi
excep
that
refere
artefa
shoul
return
compl
stubs,
only
contai
identi
inform
the
artefa
name,
descri
and
annot

`refer`
- same
full wi
excep
that
refere
item
schem
shoul
includ
items
by the
artefa
be ret

`raw` - s
as full
the
excep
that th
return
exten
codeli
not re
and m
includ
Codeli
prope
and if

				refere codeli desce are to return then t includ all inh codeli
references	query	false	array	This attribu instru web s to retu not) th artefa refere by the artefa be ret (for examp the co lists a conce used b data struct definit match the qu as wel the ar that u match artefa examp the datafl that u data struct definit match the qu

Possib
values

none -
refere
will be
return

paren
the ar
that u
artefa
match
the qu

paren
- the
artefa
that u
artefa
match
the qu
as wel
the ar
refere
by the
artefa

ances
the ar
that u
artefa
match
the qu
up to
level

child
artefa
refere
by the
artefa
be ret

desce
- refer
of
refere
up to

				level, v also b return `all` - t combi of paren and desce In add a conc type o resou may a used (examp `refer`
asOf	query	false	string	Forma date-t (as da time i RFC33 Retrie resou it was suppli point i (aka ti travel)

Request headers

Name	Required	Type	Descriptio
Accept	false	string	Specifies th output for `applicati` (the defaul indicates th

output for
a json.

Response: 200 OK

OK

Table Schema Content type application/json

Structure-structureType-agencyID-resourceID-version-Get200ApplicationJsonResponse

default

default (json)


```
{
    "data": {
        "codeLists": [{
            "agencyID": "SDMX",
            "annotations": [{
                "id": "origin",
                "text": null,
                "title": null,
                "type": null,
                "value": "INTEGRATION"
            }, {
                "id": "isFinal",
                "text": null,
                "title": null,
                "type": null,
                "value": null
            }, {
                "id": "lastUpdatedAt",
                "text": null,
                "title": null,
                "type": null,
```

```
                "value": "2023-02-21T07:31:30Z"
            }],
            "codes": [{
                "annotations": [],
                "description": "To be used for data collected or
                "descriptions": {
                    "en": "To be used for data collected or diss
                },
                "id": "A",
                "name": "Annual",
                "names": {
                    "en": "Annual"
                }
            }],
            "description": "This code list provides a set of val
            "descriptions": {
                "en": "This code list provides a set of values i
            },
            "id": "CL_FREQ",
            "isPartial": true,
            "links": [{
                "rel": "self",
                "type": "codelist",
                "urn": "urn:sdmx:org.sdmx.infomodel.codelist.Coc
            }],
            "name": "Frequency",
            "names": {
                "en": "Frequency"
            },
            "version": "2.0"
        }]
    },
    "meta": {
        "contentLanguages": ["en"],
        "id": "IDREF9418",
        "prepared": "2023-08-17T12:34:35Z",
        "schema": "https://raw.githubusercontent.com/sdmx-twg/sc
        "sender": {
            "id": "unknown"
        },
        "test": false
    }
}
```

Definitions

Name	Description
Structure-structureType-agencyID-resourceID-version-Get200ApplicationJsonResponse	
Structure-structureType-agencyID-resourceID-version-Get200ApplicationXmlResponse	

Structure-structureType-agencyID-resourceID-version-Get200ApplicationJsonResponse

Table Schema

Structure-structureType-agencyID-resourceID-version-Get200ApplicationJsonResponse

Structure-structureType-agencyID-resourceID-version-Get200ApplicationXmlResponse

Table Schema

Structure-structureType-agencyID-resourceID-version-Get200ApplicationXmlResponse

Powered by Azure API Management.