fred/series/tags

Terms of Use

- Description
- Examples
  - XML
  - JSON
- Parameters
  - api_key
  - file_type
  - series_id
  - realtime_start
  - realtime_end
  - order_by
  - sort_order

Description

Get the FRED tags for a series.

Examples

This request can return either XML or JSON by setting the file_type parameter to xml or json. Note that the default value of file_type is xml. The API key 'abcdefghijklmnopqrstuvwxyz123456' is for demonstration purposes only. Use a registered API key instead.

XML

Request (HTTPS GET)

```
https://api.stlouisfed.org/fred/series/tags?series_id=STLFSI&api_key=abcdefghijklmnopqrstuvwxyz
```

Response

```
<tags realtime_start="2013-08-14" realtime_end="2013-08-14" order_by="series_count" sort_
    <tag name="nation" group_id="geot" notes="Country Level" created="2012-02-27 10:18:1
    <tag name="nsa" group_id="seas" notes="Not seasonally adjusted" created="2012-02-27
    <tag name="usa" group_id="geo" notes="United States of America" created="2012-02-27
    <tag name="frb stl" group_id="src" notes="Federal Reserve Bank of St. Louis (source)" cr
    <tag name="financial" group_id="gen" notes="" created="2012-02-27 10:18:19-06" popula
    <tag name="weekly" group_id="freq" notes="" created="2012-02-27 10:18:19-06" popular
    <tag name="indexes" group_id="gen" notes="" created="2012-02-27 10:18:19-06" popula
    <tag name="stlfsi" group_id="rls" notes="St. Louis Financial Stress Index" created="2012
</tags>
```


JSON

Request (HTTPS GET)

```
https://api.stlouisfed.org/fred/series/tags?series_id=STLFSI&api_key=abcdefghijklmnopqrstuvwxyz
```

Response

```
{
    "realtime_start": "2013-08-14",
    "realtime_end": "2013-08-14",
    "order_by": "series_count",
    "sort_order": "desc",
    "count": 8,
    "offset": 0,
    "limit": 1000,
    "tags": [
        {
            "name": "nation",
            "group_id": "geot",
            "notes": "Country Level",
            "created": "2012-02-27 10:18:19-06",
            "popularity": 100,
            "series_count": 105200
        },
        {
            "name": "nsa",
            "group_id": "seas",
            "notes": "Not seasonally adjusted",
            "created": "2012-02-27 10:18:19-06",
            "popularity": 96,
            "series_count": 100468
        },
        {
            "name": "usa",
            "group_id": "geo",
            "notes": "United States of America",
            "created": "2012-02-27 10:18:19-06",
            "popularity": 100,
            "series_count": 59469
        },
        {
            "name": "frb stl",
            "group_id": "src",
            "notes": "Federal Reserve Bank of St. Louis (source)",
            "created": "2012-02-27 10:18:19-06",
            "popularity": 81,
            "series_count": 4329
        },
        {
            "name": "financial",
            "group_id": "gen",
            "notes": "",
            "created": "2012-02-27 10:18:19-06",
            "popularity": 70,
            "series_count": 2134
```

```
            },
            {
                "name": "weekly",
                "group_id": "freq",
                "notes": "",
                "created": "2012-02-27 10:18:19-06",
                "popularity": 82,
                "series_count": 2013
            },
            {
                "name": "indexes",
                "group_id": "gen",
                "notes": "",
                "created": "2012-02-27 10:18:19-06",
                "popularity": 79,
                "series_count": 1567
            },
            {
                "name": "stlfsi",
                "group_id": "rls",
                "notes": "St. Louis Financial Stress Index",
                "created": "2012-08-16 15:21:17-05",
                "popularity": 66,
                "series_count": 1
            }
        ]
    }
```


Parameters

api_key

Read API Keys for more information.

- 32 character alpha-numeric lowercase string, required

file_type

A key or file extension that indicates the type of file to send.

- string, optional, default: xml
- One of the following values: 'xml', 'json'
  xml = Extensible Markup Language. The HTTP Content-Type is text/xml.
  json = JavaScript Object Notation. The HTTP Content-Type is application/json.

series_id

The id for a series.

- string, required

realtime_start

The start of the real-time period. For more information, see Real-Time Periods.

- YYYY-MM-DD formatted string, optional, default: today's date

realtime_end

The end of the real-time period. For more information, see Real-Time Periods.

- YYYY-MM-DD formatted string, optional, default: today's date

order_by

Order results by values of the specified attribute.

- One of the following strings: 'series_count', 'popularity', 'created', 'name', 'group_id'.
- optional, default: series_count

sort_order

Sort results is ascending or descending order for attribute values specified by order_by.

- One of the following strings: 'asc', 'desc'.
- optional, default: asc

Subscribe to the FRED newsletter

Email Subscribe

Follow us

Need Help?

Questions or Comments

FRED Help

Legal

Privacy Notice & Policy