

mstsa: A Python Library for Information-Theoretic and Statistical Analysis of EEG Microstate Sequences

Frederic von Wegner ¹ 

¹ School of Biomedical Sciences, University of New South Wales (UNSW)  Corresponding author

Software

- [Repository](#) 

Summary

EEG microstate analysis decomposes a multichannel EEG recording into a discrete symbolic time series: each sample is assigned to one of a small number of voltage topography templates, the microstate maps, typically at sampling rates of 100–500 Hz ([Lehmann et al., 1998](#); [Michel & Koenig, 2018](#); [Pascual-Marqui et al., 1995](#)). Back-fitting the templates into the original EEG dataset yields a symbolic time series, the microstate sequence. Many research questions address the temporal structure of these sequences, such as: time series memory (Markovianity), autocorrelations including persistence and long-range correlations, measures of syntax and complexity, and comparison against certain null models.

mstsa (Microstate Time Series Analysis) is a Python library that addresses these questions. It provides a comprehensive set of information-theoretic, Markov-chain, and statistical tools for the analysis of discrete symbolic sequences, with EEG microstate data as the primary application. The library exposes six modules:

- **mstsa** (core): the classical microstate parameters duration, occurrence, and coverage; basic functions to compute Shannon, Rényi, and Tsallis entropies; extensions such as block, topological ([Adler et al., 1965](#)), and dispersion ([Rostaghi & Azami, 2016](#)) entropies; entropy rate and excess entropy ([Crutchfield & Feldman, 2003](#)); auto-information function (AIF) and partial auto-information function (PAIF) ([von Wegner et al., 2017](#); [von Wegner, 2018](#)); active information storage (AIS) ([Lizier, 2014](#)); sample entropy for discrete sequences, using exact-match comparison and a runs-tracking algorithm that computes estimates for all template lengths in a single $O(N^2)$ pass ([Lake et al., 2002](#); [Richman & Moorman, 2000](#)); Lempel–Ziv complexity ([Kaspar & Schuster, 1987](#); [Lempel & Ziv, 1976](#)); detrended fluctuation analysis (DFA) ([Peng et al., 1994](#)), rescaled-range (R/S) analysis ([Hurst, 1951](#)), and diffusion entropy analysis (DEA) ([Scafetta & Grigolini, 2002](#)), applicable to both binary-partition random walks and to indicator functions (one-hot encoding) of individual microstate classes; power spectral densities of indicator functions ([Hermann & others, 2024](#)); and random-walk construction from binary partitions ([Van De Ville et al., 2010](#); [von Wegner et al., 2016](#)).
- **markov**: Conditional and joint transition probability matrices, stationary distribution, continuous-time generator matrix, AIF and sample entropy under first-order Markov models ([von Wegner, 2026](#)), surrogate sequence generation ([von Wegner et al., 2025](#)), nearest-reversible Markov chain projection ([Nielsen & Weber, 2015](#)), and detailed-balance statistics ([Lynn et al., 2021](#); [Roldán & Parrondo, 2010](#)).
- **stats**: Likelihood-ratio (G) tests for zero-, first-, and second-order Markovianity; j- and jk-homogeneity (stationarity); conditional homogeneity; transition-matrix symmetry ([Kullback et al., 1962](#)); geometric sojourn-time distributions; sojourn-time distribution fitting that contrasts power-law, exponential, stretched-exponential, and lognormal candidates via the powerlaw package ([Alstott et al., 2014](#); [Clauset et al., 2009](#)); and a permutation-based multi-subject transition syntax test ([Lehmann et al., 2005](#)).
- **acd**: Autoregressive Conditional Duration (ACD) model ([Engle & Russell, 1998](#))

of sojourn-time sequences, with exponential, Weibull, or lognormal innovations, AIC/BIC-based order selection, a Ljung–Box residual autocorrelation test, ACD surrogate-sequence simulation, and ACF/PACF diagnostic plots — quantifying serial clustering between consecutive sojourn durations, complementary to the marginal-distribution fitting in stats.

- **eeg:** Wackermann/Palus multichannel EEG complexity measures — effective dimensionality Ω , effective voltage Σ , generalized frequency Φ , and Palus complexity coefficient (Paluš et al., 1992; Wackermann, 1996); and continuous sample entropy (sample_entropy_cont), using finite neighbourhood matching (Lake et al., 2002; Richman & Moorman, 2000).
- **microsynt:** Python implementation of the Microsynt syntactic analysis method (Artoni et al., 2023).

Computationally demanding routines are accelerated by Numba JIT compilation with persistent disk caching (Lam et al., 2015) and optional CFFI-linked C extensions for block entropy, Lempel–Ziv complexity, and continuous and discrete sample entropy.

Statement of Need

EEG microstate research spans five decades, has received growing attention in recent years, and has produced a rich body of results linking microstate dynamics to cognition, sleep, anaesthesia, and neurological and psychiatric disorders (Michel & Koenig, 2018). The standard analysis pipeline has two stages: (1) identifying the template (or microstate) maps by clustering, followed by back-fitting into the original EEG dataset, (2) analyzing the resulting symbolic sequence.

Stage 1 is well covered by existing software. CARTOOL (Brunet et al., 2011), the EEGLAB microstate toolbox (Poulsen et al., 2018), MICROSTATELAB (Nagabhushan Kalburgi et al., 2023), and the Python library Pycrostates (Férat et al., 2022) all provide clustering and segmentation tools. Pycrostates in particular integrates cleanly with the MNE-Python ecosystem and supports both subject- and group-level analyses.

Stage 2, time series analysis, is only partially covered in current software packages. The conventional summary statistics mean duration, occurrence rate, coverage, and transition probabilities, are widely available in the software packages listed above, but numerous recent developments going beyond marginal and first-order sequence properties are still unavailable as a systematic open source library. Information-theoretic characterization that reveals higher-order temporal dependencies, e.g. entropy rate, excess entropy, auto-information structure, and Lempel–Ziv complexity, and, critically, their Markov-chain reference values that establish significance baselines, has only been formalized recently (von Wegner et al., 2017; von Wegner, 2026; von Wegner & Laufs, 2024). These methods are currently scattered across individual publications and an earlier Python package implementing a subset of these methods (von Wegner & Laufs, 2018b).

mstsa fills a gap and extends that work with a substantially expanded function set, C-accelerated implementations, and Numba JIT compilation. It is the only Python library that (i) implements the full set of information-theoretic complexity measures for symbolic sequences alongside their first-order Markov-chain predictions, enabling direct quantification of non-Markovian excess structure; (ii) provides the Kullback-information likelihood-ratio tests for Markovianity, stationarity, and transition-matrix symmetry (Kullback et al., 1962); (iii) includes different methods to estimate Hurst exponents from microstate sequences (von Wegner & Laufs, 2024); and (iv) models serial dependence between consecutive sojourn durations directly, via Autoregressive Conditional Duration models (Engle & Russell, 1998), rather than only characterizing each duration's marginal distribution in isolation. The ability to compare empirical measures to analytically and/or numerically derived Markov-chain reference values is a distinctive feature of the library (von Wegner, 2026).

The library is standalone: it does not require MNE-Python and operates on any integer-valued symbolic sequence. This makes it applicable beyond EEG to any domain in which discrete time series arise, such as MEG-derived microstates, fMRI-defined sequences of network activations, and electrophysiological *in vitro* data. An earlier version (0.2.0) has been used in a series of peer-reviewed publications characterizing microstate dynamics during resting state, propofol anaesthesia, and sleep (Hermann & others, 2024; von Wegner et al., 2016, 2017; von Wegner, 2026; von Wegner & Laufs, 2018a, 2024).

Acknowledgements

This work did not receive external funding.

References

- Adler, R. L., Konheim, A. G., & McAndrew, M. H. (1965). Topological entropy. *Transactions of the American Mathematical Society*, 114(2), 309–319. <https://doi.org/10.2307/1994177>
- Alstott, J., Bullmore, E., & Plenz, D. (2014). Powerlaw: A Python package for analysis of heavy-tailed distributions. *PLOS ONE*, 9(1), e85777. <https://doi.org/10.1371/journal.pone.0085777>
- Artoni, F., Maillard, J., Britz, J., Brunet, D., Lysakowski, C., Tramèr, M. R., & Michel, C. M. (2023). Microsynt: Exploring the syntax of EEG microstates. *NeuroImage*, 277, 120196. <https://doi.org/10.1016/j.neuroimage.2023.120196>
- Brunet, D., Murray, M. M., & Michel, C. M. (2011). Spatiotemporal analysis of multichannel EEG: CARTOOL. *Computational Intelligence and Neuroscience*, 2011, 813870. <https://doi.org/10.1155/2011/813870>
- Clauset, A., Shalizi, C. R., & Newman, M. E. J. (2009). Power-law distributions in empirical data. *SIAM Review*, 51(4), 661–703. <https://doi.org/10.1137/070710111>
- Crutchfield, J. P., & Feldman, D. P. (2003). Regularities unseen, randomness observed: Levels of entropy convergence. *Chaos: An Interdisciplinary Journal of Nonlinear Science*, 13(1), 25–54. <https://doi.org/10.1063/1.1530990>
- Engle, R. F., & Russell, J. R. (1998). Autoregressive conditional duration: A new model for irregularly spaced transaction data. *Econometrica*, 66(5), 1127–1162. <https://doi.org/10.2307/2999632>
- Férat, V., Scheltienne, M., Brunet, D., Ros, T., & Michel, C. (2022). Pycrostates: A Python library to study EEG microstates. *Journal of Open Source Software*, 7(78), 4564. <https://doi.org/10.21105/joss.04564>
- Hermann, B., & others. (2024). Propofol reversibly attenuates short-range microstate ordering and 20 Hz microstate oscillations. *Brain Topography*, 37(2), 329–342. <https://doi.org/10.1007/s10548-023-01023-1>
- Hurst, H. E. (1951). Long-term storage capacity of reservoirs. *Transactions of the American Society of Civil Engineers*, 116, 770–779.
- Kaspar, F., & Schuster, H. G. (1987). Easily calculable measure for the complexity of spatiotemporal patterns. *Physical Review A*, 36(2), 842–848. <https://doi.org/10.1103/PhysRevA.36.842>
- Kullback, S., Kupperman, M., & Ku, H. H. (1962). Tests of stationarity of a Markov chain. *Technometrics*, 4(3), 307–325. <https://doi.org/10.1080/00401706.1962.10490015>

- Lake, D. E., Richman, J. S., Griffin, M. P., & Moorman, J. R. (2002). Sample entropy analysis of neonatal heart rate variability. *American Journal of Physiology — Regulatory, Integrative and Comparative Physiology*, 283(3), R789–R797. <https://doi.org/10.1152/ajpregu.00069.2002>
- Lam, S. K., Pitrou, A., & Seibert, S. (2015). Numba: A LLVM-based Python JIT compiler. *Proceedings of the Second Workshop on the LLVM Compiler Infrastructure in HPC*, 1–6. <https://doi.org/10.1145/2833157.2833162>
- Lehmann, D., Faber, P. L., Galderisi, S., Herrmann, W. M., Kinoshita, T., Koukkou, M., Mucci, A., Pascual-Marqui, R. D., Saito, N., Wackermann, J., & others. (2005). EEG microstate duration and syntax in attention-deficit hyperactivity disorder: First evidence. *Psychiatry Research: Neuroimaging*, 138(2), 141–152. <https://doi.org/10.1016/j.psychresns.2004.05.007>
- Lehmann, D., Strik, W. K., Henggeler, B., Koenig, T., & Koukkou, M. (1998). Brain electric microstates in spontaneous EEG of restful wakefulness predict onset of a novel thought. *International Journal of Psychophysiology*, 29(1), 1–11. [https://doi.org/10.1016/S0167-8760\(97\)00098-3](https://doi.org/10.1016/S0167-8760(97)00098-3)
- Lempel, A., & Ziv, J. (1976). On the complexity of finite sequences. *IEEE Transactions on Information Theory*, 22(1), 75–81. <https://doi.org/10.1109/TIT.1976.1055501>
- Lizier, J. T. (2014). JIDT: An information-theoretic toolkit for studying the dynamics of complex systems. *Frontiers in Robotics and AI*, 1, 11. <https://doi.org/10.3389/frobt.2014.00011>
- Lynn, C. W., Cornblath, E. J., Papadopoulos, L., Bertolero, M. A., & Bassett, D. S. (2021). Broken detailed balance and entropy production in the human brain. *Proceedings of the National Academy of Sciences*, 118(47), e2109889118. <https://doi.org/10.1073/pnas.2109889118>
- Michel, C. M., & Koenig, T. (2018). EEG microstates as a tool for studying the temporal dynamics of whole-brain neuronal networks: A review. *NeuroImage*, 180, 577–593. <https://doi.org/10.1016/j.neuroimage.2017.11.062>
- Nagabhushan Kalburgi, S., Kleinert, T., Aryan, D., Nash, K., Schiller, B., & Koenig, T. (2023). MICROSTATELAB: The EEGLAB toolbox for resting-state microstate analysis. *Brain Topography*, 37(4), 621–645. <https://doi.org/10.1007/s10548-023-01003-5>
- Nielsen, A., & Weber, M. (2015). Computing the nearest reversible Markov chain. *Numerical Linear Algebra with Applications*, 22(3), 483–499. <https://doi.org/10.1002/nla.1967>
- Paluš, M., Dvořák, I., & Dvořák, I. (1992). Spatio-temporal dynamics of human EEG. *Physica A: Statistical Mechanics and Its Applications*, 185(1–4), 433–438. [https://doi.org/10.1016/0378-4371\(92\)90479-T](https://doi.org/10.1016/0378-4371(92)90479-T)
- Pascual-Marqui, R. D., Michel, C. M., & Lehmann, D. (1995). Segmentation of brain electrical activity into microstates: Model estimation and validation. *IEEE Transactions on Biomedical Engineering*, 42(7), 658–665. <https://doi.org/10.1109/10.391164>
- Peng, C.-K., Buldyrev, S. V., Havlin, S., Simons, M., Stanley, H. E., & Goldberger, A. L. (1994). Mosaic organization of DNA nucleotides. *Physical Review E*, 49(2), 1685–1689. <https://doi.org/10.1103/PhysRevE.49.1685>
- Poulsen, A. T., Pedroni, A., Langer, N., & Hansen, L. K. (2018). Microstate EEGLab toolbox: An introductory guide. *bioRxiv*, 289850. <https://doi.org/10.1101/289850>
- Richman, J. S., & Moorman, J. R. (2000). Physiological time-series analysis using approximate entropy and sample entropy. *American Journal of Physiology — Heart and Circulatory Physiology*, 278(6), H2039–H2049. <https://doi.org/10.1152/ajpheart.2000.278.6.H2039>

- Roldán, É., & Parrondo, J. M. R. (2010). Estimating dissipation from single stationary trajectories. *Physical Review Letters*, 105(15), 150607. <https://doi.org/10.1103/PhysRevLett.105.150607>
- Rostaghi, M., & Azami, H. (2016). Dispersion entropy: A measure for time-series analysis. *IEEE Signal Processing Letters*, 23(5), 610–614. <https://doi.org/10.1109/LSP.2016.2542881>
- Scafetta, N., & Grigolini, P. (2002). Scaling detection in time series: Diffusion entropy analysis. *Physical Review E*, 66(3), 036130. <https://doi.org/10.1103/PhysRevE.66.036130>
- Van De Ville, D., Britz, J., & Michel, C. M. (2010). EEG microstate sequences in healthy humans at rest reveal scale-free dynamics. *Proceedings of the National Academy of Sciences*, 107(42), 18179–18184. <https://doi.org/10.1073/pnas.1007841107>
- von Wegner, F. (2018). Partial autoinformation to characterize symbolic sequences. *Frontiers in Physiology*, 9, 1382. <https://doi.org/10.3389/fphys.2018.01382>
- von Wegner, F. (2026). A quantitative comparison of two methods for higher-order EEG microstate syntax analysis. *Brain Topography*, 39, 45. <https://doi.org/10.1007/s10548-026-01196-5>
- von Wegner, F., Hermann, G., Tödt, I., Todtenhaupt, I. K., & Laufs, H. (2025). Higher-order EEG microstate syntax and surrogate testing. *Computers in Biology and Medicine*, 193, 110367. <https://doi.org/10.1016/j.compbiomed.2025.110367>
- von Wegner, F., & Laufs, H. (2018a). EEG microstate sequences from different clustering algorithms are information-theoretically invariant. *Frontiers in Computational Neuroscience*, 12, 70. <https://doi.org/10.3389/fncom.2018.00070>
- von Wegner, F., & Laufs, H. (2018b). Information-theoretical analysis of EEG microstate sequences in Python. *Frontiers in Neuroinformatics*, 12, 30. <https://doi.org/10.3389/fninf.2018.00030>
- von Wegner, F., & Laufs, H. (2024). Complexity measures for EEG microstate sequences: Concepts and algorithms. *Brain Topography*, 37(2), 296–311. <https://doi.org/10.1007/s10548-023-00996-3>
- von Wegner, F., Tagliazucchi, E., Brodbeck, V., & Laufs, H. (2016). Analytical and empirical fluctuation functions of the EEG microstate random walk — short-range vs. Long-range correlations. *NeuroImage*, 141, 442–451. <https://doi.org/10.1016/j.neuroimage.2016.07.050>
- von Wegner, F., Tagliazucchi, E., & Laufs, H. (2017). Information-theoretical analysis of resting state EEG microstate sequences — non-Markovianity, non-stationarity and periodicities. *NeuroImage*, 158, 99–111. <https://doi.org/10.1016/j.neuroimage.2017.06.063>
- Wackermann, J. (1996). Beyond mapping: Estimating complexity of multichannel EEG recordings. *Acta Neurobiologiae Experimentalis*, 56(1), 197–208.