

Secure Airport Tower

First Development Journal

frederic.jacobs@epfl.ch
hantao.zhao@epfl.ch

24 mai 2012

1 Setting up our project

The first thing to point out is the fact that we used the JRE 1.7 because we use switches on Strings and other features of the JRE 1.7. It runs smoothly on Windows, Mac and Linux (the OpenJDK is advised to avoid compilation issues). Once you created the project in Eclipse, don't forget to add the libraries that are in `/src/libs` to the build path. Once that's done, you're ready to go.

Java 1.7 SDK has some flaws on Unix-Platforms though. Written once, runs everywhere might not be true depending on the runtime. It turned out that JRE 1.7 was the most stable on Windows.

2 Project's Architecture

Our program is structured into different packages. There are two classes that are executable. `AirportGUI.java` launches everything needed to run the tower while `TestPlane.java` launches everything required for the plane to run. We are in this section going to give a quick overview of what each class does. For further information please check out our JavaDoc. We have some encapsulation flaws that are linked with late minute refactoring.

ADD ARCHITECTURE DIAGRAM

2.1 Database

This is a separate package that is specific to our innovation. We designed a REST-API that allows to fetch the logs and the position of planes. To do that, we had to have a specific syncing thread. Updating the position each time a plane sends a keep-alive wasn't sustainable so we chose to update the database every second with the latest positions. That is `DBSync.java`'s job. It fetches the positions from the journal and updates them automatically in the Tower only if they changed. We are using a JSON format that is very friendly in JavaScript for future applications such as web apps.

2.2 DataFile

`DataFile.java` is responsible for creating `DataMessages` objects from a `File`. It can also write a `File` from a bunch of `DataMessages`. The `DataMessages` should be routed to this `DataFile`. After some refactoring we didn't stick to the original description of the `DataFile` because we believed it

didn't make much sense to have this bunch of superficial variable (or we may not have understood what they were doing). We managed to get this class working with a slightly modified version of the original test.

2.3 Encryption

The `encryption` package provide all the tools required in this project related to encryption.

1. `KeyGenerator.java` - It is responsible for generating new RSA keys, both public and private. It simply requires a given size and it will generate the keys for you.
2. `KeyPair.java` - Nothing more than a simple wrapper object to store RSA Keys.
3. `RsaInputStream.java` - This is a tool for reading encrypted blocks of data coming from the network. It requires a `KeyPair` with a private key to decrypt the blocks coming from the network.
4. `RsaOutputStream.java` - Exactly the opposite of the preceding class. It is designed to encrypt blocks of data and splitting them to be RSA-safe depending on the size of the size of the key.

2.4 generals

In this package we have only one but very precious tool. It's a class called `XYPosition` it is used all over the project and defines what coordinates are. It is a timesaver and makes the code often more readable.

2.5 GUI

The `GUI` package is the main package of our application. It is the main thread of our application that will launch and dispatch all the rest of the tasks. We stucked to `AWT/SWING` for the design. Although it is not perfect, we believe it completes it's task. We also launch a bunch of other panels. Let's quickly discover all the essential classes in the `GUI`.

1. `AirportGUI.java` is our main class. It remains very simple but launches the Tower Singleton instance that will handle all the communication with the planes. It also handles all the different panels that are launched.
2. `AirportPanel.java` is the radar screen. We only made very little changes to it to allow it to work with our classes. We also improved it for having custom red airplanes in case of MayDays.
3. `Choker.java` is the our custom button to simply toggle the Choke mode. It is simple and work as expected. It's a simple button that changed from red to green depending on the choke status.
4. `CircularBuffer.java` is a buffer used in the `AirportPanel` to draw the points. It was provided. No changes.
5. `DownloadGUI.java` is a little box that displays the downloaded files from the plane. Nothing special here.
6. `JournalGUI.java` is the observer of any changes in the Journal and then automatically updates the GUI version of the journal.
7. `ModesGUI` - This class is the GUI of the optimization modes. It uses a `ButtonGroup` to let the client choose from 3 types of the modes, and it can print out the total number of

passages, the total number of fuel consumption and the waiting time of per passages. It also implements the observer so that each time we receive a bye message, the corresponded information will be updated automatically.

2.6 Messaging

Messaging is the biggest part of this project. Let's have an overview of all the classes in this package.

1. **Circle.java** - This class is the main part to arrange the landing request of the planes and also send the routing messages to different planes. It has also a method to respond the Mayday message, called the landingUrgent. The general idea of designing the routing respond is that we judge which is the closed valid route, and add the current plane to the **ArrayList** of the route. For example if the landing route is valid right now we will send a landing routing message directly. In this way all the planes will be well arranged.
2. **Event.java** - This class is a part of the journal. Each time a message is created or send out, it will be saved as an Event. It contain the information such as message, source, destination and the time at which it is created.
3. **Journal.java** - This class is a journal which will record all the event happened during the communication. It will also run the planeHasCrashed or planeDidLand method to help the GUI to print out the needed information. As it is a part of the observer mode, it extends the Observable to remind the **JournalGUI** when a new event is saved in.
4. **Modes.java** - This class is the main part of the ModesGUI, it contains three kinds of Comparator to rank the ArrayList of the tower. The comparatorChronos is based on the time order of the plane so we judge it by comparing the initial time of the planes. The comparatorFuel is based on the consummation of the plane so we judge it by comparing the consummation of the planes. The comparatorTime is based on the waiting time of the plane so we judge it by comparing the passage number of the planes.
5. **Plane.java** - This is the class of Plane. It is responsible for create a array of the planes in the Tour to save all the information of the planes which have communicated with the Tour. It has several parameters.
6. **PlanePosition.java** - This class allows to have a wrapper object for an array of Planes with an associated position, crash status and landing status.
7. **ReadMessages.java** - This class aims at converting the DataInputStream into a new created message, by using the method read (for byte[]) and readInt.
8. **Tower.java** represents the tour of airport, which have the function of receiving and sending Message with the planes.
9. **TowerMessageHandler.java** is the class file that handles received messages. This class help the Tower to handle communications with several planes, that is to say that each thread handles the connection with one plane.
10. **TowerThead.java** - This class help the Tower to handle communications with several planes, that is to say that each thread handles the connection with one plane.
11. **Visitor.java** - This class is the main part of the visitor pattern. It aims at handling different kinds of messages, such as Hello , KeepAlive and so on. Each time there is a message which needs to be handled in the tower-message handle it will call the visit() method so that the Visitor class will judge the type of different message and do different move to respond.

Please note that we have a sub-package in which we define each different type of message. Since these are only wrappers, please refer to the JavaDoc to know more about them.

2.7 Plane

3 Q&A

In ITP-02, we were asked two questions.

1. Is it a good idea to use a superclass to define Messages?
2. Why is it an abstract class?

In a object-oriented universe like Java, we like to model things hierarchically. We want all possible types of messages to have a behavior or to have some instance variables therefore defining a super-class Messages makes a lot of sense. We were asked to have these instance variables in each Message Type so we implemented these in our super-class.

```
byte[] planeID; //The unique identifier of the plane
int length; //Length of the message
int priority; //Priority in PriorityQueue
int posx; //Positioning data
int posy;
MessageType type; //Type of Message
```

The reason why we want this to be an abstract class is really straightforward. We defined a Message super-class because we expect messages to behave a given way but we also want these messages to have a type. All messages will inherit these attributes from the super-class but the super-class won't be instantiable to assure we call the right constructor when creating a message with a certain type. The keyword *abstract* does exactly this.