

# Topology optimization of a thermo-fluid system and an eigenfrequency problem

HAO LI<sup>1\*</sup>, NARI NAKAYAMA<sup>1\*</sup>, PIERRE JOLIVET<sup>2\*</sup>, NAOYUKI ISHIDA<sup>1</sup>, KOUSEI WANO<sup>1</sup>, TSUGUO KONDOH<sup>1</sup>, TAKAYUKI YAMADA<sup>3</sup>, AND SHINJI NISHIWAKI<sup>1\*</sup>

<sup>1</sup>*Department of Mechanical Engineering and Science, Kyoto University, Japan*

*li.hao.48z@st.kyoto-u.ac.jp, nakayama.nari.42z@st.kyoto-u.ac.jp, shinji@prec.kyoto-u.ac.jp*

<sup>2</sup>*Institut de Recherche en Informatique de Toulouse, France*

*pierre.jolivet@enseeiht.fr*

<sup>3</sup>*Department of Strategic Studies, Institute of Engineering Innovation, The University of Tokyo, Japan*

## Abstract

We propose a novel framework for the two- and three-dimensional topology optimization (TO) of multiphysics system. The proposed design methodology uses a reaction-diffusion equation (RDE) for updating the level-set function based on the topological sensitivity. From the numerical point of view, two key ingredients are highlighted: (i) two different types of dynamic sparse grids (adaptive mesh) are used. More accurately speaking, body-fitted mesh allows the disjoint-reunion of a global mesh whose interfaces can be described by the zero-level-set isosurface. Anisotropic mesh adaptation is highly scalable with respect to the problem size, therefore can accelerate the overall computation; (ii) our framework uses FreeFEM for finite element analysis (FEA) and PETSc for distributed linear algebra. Efficient preconditioner techniques are utilized to solve the large-scale finite element systems. From an engineering standpoint, we construct a complete product development workflow including the pre-processing, TO, B-Rep conversion, and the numerical experiment. The performance of our methodology is demonstrated by showcasing four different optimization problems: natural convection, lift-drag, multi-material design of mean compliance problem and eigenfrequency problem. For comparison and for assessing our various techniques, we benchmark our designs against state-of-the-art works.

## References

- [1] Li, H., Kondoh, T., Jolivet, P., Furuta, K., Yamada, T., Zhu, B., Zhang, H., Izui, K., and Nishiwaki, S. Optimum design and thermal modeling of 2D and 3D natural convection problems based on body-fitted topology optimization. *Preprint submitted to International Journal for Numerical Methods in Engineering*.
- [2] Li, H., Kondoh, T., Jolivet, P., Furuta, K., Yamada, T., Zhu, B., Izui, K., and Nishiwaki, S. Three-dimensional topology optimization of a fluid-structure system using body-fitted mesh adaption based on the level-set method. *Applied Mathematical Modelling*. (2022) **101**: 276-308.
- [3] Li, H., Yamada, T., Jolivet, P., Furuta, K., Kondoh, T., Izui, K., and Nishiwaki, S. Full-scale 3D structural topology optimization using adaptive mesh refinement based on the level-set method. *Finite Elements in Analysis and Design*. (2021) **194**: 103561.




Figure 1: Optimal solutions. (a)–b): natural convection; (c)–d): lift–drag; multi-material design of: (e) mean compliance and (f) eigenfrequency problem.