

# RECENT ADVANCES WITH PARALLEL FREEFEM

---

Pierre Jolivet — CNRS

December 9, 2021

FreeFEM days, 13th edition

# INTRODUCTION

1. Introduction
2. New functionalities
3. Applications
4. DD preconditioning
5. Conclusion

# INTRODUCTION



# BASIC SEQUENTIAL FUNCTIONALITIES

## Domain specific language for FE

- mesh structure
- associated finite element spaces
- vector and matrix assemblies
- algebraic operations

# INTERFACE TO OTHER LIBRARIES

- installed by PETSc (make `petsc-slepc`)
  - MPICH
  - CMake
  - BLAS
  - MUMPS or  
SuperLU\_DIST
  - SuperLU
  - SuiteSparse
  - *hypre*
  - METIS
  - ParMETIS
  - SCOTCH
  - TetGen
  - SLEPc
  - HPDDM
  - ARPACK
  - Mmg
  - ParMmg
  - Htool

# INTERFACE TO OTHER LIBRARIES

- installed by PETSc (make `petsc-slepc`)
  - MPICH
  - CMake
  - BLAS
  - MUMPS or SuperLU\_DIST
  - SuperLU
  - SuiteSparse
  - *hypre*
  - METIS
  - ParMETIS
  - SCOTCH
  - TetGen
  - SLEPc
  - HPDDM
  - ARPACK
  - Mmg
  - ParMmg
  - Htool
- tested on Windows, Linux, Apple Intel/ARM, A64FX...

# INTERFACE TO OTHER LIBRARIES

- installed by PETSc (make `petsc-slepc`)

- |   |                                   |
|---|-----------------------------------|
| <input type="checkbox"/> MPICH                    | <input type="checkbox"/> ParMETIS |
| <input type="checkbox"/> CMake                    | <input type="checkbox"/> SCOTCH   |
| <input type="checkbox"/> BLAS                     | <input type="checkbox"/> TetGen   |
| <input type="checkbox"/> MUMPS or<br>SuperLU_DIST | <input type="checkbox"/> SLEPc    |
| <input type="checkbox"/> SuperLU                  | <input type="checkbox"/> HPDDM    |
| <input type="checkbox"/> SuiteSparse              | <input type="checkbox"/> ARPACK   |
| <input type="checkbox"/> <i>hypr</i>              | <input type="checkbox"/> Mmg      |
| <input type="checkbox"/> METIS                    | <input type="checkbox"/> ParMmg   |
|   | <input type="checkbox"/> Htool    |

- tested on Windows, Linux, Apple Intel/ARM, A64FX...


⇒ sequential or parallel (with FreeFem++-mpi)

# GOING PARALLEL

- distributed-memory paradigm (MPI)
- not transparent to users
- additional lightweight macros



# NEW FUNCTIONALITIES





# IMPORTANT REMINDER

- examples, see `examples/hpddm/README.md`
- functionalities, see `CHANGELOG.md`
- developments are user-driven: ask what you need



# INTERPOLATION

- FreeFEM kernels are sequential
- interpolation between different fespaces





# INTERPOLATION

- FreeFEM kernels are sequential
- interpolation between different fespaces





# INTERPOLATION

- FreeFEM kernels are sequential
- interpolation between different fespaces




# PARALLEL INTERPOLATION

- detect intersecting subdomains





# PARALLEL INTERPOLATION

- detect intersecting subdomains



# PARALLEL INTERPOLATION



- detect intersecting subdomains
- neighborwise reduction







# PARALLEL INTERPOLATION

- detect intersecting subdomains
- neighborwise reduction





# PARALLEL INTERPOLATION

- detect intersecting subdomains
- neighborwise reduction





# PARALLEL INTERPOLATION

- detect intersecting subdomains
- neighborwise reduction





# PARALLEL INTERPOLATION

- detect intersecting subdomains
- neighborwise reduction
- interpolation into the output fespace



# PARALLEL INTERPOLATION

- detect intersecting subdomains
- neighborwise reduction
- interpolation into the output fespace





# API FOR PARALLEL INTERPOLATION

- transfer a single finite element function
- assemble a parallel **Mat**, like `interpolate`
- use with PETSc **PCMG** (GMG machinery)

# API FOR PARALLEL INTERPOLATION


- transfer a single finite element function
- assemble a parallel **Mat**, like `interpolate`
- use with PETSc **PCMG** (GMG machinery)



- 0.3M vs. 5M elements
- 61 **PCMG** iterations on 1,024 processes for Poisson
- 0.9 (nested) vs. 36 sec (non-nested) for building  $P$

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC





# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypr*
- 78 MPI processes of Irène@TGCC

---

Iteration	#1
<hr/>	
# of tetrahedra	45k
ParMmg (sec)	6.5
<i>hypr</i> (sec)	0.2

---

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2
# of tetrahedra	45k	47k
ParMmg (sec)	6.5	8.4
<i>hypre</i> (sec)	0.2	0.4

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3
# of tetrahedra	45k	47k	93k
ParMmg (sec)	6.5	8.4	13.4
<i>hypre</i> (sec)	0.2	0.4	1.1

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3	#4
# of tetrahedra	45k	47k	93k	249k
ParMmg (sec)	6.5	8.4	13.4	24.2
<i>hypre</i> (sec)	0.2	0.4	1.1	2.7

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3	#4	#5
# of tetrahedra	45k	47k	93k	249k	715k
ParMmg (sec)	6.5	8.4	13.4	24.2	43.7
<i>hypre</i> (sec)	0.2	0.4	1.1	2.7	7.2

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3	#4	#5	#6
# of tetrahedra	45k	47k	93k	249k	715k	2M
ParMmg (sec)	6.5	8.4	13.4	24.2	43.7	106
<i>hypre</i> (sec)	0.2	0.4	1.1	2.7	7.2	18

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3	#4	#5	#6	#7
# of tetrahedra	45k	47k	93k	249k	715k	2M	5.5M
ParMmg (sec)	6.5	8.4	13.4	24.2	43.7	106	78.7
<i>hypre</i> (sec)	0.2	0.4	1.1	2.7	7.2	18	30

# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3	#4	#5	#6	#7	#8
# of tetrahedra	45k	47k	93k	249k	715k	2M	5.5M	12M
ParMmg (sec)	6.5	8.4	13.4	24.2	43.7	106	78.7	231
<i>hypre</i> (sec)	0.2	0.4	1.1	2.7	7.2	18	30	58



# PARALLEL MESH ADAPTATION

- Poisson equation on the Fischera corner
- algebraic system solved with *hypre*
- 78 MPI processes of Irène@TGCC

Iteration	#1	#2	#3	#4	#5	#6	#7	#8	#9
# of tetrahedra	45k	47k	93k	249k	715k	2M	5.5M	12M	26M
ParMmg (sec)	6.5	8.4	13.4	24.2	43.7	106	78.7	231	838
<i>hypre</i> (sec)	0.2	0.4	1.1	2.7	7.2	18	30	58	—

# NONSTANDARD EIGENSOLVERS

- Nonlinear  $T(\lambda)x = 0 \implies \text{NEPSolve}$
- Polynomial  $(\sum_{i=0}^N \lambda^i A_i)x = 0, N \geq 2 \implies \text{PEPSolve}$
- SVD  $Av = \sigma u \implies \text{SVDSolve}$

## Array of PETSc matrices

As easy as FreeFEM matrices, e.g., `Mat[int] A(N+1)`

# NONSTANDARD EIGENSOLVERS

- Nonlinear  $T(\lambda)x = 0 \implies \text{NEPSolve}$
- Polynomial  $(\sum_{i=0}^N \lambda^i A_i)x = 0, N \geq 2 \implies \text{PEPSolve}$
- SVD  $Av = \sigma u \implies \text{SVDSolve}$

## Array of PETSc matrices

As easy as FreeFEM matrices, e.g., `Mat[int] A(N+1)`

$\implies$  blasius-stability-1d-SLEPc-complex.edp

## EASIER USE OF SHELLS FOR PRECONDITIONERS

Oseen equations:  $A = \begin{bmatrix} F & B \\ B^T & C \end{bmatrix} \Rightarrow \text{Mat } A = \begin{bmatrix} [F, B], \\ [B', C] \end{bmatrix}$

## EASIER USE OF SHELLS FOR PRECONDITIONERS

Oseen equations:  $A = \begin{bmatrix} F & B \\ B^T & C \end{bmatrix} \Rightarrow \text{Mat } A = \begin{bmatrix} [F, B], \\ [B', C] \end{bmatrix}$

Mat Object: 4 MPI processes

type: nest

rows=37507, cols=37507

Matrix object:

type=nest, rows=2, cols=2

MatNest structure:

(0,0) : prefix="fieldsplit\_0\_", type=mpiaij...

(0,1) : type=mpiaij, rows=33282, cols=4225

(1,0) : type=transpose, rows=4225, cols=33282

(1,1) : prefix="fieldsplit\_1\_", type=mpiaij...

## EASIER USE OF SHELLS FOR PRECONDITIONERS

Oseen equations:  $A = \begin{bmatrix} F & B \\ B^T & C \end{bmatrix} \Rightarrow \text{Mat } A = \begin{bmatrix} [F, B], \\ [B', C] \end{bmatrix}$

Triangular preconditioner:  $\tilde{A} = \begin{bmatrix} \tilde{F} & B \\ 0 & \tilde{S} \end{bmatrix}$  with  $\tilde{S}^{-1} \approx -M_p^{-1} F_p L_p^{-1}$

## EASIER USE OF SHELLS FOR PRECONDITIONERS

Oseen equations:  $A = \begin{bmatrix} F & B \\ B^T & C \end{bmatrix} \Rightarrow \text{Mat } A = \begin{bmatrix} [F, B], \\ [B', C] \end{bmatrix}$

Triangular preconditioner:  $\tilde{A} = \begin{bmatrix} \tilde{F} & B \\ 0 & \tilde{S} \end{bmatrix}$  with  $\tilde{S}^{-1} \approx -M_p^{-1}F_pL_p^{-1}$

```
func real[int] PCD(real[int]& in) {  
    real[int] out(in.n);  
    KSPSolve(Lp,in,out); MatMult(Fp,out,in);  
    KSPSolve(Mp,in,out); out *= -1.0;  
    return out; // = -Mp \ Fp * Lp \ in  
}  
set(C, parent = A, precon = PCD,  
    sparams = "-fieldsplit_1_pc_type shell");
```

# FEM-BEM INTEROPERABILITY

- distributed FE space associated to a global numbering
- renumber the global mesh accordingly



# FEM-BEM INTEROPERABILITY

- distributed FE space associated to a global numbering
- renumber the global mesh accordingly

```
Mat E,V;  
ThLocal = ThGlobal;  
createMat(ThLocal,E,P0); // elements  
createMat(ThLocal,V,P1); // vertices  
CoherentGlobalMesh(E,V,ThLocal,ThGlobal);
```

# FEM-BEM INTEROPERABILITY


- distributed FE space associated to a global numbering
- renumber the global mesh accordingly

```
Mat E,V;  
ThLocal = ThGlobal;  
createMat(ThLocal,E,P0); // elements  
createMat(ThLocal,V,P1); // vertices  
CoherentGlobalMesh(E,V,ThLocal,ThGlobal);
```

FEM and/or BEM assemblies in a Mat


- `A = varfFEM(), int2d(ThLocal)`
- `A = varfBEM(), int2dx2d(ThGlobal)(ThGlobal)`

## EXAMPLE ON A 2D GEOMETRY



Unstructured circle with inclusion

## EXAMPLE ON A 2D GEOMETRY




Canonical FreeFEM vertex numbering

## EXAMPLE ON A 2D GEOMETRY



Domain decomposed mesh

## EXAMPLE ON A 2D GEOMETRY



Coherent global FEM-BEM vertex numbering

## UPCOMING FEATURES/FIXES

- `https://github.com/FreeFem/FreeFem-sources/pull/210`
- `https://community.freefem.org/t/dmplex-can-not-read-region-number/1368`
- ask and you shall receive

# APPLICATIONS

---



# FEM-BEM COUPLING I

Solve the generalized eigenvalue problem for  $(u, \lambda)$ :

$$\begin{bmatrix} A_k & D'_k - \frac{1}{2}M^{\text{tr}} \\ M^{\text{tr}} & -S_k \end{bmatrix} u = \lambda \begin{bmatrix} M & 0 \\ 0 & 0 \end{bmatrix} u$$

```
Mat<complex> C;
```

```
Sk *= -1.0;
```

```
C = [[Ak , R*TDkM]  
     [F2B, Sk    ]];
```

# FEM-BEM COUPLING I

Solve the generalized eigenvalue problem for  $(u, \lambda)$ :

$$\begin{bmatrix} A_k & D'_k - \frac{1}{2}M^{\text{tr}} \\ M^{\text{tr}} & -S_k \end{bmatrix} u = \lambda \begin{bmatrix} M & 0 \\ 0 & 0 \end{bmatrix} u$$

```
Mat<complex> C;
```

```
Sk *= -1.0;
```

```
C = [[Ak , R*TDkM]  
      [F2B, Sk  ]];
```

```
ObjectView(C);
```

Mat Object: 4 MPI processes

type=nest, rows=2, cols=2

MatNest structure:

(0,0) : type=mpiaij, rows=10410, cols=10410

(0,1) : type=composite, rows=10410, cols=...

(1,0) : type=mpiaij, rows=1156, cols=10410

(1,1) : type=htool, rows=1156, cols=1156

# FEM-BEM COUPLING I

Solve the generalized eigenvalue problem for  $(u, \lambda)$ :

$$\begin{bmatrix} A_k & D'_k - \frac{1}{2}M^{\text{tr}} \\ M^{\text{tr}} & -S_k \end{bmatrix} u = \lambda \begin{bmatrix} M & 0 \\ 0 & 0 \end{bmatrix} u$$

```
Mat<complex> C;
```

```
Sk *= -1.0;
```

```
C = [[Ak , R*TDkM]  
      [F2B, Sk  ]];
```

```
ObjectView(C);
```

Mat Object: 4 MPI processes

type=nest, rows=2, cols=2

MatNest structure:

(0,0) : type=mpiaij, rows=10410, cols=10410

(0,1) : type=composite, rows=10410, cols=...

(1,0) : type=mpiaij, rows=1156, cols=10410

(1,1) : type=htool, rows=1156, cols=1156

⇒ no need for shell to define block PC, use field-splitting

# FEM-BEM COUPLING II





Figure 1.6: Absolute value of the eigenfunction of the truncated exterior Dirichlet problem associated with the smallest eigenvalue for the large cavity.

[Galkowski et al., 2021]

# MIXED-PRECISION FOR GEOPHYSICS



[Tournier et al., 2021]

# RADIATIVE TRANSFER I

## Semi-discretized RTE

$$\forall m \in \llbracket 1; N_d \rrbracket, (\vec{S}_m \cdot \nabla + (\kappa + \sigma)) I_m = \sigma \sum_{n=1}^{N_d} \omega_n \varphi_{m,n} \cdot I_n + \kappa B$$


# RADIATIVE TRANSFER I

## Semi-discretized RTE

$$\forall m \in \llbracket 1; N_d \rrbracket, (\vec{s}_m \cdot \nabla + (\kappa + \sigma)) I_m = \sigma \sum_{n=1}^{N_d} \omega_n \varphi_{m,n} \cdot I_n + \kappa B$$



$N_d = 80$




$N_d = 320$

$$\vec{s}_m = \begin{bmatrix} \sin \theta_m \cos \psi_m \\ \sin \theta_m \sin \psi_m \\ \cos \theta_m \end{bmatrix}$$


- $\kappa$  (resp.  $\sigma$ ) absorption (resp. scattering) coefficient
- $\varphi$  phase scattering function
- $B$  black body emissivity function

# RADIATIVE TRANSFER II

[Kobayashi et al., 2001] benchmark



(a) Problem 3i



(b) Problem 3ii



# RADIATIVE TRANSFER II

- GMVP [Nagaya et al., 2005]
- Ardra [Brown et al., 1999]


y	Problem 3i			
	Reference	MC	$P_{21}$	DOM
5	$5.96 \cdot 10^0$	$5.94 \cdot 10^0$	$5.96 \cdot 10^0$	$5.96 \cdot 10^0$
15	$1.37 \cdot 10^0$	$1.37 \cdot 10^0$	$1.34 \cdot 10^0$	$1.37 \cdot 10^0$
25	$5.01 \cdot 10^{-1}$	$5.01 \cdot 10^{-1}$	$4.95 \cdot 10^{-1}$	$5.00 \cdot 10^{-1}$
35	$2.52 \cdot 10^{-1}$	$2.53 \cdot 10^{-1}$	$2.49 \cdot 10^{-1}$	$2.50 \cdot 10^{-1}$
45	$1.50 \cdot 10^{-1}$	$1.50 \cdot 10^{-1}$	$1.56 \cdot 10^{-1}$	$1.48 \cdot 10^{-1}$
55	$9.92 \cdot 10^{-2}$	$9.92 \cdot 10^{-2}$	$1.20 \cdot 10^{-1}$	$9.84 \cdot 10^{-2}$
65	$4.23 \cdot 10^{-2}$	$4.23 \cdot 10^{-2}$	$5.10 \cdot 10^{-2}$	$4.20 \cdot 10^{-2}$
75	$1.15 \cdot 10^{-2}$	$1.15 \cdot 10^{-2}$	$8.91 \cdot 10^{-3}$	$1.14 \cdot 10^{-2}$
85	$3.25 \cdot 10^{-3}$	$3.25 \cdot 10^{-3}$	$1.95 \cdot 10^{-3}$	$3.33 \cdot 10^{-3}$
95	$9.48 \cdot 10^{-4}$	$9.49 \cdot 10^{-4}$	$6.82 \cdot 10^{-4}$	$9.69 \cdot 10^{-4}$

# RADIATIVE TRANSFER II

- GMVP [Nagaya et al., 2005]
- Ardra [Brown et al., 1999]


y	Problem 3ii		
	MC	$P_{21}$	DOM
5	$8.62 \cdot 10^0$	$8.61 \cdot 10^0$	$8.63 \cdot 10^0$
15	$2.16 \cdot 10^0$	$2.13 \cdot 10^0$	$2.16 \cdot 10^0$
25	$8.94 \cdot 10^{-1}$	$8.84 \cdot 10^{-1}$	$8.93 \cdot 10^{-1}$
35	$4.78 \cdot 10^{-1}$	$4.72 \cdot 10^{-1}$	$4.74 \cdot 10^{-1}$
45	$2.89 \cdot 10^{-1}$	$2.99 \cdot 10^{-1}$	$2.87 \cdot 10^{-1}$
55	$1.93 \cdot 10^{-1}$	$2.24 \cdot 10^{-1}$	$1.91 \cdot 10^{-1}$
65	$1.05 \cdot 10^{-1}$	$1.19 \cdot 10^{-1}$	$1.04 \cdot 10^{-1}$
75	$3.38 \cdot 10^{-2}$	$3.02 \cdot 10^{-2}$	$3.35 \cdot 10^{-2}$
85	$1.08 \cdot 10^{-2}$	$8.54 \cdot 10^{-3}$	$1.08 \cdot 10^{-2}$
95	$3.40 \cdot 10^{-3}$	$2.83 \cdot 10^{-3}$	$3.40 \cdot 10^{-3}$

# RADIATIVE TRANSFER — STRONG SCALING



Nearly transparent medium, spherical inclusions, 13B unknowns (15M tets and  $N_d = 5,120$ ), tolerance of  $10^{-6}$

# RADIATIVE TRANSFER — WEAK SCALING



1.7M unknowns/processes ( $N_d = 1,280$ ), 6 reflective surfaces, uniform spatial mesh refinement

## SOME MORE (TOMORROW)

- A. Suzuki: “Shape optimization for a heat exchanger in Navier–Stokes flow [...]”
- M. Barzegari: “BioDeg: corrosion/biodegradation simulation software [...]”
- H. Li: “Topology optimization of a thermo-fluid system and an eigenfrequency problem [...]”


# DD PRECONDITIONING

---


# ROBUST DOMAIN DECOMPOSITION METHOD

- based on GenEO [Spillane et al., 2013]
- assembly of Neumann problems [Jolivet et al., 2021]
- nonlinear solve using SNES [Brune et al., 2015]

$$-\nabla \cdot (\kappa \nabla u) - 6.2e^u = 0$$



(a) Coefficient distribution




(b) Isosurfaces of the solution

# ROBUST DOMAIN DECOMPOSITION METHOD

- based on GenEO [Spillane et al., 2013]
- assembly of Neumann problems [Jolivet et al., 2021]
- nonlinear solve using SNES [Brune et al., 2015]

$$-\nabla \cdot (\kappa \nabla u) - 6.2e^u = 0$$





# ALGEBRAIC PRECONDITIONING FOR LEAST SQUARES


Identifier	$M_{\text{balanced}}^{-1}$	$M_{\text{ASM}}^{-1}$	BoomerAMG	GAMG	HSL_MI35
mesh_deform	13	27	‡	35	<b>5</b>
EternityII_E	<b>43</b>	91	‡	63	199
lp_stocfor3	<b>34</b>	136	‡	513	211
deltaX	<b>23</b>	98	‡	784	640
sc205-2r	<b>54</b>	61	‡	195	97
stormg2-125	<b>42</b>	174	‡	†	†
Rucci1	<b>21</b>	484	118	364	†
image_interp	<b>11</b>	409	40	203	†
mk13-b5	19	21	<b>11</b>	‡	<b>11</b>
pds-100	18	202	<b>16</b>	35	110
fome21	20	104	<b>16</b>	20	41
sgpf5y6	224	264	‡	163	<b>110</b>
Hardesty2	<b>30</b>	913	88	404	†
Delor338K	<b>10</b>	11	‡	†	829
watson_2	<b>15</b>	109	‡	64	73
LargeRegFile	41	109	19	‡	<b>12</b>
cont11_l	<b>30</b>	490	53	723	‡

# FOR NONSYMMETRIC SYSTEMS



$$\nabla \cdot (Vu) - \nu \nabla \cdot (\kappa \nabla u) = 0 \text{ in } \Omega$$

$$u = 0 \text{ in } \Gamma_0$$

$$u = 1 \text{ in } \Gamma_1$$



(a) Semi-structured mesh





(b) Diffusivity coefficient  $\kappa$

# FOR NONSYMMETRIC SYSTEMS


$$\nabla \cdot (Vu) - \nu \nabla \cdot (\kappa \nabla u) = 0 \text{ in } \Omega$$

$$u = 0 \text{ in } \Gamma_0$$


$$u = 1 \text{ in } \Gamma_1$$



(a)  $\nu = 1$



(b)  $\nu = 10^{-2}$



(c)  $\nu = 10^{-4}$

# FOR NONSYMMETRIC SYSTEMS

$$\nabla \cdot (Vu) - \nu \nabla \cdot (\kappa \nabla u) = 0 \text{ in } \Omega$$

$$u = 0 \text{ in } \Gamma_0$$

$$u = 1 \text{ in } \Gamma_1$$

Dimension	$k$	$N$	$n$	$\nu$				
				1	$10^{-1}$	$10^{-2}$	$10^{-3}$	$10^{-4}$
2	1	1,024	$6.3 \cdot 10^6$	23 <small>(52,875)</small>	20 <small>(52,872)</small>	19 <small>(52,759)</small>	20 <small>(47,497)</small>	21 <small>(28,235)</small>
3	2	4,096	$8.1 \cdot 10^6$	18 <small>(1.8 · 10<sup>5</sup>)</small>	14 <small>(1.8 · 10<sup>5</sup>)</small>	11 <small>(1.6 · 10<sup>5</sup>)</small>	16 <small>(97,657)</small>	29 <small>(76,853)</small>

# FOR NONSYMMETRIC SYSTEMS

$$\nabla \cdot (Vu) - \nu \nabla \cdot (\kappa \nabla u) = 0 \text{ in } \Omega$$

$$u = 0 \text{ in } \Gamma_0$$

$$u = 1 \text{ in } \Gamma_1$$

Dimension	$k$	$N$	$n$	$\nu$				
				1	$10^{-1}$	$10^{-2}$	$10^{-3}$	$10^{-4}$
2	1	1,024	$6.3 \cdot 10^6$	23 <small>(52,875)</small>	20 <small>(52,872)</small>	19 <small>(52,759)</small>	20 <small>(47,497)</small>	21 <small>(28,235)</small>
3	2	4,096	$8.1 \cdot 10^6$	18 <small>(1.8 · 10<sup>5</sup>)</small>	14 <small>(1.8 · 10<sup>5</sup>)</small>	11 <small>(1.6 · 10<sup>5</sup>)</small>	16 <small>(97,657)</small>	29 <small>(76,853)</small>

New algebraic preconditioning

- LS: [Al Daas, Jolivet, and Scott, 2021]
- SPD: [Al Daas and Jolivet, 2021]
- $M$ -matrices: [Al Daas, Jolivet, and Rees, 2022]

# CONCLUSION

---

# FINAL WORDS

- multiphysics solvers
  - high level of abstraction of FreeFEM
  - versatility of PETSc
- composability of solvers
- `http://joliv.et/FreeFem-tutorial`

# FINAL WORDS

- multiphysics solvers
  - high level of abstraction of FreeFEM
  - versatility of PETSc
- composability of solvers
- <http://joliv.et/FreeFem-tutorial>

Thank you!



# REFERENCES I



Al Daas, Hussam and Pierre Jolivet (2021). “A robust algebraic multilevel domain decomposition preconditioner for general sparse symmetric positive definite matrices”. In: *SIAM Journal on Scientific Computing*, submitted for publication. URL: <https://arxiv.org/pdf/2109.05908.pdf>.



Al Daas, Hussam, Pierre Jolivet, and Jennifer A. Scott (2021). “A robust algebraic domain decomposition preconditioner for sparse normal equations”. In: *SIAM Journal on Scientific Computing*, submitted for publication. URL: <https://github.com/prj-/aldaas2021robust>.



Brown, Peter N., Britton Chang, and Ulf R. Hanebutte (1999). *Spherical harmonic solutions to the 3D Kobayashi benchmark suite*. Tech. rep. Lawrence Livermore National Laboratory.



Brune, Peter R., Matthew G. Knepley, Barry F. Smith, and Xuemin Tu (2015). “Composing scalable nonlinear algebraic solvers”. In: *SIAM Review* 57.4, pp. 535–565.

# REFERENCES II



Galkowski, Jeffrey, Pierre Marchand, and Euan A. Spence (2021). “Eigenvalues of the truncated Helmholtz solution operator under strong trapping”. In: arXiv: 2101.02116 [math.AP].



Jolivet, Pierre, Jose E. Roman, and Stefano Zampini (2021). “KSPHPDDM and PCHPDDM: extending PETSc with robust overlapping Schwarz preconditioners and advanced Krylov methods”. In: *Computers & Mathematics with Applications* 84, pp. 277–295. URL: <https://github.com/prj-/jolivet2020petsc>.



Kobayashi, Keisuke, Naoki Sugimura, and Yasunobu Nagaya (2001). “3D radiation transport benchmark problems and results for simple geometries with void region”. In: *Progress in Nuclear Energy* 39.2, pp. 119–144.



Nagaya, Yasunobu, Keisuke Okumura, Takamasa Mori, and Masayuki Nakagawa (2005). *MVP/GMVP 2: general purpose Monte Carlo codes for neutron and photon transport calculations based on continuous energy and multigroup methods*. Tech. rep. Japan Atomic Energy Research Institute.

# REFERENCES III



Spillane, Nicole, Victorita Dolean, Patrice Hauret, Frédéric Nataf, Clemens Pechstein, and Robert Scheichl (2013). “Abstract robust coarse spaces for systems of PDEs via generalized eigenproblems in the overlaps”. In: *Numerische Mathematik* 126.4, pp. 741–770.



Tournier, Pierre-Henri, Pierre Jolivet, Victorita Dolean, Hossein Aghamiry, Stéphane Operto, and Sebastián Rizzo (2021). “Large-scale 3D frequency-domain wave simulation with finite-element and finite-difference methods and an optimized additive Schwarz domain-decomposition preconditioner: a tool for FWI of sparse node datasets”. In: *Geophysics*, submitted for publication. URL: <https://arxiv.org/pdf/2110.15113.pdf>.