

## Table of Contents

|   |          |
|---|----------|
| <b>Change LOG .....</b>   | <b>4</b> |
| version 1811201459.....   | 4        |
| version 1812051456.....   | 4        |
| version 1812171521.....   | 4        |
| version 1812201208.....   | 4        |
| version 1901101636.....   | 4        |
| version 1901311135.....   | 4        |
| version 1902191535.....   | 4        |
| version 1903211145.....   | 5        |
| version 1904091202.....   | 5        |
| version 1905071026.....   | 5        |
| version 1906120933.....   | 5        |
| version 1907251601.....   | 5        |
| version 1908131009.....   | 5        |
| version 1910211454.....   | 5        |
| <b>1. COMMUNICATION PROTOCOL.....</b>   | <b>6</b> |
| 1.1. MESSAGE FORMAT FROM THE SOFTWARE APPLICATION TO THE FD .....                         | 6        |
| 1.2. MESSAGE FORMAT FROM THE FD TO THE SOFTWARE APPLICATION .....                         | 7        |
| 1.2.1. Acknowledgement response.....  | 7        |
| 1.2.2. Message response .....   | 8        |
| 1.3. SHORT MESSAGES FOR TESTING THE STATUS OF THE FD.....                                 | 8        |
| <b>2. DESCRIPTION OF THE COMMANDS .....</b>   | <b>9</b> |
| 2.1. FORMAT AND PRESENTATION OF COMMANDS.....   | 9        |
| 2.2. GENERAL COMMANDS.....  | 10       |
| 2.2.1. Command: 20h / SP - Status .....   | 10       |
| 2.2.2. Command: 21h / ! - Version .....   | 12       |
| 2.2.3. Command: 22h / " - Diagnostics.....  | 12       |
| 2.2.4. Command: 24h / \$ - Clear display.....   | 12       |
| 2.2.5. Command: 25h / % - Display text line 1 .....                                       | 12       |
| 2.2.6. Command: 26h / & - Display text line 2.....  | 13       |
| 2.2.7. Command: 27h / - Display text lines 1 and 2.....                                   | 13       |
| 2.2.8. Command: 28h / ( - Display date and time.....                                      | 13       |
| 2.2.9. Command: 29h / ) - Cut paper, FP only .....  | 13       |
| 2.2.10. Command: 2Ah / * - Cash drawer opening .....                                      | 13       |
| 2.2.11. Command: 2Bh / + - Paper feeding .....  | 13       |
| 2.3. FISCAL COMMANDS.....   | 14       |
| 2.3.1.1. Command: 56h / V - Set type of fiscal device, Option T.....                      | 14       |
| 2.3.1.2. Command: 41h / A - Set customer UIC information, Option 1 .....                  | 14       |
| 2.3.1.3. Command: 41h / A - Confirm fiscalization, Option 2 .....                         | 14       |
| 2.3.2. Command: 42h / B - Change VAT rates .....  | 15       |
| 2.3.3. Command: 43h / C - Change decimal point position.....                              | 15       |
| 2.4. PROGRAMMING COMMANDS .....   | 16       |
| 2.4.1. Command: 44h / D - Program payment types.....                                      | 16       |
| 2.4.2. Command: 44h / D - Program payment types, KL .....                                 | 16       |
| 2.4.3. Command: 45h / E - Program parameters .....  | 17       |
| 2.4.4. Command: 47h / G - Program department.....   | 18       |
| 2.4.5. Command: 48h / H - Program date and time .....                                     | 18       |
| 2.4.6. Command: 49h / I - Program display greeting message.....                           | 19       |
| 2.4.7. Command: 49h / I - Program header lines .....                                      | 19       |
| 2.4.8. Command: 49h / I - Program footer line.....  | 19       |
| 2.4.9. Command: 49h / I - Program header UIC prefix .....                                 | 19       |
| 2.4.10. Command: 4Ah / J - Program operator's name and password .....                     | 20       |
| 2.4.11. Command: 4Bh / K - Program article .....  | 20       |
| 2.4.12. Command: 4Bh / K - Program article general registers, Option 1 .....              | 21       |
| 2.4.13. Command: 4Bh / K - Program article quantity in stock, Option 2 .....              | 21       |
| 2.4.14. Command: 4Bh / K - Program article barcode, Option 3.....                         | 22       |
| 2.4.15. Command: 4Bh / K - Program article price, Option 4 .....                          | 22       |
| 2.4.16. Command: 4Bh / K - Erase all PLU database.....                                    | 22       |
| 2.4.17. Command: 4Ch / L - Program logo without setting a number (default number 0) ..... | 22       |
| 2.4.18. Command: 4Dh / M - Program logo with setting a number .....                       | 23       |
| 2.4.19. Command: 23h / # - Program active logo number .....                               | 23       |
| 2.4.20. Command: 51h / Q - Print barcode 'QP' (FP only) .....                             | 23       |
| 2.4.21. Command: 50h / P - Program invoice number range.....                              | 24       |
| 2.4.22. Command: 52h / R - Program customer database.....                                 | 24       |
| 2.5. DATA READING COMMANDS .....  | 25       |
| 2.5.1. Command: 60h / ' - Read FD numbers .....   | 25       |
| 2.5.2. Command: 61h / a - Read registration information .....                             | 25       |
| 2.5.3. Command: 62h / b - Read VAT rates.....   | 25       |
| 2.5.4. Command: 63h / c - Read decimal point position .....                               | 26       |

|   |    |
|---|----|
| 2.5.5. Command: 64h / d – Read payment types .....  | 26 |
| 2.5.6. Command: 64h / d – Read payment types, KL .....  | 27 |
| 2.5.7. Command: 65h / e – Read parameters.....  | 27 |
| 2.5.8. Command: 66h / f – Read detailed printer status.....   | 28 |
| 2.5.9. Command: 67h / g – Read department registers.....  | 29 |
| 2.5.10. Command: 67h / g – Read department registers, Option “(All)”.....   | 30 |
| 2.5.11. Command: 68h / h – Read date and time .....   | 30 |
| 2.5.12. Command: 69h / i – Read display greeting message .....  | 31 |
| 2.5.13. Command: 69h / i – Read header lines .....  | 31 |
| 2.5.14. Command: 69h / i – Read footer line.....  | 32 |
| 2.5.15. Command: 69h / i – Read Header UIC prefix .....   | 32 |
| 2.5.16. Command: 6Ah / j – Read operator's name and password.....   | 32 |
| 2.5.17. Command: 6Bh / k – Read article.....  | 33 |
| 2.5.18. Command: 6Bh / k – Read article registers, Option “ (All)” .....  | 34 |
| 2.5.19. Command: 6Bh / k – Read article registers, Option 1 (General).....  | 35 |
| 2.5.20. Command: 6Bh / k – Read article registers, Option 2 (Quantity) .....  | 36 |
| 2.5.21. Command: 6Bh / k – Read article registers, Option 3 (Barcode) .....   | 36 |
| 2.5.22. Command: 6Bh / k – Read article registers, Option 4 (Price) .....   | 36 |
| 2.5.23. Command: 6Ch / l – Print Logo.....  | 37 |
| 2.5.24. Command: 52h / R – Read customer database.....  | 37 |
| 2.5.25. Command: 4Fh / O – Read automatic daily report parameter .....  | 37 |
| 2.6. RECEIPT OPERATIONS COMMANDS .....  | 38 |
| 2.6.1. Command: 2Eh / . – Open Non-fiscal receipt .....   | 38 |
| 2.6.2. Command: 2Fh / / – Close Non-fiscal receipt .....  | 38 |
| 2.6.3. Command: 30h / 0 –Open Fiscal sales receipt .....  | 39 |
| 2.6.4. Command: 30h / 0 –Open ELECTRONIC Fiscal sales receipt .....   | 39 |
| 2.6.5. Command: 30h / 0 –Open Fiscal storno receipt.....  | 40 |
| 2.6.6. Command: 30h / 0 – Open Fiscal Invoice receipt with free customer data .....   | 41 |
| 2.6.7. Command: 30h / 0 – Open ELECTRONIC Fiscal Invoice receipt with free customer data .....                                  | 42 |
| 2.6.8. Command: 30h / 0 – Open Fiscal Invoice Credit Note receipt with free customer data .....                                 | 43 |
| 2.6.9. Command: 30h / 0 – Open Fiscal Invoice receipt with customer data from FD database.....                                  | 44 |
| 2.6.10. Command: 30h / 0 – Open ELECTRONIC Fiscal Invoice receipt with customer data from FD database.....                      | 45 |
| 2.6.11. Command: 30h / 0 – Open Fiscal Invoice Credit Note receipt with customer data from FD database.....                     | 46 |
| 2.6.12. Command: 31h / 1 – Sell/Correction of article belonging to VAT class definition .....                                   | 47 |
| 2.6.13. Command: 31h / 1 – Sell/Correction of article belonging to department.....  | 48 |
| 2.6.14. Command: 31h / 1 – Sell/Correction of article with specified VAT belonging to department .....                          | 49 |
| 2.6.15. Command: 32h / 2 – Sell/Correction of article from FD database.....   | 50 |
| 2.6.16. Command: 33h / 3 – Subtotal .....   | 50 |
| 2.6.17. Command: 34h / 4 – Sell/Correction of article with department definition belonging to VAT class .....                   | 51 |
| 2.6.18. Command: 34h / 4 – Sell/Correction of article with specified department .....   | 52 |
| 2.6.19. Command: 35h / 5 – Payment .....  | 53 |
| 2.6.20. Command: 35h / 5 – Pay exact sum.....   | 54 |
| 2.6.21. Command: 36h / 6 – Automatic receipt closure .....  | 54 |
| 2.6.22. Command: 37h / 7 – Free text printing .....   | 54 |
| 2.6.23. Command: 38h / 8 – Close Fiscal receipt.....  | 54 |
| 2.6.24. Command: 39h / 9 – Cancel fiscal receipt .....  | 55 |
| 2.6.25. Command: 3Ah / : – Print a copy of the last document.....   | 55 |
| 2.6.26. Command: 3Bh / ; – Non-fiscal RA and PO amounts .....   | 55 |
| 2.6.27. Command: 3Eh / > – Discount/ Addition.....  | 56 |
| 2.6.28. Command: 3Dh / = – Sell/Correction of article with fractional quantity belonging to VAT class definition .....          | 56 |
| 2.6.29. Command: 3Dh / = – Sell/Correction of article with fractional quantity belonging to department.....                     | 57 |
| 2.6.30. Command: 3Dh / = – Sell/Correction of article with fractional quantity with specified VAT belonging to department ..... | 58 |
| 2.7. COMMANDS FOR READING THE DATA IN FD'S REGISTERS.....   | 59 |
| 2.7.1. Command: 6Dh / m – Read daily sale and storno amounts by VAT groups .....  | 59 |
| 2.7.2. Command: 6Eh / n – Read registers, Option ‘0’ (on hand) .....  | 60 |
| 2.7.3. Command: 6Eh / n – Read registers, Option ‘0’, KL (on hand).....   | 60 |
| 2.7.4. Command: 6Eh / n – Read registers, Option ‘1’ (general) .....  | 61 |
| 2.7.5. Command: 6Eh / n – Read registers, Option ‘2’ (RA) .....   | 61 |
| 2.7.6. Command: 6Eh / n – Read registers, Option ‘2’, KL (RA).....  | 62 |
| 2.7.7. Command: 6Eh / n – Read registers, Option ‘3’ (PO).....  | 62 |
| 2.7.8. Command: 6Eh / n – Read registers, Option ‘3’, KL (PO).....  | 63 |
| 2.7.9. Command: 6Eh / n – Read registers, Option ‘4’ (received).....  | 63 |
| 2.7.10. Command: 6Eh / n – Read registers, Option ‘4’, KL (received) .....  | 64 |
| 2.7.11. Command: 6Eh / n – Read registers, Option ‘5’ (counters) .....  | 64 |
| 2.7.12. Command: 6Eh / n – Read registers, Option ‘6’ (change) .....  | 65 |
| 2.7.13. Command: 6Eh / n – Read registers, Option ‘6’, KL (change).....   | 65 |
| 2.7.14. Command: 6Eh / n – Read registers, Option ‘7’ (Sums in FD) .....  | 66 |
| 2.7.15. Command: 6Eh / n – Read registers, Option ‘9’, electronic signature of last daily report .....                          | 66 |
| 2.7.16. Command: 6Eh / n – Display daily turnover registers, Option ‘:’ .....   | 66 |
| 2.7.17. Command: 6Fh / o – Read operator's report, Option ‘1’ (general) .....   | 66 |
| 2.7.18. Command: 6Fh / o – Read operator's report, Option ‘2’ (RA) .....  | 67 |

|   |           |
|---|-----------|
| 2.7.19. Command: 6Fh / o – Read operator's report, Option '2', KL (RA) .....  | 68        |
| 2.7.20. Command: 6Fh / o – Read operator's report, Option '3' (PO) .....  | 68        |
| 2.7.21. Command: 6Fh / o – Read operator's report, Option '3', KL (PO) .....  | 69        |
| 2.7.22. Command: 6Fh / o – Read operator's report, Option '4' (received) .....  | 69        |
| 2.7.23. Command: 6Fh / o – Read operator's report, Option '4', KL (received) .....  | 70        |
| 2.7.24. Command: 6Fh / o – Read operator's report, Option '5' (counters) .....  | 70        |
| 2.7.25. Command: 6Fh / o – Read operator's report, Option '6' (change) .....  | 71        |
| 2.7.26. Command: 6Fh / o – Read operator's report, Option '6', KL (change) .....  | 71        |
| 2.7.27. Command: 70h / p – Read invoice number range .....  | 72        |
| 2.7.28. Command: 71h / q – Read total receipt number .....  | 72        |
| 2.7.29. Command: 72h / r – Read information about current opened receipt .....  | 72        |
| 2.7.30. Command: 72h / r – Read information about current/last receipt payments amounts, Option P .....   | 73        |
| 2.7.31. Command: 72h / r – Read information about last receipt QR barcode data, Option B .....  | 74        |
| 2.7.32. Command: 72h / r – Read information about specified number receipt QR barcode data, Option b .....  | 74        |
| 2.7.33. Command: 72h / r – Read electronic receipt by number with QR code data, Option e .....  | 74        |
| 2.7.34. Command: 72h / r – Read electronic receipt by number with ASCII specified QR symbol, Option E .....   | 75        |
| 2.7.35. Command: 72h / r – Read electronic receipt by number with Base64 encoded QR, Option E .....   | 75        |
| 2.7.36. Command: 73h / s – Read last daily report info .....  | 76        |
| 2.7.37. Command: 74h / t – Read free FM reporting records .....   | 76        |
| <b>2.7.38. Command: 75h / u – Read FM contents .....</b>  | <b>77</b> |
| <b>2.8. REPORTS PRINTING COMMANDS .....</b>   | <b>78</b> |
| 2.8.1. Command: 76h / v – Print department report .....   | 78        |
| 2.8.2. Command: 77h / w – Print special events FM report .....  | 78        |
| 2.8.3. Command: 77h / w – Print brief FM payments report .....  | 78        |
| 2.8.4. Command: 78h / x – Print detailed FM report by number of Z report blocks .....   | 78        |
| 2.8.5. Command: 78h / x – Print detailed FM payments report by number of Z report blocks .....  | 79        |
| 2.8.6. Command: 79h / y – Print brief FM report by number of Z report blocks .....  | 79        |
| 2.8.7. Command: 79h / y – Print brief FM payments report by number of Z report blocks .....   | 79        |
| 2.8.8. Command: 7Ah / z – Print detailed FM report by date .....  | 79        |
| 2.8.9. Command: 7Ah / z – Print detailed FM payments report by date .....   | 80        |
| 2.8.10. Command: 7Bh / { – Print brief FM report by date .....  | 80        |
| 2.8.11. Command: 7Bh / { – Print brief FM payments report by date .....   | 80        |
| 2.8.12. Command: 7Ch /   – Print daily fiscal report X or Z .....   | 80        |
| 2.8.13. Command: 7Ch /   – Print/Store Electronic Journal report from date do date .....  | 81        |
| 2.8.14. Command: 7Ch /   – Print Electronic Journal report from date do date with selected documents content .....                                    | 81        |
| 2.8.15. Command: 7Ch /   – Print/Store Electronic Journal report from receipt number to receipt number .....  | 82        |
| 2.8.16. Command: 7Ch /   – Print Electronic Journal report from receipt number to receipt number with selected documents content .....                | 82        |
| 2.8.17. Command: 7Ch /   – Print/Store Electronic Journal report by number of Z report blocks .....   | 83        |
| 2.8.18. Command: 7Ch /   – Print Electronic Journal report by number of Z report blocks with selected documents content .....                         | 83        |
| 2.8.19. Command: 7Ch /   – Print/Store Electronic Journal report from beginning to end .....  | 84        |
| 2.8.20. Command: 7Ch /   – Print Electronic Journal report from beginning to end with selected documents content ..                                   | 84        |
| 2.8.21. Command: 7Dh / } – Print operator's report .....  | 85        |
| 2.8.22. Command: 7Eh / ~ – Print article report .....   | 85        |
| 2.8.23. Command: 7Fh / █ – Print detailed daily report .....  | 85        |
| 2.8.24. Command: 52h / R – option X, Print Customer X or Z report .....   | 85        |
| <b>2.9. REPORTS READING COMMANDS .....</b>  | <b>86</b> |
| 2.9.1. Command: 7Ch /   – Read Electronic Journal report from date do date .....  | 86        |
| 2.9.2. Command: 7Ch /   – Read/Store Electronic Journal report from date do date with selected documents content and format .....                     | 86        |
| 2.9.3. Command: 7Ch /   – Read Electronic Journal report from receipt number to receipt number .....  | 87        |
| 2.9.4. Command: 7Ch /   – Read/Store Electronic Journal report from receipt number to receipt number with selected documents content and format ..... | 87        |
| 2.9.5. Command: 7Ch /   – Reading Electronic Journal report from number Z report to number Z report .....   | 88        |
| 2.9.6. Command: 7Ch /   – Read/Store Electronic Journal report by number of Z report blocks with selected documents content and format .....          | 88        |
| 2.9.7. Command: 7Ch /   – Read Electronic Journal report from beginning to end .....  | 89        |
| 2.9.8. Command: 7Ch /   – Read/Store Electronic Journal report from beginning to end with selected documents content and format .....                 | 90        |
| <b>2.10. NETWORK SETTINGS COMMANDS .....</b>  | <b>91</b> |
| 2.10.1. Command: 4Eh / N – Read last sent and first unsent receipts info .....  | 91        |
| <b>3. SOFTWARE APPLICATION REQUIREMENTS .....</b>   | <b>92</b> |
| 3.1. RULES FOR USING THE COMMANDS .....   | 92        |
| 3.2. SAMPLE SALE TRANSACTION OF FD .....  | 92        |
| <b>4. AUXILIARY GS PROTOCOL (COMMANDS 1Dh) .....</b>  | <b>93</b> |

## Change LOG

### version 1811201459

Changed zfpdef name from [OpenCreditNoteFromFDCustomerDB\(\)](#) to [OpenCreditNoteWithFreeCustomerData\(\)](#)

Changed zfpdef name from [OpenInvoiceFromFDCustomerDB\(\)](#) to [OpenInvoiceWithFDCustomerDB\(\)](#)

### version 1812051456

Parameter *OptionVATClass*: added new option **\*\* – Forbidden**

Command with [zfpdef ReadCurrentReceiptInfo](#): change parameter *VATinReceipt* values from – 0 – Yes, 1 – No to – 1 – Yes, 0 – No

Command with [zfpdef Payment](#): change delimiter before parameter *OptionChangeType* from **\*\*** to **;**

### version 1812171521

No protocol changes

### version 1812201208

Add command with zfpdef: [ReadSentRcpInfoStatus](#) for read last sent and first unsent receipts numbers and date time.

### version 1901101636

Remove *URN* input field from commands with zfpdefs: [OpenStornoReceipt](#), [OpenCreditNoteWithFreeCustomerData](#), [OpenCreditNoteWithFDCustomerDB](#)

Adding a command for reading QR code data in the last issued receipt with zfpdef: [ReadLastReceiptQRcodeData](#)

### version 1901311135

Adding commands for KL devices V2 with zfpdefs:

[ProgPayment\\_Old](#), [ReadPayments\\_Old](#), [ReadDailyAvailableAmounts\\_Old](#), [ReadDailyRA\\_Old](#), [ReadDailyPO\\_Old](#), [ReadDailyReceivedSalesAmounts\\_Old](#), [ReadDailyReturnedChangeAmounts\\_Old](#), [ReadDailyRabyOperator\\_Old](#), [ReadDailyPObyOperator\\_Old](#), [ReadDailyReceivedSalesAmountsByOperator\\_Old](#), [ReadDailyReturnedChangeAmountsByOperator\\_Old](#)

Command with zfpdef: [OpenStornoReceipt](#) from parameter *StornoReason* is removed option 2 – *Tax relief*

Commands with zfpdefs: [OpenCreditNoteWithFreeCustomerData](#) and [OpenCreditNoteWithFDCustomerDB](#), parameter *StornoReason* is hardcoded with value **'2'** – *tax relief*

Command with zfpdef: [ReceivedOnAccount\\_PaidOut](#) Parameter length *OperPass* is changed from 4 symbols to 6 symbols.

Command with zfpdef: [ReadCurrentReceiptInfo\(\)](#) changes positions of parameters *SubtotalAmountVAT4*, *SubtotalAmountVAT5*, *SubtotalAmountVAT6*, *SubtotalAmountVAT7*.

### version 1902191535

Adding additional message response format in point 1.3

Adding parameter for printing RA/PO availability in command [ReceivedOnAccount](#), parameter name *PrintAvailability*.

### **version 1903211145**

Commands with **zfpdefs:** *SetDateTime(DateTime)*, *OpenStornoReceipt()*, *OpenCreditNoteWithFreeCustomerData()*, *OpenCreditNoteWithFDCustomerDB()* are with added seconds in the related parameters. This will not confuse the workflow with V2 devices!

Command with **zfpdef:** *OpenStornoReceipt* from parameter *StornoReason* is added option 2 – *Tax relief*

Commands with **zfpdefs:** *OpenCreditNoteWithFreeCustomerData* and *OpenCreditNoteWithFDCustomerDB*, parameter *StornoReason* is with added options values - '0' – *Operator error*, - '1' – *Goods Claim or Goods return*

### **version 1904091202**

Adding new commands with **zfpdefs:** *OpenElectronicReceipt()*, *OpenElectronicStornoReceipt()*, *OpenElectronicInvoiceWithFreeCustomerData()*, *OpenElectronicCreditNoteWithFreeCustomerData()*, *OpenElectronicInvoiceWithFDCustomerDB()*, *OpenElectronicCreditNoteWithFDCustomerDB()* for opening of all types receipts in electronic formats

Adding new command with **zfpdef:** *ReadReceiptNumQRcodeData()* for reading QR code data of specified receipt number

### **version 1905071026**

Commands with **zfpdefs:** *ProgPayment()*, *ProgPayment\_Old()*, *ReadPayments()*, *ReadPayments\_Old()*, parameters *ExchangeRate* and *Rate* are with changed length from 10 to 1..10.

Adding new command with **zfpdef:** *ReadElectronicReceiptNumDataFromEJ*

### **version 1906120933**

Command with **zfpdef:** *ReadElectronicReceiptNumDataFromEJ()* is renamed to *ReadElectronicReceiptDataFromEJ()*

### **version 1907251601**

Add new commands with **zfpdef:** *ReadElectronicReceipt\_QR\_Data()*, *ReadElectronicReceipt\_QR\_ASCII()* and *ReadElectronicReceipt\_QR\_BMP()* for reading electronic receipts with their QR code in different formats

### **version 1908131009**

Edit command *ReadLastDailyReportInfo()* parameter *LastReceiptType* parameter  
Remove commands for open electronic storno and credit note receipts.

### **version 1910211454**

No protocol changes.

## 1. COMMUNICATION PROTOCOL

The type of the protocol is Master / Slave. The communication session is always initiated by the Application Software. FD carries out the commands send by the software application and provides a feedback depending on the result. FD sends back an „Acknowledgement response” or „message response”. All messages of the protocol are either packed or single-byte. FD supports communication standard RS232, USB, BT, TCP (WiFi, LAN).

Serial port adjustment parameters:

Speed: 115200 bit/s (or 19200, 38400, 57600 and 9600 if such is set for the FD)  
8 bits word  
No parity  
1 stop bit

TCP adjustment parameters:

Port: Always 8000

Password: Send directly to opened socket with **0Ah**(LF) for end.

In example if password is 1234 when open TCP socket sends

0x31 0x32 0x33 0x34 0x0A

### 1.1. MESSAGE FORMAT FROM THE SOFTWARE APPLICATION TO THE FD

All messages except those described in section 4., sent to the FD by the PC have the following structure:

**<STX><LEN><NBL><CMD><DATA...DATA><CS><CS><ETX>**

The table below contains description of the field enclosed between the symbols < and >:

| Field          | No. of bytes | Value   |
|----------------|--------------|---|
| STX            | 1            | <b>Message start</b> – always <b>02h</b>  |
| LEN            | 1            | <b>Message length</b> (number of bytes including LEN, NBL, CMD, DATA) increased by <b>20h</b> i.e. a number in the 20h - 9Fh range  |
| NBL            | 1            | <b>Message number</b> increased by <b>20h</b> i.e. a number in the 20h - 9Fh range  |
| CMD            | 1            | <b>Command</b> - a number in the 20h - 7Fh range(see the description of commands)   |
| DATA..<br>DATA | 0 -<br>3902  | <b>Additional data</b> – a group of data fields separated with the symbols ';', giving additional information needed for execution of the command (see the description of commands)     |
| CS CS          | 2            | <b>Checksum</b> , compiled as follows:<br>1) Operation XOR of all bytes from LEN to DATA inclusive = 0 .. FFh<br>2) Conversion of 2 bytes by adding 30h, for example:<br>B5h -> 3Bh 35h |
| ETX            | 1            | <b>End of message</b> – always <b>0Ah</b> (LF)  |

The texts data of the message is sent as ASCII text with code table cp1251 (Windows 1251).

## 1.2. MESSAGE FORMAT FROM THE FD TO THE SOFTWARE APPLICATION

There are several types of response depending on the message received.

### 1.2.1. Acknowledgement response

**Positive acknowledgement** – when package format is correct. It is sent when the command is acknowledged as well as when it is rejected (errors in the data sent (field <DATA...DATA>) or the command cannot be executed or the command is illegal depending on the current status of the FD indicated by the two status bytes). It is a package message with the following format:

**<ACK><NBL><STE><STE><CS><CS><ETX>**

Fields description:

| Field      | No bytes | Value   |
|------------|----------|---|
| ACK        | 1        | 06h   |
| NBL        | 1        | <b>No. of message</b> = NBL of message related to receipt   |
| STE<br>STE | 2        | <b>2 error status-bytes</b> . A two-digit ASCII number. (see Table Errors)  |
| CS CS      | 2        | <b>Checksum</b> , compiled as follows:<br>1) Operation XOR on NBL STE и STE = 00h .. FFh<br>2) Conversion of 2 bytes by adding 30h, for example: B5h -> 3Bh 35h |
| ETX        | 1        | 0Ah (LF)  |

The two status-bytes are a two-digit ASCII number, in which the first digit provides information about the error in the FD, and the second one – about a command error.

**Table Errors:**

| Byte value | FD errors  | Byte value | Command errors                         |
|------------|--|------------|--|
| 30         | OK   | 30         | OK                                     |
| 31         | Out of paper, printer failure  | 31         | Invalid command                        |
| 32         | Registers overflow   | 32         | Illegal command                        |
| 33         | Clock failure or incorrect date&time                                     | 33         | Z daily report is not zero             |
| 34         | Opened fiscal receipt  | 34         | Syntax error                           |
| 35         | Payment residue account  | 35         | Input registers overflow               |
| 36         | Opened non-fiscal receipt  | 36         | Zero input registers                   |
| 37         | Registered payment but receipt is not closed                             | 37         | Unavailable transaction for correction |
| 38         | Fiscal memory failure  | 38         | Insufficient amount on hand            |
| 39         | Incorrect password   |            |  |
| 3a         | Missing external display   |            |  |
| 3b         | 24hours block – missing Z report   |            |  |
| 3c         | Overheated printer thermal head.   |            |  |
| 3d         | Interrupt power supply in fiscal receipt (one time until status is read) |            |  |
| 3e         | Overflow EJ  |            |  |
| 3f         | Insufficient conditions  |            |  |

A two-digit number is compiled depending on the type of error.  
Example: Error 32 – Illegal command due to clock failure

**Negative acknowledgement** – It is sent when the package format is incorrect. It is 1-byte **NACK = 15h** without checksum.

**Repetition request** – It is sent when the FD is busy executing the preceding command. It is 1 byte **RETRY = 0Eh** without checksum.

### 1.2.2. Message response

It has the format of the packed message sent by the SA to the FD (see 3.1.) but is returned by the FD to the SA and contains information – response to the query (see description of commands).

### 1.3. SHORT MESSAGES FOR TESTING THE STATUS OF THE FD

The exchange protocol includes two unpacked single-byte codes for testing the status of the FD, which can quickly determine the status of the device. The two codes and their meaning are shown in the table below:

| Query SA | Response FD |  | Meaning                              |
|----------|-------------|--|--------------------------------------|
| 04       | 04          |  | FD is on                             |
| 09       | 40          | Bit.0  | FD is READY                          |
|          | 41          |  | FD is busy                           |
|          | 42          | Bit.1  | FD out of paper                      |
|          | 43          |  | FD out of paper and busy             |
|          | 44          | Bit.2  | FD printer is overheated             |
|          | 45          |  | FD printer is overheated and busy    |
|          | 48          | Bit.3  | FD missing external display          |
|          | 49          |  | FD missing external display and busy |
|          | 50          | FD is waiting for password (LAN or WiFi connection only)                 |                                      |
|          | 60          | FD is already busy with another connection (LAN or WiFi connection only) |                                      |
|          | 70          | Wrong password (LAN or WiFi connection only)                             |                                      |

The format of the commands is described in art. 2. **DESCRIPTION OF THE COMMANDS OF FISCAL DEVICE**



## 2. DESCRIPTION OF THE COMMANDS

### 2.1. FORMAT AND PRESENTATION OF COMMANDS

All commands are described and presented using the following terms and symbols:

#### Key terms:

**Command** – the value of the CMD field of the message sent by the software application and in the message response of the the FD.

**input** – structure of the fields included in the DATA field of the message sent by the software application.

**output** – for each command it may be one of the following:

- Acknowledgement response.
- Structure of the fields included in the DATA field of the message response sent by the FD.

**Input data** – description of the contents of the “input” fields.

**Output data** – description of the contents of the “output” fields.

#### Key symbols:

' ' – compulsory symbol

“ ” – compulsory DateTime format

< > – compulsory data field

<;> – field separator

[ ] – field length

{ } – non-compulsory data field

**zfpdef:** - function name in the generated source code and file server file name

#### General rules:

Format of the price/value field – from 1 to 10 symbols, a floating decimal point number, preceded by +, - or SPACE.

Examples: -12.34 +56.7 8

Format of the quantity field – from 1 to 10 symbols, a floating decimal point number, up to three digits after the decimal point.

Examples: 1.234 56.78 9

Format of the rate (percentage) field – from 2 to 7 symbols, a floating decimal point number, up to two digits after the decimal point, preceded by the percent symbol - %.

Examples: -12.34% +5.67% 8.9% 10%

Payment Number 0 corresponds to the main payment – IN CASH, payment Number 11 corresponds to the special currency payment - VAT account.

## 2.2. GENERAL COMMANDS

These are commands for the general functions of the FD, related to obtaining diagnostic information and to direct access to some of the functions of the device (paper feeding, paper cutting, and display visualization).

### 2.2.1. Command: 20h / SP - Status

**input:** n. a.

**output:** <StatusBytes[7]>

**FPR operation:** Provides detailed 7-byte information about the current status of the fiscal printer.

**Input data :** n. a.

**Output data :**

| <i>N<br/>byte</i> | <i>N bit</i> | <i>status flag</i>                  |
|-------------------|--------------|-------------------------------------|
| ST0               | 0            | FM Read only                        |
|                   | 1            | Power down in opened fiscal receipt |
|                   | 2            | Printer not ready - overheat        |
|                   | 3            | DateTime not set                    |
|                   | 4            | DateTime wrong                      |
|                   | 5            | RAM reset                           |
|                   | 6            | Hardware clock error                |
|                   | 7            | 1                                   |

|     |   |                               |
|-----|---|-------------------------------|
| ST1 | 0 | Printer not ready - no paper  |
|     | 1 | Reports registers Overflow    |
|     | 2 | Customer report is not zeroed |
|     | 3 | Daily report is not zeroed    |
|     | 4 | Article report is not zeroed  |
|     | 5 | Operator report is not zeroed |
|     | 6 | Duplicate printed             |
|     | 7 | 1                             |

|     |   |                                |
|-----|---|--------------------------------|
| ST2 | 0 | Opened Non-fiscal Receipt      |
|     | 1 | Opened Fiscal Receipt          |
|     | 2 | Opened Fiscal Detailed Receipt |
|     | 3 | Opened Fiscal Receipt with VAT |
|     | 4 | Opened Invoice Fiscal Receipt  |
|     | 5 | SD card near full              |
|     | 6 | SD card full                   |
|     | 7 | 1                              |

|     |   |                                  |
|-----|---|----------------------------------|
| ST3 | 0 | No FM module                     |
|     | 1 | FM error                         |
|     | 2 | FM full                          |
|     | 3 | FM near full                     |
|     | 4 | Decimal point (1=fract, 0=whole) |
|     | 5 | FM fiscalized                    |
|     | 6 | FM produced                      |
|     | 7 | 1                                |

|     |   |                                       |
|-----|---|---------------------------------------|
| ST4 | 0 | Printer: automatic cutting            |
|     | 1 | External display: transparent display |
|     | 2 | Speed is 9600                         |
|     | 3 | reserve                               |
|     | 4 | Drawer: automatic opening             |
|     | 5 | Customer logo included in the receipt |
|     | 6 | reserve                               |
|     | 7 | 1                                     |

|     |   |   |
|-----|---|---|
| ST5 | 0 | Wrong SIM card                          |
|     | 1 | Blocking 3 days without mobile operator |
|     | 2 | No task from NRA                        |
|     | 3 | reserved                                |
|     | 4 | reserved                                |
|     | 5 | Wrong SD card                           |
|     | 6 | Deregistered                            |
|     | 7 | 1                                       |

|     |   |                          |
|-----|---|--------------------------|
| ST6 | 0 | No SIM card              |
|     | 1 | No GPRS Modem            |
|     | 2 | No mobile operator       |
|     | 3 | No GPRS service          |
|     | 4 | Near end of paper        |
|     | 5 | Unsent data for 24 hours |
|     | 6 | reserved                 |
|     | 7 | 1                        |

[zfpdef:ReadStatus\(\)](#)

### 2.2.2. Command: 21h / ! – Version

**input:** n. a.

**output:** <DeviceType[1..2]> <;> <CertificateNum[6]> <;>

<CertificateDateTime “DD-MM-YYYY HH:MM”> <;> <Model[50]> <;> <Version[20]>

**FPR operation:** Provides information about the device type, Certificate number, Certificate date and time and Device model.

**Input data : n. a.**

**Output data :**

|                     |   |
|---------------------|---|
| DeviceType          | 1 or 2 symbols for type of fiscal device:<br>- '1' – ECR<br>- '11' – ECR for online store<br>- '2' – FPr<br>- '21' – FPr for online store<br>- '3' – Fuel<br>- '31' – Fuel system<br>- '5' – for FUVAS device |
| CertificateNum      | 6 symbols for Certification Number of device model  |
| CertificateDateTime | 16 symbols for Certificate Date and time parameter<br>in format: DD-MM-YYYY HH:MM   |
| Model               | Up to 50 symbols for Model name   |
| Version             | Up to 20 symbols for Version name and Check sum   |

**zfpdef:** ReadVersion()

### 2.2.3. Command: 22h / " – Diagnostics

**input:** n. a.

**output:** ACK

**FPR operation:** Prints out a diagnostic receipt.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** PrintDiagnostics()

### 2.2.4. Command: 24h / \$ – Clear display

**input:** n. a.

**output:** ACK

**FPR operation:** Clears the external display.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** ClearDisplay()

### 2.2.5. Command: 25h / % – Display text line 1

**input:** <Text[20]>

**output:** ACK

**FPR operation:** Shows a 20-symbols text in the upper external display line.

**Input data :**

Text                      20 symbols text

**Output data: n. a.**

**zfpdef:** DisplayTextLine1(Text)

### 2.2.6. Command: 26h / & – Display text line 2

input: <Text[20]>

output: ACK

FPR operation: Shows a 20-symbols text in the lower external display line.

**Input data :**

Text                      20 symbols text

**Output data: n. a.**

**zfpdef:** DisplayTextLine2(Text)

### 2.2.7. Command: 27h / ' – Display text lines 1 and 2

input: <Text[40]>

output: ACK

FPR operation: Shows a 20-symbols text in the first line and last 20-symbols text in the second line of the external display lines.

**Input data :**

Text                      40 symbols text

**Output data: n. a.**

**zfpdef:** DisplayTextLines1and2(Text)

### 2.2.8. Command: 28h / ( – Display date and time

input: n. a.

output: ACK

FPR operation: Shows the current date and time on the external display.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** DisplayDateTime()

### 2.2.9. Command: 29h / ) – Cut paper, FP only

input: n. a.

output: ACK

FPR operation: Start paper cutter. The command works only in fiscal printer devices.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** CutPaper()

### 2.2.10. Command: 2Ah / \* – Cash drawer opening

input: n. a.

output: ACK

FPR operation: Opens the cash drawer.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** CashDrawerOpen()

### 2.2.11. Command: 2Bh / + – Paper feeding

input: n. a.

output: ACK

FPR operation: Feeds one line of paper.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** PaperFeed()

## 2.3. FISCAL COMMANDS

These are commands requiring data recording in the fiscal memory of the device. Password access is required.

### 2.3.1.1. Command: 56h / V – Set type of fiscal device, Option T

**input:** <'T'> <;> <FType[1]> <;> <Password[3]>

**output:** ACK

**FPR operation:** Define Fiscal device type. The command is allowed only in non-fiscal mode, before fiscalization and after deregistration before the next fiscalization. The type of device can be read by Version command 0x21.

**Input data :**

|          |   |
|----------|---|
| 'T'      | 1 symbol for option 'T'   |
| FType    | 1 symbol for fiscal device type with value: <ul style="list-style-type: none"><li>- '0' - FPr for Fuel type 3</li><li>- '1' – Main FPr for Fuel system type 31</li><li>- '2' - ECR for online store type 11</li><li>- '3' - FPr for online store type 21</li><li>- '*' – reset default type</li></ul> |
| Password | 3-symbols string  |

**Output data: n. a.**

**zfpdef:** SetFiscalDeviceType(FType, Password)

### 2.3.1.2. Command: 41h / A – Set customer UIC information, Option 1

**input:** <Password[6]> <;> <'1'> <;> <UIC[13]> <;> <UICType[1]>

**output:** ACK

**FPR operation:** Stores the Unique Identification Code (UIC) and UIC type into the operative memory.

**Input data :**

|          |   |
|----------|---|
| Password | 6-symbols string  |
| '1'      | One symbol with value 1   |
| UIC      | 13 symbols for UIC  |
| UICType  | 1 symbol for type of UIC number: <ul style="list-style-type: none"><li>- '0' - Bulstat</li><li>- '1' - EGN</li><li>- '2' – Foreigner Number</li><li>- '3' – NRA Official Number</li></ul> |

**Output data: n. a.**

**zfpdef:** SetCustomerUIC>Password, UIC, UICType)

### 2.3.1.3. Command: 41h / A – Confirm fiscalization, Option 2

**input:** <Password[6]> <;> <'2'>

**output:** ACK

**FPR operation:** Confirm Unique Identification Code (UIC) and UIC type into the operative memory.

**Input data :**

|          |                           |
|----------|---------------------------|
| Password | 6-symbols string          |
| '2'      | One symbol with value '2' |

**Output data: n. a.**

**zfpdef:** ConfirmFiscalization>Password)

### 2.3.2. Command: 42h / B – Change VAT rates

**input:** <Password[6]> <;> <VATrate0[6]> <;> <VATrate1[6]> <;> <VATrate2[6]> <;>  
<VATrate3[6]> <;> <VATrate4[6]><;> <VATrate5[6]><;> <VATrate6[6]> <;> <VATrate7[6]>

**output:** ACK

**FPR operation:** Stores a block containing the values of the VAT rates into the fiscal memory. Print the values on the printer.

**Input data :**

|          |  |
|----------|--|
| Password | 6-symbols string                                   |
| VATrate0 | Value of VAT rate A from 6 symbols in format ##.## |
| VATrate1 | Value of VAT rate Б from 6 symbols in format ##.## |
| VATrate2 | Value of VAT rate В from 6 symbols in format ##.## |
| VATrate3 | Value of VAT rate Г from 6 symbols in format ##.## |
| VATrate4 | Value of VAT rate Д from 6 symbols in format ##.## |
| VATrate5 | Value of VAT rate Е from 6 symbols in format ##.## |
| VATrate6 | Value of VAT rate Ж from 6 symbols in format ##.## |
| VATrate7 | Value of VAT rate З from 6 symbols in format ##.## |

**Output data: n. a.**

**zfpdef:** ProgVATrates(Password, VATrate0, VATrate1, VATrate2, VATrate3, VATrate4, VATrate5, VATrate6, VATrate7)

### 2.3.3. Command: 43h / C – Change decimal point position

**input:** <Password[6]> <;> <DecimalPointPosition[1]>

**output:** ACK

**FPR operation:** Stores a block containing the number format into the fiscal memory. Print the current status on the printer.

**Input data :**

|                      |   |
|----------------------|---|
| Password             | 6-symbols string  |
| DecimalPointPosition | 1 symbol with values: <ul style="list-style-type: none"><li>- '0' - Whole numbers</li><li>- '2' - Fractions</li></ul> |

**Output data: n. a.**

**zfpdef:** ProgDecimalPointPosition(Password, DecimalPointPosition)

## 2.4. PROGRAMMING COMMANDS

Set of commands, for programming the FD configuration according to the POS requirements and the user's needs.

### 2.4.1. Command: 44h / D – Program payment types

**input:** <PaymentNum[1..2]> <;> <Name[10]> { <;> <Rate[1..10]> }

**output:** ACK

**FPR operation:** Preprogram the name of the payment type.

**Input data :**

*PaymentNum* 1 symbol for payment type

- '9' – Payment 9
- '10' – Payment 10
- '11' – Payment 11

*Name* 10 symbols for payment type name

*Rate* (Exchange Rate) Up to 10 symbols for exchange rate in format: #####.#####  
of the 11th payment type, maximal value 0420.00000

**Output data: n. a.**

**zfpdef:** *ProgPayment(PaymentNum, Name, PaymentRate)*

### 2.4.2. Command: 44h / D – Program payment types, KL

**input:** <Number[1]><;> <Name[10]>{<;><Rate[1..10]><;><CodePayment[1]>}

**output:** ACK

**FPR operation:** Preprogram the name of the type of payment. Command works for KL version 2 devices.

**Input data :**

*Number* 1 symbol for payment type

- '1' – Payment 1
- '2' – Payment 2
- '3' – Payment 3
- '4' – Payment 4

*Name* 10 symbols for payment type name

*Rate* (Exchange Rate) Up to 10 symbols for exchange rate in format: #####.#####  
of the 4th payment type, maximal value 0420.00000

*CodePayment* 1 symbol for code payment type with name:

- '1' – Check
- '2' – Talon
- '3' – V. Talon
- '4' – Packaging
- '5' – Service
- '6' – Damage
- '7' – Card
- '8' – Bank
- '9' – Programming Name1
- '.' – Programming Name2

**Output data: n. a.**

**Note:** For Payment type 4 code payment type cannot be selected

**zfpdef:** *ProgPayment\_Old(Number, Name, PaymentRate, CodePayment)*



### 2.4.3. Command: 45h / E – Program parameters

**input:** <POSNum[4]> <;> <PrintLogo[1]> <;> <AutoOpenDrawer[1]> <;>  
<AutoCut[1]> <;> <ExternalDispManagement[1]> <;> <ArticleReportType[1]> <;>  
<EnableCurrency[1]> <;> <EJFontType[1]> <;> <reserved['0']> <;>  
<WorkOperatorCount[1]>

**output: ACK**

**FPR operation:** Programs the number of POS, printing of logo, cash drawer opening, cutting permission, external display management mode, article report type, enable or disable currency in receipt, EJ font type and working operators counter.

**Input data :**

|                               |  |
|-------------------------------|--|
| <i>POSNum</i>                 | (POS Number) 4 symbols for number of POS in format ####  |
| <i>PrintLogo</i>              | (Print Logo) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - Yes</li><li>- '0' - No</li></ul>                   |
| <i>AutoOpenDrawer</i>         | (Auto Open Drawer) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - Yes</li><li>- '0' - No</li></ul>             |
| <i>AutoCut</i>                | (Auto Cut) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - Yes</li><li>- '0' - No</li></ul>                     |
| <i>ExternalDispManagement</i> | (Ext. Display Management) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - Manual</li><li>- '0' - Auto</li></ul> |
| <i>ArticleReportType</i>      | (Article Report) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - Detailed</li><li>- '0' - Brief</li></ul>       |
| <i>EnableCurrency</i>         | (Enable Currency) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' – Yes</li><li>- '0' – No</li></ul>              |
| <i>EJFontType</i>             | (EJ Font) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - Low Font</li><li>- '0' - Normal Font</li></ul>        |
| <i>reserved</i>               | 1 symbol reserved '0'  |
| <i>WorkOperatorCount</i>      | (Work Operator Count) 1 symbol of value: <ul style="list-style-type: none"><li>- '1' - One</li><li>- '0' - More</li></ul>        |

**Output data: n. a.**

**Notes:**

The logo is a graphical file in **BMP** format with dimensions 384x80 / 448 X 160 /576x80 points, which is printed at the head of every receipt

“ExternalDispManagement” is a mode, in which the FD does not send information to the display except when executing the 25h, 26h and 27h commands. When this mode is off the FD “uses” the display to show data during sales, at receipt finalization, etc.

**zfpdef:** ProgParameters(POSNum, *PrintLogo*, *AutoOpenDrawer*, *AutoCut*, *ExternalDispManagement*, *EJFormat*, *ArticleRepType*, *EnableCurrency*, *EJFontType*, *WorkOperatorCount*)

#### 2.4.4. Command: 47h / G – Program department

**input:** <Number[2]> <;> <Name[20]> <;> <OptionVATClass[1]> { <;> <Price[1..10]> <;> <OptionDepPrice[1]> <;> <AdditionalName[14]> }

**output:** ACK

**FPR operation:** Set data for the state department number from the internal FD database. Parameters *Price*, *OptionDepPrice* and *AdditionalName* are not obligatory and require the previous not obligatory parameter.

**Input data:**

|                       |   |
|-----------------------|---|
| <i>Number</i>         | 2 symbols department number in format ##  |
| <i>Name</i>           | 20 characters department name   |
| <i>OptionVATClass</i> | 1 character for VAT class: <ul style="list-style-type: none"><li>- 'A' – VAT Class 0</li><li>- 'B' – VAT Class 1</li><li>- 'B' – VAT Class 2</li><li>- 'Г' – VAT Class 3</li><li>- 'Д' – VAT Class 4</li><li>- 'E' – VAT Class 5</li><li>- 'Ж' – VAT Class 6</li><li>- '3' – VAT Class 7</li><li>- '*' - Forbidden</li></ul>  |
| <i>Price</i>          | Up to 10 symbols for department price   |
| <i>OptionDepPrice</i> | 1 symbol for Department price flags with next value: <ul style="list-style-type: none"><li>- '0' - Free price disabled</li><li>- '1' - Free price enabled</li><li>- '2' - Limited price</li><li>- '4' - Free price disabled for single transaction</li><li>- '5' - Free price enabled for single transaction</li><li>- '6' - Limited price for single transaction</li></ul> |
| <i>AdditionalName</i> | 14 characters additional department name  |

**Output data : n. a.**

**Note:**

When changing the VAT group attachment of department must actualize the VAT groups of all articles attached to this department. Otherwise they won't be accessible for sale.

**zfpdef:** *ProgDepartment(Number, Name, OptionVATClass, Price, OptionDepPrice, AdditionalName)*

#### 2.4.5. Command: 48h / H – Program date and time

**input:** <DateTime “DD-MM-YY HH:MM:SS”>

**output:** ACK

**FPR operation:** Sets the date and time and prints out the current values.

**Input data :**

*DateTime*          Date Time parameter in format: DD-MM-YY HH:MM:SS

**Output data : n. a.**

**zfpdef:** *SetDateTime(DateTime)*

#### 2.4.6. Command: 49h / I – Program display greeting message

input: <'0'> <;> <DisplayGreetingText[20]>

output: ACK

FPR operation: Program the contents of a Display Greeting message.

##### Input data :

'0' 1 symbol with value '0'

DisplayGreetingText 20 symbols for Display greeting message

Output data: n. a.

[zfpdef:ProgDisplayGreetingMessage\(DisplayGreetingText\)](#)

#### 2.4.7. Command: 49h / I – Program header lines

input: <OptionHeaderLine[1]> <;> <HeaderText[TextLength]>

output: ACK

FPR operation: Program the contents of a header lines.

##### Input data :

OptionHeaderLine (Line Number) 1 symbol with value:

- '1' – Header 1

- '2' – Header 2

- '3' – Header 3

- '4' – Header 4

- '5' – Header 5

- '6' – Header 6

- '7' – Header 7

HeaderText TextLength symbols for header lines

Output data: n. a.

[zfpdef:ProgHeader\(OptionHeaderLine, HeaderText\)](#)

#### 2.4.8. Command: 49h / I – Program footer line

input: <'8'> <;> <FooterText[TextLength]>

output: ACK

FPR operation: Program the contents of a footer lines.

##### Input data :

'8' 1 symbol with value '8'

FooterText TextLength symbols for footer line

Output data: n. a.

[zfpdef:ProgFooter\(FooterText\)](#)

#### 2.4.9. Command: 49h / I – Program header UIC prefix

input: <'9'> <;> <HeaderUICprefix[12]>

output: ACK

FPR operation: Program the content of the header UIC prefix.

##### Input data :

'9' 1 symbol with value '9'

HeaderUICprefix 12 symbols for header UIC prefix

Output data: n. a.

[zfpdef: ProgHeaderUICprefix\(HeaderUICprefix\)](#)

## 2.4.10. Command: 4Ah / J – Program operator's name and password

**input:** <Number[1..2]> <;> <Name[20]> <;> <Password[6]>

**output:** ACK

**FPR operation:** Programs the operator's name and password.

### **Input data :**

*Number*                Symbols from '1' to '20' corresponding to operator's number

*Name*                 20 symbols for operator's name

*Password*            6 symbols for operator's password

### **Output data : n. a.**

**zfpdef:** *ProgOperator(*Number*, Name, Password)*

## 2.4.11. Command: 4Bh / K – Program article

**input:** <PLUNum[5]> <;> <Name[20]> <;> <Price[1..10]> <;> <OptionVATClass[1]>  
<;> <BelongToDepNum[1..2]>

**output:** ACK

**FPR operation:** Programs the data for a certain article (item) in the internal database. The price may have variable length, while the name field is fixed.

### **Input data :**

*PLUNum*                5 symbols for article number in format: #####

*Name*                 20 symbols for article name

*Price*                 Up to 10 symbols for article price

*OptionVATClass*      1 character for VAT class:

- 'A' – VAT Class 0

- 'B' – VAT Class 1

- 'B' – VAT Class 2

- 'Г' – VAT Class 3

- 'Д' – VAT Class 4

- 'E' – VAT Class 5

- 'Ж' – VAT Class 6

- '3' – VAT Class 7

- '\*' - Forbidden

*BelongToDepNum*    (Department Number) *BelongToDepNum* + 80h, 1 symbol for article department attachment, formed in the following manner:  
*BelongToDepNum* [HEX] + 80h example: Dep01 = 81h, Dep02 = 82h ...  
Dep19 = 93h

### **Output data: n. a.**

#### **Notes:**

When programming department attachment, FD checks whether the corresponding department is attached to same VAT group. In case they don't match no changes will be applied. Programming of value 0 (no department attachment) is possible any time.

**If no number is entered in the field of department attachment the command will execute with value 0 (no department attachment).**

**zfpdef:** *ProgPLU\_Old(*PLUNum*, Name, Price, OptionVATClass, BelongToDepNum)*

## 2.4.12. Command: 4Bh / K – Program article general registers, Option 1

**input:** <PLUNum[5]> <;> <Option['#@1+\$']> <;> <Name[34]> <;> <Price[1..10]> <;>  
<OptionPrice[1]> <;> <OptionVATClass[1]> <;> <BelongToDepNum[1..2]> <;>  
<SingleTransaction[1]>

**output: ACK**

**FPR operation:** Programs the general data for a certain article in the internal database. The price may have variable length, while the name field is fixed.

### **Input data :**

|                   |  |
|-------------------|--|
| PLUNum            | 5 symbols for article number in format: #####  |
| Option            | 5 symbols with value '#@1+\$'  |
| Name              | 34 symbols for article name  |
| Price             | Up to 10 symbols for article price   |
| OptionPrice       | 1 symbol for price flag with next value: <ul style="list-style-type: none"><li>- '0'- Free price is disable valid only programmed price</li><li>- '1'- Free price is enable</li><li>- '2'- Limited price</li></ul>   |
| OptionVATClass    | 1 character for VAT class: <ul style="list-style-type: none"><li>- 'A' – VAT Class 0</li><li>- 'Б' – VAT Class 1</li><li>- 'B' – VAT Class 2</li><li>- 'Г' – VAT Class 3</li><li>- 'Д' – VAT Class 4</li><li>- 'E' – VAT Class 5</li><li>- 'Ж' – VAT Class 6</li><li>- '3' – VAT Class 7</li><li>- '*' - Forbidden</li></ul> |
| BelongToDepNum    | (Department Number) BelongToDepNum + 80h, 1 symbol for article department attachment, formed in the following manner:<br>BelongToDepNum[HEX] + 80h example: Dep01 = 81h, Dep02 = 82h ...<br>Dep19 = 93h  |
| SingleTransaction | 1 symbol with value: <ul style="list-style-type: none"><li>- '0' – Inactive, default value</li><li>- '1' - Active Single transaction in receipt</li></ul>  |

### **Output data: n. a.**

**zfpdef:** ProgPLUgeneral(PLUNum, Name, Price, OptionPrice, OptionVATClass, BelongToDepNum, SingleTransaction)

## 2.4.13. Command: 4Bh / K – Program article quantity in stock, Option 2

**input:** <PLUNum[5]> <;> <Option['#@2+\$']> <;> <AvailableQuantity[1..11]> <;>  
<OptionQuantityType[1]>

**output: ACK**

**FPR operation:** Programs available quantity and Quantity type for a certain article in the internal database.

### **Input data :**

|                    |  |
|--------------------|--|
| PLUNum             | 5 symbols for article number in format: #####  |
| Option             | 5 symbols with value '#@2+\$'  |
| AvailableQuantity  | (Available Quantity) Up to 11 symbols for available quantity in stock  |
| OptionQuantityType | 1 symbol for Quantity flag with next value: <ul style="list-style-type: none"><li>- '0'- Availability of PLU stock is not monitored</li><li>- '1'- Disable negative quantity</li><li>- '2'- Enable negative quantity</li></ul> |

### **Output data: n. a.**

**zfpdef:** ProgPLUqty(PLUNum, AvailableQty, OptionQuantityType)

#### 2.4.14. Command: 4Bh / K – Program article barcode, Option 3

**input:** <PLUNum[5]> <;> <Option['#@3+\$']> <;> <Barcode[13]>

**output:** ACK

**FPR operation:** Programs Barcode of article in the internal database.

**Input data :**

PLUNum 5 symbols for article number in format: #####

Option 5 symbols with value '#@3+\$'

Barcode 13 symbols for barcode

**Output data: n. a.**

**zfpdef:** ProgPLUbarcode(PLUNum, Barcode)

#### 2.4.15. Command: 4Bh / K – Program article price, Option 4

**input:** <PLUNum[5]> <;> <Option['#@4+\$']> <;> <Price[1..10]> <;>  
<OptionPrice[1]>

**output:** ACK

**FPR operation:** Programs price and price type for a certain article in the internal database.

**Input data :**

PLUNum 5 symbols for article number in format: #####

Option 5 symbols with value '#@4+\$'

Price Up to 10 symbols for article price

OptionPrice 1 symbol for price flag with next value:  
- '0'- Free price is disable valid only programmed price  
- '1'- Free price is enable  
- '2'- Limited price

**Output data: n. a.**

**zfpdef:** ProgPLUprice(PLUNum, Price, OptionPrice)

#### 2.4.16. Command: 4Bh / K – Erase all PLU database

**input:** <PLUNum['00000']> <;> <Option['#@\$+\$']> <;> <Password[6]>

**output:** ACK

**FPR operation:** Erase all articles in PLU database.

**Input data :**

PLUNum 5 symbols '00000'

Option 5 symbols with value '#@\$+\$'

Password 6 symbols for password

**Output data: n. a.**

**zfpdef:** EraseAllPLUs(Password)

#### 2.4.17. Command: 4Ch / L – Program logo without setting a number (default number 0)

**input:** <BMPfile[9022]>

**output:** ACK

**FPR operation:** Stores in the memory the graphic file under number 0. Prints information about loaded in the printer graphic files.

**Input data:**

BMPfile \*BMP file with fixed size 9022 bytes

**Output data: n. a.**

**Notes:**

FD has the ability to store up to 10 different BMP files for logo with numbers from 0 to 9, as one of them is „active“ and is printed as receipt's logo. If there is no file loaded under the number, stated as „active“, FD will work as set for work without logo.

**zfpdef:** ProgLogo(BMPfile)

#### 2.4.18. Command: 4Dh / M – Program logo with setting a number

**input:** <LogoNumber[1]> <BMPfile[3902/9022/5822]>

**output:** ACK

**FPR operation:** Stores in the memory the graphic file under stated number. Prints information about loaded in the printer graphic files.

**Input data:**

*LogoNumber* 1 character value from '0' to '9' setting the number where the logo will be saved.

*BMPfile* BMP file with fixed size 3902/9022/5822 bytes

**Output data:** n. a.

**zfpdef:** ProgLogoNum(LogoNumber, BMPfile)

#### 2.4.19. Command: 23h / # – Program active logo number

**Input:** <LogoNumber[1]>

**output:** ACK

**FPR operation:** Sets logo number, which is active and will be printed as logo in the receipt header. Print information about active number.

**Input data:**

*LogoNumber* 1 character value from '0' to '9' or '?'. The number sets the active file, and the '?' invokes only printing of information

**Output data:** n. a.

**zfpdef:** SetActiveLogoNum(LogoNumber)

#### 2.4.20. Command: 51h / Q – Print barcode 'QP' (FP only)

**input:** <'P'> <;> <CodeType[1]> <;> <CodeLen[1..2]> <;> <CodeData[100]>

**output:** ACK

**FPR Operation:** Prints barcode from type stated by CodeType and CodeLen and with data stated in CodeData field. Command works only for fiscal printer devices. ECR does not support this command.

**Input data:**

*'P'* 1 character 'P'

*CodeType* 1 symbol with possible values:

- '0' – UPC A
- '1' – UPC E
- '2' – EAN 13
- '3' – EAN 8
- '4' – CODE 39
- '5' – ITF
- '6' – CODABAR
- 'H' – CODE 93
- 'I' – CODE 128

*CodeLen* Up to 2 bytes for number of bytes according to the table

*CodeData* Up to 100 bytes data in range according to the table

**Output data:** n.a.

Table:

| Barcode type  | <CodeType> | <CodeLen> | Range of <CodeData>    |
|---------------|------------|-----------|------------------------|
| UPC-A         | '0' or 'A' | 11 or 12  | Digits from '0' to '9' |
| UPC-E         | '1' or 'B' | 11 or 12  | Digits from '0' to '9' |
| JAN13 (EAN13) | '2' or 'C' | 12 or 13  | Digits from '0' to '9' |



|                |            |                              |   |
|----------------|------------|------------------------------|---|
| JAN8<br>(EAN8) | '3' or 'D' | 7 or 8                       | Digits from '0' to '9'  |
| CODE 39        | '4' or 'E' | from 1 to 10                 | Characters: 'SP' '\$' '%' '+' '-' '.' '/'<br>Digits from '0' to '9' letters from 'A' to 'Z' |
| ITF            | '5' or 'F' | from 2 to 18<br>(evens only) | Digits from '0' to '9'  |
| CODABAR        | '6' or 'G' | From 1 to 15                 | Characters: '\$' '+' '-' '/'<br>digits from '0' to '9' letters from 'A' to 'D'              |
| CODE 93        | 'H'        | From 1 to 14                 | Bytes from 0 to 7F  |
| CODE 128       | 'I'        | From 1 to 12                 | Bytes from 0 to 7F  |

The length restriction for some of the barcode types is because of the the print area not because of the barcode standard. If more data is sent the printed barcode may not be read correctly.

**zfpdef:** PrintBarcode(CodeType, CodeLen, CodeData)

#### 2.4.21. Command: 50h / P – Program invoice number range

**input:** <StartNum[10]> <;> <EndNum[10]>

**output:** ACK

**FPR Operation:** Set invoice start and end number range. To execute the command is necessary to grand following condition: the number range to be spent, not used, or not set after the last RAM reset.

**Input data:**

StartNum 10 characters for start number in format: #####

EndNum 10 characters for end number in format: #####

**Output data: n. a.**

**zfpdef:** SetInvoiceRange(StartNumber, EndNumber)

#### 2.4.22. Command: 52h / R – Program customer database

**input:** <Option['P']> <;> <CustomerNum[4]> <;> <CustomerCompanyName[26]>  
<;> <CustomerFullName[16]> <;> <VATNumber[13]> <;> <UIC[13]> <;> <Address[30]>  
<;> <UICType[1]>

**output:** ACK

**FPR Operation:** Program customer in FD data base.

**Input data:**

Option 1 symbol with value 'P'

CustomerNum (Customer Number) 4 symbols for customer number in format ####

CustomerCompanyName (Company name) 26 symbols for customer name

CustomerFullName (Buyer Name) 16 symbols for Buyer name

VATNumber 13 symbols for VAT number on customer

UIC 13 symbols for customer Unique Identification Code

Address 30 symbols for address on customer

UICType 1 symbol for type of Unique Identification Code:

- '0' - Bulstat

- '1' - EGN

- '2' – Foreigner Number

- '3' – NRA Official Number

**Output data: n. a.**

**zfpdef:** ProgCustomerData(CustomerNum, CustomerFirmName, CustomerFullName, UIC, FiscNum, Address, UICType)



## 2.5. DATA READING COMMANDS

Set of commands for receiving information from the FD about programmed values as well as additional information.

### 2.5.1. Command: 60h / ' – Read FD numbers

**input:** n. a.

**output:** <SerialNumber[8]> <;> <FMNumber[8]>

**FPR operation:** Provides information about the manufacturing number of the fiscal device and FM number.

**Input data : n. a.**

**Output data :**

SerialNumber 8 symbols for individual number of the fiscal device

FMNumber 8 symbols for individual number of the fiscal memory

**zfpdef:** [ReadSerialAndFiscalNums\(\)](#)

### 2.5.2. Command: 61h / a – Read registration information

**input:** n. a.

**output:** <UIC[13]> <;> <UICType[1]><;> <NRARegistrationNumber[6]><;>

<NRARegistrationDate “DD-MM-YYYY HH:MM” >

**FPR operation:** Provides information about the programmed VAT number, type of VAT number, register number in NRA and Date of registration in NRA.

**Input data : n. a.**

**Output data :**

UIC 13 symbols for Unique Identification Code

UICType 1 symbol for type of Unique Identification Code:

- '0' - Bulstat

- '1' - EGN

- '2' – Foreigner Number

- '3' – NRA Official Number

NRARegistrationNumber Register number on the Fiscal device from NRA

NRARegistrationDate Date of registration in NRA

**zfpdef:** [ReadRegistrationInfo\(\)](#)

### 2.5.3. Command: 62h / b – Read VAT rates

**input:** n. a.

**output:** <VATrate0[7]> <;> <VATrate1[7]> <;> <VATrate2[7]> <;> <VATrate3[7]>

<;> <VATrate4[7]> <;> <VATrate5[7]> <;> <VATrate6[7]> <;> <VATrate7[7]>

**FPR operation:** Provides information about the current VAT rates which are the last values stored into the FM.

**Input data : n. a.**

**Output data :**

VATrate0 Value of VAT rate A from 7 symbols in format ##.##%

VATrate1 Value of VAT rate Б from 7 symbols in format ##.##%

VATrate2 Value of VAT rate В from 7 symbols in format ##.##%

VATrate3 Value of VAT rate Г from 7 symbols in format ##.##%

VATrate4 Value of VAT rate Д from 7 symbols in format ##.##%

VATrate5 Value of VAT rate Е from 7 symbols in format ##.##%

VATrate6 Value of VAT rate Ж from 7 symbols in format ##.##%

VATrate7 Value of VAT rate З from 7 symbols in format ##.##%

**zfpdef:** [ReadVATrates\(\)](#)

## 2.5.4. Command: 63h / c – Read decimal point position

**input:** n. a.

**output:** <DecimalPointPosition[1]>

**FPR operation:** Provides information about the current (the last value stored into the FM) decimal point format.

**Input data :** n. a.

**Output data:**

*DecimalPointPosition*      1 symbol with values:  
                                     - '0' - Whole numbers  
                                     - '2' - Fractions

**zfpdef:** ReadDecimalPoint()

## 2.5.5. Command: 64h / d – Read payment types

**input:** n. a.

**output:** <NamePayment0[10]> <;> <NamePayment1[10]> <;>

<NamePayment2[10]> <;> <NamePayment3[10]> <;> <NamePayment4[10]> <;>

<NamePayment5[10]> <;> <NamePayment6[10]> <;> <NamePayment7[10]> <;>

<NamePayment8[10]> <;> <NamePayment9[10]> <;> <NamePayment10[10]> <;>

<NamePayment11[10]> <;> <ExchangeRate[1..10]>

**FPR operation:** Provides information about all programmed types of payment, currency name and currency exchange rate.

**Input data :** n. a.

**Output data :**

|                      |   |
|----------------------|---|
| <i>NamePayment0</i>  | 10 symbols for payment name type 0  |
| <i>NamePayment1</i>  | 10 symbols for payment name type 1  |
| <i>NamePayment2</i>  | 10 symbols for payment name type 2  |
| <i>NamePayment3</i>  | 10 symbols for payment name type 3  |
| <i>NamePayment4</i>  | 10 symbols for payment name type 4  |
| <i>NamePayment5</i>  | 10 symbols for payment name type 5  |
| <i>NamePayment6</i>  | 10 symbols for payment name type 6  |
| <i>NamePayment7</i>  | 10 symbols for payment name type 7  |
| <i>NamePayment8</i>  | 10 symbols for payment name type 8  |
| <i>NamePayment9</i>  | 10 symbols for payment name type 9  |
| <i>NamePayment10</i> | 10 symbols for payment name type 10   |
| <i>NamePayment11</i> | 10 symbols for payment name type 11   |
| <i>ExchangeRate</i>  | Up to 10 symbols for exchange rate of payment type 11 in format:<br>#####.##### |

**zfpdef:** ReadPayments()

## 2.5.6. Command: 64h / d – Read payment types, KL

**input:** n. a.

**output:** <NamePaym0[10]> <;> <NamePaym1[10]> <;> <NamePaym2[10]> <;>  
<NamePaym3[10]> <;> <NamePaym4[10]><;><ExRate[1..10]> <;> <CodePaym0[1]><;>  
<CodePaym1[1]><;> <CodePaym2[1]><;> <CodePaym3[1]> <;> <CodePaym4[1]>

**FPR operation:** Provides information about all programmed types of payment.

Command works for KL version 2 devices.

**Input data :** n. a.

**Output data :**

|           |   |
|-----------|---|
| NamePaym0 | 10 symbols for payment name type 0  |
| NamePaym1 | 10 symbols for payment name type 1  |
| NamePaym2 | 10 symbols for payment name type 2  |
| NamePaym3 | 10 symbols for payment name type 3  |
| NamePaym4 | 10 symbols for payment name type 4  |
| ExRate    | Up to 10 symbols for exchange rate of payment type 4 in format: #####.##### |
| CodePaym0 | 1 symbol for code of payment 0 = 0xFF (currency in cash)                    |
| CodePaym1 | 1 symbol for code of payment 1 (default value is '7')                       |
| CodePaym2 | 1 symbol for code of payment 2 (default value is '1')                       |
| CodePaym3 | 1 symbol for code of payment 3 (default value is '2')                       |
| CodePaym4 | 1 symbol for code of payment 4 = 0xFF (currency in cash)                    |

**zfpdef:** [ReadPayments\\_Old\(\)](#)

## 2.5.7. Command: 65h / e – Read parameters

**input:** n. a.

**output:** <POSNum[4]> <;> <PrintLogo[1]> <;> <AutoOpenDrawer[1]> <;>  
<AutoCut[1]> <;> <ExternalDispManagement[1]> <;> <ArticleReportType[1]> <;>  
<EnableCurrency[1]> <;> <EJFontType[1]> <;> <reserved['0']> <;>  
<WorkOperatorCount[1]>

**FPR operation:** Provides information about the number of POS, printing of logo, cash drawer opening, cutting permission, display mode, article report type, Enable/Disable currency in receipt, EJ font type and working operators counter.

**Input data :** n. a.

**Output data :**

|                        |  |
|------------------------|--|
| POSNum                 | (POS Number) 4 symbols for number of POS in format ####                            |
| PrintLogo              | (Print Logo) 1 symbol of value:<br>- '1' - Yes<br>- '0' - No                       |
| AutoOpenDrawer         | (Auto Open Drawer) 1 symbol of value:<br>- '1' - Yes<br>- '0' - No                 |
| AutoCut                | (Auto Cut) 1 symbol of value:<br>- '1' - Yes<br>- '0' - No                         |
| ExternalDispManagement | (External Display Management) 1 symbol of value:<br>- '1' - Manual<br>- '0' - Auto |
| ArticleReportType      | (Article Report) 1 symbol of value:<br>- '1' - Detailed<br>- '0' - Brief           |
| EnableCurrency         | (Enable Currency) 1 symbol of value:<br>- '1' - Yes<br>- '0' - No                  |

*EJFontType* (EJ Font) 1 symbol of value:  
 - '1' - Low Font  
 - '0' - Normal Font  
*reserved* 1 symbol reserved '0'  
*WorkOperatorCount* (Work Operator Count) 1 symbol of value:  
 - '1' - One  
 - '0' - More

**zfpdef:** ReadParameters()

## 2.5.8. Command: 66h / f – Read detailed printer status

**input:** n. a.

**output:** <ExternalDisplay[1]> <;> <StatPRN[4]> <;> <FlagServiceJumper[1]>

**FPR operation:** Provides additional status information

**Input data : n. a.**

**Output data :**

*ExternalDisplay* 1 symbol – connection with external display  
 - 'Y' - Yes  
 - 'N' - No

*StatPRN* 4 symbols for detailed status of printer (only for printers with **ASB**)

| <i>N<br/>byte</i> | <i>N bit</i> | <i>status flag</i>      |
|-------------------|--------------|-------------------------|
| ST0               | 0            | Reserved                |
|                   | 1            | Reserved                |
|                   | 2            | Signal level for drawer |
|                   | 3            | Printer not ready       |
|                   | 4            | Reserved                |
|                   | 5            | Open cover              |
|                   | 6            | Paper feed status       |
|                   | 7            | Reserved                |

|     |   |              |
|-----|---|--------------|
| ST1 | 0 | Reserved     |
|     | 1 | Reserved     |
|     | 2 | Reserved     |
|     | 3 | Cutter error |
|     | 4 | Reserved     |
|     | 5 | Fatal error  |
|     | 6 | Overheat     |
|     | 7 | Reserved     |

|     |   |                              |
|-----|---|------------------------------|
| ST2 | 0 | JNP (journal paper near end) |
|     | 1 | RNP (receipt paper near end) |
|     | 2 | JPE (journal paper end)      |
|     | 3 | RPE (receipt paper end)      |
|     | 4 | Reserved                     |
|     | 5 | Reserved                     |
|     | 6 | Reserved                     |
|     | 7 | Reserved                     |

|     |   |                               |
|-----|---|-------------------------------|
| ST3 | 0 | Print data buffer data exists |
|-----|---|-------------------------------|

|  |   |          |
|--|---|----------|
|  | 1 | Reserved |
|  | 2 | Reserved |
|  | 3 | Reserved |
|  | 4 | Reserved |
|  | 5 | Reserved |
|  | 6 | Reserved |
|  | 7 | Reserved |

*FlagServiceJumper* 1 symbol with value:

- 'J' - Yes
- ' ' - No

**zfpdef:** [ReadDetailedPrinterStatus\(\)](#)

## 2.5.9. Command: 67h / g – Read department registers

**input:** <DepNum[2]>

**output:** <DepNum[2]> <;> <DepName[20]> <;> <OptionVATClass[1]> <;>  
 <Turnover[1..13]> <;> <SoldQuantity[1..13]> <;> <LastZReportNumber[1..5]> <;>  
 <LastZReportDate "DD-MM-YYYY HH:MM">

**FPR operation:** Provides information for the programmed data, the turnover from the stated department number

### **Input data :**

*DepNum* (Department Number) 2 symbols for department number in format: ##

### **Output data :**

*DepNum* 2 symbols for department number in format: ##

*DepName* 20 symbols for department name

*OptionVATClass* 1 character for VAT class:

- 'A' – VAT Class 0
- 'Б' – VAT Class 1
- 'В' – VAT Class 2
- 'Г' – VAT Class 3
- 'Д' – VAT Class 4
- 'Е' – VAT Class 5
- 'Ж' – VAT Class 6
- 'З' – VAT Class 7
- '\*' - Forbidden

*Turnover* Up to 13 symbols for accumulated turnover of the article

*SoldQuantity* Up to 13 symbols for sold quantity of the department

*LastZReportNumber* Up to 5 symbols for the number of last Z Report

*LastZReportDate* 16 symbols for date and hour on last Z Report in format  
 "DD-MM-YYYY HH:MM"

**zfpdef:** [ReadDepartment\(\*DepNum\*\)](#)

## 2.5.10. Command: 67h / g – Read department registers, Option “(All)”

**input:** <DepNum[2]> <;> <reserved[""]>

**output:** <DepNum[2]> <;> <reserved[""]> <;> <DepName[34]> <;>  
<OptionVATClass[1]> <;> <Price[1..10]> <;> <OptionDepPrice[1]> <;>  
<TurnoverAmount[1..13]> <;> <SoldQuantity[1..13]> <;> <StornoAmount[1..13]> <;>  
<StornoQuantity[1..13]> <;> <LastZReportNumber[1..5]> <;>  
<LastZReportDate “DD-MM-YYYY HH:MM”>

**FPR operation:** Provides information for the programmed data, the turnovers from the stated department number

### **Input data :**

DepNum (Department Number) 2 symbols for department number in format: ##  
Reserved 1 symbol with value ""

### **Output data :**

DepNum 2 symbols for department number in format: ##  
reserved 1 symbol with value "" quotation mark.  
DepName 20 symbols for department name  
OptionVATClass 1 character for VAT class:  
- 'A' – VAT Class 0  
- 'B' – VAT Class 1  
- 'B' – VAT Class 2  
- 'Г' – VAT Class 3  
- 'Д' – VAT Class 4  
- 'E' – VAT Class 5  
- 'Ж' – VAT Class 6  
- '3' – VAT Class 7  
- '\*' - Forbidden  
Price Up to 10 symbols for department price  
OptionDepPrice 1 symbol for Department flags with next value:  
- '0' - Free price disabled  
- '1' - Free price enabled  
- '2' - Limited price  
- '4' - Free price disabled for single transaction  
- '5' - Free price enabled for single transaction  
- '6' - Limited price for single transaction  
TurnoverAmount Up to 13 symbols for accumulated turnover of the article  
SoldQuantity Up to 13 symbols for sold quantity of the department  
StornoAmount Up to 13 symbols for accumulated storno amount  
StornoQuantity Up to 13 symbols for accumulated storno quantity  
LastZReportNumber Up to 5 symbols for the number of last Z Report  
LastZReportDate 16 symbols for date and hour on last Z Report in format  
“DD-MM-YYYY HH:MM”

**zfpdef:** ReadDepartmentAll(DepNum)

## 2.5.11. Command: 68h / h – Read date and time

**input:** n. a.

**output:** <DateTime “DD-MM-YYYY HH:MM”>

**FPR operation:** Provides information about the current date and time.

### **Input data : n. a.**

### **Output data :**

DateTime Date Time parameter in format: DD-MM-YYYY HH:MM

**zfpdef:** ReadDateTime()

## 2.5.12. Command: 69h / i – Read display greeting message

**input:** <'0'>

**output:** <'0'> <;> <DisplayGreetingText[20]>

**FPR operation:** Provides the content of the Display Greeting message.

### **Input data :**

'0' 1 symbol with value 0

### **Output data:**

'0' 1 symbol with value 0

DisplayGreetingText 20 symbols for display greeting message

**zfpdef:** ReadDisplayGreetingMessage()

## 2.5.13. Command: 69h / i – Read header lines

**input:** <OptionHeaderLine[1]>

**output:** <OptionHeaderLine[1]> <;> <HeaderText[TextLength]>

**FPR operation:** Provides the content of the header lines

### **Input data :**

OptionHeaderLine (Line Number) 1 symbol with value:  
- '1' – Header 1  
- '2' – Header 2  
- '3' – Header 3  
- '4' – Header 4  
- '5' – Header 5  
- '6' – Header 6  
- '7' – Header 7

### **Output data:**

OptionHeaderLine (Line Number) 1 symbol with value:  
- '1' – Header 1  
- '2' – Header 2  
- '3' – Header 3  
- '4' – Header 4  
- '5' – Header 5  
- '6' – Header 6  
- '7' – Header 7

HeaderText TextLength symbols for header lines

**zfpdef:** ReadHeader(OptionHeaderLine)

#### 2.5.14. Command: 69h / i – Read footer line

**input:** <'8'>

**output:** <'8'> <;> <FooterText[TextLength]>

**FPR operation:** Provides the content of the footer line.

**Input data :**

'8' 1 symbol with value '8'

**Output data:**

'8' 1 symbol with value '8'

FooterText TextLength symbols for footer line

**zfpdef:** ReadFooter()

#### 2.5.15. Command: 69h / i – Read Header UIC prefix

**input:** <'9'>

**output:** <'9'> <;> <HeaderUICprefix[12]>

**FPR operation:** Provides the content of the header UIC prefix.

**Input data :**

'9' 1 symbol with value '9'

**Output data:**

'9' 1 symbol with value '9'

HeaderUICprefix 12 symbols for Header UIC prefix

**zfpdef:** ReadHeaderUICPrefix()

#### 2.5.16. Command: 6Ah / j – Read operator's name and password

**input:** <Number[1..2]>

**output:** <Number[1..2]> <;> <Name[20]> <;> <Password[6]>

**FPR operation:** Provides information about operator's name and password.

**Input data :**

Number (Operator Number) Symbol from 1 to 20 corresponding to the number of operators.

**Output data:**

Number Symbol from 1 to 20 corresponding to the number of operator

Name 20 symbols for operator's name

Password 6 symbols for operator's password

**zfpdef:** ReadOperatorNamePassword(Number)



## 2.5.17. Command: 6Bh / k – Read article

**input:** <PLUNum[5]>

**output:** <PLUNum[5]> <;> <PLUName[20]> <;> <Price[1..11]> <;>  
<OptionVATClass[1]> <;> <Turnover[1..13]> <;> <QuantitySold[1..13]> <;>  
<LastZReportNumber[1..5]> <;> <LastZReportDate "DD-MM-YYYY HH:MM"> <;>  
<BelongToDepNumber[1..2]>

**FPR operation:** Provides information about the registers of the specified article.

### **Input data :**

*PLUNum* (PLU Number) 5 symbols for article number in format #####

### **Output data:**

*PLUNum* 5 symbols for article number format #####

*PLUName* 20 symbols for article name

*Price* Up to 11 symbols for article price

*OptionVATClass* 1 character for VAT class:

- 'A' – VAT Class 0

- 'B' – VAT Class 1

- 'B' – VAT Class 2

- 'Г' – VAT Class 3

- 'Д' – VAT Class 4

- 'E' – VAT Class 5

- 'Ж' – VAT Class 6

- 'З' – VAT Class 7

- '\*' - Forbidden

*Turnover* Up to 13 symbols for turnover by this article

*QuantitySold* Up to 13 symbols for sold quantity

*LastZReportNumber* Up to 5 symbols for the number of last Z Report

*LastZReportDate* 16 symbols for date and hour on last Z Report in format  
DD-MM-YYYY HH:MM

*BelongToDepNumber* *BelongToDepNumber* + 80h, 1 symbol for article department  
attachment, formed in the following manner:  
*BelongToDepNumber*[HEX] + 80h example: Dep01 = 81h, Dep02  
= 82h ... Dep19 = 93h

**zfpdef:** *ReadPLU\_Old(PLUNum)*

## 2.5.18. Command: 6Bh / k – Read article registers, Option “ (All)

**input:** <PLUNum[5]> <;> <Option[""]>

**output:** <PLUNum[5]> <;> <Option[""]> <;> <PLUName[34]> <;> <Price[1..10]> <;>  
 <FlagsPricePLU[1]> <;> <OptionVATClass[1]> <;> <BelongToDepNumber[1..2]> <;>  
 <TurnoverAmount[1..13]> <;> <SoldQuantity[1..13]> <;> <StornoAmount[1..13]> <;>  
 <StornoQuantity[1..13]> <;> <LastZReportNumber[1..5]> <;>  
 <LastZReportDate “DD-MM-YYYY HH:MM”> <;> <AvailableQuantity[1..11]> <;>  
 <Barcode[13]>

**FPR operation:** Provides information about all the registers of the specified article.

### Input data :

**PLUNum** (PLU Number) 5 symbols for article number with leading zeroes in format: #####  
**Option** One symbol with value "" quotation mark

### Output data :

**PLUNum** 5 symbols for article number with leading zeroes in format: #####  
**Option** One symbol with value ""  
**PLUName** 34 symbols for article name, *new line=0x7C*.  
**Price** Up to 10 symbols for article price  
**FlagsPricePLU** 1 symbol for flags = 0x80 + FlagSinglTr + FlagQTY + OptionPrice

Where

OptionPrice:

0x00 - for free price is disable valid only programmed price

0x01 - for free price is enable

0x02 - for limited price

FlagQTY:

0x00 - for availability of PLU stock is not monitored

0x04 - for disable negative quantity

0x08 - for enable negative quantity

FlagSingleTr:

0x00 – no single transaction

0x10 – single transaction is active

**OptionVATClass** 1 character for VAT class:

- 'A' – VAT Class 0

- 'B' – VAT Class 1

- 'B' – VAT Class 2

- 'Г' – VAT Class 3

- 'Д' – VAT Class 4

- 'E' – VAT Class 5

- 'Ж' – VAT Class 6

- '3' – VAT Class 7

- '\*' - Forbidden

**BelongToDepNumber** *BelongToDepNumber* + 80h, 1 symbol for PLU department attachment = 0x80 ... 0x93

**TurnoverAmount** Up to 13 symbols for PLU accumulated turnover

**SoldQuantity** Up to 13 symbols for Sales quantity of the article

**StornoAmount** Up to 13 symbols for accumulated storno amount

**StornoQuantity** Up to 13 symbols for accumulated storno quantity

**LastZReportNumber** Up to 5 symbols for the number of the last article report with zeroing

**LastZReportDate** 16 symbols for the date and time of the last article report with zeroing in format *DD-MM-YYYY HH:MM*

**AvailableQuantity** (Available Quantity) Up to 11 symbols for quantity in stock

**Barcode** 13 symbols for article barcode

**zfpdef:** *ReadPLUallData(PLUNum)*

## 2.5.19. Command: 6Bh / k – Read article registers, Option 1 (General)

**input:** <PLUNum[5]> <;> <Option['1']>

**output:** <PLUNum[5]> <;> <Option['1']> <;> <PLUName[34]> <;> <Price[1..10]> <;>  
<OptionPrice[1]> <;> <OptionVATClass[1]> <;> <BelongToDepNumber[1..2]> <;>  
<TurnoverAmount[1..13]> <;> <SoldQuantity[1..13]> <;> <StornoAmount[1..13]> <;>  
<StornoQuantity[1..13]> <;> <LastZReportNumber[1..5]> <;>  
<LastZReportDate "DD-MM-YYYY HH:MM"> <;> <SingleTransaction[1]>

**FPR operation:** Provides information about the general registers of the specified article.

### **Input data :**

*PLUNum* (PLU No) 5 symbols for article number with leading zeroes in format: #####

*Option* One symbol with value '1'

### **Output data :**

*PLUNum* 5 symbols for article number with leading zeroes in format #####

*Option* One symbol with value '1'

*PLUName* 34 symbols for article name, *new line=0x7C*.

*Price* Up to 10 symbols for article price

*OptionPrice* 1 symbol for price flag with next value:

- '0'- Free price is disable valid only programmed price
- '1'- Free price is enable
- '2'- Limited price

*OptionVATClass* 1 character for VAT class:

- 'A' – VAT Class 0
- 'B' – VAT Class 1
- 'B' – VAT Class 2
- 'Γ' – VAT Class 3
- 'Δ' – VAT Class 4
- 'E' – VAT Class 5
- 'Ж' – VAT Class 6
- '3' – VAT Class 7
- '\*' - Forbidden

*BelongToDepNumber* *BelongToDepNumber* + 80h, 1 symbol for PLU department attachment= 0x80 ... 0x93

*TurnoverAmount* Up to 13 symbols for PLU accumulated turnover

*SoldQuantity* Up to 13 symbols for Sales quantity of the article

*StornoAmount* Up to 13 symbols for accumulated storno amount

*StornoQuantity* Up to 13 symbols for accumulated storno quantity

*LastZReportNumber* Up to 5 symbols for the number of the last article report with zeroing

*LastZReportDate* 16 symbols for the date and time of the last article report with zeroing in format *DD-MM-YYYY HH:MM*

*SingleTransaction* 1 symbol with value:

- '0' – Inactive, default value
- '1' - Active Single transaction in receipt

**zfpdef:** *ReadPLUGeneral(PLUNum)*

## 2.5.20. Command: 6Bh / k – Read article registers, Option 2 (Quantity)

**input:** <PLUNum[5]> <;> <Option['2']>

**output:** <PLUNum[5]> <;> <Option['2']> <;> <AvailableQuantity[1..13]> <;>  
<OptionQuantityType[1]>

**FPR operation:** Provides information about the quantity registers of the specified article.

### **Input data :**

PLUNum (PLU Number) 5 symbols for article number with leading zeroes in format: #####

Option One symbol with value 2

### **Output data :**

PLUNum 5 symbols for article number with leading zeroes in format #####

Option One symbol with value 2

AvailableQuantity Up to 13 symbols for quantity in stock

OptionQuantityType 1 symbol for Quantity flag with next value:

- '0'- Availability of PLU stock is not monitored
- '1'- Disable negative quantity
- '2'- Enable negative quantity

**zfpdef:** ReadPLUqty(PLUNum)

## 2.5.21. Command: 6Bh / k – Read article registers, Option 3 (Barcode)

**input:** <PLUNum[5]> <;> <Option['3']>

**output:** <PLUNum[5]> <;> <Option['3']> <;> <Barcode[13]>

**FPR operation:** Provides information about the barcode of the specified article.

### **Input data :**

PLUNum (PLU Number) 5 symbols for article number with leading zeroes in format: #####

Option One symbol with value 3

### **Output data :**

PLUNum 5 symbols for article number with leading zeroes in format #####

Option One symbol with value 3

Barcode 13 symbols for article barcode

**zfpdef:** ReadPLUbarcode(PLUNum)

## 2.5.22. Command: 6Bh / k – Read article registers, Option 4 (Price)

**input:** <PLUNum[5]> <;> <Option['4']>

**output:** <PLUNum[5]> <;> <Option['4']> <;> <Price[1..10]> <;> <OptionPrice[1]>

**FPR operation:** Provides information about the price and price type of the specified article.

### **Input data :**

PLUNum (PLU Number) 5 symbols for article number with leading zeroes in format: #####

Option One symbol with value 4

### **Output data :**

PLUNum 5 symbols for article number with leading zeroes in format #####

Option One symbol with value 4

Price Up to 10 symbols for article price

OptionPrice 1 symbol for price flag with next value:

- '0'- Free price is disable valid only programmed price
- '1'- Free price is enable
- '2'- Limited price

**zfpdef:** ReadPLUprice(PLUNum)

### 2.5.23. Command: 6Ch / I – Print Logo

**input:** <Number[1..2]>

**output:** ACK

**FPR operation:** Prints the programmed graphical logo with the stated number.

**Input data :**

Number                      Number of logo to be printed. If missing, prints logo with number 0

**Output data : n. a.**

**zfpdef:** PrintLogo(Number)

### 2.5.24. Command: 52h / R – Read customer database

**input:** <Option['R']> <;> <CustomerNum[4]>

**output:** <CustomerNum[4]> <;> <CustomerCompanyName[26]> <;>

<CustomerFullName[16]> <;> <VATNumber[13]> <;> <UIC[13]> <;> <Address[30]> <;>  
<UICType[1]>

**FPR Operation:** Provide information for specified customer from FD data base.

**Input data:**

Option                      1 symbol 'R'

CustomerNum                (Customer Number) 4 symbols for customer number in format ####

**Output data:**

CustomerNum                (Customer Number) 4 symbols for customer number in format ####

CustomerCompanyName      (Company name) 26 symbols for customer name

CustomerFullName          (Buyer Name) 16 symbols for Buyer name

VATNumber                  13 symbols for VAT number on customer

UIC                          13 symbols for customer Unique Identification Code

Address                     30 symbols for address on customer

UICType                     1 symbol for type of Unique Identification Code:

- '0' - Bulstat

- '1' - EGN

- '2' – Foreigner Number

- '3' – NRA Official Number

**zfpdef:** ReadCustomerData(CustomerNum)

### 2.5.25. Command: 4Fh / O – Read automatic daily report parameter

**input:** <'H'> <;> <'R'>

**output:** <'H'> <;> <'R'> <;> <DailyReportSetting[1]>

**FPR Operation:** Provide information about daily report parameter. If the parameter is set to 0 the status flag 4.6 will become 1 and the device will block all sales operation until daily report is printed. If the parameter is set to 1 the report will be generated automatically without printout

**Input data:**

'H'                          1 symbol with value 'H'

'R'                          1 symbol with value 'R'

**Output data: n. a.**

'H'                          1 symbol with value 'H'

'R'                          1 symbol with value 'R'

DailyReportSetting        1 symbol with value:  
- '0' –Z report with printing  
- '1' – Automatic Z report without printing

**zfpdef:** ReadDailyReportParameter()

## 2.6. RECEIPT OPERATIONS COMMANDS

These commands are used mainly for FD sales registration. The group also includes some auxiliary commands providing information for the current receipt as well as commands for RA and PO amounts.

### 2.6.1. Command: 2Eh / . – Open Non-fiscal receipt

**input:** <OperNum[1..2]> <;> <OperPass[6]> {<;> <Reserved['0']> <;>  
<NonFiscalPrintType[1]>}

**output:** ACK

**FPR operation:** Opens a non-fiscal receipt assigned to the specified operator number, operator password and print type.

**Input data :**

|                    |   |
|--------------------|---|
| OperNum            | (Operator Number) Symbols from 1 to 20 corresponding to operator's number                           |
| OperPass           | (Operator Password) 6 symbols for operator's password   |
| Reserved           | 1 symbol with value '0'   |
| NonFiscalPrintType | (Printing type) 1 symbol with value:<br>- '0' – Step by step printing<br>- '1' – Postponed Printing |

**Output data: n. a.**

**zfpdef:** *OpenNonFiscalReceipt(OperNum, OperPass, NonFiscalPrintType)*

### 2.6.2. Command: 2Fh / / – Close Non-fiscal receipt

**input:** n. a.

**output:** ACK

**FPR operation:** Closes the non-fiscal receipt.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** *CloseNonFiscalReceipt()*



### 2.6.3. Command: 30h / 0 –Open Fiscal sales receipt

**input:**<OperNum[1..2]> <;> <OperPass[6]> <;> <ReceiptFormat[1]> <;>  
<PrintVAT[1]> <;> <FiscalRcpPrintType[1]> {<'\$'> <UniqueReceiptNumber[24]>}

**output: ACK**

**FPR operation:** Opens a fiscal receipt assigned to the specified operator number and operator password, parameters for receipt format, print VAT, printing type and unique receipt number.

**Input data :**

|                     |   |
|---------------------|---|
| OperNum             | (Operator Number) Symbols from 1 to 20 corresponding to operator's number   |
| OperPass            | (Operator Password) 6 symbols for operator's password   |
| ReceiptFormat       | (Format) 1 symbol with value:<br>- '1' - Detailed<br>- '0' - Brief  |
| PrintVAT            | (VAT included in the receipt) 1 symbol with value:<br>- '1' – Yes<br>- '0' – No   |
| FiscalRcpPrintType  | (Printing type) 1 symbol with value:<br>- '0' – Step by step printing<br>- '2' – Postponed printing<br>- '4' – Buffered printing  |
| UniqueReceiptNumber | Up to 24 symbols for unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYY – 7 symbols [0-9] for next number of the receipt |

**Output data: n. a.**

**zfpdef:** OpenReceipt(OperNum, OperPass, RcpFormat, PrintVAT, FiscalRcpPrintType, UniqueReceiptNumber)

### 2.6.4. Command: 30h / 0 –Open ELECTRONIC Fiscal sales receipt

**input:**<OperNum[1..2]> <;> <OperPass[6]> <;> <ReceiptFormat[1]> <;>  
<PrintVAT[1]> <;> <FiscalRcpPrintType[8]> {<'\$'> <UniqueReceiptNumber[24]>}

**output: ACK**

**FPR operation:** Opens an postponed electronic fiscal receipt with 1 minute timeout assigned to the specified operator number and operator password, parameters for receipt format, print VAT, printing type and unique receipt number.

**Input data :**

|                     |   |
|---------------------|---|
| OperNum             | (Operator Number) Symbols from 1 to 20 corresponding to operator's number   |
| OperPass            | (Operator Password) 6 symbols for operator's password   |
| ReceiptFormat       | (Format) 1 symbol with value:<br>- '1' - Detailed<br>- '0' - Brief  |
| PrintVAT            | (VAT included in the receipt) 1 symbol with value:<br>- '1' – Yes<br>- '0' – No   |
| FiscalRcpPrintType  | 1 symbol with value '8' for Postponed printing of electronic receipt  |
| UniqueReceiptNumber | Up to 24 symbols for unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYY – 7 symbols [0-9] for next number of the receipt |

**Output data: n. a.**

**zfpdef:** OpenElectronicReceipt(OperNum, OperPass, RcpFormat, PrintVAT, UniqueReceiptNumber)

## 2.6.5. Command: 30h / 0 –Open Fiscal storno receipt

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <ReceiptFormat[1]> <;>  
<PrintVAT[1]> <;> <StornoRcpPrintType[1]> <;> <StornoReason[1]> <;>  
<RelatedToRcpNum[1..6]> <;> <RelatedToRcpDateTime "DD-MM-YY HH:MM:SS"> <;>  
<FMNum[8]> {<;> <RelatedToURN[24]>}

**output:** ACK

**FPR operation:** Open a fiscal storno receipt assigned to the specified operator number and operator password, parameters for receipt format, print VAT, printing type and parameters for the related storno receipt.

### **Input data :**

|                      |  |
|----------------------|--|
| OperNum              | (Operator Number) Symbols from 1 to 20 corresponding to operator's number  |
| OperPass             | (Operator Password) 6 symbols for operator's password  |
| ReceiptFormat        | (Format) 1 symbol with value:<br>- '1' - Detailed<br>- '0' - Brief   |
| PrintVAT             | (VAT included in the receipt) 1 symbol with value:<br>- '1' – Yes<br>- '0' – No  |
| StornoRcpPrintType   | (Printing type) 1 symbol with value:<br>- '@' – Step by step printing<br>- 'B' – Postponed Printing<br>- 'D' – Buffered Printing   |
| StornoReason         | 1 symbol for reason of storno operation with value:<br>- '0' – Operator error<br>- '1' – Goods Claim or Goods return<br>- '2' – Tax relief   |
| RelatedToRcpNum      | (Receipt number) Up to 6 symbols for issued receipt number   |
| RelatedToRcpDateTime | (Receipt Date and Time) 17 symbols for Date and Time of the issued receipt in format DD-MM-YY HH:MM:SS   |
| FMNum                | 8 symbols for number of the Fiscal Memory  |
| RelatedToURN         | Up to 24 symbols for the issued receipt unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYYY – 7 symbols [0-9] for next number of the receipt |

### **Output data: n. a.**

#### **Note:**

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenStornoReceipt(OperNum, OperPass, ReceiptFormat, PrintVAT, StornoRcpPrintType, StornoReason, RelatedToRcpNum, RelatedToRcpDateTime, FMNum, RelatedToURN)*



## 2.6.6. Command: 30h / 0 – Open Fiscal Invoice receipt with free customer data

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <reserved['0']> <;> <InvoicePrintType[1]> <;> <Recipient[26]> <;> <Buyer[16]> <;> <VATNumber[13]> <;> <UIC[13]> <;> <Address[30]> <;> <UICType[1]> { <'\$> <UniqueReceiptNumber[24]> }

**output:** ACK

**FPR operation:** Opens a fiscal invoice receipt assigned to the specified operator number and operator password with free info for customer data. The Invoice receipt can be issued only if the invoice range (start and end numbers) is set.

### **Input data :**

|                            |   |
|----------------------------|---|
| <i>OperNum</i>             | (Operator Number) Symbol from 1 to 20 corresponding to operator's number  |
| <i>OperPass</i>            | (Operator Password) 6 symbols for operator's password   |
| <i>reserved</i>            | 1 symbol with value '0'   |
| <i>reserved</i>            | 1 symbol with value '0'   |
| <i>InvoicePrintType</i>    | (Printing type) 1 symbol with value:<br>- '1' – Step by step printing<br>- '3' – Postponed Printing<br>- '5' – Buffered Printing  |
| <i>Recipient</i>           | 26 symbols for Invoice recipient  |
| <i>Buyer</i>               | 16 symbols for Invoice buyer  |
| <i>VATNumber</i>           | 13 symbols for customer Fiscal number   |
| <i>UIC</i>                 | 13 symbols for customer Unique Identification Code  |
| <i>Address</i>             | 30 symbols for Address  |
| <i>UICType</i>             | <b>1 symbol for type of Unique Identification Code:</b><br>- '0' - Bulstat<br>- '1' - EGN<br>- '2' – Foreigner Number<br>- '3' – NRA Official Number  |
| <i>UniqueReceiptNumber</i> | Up to 24 symbols for unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYY – 7 symbols [0-9] for next number of the receipt |

### **Output data: n. a.**

#### **Note:**

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenInvoiceWithFreeCustomerData(OperNum, OperPass, InvoicePrintType, Recipient, Buyer, UIC, IDNumber, Address, UICType, UniqueReceiptNumber)*

### 2.6.7. Command: 30h / 0 – Open **ELECTRONIC** Fiscal Invoice receipt with free customer data

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <reserved['0']>  
<;> <InvoicePrintType['9']> <;> <Recipient[26]> <;> <Buyer[16]> <;> <VATNumber[13]>  
<;> <UIC[13]> <;> <Address[30]> <;> <UICType[1]> { <'>'> <UniqueReceiptNumber[24]> }

**output:** ACK

**FPR operation:** Opens an electronic fiscal invoice receipt with 1 minute timeout assigned to the specified operator number and operator password with free info for customer data. The Invoice receipt can be issued only if the invoice range (start and end numbers) is set.

#### **Input data :**

|                     |   |
|---------------------|---|
| OperNum             | (Operator Number) Symbol from 1 to 20 corresponding to operator's number  |
| OperPass            | (Operator Password) 6 symbols for operator's password   |
| reserved            | 1 symbol with value '0'   |
| reserved            | 1 symbol with value '0'   |
| InvoicePrintType    | 1 symbol with value '9' for Postponed Printing of electronic receipt  |
| Recipient           | 26 symbols for Invoice recipient  |
| Buyer               | 16 symbols for Invoice buyer  |
| VATNumber           | 13 symbols for customer Fiscal number   |
| UIC                 | 13 symbols for customer Unique Identification Code  |
| Address             | 30 symbols for Address  |
| UICType             | 1 symbol for type of Unique Identification Code:<br>- '0' - Bulstat<br>- '1' - EGN<br>- '2' – Foreigner Number<br>- '3' – NRA Official Number   |
| UniqueReceiptNumber | Up to 24 symbols for unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYY – 7 symbols [0-9] for next number of the receipt |

#### **Output data: n. a.**

##### **Note:**

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenElectronicInvoiceWithFreeCustomerData(OperNum, OperPass, Recipient, Buyer, UIC, IDNumber, Address, UICType, UniqueReceiptNumber)*

## 2.6.8. Command: 30h / 0 – Open Fiscal Invoice Credit Note receipt with free customer data

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <reserved['0']> <;>  
 <InvoiceCreditNotePrintType[1]> <;> <Recipient[26]> <;> <Buyer[16]> <;> <VATNumber[13]>  
 <;> <UIC[13]> <;> <Address[30]> <;> <UICType[1]> <;> <StornoReason[1]> <;>  
 <RelatedToInvoiceNum[10]> <;> <RelatedToInvoiceDateTime"DD-MM-YY HH:MM:SS">  
 <;> <RelatedToRcpNum[1..6]> <;> <FMNum[8]> { <;> <RelatedToURN[24]> }

**output: ACK**

**FPR operation:** Opens a fiscal invoice credit note receipt assigned to the specified operator number and operator password with free info for customer data. The Invoice receipt can be issued only if the invoice range (start and end numbers) is set.

### Input data :

|                            |  |
|----------------------------|--|
| OperNum                    | (Operator Number) Symbol from 1 to 20 corresponding to operator's number   |
| OperPass                   | (Operator Password) 6 symbols for operator's password  |
| reserved                   | 1 symbol with value '0'  |
| reserved                   | 1 symbol with value '0'  |
| InvoiceCreditNotePrintType | (Printing type) 1 symbol with value:<br>- 'A' – Step by step printing<br>- 'C' – Postponed Printing<br>- 'E' – Buffered Printing   |
| Recipient                  | 26 symbols for Invoice recipient   |
| Buyer                      | 16 symbols for Invoice buyer   |
| VATNumber                  | 13 symbols for customer Fiscal number  |
| UIC                        | 13 symbols for customer Unique Identification Code   |
| Address                    | 30 symbols for Address   |
| UICType                    | 1 symbol for type of Unique Identification Code:<br>- '0' - Bulstat<br>- '1' - EGN<br>- '2' – Foreigner Number<br>- '3' – NRA Official Number  |
| StornoReason               | 1 symbol for reason of storno operation with value:<br>- '0' – Operator error<br>- '1' – Goods Claim or Goods return<br>- '2' – Tax relief   |
| RelatedToInvoiceNum        | 10 symbols for issued invoice number   |
| RelatedToInvoiceDateTime   | 17 symbols for issued invoice date and time in format<br>DD-MM-YY HH:MM:SS   |
| RelatedToRcpNum            | (Receipt number) Up to 6 symbols for issued receipt number   |
| FMNum                      | 8 symbols for number of the Fiscal Memory  |
| RelatedToURN               | Up to 24 symbols for the issued invoice receipt unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYY – 7 symbols [0-9] for next number of the receipt |

### Output data: n. a.

#### Note:

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenCreditNoteWithFreeCustomerData(OperNum, OperPass, InvoiceCreditNotePrintType, Recipient, Buyer, UIC, IDNumber, Address, UICType, RelatedToInvoiceNum, RelatedToInvoiceDateTime, RelatedToRcpNum, FMNum, RelatedToURN)*

## 2.6.9. Command: 30h / 0 – Open Fiscal Invoice receipt with customer data from FD database

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <reserved['0']> <;>  
<InvoicePrintType[1]> <;> <CustomerNum[5]> { <'<''>'> <UniqueReceiptNumber[24]> }

**output: ACK**

**FPR operation:** Opens a fiscal invoice receipt assigned to the specified operator number and operator password with internal DB info for customer data. The Invoice receipt can be issued only if the invoice range (start and end numbers) is set.

### **Input data :**

|                     |   |
|---------------------|---|
| OperNum             | (Operator Number) Symbol from 1 to 20 corresponding to operator's number  |
| OperPass            | (Operator Password) 6 symbols for operator's password   |
| reserved            | 1 symbol with value '0'   |
| reserved            | 1 symbol with value '0'   |
| InvoicePrintType    | (Printing type) 1 symbol with value:<br>- '1' – Step by step printing<br>- '3' – Postponed Printing<br>- '5' – Buffered Printing  |
| CustomerNum         | Symbol '#' and following up to 4 symbols for related customer ID number corresponding to the FD database  |
| UniqueReceiptNumber | Up to 24 symbols for unique receipt number.<br>NRA format: XXXXXXXX-XXXX-YYYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* XXXX – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYYY – 7 symbols [0-9] for next number of the receipt |

### **Output data: n. a.**

#### **Note:**

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenInvoiceWithFDCustomerDB(OperNum, OperPass, InvoicePrintType, CustomerNum, UniqueReceiptNumber)*

## 2.6.10. Command: 30h / 0 – Open ELECTRONIC Fiscal Invoice receipt with customer data from FD database

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <reserved['0']> <;>  
<InvoicePrintType['9']> <;> <CustomerNum[5]> { <'\$'> <UniqueReceiptNumber[24]> }

**output:** ACK

**FPR operation:** Opens an electronic fiscal invoice receipt with 1 minute timeout assigned to the specified operator number and operator password with internal DB info for customer data. The Invoice receipt can be issued only if the invoice range (start and end numbers) is set.

### **Input data :**

|                     |   |
|---------------------|---|
| OperNum             | (Operator Number) Symbol from 1 to 20 corresponding to operator's number  |
| OperPass            | (Operator Password) 6 symbols for operator's password   |
| reserved            | 1 symbol with value '0'   |
| reserved            | 1 symbol with value '0'   |
| InvoicePrintType    | <b>1 symbol with value '9' for Postponed Printing of electronic receipt</b>   |
| CustomerNum         | Symbol '#' and following up to 4 symbols for related customer ID number corresponding to the FD database  |
| UniqueReceiptNumber | Up to 24 symbols for unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYY – 7 symbols [0-9] for next number of the receipt |

### **Output data: n. a.**

#### **Note:**

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenElectronicInvoiceWithFDCustomerDB(OperNum, OperPass, CustomerNum, UniqueReceiptNumber)*

## 2.6.11. Command: 30h / 0 – Open Fiscal Invoice Credit Note receipt with customer data from FD database

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <reserved['0']> <;>  
<InvoiceCreditNotePrintType[1]> <;> <CustomerNum[5]> <;> <StornoReason[1]> <;>  
<RelatedToInvoiceNum[10]> <;> <RelatedToInvoiceDateTime "DD-MM-YY HH:MM:SS">  
<;> <RelatedToRcpNum[1..6]> <;> <FMNum[8]> { <;> <RelatedToURN[24]> }

**output: ACK**

**FPR operation:** Opens a fiscal invoice credit note receipt assigned to the specified operator number and operator password with internal DB info for customer data. The Invoice receipt can be issued only if the invoice range (start and end numbers) is set.

### **Input data :**

|                            |  |
|----------------------------|--|
| OperNum                    | (Operator Number) Symbol from 1 to 20 corresponding to operator's number   |
| OperPass                   | (Operator Password) 6 symbols for operator's password  |
| reserved                   | 1 symbol with value '0'  |
| reserved                   | 1 symbol with value '0'  |
| InvoiceCreditNotePrintType | (Printing type) 1 symbol with value:<br>- 'A' – Step by step printing<br>- 'C' – Postponed Printing<br>- 'E' – Buffered Printing   |
| CustomerNum                | Symbol '#' and following up to 4 symbols for related customer ID number corresponding to the FD database   |
| StornoReason               | 1 symbol for reason of storno operation with value:<br>- '0' – Operator error<br>- '1' – Goods Claim or Goods return<br>- '2' – Tax relief   |
| RelatedToInvoiceNum        | 10 symbols for issued invoice number   |
| RelatedToInvoiceDateTime   | 17 symbols for issued invoice date and time in format DD-MM-YY HH:MM:SS  |
| RelatedToRcpNum            | (Receipt number) Up to 6 symbols for issued receipt number   |
| FMNum                      | 8 symbols for number of the Fiscal Memory  |
| RelatedToURN               | Up to 24 symbols for the issued invoice receipt unique receipt number.<br>NRA format: XXXXXXXX-ZZZZ-YYYYYYYY where:<br>* XXXXXXXX – 8 symbols [A-Z, a-z, 0-9] for individual device number,<br>* ZZZZ – 4 symbols [A-Z, a-z, 0-9] for code of the operator,<br>* YYYYYYYY – 7 symbols [0-9] for next number of the receipt |

### **Output data: n. a.**

#### **Note:**

If Postponed printing is enabled after opened fiscal receipt, all the next commands will be executed but won't be printed immediately. The data for whole receipt is stored to be printed up to AS sent information for receipt closure. If up to 5 sec timeout no command ECR closing the receipt

**zfpdef:** *OpenCreditNoteWithFDCustomerDB(OperNum, OperPass, InvoiceCreditNotePrintType, CustomerNum, RelatedToInvoiceNum, RelatedToInvoiceDateTime, RelatedToRcpNum, FMNum, RelatedToURN)*



## 2.6.12. Command: 31h / 1 – Sell/Correction of article belonging to VAT class definition

**input:** <NamePLU[36]> <;> <OptionVATClass[1]> <;> <Price[1..10]> {<'\*'>  
<Quantity[1..10]>} {<'> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article with specified name, price, quantity, VAT class and/or discount/addition on the transaction.

### **Input data :**

|                |  |
|----------------|--|
| NamePLU        | (PLU Name) 36 symbols for article's name. 34 symbols are printed on paper.<br>Symbol 0x7C ' ' is new line separator.   |
| OptionVATClass | 1 character for VAT class: <ul style="list-style-type: none"><li>- 'A' – VAT Class 0</li><li>- 'Б' – VAT Class 1</li><li>- 'В' – VAT Class 2</li><li>- 'Г' – VAT Class 3</li><li>- 'Д' – VAT Class 4</li><li>- 'Е' – VAT Class 5</li><li>- 'Ж' – VAT Class 6</li><li>- 'З' – VAT Class 7</li><li>- '*' - Forbidden</li></ul> |
| Price          | Up to 10 symbols for article's price. Use minus sign '-' for correction  |
| '*'            | 1 symbol '*' indicating the presence of quantity field   |
| Quantity       | Up to 10 symbols for quantity  |
| ','            | 1 symbol ',' indicating the presence of discount/addition field  |
| DiscAddP       | (Discount/Addition %) Up to 7 symbols for percentage of discount/addition.<br>Use minus sign '-' for discount  |
| ':'            | 1 symbol ':' indicating the presence of value discount/addition field  |
| DiscAddV       | (Discount/Addition Value) Up to 8 symbols for value of discount/addition.<br>Use minus sign '-' for discount   |

### **Output data : n. a.**

#### **Notes:**

The quantity fields are not obligatory. If no value is stated for them the FD executed the command for a default quantity of 1.000

The discount/addition fields are not obligatory. The discount/addition must be in percents and is determined from the presence or absence of the '-' symbol.

**zfpdef:** SellPLUwithSpecifiedVAT(NamePLU, OptionVATClass, Price, Quantity, DiscAddP, DiscAddV)

### 2.6.13. Command: 31h / 1 – Sell/Correction of article belonging to department

**input:** <NamePLU[36]> <;> <reserved[' ']> <;> <Price[1..10]> {<'\*>  
<Quantity[1..10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>} {<'!'> <DepNum[1..2]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article belonging to department with specified name, price, quantity and/or discount/addition on the transaction. The VAT of article got from department to which article belongs.

#### **Input data :**

|          |  |
|----------|--|
| NamePLU  | (PLU Name) 36 symbols for article's name. 34 symbols are printed on paper. Symbol 0x7C '[' is new line separator.  |
| reserved | 1 symbol with value "space"  |
| Price    | Up to 10 symbols for article's price. Use minus sign '-' for correction  |
| '*'      | 1 symbol '*' indicating the presence of quantity field   |
| Quantity | Up to 10 symbols for quantity  |
| ','      | 1 symbol ',' indicating the presence of discount/addition field  |
| DiscAddP | (Discount/Addition %) Up to 7 symbols for percentage of discount/addition. Use minus sign '-' for discount   |
| ':'      | 1 symbol ':' indicating the presence of value discount/addition field  |
| DiscAddV | (Discount/Addition Value) Up to 8 symbols for value of discount/addition. Use minus sign '-' for discount  |
| '!'      | 1 symbol '!' indicating the presence of department   |
| DepNum   | DepNum + 80h (Department Number) 1 symbol for article department attachment, formed in the following manner; example: Dep01=81h, Dep02=82h ... Dep19=93h |

#### **Output data : n. a.**

##### **Notes:**

The quantity fields are not obligatory. If no value is stated for them the FD executed the command for a default quantity of 1.000

The discount/addition fields are not obligatory. The discount/addition must be in percents and is determined from the presence or absence of the '-' symbol.

**zfpdef:** SellPLUfromDep(NamePLU, Price, Quantity, DiscAddP, DiscAddV, DepNum)



## 2.6.14. Command: 31h / 1 – Sell/Correction of article with specified VAT belonging to department

**input:** <NamePLU[36]> <;> <OptionVATClass[1]> <;> <Price[1..10]> {<'\*'>  
<Quantity[1..10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>} {<'!'> <DepNum[1..2]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article with specified VAT. If department is present the relevant accumulations are performed in its registers.

### **Input data :**

|                |  |
|----------------|--|
| NamePLU        | (PLU Name) 36 symbols for article's name. 34 symbols are printed on paper. Symbol 0x7C '[' is new line separator.  |
| OptionVATClass | 1 character for VAT class: <ul style="list-style-type: none"><li>- 'A' – VAT Class 0</li><li>- 'B' – VAT Class 1</li><li>- 'B' – VAT Class 2</li><li>- 'Г' – VAT Class 3</li><li>- 'Д' – VAT Class 4</li><li>- 'E' – VAT Class 5</li><li>- 'Ж' – VAT Class 6</li><li>- '3' – VAT Class 7</li><li>- '*' - Forbidden</li></ul> |
| Price          | Up to 10 symbols for article's price. Use minus sign '-' for correction  |
| '*'            | 1 symbol '*' indicating the presence of quantity field   |
| Quantity       | Up to 10 symbols for quantity  |
| ','            | 1 symbol ',' indicating the presence of discount/addition field  |
| DiscAddP       | (Discount/Addition %) Up to 7 symbols for percentage of discount/addition.   |
|                | Use minus sign '-' for discount  |
| ':'            | 1 symbol ':' indicating the presence of value discount/addition field  |
| DiscAddV       | (Discount/Addition Value) Up to 8 symbols for value of discount/addition.  |
|                | Use minus sign '-' for discount  |
| '!'            | 1 symbol '!' indicating the presence of department   |
| DepNum         | DepNum + 80h (Department Number) 1 symbol for article department attachment, formed in the following manner; <i>example: Dep01 = 81h, Dep02 = 82h ... Dep19 = 93h</i>  |

### **Output data : n. a.**

#### **Notes:**

The quantity fields are not obligatory. If no value is stated for them the FD executed the command for a default quantity of 1.000

The discount/addition fields are not obligatory. The discount/addition must be in percents and is determined from the presence or absence of the '-' symbol.

**zfpdef:** SellPLUwithSpecifiedVATfromDep(NamePLU, OptionVATClass, Price, Quantity, DiscAddP, DiscAddV, DepNum)

### 2.6.15. Command: 32h / 2 – Sell/Correction of article from FD database

**input:** <OptionSign[1]> <PLUNum[5]> {<'\$'> <Price[1..8]>} {<'\*'> <Quantity[1..10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>}

**output:** ACK

**FPR operation:** Register the sell or correction with specified quantity of article from the internal FD database. The FD will perform a correction operation only if the same quantity of the article has already been sold.

#### **Input data :**

|                   |  |
|-------------------|--|
| <i>OptionSign</i> | (Sale/Correction) 1 symbol with optional value:<br>- '+' – Sale<br>- '-' - Correction                          |
| <i>PLUNum</i>     | (PLU Number) 5 symbols for PLU number of FD's database in format #####   |
| <i>'\$'</i>       | 1 symbol '\$' indicating the presence of price   |
| <i>Price</i>      | Up to 10 symbols for sale price  |
| <i>'*'</i>        | 1 symbol '*' indicating the presence of quantity field   |
| <i>Quantity</i>   | Up to 10 symbols for article's quantity sold   |
| <i>','</i>        | 1 symbol ',' indicating the presence of discount/addition field  |
| <i>DiscAddP</i>   | (Discount/Addition %) Up to 7 for percentage of discount/addition. Use minus sign '-' for discount             |
| <i>':'</i>        | 1 symbol ':' indicating the presence of discount/addition field  |
| <i>DiscAddV</i>   | (Discount/Addition Value) Up to 8 symbols for percentage of discount/addition. Use minus sign '-' for discount |

#### **Output data : n. a.**

**zfpdef:** SellPLUFromFD\_DB(*OptionSign*, *PLUNum*, *Price*, *Quantity*, *DiscAddP*, *DiscAddV*)

### 2.6.16. Command: 33h / 3 – Subtotal

**input:** <OptionPrinting[1]> <;> <OptionDisplay[1]> {<':'> <DiscAddV[1..8]>} {<','> <DiscAddP[1..7]>}

**output:** <SubtotalValue[1..10]>

**FPR operation:** Calculate the subtotal amount with printing and display visualization options. Provide information about values of the calculated amounts. If a percent or value discount/addition has been specified the subtotal and the discount/addition value will be printed regardless the parameter for printing.

#### **Input data :**

|                       |  |
|-----------------------|--|
| <i>OptionPrinting</i> | 1 symbol with value:<br>- '1' – Yes<br>- '0' – No  |
| <i>OptionDisplay</i>  | 1 symbol with value:<br>- '1' – Yes<br>- '0' – No  |
| <i>':'</i>            | 1 symbol ':' indicating the presence of value discount/addition field  |
| <i>DiscAddV</i>       | (Discount/Addition Value) Up to 8 symbols for the value of the discount/addition. Use minus sign '-' for discount        |
| <i>','</i>            | 1 symbol ',' indicating the presence of percent discount/addition field  |
| <i>DiscAddP</i>       | (Discount/Addition %) Up to 7 symbols for the percentage value of the discount/addition. Use minus sign '-' for discount |

#### **Output data:**

|                      |   |
|----------------------|---|
| <i>SubtotalValue</i> | Up to 10 symbols for the value of the subtotal amount |
|----------------------|---|

#### **Notes:**

When the discount/addition is a percentage the amount is distributed proportionally over the turnover items and is automatically transferred to the turnovers of the corresponding VAT groups.

A value discount/addition may be specified only if all sales are of articles (items) belonging to one and the same VAT group.

**zfpdef:** Subtotal(*OptionPrinting*, *OptionDisplay*, *DiscAddP*, *DiscAddV*)

## 2.6.17. Command: 34h / 4 – Sell/Correction of article with department definition belonging to VAT class

**input:** <NamePLU[36]> <;> <DepNum[1..2]> <;> <Price[1..10]> {<'\*>  
<Quantity[1..10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>} {<'!'>  
<OptionVATClass[1]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article with specified department. If VAT is present the relevant accumulations are performed in its registers.

### **Input data :**

|                |   |
|----------------|---|
| NamePLU        | (PLU Name) 36 symbols for name of sale. 34 symbols are printed on paper. Symbol 0x7C ' ' is new line separator.   |
| DepNum         | DepNum + 80h, (Department Number) 1 symbol for article department attachment, formed in the following manner: DepNum[HEX] + 80h<br>example: Dep01 = 81h, Dep02 = 82h ... Dep19 = 93h  |
| Price          | Up to 10 symbols for article's price. Use minus sign '-' for correction   |
| '*             | 1 symbol '*' indicating the presence of quantity field  |
| Quantity       | Up to 10 symbols for article's quantity sold  |
| ','            | 1 symbol ',' indicating the presence of discount/addition field   |
| DiscAddP       | (Discount/Addition %) Up to 7 for percentage of discount/addition. Use minus sign '-' for discount  |
| ':'            | 1 symbol ':' indicating the presence of discount/addition field   |
| DiscAddV       | (Discount/Addition Value) Up to 8 symbols for percentage of discount/addition. Use minus sign '-' for discount  |
| '!             | 1 symbol with value '!'   |
| OptionVATClass | 1 character for VAT class:<br>- 'A' – VAT Class 0<br>- 'B' – VAT Class 1<br>- 'B' – VAT Class 2<br>- 'Г' – VAT Class 3<br>- 'Д' – VAT Class 4<br>- 'E' – VAT Class 5<br>- 'Ж' – VAT Class 6<br>- '3' – VAT Class 7<br>- '*' - Forbidden |

### **Output data: n. a.**

#### **Notes:**

Sale/correction will be collected in VAT group on department, value and qty will be gain (removed) in this department.

For correction use '-' before value price.

Field for quantity is optional. If there no set qty default value is 1.000

Fields for Disc/add are optional. Disc/add can be only in percents, for discount use '-' before value. Cannot make correction with Disc/add.

**zfpdef:** SellPLUwithSpecifiedVATfromDep\_(NameSale, DepNum, Price, Quantity, DiscAddP, DiscAddV, OptionVATClass)

## 2.6.18. Command: 34h / 4 – Sell/Correction of article with specified department

**input:** <NamePLU[36]> <;> <DepNum[1..2]> <;> <Price[1..10]> {<'\*>  
<Quantity[1..10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>}

**output:** ACK

**FPR operation:** Registers the sell (for correction use minus sign in the price field) of article with specified department, name, price, quantity and/or discount/addition on the transaction.

### **Input data :**

|                 |   |
|-----------------|---|
| <i>NamePLU</i>  | (PLU Name) 36 symbols for name of sale. 34 symbols are printed on paper. Symbol 0x7C ' ' is new line separator.   |
| <i>DepNum</i>   | <i>DepNum</i> + 80h, (Department Number) 1 symbol for article department attachment, formed in the following manner: <i>DepNum</i> [HEX] + 80h<br>example: Dep01 = 81h, Dep02 = 82h ... Dep19 = 93h |
| <i>Price</i>    | Up to 10 symbols for article's price. Use minus sign '-' for correction   |
| '*'             | 1 symbol '*' indicating the presence of quantity field  |
| <i>Quantity</i> | Up to 10 symbols for article's quantity sold  |
| ','             | 1 symbol ',' indicating the presence of discount/addition field   |
| <i>DiscAddP</i> | (Discount/Addition %) Up to 7 for percentage of discount/addition. Use minus sign '-' for discount  |
| ':'             | 1 symbol ':' indicating the presence of discount/addition field   |
| <i>DiscAddV</i> | (Discount/Addition Value) Up to 8 symbols for percentage of discount/addition. Use minus sign '-' for discount  |

### **Output data: n. a.**

#### **Notes:**

Sale/correction will be collected in VAT group on department, value and qty will be gain (removed) in this department.

For correction use '-' before value price.

Fields for qty are optional. If there no set qty default value is 1.000

Fields for Disc/add are optional. Disc/add can be only in percents, for discount use '-' before value. Cannot make correction with Disc/add.

**zfpdef:** SellPLUfromDep\_(NameSale, DepNum, Price, Quantity, DiscAddP, DiscAddV)

## 2.6.19. Command: 35h / 5 – Payment

**input:** <PaymentType[1..2]> <;> <OptionChange[1]> <;> <Amount[1..10]> { <;>  
<OptionChangeType[1]> }

**output:** ACK

**FPR operation:** Register the payment in the receipt with specified type of payment with amount received.

### **Input data :**

|                         |   |
|-------------------------|---|
| <i>PaymentType</i>      | (Payment Types)1 symbol for payment type: <ul style="list-style-type: none"><li>- '0' – Payment 0</li><li>- '1' – Payment 1</li><li>- '2' – Payment 2</li><li>- '3' – Payment 3</li><li>- '4' – Payment 4</li><li>- '5' – Payment 5</li><li>- '6' – Payment 6</li><li>- '7' – Payment 7</li><li>- '8' – Payment 8</li><li>- '9' – Payment 9</li><li>- '10' – Payment 10</li><li>- '11' – Payment 11</li></ul> |
| <i>OptionChange</i>     | (Change) Default value is 0, 1 symbol with value: <ul style="list-style-type: none"><li>- '0' – With Change</li><li>- '1' – Without Change</li></ul>  |
| <i>Amount</i><br>'*'    | Up to 10 characters for received amount<br>1 symbol with value '*'  |
| <i>OptionChangeType</i> | 1 symbols with value: <ul style="list-style-type: none"><li>- '0' – Change In Cash</li><li>- '1' – Same As The payment</li><li>- '2' – Change In Currency</li></ul>   |

### **Output data: n. a.**

#### **Notes:**

By executing this command the FD enters the payment mode. No further sales and/or corrections are allowed.

If the amount received is equal to or greater than the grand total amount (the amount due) the FD quits the procedure and calculates the change in the specified type of payment except in the cases when OptionChange is not 1 – in such cases the operator is liable for the stated amount.

The receipt can be finalized only when the last payment transfer is sufficient to cover the whole amount due (the grand total amount), i.e. the payment procedure has been finalized.

**zfpdef:** *Payment(PaymentType, OptionChange, Amount, OptionChangeType)*

## 2.6.20. Command: 35h / 5 – Pay exact sum

**input:** <PaymentType[1..2]> <;> <Option['0']> <;> <Amount[']>

**output:** ACK

**FPR operation:** Register the payment in the receipt with specified type of payment and exact amount received.

**Input data :**

*PaymentType* (Payment Types) 1 symbol for payment type:

- '0' – Payment 0
- '1' – Payment 1
- '2' – Payment 2
- '3' – Payment 3
- '4' – Payment 4
- '5' – Payment 5
- '6' – Payment 6
- '7' – Payment 7
- '8' – Payment 8
- '9' – Payment 9
- '10' – Payment 10
- '11' – Payment 11

*Option* 1 symbol with value 0

*Amount* 1 symbol ' ' , quotation mark, for pay with exact sum

**Output data:** n.a.

**zfpdef:** *PayExactSum(PaymentType)*

## 2.6.21. Command: 36h / 6 – Automatic receipt closure

**input:** n. a.

**output:** ACK

**FPR operation:** Paying the exact amount in cash and close the fiscal receipt.

**Input data :** n. a.

**Output data :** n. a.

**zfpdef:** *CashPayCloseReceipt()*

## 2.6.22. Command: 37h / 7 – Free text printing

**input:** <Text[TextLength-2]>

**output:** ACK

**FPR operation:** Print a free text. The command can be executed only if receipt is opened (Fiscal receipt, Invoice receipt, Storno receipt, Credit Note or Non-fical receipt). In the beginning and in the end of line symbol '#' is printed.

**Input data :**

*Text* *TextLength-2* symbols

**Output data:** n. a.

**zfpdef:** *PrintText(Text)*

## 2.6.23. Command: 38h / 8 – Close Fiscal receipt

**input:** n. a.

**output:** ACK

**FPR operation:** Close the fiscal receipt (Fiscal receipt, Invoice receipt, Storno receipt, Credit Note or Non-fical receipt). When the payment is finished.

**Input data :** n. a.

**Output data :** n. a.

**zfpdef:** *CloseReceipt()*

#### 2.6.24. Command: 39h / 9 – Cancel fiscal receipt

**input:** n. a.

**output:** ACK

**FPR operation:** Available only if receipt is not closed. Void all sales in the receipt and close the fiscal receipt (Fiscal receipt, Invoice receipt, Storno receipt or Credit Note). If payment is started, then finish payment and close the receipt.

**Input data :** n. a.

**Output data :** n. a.

**zfpdef:** *CancelReceipt()*

#### 2.6.25. Command: 3Ah / : – Print a copy of the last document

**input:** n. a.

**output:** ACK

**FPR operation:** Print a copy of the last receipt issued. When FD parameter for duplicates is enabled.

**Input data :** n. a.

**Output data :** n. a.

**zfpdef:** *PrintLastReceiptDuplicate()*

#### 2.6.26. Command: 3Bh / ; – Non-fiscal RA and PO amounts

**input:** <OperNum[1..2]> <;> <OperPass[6]> <;> <reserved['0']> <;> <Amount[1..10]> {<'\$'> <PrintAvailability[1]> } {<;> <Text[TextLength-2]>}

**output:** ACK

**FPR operation:** Registers cash received on account or paid out.

**Input data :**

|                          |  |
|--------------------------|--|
| <i>OperNum</i>           | (Operator Number) Symbols from 1 to 20 corresponding to the operator's number        |
| <i>OperPass</i>          | (Operator Password) 6 symbols for operator's password                                |
| <i>reserved</i>          | 1 symbol reserved with value '0'   |
| <i>Amount</i>            | Up to 10 symbols for the amount lodged. Use minus sign for withdrawn                 |
| <i>'\$'</i>              | 1 symbol with value '\$'   |
| <i>PrintAvailability</i> | 1 symbol with value:<br>- '0' – No<br>- '1' – Yes                                    |
| <i>Text</i>              | TextLength-2 symbols. In the beginning and in the end of line symbol '#' is printed. |

**Output data:** n. a.

**zfpdef:** *ReceivedOnAccount\_PaidOut(OperNum, OperPass, Amount, PrintAvailability, Text)*



## 2.6.27. Command: 3Eh / > – Discount/ Addition

**input:** <Type[1]> <;> <OptionSubtotal[1]> {<':'> <DiscAddV[1..8]>} {<','> <DiscAddP[1..7]>}

**output:** ACK

**FPR operation:** Percent or value discount/addition over sum of transaction or over subtotal sum specified by field “Type”.

**Input data :**

|                |  |
|----------------|--|
| Type           | 1 symbol with value<br>- '2' - Defined from the device<br>- '1' - Over subtotal<br>- '0' - Over transaction sum          |
| OptionSubtotal | (Display Subtotal) 1 symbol with value<br>- '1' - Yes<br>- '0' - No  |
| ':'            | 1 symbol ':' indicating the presence of value discount/addition field  |
| DiscAddV       | (Discount/Addition Value) Up to 8 symbols for the value of the discount/addition. Use minus sign '-' for discount        |
| ','            | 1 symbol ',' indicating the presence of percent discount/addition field  |
| DiscAddP       | (Discount/Addition %) Up to 7 symbols for the percentage value of the discount/addition. Use minus sign '-' for discount |

**Output data: n.a.**

**zfpdef:** PrintDiscountOrAddition(*Type, OptionSubtotal, DiscAddV, DiscAddP*)

## 2.6.28. Command: 3Dh / = – Sell/Correction of article with fractional quantity belonging to VAT class definition

**input:** <NamePLU[36]> <;> <OptionVATClass[1]> <;> <Price[1..10]> {<'\*'> <Quantity[10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article with specified name, price, fractional quantity, VAT class and/or discount/addition on the transaction.

**Input data :**

|                |   |
|----------------|---|
| NamePLU        | (PLU Name) 36 symbols for article's name. 34 symbols are printed on paper. Symbol 0x7C ' ' is new line separator.   |
| OptionVATClass | 1 character for VAT class:<br>- 'A' – VAT Class 0<br>- 'B' – VAT Class 1<br>- 'B' – VAT Class 2<br>- 'Г' – VAT Class 3<br>- 'Д' – VAT Class 4<br>- 'E' – VAT Class 5<br>- 'Ж' – VAT Class 6<br>- '3' – VAT Class 7<br>- '*' – Forbidden |
| Price          | Up to 10 symbols for article's price. Use minus sign '-' for correction   |
| '*'            | 1 symbol '*' indicating the presence of quantity field  |
| Quantity       | From 3 to 10 symbols for quantity in format fractional format, e.g. 1/3   |
| ','            | 1 symbol ',' indicating the presence of discount/addition field   |
| DiscAddP       | (Discount/Addition %) 1 to 7 symbols for percentage of discount/addition. Use minus sign '-' for discount   |
| ':'            | 1 symbol ':' indicating the presence of value discount/addition field   |
| DiscAddV       | (Discount/Addition Value) 1 to 8 symbols for value of discount/addition. Use minus sign '-' for discount  |

**Output data : n. a.**



**Notes:**

If the price field is preceded by a '-' the command is executed by the FD as a correction/void (only if the amount of the corresponding VAT group of the receipt is sufficient).

The quantity fields are not obligatory. If no value is stated for them the FD executed the command for a default quantity of 1.000

The discount/addition fields are not obligatory. The discount/addition must be in percents and is determined from the presence or absence of the '-' symbol.

**zfpdef:** SellFractQtyPLUwithSpecifiedVAT(NamePLU, OptionVATClass, Price, Quantity, DiscAddP, DiscAddV)

## 2.6.29. Command: 3Dh / = – Sell/Correction of article with fractional quantity belonging to department

**input:** <NamePLU[36]> <;> <reserved[' ']> <;> <Price[1..10]> {<'\*> <Quantity[10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>} {<'!'> <DepNum[1..2]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article belonging to department with specified name, price, fractional quantity and/or discount/addition on the transaction. The VAT of article got from department to which article belongs.

### Input data :

|          |   |
|----------|---|
| NamePLU  | (PLU Name) 36 symbols for article's name. 34 symbols are printed on paper. Symbol 0x7C ' ' is new line separator.   |
| reserved | 1 symbol with value "space"   |
| Price    | Up to 10 symbols for article's price. Use minus sign '-' for correction   |
| '*'      | 1 symbol '*' indicating the presence of quantity field  |
| Quantity | From 3 to 10 symbols for quantity in format fractional format, e.g. 1/3   |
| ','      | 1 symbol ',' indicating the presence of discount/addition field   |
| DiscAddP | (Discount/Addition %) 1 to 7 symbols for percentage of discount/addition. Use minus sign '-' for discount   |
| ':'      | 1 symbol ':' indicating the presence of value discount/addition field   |
| DiscAddV | (Discount/Addition Value) 1 to 8 symbols for value of discount/addition. Use minus sign '-' for discount  |
| '!'      | 1 symbol '!' indicating the presence of department  |
| DepNum   | DepNum + 80h (Department Number) 1 symbol for article department attachment, formed in the following manner; <i>example: Dep01 = 81h, Dep02 = 82h ... Dep19 = 93h</i> |

### Output data : n. a.

#### Notes:

If the price field is preceded by a '-' the command is executed by the FD as a correction/void (only if the amount of the corresponding VAT group of the receipt is sufficient).

The quantity fields are not obligatory. If no value is stated for them the FD executed the command for a default quantity of 1.000

The discount/addition fields are not obligatory. The discount/addition must be in percents and is determined from the presence or absence of the '-' symbol.

**zfpdef:** SellFractQtyPLUfromDep(NamePLU, Price, Quantity, DiscAddP, DiscAddV, DepNum)

## 2.6.30. Command: 3Dh / = – Sell/Correction of article with fractional quantity with specified VAT belonging to department

**input:** <NamePLU[36]> <;> <OptionVATClass[1]> <;> <Price[1..10]> {<'\*'>  
<Quantity[10]>} {<','> <DiscAddP[1..7]>} {<':'> <DiscAddV[1..8]>} {<'!'> <DepNum[1..2]>}

**output:** ACK

**FPR operation:** Register the sell (for correction use minus sign in the price field) of article with specified VAT. If department is present the relevant accumulations are performed in its registers.

### **Input data :**

|                |  |
|----------------|--|
| NamePLU        | (PLU Name) 36 symbols for article's name. 34 symbols are printed on paper. Symbol 0x7C '[' is new line separator.  |
| OptionVATClass | 1 character for VAT class: <ul style="list-style-type: none"><li>- 'A' – VAT Class 0</li><li>- 'B' – VAT Class 1</li><li>- 'B' – VAT Class 2</li><li>- 'Г' – VAT Class 3</li><li>- 'Д' – VAT Class 4</li><li>- 'E' – VAT Class 5</li><li>- 'Ж' – VAT Class 6</li><li>- '3' – VAT Class 7</li><li>- '*' - Forbidden</li></ul> |
| Price          | Up to 10 symbols for article's price. Use minus sign '-' for correction  |
| '*'            | 1 symbol '*' indicating the presence of quantity field   |
| Quantity       | From 3 to 10 symbols for quantity in format fractional format, e.g. 1/3  |
| ','            | 1 symbol ',' indicating the presence of discount/addition field  |
| DiscAddP       | (Discount/Addition %) Up to 7 symbols for percentage of discount/addition.   |
|                | Use minus sign '-' for discount  |
| ':'            | 1 symbol ':' indicating the presence of value discount/addition field  |
| DiscAddV       | (Discount/Addition Value) Up to 8 symbols for value of discount/addition.  |
|                | Use minus sign '-' for discount  |
| '!'            | 1 symbol '!' indicating the presence of department   |
| DepNum         | DepNum + 80h (Department Number) 1 symbol for article department attachment, formed in the following manner; <i>example: Dep01 = 81h, Dep02 = 82h ... Dep19 = 93h</i>  |

### **Output data : n. a.**

#### **Notes:**

If the price field is preceded by a '-' the command is executed by the FD as a correction/void (only if the amount of the corresponding VAT group of the receipt is sufficient).

The quantity fields are not obligatory. If no value is stated for them the FD executed the command for a default quantity of 1.000

The discount/addition fields are not obligatory. The discount/addition must be in percents and is determined from the presence or absence of the '-' symbol.

**zfpdef:** SellFractQtyPLUwithSpecifiedVATfromDep(NamePLU, OptionVATClass, Price, Quantity, DiscAddP, DiscAddV, DepNum)

## 2.7. COMMANDS FOR READING THE DATA IN FD'S REGISTERS

This set of commands provides information about the status of FD's registers without causing a device activity, i.e. the information is obtained through the communication interface without printing or display visualization.

### 2.7.1. Command: 6Dh / m – Read daily sale and storno amounts by VAT groups

**input:** n. a.

**output:** <SaleAmountVATGr0[1..13]> <;> <SaleAmountVATGr1[1..13]> <;>  
<SaleAmountVATGr2[1..13]> <;> <SaleAmountVATGr3[1..13]> <;> <SaleAmountVATGr4[1..13]>  
<;> <SaleAmountVATGr5[1..13]> <;> <SaleAmountVATGr6[1..13]> <;>  
<SaleAmountVATGr7[1..13]> <;> <SumAllVATGr[1..13]> <;>  
<StornoAmountVATGr0[1..13]> <;> <StornoAmountVATGr1[1..13]> <;>  
<StornoAmountVATGr2[1..13]> <;> <StornoAmountVATGr3[1..13]> <;>  
<StornoAmountVATGr4[1..13]> <;> <StornoAmountVATGr5[1..13]> <;>  
<StornoAmountVATGr6[1..13]> <;> <StornoAmountVATGr7[1..13]> <;>  
<StornoAllVATGr[1..13]>

**FPR operation:** Provides information about the accumulated sale and storno amounts by VAT group.

**Input data :** n. a.

**Output data :**

|                           |  |
|---------------------------|--|
| <i>SaleAmountVATGr0</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group A  |
| <i>SaleAmountVATGr1</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group Б  |
| <i>SaleAmountVATGr2</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group В  |
| <i>SaleAmountVATGr3</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group Г  |
| <i>SaleAmountVATGr4</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group Д  |
| <i>SaleAmountVATGr5</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group Е  |
| <i>SaleAmountVATGr6</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group Ж  |
| <i>SaleAmountVATGr7</i>   | Up to 13 symbols for the amount accumulated from sales by VAT group З  |
| <i>SumAllVATGr</i>        | Up to 13 symbols for sum of all VAT groups                             |
| <i>StornoAmountVATGr0</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group A |
| <i>StornoAmountVATGr1</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group Б |
| <i>StornoAmountVATGr2</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group В |
| <i>StornoAmountVATGr3</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group Г |
| <i>StornoAmountVATGr4</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group Д |
| <i>StornoAmountVATGr5</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group Е |
| <i>StornoAmountVATGr6</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group Ж |
| <i>StornoAmountVATGr7</i> | Up to 13 symbols for the amount accumulated from Storno by VAT group З |
| <i>StornoAllVATGr</i>     | Up to 13 symbols for the amount accumulated from Storno by all groups  |

**zfpdef:** ReadDailySaleAndStornoAmountsByVAT()

### 2.7.2. Command: 6Eh / n – Read registers, Option ‘0’ (on hand)

**input:** <'0'>

**output:** <'0'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <AmountPayment5[1..13]> <;> <AmountPayment6[1..13]> <;>  
<AmountPayment7[1..13]> <;> <AmountPayment8[1..13]> <;> <AmountPayment9[1..13]>  
<;> <AmountPayment10[1..13]> <;> <AmountPayment11[1..13]>

**FPR operation:** Provides information about the amounts on hand by type of payment.

**Input data :**

'0' 1 symbol obligatory '0'

**Output data:**

'0' 1 symbol obligatory '0'  
*AmountPayment0* Up to 13 symbols for the accumulated amount by payment type 0  
*AmountPayment1* Up to 13 symbols for the accumulated amount by payment type 1  
*AmountPayment2* Up to 13 symbols for the accumulated amount by payment type 2  
*AmountPayment3* Up to 13 symbols for the accumulated amount by payment type 3  
*AmountPayment4* Up to 13 symbols for the accumulated amount by payment type 4  
*AmountPayment5* Up to 13 symbols for the accumulated amount by payment type 5  
*AmountPayment6* Up to 13 symbols for the accumulated amount by payment type 6  
*AmountPayment7* Up to 13 symbols for the accumulated amount by payment type 7  
*AmountPayment8* Up to 13 symbols for the accumulated amount by payment type 8  
*AmountPayment9* Up to 13 symbols for the accumulated amount by payment type 9  
*AmountPayment10* Up to 13 symbols for the accumulated amount by payment type 10  
*AmountPayment11* Up to 13 symbols for the accumulated amount by payment type 11

[zfpdef: ReadDailyAvailableAmounts\(\)](#)

### 2.7.3. Command: 6Eh / n – Read registers, Option ‘0’, KL (on hand)

**input:** <'0'>

**output:** <'0'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>

**FPR operation:** Provides information about the amounts on hand by type of payment. Command works for KL version 2 devices.

**Input data :**

'0' 1 symbol obligatory '0'

**Output data:**

'0' 1 symbol obligatory '0'  
*AmountPayment0* Up to 13 symbols for the accumulated amount by payment type 0  
*AmountPayment1* Up to 13 symbols for the accumulated amount by payment type 1  
*AmountPayment2* Up to 13 symbols for the accumulated amount by payment type 2  
*AmountPayment3* Up to 13 symbols for the accumulated amount by payment type 3  
*AmountPayment4* Up to 13 symbols for the accumulated amount by payment type 4

[zfpdef: ReadDailyAvailableAmounts\\_Old\(\)](#)

## 2.7.4. Command: 6Eh / n – Read registers, Option ‘1’ (general)

**input:** <'1'>

**output:** <'1'> <;> <CustomersNum[1..5]> <;> <DiscountsNum[1..5]> <;>  
<DiscountsAmount[1..13]> <;> <AdditionsNum[1..5]> <;> <AdditionsAmount[1..13]> <;>  
<CorrectionsNum[1..5]> <;> <CorrectionsAmount[1..13]>

**FPR operation:** Provides information about the number of customers (number of fiscal receipt issued), number of discounts, additions and corrections made and the accumulated amounts.

### **Input data :**

'1' 1 symbol with value '1'

### **Output data:**

'1' 1 symbol with value '1'  
CustomersNum Up to 5 symbols for number of customers  
DiscountsNum Up to 5 symbols for number of discounts  
DiscountsAmount Up to 13 symbols for accumulated amount of discounts  
AdditionsNum Up to 5 symbols for number of additions  
AdditionsAmount Up to 13 symbols for accumulated amount of additions  
CorrectionsNum Up to 5 symbols for number of corrections  
CorrectionsAmount Up to 13 symbols for accumulated amount of corrections

[\*\*zfpdef:\*\*ReadGeneralDailyRegisters\(\)](#)

## 2.7.5. Command: 6Eh / n – Read registers, Option ‘2’ (RA)

**input:** <'2'>

**output:** <'2'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <AmountPayment5[1..13]> <;> <AmountPayment6[1..13]> <;>  
<AmountPayment7[1..13]> <;> <AmountPayment8[1..13]> <;> <AmountPayment9[1..13]>  
<;> <AmountPayment10[1..13]> <;> <AmountPayment11[1..13]> <;> <RANum[1..5]> <;>  
<SumAllPayment[1..13]>

**FPR operation:** Provides information about the RA amounts by type of payment and the total number of operations.

### **Input data :**

'2' 1 symbol obligatory '2'

### **Output data:**

'2' 1 symbol obligatory '2'  
AmountPayment0 Up to 13 symbols for the accumulated amount by payment type 0  
AmountPayment1 Up to 13 symbols for the accumulated amount by payment type 1  
AmountPayment2 Up to 13 symbols for the accumulated amount by payment type 2  
AmountPayment3 Up to 13 symbols for the accumulated amount by payment type 3  
AmountPayment4 Up to 13 symbols for the accumulated amount by payment type 4  
AmountPayment5 Up to 13 symbols for the accumulated amount by payment type 5  
AmountPayment6 Up to 13 symbols for the accumulated amount by payment type 6  
AmountPayment7 Up to 13 symbols for the accumulated amount by payment type 7  
AmountPayment8 Up to 13 symbols for the accumulated amount by payment type 8  
AmountPayment9 Up to 13 symbols for the accumulated amount by payment type 9  
AmountPayment10 Up to 13 symbols for the accumulated amount by payment type 10  
AmountPayment11 Up to 13 symbols for the accumulated amount by payment type 11  
RANum Up to 5 symbols for the total number of operations  
SumAllPayment Up to 13 symbols to sum all payments

[\*\*zfpdef:\*\* ReadDailyRA\(\)](#)



### 2.7.6. Command: 6Eh / n – Read registers, Option ‘2’, KL (RA)

**input:** <'2'>

**output:** <'2'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <RANum[1..5]> <;> <SumAllPayment[1..13]>

**FPR operation:** Provides information about the RA amounts by type of payment and the total number of operations. Command works for KL version 2 devices.

**Input data :**

'2' 1 symbol obligatory '2'

**Output data:**

'2' 1 symbol obligatory '2'  
AmountPayment0 Up to 13 symbols for the accumulated amount by payment type 0  
AmountPayment1 Up to 13 symbols for the accumulated amount by payment type 1  
AmountPayment2 Up to 13 symbols for the accumulated amount by payment type 2  
AmountPayment3 Up to 13 symbols for the accumulated amount by payment type 3  
AmountPayment4 Up to 13 symbols for the accumulated amount by payment type 4  
RANum Up to 5 symbols for the total number of operations  
SumAllPayment Up to 13 symbols to sum all payments

[zfpdef: ReadDailyRA\\_Old\(\)](#)

### 2.7.7. Command: 6Eh / n – Read registers, Option ‘3’ (PO)

**input:** <'3'>

**output:** <'3'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <AmountPayment5[1..13]> <;> <AmountPayment6[1..13]> <;>  
<AmountPayment7[1..13]> <;> <AmountPayment8[1..13]> <;> <AmountPayment9[1..13]>  
<;> <AmountPayment10[1..13]> <;> <AmountPayment11[1..13]> <;> <PONum[1..5]> <;>  
<SumAllPayment[1..13]>

**FPR operation:** Provides information about the PO amounts by type of payment and the total number of operations.

**Input data :**

'3' 1 symbol obligatory '3'

**Output data:**

'3' 1 symbol obligatory '3'  
AmountPayment0 Up to 13 symbols for the accumulated amount by payment type 0  
AmountPayment1 Up to 13 symbols for the accumulated amount by payment type 1  
AmountPayment2 Up to 13 symbols for the accumulated amount by payment type 2  
AmountPayment3 Up to 13 symbols for the accumulated amount by payment type 3  
AmountPayment4 Up to 13 symbols for the accumulated amount by payment type 4  
AmountPayment5 Up to 13 symbols for the accumulated amount by payment type 5  
AmountPayment6 Up to 13 symbols for the accumulated amount by payment type 6  
AmountPayment7 Up to 13 symbols for the accumulated amount by payment type 7  
AmountPayment8 Up to 13 symbols for the accumulated amount by payment type 8  
AmountPayment9 Up to 13 symbols for the accumulated amount by payment type 9  
AmountPayment10 Up to 13 symbols for the accumulated amount by payment type 10  
AmountPayment11 Up to 13 symbols for the accumulated amount by payment type 11  
PONum Up to 5 symbols for the total number of operations  
SumAllPayment Up to 13 symbols to sum all payments

[zfpdef: ReadDailyPO\(\)](#)

### 2.7.8. Command: 6Eh / n – Read registers, Option ‘3’, KL (PO)

**input:** <'3'>

**output:** <'3'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <PONum[1..5]> <;> <SumAllPayment[1..13]>

**FPR operation:** Provides information about the PO amounts by type of payment and the total number of operations. Command works for KL version 2 devices.

**Input data :**

'3' 1 symbol obligatory '3'

**Output data:**

'3' 1 symbol obligatory '3'

AmountPayment0 Up to 13 symbols for the accumulated amount by payment type 0

AmountPayment1 Up to 13 symbols for the accumulated amount by payment type 1

AmountPayment2 Up to 13 symbols for the accumulated amount by payment type 2

AmountPayment3 Up to 13 symbols for the accumulated amount by payment type 3

AmountPayment4 Up to 13 symbols for the accumulated amount by payment type 4

PONum Up to 5 symbols for the total number of operations

SumAllPayment Up to 13 symbols to sum all payments

[zfpdef: ReadDailyPO\\_Old\(\)](#)

### 2.7.9. Command: 6Eh / n – Read registers, Option ‘4’ (received)

**input:** <'4'>

**output:** <'4'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <AmountPayment5[1..13]> <;> <AmountPayment6[1..13]> <;>  
<AmountPayment7[1..13]> <;> <AmountPayment8[1..13]> <;> <AmountPayment9[1..13]>  
<;> <AmountPayment10[1..13]> <;> <AmountPayment11[1..13]>

**FPR operation:** Provides information about the amounts received from sales by type of payment.

**Input data :**

'4' 1 symbol obligatory '4'

**Output data:**

'4' 1 symbol obligatory '4'

AmountPayment0 Up to 13 symbols for the accumulated amount by payment type 0

AmountPayment1 Up to 13 symbols for the accumulated amount by payment type 1

AmountPayment2 Up to 13 symbols for the accumulated amount by payment type 2

AmountPayment3 Up to 13 symbols for the accumulated amount by payment type 3

AmountPayment4 Up to 13 symbols for the accumulated amount by payment type 4

AmountPayment5 Up to 13 symbols for the accumulated amount by payment type 5

AmountPayment6 Up to 13 symbols for the accumulated amount by payment type 6

AmountPayment7 Up to 13 symbols for the accumulated amount by payment type 7

AmountPayment8 Up to 13 symbols for the accumulated amount by payment type 8

AmountPayment9 Up to 13 symbols for the accumulated amount by payment type 9

AmountPayment10 Up to 13 symbols for the accumulated amount by payment type 10

AmountPayment11 Up to 13 symbols for the accumulated amount by payment type 11

[zfpdef: ReadDailyReceivedSalesAmounts\(\)](#)

## 2.7.10. Command: 6Eh / n – Read registers, Option ‘4’, KL (received)

**input:** <'4'>

**output:** <'4'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>

**FPR operation:** Provides information about the amounts received from sales by type of payment. Command works for KL version 2 devices.

**Input data :**

'4' 1 symbol obligatory '4'

**Output data:**

'4' 1 symbol obligatory '4'

*AmountPayment0* Up to 13 symbols for the accumulated amount by payment type 0

*AmountPayment1* Up to 13 symbols for the accumulated amount by payment type 1

*AmountPayment2* Up to 13 symbols for the accumulated amount by payment type 2

*AmountPayment3* Up to 13 symbols for the accumulated amount by payment type 3

*AmountPayment4* Up to 13 symbols for the accumulated amount by payment type 4

**zfpdef:** [ReadDailyReceivedSalesAmounts\\_Old\(\)](#)

## 2.7.11. Command: 6Eh / n – Read registers, Option ‘5’ (counters)

**input:** <'5'>

**output:** <'5'> <;> <LastReportNumFromReset[1..5]> <;> <LastFMBlockNum[1..5]>  
<;> <EJNum[1..5]> <;> <DateTime “DD-MM-YYYY HH:MM”>

**FPR operation:** Provides information about the current reading of the daily-report-with-zeroing counter, the number of the last block stored in FM, the number of EJ and the date and time of the last block storage in the FM.

**Input data :**

'5' 1 symbol obligatory '5'

**Output data:**

'5' 1 symbol obligatory '5'

*LastReportNumFromReset* Up to 5 symbols for number of the last report from reset

*LastFMBlockNum* Up to 5 symbols for number of the last FM report

*EJNum* Up to 5 symbols for number of EJ

*DateTime* 16 symbols for date and time of the last block storage in FM in format “DD-MM-YYYY HH:MM”

**zfpdef:** [ReadDailyCounters\(\)](#)



## 2.7.12. Command: 6Eh / n – Read registers, Option ‘6’ (change)

**input:** <'6'>

**output:** <'6'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>  
<;> <AmountPayment5[1..13]> <;> <AmountPayment6[1..13]> <;>  
<AmountPayment7[1..13]> <;> <AmountPayment8[1..13]> <;> <AmountPayment9[1..13]>  
<;> <AmountPayment10[1..13]> <;> <AmountPayment11[1..13]>

**FPR operation:** Provides information about the amounts returned as change by type of payment.

**Input data :**

'6' 1 symbol obligatory '6'

**Output data:**

|                 |  |
|-----------------|--|
| '6'             | 1 symbol obligatory '6'  |
| AmountPayment0  | Up to 13 symbols for the accumulated amount by payment type 0  |
| AmountPayment1  | Up to 13 symbols for the accumulated amount by payment type 1  |
| AmountPayment2  | Up to 13 symbols for the accumulated amount by payment type 2  |
| AmountPayment3  | Up to 13 symbols for the accumulated amount by payment type 3  |
| AmountPayment4  | Up to 13 symbols for the accumulated amount by payment type 4  |
| AmountPayment5  | Up to 13 symbols for the accumulated amount by payment type 5  |
| AmountPayment6  | Up to 13 symbols for the accumulated amount by payment type 6  |
| AmountPayment7  | Up to 13 symbols for the accumulated amount by payment type 7  |
| AmountPayment8  | Up to 13 symbols for the accumulated amount by payment type 8  |
| AmountPayment9  | Up to 13 symbols for the accumulated amount by payment type 9  |
| AmountPayment10 | Up to 13 symbols for the accumulated amount by payment type 10 |
| AmountPayment11 | Up to 13 symbols for the accumulated amount by payment type 11 |

**zfpdef:** [ReadDailyReturnedChangeAmounts\(\)](#)

## 2.7.13. Command: 6Eh / n – Read registers, Option ‘6’, KL (change)

**input:** <'6'>

**output:** <'6'> <;> <AmountPayment0[1..13]> <;> <AmountPayment1[1..13]> <;>  
<AmountPayment2[1..13]> <;> <AmountPayment3[1..13]> <;> <AmountPayment4[1..13]>

**FPR operation:** Provides information about the amounts returned as change by type of payment. Command works for KL version 2 devices.

**Input data :**

'6' 1 symbol obligatory '6'

**Output data:**

|                |   |
|----------------|---|
| '6'            | 1 symbol obligatory '6'                                       |
| AmountPayment0 | Up to 13 symbols for the accumulated amount by payment type 0 |
| AmountPayment1 | Up to 13 symbols for the accumulated amount by payment type 1 |
| AmountPayment2 | Up to 13 symbols for the accumulated amount by payment type 2 |
| AmountPayment3 | Up to 13 symbols for the accumulated amount by payment type 3 |
| AmountPayment4 | Up to 13 symbols for the accumulated amount by payment type 4 |

**zfpdef:** [ReadDailyReturnedChangeAmounts\\_Old\(\)](#)

#### 2.7.14. Command: 6Eh / n – Read registers, Option '7' (Sums in FD)

input: <'7'>

output: <'7'> <;> <GrandFiscalTurnover[1..14]> <;> <GrandFiscalVAT[1..14]> <;>  
<GrandFiscalStornoTurnover[1..14]> <;> <GrandFiscalStornoVAT[1..14]>

FPR operation: Read the Grand fiscal turnover sum and Grand fiscal VAT sum.

Input data :

'7' 1 symbol obligatory '7'

Output data:

'7' 1 symbol obligatory '7'

GrandFiscalTurnover Up to 14 symbols for sum of turnover in FD

GrandFiscalVAT Up to 14 symbols for sum of VAT value in FD

GrandFiscalStornoTurnover Up to 14 symbols for sum of STORNO turnover in FD

GrandFiscalStornoVAT Up to 14 symbols for sum of STORNO VAT value in FD

zfpdef: ReadGrandFiscalSalesAndStornoAmounts()

#### 2.7.15. Command: 6Eh / n – Read registers, Option '9', electronic signature of last daily report

input: <'9'>

output: <'9'> <;> <LastDailyReportSignature[40]>

FPR operation: Provides information about electronic signature of last daily report.

Input data :

'9' 1 symbol obligatory '9'

Output data:

'9' 1 symbol obligatory '9'

LastDailyReportSignature 40 symbols electronic signature

zfpdef: ReadLastDailySignature()

#### 2.7.16. Command: 6Eh / n – Display daily turnover registers, Option ':'

input: <':'>

output: ACK

FPR operation: Provides information about daily turnover on the FD client display

Input data :

':' 1 symbol obligatory ':'

Output data: n. a.

zfpdef: DisplayDailyTurnover()

#### 2.7.17. Command: 6Fh / o – Read operator's report, Option '1' (general)

input: <'1'> <;> <OperNum[1..2]>

output: <'1'> <;> <OperNum[1..2]> <;> <CustomersNum[1..5]> <;>  
<DiscountsNum[1..5]> <;> <DiscountsAmount[1..13]> <;> <AdditionsNum[1..5]> <;>  
<AdditionsAmount[1..13]> <;> <CorrectionsNum[1..5]> <;> <CorrectionsAmount[1..13]>

FPR operation: Read the total number of customers, discounts, additions, corrections and accumulated amounts by specified operator.

Input data :

'1' 1 symbol obligatory '1'

OperNum (Operator Number) Symbols from 1 to 20 corresponding to operator's number

Output data:

'1' 1 symbol obligatory '1'

OperNum Symbols from 1 to 20 corresponding to operator's number

CustomersNum Up to 5 symbols for number of customers

DiscountsNum Up to 5 symbols for number of discounts

DiscountsAmount Up to 13 symbols for accumulated amount of discounts

|                          |  |
|--------------------------|--|
| <i>AdditionsNum</i>      | Up to 5 symbols for number of additions                |
| <i>AdditionsAmount</i>   | Up to 13 symbols for accumulated amount of additions   |
| <i>CorrectionsNum</i>    | Up to 5 symbols for number of corrections              |
| <i>CorrectionsAmount</i> | Up to 13 symbols for accumulated amount of corrections |

**zfpdef:** [ReadDailyGeneralRegistersByOperator\(OperNum\)](#)

## 2.7.18. Command: 6Fh / o – Read operator's report, Option '2' (RA)

**input:** <'2'> <;> <OperNum[1..2]>

**output:** <'2'> <;> <OperNum[1..2]> <;> <AmountRA\_Payment0[1..13]> <;>  
 <AmountRA\_Payment1[1..13]> <;> <AmountRA\_Payment2[1..13]> <;>  
 <AmountRA\_Payment3[1..13]> <;> <AmountRA\_Payment4[1..13]> <;>  
 <AmountRA\_Payment5[1..13]> <;> <AmountRA\_Payment6[1..13]> <;>  
 <AmountRA\_Payment7[1..13]> <;> <AmountRA\_Payment8[1..13]> <;>  
 <AmountRA\_Payment9[1..13]> <;> <AmountRA\_Payment10[1..13]> <;>  
 <AmountRA\_Payment11[1..13]> <;> <NoRA[1..5]>

**FPR operation:** Read the RA by type of payment and the total number of operations by specified operator.

### **Input data :**

|         |   |
|---------|---|
| '2'     | 1 symbol obligatory '2'   |
| OperNum | (Operator Number) Symbols from 1 to 20 corresponding to operator's number |

### **Output data:**

|                    |   |
|--------------------|---|
| '2'                | 1 symbol obligatory '2'                                 |
| OperNum            | Symbols from 1 to 20 corresponding to operator's number |
| AmountRA_Payment0  | Up to 13 symbols for the RA by type of payment 0        |
| AmountRA_Payment1  | Up to 13 symbols for the RA by type of payment 1        |
| AmountRA_Payment2  | Up to 13 symbols for the RA by type of payment 2        |
| AmountRA_Payment3  | Up to 13 symbols for the RA by type of payment 3        |
| AmountRA_Payment4  | Up to 13 symbols for the RA by type of payment 4        |
| AmountRA_Payment5  | Up to 13 symbols for the RA by type of payment 5        |
| AmountRA_Payment6  | Up to 13 symbols for the RA by type of payment 6        |
| AmountRA_Payment7  | Up to 13 symbols for the RA by type of payment 7        |
| AmountRA_Payment8  | Up to 13 symbols for the RA by type of payment 8        |
| AmountRA_Payment9  | Up to 13 symbols for the RA by type of payment 9        |
| AmountRA_Payment10 | Up to 13 symbols for the RA by type of payment 10       |
| AmountRA_Payment11 | Up to 13 symbols for the RA by type of payment 11       |
| NoRA               | Up to 5 symbols for the total number of operations      |

**zfpdef:** [ReadDailyRAbyOperator\(OperNum\)](#)

## 2.7.19. Command: 6Fh / o – Read operator's report, Option '2', KL (RA)

**input:** <'2'> <;> <OperNum[1..2]>

**output:** <'2'> <;> <OperNum[1..2]> <;> <AmountRA\_Payment0[1..13]> <;>  
<AmountRA\_Payment1[1..13]> <;> <AmountRA\_Payment2[1..13]> <;>  
<AmountRA\_Payment3[1..13]> <;> <AmountRA\_Payment4[1..13]> <;> <;> <NoRA[1..5]>

**FPR operation:** Read the RA by type of payment and the total number of operations by specified operator. Command works for KL version 2 devices.

### **Input data :**

'2' 1 symbol obligatory '2'  
OperNum (Operator Number) Symbols from 1 to 20 corresponding to operator's number

### **Output data:**

'2' 1 symbol obligatory '2'  
OperNum Symbols from 1 to 20 corresponding to operator's number  
AmountRA\_Payment0 Up to 13 symbols for the RA by type of payment 0  
AmountRA\_Payment1 Up to 13 symbols for the RA by type of payment 1  
AmountRA\_Payment2 Up to 13 symbols for the RA by type of payment 2  
AmountRA\_Payment3 Up to 13 symbols for the RA by type of payment 3  
AmountRA\_Payment4 Up to 13 symbols for the RA by type of payment 4  
NoRA Up to 5 symbols for the total number of operations

**zfpdef:** [ReadDailyRAbyOperator\\_Old\(OperNum\)](#)

## 2.7.20. Command: 6Fh / o – Read operator's report, Option '3' (PO)

**input:** <'3'> <;> <OperNum[1..2]>

**output:** <'3'> <;> <OperNum[1..2]> <;> <AmountPO\_Payment0[1..13]> <;>  
<AmountPO\_Payment1[1..13]> <;> <AmountPO\_Payment2[1..13]> <;>  
<AmountPO\_Payment3[1..13]> <;> <AmountPO\_Payment4[1..13]> <;>  
<AmountPO\_Payment5[1..13]> <;> <AmountPO\_Payment6[1..13]> <;>  
<AmountPO\_Payment7[1..13]> <;> <AmountPO\_Payment8[1..13]> <;>  
<AmountPO\_Payment9[1..13]> <;> <AmountPO\_Payment10[1..13]> <;>  
<AmountPO\_Payment11[1..13]> <;> <NoPO[1..5]>

**FPR operation:** Read the PO by type of payment and the total number of operations by specified operator

### **Input data :**

'3' 1 symbol obligatory '3'  
OperNum (Operator Number) Symbols from 1 to 20 corresponding to operator's number

### **Output data:**

'3' 1 symbol obligatory '3'  
OperNum Symbols from 1 to 20 corresponding to operator's number  
AmountPO\_Payment0 Up to 13 symbols for the PO by type of payment 0  
AmountPO\_Payment1 Up to 13 symbols for the PO by type of payment 1  
AmountPO\_Payment2 Up to 13 symbols for the PO by type of payment 2  
AmountPO\_Payment3 Up to 13 symbols for the PO by type of payment 3  
AmountPO\_Payment4 Up to 13 symbols for the PO by type of payment 4  
AmountPO\_Payment5 Up to 13 symbols for the PO by type of payment 5  
AmountPO\_Payment6 Up to 13 symbols for the PO by type of payment 6  
AmountPO\_Payment7 Up to 13 symbols for the PO by type of payment 7  
AmountPO\_Payment8 Up to 13 symbols for the PO by type of payment 8  
AmountPO\_Payment9 Up to 13 symbols for the PO by type of payment 9  
AmountPO\_Payment10 Up to 13 symbols for the PO by type of payment 10  
AmountPO\_Payment11 Up to 13 symbols for the PO by type of payment 11  
NoPO 5 symbols for the total number of operations

**zfpdef:** [ReadDailyPObyOperator\(OperNum\)](#)

## 2.7.21. Command: 6Fh / o – Read operator's report, Option '3', KL (PO)

**input:** <'3'> <;> <OperNum[1..2]>

**output:** <'3'> <;> <OperNum[1..2]> <;> <AmountPO\_Payment0[1..13]> <;>  
<AmountPO\_Payment1[1..13]> <;> <AmountPO\_Payment2[1..13]> <;>  
<AmountPO\_Payment3[1..13]> <;> <AmountPO\_Payment4[1..13]> <;> <;> <NoPO[1..5]>

**FPR operation:** Read the PO by type of payment and the total number of operations by specified operator. Command works for KL version 2 devices.

### **Input data :**

'3' 1 symbol obligatory '3'  
OperNum (Operator Number) Symbols from 1 to 20 corresponding to operator's number

### **Output data:**

'3' 1 symbol obligatory '3'  
OperNum Symbols from 1 to 20 corresponding to operator's number  
AmountPO\_Payment0 Up to 13 symbols for the PO by type of payment 0  
AmountPO\_Payment1 Up to 13 symbols for the PO by type of payment 1  
AmountPO\_Payment2 Up to 13 symbols for the PO by type of payment 2  
AmountPO\_Payment3 Up to 13 symbols for the PO by type of payment 3  
AmountPO\_Payment4 Up to 13 symbols for the PO by type of payment 4  
NoPO Up to 5 symbols for the total number of operations

**zfpdef:** [ReadDailyPObyOperator\\_Old\(OperNum\)](#)

## 2.7.22. Command: 6Fh / o – Read operator's report, Option '4' (received)

**input:** <'4'> <;> <OperNum[1..2]>

**output:** <'4'> <;> <OperNum[1..2]> <;> <ReceivedSalesAmountPayment0[1..13]> <;>  
<ReceivedSalesAmountPayment1[1..13]> <;> <ReceivedSalesAmountPayment2[1..13]> <;>  
<ReceivedSalesAmountPayment3[1..13]> <;> <ReceivedSalesAmountPayment4[1..13]> <;>  
<ReceivedSalesAmountPayment5[1..13]> <;> <ReceivedSalesAmountPayment6[1..13]> <;>  
<ReceivedSalesAmountPayment7[1..13]> <;> <ReceivedSalesAmountPayment8[1..13]> <;>  
<ReceivedSalesAmountPayment9[1..13]> <;> <ReceivedSalesAmountPayment10[1..13]> <;>  
<ReceivedSalesAmountPayment11[1..13]>

**FPR operation:** Read the amounts received from sales by type of payment and specified operator.

### **Input data :**

'4' 1 symbol obligatory '4'  
OperNum (Operator Number) Symbols from 1 to 20 corresponding to operator's number

### **Output data:**

'4' 1 symbol obligatory '4'  
OperNum Symbols from 1 to 20 corresponding to operator's number  
ReceivedSalesAmountPayment0 Up to 13 symbols for amounts received by sales for payment 0  
ReceivedSalesAmountPayment1 Up to 13 symbols for amounts received by sales for payment 1  
ReceivedSalesAmountPayment2 Up to 13 symbols for amounts received by sales for payment 2  
ReceivedSalesAmountPayment3 Up to 13 symbols for amounts received by sales for payment 3  
ReceivedSalesAmountPayment4 Up to 13 symbols for amounts received by sales for payment 4  
ReceivedSalesAmountPayment5 Up to 13 symbols for amounts received by sales for payment 5  
ReceivedSalesAmountPayment6 Up to 13 symbols for amounts received by sales for payment 6  
ReceivedSalesAmountPayment7 Up to 13 symbols for amounts received by sales for payment 7  
ReceivedSalesAmountPayment8 Up to 13 symbols for amounts received by sales for payment 8  
ReceivedSalesAmountPayment9 Up to 13 symbols for amounts received by sales for payment 9  
ReceivedSalesAmountPayment10 Up to 13 symbols for amounts received by sales for payment 10  
ReceivedSalesAmountPayment11 Up to 13 symbols for amounts received by sales for payment 11

**zfpdef:** [ReadDailyReceivedSalesAmountsByOperator\(OperNum\)](#)



### 2.7.23. Command: 6Fh / o – Read operator's report, Option '4', KL (received)

**input:** <'4'> <;> <OperNum[1..2]>

**output:** <'4'> <;> <OperNum[1..2]> <;> <ReceivedSalesAmountPayment0[1..13]> <;>  
<ReceivedSalesAmountPayment1[1..13]> <;> <ReceivedSalesAmountPayment2[1..13]> <;>  
<ReceivedSalesAmountPayment3[1..13]> <;> <ReceivedSalesAmountPayment4[1..13]>

**FPR operation:** Read the amounts received from sales by type of payment and specified operator. Command works for KL version 2 devices.

#### **Input data :**

|         |   |
|---------|---|
| '4'     | 1 symbol obligatory '4'   |
| OperNum | (Operator Number) Symbols from 1 to 20 corresponding to operator's number |

#### **Output data:**

|                             |  |
|-----------------------------|--|
| '4'                         | 1 symbol obligatory '4'                                      |
| OperNum                     | Symbols from 1 to 20 corresponding to operator's number      |
| ReceivedSalesAmountPayment0 | Up to 13 symbols for amounts received by sales for payment 0 |
| ReceivedSalesAmountPayment1 | Up to 13 symbols for amounts received by sales for payment 1 |
| ReceivedSalesAmountPayment2 | Up to 13 symbols for amounts received by sales for payment 2 |
| ReceivedSalesAmountPayment3 | Up to 13 symbols for amounts received by sales for payment 3 |
| ReceivedSalesAmountPayment4 | Up to 13 symbols for amounts received by sales for payment 4 |

**zfpdef:** [ReadDailyReceivedSalesAmountsByOperator\\_Old\(OperNum\)](#)

### 2.7.24. Command: 6Fh / o – Read operator's report, Option '5' (counters)

**input:** <'5'> <;> <OperNum[1..2]>

**output:** <'5'> <;> <OperNum[1..2]> <;> <WorkOperatorsCounter[1..5]> <;>  
<LastOperatorReportDateTime "DD-MM-YYYY HH:MM">

**FPR operation:** Read the last operator's report number and date and time.

#### **Input data :**

|         |   |
|---------|---|
| '5'     | 1 symbol obligatory '5'   |
| OperNum | (Operator Number) Symbols from 1 to 20 corresponding to operator's number |

#### **Output data:**

|                            |   |
|----------------------------|---|
| '5"                        | 1 symbol obligatory '5'   |
| OperNum                    | Symbols from 1 to 20 corresponding to operator's number                               |
| WorkOperatorsCounter       | Up to 5 symbols for number of the work operators                                      |
| LastOperatorReportDateTime | 16 symbols for date and time of the last operator's report in format DD-MM-YYYY HH:MM |

**zfpdef:** [ReadDailyCountersByOperator\(OperNum\)](#)

## 2.7.25. Command: 6Fh / o – Read operator's report, Option '6' (change)

**input:** <'6'> <;> <OperNum[1..2]>

**output:** <'6'> <;> <OperNum[1..2]> <;> <ChangeAmountPayment0[1..13]> <;>  
<ChangeAmountPayment1[1..13]> <;> <ChangeAmountPayment2[1..13]> <;>  
<ChangeAmountPayment3[1..13]> <;> <ChangeAmountPayment4[1..13]> <;>  
<ChangeAmountPayment5[1..13]> <;> <ChangeAmountPayment6[1..13]> <;>  
<ChangeAmountPayment7[1..13]> <;> <ChangeAmountPayment8[1..13]> <;>  
<ChangeAmountPayment9[1..13]> <;> <ChangeAmountPayment10[1..13]> <;>  
<ChangeAmountPayment11[1..13]>

**FPR operation:** Read the amounts returned as change by different payment types for the specified operator.

### **Input data :**

|         |  |
|---------|--|
| 6'      | 1 symbol obligatory '6'  |
| OperNum | (Operator Number) Symbol from 1 to 20 corresponding to operator's number |

### **Output data:**

|                       |   |
|-----------------------|---|
| '6'                   | 1 symbol obligatory '6'                                     |
| OperNum               | Symbols from 1 to 20 corresponding to operator's number     |
| ChangeAmountPayment0  | Up to 13 symbols for amounts received by type of payment 0  |
| ChangeAmountPayment1  | Up to 13 symbols for amounts received by type of payment 1  |
| ChangeAmountPayment2  | Up to 13 symbols for amounts received by type of payment 2  |
| ChangeAmountPayment3  | Up to 13 symbols for amounts received by type of payment 3  |
| ChangeAmountPayment4  | Up to 13 symbols for amounts received by type of payment 4  |
| ChangeAmountPayment5  | Up to 13 symbols for amounts received by type of payment 5  |
| ChangeAmountPayment6  | Up to 13 symbols for amounts received by type of payment 6  |
| ChangeAmountPayment7  | Up to 13 symbols for amounts received by type of payment 7  |
| ChangeAmountPayment8  | Up to 13 symbols for amounts received by type of payment 8  |
| ChangeAmountPayment9  | Up to 13 symbols for amounts received by type of payment 9  |
| ChangeAmountPayment10 | Up to 13 symbols for amounts received by type of payment 10 |
| ChangeAmountPayment11 | Up to 13 symbols for amounts received by type of payment 11 |

**zfpdef:** [ReadDailyReturnedChangeAmountsByOperator\(OperNum\)](#)

## 2.7.26. Command: 6Fh / o – Read operator's report, Option '6', KL (change)

**input:** <'6'> <;> <OperNum[1..2]>

**output:** <'6'> <;> <OperNum[1..2]> <;> <ChangeAmountPayment0[1..13]> <;>  
<ChangeAmountPayment1[1..13]> <;> <ChangeAmountPayment2[1..13]> <;>  
<ChangeAmountPayment3[1..13]> <;> <ChangeAmountPayment4[1..13]> <;>

**FPR operation:** Read the amounts returned as change by different payment types for the specified operator. Command works for KL version 2 devices.

### **Input data :**

|         |  |
|---------|--|
| 6'      | 1 symbol obligatory '6'  |
| OperNum | (Operator Number) Symbol from 1 to 20 corresponding to operator's number |

### **Output data:**

|                      |  |
|----------------------|--|
| '6'                  | 1 symbol obligatory '6'                                    |
| OperNum              | Symbols from 1 to 20 corresponding to operator's number    |
| ChangeAmountPayment0 | Up to 13 symbols for amounts received by type of payment 0 |
| ChangeAmountPayment1 | Up to 13 symbols for amounts received by type of payment 1 |
| ChangeAmountPayment2 | Up to 13 symbols for amounts received by type of payment 2 |
| ChangeAmountPayment3 | Up to 13 symbols for amounts received by type of payment 3 |
| ChangeAmountPayment4 | Up to 13 symbols for amounts received by type of payment 4 |

**zfpdef:** [ReadDailyReturnedChangeAmountsByOperator\\_Old\(OperNum\)](#)

## 2.7.27. Command: 70h / p – Read invoice number range

**input:** n. a.

**output:** <StartNum[10]> <;> <EndNum[10]>

**FPR operation:** Provide information about invoice start and end numbers range.

**Input data : n. a.**

**Output data :**

StartNum 10 symbols for start No with leading zeroes in format #####

EndNum 10 symbols for end No with leading zeroes in format #####

**zfpdef:** ReadInvoiceRange()

## 2.7.28. Command: 71h / q – Read total receipt number

**input:** n. a.

**output:** <TotalReceiptCounter[6]>

**FPR operation:** Read the total counter of last issued receipt.

**Input data : n. a.**

**Output data :**

TotalReceiptCounter 6 symbols for the total receipt counter in format #####  
up to current last issued receipt by FD

**zfpdef:** ReadLastReceiptNum()

## 2.7.29. Command: 72h / r – Read information about current opened receipt

**input:** n. a.

**output:** <IsReceiptOpened[1]> <;> <SalesNumber[3]> <;> <SubtotalAmountVAT0[1..13]>  
<;> <SubtotalAmountVAT1[1..13]> <;> <SubtotalAmountVAT2[1..13]> <;> <ForbiddenVoid[1]> <;>  
<VATinReceipt[1]> <;> <ReceiptFormat[1]> <;> <InitiatedPayment[1]> <;> <FinalizedPayment[1]>  
<;> <PowerDownInReceipt[1]> <;> <TypeReceipt[1]> <;> <ChangeAmount[1..13]> <;>  
<OptionChangeType[1]> <;> <SubtotalAmountVAT3[1..13]> <;> <SubtotalAmountVAT4[1..13]>  
<;> <SubtotalAmountVAT5[1..13]> <;> <SubtotalAmountVAT6[1..13]> <;>  
<SubtotalAmountVAT7[1..13]> <;> <CurrentReceiptNumber[6]>

**FPR operation:** Read the current status of the receipt.

**Input data : n. a.**

**Output data :**

|                    |  |
|--------------------|--|
| IsReceiptOpened    | 1 symbol with value:<br>- '0' - No<br>- '1' - Yes                  |
| SalesNumber        | 3 symbols for number of sales in format ###                        |
| SubtotalAmountVAT0 | Up to 13 symbols for subtotal by VAT group A                       |
| SubtotalAmountVAT1 | Up to 13 symbols for subtotal by VAT group B                       |
| SubtotalAmountVAT2 | Up to 13 symbols for subtotal by VAT group B                       |
| ForbiddenVoid      | 1 symbol with value:<br>- '0' – allowed<br>- '1' - forbidden       |
| VATinReceipt       | 1 symbol with value:<br>- '0' – No<br>- '1' - Yes                  |
| ReceiptFormat      | (Format) 1 symbol with value:<br>- '1' - Detailed<br>- '0' - Brief |
| InitiatedPayment   | 1 symbol with value:<br>- '0' – No<br>- '1' – Yes                  |



|                             |  |
|-----------------------------|--|
| <i>FinalizedPayment</i>     | 1 symbol with value:<br>- '0' - No<br>- '1' - Yes  |
| <i>PowerDownInReceipt</i>   | 1 symbol with value:<br>- '0' - No<br>- '1' - Yes  |
| <i>TypeReceipt</i>          | (Receipt and Printing type) 1 symbol with value:<br>- '0' - Sales receipt printing step by step<br>- '2' - Sales receipt Postponed Printing<br>- '4' - Storno receipt printing step by step<br>- '6' - Storno receipt Postponed Printing<br>- '1' – Invoice sales receipt printing step by step<br>- '3' – Invoice sales receipt Postponed Printing<br>- '5' – Invoice Credit note receipt printing step by step<br>- '7' – Invoice Credit note receipt Postponed Printing |
| <i>ChangeAmount</i>         | Up to 13 symbols the amount of the due change in the stated payment type   |
| <i>OptionChangeType</i>     | 1 symbol with value:<br>- '0' - Change In Cash<br>- '1' - Same As The payment<br>- '2' – Change In Currency  |
| <i>SubtotalAmountVAT3</i>   | Up to 13 symbols for subtotal by VAT group Г   |
| <i>SubtotalAmountVAT4</i>   | Up to 13 symbols for subtotal by VAT group Д   |
| <i>SubtotalAmountVAT5</i>   | Up to 13 symbols for subtotal by VAT group Е   |
| <i>SubtotalAmountVAT6</i>   | Up to 13 symbols for subtotal by VAT group Ж   |
| <i>SubtotalAmountVAT7</i>   | Up to 13 symbols for subtotal by VAT group З   |
| <i>CurrentReceiptNumber</i> | 6 symbols for fiscal receipt number in format #####  |

**zfpdef:** ReadCurrentReceiptInfo()

## 2.7.30. Command: 72h / r – Read information about current/last receipt payments amounts, Option P

**input:** <'P'>

**output:** <'P'> <;> <IsReceiptOpened[1]> <;> <Payment0Amount[1..13]> <;>  
 <Payment1Amount[1..13]> <;> <Payment2Amount[1..13]> <;> <Payment3Amount[1..13]>  
 <;> <Payment4Amount[1..13]> <;> <Payment5Amount[1..13]> <;>  
 <Payment6Amount[1..13]> <;> <Payment7Amount[1..13]> <;> <Payment8Amount[1..13]>  
 <;> <Payment9Amount[1..13]> <;> <Payment10Amount[1..13]> <;>  
 <Payment11Amount[1..13]>

**FPR operation:** Provides information about the payments in current receipt. This command is valid after receipt closing also.

**Input data :**

'P' 1 symbol 'P' for option

**Output data :**

'P' 1 symbol 'P' for option

*IsReceiptOpened* 1 symbol with value:

- '0' - No

- '1' - Yes

*Payment0Amount* Up to 13 symbols for type 0 payment amount

*Payment1Amount* Up to 13 symbols for type 1 payment amount

*Payment2Amount* Up to 13 symbols for type 2 payment amount

*Payment3Amount* Up to 13 symbols for type 3 payment amount

*Payment4Amount* Up to 13 symbols for type 4 payment amount

*Payment5Amount* Up to 13 symbols for type 5 payment amount

*Payment6Amount* Up to 13 symbols for type 6 payment amount

*Payment7Amount* Up to 13 symbols for type 7 payment amount

*Payment8Amount* Up to 13 symbols for type 8 payment amount  
*Payment9Amount* Up to 13 symbols for type 9 payment amount  
*Payment10Amount* Up to 13 symbols for type 10 payment amount  
*Payment11Amount* Up to 13 symbols for type 11 payment amount  
**zfpdef:**ReadCurrentOrLastReceiptPaymentAmounts()

### 2.7.31. Command: 72h / r – Read information about last receipt QR barcode data, Option B

**input:** <'B'>

**output:** <QRcodeData[60]>

**FPR operation:** Provides information about the QR code data in last issued receipt.

#### **Input data :**

'B' 1 symbol 'B' for option

#### **Output data :**

*QRcodeData* Up to 60 symbols for last issued receipt QR code data separated by symbol '\*' in format: FM Number\*Receipt Number\*Receipt Date\*Receipt Hour\*Receipt Amount

**zfpdef:**ReadLastReceiptQRcodeData()

### 2.7.32. Command: 72h / r – Read information about specified number receipt QR barcode data, Option b

**input:** <'b'><;><RcpNum[6]>

**output:** <QRcodeData[60]>

**FPR operation:** Provides information about the QR code data in specified number issued receipt.

#### **Input data :**

'B' 1 symbol 'B' for option  
*RcpNum* 6 symbols with format #####

#### **Output data :**

*QRcodeData* Up to 60 symbols for last issued receipt QR code data separated by symbol '\*' in format: FM Number\*Receipt Number\*Receipt Date\*Receipt Hour\*Receipt Amount

**zfpdef:** ReadSpecifiedReceiptQRcodeData(RcpNum)

### 2.7.33. Command: 72h / r – Read electronic receipt by number with QR code data, Option e

**input:** <'e'><;><RcpNum[6]>

**output:** ACK+

**FPR operation:** Starts session for reading electronic receipt by number with its QR code data in the end.

#### **Input data :**

'e' 1 symbol 'e' for option  
*RcpNum* 6 symbols with format #####

#### **Output data: n. a.**

**zfpdef:** ReadElectronicReceipt\_QR\_Data(RcpNum)

### 2.7.34. Command: 72h / r – Read electronic receipt by number with ASCII specified QR symbol, Option E

**input:** <'E'> <;> <RcpNum[6]> <;> <QRSymbol[1]>

**output:** ACK+

**FPR operation:** Starts session for reading electronic receipt by number with specified ASCII symbol for QR code block.

**Input data :**

|          |                                    |
|----------|------------------------------------|
| 'E'      | 1 symbol 'E' for option            |
| RcpNum   | 6 symbols with format #####        |
| QRSymbol | 1 symbol for QR code drawing image |

**Output data: n. a.**

**zfpdef:** ReadElectronicReceipt\_QR\_ASCII(RcpNum, QRSymbol)

### 2.7.35. Command: 72h / r – Read electronic receipt by number with Base64 encoded QR, Option E

**input:** <'E'> <;> <RcpNum[6]> <;> <QRSymbol[',']>

**output:** ACK+

**FPR operation:** Starts session for reading electronic receipt by number with Base64 encoded BMP QR code.

**Input data :**

|          |                             |
|----------|-----------------------------|
| 'E'      | 1 symbol 'E' for option     |
| RcpNum   | 6 symbols with format ##### |
| QRSymbol | 1 symbol with value ','     |

**Output data: n. a.**

**zfpdef:** ReadElectronicReceipt\_QR\_BMP(RcpNum)

## 2.7.36. Command: 73h / s– Read last daily report info

input: n. a.

output: <LastZDailyReportDate "DD-MM-YYYY"> <;> <LastZDailyReportNum[1..4]>  
<;> <LastRAMResetNum[1..4]> <;> <TotalReceiptCounter[6]> <;>  
<DateTimeLastFiscRec "DD-MM-YYYY HH:MM"> <;> <EJNum[2]> <;>  
<LastReceiptType[1]>

**FPR operation:** Read date and number of last Z-report and last RAM reset event.

**Input data : n. a.**

**Output data :**

|                             |   |
|-----------------------------|---|
| <i>LastZDailyReportDate</i> | 10 symbols for last Z-report date in DD-MM-YYYY format  |
| <i>LastZDailyReportNum</i>  | Up to 4 symbols for the number of the last daily report   |
| <i>LastRAMResetNum</i>      | Up to 4 symbols for the number of the last RAM reset  |
| <i>TotalReceiptCounter</i>  | 6 symbols for the total number of receipts in format #####  |
| <i>DateTimeLastFiscRec</i>  | Date Time parameter in format: DD-MM-YYYY HH:MM   |
| <i>EJNum</i>                | Up to 2 symbols for number of EJ  |
| <i>LastReceiptType</i>      | (Receipt and Printing type) 1 symbol with value: <ul style="list-style-type: none"><li>- '0' - Sales receipt printing</li><li>- '2' – Non fiscal receipt</li><li>- '4' - Storno receipt</li><li>- '1' – Invoice sales receipt</li><li>- '5' – Invoice Credit note</li></ul> |

**zfpdef:** ReadLastDailyReportInfo()

## 2.7.37. Command: 74h / t – Read free FM reporting records

input: n. a.

output: <FreeFMrecords[4]>

**FPR operation:** Read the number of the remaining free records for Z-report in the Fiscal Memory.

**Input data : n. a.**

**Output data :**

*FreeFMrecords* 4 symbols for the number of free records for Z-report in the FM

**zfpdef:** ReadFMfreeRecords()

## 2.7.38. Command: 75h / u – Read FM contents

**input:** n. a.

**output:** ACK +

*end number of packed messages for every block stored in FM:*

*<Nsegm[4]><OptionCodeStored[1]><DateStored[16]><Status[1]><ReadData [~]> +*

*a message for end of string: <Nsegm[4]><'@'>*

**FPR operation:** Provides consequently information about every single block stored in the FM starting with Acknowledgements and ending with end message.

**Input data :** n. a.

**Output data :**

|                         |  |
|-------------------------|--|
| <i>Nsegm</i>            | 4 symbols for physical FM block number   |
| <i>OptionCodeStored</i> | 1 symbol stating the type of the stored block with the following values:<br>0 – factory number of FD<br>1 – VAT number, decimal point position and VAT rate at fiscalization<br>4 – daily financial report<br>5 – RAM reset<br>6 – change of VAT rates<br>7 – change of decimal point position<br>: – deleted EJ |
| <i>DateStored</i>       | 16 symbols for the date and time of block storing  |
| <i>Status</i>           | 1 symbol 0 or 1 resp. for correct/incorrect block checksum   |
| <i>ReadData</i>         | Total fields of data read  |
| <i>&lt;'@'&gt;</i>      | 1 symbol obligatory '@' for end of string  |

**zfpdef:** ReadFMcontent()

## 2.8. REPORTS PRINTING COMMANDS

Set of commands for printing of reports generated by FD.

### 2.8.1. Command: 76h / v – Print department report

input: <OptionZeroing[1]>

output: ACK

FPR operation: Print a department report with or without zeroing ('Z' or 'X').

**Input data :**

OptionZeroing (Parameter Zero) 1 symbol with value:  
- 'Z' – Zeroing  
- 'X' – Without zeroing

**Output data : n. a.**

**zfpdef:** *PrintDepartmentReport(OptionZeroing)*

### 2.8.2. Command: 77h / w – Print special events FM report

input: n. a.

output: ACK

FPR operation: Print whole special FM events report.

**Input data : n. a.**

**Output data : n. a.**

**zfpdef:** *PrintSpecialEventsFMreport()*

### 2.8.3. Command: 77h / w – Print brief FM payments report

input: <Option['P']>

output: ACK

FPR operation: Prints a brief payments from the FM.

**Input data :**

Option 1 symbol with value 'P'

**Output data : n. a.**

**zfpdef:** *PrintBriefFMPaymentsReport()*

### 2.8.4. Command: 78h / x – Print detailed FM report by number of Z report blocks

input: <StartZNum[4]> <;> <EndZNum[4]>

output: ACK

FPR operation: Print a detailed FM report by initial and end FM report number.

**Input data :**

StartZNum 4 symbols for the initial report number included in report, format ####

EndZNum 4 symbols for the final report number included in report, format ####

**Output data: n. a.**

**zfpdef:** *PrintDetailedFMReportByZBlocks(StartNo, EndNo)*

### 2.8.5. Command: 78h / x – Print detailed FM payments report by number of Z report blocks

**input:** <StartZNum[4]> <;> <EndZNum[4]> <;> <Option['P']>

**output:** ACK

**FPR operation:** Print a detailed FM payments report by initial and end FM report number.

#### **Input data :**

*StartZNum* 4 symbols for initial FM report number included in report, format #####

*EndZNum* 4 symbols for final FM report number included in report, format #####

*Option* 1 symbol 'P'

**Output data: n. a.**

**zfpdef:** *PrintDetailedFMPaymentsReportByZBlocks(StartNo, EndNo)*

### 2.8.6. Command: 79h / y – Print brief FM report by number of Z report blocks

**input:** <StartZNum[4]> <;> <EndZNum[4]>

**output:** ACK

**FPR operation:** Print a brief FM report by initial and end FM report number.

#### **Input data :**

*StartZNum* 4 symbols for the initial FM report number included in report, format #####

*EndZNum* 4 symbols for the final FM report number included in report, format #####

**Output data: n. a.**

**zfpdef:** *PrintBriefFMReportByZBlocks(StartNo, EndNo)*

### 2.8.7. Command: 79h / y – Print brief FM payments report by number of Z report blocks

**input:** <StartZNum[4]> <;> <EndZNum[4]> <;> <Option['P']>

**output:** ACK

**FPR operation:** Print a brief FM payments report by initial and end FM report number.

#### **Input data :**

*StartZNum* 4 symbols for the initial FM report number included in report, format #####

*EndZNum* 4 symbols for the final FM report number included in report, format #####

*Option* 1 symbol 'P'

**Output data: n. a.**

**zfpdef:** *PrintBriefFMPaymentsReportByZBlocks(StartNo, EndNo)*

### 2.8.8. Command: 7Ah / z – Print detailed FM report by date

**input:** <StartDate "DDMMYY"> <;> <EndDate "DDMMYY">

**output:** ACK

**FPR operation:** Prints a detailed FM report by initial and end date.

#### **Input data :**

*StartDate* 6 symbols for initial date in the DDMMYY format

*EndDate* 6 symbols for final date in the DDMMYY format

**Output data: n. a.**

**zfpdef:** *PrintDetailedFMReportByDate(StartDate, EndDate)*

### 2.8.9. Command: 7Ah / z – Print detailed FM payments report by date

input: <StartDate "DDMMYY"> <;> <EndDate "DDMMYY"> <;> <Option['P']>

output: ACK

FPR operation: Print a detailed FM payments report by initial and end date.

#### Input data :

StartDate 6 symbols for initial date in the DDMMYY format

EndDate 6 symbols for final date in the DDMMYY format

Option 1 symbol 'P'

Output data: n. a.

zfpdef: [PrintDetailedFMPaymentsReportByDate\(StartDate, EndDate\)](#)

### 2.8.10. Command: 7Bh / { – Print brief FM report by date

input: <StartDate "DDMMYY"> <;> <EndDate "DDMMYY">

output: ACK

FPR operation: Print a brief FM report by initial and end date.

#### Input data :

StartDate 6 symbols for initial date in the DDMMYY format

EndDate 6 symbols for final date in the DDMMYY format

Output data: n. a.

zfpdef: [PrintBriefFMReportByDate\(StartDate, EndDate\)](#)

### 2.8.11. Command: 7Bh / { – Print brief FM payments report by date

input: <StartDate "DDMMYY"> <;> <EndDate "DDMMYY"> <;> <Option['P']>

output: ACK

FPR operation: Print a brief FM payments report by initial and end date.

#### Input data :

StartDate 6 symbols for initial date in the DDMMYY format

EndDate 6 symbols for final date in the DDMMYY format

Option 1 symbol 'P'

Output data: n. a.

zfpdef: [PrintBriefFMPaymentsReportByDate\(StartDate, EndDate\)](#)

### 2.8.12. Command: 7Ch / | – Print daily fiscal report X or Z

input: <OptionZeroing[1]>

output: ACK

FPR operation: Depending on the parameter prints:

- daily fiscal report with zeroing and fiscal memory record, preceded by Electronic Journal report print ('Z');
- daily fiscal report without zeroing ('X');

#### Input data:

OptionZeroing 1 character with following values:

- 'Z' – Zeroing
- 'X' – Without zeroing

Output data: n.a.

zfpdef: [PrintDailyReport\(OptionZeroing\)](#)



### 2.8.13. Command: 7Ch / | – Print/Store Electronic Journal report from date do date

**input:** <ReportStorage[2]> <;> <'D'> <;> <StartRepFromDate "DDMMYY"> <;>  
<EndRepFromDate "DDMMYY">

**output:** ACK

**FPR operation:** Print or store Electronic Journal Report by initial and end date.

#### **Input data:**

*ReportStorage* (EJ Report storage) 1 character with value:  
- 'J1' – Printing  
- 'J2' – USB storage  
- 'J4' – SD card storage  
  
'D' 1 symbol 'D'  
*StartRepFromDate* 6 symbols for initial date in the DDMMYY format  
*EndRepFromDate* 6 symbols for final date in the DDMMYY format

**Output data:** n. a.

**zfptdef:** PrintOrStoreEJByDate(StartDate, EndDate)

### 2.8.14. Command: 7Ch / | – Print Electronic Journal report from date do date with selected documents content

**input:** <'j1'> <;> <'X'> <;> <FlagsReceipts [1]> <;> <FlagsReports [1]> <;> <'D'>  
<;> <StartRepFromDate "DDMMYY"> <;> <EndRepFromDate "DDMMYY">

**output:** ACK

**FPR operation:** Print Electronic Journal Report by initial and end date, and selected documents content. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

#### **Input data:**

'j1' 2 symbols with value 'j1'  
'X' 1 symbol with value 'X'  
*FlagsReceipts* (Receipts included in EJ) 1 symbol for Receipts included in EJ:  
Flags.7=0  
Flags.6=1  
Flags.5=1 Yes, Flags.5=0 No (Include PO)  
Flags.4=1 Yes, Flags.4=0 No (Include RA)  
Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)  
Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)  
Flags.1=1 Yes, Flags.1=0 No (Include Invoice)  
Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)  
';' 1 symbol with value ';'   
*FlagsReports* (Reports included in EJ) 1 symbol for Reports included in EJ:  
Flags.7=0  
Flags.6=1  
Flags.5=0  
Flags.4=1 Yes, Flags.4=0 No (Include FM reports)  
Flags.3=1 Yes, Flags.3=0 No (Include Other reports)  
Flags.2=1 Yes, Flags.2=0 No (Include Daily X)  
Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)  
Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)  
  
'D' 1 symbol 'D'  
*StartRepFromDate* 6 symbols for initial date in the DDMMYY format  
*EndRepFromDate* 6 symbols for final date in the DDMMYY format

**Output data:** n. a.

**zfptdef:** PrintEJByDateCustom(FlagsReceipts, FlagsReports, StartDate, EndDate)

### 2.8.15. Command: 7Ch / | – Print/Store Electronic Journal report from receipt number to receipt number

**input:** <ReportStorage[2]> <;> <'N'> <;> <StartRcpNum[6]> <;> <EndRcpNum[6]>

**output:** ACK

**FPR operation:** Print or store Electronic Journal Report from receipt number to receipt number.

**Input data:**

*ReportStorage* (EJ Report storage) 1 character with value:

- 'J1' – Printing
- 'J2' – USB storage
- 'J4' – SD card storage

*'N'* 1 symbol 'N'

*StartRcpNum* 6 symbols for initial receipt number included in report, in format #####.

*EndRcpNum* 6 symbols for final receipt number included in report in format #####.

**Output data: n. a.**

**zfpdef:** PrintOrStoreEJByRcpNum(ReportStorage, StartNo, EndNo)

### 2.8.16. Command: 7Ch / | – Print Electronic Journal report from receipt number to receipt number with selected documents content

**input:** <'j1'> <;> <'X'> <;> <FlagsReceipts [1]> <;> <FlagsReports [1]> <;> <'N'> <;> <StartRcpNum[6]> <;> <EndRcpNum[6]>

**output:** ACK

**FPR operation:** Print Electronic Journal Report from receipt number to receipt number and selected documents content. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

**Input data:**

*'j1'* 2 symbols with value 'j1'

*'X'* 1 symbol with value 'X'

*FlagsReceipts* (Receipts included in EJ) 1 symbol for Receipts included in EJ:

Flags.7=0

Flags.6=1

Flags.5=1 Yes, Flags.5=0 No (Include PO)

Flags.4=1 Yes, Flags.4=0 No (Include RA)

Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)

Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)

Flags.1=1 Yes, Flags.1=0 No (Include Invoice)

Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)

*','* 1 symbol with value ','

*FlagsReports* (Reports included in EJ) 1 symbol for Reports included in EJ:

Flags.7=0

Flags.6=1

Flags.5=0

Flags.4=1 Yes, Flags.4=0 No (Include FM reports)

Flags.3=1 Yes, Flags.3=0 No (Include Other reports)

Flags.2=1 Yes, Flags.2=0 No (Include Daily X)

Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)

Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)

*'N'* 1 symbol 'N'

*StartRcpNum* 6 symbols for initial receipt number included in report in format #####.

*EndRcpNum* 6 symbols for final receipt number included in report in format #####.

**Output data: n. a.**

**zfpdef:** PrintEJByRcpNumCustom(FlagsReceipts, FlagsReports, StartNo, EndNo)

### 2.8.17. Command: 7Ch / | – Print/Store Electronic Journal report by number of Z report blocks

**input:** <ReportStorage[2]> <;> <'Z'> <;> <StartZNum[4]> <;> <EndZNum[4]>

**output:** ACK

**FPR operation:** Print or store Electronic Journal Report from by number of Z report blocks.

#### **Input data:**

*ReportStorage* (EJ Report storage) 1 character with value:

- 'J1' – Printing
- 'J2' – USB storage
- 'J4' – SD card storage

*'Z'* 1 symbol 'Z'

*StartZNum* 4 symbols for initial number report in format #####

*EndZNum* 4 symbols for final number report in format #####

#### **Output data: n. a.**

**zfpdef:** PrintOrStoreEJByZBlocks(StartNo, EndNo)

### 2.8.18. Command: 7Ch / | – Print Electronic Journal report by number of Z report blocks with selected documents content

**input:** <'j1'> <;> <'X'> <;> <FlagsReceipts [1]> <;> <FlagsReports [1]> <;> <'Z'> <;> <StartZNum[4]> <;> <EndZNum[4]>

**output:** ACK

**FPR operation:** Print Electronic Journal Report by number of Z report blocks and selected documents content. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

#### **Input data:**

*'j1'* 2 symbols with value 'j1'

*'X'* 1 symbol with value 'X'

*FlagsReceipts* (Receipts included in EJ) 1 symbol for Receipts included in EJ:

Flags.7=0

Flags.6=1

Flags.5=1 Yes, Flags.5=0 No (Include PO)

Flags.4=1 Yes, Flags.4=0 No (Include RA)

Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)

Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)

Flags.1=1 Yes, Flags.1=0 No (Include Invoice)

Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)

*','* 1 symbol with value ','

*FlagsReports* (Reports included in EJ) 1 symbol for Reports included in EJ:

Flags.7=0

Flags.6=1

Flags.5=0

Flags.4=1 Yes, Flags.4=0 No (Include FM reports)

Flags.3=1 Yes, Flags.3=0 No (Include Other reports)

Flags.2=1 Yes, Flags.2=0 No (Include Daily X)

Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)

Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)

*'Z'* 1 symbol 'Z'

*StartZNum* 4 symbols for initial number report in format #####

*EndZNum* 4 symbols for final number report in format #####

#### **Output data: n. a.**

**zfpdef:** PrintEJByZBlocksCustom(FlagsReceipts, FlagsReports, StartNo, EndNo)

## 2.8.19. Command: 7Ch / | – Print/Store Electronic Journal report from beginning to end

input: <ReportStorage[2]> <;> <'\*>

output: ACK

FPR operation: Print or store Electronic Journal report with all documents.

### Input data:

ReportStorage (EJ Report storage) 1 character with value:

- 'J1' – Printing
- 'J2' – USB storage
- 'J4' – SD card storage

'\*' 1 symbol '\*'

### Output data: n. a.

zfpdef: PrintOrStoreEJ()

## 2.8.20. Command: 7Ch / | – Print Electronic Journal report from beginning to end with selected documents content

input: <'j1'> <;> <'X'> <;> <FlagsReceipts [1]> <;> <FlagsReports [1]> <;> <'\*>

output: ACK

FPR operation: Print Electronic Journal report with selected documents content.

FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

### Input data:

'j1' 2 symbols with value 'j1'

'X' 1 symbol with value 'X'

FlagsReceipts (Receipts included in EJ) 1 symbol for Receipts included in EJ:

Flags.7=0

Flags.6=1

Flags.5=1 Yes, Flags.5=0 No (Include PO)

Flags.4=1 Yes, Flags.4=0 No (Include RA)

Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)

Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)

Flags.1=1 Yes, Flags.1=0 No (Include Invoice)

Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)

';' 1 symbol with value ';' ;

FlagsReports (Reports included in EJ) 1 symbol for Reports included in EJ:

Flags.7=0

Flags.6=1

Flags.5=0

Flags.4=1 Yes, Flags.4=0 No (Include FM reports)

Flags.3=1 Yes, Flags.3=0 No (Include Other reports)

Flags.2=1 Yes, Flags.2=0 No (Include Daily X)

Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)

Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)

'\*' 1 symbol '\*'

### Output data: n. a.

zfpdef: PrintEJCustom(FlagsReceipts, FlagsReports)

### 2.8.21. Command: 7Dh / } – Print operator's report

**input:** <OptionZeroing[1]> <;> <Number[1..2]>

**output:** ACK

**FPR operation:** Prints an operator's report for a specified operator (0 = all operators) with or without zeroing ('Z' or 'X'). When a 'Z' value is specified the report should include all operators.

**Input data :**

*OptionZeroing* 1 character (Parameter) with following values:

- 'Z' – Zeroing
- 'X' – Without zeroing

*Number* (Operator Number) Symbols from 0 to 20 corresponding to operator's number  
,0 for all operators

**Output data: n. a.**

**zfpdef:** PrintOperatorReport(OptionZeroing, Number)

### 2.8.22. Command: 7Eh / ~ – Print article report

**input:** <OptionZeroing[1]>

**output:** ACK

**FPR operation:** Prints an article report with or without zeroing ('Z' or 'X').

**Input data :**

*OptionZeroing* 1 character (Parameter) with following values:

- 'Z' – Zeroing
- 'X' – Without zeroing

**Output data: n. a.**

**zfpdef:** PrintArticleReport(OptionZeroing)

### 2.8.23. Command: 7Fh / ■ – Print detailed daily report

**input:** <OptionZeroing[1]>

**output:** ACK

**FPR operation:** Prints an extended daily financial report (an article report followed by a daily financial report) with or without zeroing ('Z' or 'X').

**Input data :**

*OptionZeroing* 1 character (Parameter) with following values:

- 'Z' –Zeroing
- 'X' – Without zeroing

**Output data: n. a.**

**zfpdef:** PrintDetailedDailyReport(OptionZeroing)

### 2.8.24. Command: 52h / R – option X, Print Customer X or Z report

**input:** <OptionZeroing[1]>

**output:** ACK

**FPR Operation:** Print Customer X or Z report

**Input data:**

*OptionZeroing* 1 character (Parameter) with following values:

- 'Z' –Zeroing
- 'X' – Without zeroing

**Output data: n.a.**

**zfpdef:** PrintCustomerReport(OptionZeroing)

## 2.9. REPORTS READING COMMANDS

Set of commands for reading of reports generated by FD.

### 2.9.1. Command: 7Ch / | – Read Electronic Journal report from date do date

**input:** <ReportFormat[2]> <;> <'D'> <;> <StartRepFromDate "DDMMYY"> <;>  
<EndRepFromDate "DDMMYY">

**output:** ACK+

**FPR operation:** Read Electronic Journal Report by initial to end date.

**Input data:**

*ReportFormat* (EJ Report format) 1 character with value  
- 'J0' – Detailed EJ  
- 'J8' – Brief EJ  
'D' 1 symbol 'D'  
*StartRepFromDate* 6 symbols for initial date in the DDMMYY format  
*EndRepFromDate* 6 symbols for final date in the DDMMYY format

**Output data:** n. a.

**zfpdef:** ReadEJByDate(ReportFormat, StartRepFromDate, EndRepFromDate)

### 2.9.2. Command: 7Ch / | – Read/Store Electronic Journal report from date do date with selected documents content and format

**input:** <StorageReport[2]> <;> <CSVformat[1]> <;> <FlagsReceipts[1]> <;>  
<FlagsReports[1]> <;> <'D'> <;> <StartRepFromDate "DDMMYY"> <;>  
<EndRepFromDate "DDMMYY">

**output:** ACK+

**FPR operation:** Read or Store Electronic Journal Report by initial to end date, CSV format option and document content. If CSV format is set the content can includes only fiscal receipts. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

**Input data:**

*StorageReport* (EJ Report storage) 1 character with value  
- 'j0' – To PC  
- 'j2' – To USB Flash Drive  
- 'j4' – To SD card  
*CSVformat* 1 symbol with value:  
- 'C' – Yes  
- 'X' – No  
*FlagsReceipts* (Receipts included in EJ) 1 symbol for Receipts included in EJ:  
Flags.7=0  
Flags.6=1, 0=w  
Flags.5=1 Yes, Flags.5=0 No (Include PO)  
Flags.4=1 Yes, Flags.4=0 No (Include RA)  
Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)  
Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)  
Flags.1=1 Yes, Flags.1=0 No (Include Invoice)  
Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)  
'.'  
'.' 1 symbol with value '.'

*FlagsReports* (Reports included in EJ) 1 symbol for Reports included in EJ:

Flags.7=0

Flags.6=1, 0=w

Flags.5=1, 0=w

Flags.4=1 Yes, Flags.4=0 No (Include FM reports)

Flags.3=1 Yes, Flags.3=0 No (Include Other reports)

Flags.2=1 Yes, Flags.2=0 No (Include Daily X)

Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)

Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)

'D' 1 symbol 'D'

*StartRepFromDate* 6 symbols for initial date in the DDMMYY format

*EndRepFromDate* 6 symbols for final date in the DDMMYY format

**Output data: n. a.**

**zfpdef:** ReadEJByDateCustom(StorageReport, CSVformat, FlagsReceipts, FlagsReports, StartRepFromDate, EndRepFromDate)

### 2.9.3. Command: 7Ch / | – Read Electronic Journal report from receipt number to receipt number

**input:** <ReportFormat[2]> <;> <'N'> <;> <StartRcpNum[6]> <;> <EndRcpNum[6]>

**output:** ACK+

**FPR operation:** Read Electronic Journal Report from receipt number to receipt number.

**Input data:**

*ReportFormat* (EJ Report format) 1 character with value

- 'J0' – Detailed EJ

- 'J8' – Brief EJ

'N' 1 symbol 'N'

*StartRcpNum* 6 symbols for initial receipt number included in report in format #####

*EndRcpNum* 6 symbols for final receipt number included in report in format #####

**Output data: n. a.**

**zfpdef:** ReadEJByReceiptNum(ReportFormat, StartNo, EndNo)

### 2.9.4. Command: 7Ch / | – Read/Store Electronic Journal report from receipt number to receipt number with selected documents content and format

**input:** <StorageReport[2]> <;> <CSVformat[1]> <;> <FlagsReceipts[1]> <;> <FlagsReports[1]> <;> <'N'> <;> <StartRcpNum[6]> <;> <EndRcpNum[6]>

**output:** ACK+

**FPR operation:** Read or Store Electronic Journal Report from receipt number to receipt number, CSV format option and document content. If CSV format is set the content can includes only fiscal receipts. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

**Input data:**

*StorageReport* (EJ Report storage) 1 character with value

- 'j0' – To PC

- 'j2' – To USB Flash Drive

- 'j4' – To SD card

*CSVformat* 1 symbol with value:

- 'C' – Yes



- 'X' - No  
*FlagsReceipts* (Receipts included in EJ) 1 symbol for Receipts included in EJ:  
 Flags.7=0  
 Flags.6=1  
 Flags.5=1 Yes, Flags.5=0 No (Include PO)  
 Flags.4=1 Yes, Flags.4=0 No (Include RA)  
 Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)  
 Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)  
 Flags.1=1 Yes, Flags.1=0 No (Include Invoice)  
 Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)  
 ',' 1 symbol with value ','  
*FlagsReports* (Reports included in EJ) 1 symbol for Reports included in EJ:  
 Flags.7=0  
 Flags.6=1  
 Flags.5=0  
 Flags.4=1 Yes, Flags.4=0 No (Include FM reports)  
 Flags.3=1 Yes, Flags.3=0 No (Include Other reports)  
 Flags.2=1 Yes, Flags.2=0 No (Include Daily X)  
 Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)  
 Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)  
 'N' 1 symbol 'N'  
*StartRcpNum* 6 symbols for initial receipt number included in report in format #####.  
*EndRcpNum* 6 symbols for final receipt number included in report in format #####.

**Output data: n. a.**

**zfpdef:** ReadEJByReceiptNumCustom(StorageReport, CSVformat,FlagsReceipts, FlagsReports, StartNo, EndNo)

## 2.9.5. Command: 7Ch / | – Reading Electronic Journal report from number Z report to number Z report

**input:** <ReportFormat[2]> <;> <'Z'> <;> <StartNo[4]> <;> <EndNo[4]>

**output:** ACK+

**FPR operation:** Reading Electronic Journal Report by number of Z report blocks.

**Input data:**

*ReportFormat* (EJ Report format) 1 character with value  
 - 'J0' – Detailed EJ  
 - 'J8' – Brief EJ  
 'Z' 1 symbol 'Z'  
*StartNo* 4 symbols for initial number report in format ####  
*EndNo* 4 symbols for final number report in format ####

**Output data: n. a.**

**zfpdef:** ReadEJByZBlocks(ReportFormat, StartNo, EndNo)

## 2.9.6. Command: 7Ch / | – Read/Store Electronic Journal report by number of Z report blocks with selected documents content and format

**input:** <StorageReport[2]> <;> <CSVformat[1]> <;> <FlagsReceipts[1]> <;>  
 <FlagsReports[1]> <;> <'Z'> <;> <StartZNum[4]> <;> <EndZNum[4]>

**output:** ACK+

**FPR operation:** Read or Store Electronic Journal Report by number of Z report blocks, CSV format option and document content. If CSV format is set the content can includes only fiscal receipts. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

**Input data:**

*StorageReport* (EJ Report storage) 1 character with value  
 - 'j0' – To PC

- 'j2' – To USB Flash Drive  
 - 'j4' – To SD card  
*CSVformat* 1 symbol with value:  
 - 'C' – Yes  
 - 'X' - No  
*FlagsReceipts* (Receipts included in EJ) 1 symbol for Receipts included in EJ:  
 Flags.7=0  
 Flags.6=1  
 Flags.5=1 Yes, Flags.5=0 No (Include PO)  
 Flags.4=1 Yes, Flags.4=0 No (Include RA)  
 Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)  
 Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)  
 Flags.1=1 Yes, Flags.1=0 No (Include Invoice)  
 Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)  
 ','  
 ;  
*FlagsReports* (Reports included in EJ) 1 symbol for Reports included in EJ:  
 Flags.7=0  
 Flags.6=1  
 Flags.5=0  
 Flags.4=1 Yes, Flags.4=0 No (Include FM reports)  
 Flags.3=1 Yes, Flags.3=0 No (Include Other reports)  
 Flags.2=1 Yes, Flags.2=0 No (Include Daily X)  
 Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)  
 Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)  
 'Z'  
 1 symbol 'Z'  
*StartZNum* 4 symbols for initial number report in format #####  
*EndZNum* 4 symbols for final number report in format #####

**Output data: n. a.**

**zfpdef:** ReadEJByZBlocksCustom(StorageReport, CSVformat, FlagsReceipts, FlagsReports, StartNo, EndNo)

## 2.9.7. Command: 7Ch / | – Read Electronic Journal report from beginning to end

**input:** <ReportFormat[2]> <;> <'\*'\*>

**output:** ACK+

**FPR operation:** Read Electronic Journal report with all documents.

**Input data:**

*ReportFormat* (EJ Report format) 1 character with value  
 - 'J0' – Detailed EJ  
 - 'J8' – Brief EJ  
 '\*'  
 1 symbol '\*'

**Output data: n. a.**

**zfpdef:** ReadEJ(ReportFormat)

### 2.9.8. Command: 7Ch / | – Read/Store Electronic Journal report from beginning to end with selected documents content and format

**input:** <StorageReport[2]> <;> <CSVformat[1]> <;> <FlagsReceipts[1]> <;>  
<FlagsReports[1]> <;> <'\*'\*>

**output: ACK+**

**FPR operation:** Read or Store Electronic Journal report by CSV format option and document content selecting. If CSV format is set the content can includes only fiscal receipts. FlagsReceipts is a char with bits representing the receipt types. FlagsReports is a char with bits representing the report type.

#### **Input data:**

**StorageReport** (EJ Report storage) 1 character with value  
- 'j0' – To PC  
- 'j2' – To USB Flash Drive  
- 'j4' – To SD card

**CSVformat** 1 symbol with value:  
- 'C' – Yes  
- 'X' - No

**FlagsReceipts** (Receipts included in EJ) 1 symbol for Receipts included in EJ:  
Flags.7=0  
Flags.6=1  
Flags.5=1 Yes, Flags.5=0 No (Include PO)  
Flags.4=1 Yes, Flags.4=0 No (Include RA)  
Flags.3=1 Yes, Flags.3=0 No (Include Credit Note)  
Flags.2=1 Yes, Flags.2=0 No (Include Storno Rcp)  
Flags.1=1 Yes, Flags.1=0 No (Include Invoice)  
Flags.0=1 Yes, Flags.0=0 No (Include Fiscal Rcp)

**FlagsReports** (Reports included in EJ) 1 symbol for Reports included in EJ:  
Flags.7=0  
Flags.6=1  
Flags.5=0  
Flags.4=1 Yes, Flags.4=0 No (Include FM reports)  
Flags.3=1 Yes, Flags.3=0 No (Include Other reports)  
Flags.2=1 Yes, Flags.2=0 No (Include Daily X)  
Flags.1=1 Yes, Flags.1=0 No (Include Daily Z)  
Flags.0=1 Yes, Flags.0=0 No (Include Duplicates)

**'\*'**  
1 symbol '\*'

#### **Output data: n. a.**

**zfpdef:** ReadEJCustom(StorageReport, CSVformat, FlagsReceipts, FlagsReports)

## 2.10. NETWORK SETTINGS COMMANDS

Set of commands for network settings.

### 2.10.1. Command: 4Eh / N – Read last sent and first unsent receipts info

**input:** <Option['R']> <;> <'R'><;><'R'>

**output:** <LastSentRcpNum[1..6]> <;> <LastSentRcpDateTime "DD-MM-YYYY HH:MM">  
<;> <FirstUnsentRcpNum[1..6]> <;> <FirstUnsentRcpDateTime "DD-MM-YYYY HH:MM"> <;>  
<NRA\_ErrorMessage[100]>

**FPR operation:** Provides information about last sent receipt number and date time to NRA server and first unsent receipt number and date time to NRA. If there is no unsent receipt the number will be 0 and date time will be 00-00-0000 00:00 Parameter NRA\_ErrorMessage provide error message from NRA server if exist. Command is not allowed if device is deregistered, not fiscalized or in opened receipt.

**Input data :**

|        |                         |
|--------|-------------------------|
| Option | 1 symbol with value 'R' |
| 'R'    | 1 symbol with value 'R' |
| 'R'    | 1 symbol with value 'R' |

**Output data:**

|                        |   |
|------------------------|---|
| LastSentRcpNum         | Up to 6 symbols for the last sent receipt number to NRA server  |
| LastSentRcpDateTime    | 16 symbols for the date and time of the last sent receipt to NRA server in format DD-MM-YYYY HH:MM    |
| FirstUnsentRcpNum      | Up to 6 symbols for the first unsent receipt number to NRA server                                     |
| FirstUnsentRcpDateTime | 16 symbols for the date and time of the first unsent receipt to NRA server in format DD-MM-YYYY HH:MM |
| NRA_ErrorMessage       | Up to 100 symbols for error message from NRA server, if exist   |

**zfpdef:** [ReadSentRcpInfoStatus\(\)](#)

### **3. SOFTWARE APPLICATION REQUIREMENTS**

#### **3.1. RULES FOR USING THE COMMANDS**

The commands should be used observing the following rules:

- Do not send a subsequent command prior to receiving a response of the preceding one.
- Observe the sequence of sent and received messages.
- The number of the message in every subsequent command should differ from that in the preceding one.
- Observe the two status bites of the Acknowledgment response.
- When the information received is insufficient request detailed status information – Command 20h.
- Use unpacked messages to check the standby status of the FD.

#### **3.2. SAMPLE SALE TRANSACTION OF FD**

The sale transaction controlled by a software application (SA) is a procedure, which consists of several commands, of which obligatory are: initiation of customer fiscal receipt (command 30h), sale registration (command 31h or 32h), payment (command 35h) and finalization of the fiscal receipt (command 38h).

Sample command sequence for issuing a customer fiscal receipt:

- fiscal receipt opening (command 30h) – contains information about the operator's number and password, the type of receipt – detailed/brief, with/without VAT printing.
- sale registration (command 31h) – contains information about the article's name, price and VAT group as well as non-compulsory information about the quantity sold and value/percent discount/addition;
- subtotal amount (command 33h) – contains non-compulsory parameters for printing, external display visualization and value/percent discount/addition of the amount accumulated;
- current receipt information (command 72h) – requires a response from the FD, which contains the current parameters of the receipt, the number of sales, the accumulated amounts by VAT groups, information about initiated or finalized payments;
- calculation and payment of VAT on VAT account (command 36h) – performs automatic calculation of VAT in the receipt and its payment on VAT account;
- payment (command 35h) – contains information about the amount due and type of payment, which may cover partially or in full the grand total amount due as well as a parameter for calculation of change due;
- fiscal receipt closure (command 38h).

#### 4. AUXILARY GS PROTOCOL (COMMANDS 1Dh)

| GS command  | Message from the AS  | FP Answer  |
|-------------|--|--|
| Information | <1Dh><Info><br>where:<br><b>Info</b> – character 49h - 'I' | <'I'><Number of printable characters per line[2]><br><;> <PLU number[5]><br><;> <Departments number[2]><br><;> <Operators number[2]><br><;> <VAT classs number[1]><br><;> <header lines number[2]><br><;> <payments number[2]><br><;> <logo number[2]><br><;> <reserve='00'[2]><br><;> <receipt transaction number[3]><br><;> <customers base info [4]><br><0Ah>   |
| Model       | <1Dh><Model><br>where:<br>Model – character 77h - 'M'      | <'M'> <country[2]><br><;> <encoding[1..20]><br><;> <device type [2]><br><;> <license No[2..4]><br><;> <license date [10]><br><;> <interfaces[1..40]><br><;> <current interface[1..4]><br><;> <battery support[0..12]><br><;> <current battery suplay ('E' or 'B') [1]><br><;> <sleep mode [1] ><br><;> < Sd card journal [1]><br><;> <SD card format [1..4]><br><;> <SD card additional DB [1]><br><;> <server exchange[1]><br><;> < Number of printable characters per line[2]><br><;> <number of printable free text[2]><br><;> <article name symbols in command[2]><br><;> <printable article name symbols[2]><br><;> <department name symbols in command[2]><br><;> <printable department name symbols[2]><br><;> <department first number[1]><br><;> <PLU last number[5]><br><;> <total number of headers><br><;> <number of fiscal headers only><br><;> <number of footers><br><0Ah> |