



Maximum
likelihood
identification

Xing Chao

Maximum likelihood identification

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Xing Chao

School of Astronautics, Northwestern Polytechnical University



Maximum
likelihood
identification

Xing Chao

Identification criterion The probability of the observed value is the largest

likelihood function Probability density function of observed values

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula



Maximum
likelihood
identification

Xing Chao

- ① It can be applied to correlated noises $\xi(k)$;
- ② When the system SNR is relatively small, it has a better estimation effect ;
- ③ The algorithm has good stability ;
- ④ There is recursive calculation method ;
- ⑤ It is widely used in practical engineering

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise
Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

A discrete stochastic process $\{V_k\}$ is related to θ , parameters to be identified. The probability distribution density $f(V_k|\theta)$ is known. If n independent observations are measured as V_1, V_2, \dots, V_n , Its distribution density is $f(V_1|\theta), \dots, f(V_n|\theta)$, Define likelihood function L as:

$$L(V_1, \dots, V_n|\theta) = f(V_1|\theta) \cdot f(V_2|\theta) \cdots f(V_n|\theta)$$



The principle of identifying θ is to make the L reach the maximum:

$$\frac{\partial L}{\partial \theta} = 0$$

Usually the logarithm of the L is taken:

$$\ln L = \ln f(V_1|\theta) + \cdots + \ln f(V_n|\theta)$$

result is:

$$\frac{\partial \ln L}{\partial \theta}$$

Obtained θ is maximum likelihood estimation $\hat{\theta}_{ML}$

Maximum likelihood identification of difference equations: system model (white noise case)



Maximum
likelihood
identification

Xing Chao

System difference equation:

$$a(z^{-1})y(k) = b(z^{-1})u(k) + \xi(k)$$

where $\xi(k)$ is Gauss white noise sequence and is uncorrelated to $u(k)$. Represented in vector form:

$$Y_N = \Phi_N \theta + \xi$$

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Maximum likelihood identification of difference equations: residual (white noise)



System estimation residual:

$$\begin{aligned}e_N &= Y_N - \Phi_N \hat{\theta} \\e_N &= [e(n+1), e(n+2), \dots, e(n+N)]^T\end{aligned}$$

Since $\xi(k)$ is gaussian white noise, it is assumed that $e(k)$ is also the Gauss white noise. Let $e(k)$ variance be σ^2 .

Probability density function is:

$$p(e(k)|\hat{\theta}) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{e^2(k)}{2\sigma^2}}$$

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Maximum likelihood identification of difference equations: likelihood function (white noise case)



likelihood function is,

$$\begin{aligned}L(Y_N|\hat{\theta}) &= \prod_{k=n+1}^{n+N} p(e(k)|\hat{\theta}) \\&= \frac{1}{(2\pi\sigma^2)^{N/2}} \exp\left[-\frac{\sum e^2(k)}{2\sigma^2}\right] \\&= \frac{1}{(2\pi\sigma^2)^{N/2}} \exp\left[-\frac{(Y_N - \Phi_N\hat{\theta})^T(Y_N - \Phi_N\hat{\theta})}{2\sigma^2}\right] \\ \ln L(Y_N|\hat{\theta}) &= -\frac{N}{2} \ln 2\pi - \frac{N}{2} \ln \sigma^2 - \frac{(Y_N - \Phi_N\hat{\theta})^T(Y_N - \Phi_N\hat{\theta})}{2\sigma^2}\end{aligned}$$

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula

Maximum likelihood identification of difference equations: likelihood function (white noise case)



According to the principle of maximum likelihood identification:

$$\frac{\partial \ln L(Y_N | \hat{\theta})}{\partial \hat{\theta}} = \frac{\Phi_N^T Y_N - \Phi_N^T \Phi_N \hat{\theta}}{\sigma^2} = 0$$

$$\frac{\partial \ln L(Y_N | \hat{\theta})}{\partial \hat{\sigma}^2} = -\frac{N}{2\sigma^2} + \frac{(Y_N - \Phi_N \hat{\theta})^T (Y_N - \Phi_N \hat{\theta})}{2\sigma^4} = 0$$

solve equations :

$$\begin{aligned}\hat{\theta}_{ML} &= (\Phi_N^T \Phi_N)^{-1} \Phi_N^T Y_N \\ \sigma^2 &= \frac{(Y_N - \Phi_N \hat{\theta})^T (Y_N - \Phi_N \hat{\theta})}{N}\end{aligned}$$

It is shown that in the special case of $\xi(k)$ being Gauss white noise sequence, the maximum likelihood identification has the same result as the general least squares identification.

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Maximum likelihood identification of difference equations: a system model (colored noise case)



Maximum
likelihood
identification

Xing Chao

$$a(z^{-1})y(k) = b(z^{-1})u(k) + c(z^{-1})\varepsilon(k)$$

其中:

$$a(z^{-1}) = 1 + a_1z^{-1} + \cdots + a_nz^{-n}$$

$$b(z^{-1}) = b_0 + b_1z^{-1} + \cdots + b_nz^{-n}$$

$$c(z^{-1}) = 1 + c_1z^{-1} + \cdots + c_nz^{-n}$$

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Maximum likelihood identification of difference equations: prediction error (colored noise case)

prediction error:

$$e(k) = y(k) - \hat{y}(k)$$

vector form is:

$$e_N = Y_N - \Phi_N \hat{\theta}$$

where:

$$\begin{aligned}\hat{\theta} &= [\hat{a}_1, \dots, \hat{a}_n, \hat{b}_0, \dots, \hat{b}_n, \hat{c}_1, \dots, \hat{c}_n]^T \\ Y_N &= [y(n+1), \dots, y(n+N)]^T \\ e_N &= [e(n+1), \dots, e(n+N)]^T \\ \Phi_N &= \begin{bmatrix} -y_n & \cdots & -y_1 & u_{n+1} & \cdots & u_1 & e_n & \cdots & e_1 \\ -y_{n+1} & \cdots & -y_2 & u_{n+2} & \cdots & u_2 & e_{n+1} & \cdots & e_2 \\ \vdots & & \vdots & \vdots & & \vdots & \vdots & \vdots & \vdots \\ -y_{n+N-1} & \cdots & -y_N & u_{n+N} & \cdots & u_N & e_{n+N-1} & \cdots & e_N \end{bmatrix}\end{aligned}$$

Maximum likelihood identification of difference equations: likelihood function (colored noise case)



Since $\varepsilon(k)$ is Gauss white noise, $e(k)$ can be assumed to be the zero mean Gauss white noise. Then the likelihood function is:

$$L(Y_N|\hat{\theta}) = \frac{1}{(2\pi\sigma^2)^{N/2}} \exp\left[-\frac{(Y_N - \phi_N\hat{\theta})^T(Y_N - \phi_N\hat{\theta})}{2\sigma^2}\right]$$

$$\ln L(Y_N|\hat{\theta}) = -\frac{N}{2} \ln 2\pi - \frac{N}{2} \ln \sigma^2 - \frac{1}{2\sigma^2} \sum_{k=n+1}^{n+N} e^2(k)$$

From $\frac{\partial \ln L(Y_N|\hat{\theta})}{\partial \sigma^2} = 0$:

$$\hat{\sigma}^2 = \frac{1}{N} \sum_{k=n+1}^{n+N} e^2(k)$$

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula

Maximum likelihood identification of difference equations: criteria (colored noise case)



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

$$J = \frac{1}{2} \sum_{k=n+1}^{n+N} e^2(k)$$

$$\sigma^2 = \frac{2}{N} J$$

$$\ln L(Y_N|\hat{\theta}) = -\frac{N}{2} \ln 2\pi - \frac{N}{2} \ln\left(\frac{2J}{N}\right) - \frac{N}{2}$$

- J is a quadratic form function of parameter $a_1, a_2, \dots, a_n; b_0, b_1, \dots, b_n; c_1, c_2, \dots, c_n$.
- The maximum L of $\hat{\theta}$, is equivalent to find $\hat{\theta}$ with minimum J under the constraint conditions,

$$\hat{c}(z^{-1})e(k) = \hat{a}(z^{-1})y(k) - \hat{b}(z^{-1})u(k)$$

The difference of maximum likelihood identification equation: Newton-Raphson



Maximum
likelihood
identification

Xing Chao

Newton-Raphson iteration:

$$\hat{\theta}_1 = \hat{\theta}_0 - \left[\left(\frac{\partial^2 J}{\partial \theta^2} \right)^{-1} \frac{\partial J}{\partial \theta} \right] \bigg|_{\theta = \hat{\theta}_0}$$

where:

- $\frac{\partial J}{\partial \theta}$ is gradient
- $\frac{\partial^2 J}{\partial \theta^2}$ is Hessian matrix

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula



Maximum
likelihood
identification

Xing Chao

$$\hat{\theta}_0 = [\hat{a}_1, \dots, \hat{a}_n, \hat{b}_0, \dots, \hat{b}_n, \hat{c}_1, \dots, \hat{c}_n]^T$$

where:

- $\hat{a}_1, \dots, \hat{a}_n, \hat{b}_0, \dots, \hat{b}_n$ can be obtained by least squares method
- $\hat{c}_1, \dots, \hat{c}_n$ can be zeros or arbitrarily assumed

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula



- Prediction error, cost function and estimation of error variance:

$$\begin{aligned}e(k) &= y(k) - \hat{y}(k) \\ J &= \frac{\sum_{k=n+1}^{n+N} e^2(k)}{2} \\ \sigma^2 &= \frac{2J}{N}\end{aligned}$$

Newton-Raphson iterative procedure: gradient matrix and Hessian matrix

$$\begin{aligned}\frac{\partial J}{\partial \theta} &= \sum_{k=n+1}^{n+N} e(k) \frac{\partial e(k)}{\partial \theta} \\ \frac{\partial^2 J}{\partial \theta^2} &= \sum_{k=n+1}^{n+N} \frac{\partial e(k)}{\partial \theta} \left[\frac{\partial e(k)}{\partial \theta} \right]^T + \sum_{k=n+1}^{n+N} e(k) \frac{\partial^2 e(k)}{\partial \theta^2} \\ &\approx \sum_{k=n+1}^{n+N} \frac{\partial e(k)}{\partial \theta} \left[\frac{\partial e(k)}{\partial \theta} \right]^T\end{aligned}$$

where:

$$\frac{\partial e(k)}{\partial \theta} = \left[\frac{\partial e(k)}{\partial a_1}, \dots, \frac{\partial e(k)}{\partial a_n}, \frac{\partial e(k)}{\partial b_0}, \dots, \frac{\partial e(k)}{\partial b_n}, \frac{\partial e(k)}{\partial c_1}, \dots, \frac{\partial e(k)}{\partial c_n} \right]^T$$



$$\hat{\theta}_1 = \hat{\theta}_0 - \left[\left(\frac{\partial^2 J}{\partial \theta^2} \right)^{-1} \frac{\partial J}{\partial \theta} \right] \bigg|_{\theta = \hat{\theta}_0}$$

stop criterion:

$$\frac{\hat{\sigma}_{r+1}^2 - \hat{\sigma}_r^2}{\hat{\sigma}_r^2} < \delta$$

where δ can be small number, i.e. $\delta = 10^{-4}$.

System difference equation



Maximum
likelihood
identification

Xing Chao

where:

$$\begin{aligned}a(z^{-1}) &= 1 + a_1 z^{-1} + \cdots + a_n z^{-n} \\b(z^{-1}) &= b_0 + b_1 z^{-1} + \cdots + b_n z^{-n} \\c(z^{-1}) &= 1 + c_1 z^{-1} + \cdots + c_n z^{-n}\end{aligned}$$

can be written as:

$$\varepsilon(k) = c^{-1}(z^{-1})[a(z^{-1})y(k) - b(z^{-1})u(k)]$$

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula



The cost function is approximately represented as a quadratic form:

$$\begin{aligned} J_N &= \sum_{k=n+1}^{n+N} \varepsilon^2(k) \\ &\approx (\boldsymbol{\theta} - \hat{\boldsymbol{\theta}}_N)^T \mathbf{P}_N^{-1} (\boldsymbol{\theta} - \hat{\boldsymbol{\theta}}_N) + \beta_N \end{aligned}$$



Using Taylor series expand $\varepsilon(k)$ at estimated $\hat{\theta}$:

$$\varepsilon(k) \approx \varepsilon(k, \hat{\theta}) + \left[\frac{\partial \varepsilon(k, \theta)}{\partial \theta} \right]^T \bigg|_{\hat{\theta}} (\theta - \hat{\theta})$$

where:

$$\begin{aligned} \varepsilon(k, \hat{\theta}) &= e(k) \\ e(k) &= \hat{c}^{-1}(z^{-1})[\hat{a}(z^{-1})y(k) - \hat{b}(z^{-1})u(k)] \end{aligned}$$



Result:

$$\begin{aligned}
 J_{N+1} &= \sum_{k=n+1}^{n+N+1} \varepsilon^2(k) \\
 &\approx (\boldsymbol{\theta} - \hat{\boldsymbol{\theta}}_N)^T \mathbf{p}_N^{-1} (\boldsymbol{\theta} - \hat{\boldsymbol{\theta}}_N) \\
 &\quad + \beta_N + [e_{N+1} + \boldsymbol{\psi}_{N+1}^T (\boldsymbol{\theta} - \hat{\boldsymbol{\theta}}_N)]^2
 \end{aligned}$$

where:

$$\begin{aligned}
 e_{N+1} &= e(n + N + 1) \\
 \boldsymbol{\psi}_{N+1} &= \frac{\partial e_{N+1}}{\partial \hat{\boldsymbol{\theta}}}
 \end{aligned}$$

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise
Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Let:

$$\theta - \hat{\theta} = \Delta$$

result:

$$\begin{aligned} J_{N+1}(\theta) &= \Delta^T (P_N^{-1} + \Psi_{N+1} \Psi_{N+1}^T) \Delta \\ &\quad + 2e_{N+1} \Psi_{N+1}^T \Delta + e_{N+1}^2 + \beta_N \\ &= (\Delta + r_{N+1})^T P_{N+1}^{-1} (\Delta + r_{N+1}) + \beta_{N+1} \end{aligned}$$

where:

$$\begin{aligned} P_{N+1}^{-1} &= P_N^{-1} + \Psi_{N+1} \Psi_{N+1}^T \\ r_{N+1} &= P_{N+1} \Psi_{N+1} e_{N+1} \\ \beta_{N+1} &= e_{N+1}^2 + \beta_N - e_{N+1} \Psi_{N+1}^T P_{N+1} \Psi_{N+1} e_{N+1} \end{aligned}$$

β_{N+1} is known, so J_{N+1} is minimum when:

$$\hat{\theta}_{N+1} = \hat{\theta}_N - r_{N+1}$$



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula

update $\mathbf{P}_{N+1}, \hat{\boldsymbol{\theta}}_{N+1}$

By using the inverse lemma of matrices, we obtain:

$$\mathbf{P}_{N+1}^{-1} = \mathbf{P}_N^{-1} + \boldsymbol{\Psi}_{N+1} \boldsymbol{\Psi}_{N+1}^T$$

$$\mathbf{P}_{N+1} = \mathbf{P}_N \left[\mathbf{I} - \frac{\boldsymbol{\Psi}_{N+1} \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N}{1 + \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1}} \right]$$

$$\mathbf{r}_{N+1} = \mathbf{P}_{N+1} \boldsymbol{\Psi}_{N+1} \mathbf{e}_{N+1}$$

$$= \mathbf{P}_N \left[\mathbf{I} - \frac{\boldsymbol{\Psi}_{N+1} \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N}{1 + \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1}} \right] \boldsymbol{\Psi}_{N+1} \mathbf{e}_{N+1}$$

$$= \mathbf{P}_N \left[\frac{1 + \boldsymbol{\Psi}_{N+1} \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1} - \boldsymbol{\Psi}_{N+1} \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1}}{1 + \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1}} \right] \mathbf{e}_{N+1}$$

$$= \frac{\mathbf{P}_N \boldsymbol{\Psi}_{N+1} \mathbf{e}_{N+1}}{1 + \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1}}$$

$$\hat{\boldsymbol{\theta}}_{N+1} = \hat{\boldsymbol{\theta}}_N - \mathbf{r}_{N+1}$$

$$= \hat{\boldsymbol{\theta}}_N - \mathbf{P}_N \boldsymbol{\Psi}_{N+1} (1 + \boldsymbol{\Psi}_{N+1}^T \mathbf{P}_N \boldsymbol{\Psi}_{N+1})^{-1} \mathbf{e}_{N+1}$$

update Ψ_{N+1}



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formula

$$\Psi_{N+1} = \begin{bmatrix} A & 0 & 0 \\ 0 & B & 0 \\ 0 & 0 & C \end{bmatrix} \Psi_N + D$$

where:

$$A = \begin{bmatrix} -\hat{c}_1 & \cdots & \cdots & -\hat{c}_n \\ 1 & \cdots & \cdots & 0 \\ & \ddots & & \vdots \\ & & 1 & 0 \end{bmatrix}$$



Maximum likelihood identification

Xing Chao

Introduction

Maximum likelihood principle

Maximum likelihood identification

White noise

Colored noise situation

Recursive Maximum Likelihood Method

Approximately Recursive Maximum Likelihood Method

Newton-Raphson recursive formular

$$B = \begin{bmatrix} -\hat{c}_1 & \cdots & \cdots & -\hat{c}_n & 0 \\ 1 & \cdots & \cdots & 0 & 0 \\ & \ddots & & \vdots & \vdots \\ & & 1 & 0 & 0 \end{bmatrix}$$

$$C = \begin{bmatrix} -\hat{c}_1 & \cdots & \cdots & -\hat{c}_n \\ 1 & \cdots & \cdots & 0 \\ & \ddots & & \vdots \\ & & 1 & 0 \end{bmatrix}$$

$$D = [y_{n+N}, 0, \cdots, 0, -u_{n+N+1}, 0, \cdots, 0, -e_{n+N}, 0, \cdots, 0]^T$$

deduction of A, B, C

from

$$e(k) = \hat{c}^{-1}(z^{-1})[\hat{a}(z^{-1})y(k) - \hat{b}(z^{-1})u(k)]$$

get:

$$\frac{\partial e(k)}{\partial \hat{a}_i} = \hat{c}^{-1}(z^{-1})y(k-i)$$

$$\frac{\partial e(k)}{\partial \hat{b}_i} = -\hat{c}^{-1}(z^{-1})u(k-i)$$

$$\frac{\partial e(k)}{\partial \hat{c}_i} = -\hat{c}^{-1}(z^{-1})e(k-i)$$

then:

$$\frac{\partial e(k)}{\partial \hat{a}_i} = \frac{\partial e(k-i+j)}{\partial \hat{a}_j}$$

$$\frac{\partial e(k)}{\partial \hat{b}_i} = \frac{\partial e(k-i+j)}{\partial \hat{b}_j}$$

$$\frac{\partial e(k)}{\partial \hat{c}_i} = \frac{\partial e(k-i+j)}{\partial \hat{c}_j}$$



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

Recursive formular using Newton-Raphson method: system difference equation



Maximum
likelihood
identification

Xing Chao

where:

$$a(z^{-1}) = 1 + a_1 z^{-1} + \cdots + a_n z^{-n}$$

$$b(z^{-1}) = b_0 + b_1 z^{-1} + \cdots + b_n z^{-n}$$

$$d(z^{-1}) = 1 + d_1 z^{-1} + \cdots + d_n z^{-n}$$

parameter vectors are:

$$\mathbf{a} = [a_1, a_2, \cdots, a_n]^T$$

$$\mathbf{b} = [b_0, b_1, \cdots, b_n]^T$$

$$\mathbf{d} = [d_1, d_2, \cdots, d_n]^T$$

$$\boldsymbol{\theta} = [\mathbf{a}^T, \mathbf{b}^T, \mathbf{d}^T]^T$$

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

compute $\frac{\partial \varepsilon(k)}{\partial \theta}$



rewrite system difference equation as:

$$\varepsilon(k) = d(z^{-1})[a(z^{-1})y(k) - b(z^{-1})u(k)]$$

result:

$$\frac{\partial \varepsilon(k)}{\partial a_j} = d(z^{-1})y(k-j) = y_{k-j}^F, j = 1, 2, \dots, n$$

$$\frac{\partial \varepsilon(k)}{\partial b_j} = -d(z^{-1})u(k-j) = u_{k-j}^F, j = 0, 1, 2, \dots, n$$

$$\frac{\partial \varepsilon(k)}{\partial d_j} = a(z^{-1})y(k-j) - b(z^{-1})u(k-j) = -\mu_{k-j}, j = 1, 2, \dots, n$$

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise
Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

compute $\frac{\partial \varepsilon(k)}{\partial \theta}$



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise
Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular

$$\frac{\partial \varepsilon(k)}{\partial \theta} = \begin{bmatrix} \bar{y}_{(n)}^F \\ -\bar{u}_{(n+1)}^F \\ -\bar{\mu}_{(n)} \end{bmatrix}$$

where:

$$\begin{aligned} \bar{y}_{(n)}^F &= [y_{k-1}^F, y_{k-2}^F, \dots, y_{k-n}^F]^T \\ -\bar{u}_{(n+1)}^F &= [u_k^F, u_{k-1}^F, \dots, u_{k-n}^F]^T \\ -\bar{\mu}_{(n)} &= [\mu_{k-1}, \mu_{k-2}, \dots, \mu_{k-n}]^T \end{aligned}$$

compute $\frac{\partial^2 \varepsilon(k)}{\partial \theta^2}$



Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
resursive formular

$$\frac{\partial^2 \varepsilon(k)}{\partial \theta^2} = \begin{bmatrix} \frac{\partial^2 \varepsilon(k)}{\partial a^2} & \frac{\partial^2 \varepsilon(k)}{\partial a \partial b} & \frac{\partial^2 \varepsilon(k)}{\partial a \partial d} \\ \frac{\partial^2 \varepsilon(k)}{\partial b \partial a} & \frac{\partial^2 \varepsilon(k)}{\partial b^2} & \frac{\partial^2 \varepsilon(k)}{\partial b \partial d} \\ \frac{\partial^2 \varepsilon(k)}{\partial d \partial a} & \frac{\partial^2 \varepsilon(k)}{\partial d \partial b} & \frac{\partial^2 \varepsilon(k)}{\partial d^2} \end{bmatrix}$$

where:

$$\frac{\partial^2 \varepsilon(k)}{\partial a_j \partial d_m} = \frac{\partial^2 \varepsilon(k)}{\partial d_m \partial a_j} = y(k - j - m)$$

$$\frac{\partial^2 \varepsilon(k)}{\partial b_j \partial d_m} = \frac{\partial^2 \varepsilon(k)}{\partial d_m \partial b_j} = -u(k - j - m)$$



gradient:

$$\frac{\partial J}{\partial \hat{\theta}} = \sum_{k=n+1}^{n+N} e(k) \frac{\partial e(k)}{\partial \hat{\theta}} = q(N)$$

Hessian Matrix:

$$\frac{\partial^2 J}{\partial \hat{\theta}^2} = \sum_{k=n+1}^{n+N} \left[\frac{\partial e(k)}{\partial \hat{\theta}} \left(\frac{\partial e(k)}{\partial \hat{\theta}} \right)^T + e(k) \frac{\partial^2 e(k)}{\partial \hat{\theta}^2} \right] = R(N)$$

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
recursive formular



Newton-Raphson formular:

$$\hat{\theta}_r = \hat{\theta}_{r-1} - R^{-1}(N)q(N)$$

iteration formular for q and R :

$$\begin{aligned} q(N) &= q(N-1) + e(n+N) \frac{\partial e(n+N)}{\partial \hat{\theta}} \\ R(N) &= R(N-1) + \frac{\partial e(n+N)}{\partial \hat{\theta}} \left(\frac{\partial e(n+N)}{\partial \hat{\theta}} \right)^T \\ &\quad + e(n+N) \frac{\partial^2 e(n+N)}{\partial \hat{\theta}^2} \end{aligned}$$

Maximum
likelihood
identification

Xing Chao

Introduction

Maximum
likelihood
principle

Maximum
likelihood
identification

White noise

Colored noise
situation

Recursive
Maximum
Likelihood
Method

Approximately
Recursive Maximum
Likelihood Method

Newton-Raphson
resursive formular