



deeplearning.ai

Case Studies

**Why look at
case studies?**

Outline

Classic networks:

- LeNet-5 ←
- AlexNet ←
- VGG ←

ResNet (152)

Inception




deeplearning.ai

Case Studies

**Classic
networks**

LeNet - 5



60K parameters.

$n_H, n_W \downarrow$

$n_C \uparrow$

non-linearly
over pooling

$n_H \times n_W \times n_C$


$f \times f \times n_C$

conv pool conv pool fc fc output

Activation: sigmoid/tanh ReLU



AlexNet



- Similar to LeNet, but much bigger.

- ReLU

- Multiple GPUs.

- Local Response Normalization (LRN)




~60M parameters

VGG - 16

CONV = 3x3 filter, s = 1, same

VGG-19

MAX-POOL = 2x2, s = 2



224x224x3

[CONV 64]
2

224x224x64

POOL

112x112x64

[CONV 128]
2

112x112x128

POOL

56x56x128

[CONV 256]
3

56x56x256

POOL

28x28x256

[CONV 512]
3

28x28x512

POOL

14x14x512

[CONV 512]
3

14x14x512

POOL

7x7x512

FC
4096

FC
4096

Softmax
1000

$n_h, n_w \downarrow$

$n_c \uparrow$

~138M






deeplearning.ai


Case Studies

Residual Networks (ResNets)

Residual block



"short cut" / skip connection



"main path"

$$z^{[l+1]} = W^{[l+1]} a^{[l]} + b^{[l+1]}$$


$$a^{[l+1]} = g(z^{[l+1]})$$

$$z^{[l+2]} = W^{[l+2]} a^{[l+1]} + b^{[l+2]}$$


~~$$a^{[l+2]} = g(z^{[l+2]})$$~~

$$a^{[l+2]} = g(z^{[l+2]} + a^{[l]})$$


Residual Network



Plain



ResNet






deeplearning.ai


Case Studies

**Network in Network
and 11 convolutions**

Why does a 1 1 convolution do?



Using 11 convolutions






deeplearning.ai


Case Studies

Inception network motivation


Motivation for inception network



The problem of computational cost



Using 11 convolution






deeplearning.ai

Case Studies

Inception network

Inception module



GoLeNet



