




deeplearning.ai

# One hidden layer Neural Network

---

## **Derivatives of activation functions**

# Sigmoid activation function



$$g(z) = \frac{1}{1 + e^{-z}}$$

$$a = g(z) = \frac{1}{1 + e^{-z}}$$

$$\boxed{g'(z)} = \boxed{\frac{d}{dz} g(z)} = \text{slope of } g(z) \text{ at } z$$

$$= \frac{1}{1 + e^{-z}} \left( 1 - \frac{1}{1 + e^{-z}} \right)$$

$$= g(z) (1 - g(z)) \leftarrow$$

$$= \boxed{a(1-a)} \quad \left| \begin{array}{l} g'(z) = a(1-a) \\ \uparrow \\ a \end{array} \right.$$

$$z = 10, \quad g(z) \approx 1$$

$$\frac{d}{dz} g(z) \approx 1(1-1) \approx 0$$


$$z = -10, \quad g(z) \approx 0$$

$$\frac{d}{dz} g(z) \approx 0(1-0) \approx 0$$

$$z = 0, \quad g(z) = \frac{1}{2}$$

$$\frac{d}{dz} g(z) = \frac{1}{2} \left( 1 - \frac{1}{2} \right) = \frac{1}{4}$$

# Tanh activation function



$$g(z) = \tanh(z)$$

$$= \frac{e^z - e^{-z}}{e^z + e^{-z}}$$


$$g'(z) = \frac{d}{dz} g(z) = \text{slope of } g(z) \text{ at } z$$

$$= \underline{1 - (\tanh(z))^2} \leftarrow$$

$$a = g(z), \quad g'(z) = 1 - \underset{\uparrow}{a^2}$$

$$\left| \begin{array}{ll} z=10 & \tanh(z) \approx 1 \\ & g'(z) \approx 0 \\ z=-10 & \tanh(z) \approx -1 \\ & g'(z) \approx 0 \\ z=0 & \tanh(z) = 0 \\ & g'(z) = 1 \end{array} \right.$$

# ReLU and Leaky ReLU




ReLU

$$g(z) = \max(0, z)$$
$$\rightarrow g'(z) = \begin{cases} 0 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$$

~~$z = 0$~~

$z = 0.0000000000$



Leaky ReLU

$$g(z) = \max(0.01z, z)$$
$$g'(z) = \begin{cases} 0.01 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$$