

Read before Start

Read this document before you start. It will help you to use this product smoothly.
You can ignore the file readme.md.

Getting Started

After downloading the ZIP file we provided, unzip it and you get a folder containing several files and several folders, two of which are named C and Python. They are development methods based on two different languages when programming ESP8266.

The C folder stores C/C++ programming materials based on the Arduino IDE, while the Python folder saves those of MicroPython based on Thonny.

If you choose C folder

- C_Tutorial.pdf
It contains basic operations such as uploading a sketch to ESP8266 board.

If you are using Python folder

- Python_Tutorial.pdf
It contains basic operations like running python code on the ESP8266 board online or offline.

Get Support

Meet problems? Don't panic!

Whether there are package damage, quality problems, or questions encountered in use, just send an email to:

support@freenove.com

We will reply to you within one working day and provide satisfactory solutions.

Frequently Asked Problems

Here are some common problems and their solutions.

If the following solutions cannot solve the problem encountered, please feel free to contact our support.

ESP8266 board cannot be recognized by computer or Arduino IDE

Reinstall the latest version of Arduino IDE. During the installation, agree to install the driver.

If it is still unrecognized, try to use another USB cable if you have.

If it still does not work, please contact our support.

Fail to upload sketch

Check if the correct board and port are selected.

If it still does not work, please copy the complete error message and send it to our support.

Project doesn't work

Check wiring, chip direction, and try changing wires.

If it still does not work, please take some pictures and send them to our support.

ESP8266 functions abnormally when running

Press the reset button, or disconnect the power supply, and power on the board again. Check whether the board is back to normal. This may be caused by incorrect operation or environmental reasons. If every time you power on the board, ESP8266 is abnormal when it runs for a certain period of time, please check whether your code is reasonable. If you cannot solve the problem, please take some photos and send them to our support.