Free your innovation

Freenove is an open-source electronics platform.
www.freenove.com

Warning

When you purchase or use this product, please note the following:

- This product contains small parts. Swallowing or improper operation them can cause serious infections and death. Seek immediate medical attention when the accident happened.
- Do not allow children under 3 years old to play with or near this product. Please place this product in where children under 3 years of age cannot reach.
- Do not allow children lack of ability of safe to use this product alone without parental care.
- Never use this product and its parts near any AC electrical outlet or other circuits to avoid the potential risk of electric shock.
- Never use this product near any liquid and fire.
- Keep conductive materials away from this product.
- Never store or use this product in any extreme environments such as extreme hot or cold, high humidity and etc.
- Remember to turn off circuits when not in use this product or when left.
- Do not touch any moving and rotating parts of this product while they are operating.
- Some parts of this product may become warm to touch when used in certain circuit designs. This is normal. Improper operation may cause excessively overheating.
- Using this product not in accordance with the specification may cause damage to the product.

About

Freenove is an open-source electronics platform. Freenove is committed to helping customer quickly realize the creative idea and product prototypes, making it easy to get started for enthusiasts of programing and electronics and launching innovative open source products. Our services include:

- Electronic components and modules
- Learning kits for Arduino
- Learning kits for Raspberry Pi
- Learning kits for Technology
- Robot kits
- Auxiliary tools for creations

Our code and circuit are open source. You can obtain the details and the latest information through visiting the following web sites:
http://www.freenove.com
https://github.com/freenove

Your comments and suggestions are warmly welcomed, please send them to the following email address:
support@freenove.com

References

You can download the sketches and references used in this product in the following websites:
http://www.freenove.com
https://github.com/freenove
If you have any difficulties, you can send email to technical support for help.

The references for this product is named Freenove Ultrasonic Starter Kit for Arduino, which includes the following folders and files:

- Datasheet Datasheet of electronic components and modules
- Libraries Library files of Arduino Software
- Sketches Code of Arduino Software
- Readme.txt Instructions

Support

Freenove provides free and quick technical support, including but not limited to:

- Quality problems of products
- Problems in using products
- Questions for learning and technology
- Opinions and suggestions
- Ideas and thoughts

Please send email to:
support@freenove.com
On working day, we usually reply to you within 24 hours.

Copyright

Contents

Preface

If you want to creat somethings fun or make your great ideas real, using this product will be a good start. Maybe you have heard of Arduino before. If not, it doesn't matter. You can easily create dozens of interesting projects, and gradually realize the fun of using Arduino to complete creative works by reference to this book.

Arduino is an open-source electronics platform based on easy-to-use hardware and software. It's intended for anyone making interactive projects. Arduino has a lot of fans in the world. They contributed a lot of high quality open source code and circuit, so we can use these free code and the circuit to realize our own creativity more efficiently.

Usually, an Arduino project consists of code and circuit. If you never dealt with code and circuit before, don't worry. Because this book will gradually introduce C programming language and basic knowledge of electronic circuit from easy to difficult. And this product contains all electronic components and modules needed to complete these projects. You can also ask us for fast and free technical support at any time. It is especially suitable for beginners.

Arduino Board

Arduino Board is a circuit board, which integrates micro controller, input, output interface and etc. Arduino Board can use the sensor to sense the environment and receive user's operation to control LED, motor rotation, etc. We just need to assembly circuit and write the code.

Currently, Arduino Board has several models, and the code between boards of different types is universal (some boards may not be completely compatible because of the differences in hardware). Popular boards include:

UNO



MICRO	NANO
	

MEGA



The board used in this book is Freenove UNO, and it is fully compatible to Arduino UNO. Diagram of Freenove UNO board is shown below:



- Digital I/O ports is used to connect to other components or modules, to receive an input signal, or to send a control signal. Usually, we name it by adding a "D" in front of the number, such as D13.
- USB interface is used to provide power, upload code or communicate with PC.
- LED L is connected to digital I/O port 13 (D13).
- LED TX, RX is used to indicate the state of the serial communication.
- DC interface is connected DC power to provide power for the board.
- Power ports can provide power for electronic components and modules.
- Analog I/O ports can be used to measure analog signals.
- LED ON is used to indicate the power state.

Freenove UNO is the most suitable board to complete the experiments of this book. You can also choose to use Arduino UNO, Arduino MICRO, Arduino NANO, Arduino MEGA (or other boards compatible to them).

Arduino Software

Arduino Software (IDE) is used to write and upload the code for Arduino Board.

First, install Arduino Software (IDE): visit https://www.arduino.cc, click "Download" to enter the download page.



Download corresponding installation program according to your operating system. If you are a Windows user, please select the "Windows Installer" to download to install the driver correctly.



After the download completes, run the installer. For Windows users, there may pop up a installation dialog box of driver during the installation process. When it is popped up, please allow the installation.
After installation is complete, an Arduino Software shortcut will be generated in the desktop. Run the Arduino Software.

The interface of Arduino Software is as follows:



Programs written using Arduino Software (IDE) are called **sketches**. These sketches are written in the text editor and are saved with the file extension **.ino**. The editor has features for cutting/pasting and for searching/replacing text. The message area gives feedback while saving and exporting and also displays errors. The console displays text output by the Arduino Software (IDE), including complete error messages and other information. The bottom righthand corner of the window displays the configured board and serial port. The toolbar buttons allow you to verify and upload programs, create, open, and save sketches, and open the serial monitor.

Verify
Checks your code for errors compiling it.

Upload
Compiles your code and uploads it to the configured board.

New
Creates a new sketch.

Open
Presents a menu of all the sketches in your sketchbook. Clicking one will open it within the current window overwriting its content.

Save
Saves your sketch.

Serial Monitor
Opens the serial monitor.

Additional commands are found within the five menus: File, Edit, Sketch, Tools, Help. The menus are context sensitive, which means only those items relevant to the work currently being carried out are available.

First Use

Open the exmple sketch "Blink" with Arduino Software.



Select board "Arduino/Genuino Uno".



Connect Freenove UNO to computer with USB cable.



Select the serial port. Your serial number may be different from the following figure. If it is not detected immediately, please wait for a while, then click "Tools" to check again.



Click "Verify" button.



The following figure shows the code is being compiled.



Wait a moment for the compiling to be completed. Figure below shows the code size and percentage of space occupation.



Usually, when we write code, if it has a syntax error, the interface will prompt the error message. Then the compiling can't be completed.

Click "Upload" button.



Figure below shows code are uploading.



Wait a moment, then the uploading is completed.



After that, we will see the LED marked with "L" on Freenove UNO starts blinking. It indicates that the code is running now!



So far, we have completed the first use. I believe you have felt the joy of it. Next, we will carry out a series of projects, from easy to difficult, taking you to learn the Arduino programming and the building of electronic circuit.

Chapter 1 LED Blink

We have previously tried to make the LED marked with "L" blink on Freenove UNO board. Now let us use electronic components and code to reproduce the phenomenon, and try to understand the principle among them.

Project 1.1 Control LED by Manual Button

First, try using the push button to make the LED blink manually.

Component list

Freenove UNO x1 	Breadboard x1 		
USB cable x1 	LED x1 	Resistor 220Ω x1 	Push button x1 
Jumper M/M x2 			

Circuit knowledge

Power supply

Power supply provide energy for the circuit, and it is divided into DC power and AC power.

Voltage and current of DC power supply remains the same over time, such as battery, power adapter.

Voltage and current of AC power supply evolves periodically with time. Its basic form is sinusoidal voltage(current). It is suitable for long-distance transmission of electric energy. And it is used to supply power to homes.



Generally, electronic circuits use DC. Home appliances have rectifiers to convert AC into DC before they use.

Battery or battery pack can be represented by the following symbols:

The positive and negative poles of the power supply can not be directly connected , otherwise it may scald you and cause damage to the battery.

Voltage

The unit of voltage(U) is volt(V). 1kV=1000V, 1V=1000mV, 1mV=1000μv.

Voltage is relative. As to a dry battery marked with "1.5V", it's positive (+) voltage is 1.5V higher than the negative (-) voltage. If you specify the negative as reference （0V）, the positive voltage will be +1.5V.



When two dry batteries are connected in series, the voltage of each point is as follows:



In practical circuits, we usually specify negative as reference voltage (0V), which is called "Ground". The positive is usually called "VCC". The positive and negative of power supply is usually represented by two following symbols:

Positive(VCC) Negative(Ground)

Current

The unit of current(I) is ampere(A). 1A=1000mA, 1mA=1000μA.

Closed loop consisting of electronic components is necessary for current.

In the figure below: the left is a loop circuit, so current flows through the circuit. The right is not a loop circuit, so there is no current.



Resistor

The unit of resistance(R) is ohm(Ω). 1mΩ=1000kΩ, 1kΩ=1000Ω.

Resistor is an electrical component that limits or regulates the flow of current in an electronic circuit.

The left is the appearance of resistor. and the right is the symbol of resistor represented in circuit.



Color rings attached to the resistor is used to indicate its resistance. For more details of resistor color code, please refer to the appendix of this book.

With the same voltage there will be less current with more resistance. And the links among current, voltage and resistance can be expressed by the formula below: I=U/R.

In the following diagram, the current through R1 is: I=U/R=5V/10kΩ=0.0005A=0.5mA.



Do not connect the two poles of power supply with low resistance, which will make the current too high to damage electronic components.

Component knowledge

Let us learn about the basic features of components to use them better.

Jumper

Jumper is a kind of wire. It is designed to connect the components together with its two terminals by inserting it onto Breadboard or Freenove UNO.
Jumpers have male end (pin) and female end (slot), so jumpers can be divided into the following 3 types.

Breadboard

There are many small holes on breadboard to connect Jumper.
Some small holes are connected inside breadboard. The following figure shows the inner links among those holes.



Push button

Push button has 4 pins. Two pins on the left is connected, and the right is similar as the left, which is shown in the below:



When the push button is pressed, the circuit is turned on.

LED

LED is a kind of diode. LED will shine only if the long pin of LED is connected to the positive electrode and the short pin is connected to negative electrode.

This is also the features of the common diode. Diode works only if the voltage of its positive electrode is higher than its negative electrode.



The LED can not be directly connected to power supply, which can damage component. A resistor with certain resisitance must be connected in series in the circuit of LED.

Circuit

In this experiment, the LED is controlled by push button, and Freenove UNO here only plays the role of power supply in the circuit.

Firstly, connect conmponents with jumpers according to "hardware connection". Secondly, check the connetion to confirm there is no mistakes. Finally, connect Freenove UNO board to computer with USB cable to avoid that touch on wires may cause short-circuit fault.

Schematic diagram	Hardware connection
	

LED lights up when you press the push button, and it get off when you release the button.



Project 1.2 Control LED by Arduino

Now, try using Arduino to make LED blink through programing.

Component list

Components are basically the same with those in last section. Push button is no more needed.

Circuit knowledge

Analog signal and Digital signal

The analog signal is a continuous signal in time and value. On the contrary, digital signal is a discrete signal in time and value.

Most signals in life are analog signals, for example, the temperature in one day is continuously changing, and will not appea a sudden change directly from 0C° to 10C°, while the digital signal is a jump change, which can be directly from 1 to 0.

Their difference can be illustrated by the following figure.



In practical application, the frequently used digital signal is binary signal, that is 0 and 1. The binary signal only has two forms (0 or 1), so it has strong stability. And digital signal and analog signal can be converted to each other.

Low level and high level

In circuit, the form of binary (0 and 1) is present as low level and high level.

Low level is generally equal to ground voltage(0V). High level is generally equal to the operating voltage of components.

The low level of Freenove UNO is 0V and high level is 5V, as shown below. When IO port on Freenove UNO outputs high level, components of small power can be directly lit, like LED.



Code knowledge

Before start writting code, we should learn about the basic programming knowledge.

Comments

Comments are the words used to explain for the sketchs, and won't affect the running of code.
There are two ways to use comments of sketchs.

1. Symbol "//"

"//" will comment out the content behind it in current line:

```
1  // this is a comment area in this line.
```

The content in front of "//" will not be affected.

```
1  delay(1000);              // wait for a second
```

2. Symbol "/*"and "*/"

"/*" and "*/" will comment out the content between them:

```
1  /* this is comment area. */
```

"/*" and "*/" can comment out multiple lines.:

```
1  /*
2     this is a comment line.
3     this is a comment line.
4  */
```

Data type

When programming, we often use digital, characters and other data. C language has several basic data types as follws:
int: A number that does not have a fractional part, an integer, such as 0, 12, -1;
float: A number that has a fractional part, such as 0.1, -1.2;
char: It means character, such as 'a', '@', '0';
For more date types, please visit the website: https://www.arduino.cc-Learning-Reference-Data Types.

Constant

Constant is a kind of data that can not be changed, such as int type 0, 1, float type 0.1, -0.1, char type 'a', 'B'.

Variable

A variable is a kind of data that can be changed. It consists of a name, a value, and a type. Variables need to be defined before use, such as:

```
1  int i;
```

"int" indicates the type, ";" indicates the end of the statement. The statement is usually written in one single line; and these statements form the code.
After declaration of the variable, you can use it. The following is an assignment to a variable:

```
1  i = 0;                    // after the execution, the value of i is 0
```

"=" is used to passes the value of a variable or constant on the right side to the variable on the left.

A certain number of variables can be declard in one statement, and a variable can be assigned multiple times. Also, the value of a variable can be passed to other variables. For example:

```
int i, j;
i = 0;                    // after the execution,the value of i is 0
i = 1;                    // after the execution,the value of i is 1
j = i;                    // after the execution,the value of j is 1
```

Function

Function is a collection of statements with a sequence of order, which perform a defined task. Let's define a function void blink() as follows:

```
void blink() {
  digitalWrite(13, HIGH);
  delay(1000);
  digitalWrite(13, LOW);
  delay(1000);
}
```

"void" indicates that the function does not return a value (the chapter 4 will detail the return value of functions);
"()" its inside is parameters of a function (the chapter 2 will detail the parameters of the function). No content inside it indicates that this function has no parameters;
"{}" contains the entire code of the function.
After the function is defined, it is necessary to be called before it is executed. Let's call the function void blink(), as shown below.

```
blink();
```

When the code is executed to a statement calling the function, the function will be executed. After execution of the function is finished, it will go back to the statement and execute the next statement.



Some functions have one or more parameters. When you call such functions, you need to write parameters inside "()":

```
digitalWrite(13, HIGH);   // turn the LED on (HIGH is the voltage level)
delay(1000);              // wait for a second
```

Circuit

Now, let 's use IO port of UNO Freenove to provide power for the LED. D13 pin of Freenove UNO is the digital pin. It can output high level or low level. In this way, Freenove UNO can control the sate of LED.

Schematic diagram	Hardware connection
	

Sketch

Sketch 1.2.1

In order to make the LED blink, we need to make the 13 pin (D13) of Freenove UNO output high and low level alternately.

We highly recommend you type the code in person instead of copying and pasting, by this method, you can develop your coding skills and get more knowledge.

```
1  // the setup function runs once when you press reset or power the board
2  void setup() {
3    // initialize digital pin 13 as an output
4    pinMode(13, OUTPUT);
5  }
6
7  // the loop function runs over and over again forever
8  void loop() {
9    digitalWrite(13, HIGH);   // turn the LED on (HIGH is the voltage level)
10   delay(1000);              // wait for a second
11   digitalWrite(13, LOW);    // turn the LED off by making the voltage LOW
12   delay(1000);              // wait for a second
13 }
```

The Arduino code usually contain two basic functions: void setup() and void loop().

After Arduino board is reset, the setup() function will be executed firstly, then the loop() function will be executed.

setup() function is generally used to write code to initialize the hardware. And loop() function is used to write code to achieve certain functions. loop() function is executed repeatedly. When the execution reaches the end of loop(), it will jump to the beginning of loop() to run again.

Reset

Reset operation will lead the code to be execute from the beginning. Switching on the power, finishing uploading the code and pressing the reset button will trigger reset operation.



In the setup () function, first, we set the 13 pin of UNO board as output mode, which can make the port output high level or low level.

```
3   // initialize digital pin 13 as an output.
4   pinMode(13, OUTPUT);
```

Then, in the loop () function, set the 13 pin of UNO to output high level to make LED light up.

```
9   digitalWrite(13, HIGH);   // turn the LED on (HIGH is the voltage level)
```

Wait for 1000ms, that is 1s. Delay () function is used to make control board wait for a moment before executing the next statement. The parameter indicates the number of millisecondst to wait for.

```
10  delay(1000);              // wait for a second
```

Then set the 13 pint to output low level, and LED light off. One second later, the execution of loop () function will be completed.

```
11  digitalWrite(13, LOW);    // turn the LED off by making the voltage LOW
12  delay(1000);              // wait for a second
```

The loop() function is constantly being executed, so LED will keep blinking.

The function called above is standard function of the Arduino, which has been defined in the Arduino Software. Those function can be called directly. We will introduce more common standard functions in later chapters. For more standard functions and the specific use method, please visit https://www.arduino.cc-Learning-Reference-Functions.

Verify and upload the code, then the LED starts blinking.



Chapter 2 Two LEDs Blink

In last chapter, we have already written code to make 1 LED blink on Freenove UNO board. And now, we will try to make 2 LEDs blink for further programming study.

Project 2.1 Two LEDs Blink

Now, try to make two LEDs blink trough Freenove UNO board.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	LED x2 	Resistor 220Ω x2 
Jumper M/M x3 		

Code knowledge

In the last chapter, we have simple understanding of programming. Now let's learn more about the basic programming knowledge.

Parameters of function

In the last chapter, we have used a function with a parameter, such as:

```
1  delay(1000);                // wait for a second
```

Next, we will define a function with a parameter as below:

```
1  void functionA(int i) {
2    i = i + 1;
3  }
```

"i" is the parameter of this function. "int" is the type of i. When calling this function, it is necessary to enter the parameter of int type:

```
1  functionA(1);
```

The input parameter will be assigned to "i" and involved in the calculation of the functionA(int i):



A function can define more than one parameter and the type of the parameters can be different:

```
1  void functionB(int i, char j) {
2    char k = 'a';
3    i = i + 1;
4    k = j;
5  }
```

Boolean data type

Date of Boolean type can only be assigned to "true" or "false".

"true" generally represents a certain relationship which is tenable and correct, and "false" is the opposite.

```
1  boolean isTrue;
2  isTrue = true;              // after the execution, "isTrue" is assigned to true.
3  isTrue = false;             // after the execution, "isTrue" is assigned to false.
```

In the code, the number 0 can be considered to be false, and nonzero numbers can be considered ture.

Logical operator

The logic operators have "&&" (and), "||" (or), "!" (non), and the calculation object of them are boolean type. The result of logic operation is as follows:

&&	true	false
true	true	false
false	false	false

||	true	false
true	true	true
false	ture	false

	!
true	false
false	true

For example：

```
boolean isTrue;
isTrue = true && false;   // after the execution, "isTrue"is assigned to false.
isTrue = true || false;   // after the execution, "isTrue"is assigned to true.
isTrue = !true;           // after the execution, "isTrue"is assigned to false.
```

Relation operator

Relational operator is used to judge whether the relationship of the two amount is tenable and correct. If the relationship is tenable, the result is true. Otherwise, the result is false.

For example, the results of "1>2" is true and the result of "1<2" is false:

```
boolean isTrue;
isTrue = 1 < 2;           // after the execution, "isTrue"is true.
isTrue = 1 > 2;           // after the execution, "isTrue"is false.
```

There are orther relational operators such as "==" (equal to), ">=" (greater than or equal to), "<=" (less than or equal to) and "=!" (not equal to).

Conditional statement

Conditional statements are used to decide whether or not to execute the program based on the result of judgment statement.

```
int i = 0;
if (i == 0)    // ture
  i = 1;       // execution
functionX();
...
```

```
int i = 0;
if (i != 0)    // false
  i = 1;       // no execution
functionX();
...
```

When there are many statements needed to be executed, we can put them into "{}":

```
int i = 0, j = 0;
if (i == 0) { // ture
  i = 1;      // execution
  j = 1;      // execution
}
functionX();
...
```

```
int i = 0, j = 0;
if (i != 0) { // false
  i = 1;      // no execution
  j = 1;      // no execution
}
functionX();
...
```

Only the section of code in which conditions are tenable will be executed:

```
int i = 0;
if (i == 0)    // ture
  i = 1;       // execution
else
  i = 1;       // no execution
functionX();
...
```

```
int i = 0;
if (i != 0)    // false
  i = 1;       // no execution
else
  i = 1;       // execution
functionX();
...
```

In addition, it can judge multiple condition.

```
1   int i = 1;
2   if (i == 0)       // false
3     i = 1;          // no execution
4   else if (i == 1)// ture
5     i = 2;          // execution
6   else if (i == 2)
7     i = 3;          // no execution
8   else
9     i = 4;          // no execution
10  functionX();
... ...
```

```
1   int i = 3;
2   if (i == 0)       // false
3     i = 1;          // no execution
4   else if (i == 1)// false
5     i = 2;          // no execution
6   else if (i == 2)// false
7     i = 3;          // no execution
8   else
9     i = 4;          // execution
10  functionX();
... ...
```

Circuit

Use D4 and D5 pin of Freenove UNO to drive these two LEDs respectively.

Schematic diagram



Hardware connection



Sketch

In order to show the difference between use of function and no use of function, we will write two different sketches to make two LEDs blink.

Sketch 2.1.1

At first, use sketch without function to make two LEDs blink alternatively.

```
1  // set pin numbers:
2  int led1Pin = 4;            // the number of the LED1 pin
3  int led2Pin = 5;            // the number of the LED2 pin
4
5  void setup() {
6    // initialize the LED pin as an output:
7    pinMode(led1Pin, OUTPUT);
8    pinMode(led2Pin, OUTPUT);
9  }
10
11 void loop() {
12   digitalWrite(led1Pin, HIGH);   // turn the LED1 on
13   digitalWrite(led2Pin, LOW);    // turn the LED2 off
14   delay(1000);                   // wait for a second
15
16   digitalWrite(led1Pin, LOW);    // turn the LED1 off
17   digitalWrite(led2Pin, HIGH);   // turn the LED2 on
18   delay(1000);                   // wait for a second
19 }
```

This section of code is similar with the last section. The difference is the amount of LEDs are two. And two LED blink alternatively.

Variable scope

In the 2,3 rows of code above, we define two variables to store the pin number. These two variables defined outside of the function are called "Global variable", which can be called by all other functions. Variables defined within a function is called "local variable", which can be called only by the current function. When local variables and global variables have same names, the variable names represents local variable in the current function.

Verify and upload the code, then you will see the two LEDs blink alternatively.



Sketch 2.1.2

In the last sketch, we can see that the following two sections of the code are similar, so we will use one function to replace them to simplify code.

```
12    digitalWrite(led1Pin, HIGH);   // turn the LED1 on
13    digitalWrite(led2Pin, LOW);    // turn the LED2 off
14    delay(1000);                   // wait for a second
```

```
16    digitalWrite(led1Pin, LOW);    // turn the LED1 off
17    digitalWrite(led2Pin, HIGH);   // turn the LED2 on
18    delay(1000);                   // wait for a second
```

Now, we will use the function to improve the above code.

```
1   // set pin numbers:
2   int led1Pin = 4;            // the number of the LED1 pin
3   int led2Pin = 5;            // the number of the LED2 pin
4
5   void setup() {
6     // initialize the LED pin as an output:
7     pinMode(led1Pin, OUTPUT);
8     pinMode(led2Pin, OUTPUT);
9   }
10
11  void loop() {
12    setLed(HIGH, LOW);      // set LED1 on, and LED2 off.
13    setLed(LOW, HIGH);      // set LED1 off, and LED2 on.
14  }
15
16  void setLed(int led1, int led2) {
17    digitalWrite(led1Pin, led1);   // the state of LED1 is determined by variable led1.
18    digitalWrite(led2Pin, led2);   // the state of LED2 is determined by variable led2.
19    delay(1000);                   // wait for a second
20  }
```

In the sketch above, we integrate the 2 LED statements into one function void setLed(int led1, int led2), and control two LEDs through the parameters led1 and led2.

```
16  void setLed(int led1, int led2) {
17    digitalWrite(led1Pin, led1);   // the state of LED1 is determined by variable led1.
18    digitalWrite(led2Pin, led2);   // the state of LED2 is determined by variable led2.
19    delay(1000);                   // wait for a second
20  }
```

When the function above is called, we will control the two LEDs by using different parameters as below.

```
12    setLed(HIGH, LOW);      // set LED1 on, and LED2 off.
13    setLed(LOW, HIGH);      // set LED1 off, and LED2 on.
```

Verify and upload the code, then you will see the two LEDs blink alternatively.

HIGH and LOW

The macro is an identifier that represents a number, a statement, or a piece of code. HIGH and LOW are two macros. HIGH and LOW is defined in Arduino Software as below:

```
#define HIGH 1
#define LOW 0
```

In the code, a macro is used as the content defined by itself. For example, setLed (HIGH, LOW) is equivalent to setLed (1, 0).

Using macros can enhance the readability of code and simplify code, such as INPUT, OUTPUT.

Sketch 2.1.3

In the last section of code, we used a function that integrates two similar paragraph of code. And We control two LEDs by using two parameters. As the two LEDs are always blinking alternatively, so let's try to use one parameter to control these two LEDs, which is achieved by conditional statements.

Now, we'll use conditional statement to improve the code above.

```
// set pin numbers:
int led1Pin = 4;            // the number of the LED1 pin
int led2Pin = 5;            // the number of the LED2 pin

void setup() {
  // initialize the LED pin as an output:
  pinMode(led1Pin, OUTPUT);
  pinMode(led2Pin, OUTPUT);
}

void loop() {
  setLed1(HIGH);     // set LED1 on, and LED2 off.
  setLed1(LOW);      // set LED1 off, and LED2 on.
}

void setLed1(int led1) {
  digitalWrite(led1Pin, led1);   // the state of LED1 is determined by variable led1.

  if (led1 == HIGH)              // the state of LED2 is determined by variable led1.
    digitalWrite(led2Pin, LOW);  // if LED1 is turned on, LED2 will be turned off.
  else
    digitalWrite(led2Pin, HIGH); // if LED1 is turned off, LED2 will be turned on.

  delay(1000);                   // wait for a second
}
```

Here, we rewrite the function so that we only need to set the state of LED1. And the state of LED2 can be set automatically.

Verify and upload the code, then two LEDs blink alternatively.

Chapter 3 LED bar graph

We have learned previously how to control 1 or 2 LED through Sketch on Freenove UNO board and learn some basic knowledge of programming. Now let's try to control 10 LEDs and learn how to simplify the code.

Project 3.1 LED bar graph Display

Let us use Freenove UNO to control a bar graph LED consist of 10 LEDs.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	LED bar graph x1 	Resistor 220Ω x10 
Jumper M/M x11 		

Component knowledge

Let us learn about the basic features of components to use them better.

LED bar graph

LED bar graph is a component Integration consist of 10 LEDs. There are two rows of pins at its bottom. At the bottom of the LED bar graph, there are two rows of pins, corresponding to positive and negative pole separately. If the LED bar graph can not work in the circuit, it was probably because the connection between positive and negative pole is wrong. Please try to reverse the LED bar graph connection.



Code knowledge

This section will use new code knowledge.

Array

Array is used to record a set of variables. An array is defined below:

```
1  int a[10];
```

"int" is the type of the array and "10" is an element of the array. This array can store 10 int types of elements as below.

```
1  int a[10] = {0, 1, 2, 3, 4, 5, 6, 7, 8, 9};
```

Or there is another form that the number of elements is the size of the array:

```
1  int a[] = {0, 1, 2, 3, 4, 5, 6, 7, 8, 9};
```

We can reference elements of an array as below：

```
1  int i, j;
2  i = a[0];
3  j = a[1];
4  a[0] = 0;
```

Among them, "[]" is the array index, with a[0] as the first elements in the array.

For example, now we define an arry b[] below:

```
int b[] = {5, 6, 7, 8};
```

The value of each element in array b[] is as follows:

b[0]	b[1]	b[2]	b[3]
5	6	7	8

This is just the use of one-dimensional array. And there are two-dimensional arrays, three-dimensional arrays, and multi-dimensional arrays. Readers interested of this part can develop your own learning.

Loop

The loop statement is used to perform repetitive work such as the initialization to all the elements of an array.

```
while(expression)
  functionX();
```

When there is more than one statement to be executed, the form is as follows:

```
while(expression){
  functionX();
  functionY();
}
```

The first step of the execution is judgment expression inside "()". If the result is false, the statements inside "{}" will not be executed; if resut is ture, the statements will be executed.

```
int i = 0;
while (i < 2)
  i = i + 1;
i = 5;
```

First time: i<2, i=0 is tenable, execute i=i+1, then i=1;

Second time: i<2, i=1 is tenable, execute i=i+1, then i=2;

Third time: i<2, i=2 is not tenable, execution of loop statements is completed. Statement i=5 will be executed next.

"do while" and "while" is similar. The difference is that the loop statements of "do while" is executed before judging expression. The result of the judgment will decide whether or not go on the next execution:

```
do {
  functionX();
} while (expression);
```

"for" is another loop satement, and its form is as follows:

```
for (expression1; expression2; expression 3)
  functionX();
```

When there is more than one statement to be executed, the form is as follows:

```
for (expression 1; expression 2; expression 3) {
  functionX();
  functionY();
}
```

Expression 1 is generally used to initialize variables; expression 2 is judgement which is used to decide wether or not to execute loop statements; the expression 3 is generally used to change the value of variables.

For example:

```
1  int i = 0, j = 0;
2  for (i = 0; i < 2; i++)
3    j++;
4  i = 5;
```

First: i=0, i<2 is tenable, execute j++, and execute i++, then i=1, j=1;

Second: i=1, i<2 is tenable, execute j++, and execute i++, then i=2, j=2;

Third times: i<2 is tenable, i=2 is not tenable. The execution of loop statements is completed. Statement i=5 will be executed next.

Operator ++, --

"i++" is equivalent to "i=i+1". And "i--" equivalent to "i=i-1".

Circuit

Let us use D3, D4, D5, D6, D7, D8, D9, D10, D11, D12 pin of Freenove UNO board to drive LED bar graph.

Schematic diagram



Hardware connection



Sketch

Now let us complete the sketch to control LED bar graph.

Sketch 3.1.1

First, write a sketch which can achieve the LED light water.

```
const int ledCount = 10;    // the number of LEDs in the bar graph

// an array of pin numbers to which LEDs are attached
int ledPins[] = { 3, 4, 5, 6, 7, 8, 9, 10, 11, 12 };

void setup() {
  // loop over the pin array and set them all to output:
  for (int i = 0; i < ledCount; i++) {
    pinMode(ledPins[i], OUTPUT);
  }
}

void loop() {
  // the ith LED of LED bar graph will light up in turn
  for (int i = 0; i < ledCount; i++) {
    barGraphDisplay(i);
  }
}

void barGraphDisplay(int ledOn) {
  // make the "ledOn"th LED of bar graph LED on and the others off
  for (int i = 0; i < ledCount; i++) {
    if (i == ledOn)
      digitalWrite(ledPins[i], HIGH);
    else
      digitalWrite(ledPins[i], LOW);
  }
  delay(100);
}
```

Firstly, let us define a read-only variable to record the number of LEDs as the number of times in the loop.

```
const int ledCount = 10;    // the number of LEDs in the bar graph
```

Read-only variable

"const" keyword is used to define read-only variables, which is called in the same way with comen variable. But read-only variables can be assigned only once.

Then we define an array used to store the number of pins connected to LED bar graph. So it is convenient to manipulate arrays to modify the pin number.

```
3  // an array of pin numbers to which LEDs are attached
4  int ledPins[] = { 3, 4, 5, 6, 7, 8, 9, 10, 11, 12 };
```

Use loop statement to set the pins to output mode in function setup().

```
6  void setup() {
7    // loop over the pin array and set them all to output:
8    for (int i = 0; i < ledCount; i++) {
9      pinMode(ledPins[i], OUTPUT);
10   }
11 }
```

Define a function to open a certain LED on the LED bar graph and close the other LEDs.

```
20 void barGraphDisplay(int ledOn) {
21   // make the "ledOn"th LED of LED bar graph on and the others off
22   for (int i = 0; i < ledCount; i++) {
23     if (i == ledOn)
24       digitalWrite(ledPins[i], HIGH);
25     else
26       digitalWrite(ledPins[i], LOW);
27   }
28   delay(100);
29 }
```

Finally, when the above function is called cyclically, there will be the formation of LED water effect in LED bar graph.

```
13 void loop() {
14   // make the "i"th LED of LED bar graph on and the others off in turn
15   for (int i = 0; i < ledCount; i++) {
16     barGraphDisplay(i);
17   }
18 }
```

Verify and upload the code, then you will see the light water on the LED bar graph.

Sketch 3.1.2

Then modify the code to create a reciprocating LED light watert.

```
const int ledCount = 10;    // the number of LEDs in the bar graph

// an array of pin numbers to which LEDs are attached
int ledPins[] = { 3, 4, 5, 6, 7, 8, 9, 10, 11, 12 };

void setup() {
  // loop over the pin array and set them all to output:
  for (int i = 0; i < ledCount; i++) {
    pinMode(ledPins[i], OUTPUT);
  }
}

void loop() {
  // makes the "i"th LED of LED bar graph bright in turn
  for (int i = 0; i < ledCount; i++) {
    barGraphDisplay(i);
  }
  // makes the "i"th LED of LED bar graph bright in reverse order
  for (int i = ledCount; i > 0; i--) {
    barGraphDisplay(i - 1);
  }
}

void barGraphDisplay(int ledOn) {
  // make the "ledOn"th LED of LED bar graph on and the others off
  for (int i = 0; i < ledCount; i++) {
    if (i == ledOn)
      digitalWrite(ledPins[i], HIGH);
    else
      digitalWrite(ledPins[i], LOW);
  }
  delay(100);
}
```

We have modified the code inside the function loop() and make the LED bar graph light in order, and then light in reverse order cyclically.

Verify and upload the code, then you will see the reciprocating LED light water on LED bar graph.

Chapter 4 LED Blink Smoothly

In the previous chapter, we have used Sketch on the Freenove UNO board to control up to 10 LED blink and learned some basic knowledge of programming. Now, let us try to make LED emit different brightness of light.

Project 4.1 LEDs Emit Different Brightness

Now, let us use Freenove UNO board to make 4 LED emit different brightness of light.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	LED x4 	Resistor 220Ω x4 
Jumper M/M x5 		

Circuit knowledge

At first, let us learn the kowledge how to use the circuit to make LED emit different brightness of light,

PWM

PWM, namely Width Modulation Pulse, is a very effective technique for using digital signals to control analog circuits. The commen processors can not directly output analog signals. PWM technology make it very convenient to achieve this purpose.

PWM technology uses digital pins to send certain frequency of square waves, that is, the output of high level and low level last for a period alternately. The total time for each set of high level and low level is generally fixed, which is called period (the reciprocal of the period is frequency). Output high time is generally called pulse width, and the percentage of pulse width is called duty cycle.

The longer the output of high level last, the larger the duty cycle and the larger the corresponding voltage in analog signal. The following figures show how the analogs ignal voltage vary between 0V-5V (high level is 5V) corresponding to the pulse width 0%-100%:



The larger PWM duty ratio, the lager the output power. So we can use PWM to control the brightness of LED, the speed of DC motor and so on.

Code knowledge

We will use new code knowledge in this section.

Return value of function

We have learned and used the function without return value, now we will learn how to use the function with return value. A function with return value is shown as follow:

```
1  int sum(int i, int j) {
2    int k = i + j;
3    return k;
4  }
```

"int" declare the type of return value of the function sum(int i, int j). If the tape of the return value is void, the function does not return a value.

One function can only return one value. It is necessary to use the return statement to return the value of function.

When the return statement is executed, the function will return immediately regardless of code behind return statement in this function.

A function with return value is called as follows:

```
1  int a = 1, b = 2, c = 0;
2  c = sum(1, 2);              // after the execution the value of c is 3
```

A function with a return value can also be used as a parameter of functions, for example:

```
1  delay(sum(100, 200));
```

It is equivalent to the following code:

```
1  delay(300);
```

return

We have learned the role of the return statement in a function with a return value. It can also be used in functions without return value, and there is no data behind the return keyword:

```
1  return;
```

In this case, when the return statement is executed, the function will immediate end end its execution rather than return in the end of the function. For example:



Circuit

Use D5, D6, D9, D10 pin on Freenove UNO board to drive 4 LEDs.

Schematic diagram	Hardware connection
	

Sketch

Sketch 4.1.1

Now let us use sketch to make 4 LEDs emit different brightness of light. We will transmit signal to make the 4 ports connected to LEDs output the PWM waves with duty cycle of 2%, 10%, 50%, and 100% to let the LED emit different brightness of the light.

```
1  // set pin numbers:
2  int ledPin1 = 5,            // the number of the LED1 pin
3      ledPin2 = 6,            // the number of the LED2 pin
4      ledPin3 = 9,            // the number of the LED3 pin
5      ledPin4 = 10;           // the number of the LED4 pin
6
```

```
7  void setup() {
8    // initialize the LED pin as an output:
9    pinMode(ledPin1, OUTPUT);
10   pinMode(ledPin2, OUTPUT);
11   pinMode(ledPin3, OUTPUT);
12   pinMode(ledPin4, OUTPUT);
13 }
14
15 void loop()
16 {
17   // set the ports output PWM waves with differrent duty cycle
18   analogWrite(ledPin1, map(2, 0, 100, 0, 255));
19   analogWrite(ledPin2, map(10, 0, 100, 0, 255));
20   analogWrite(ledPin3, map(50, 0, 100, 0, 255));
21   analogWrite(ledPin4, map(100, 0, 100, 0, 255));
22 }
```

After the initialization of the 4 ports, we set the ports to output PWM waves with different duty cycle. Take ledPin1 as an example, firstly map 2% to the 0-255 range, and then output the PWM wave with duty cycle of 2%,

```
1   analogWrite(ledPin1, map(2, 0, 100, 0, 255));
```

analogWrite(pin, value)

Arduino Software provides the function analogWrite (pin, value) which can make ports directly output PWM waves. Only the digital pin marked "~" symbol on The UNO board can use this function to output PWM waves. In the function analogWrite(pin, value), the parameter "pin" specifies the port used to output PWM wave. The range of value is 0-255, which represent the duty ratio 0%-100%.
In order to use this function, we need to set the port to output mode.

map(value, fromLow, fromHigh, toLow, toHigh)

This function is used to remap a value, which will return a new value whose percent in the rang of toLow-toHigh is equat to the percent of "value" accouting for in range of fromLow-fromHigh. Such as 1 is in the range 0-1 in the maximum and the maximum value in the scope of 0-2 is 2, that is, the result value map (1, 0, 1, 0, 2) is 2.

Verify and upload the code, then you will see the 4 LEDs emit light with different brightness.



Project 4.2 LED Blink Smoothly

We will learn how to mke a LED blink smoothly, that is, breathing light.

Component list

The Component list is basically the same as those in last section. And we need to get rid of a few LEDs and resistors.

Circuit

Remove some LEDs and resistors connected to D6, D9, D10 pin on Freenove UNO board in circuit of the last section.

Schematic diagram	Hardware connection
	

Sketch

Sketch 4.2.1

Now complete sketch to make brightness of LED change from dark to bright, and then from the bright to dark. That is to make the duty cycle of the PWM wave change from 0%-100%, and then from 100%-0% cyclically.

```
// set pin numbers:
int ledPin = 5;             // the number of the LED pin

void setup() {
  // initialize the LED pin as an output:
  pinMode(ledPin, OUTPUT);
}

void loop() {
  // call breath() cyclically
  breath(ledPin, 6);
  delay(500);
}

void breath(int ledPin, int delayMs) {
  for (int i = 0; i <= 255; i++) {  // "i" change from 0 to 255
    analogWrite(ledPin, i);         // corespongding duty cycle change from 0%-100%
    delay(delayMs);                 // adjust the rate of change of brightness
  }
  for (int i = 255; i >= 0; i--) {  // "i" change from 255 to 0
    analogWrite(ledPin, i);         // corespongding duty cycle change from 0%-100%
    delay(delayMs);                 // adjust the rate of change in brightness
  }
}
```

Through two cycles, the duty cycle of the PWM wave changes from 0% to 100%, and then from 100% to 0% cyclically. delay(ms) function is used to control the rate of change in the "for" cycle, and you can try to modify the parameters to modify the rate of change in brightness.

Verify and upload the code, then you will see that the brightness of the LED changes from dark to light, and from the light to dark cyclically.



Chapter 5 Control LED Through Push Button

From previous chapter, we have use Freenove UNO to output signals to make 10 LEDs flash, and make one LED emit different brightness. Now, let's learn how to get the input signal.

Project 5.1 Control LED Through Push Button

We will use the Freenove UNO to get the status of the push button, and show that through LED.

Component list

<table>
<tr><td colspan="2">Freenove UNO x1
  </td><td colspan="3">Breadboard x1
  </td></tr>
<tr><td colspan="2">USB cable x1
  </td><td>LED x1
  </td><td>Resistor
220Ω x1
  </td><td>Resistor
10kΩ x2
  </td><td>Push button x1
  </td></tr>
<tr><td colspan="2">Jumper M/M x4
  </td><td colspan="3"></td></tr>
</table>

Circuit knowledge

Connection of Push Button

In Chapter 1, we connect push button directly to power line of the circuit to control the LED to light on or off. In digital circuits, we need to use the push button as the input signal. The recommended connection is as follows:



In the above circuit diagram, when the button is not pressed, 5V (high level) will be detected by UNO port; and 0V (low level) when the button is pressed. The role of Resistor R2 here is to prevent the port from being set to output high level by accident, which could be connected directly to the cathode and cause a short circuit when the button is pressed.

The following diagram shows another connection, in which the level detected by UNO port is opposite to above diagram, when the button is pressed or not.



Circuit

Use D12 of Freenove UNO to detect the status of push button, and D9 to drive LED.

Schematic diagram	Hardware Connection
	

Sketch

Sketch 5.1.1

Now, write code to detect the state of push button, and show that through LED.

```
int buttonPin = 12; // the number of the push button pin
int ledPin = 9;     // the number of the LED pin

void setup() {
  pinMode(buttonPin, INPUT);  // set push button pin into input mode
  pinMode(ledPin, OUTPUT);    // set LED pin into output mode
}

void loop() {
  if (digitalRead(buttonPin) == HIGH) // if the button is not pressed
    digitalWrite(ledPin, LOW);        // switch off LED
  else                                // if the button is pressed
    digitalWrite(ledPin, HIGH);       // switch on LED
}
```

After the port is initialized, the LED will be switched on or off in accordance with the state of the pin connected to push button.

digitalRead(pin)

Arduino Software provides a function digitalRead(pin) to obtain the state of the port pin. The return value is HIGH or LOW, that is, high level or low level.

Verify and upload the code, press the button, then LED lights up; loosen the button, then LED lights off.



Project 5.2 Change LED State by Push Button

In the last section, we have finished the experiment that LED lights on when push button is pressed, and off as soon as it's released. Now, let's try something new: each time you pressed the button down, the state of LED will be changed.

Component List

Same with the last section.

Circuit knowledge

Debounce for push button

When push button is pressed, the potential won't transfer from one state to another state ideally. In fact, it will occur a continuous bounce process before it becomes final stable state.



If you detect the state of push button, there may be repeated "press" and "release" detected during one process of pressing. So it is necessary to eliminate the influence caused by the bounce. Here is the most direct and effective way: when the changed signals are received by Freenove UNO for the first time, the program does not operate immediately, just waits for a certain time to skip the bounce process and confirm the final state of push button.

Circuit

Same with the last section.

Sketch

Sketch 5.2.1

Now, write the code to detect the state of push button. Every time you pressed, the state of LED will be changed.

```
int buttonPin = 12; // the number of the push button pin
int ledPin = 9;     // the number of the LED pin
boolean isLighting = false; // define a variable to save the state of LED

void setup() {
  pinMode(buttonPin, INPUT);  // set push button pin into input mode
  pinMode(ledPin, OUTPUT);    // set LED pin into output mode
}

void loop() {
  if (digitalRead(buttonPin) == LOW) {        // if the button is pressed
    delay(10);    // delay for a certain time to skip the bounce
    if (digitalRead(buttonPin) == LOW) {      // confirm again if the button is pressed
      reverseLED();                           // reverse LED
      while (digitalRead(buttonPin) == LOW);  // wait for releasing
      delay(10);  // delay for a certain time to skip bounce when the button is released
    }
  }
}

void reverseLED() {
  if (isLighting) {             // if LED is lighting,
    digitalWrite(ledPin, LOW);  // switch off LED
    isLighting = false;         // store the state of LED
  }
  else {                        // if LED is off,
    digitalWrite(ledPin, HIGH); // switch LED
    isLighting = true;          // store the state of LED
  }
}
```

We use a function reverseLED () to change the state of the LED.

When judging the push button state, if it is detected "pressed down", wait for a certain time to detect again to eliminate the effect of bounce. When confirmed, it starts to wait for the push button to be released, and waits for a certain time to eliminate the effect of bounce after it is released.

Verify and upload the code, then each time you press the button, LED changes its state accordingly.

Sketch 5.2.2

Beginners can upload Sketch_5.2.2 to try not dealing with the push button bounce and see what happens.

Chapter 6 Serial

Earlier, we already try to output signals to LED, and get the input signal of push button. Now, we can try a more advanced means of communication—serial communication.

Project 6.1 Send data through Serial

We will use the serial port on Freenove UNO to send data to computer.

Component list

Freenove UNO x1 	USB cable x1 

Code knowledge

Bit and Byte

As mentioned earlier, the computer uses a binary signal. A binary signal is called 1 bit, and 8 bits organize in order is called 1 byte. Byte is the most basic unit of storage and communications for processors. 1 byte can represent a 2^8=256 numbers, that is, 0-255. For example:

As to binary number 10010110, "0" usually present the lowest in code.

Sequence	7	6	5	4	3	2	1	0
Number	1	0	0	1	0	1	1	0

When a binary number need to be converted to decimal number, first, the nth number of it need be multiplied by n power of 2, then sum all multiplicative results. Take 10010110 as an example:

1*2^7+0*2^6+0*2^5+1*2^4+0*2^3+1*2^2+1*2^1+0*2^0=150

We can make decimal number divided by 2 to convert it to binary number. Quotient continuously obtained divided by 2 until quotient is zero. Arrange all remainders from right to left in a line. Then we complete the conversion. For example:

		Remainder	Sequence
2	150	0	0
2	75	1	1
2	37	1	2
2	18	0	3
2	9	1	4
2	4	0	5
2	2	0	6
2	1	1	7
	0		

The result is 10010110.

Circuit knowledge

Serial and parallel communication

Serial communication uses one data cable to transfer data one bit by another in turn. Parallel communication means that the data is transmitted simultaneously on multiple cables. Serial communication takes only a few cables to exchange information between systems, especially suitable for computers to computer, long distance communication between computers and peripherals. Parallel communication is faster, but with more cables and the high cost, so it is not appropriate for long distance communication.



Serial communication

Serial communication generally refers to the Universal Asynchronous Receiver/Transmitter (UART). And it is commonly used in electronic circuit communication. It has two communication lines, one is responsible for sending data (TX line) and another for receiving data (RX line). The serial communication connections two devices use is as follows:



Before serial communication starts, the baud rate in both sides must be the same. Only use the same baud rate can the communication between devices be normal. The baud rates commonly used is 9600 and 115200.

Serial port on Arduino

Freenove UNO has integrated USB to serial transfer, could communicates with computer when USB cable get connected to it. Arduino Software also uploads code for Freenove UNO through the serial connection. Computer identifies serial devices connected to your computer as COMx. We can use the Serial Monitor window of Arduino Software to communicate with Freenove UNO, connect Freenove UNO to computer through the USB cable, choose the right device, and then click the Serial Monitor icon to open the Serial Monitor window.



Interface of Serial Monitor window is as follows. If you can't open it, make sure Freenove UNO had been connected to the computer, and choose the right serial port in the menu bar "Tools".



Circuit

Connect Freenove UNO to the computer with USB cable.



Sketch

Sketch 6.1.1

Now, write code to send some text to the Serial Monitor window

```
1
2
int counter = 0;  // define a variable as a data sending to serial port
```

```
3   void setup() {
4     Serial.begin(9600);                  // initialize the serial port, set the baud rate to 9600
5     Serial.println("UNO is ready!");     // print the string "UNO is ready!"
6   }
7
8   void loop() {
9     // print variable counter value to serial
10    Serial.print("counter:");    // print the string "counter:"
11    Serial.println(counter);     // print the variable counter value
12    delay(500);                  // wait 500ms to avoid cycling too fast
13    counter++;                   // variable counter increases 1
14  }
```

setup() function initializes the serial port and send the string "UNO is ready!".
Then continuously sends variable counter values in the loop () function.

Serial class

Class is a C++ language concept. Arduino Software supports C++ language, which is a language extension. We don't explain specifically the concept here, only describes how to use it. If you are interested, you can learn that by yourself. Serial is a class name, which contains variables and functions. You can use the "." operational character to visit class variables and functions, such as:

Serial.begin(speed): Initialize serial port, the parameter is the serial port baud rate;
Serial.print(val): Send string, the parameter here is what you want to send;
Serial.println(val): Send newline behind string.

Verify and upload the code, open the Serial Monitor, then you'll see data sent from UNO.
If it is not displayed correctly, check the Serial Monitor whether configuration in the lower right corner of the window is correct.



Project 6.2 Receive Data through Serial Port

From last section, we use Serial port on Freenove UNO to send data to a computer, now we will use that to receive data from computer.

Component list

Same with last section.

Code knowledge

Interruption

Interruption is controller's response to an event. The event causing an interruption is interruption source. We'll illustrate this interruption concept. If you're watching TV, while water is heating, then you have to check whether the water is boiling or not from time to time, so you can't concentrate on watching TV. But interruption can work as warning device for kettle, and before the water is boiling, you can focus on watching TV until a beep warning comes out, then go to handle it.

Advantages of interruption here: Processor won't need to check whether the event has happened every now and then., but when the event occurs, it informs the controller immediately. When an interruption occurs, the processor will jump to the interrupt function to handle interruption events, then return to the interruption place after finishing it and go on this program.



Circuit

Same with last section.

Sketch

Sketch 6.2.1

Now, write code to receive the characters from Serial Monitor window, and send it back.

```
1  char inChar;      // define a variable to store characters received from serial port
2
3  void setup() {
4    Serial.begin(9600);                 // initialize serial port, set baud rate to 9600
5    Serial.println("UNO is ready!");    // print the string "UNO is ready!"
6  }
7
8  void loop() {
9    if (Serial.available()) {          // judge whether data has been received
10     inChar = Serial.read();          // read one character
11     Serial.print("UNO received:");   // print the string "UNO received:"
12     Serial.println(inChar);          // print the received character
13   }
14 }
```

In the setup() function, we initialize the serial port and send the string "UNO is ready!". Then, the loop() function will continuously detect whether there are data needs to be read. if so, read the character and send it back.

Serial Class

Serial.available(): return bytes of data that need to be read by serial port;
Serial.read(): return 1 byte of data that need to be read by serial port.

Verify and upload the code, open the Serial Monitor, write character in sending area, click Send button, then you'll see information returned from UNO.



char type

char type variable can represent a character, but char type cannot store characters directly. It stores numbers to replace characters. char type occupies 1-byte store area, and use a value 0-127 to correspond to 128 characters. The corresponding relation between number and character is ruled by ASCII table. For more details of ASCII table, please refer to the appendix of this book.
Example: Define char aChar = 'a', bChar = '0', then the decimal value of aChar is 97, bChar will be 48.

Sketch 6.2.2

When serial port receives data, it can trigger an interrupt event, and enter into the interrupt handling function. Now we use an interrupt to receive information from Serial Monitor window, and sends it back. To illustrate the interrupt does not influence the program's running, we will constantly send changing number in loop () function.

```
1  char inChar;      // define a variable to store character received from serial port
2  int counter = 0;  // define a variable as the data sent to Serial port
3
4  void setup() {
5    Serial.begin(9600);                 // initialize serial port and set baud rate to 9600
6    Serial.println("UNO is ready!");    // print the string "UNO is ready!"
7  }
8
9  void loop() {
10   // Print value of variable counter to serial
11   Serial.print("counter:");    // print the string "counter:"
12   Serial.println(counter);     // print the value of variable "counter"
13   delay(1000);                 // wait 1000ms to avoid cycling too fast
14   counter++;                   // variable "counter" increases 1
15 }
16
17 void serialEvent() {
18   if (Serial.available()) {          // judge whether the data has been received
19     inChar = Serial.read();          // read one character
20     Serial.print("UNO received:");   // print the string "UNO received:"
21     Serial.println(inChar);          // print the received character
22   }
23 }
```

void serialEvent () function here is the serial port interrupt function. When serial receives data, processor will jump to this function, and return to the original interrupt place to proceed after execution. So loop () function's running is not affected.

Verify and upload the code, open the Serial Monitor, then you'll see the number constantly sent from UNO. Fill character in the sending area, and click the Send button, then you'll see the string returned from UNO.



Project 6.3 Application of Serial

We will use the serial port on Freenove UNO to control one LED.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	LED x1 	Resistor 220Ω x1 
Jumper M/M x2 		

Circuit

Here we will use D11 pin of Freenove UNO to output PWM to drive 1 LED.

Schematic diagram	Hardware connection
	

Sketch

Sketch 6.3.1

Code is basically the same with Sketch 6.2.1. But after receiving the data, Freenove UNO will convert it into PWM duty cycle from output port.

```
int inInt;        // define a variable to store the data received from serial
int counter = 0;  // define a variable as the data sending to serial
int ledPin = 11;  // the number of the LED pin

void setup() {
  pinMode(ledPin, OUTPUT);             // initialize the LED pin as an output
  Serial.begin(9600);                  // initialize serial port, set baud rate to 9600
  Serial.println("UNO is ready!");     // print the string "UNO is ready!"
}

```

```
11  void loop() {
12    if (Serial.available()) {          // judge whether the data has been received
13      inInt = Serial.parseInt();       // read an integer
14      Serial.print("UNO received:");   // print the string "UNO received:"
15      Serial.println(inInt);           // print the received character
16      // convert the received integer into PWM duty cycle of ledPin port
17      analogWrite(ledPin, constrain(inInt, 0, 255));
18    }
19  }
```

When serial receives data, it converts the data into PWM duty cycle of output port, and then causes LED to emit light with corresponding brightness.

Serial Class

Serial.parseInt(): Receive an int type number as the return value.

constrain(x, a, b)

Limit x between a and b, if x<a, return a; if x>b, return b.

Verify and upload the code, open the Serial Monitor, and put a number in the range 0-255 into the sending area and click the Send button. Then you'll see information returned from UNO, meanwhile, LED can emit light with different brightness according to the number you send.



Chapter 7 ADC

Before, we have learned the digital ports of Freenove UNO, and tried the output and input signals. Now, let's learn how to use analog ports.

Project 7.1 ADC

ADC is used to convert analog signals into digital signals. Control chip on Freenove has integrated this function. Now let us try to use this function to convert analog signals into digital signals.

Component list

Freenove UNO x1 	Breadboard x1 
USB cable x1 	Rotary potentiometer x1 
Jumper M/M x3 	

Circuit knowledge

ADC

ADC, Analog-to-Digital Converter, is a device used to convert analog to digital. Freenove UNO has a 10 bits ADC, that means the resolution is 2^10=1024, and the range (here is 5V) will be divided equally into 1024 parts. The analog of each section corresponds to one ADC value. So the more bits ADC has, the denser the partition of analog will be, also the higher precision of the conversion will be.



Subsection 1: the analog in rang of 0V-5/1024V corresponds to digital 0;
Subsection 2: the analog in rang of 5 /1024V-2*5/1024V corresponds to digital 1;
...
The following analog will be divided accordingly.

Component knowledge

Potentiometer

Potentiometer is a resistive component with three terminal parts and its resistance can be adjusted in accordance with according to a certain change rule. Potentiometer is often made up by resistance and removable brush. When the brush moves along the resistor body, there will be resistance or voltage that has a certain relationship with displacement on the output side (3). Figure shown below is the linear sliding potentiometer and its symbol.



Pin 1 and pin 2 of the potentiometer is connected to two ends of a resistor body respectively, and pins 3 is connected to a brush. When the brush moves from pin 1 to pin 2, resistance between pin 1 and pin 3 will increase up to max resistance of the resistor body linearly, and resistance between pin 2 and pin 3 will decrease down to 0 linearly.

In the circuit, the two sides of resistor body are often connected to the positive and negative electrodes of a power respectively. When you slide the brush of pin 3, you can get a certain voltage in the range of negative voltage to positive voltage of the power supply.



Rotary potentiometer

Rotary potentiometer and linear potentiometer have similar function; the only difference is: the resistance is adjusted through rotating the potentiometer.



Circuit

Use A0 port on Freenove UNO to detect the voltage of rotary potentiometer.

Schematic diagram	Hardware connection
	

Sketch

Sketch 7.1.1

Now, write code to detect the voltage of rotary potentiometer, and send the data to Serial Monitor window of Arduino Software through serial port.

```
int adcValue;     // Define a variable to save ADC value
float voltage;    // Define a variable to save the calculated voltage value

void setup() {
  Serial.begin(9600);      // Initialize the serial port and set the baud rate to 9600
  Serial.println("UNO is ready!");    // Print the string "UNO is ready!"
}

void loop() {
  adcValue = analogRead(A0);          // Convert analog of A0 port to digital
  voltage = adcValue * (5.0 / 1023.0);// Calculate voltage according to digital
  // Send the result to computer through serial
  Serial.print("convertValue:");
  Serial.println(adcValue);
  Serial.print("Voltage:");
  Serial.println(voltage);
  delay(500);
}
```

From the code, we get the ADC value of A0 pin, then convert it into voltage and sent to the serial port. Verify and upload the code, open the Serial Monitorto, then you will see the original ADC value and converted voltage sent from UNO.

Turn the rotary potentiometer shaft, and you can see the voltage change.



Project 7.2 Control LED by Potentiometer

In the last section, we have finished reading ADC value and convert it into voltage. Now, we will try to use potentiometer to control the brightness of LED.

Component list

<table>
<tr><td colspan="2">Freenove UNO x1
  </td><td colspan="3">Breadboard x1
  </td></tr>
<tr><td colspan="2">USB cable x1
  </td><td rowspan="2">Rotary potentiometer x1
  </td><td rowspan="2">LED x1
  </td><td rowspan="2">Resistor 220Ω x1
  </td></tr>
<tr><td colspan="2">Jumper M/M x5
  </td></tr>
</table>

Circuit

Use A0 on Freenove UNO to detect the voltage of rotary potentiometer, and use D9 to control one LED.

Schematic diagram	Hardware connection
	

Sketch

Sketch 7.2.1

Now, write the code to detect the voltage of rotary potentiometer, and control LED to emit light with different brightness according to that.

```
int adcValue;      // Define a variable to save the ADC value
int ledPin = 9;    // Use D9 on Freenove UNO to control the LED

void setup() {
  pinMode(ledPin, OUTPUT);              // Initialize the LED pin as an output
}

void loop() {
  adcValue = analogRead(A0);            // Convert the analog of A0 port to digital
  // Map analog to the 0-255 range, and works as PWM duty cycle of ledPin port
  analogWrite(ledPin, map(adcValue, 0, 1023, 0, 255));
}
```

In the code, we get the ADC value of A0 pin and map it to PWM duty cycle of LED pin port. According to different LED brightness, we can see the voltage changes easily.

Verify and upload the code, turn the rotary potentiometer shaft, then you will see the LED brightness changes.



Project 7.3 Control LED through Photoresistor

In the last section, we have finished reading ADC value and converted it into LED brightness. There are many components, especially the sensor whose output is analog. Now, we will try to use photoresistor to measure the brightness of light.

Component list

Freenove UNO x1 		Breadboard x1 		
USB cable x1 		Photoresistor x1 	LED x1 	Resistor 10kΩ x1 	Resistor 220Ω x1 
Jumper M/M x5				

Component knowledge

Photoresistor

Photoresistor is a light sensitive resistor. When the strength that light casts onto the photoresistor surface is not the same, resistance of photoresistor will change. With this feature, we can use photoresistor to detect light intensity. Photoresistor and symbol are as follows.



The circuit below is often used to detect the change of photoresistor resistance:



In the above circuit, when photoresistor resistance changes due to light intensity, voltage between photoresistor and resistor R1 will change, so light's intensity can be obtained by measuring the voltage.

Circuit

Use A0 port on Freenove UNO to detect the voltage of photoresistor, and use D9 to control one LED.

Schematic diagram	Hardware connection
	

Sketch

Sketch 7.3.1

Now, write code to detect the voltage of photoresistor, and control LED to emit light with different brightness according to that.

```
int convertValue; // Define a variable to save the ADC value
int ledPin = 9;   // The number of the LED pin

void setup() {
  pinMode(ledPin, OUTPUT);  // Set ledPin into output mode
}

void loop() {
  convertValue = analogRead(A0);  // Read analog voltage value of A0 port, and save
  // Map analog to the 0-255 range, and works as ledPin duty cycle setting
  analogWrite(ledPin, map(convertValue, 0, 1023, 0, 255));
}
```

In the code, we get the ADC value of A0 pin, map that to PWM duty cycle of LED pin port. According to the LED brightness, we can see the voltage changes easily.

Verify and upload the code, cover photoresistor with your hand, then you can see the LED brightness changes.



Chapter 8 RGB LED

Before, we have learned to apply the analog port and ADC of Freenove UNO. Now, we'll use ADC to control RGB LED.

Project 8.1 Control RGB LED through Potentiometer

RGB LED has three different-color LED inside, and we will use 3 potentiometers to control these 3 LEDs to emit light with different brightness, and observe what will happen.

Component list

<table>
<tr><td>Freenove UNO x1
  </td><td colspan="3">Breadboard x1
  </td></tr>
<tr><td>USB cable x1
  </td><td rowspan="2">Rotary potentiometer x3
  </td><td rowspan="2">RGB LED x1
  </td><td rowspan="2">Resistor 220Ω x3
  </td></tr>
<tr><td>Jumper M/M x15
  </td></tr>
</table>

Component knowledge

RGB LED

RGB LED has integrated 3 LEDs that can respectively emit red, green and blue light, and it has 4 pins. The long pin (1) is the common port, that is, 3 LED 's cathode or anode. The RGB LED with common anode and its symbol are as follows. By controlling these 3 LED to emit light with different brightness, we can make RGB LED emit various colors of light.



Red, green, and blue light are called tricolor light. When you combine these three primary-color light with different brightness, it can produce almost all visible light. Computer screens, single pixel of cell phone screen, neon, and etc. are working through this principle.



We know from previous section that, UNO controls LED to emit a total 256(0-255) different brightness by PWM. So, through the combination of three different colors of LED, RGB LED can emit 256^3=16777216 Colors, 16Million colors.

Circuit

Use A0, A1, A2 port of Freenove UNO to detect the voltage of rotary potentiometer, and control RGB LED by D9, D10, D11.

Schematic diagram



Hardware connection



Sketch

Sketch 8.1.1

Now, write code to detect the voltage of these three rotary potentiometers, and convert that into PWM duty cycle to control 3 LED inside the RGB LED.

```
// set pin numbers:
int ledPinR = 11;   // the number of the LED R pin
int ledPinG = 10;   // the number of the LED G pin
int ledPinB = 9;    // the number of the LED B pin

void setup() {
  // initialize the LED pin as an output:
  pinMode(ledPinR, OUTPUT);
  pinMode(ledPinG, OUTPUT);
  pinMode(ledPinB, OUTPUT);
}

void loop() {
  int adcValue;     // Define a variable to save the ADC value
  // Convert analog of A0 port into digital, and work as PWM duty cycle of ledPinR port
  adcValue = analogRead(A0);
  analogWrite(ledPinR, map(adcValue, 0, 1023, 0, 255));
  // Convert analog of A1 port into digital, and work as PWM duty cycle of ledPinG port
  adcValue = analogRead(A1);
  analogWrite(ledPinG, map(adcValue, 0, 1023, 0, 255));
  // Convert analog of A2 port into digital, and work as PWM duty cycle of ledPinB port
  adcValue = analogRead(A2);
  analogWrite(ledPinB, map(adcValue, 0, 1023, 0, 255));
}
```

In the code, we get the voltage of three rotary potentiometers, and convert that into PWM duty cycle to control these three LED of the RGB LED to emit light with different brightness.

Verify and upload the code, turn the three rotary potentiometer shaft, then you can see the LED light changes in color and brightness.

Project 8.2 Colorful LED

From previous section, we have finished controlling the RGB LED to emit light with different color and brightness through three potentiometers. Now, we will try to make RGB LED emit colorful light automatically.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	RGB LED x1 	Resistor 220Ω x3 
Jumper M/M x4 		

Circuit

Use D9, D10, D11 of Freenove UNO to control RGB LED.

Schematic diagram



Hardware connection



Sketch

Sketch 8.2.1

Now, write code to generate three random number, and convert that into PWM duty cycle to control these three LED of RGB LED.

```
// set pin numbers:
int ledPinR = 11;   // the number of the LED R pin
int ledPinG = 10;   // the number of the LED G pin
int ledPinB = 9;    // the number of the LED B pin

void setup() {
  // initialize the LED pin as an output:
  pinMode(ledPinR, OUTPUT);
  pinMode(ledPinG, OUTPUT);
  pinMode(ledPinB, OUTPUT);
}

void loop() {
  // Generate three random numbers between 0-255 as the output PWM duty cycle of ledPin
  rgbLedDisplay(random(256), random(256), random(256));
  delay(500);
}

void rgbLedDisplay(int red, int green, int blue) {
  // Set three ledPin to output the PWM duty cycle
  analogWrite(ledPinR, constrain(red, 0, 255));
  analogWrite(ledPinG, constrain(green, 0, 255));
  analogWrite(ledPinB, constrain(blue, 0, 255));
}
```

In the code, we create three random number, and convert that into PWM duty cycle, controlling these three LED of RGB LED to emit light with different brightness. At regular intervals, a new random number will be created, so RGB LED will start flashing light with different colors and brightness.

random(min, max)

random (min, max) function is used to generate random number, and it will return a random value in the range (min, Max-1).

You can also use random (max) function, the function set the minimum value into 0 by default, and returns a random value in the range (0, Max-1).

Verify and upload the code, then RGB LED starts flashing with different colors and brightness.

Chapter 9 Buzzer

Before, we have used Freenove UNO and basic electronic components to carry out a series of interesting projects. Now, let's learn how to use some integrated electronic components and modules. These modules are usually integrated with a number of electronic components, so it has special features and uses.

In this chapter, we'll use a sounding module, buzzer. It has two types: active and passive buzzer.

Project 9.1 Active Buzzer

First, let's study some knowledge about active buzzer.

Component list

Freenove UNO x1 		Breadboard x1 		
USB cable x1 		Jumper M/M x6 		
NPN transistorx1 	Active buzzer x1 	Push button x1 	Resistor 1kΩ x1 	Resistor 10kΩ x2 

Component knowledge

Transistor

Transistor, the full name: semiconductor transistor, is a semiconductor device that controls current. Transistor can be used to amplify weak signal, or works as a switch. It has three electrodes(PINs): base (b), collector (c) and emitter (e). When there is current passing between "be", "ce" will allow several-fold current (transistor magnification) pass, at this point, transistor works in the amplifying area. When current between "be" exceeds a certain value, "ce" will not allow current to increase any longer, at this point, transistor works in the saturation area. Transistor has two types shown below: PNP and NPN,

PNP transistor



NPN transistor



According to the transistor's characteristics, it is often used as a switch in digital circuits. For micro-controller's capacity of output current is very weak, we will use transistor to amplify current and drive large-current components.

Buzzer

Buzzer is a sounding component, which is widely used in electronic devices such as calculator, electronic warning clock, alarm. Buzzer has active and passive type. Active buzzer has oscillator inside, and it will make a sound as long as it is supplied with power. Passive buzzer requires external oscillator signal (generally use PWM with different frequency) to make a sound.

Active buzzer



Passive buzzer



Active buzzer is easy to use. Generally, it can only make a specific frequency of sound. Passive buzzer requires an external circuit to make a sound, but it can be controlled to make a sound with different frequency. The resonant frequency of the passive buzzer is 2kHz, which means the passive buzzer is loudest when its resonant frequency is 2kHz.

Buzzer needs larger current when it works. But generally, microcontroller port cannot provide enough current for that. In order to control buzzer by UNO, transistor can be used to drive a buzzer indirectly.

When use NPN transistor to drive buzzer, we often adopt the following method. If UNO pin outputs high level, current will flow through R1, the transistor gets conducted, and the buzzer make a sound. If UNO pin outputs low level, no current flows through R1, the transistor will not be conducted, and buzzer will not sound.



When use PNP transistor to drive buzzer, we often adopt the following method. If UNO pin outputs low level, current will flow through R1, the transistor gets conducted, buzzer make a sound. If UNO pin outputs high level, no current flows through R1, the transistor will not be conducted, and buzzer will not sound.



Circuit

Use D12 port of Freenove UNO to detect the state of push button, and D9 to drive active buzzer.

Schematic diagram



Hardware connections



Sketch

Sketch 9.1.1

Now, write code to detect the state of push button, and drive active buzzer to make a sound when it is pressed.

```
int buttonPin = 12;    // the number of the push button pin
int buzzerPin = 9;     // the number of the buzzer pin

void setup() {
  pinMode(buttonPin, INPUT);  // Set push button pin into input mode
  pinMode(buzzerPin, OUTPUT); // Set Buzzer pin into output mode
}

void loop() {
 if (digitalRead(buttonPin) == HIGH)// If the pin is high level, the button is not pressed.
    digitalWrite(buzzerPin, LOW);     // Turn off Buzzer
  else                                // The button is pressed, if the pin is low level
    digitalWrite(buzzerPin, HIGH);    // Turn on Buzzer
}
```

In the code, we check the state of push button. When it is pressed, the output high level controls transistor to get conducted, and drives active buzzer to make a sound.

Verify and upload the code, press the push button, then the active buzzer will make a sound.



Project 9.2 Passive Buzzer

In the last section, we have finished using transistor to driven active buzzer to beep. Now, we will try to use passive buzzer to make a sound with different frequency.

Component list

Freenove UNO x1 	Breadboard x1 		
USB cable x1 	NPN transistor x1 	Passive buzzer x1 	Resistor 1kΩ x1 
Jumper M/M x4 			

Circuit

Use D9 port of Freenove UNO to drive a passive buzzer.

Schematic diagram	Hardware connection
	

Sketch

Sketch 9.2.1

Now, write code to drive a passive buzzer to make a warning sound. The frequency of that conforms roughly to following sine curve over time:



Output PWM wave with different frequency to the port, which is connected to transistor, to drive buzzer to make a sound with different frequency.

```
1  int buzzerPin = 9;     // the number of the buzzer pin
2  float sinVal;          // Define a variable to save sine value
3  int toneVal;           // Define a variable to save sound frequency
4
5  void setup() {
6    pinMode(buzzerPin, OUTPUT); // Set Buzzer pin to output mode
7  }
8
9  void loop() {
10   for (int x = 0; x < 360; x++) {        // X from 0 degree->360 degree
11     sinVal = sin(x * (PI / 180));        // Calculate the sine of x
12     toneVal = 2000 + sinVal * 500;       // Calculate sound frequency according to the sine of x
13     tone(buzzerPin, toneVal);            // Output sound frequency to buzzerPin
14     delay(1);
15   }
16 }
```

In the code, use one loop to control the sound frequency, varying according to sine curve in the range 2000±500.

```
10   for (int x = 0; x < 360; x++) {        // X from 0 degree->360 degree
11     sinVal = sin(x * (PI / 180));        // Calculate the sine of x
12     toneVal = 2000 + sinVal * 500;       // Calculate sound frequency according to the sine of x
13     tone(buzzerPin, toneVal);            // Output sound frequency to buzzerPin
14     delay(1);
15   }
```

The parameter of sin() function is radian, so we should convert unit of π from angle to radian first before using it.

tone(pin, frequency)

Generates a square wave of the specified frequency (and 50% duty cycle) on a pin.

Verify and upload the code, passive buzzer starts making a warning sound.

You can try using PNP transistor to complete the project of this chapter again.

Chapter 10 Temperature Sensor

Before, we have used Freenove UNO and photoresistor to detect the intensity of light. Now, we will learn to use the temperature sensor.

Project 10.1 Detect the temperature

We will use a thermistor to detect the ambient temperature.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	Thermistor x1 	Resistor 10kΩ x1 
Jumper M/M x3 		

Component knowledge

Thermistor

Thermistor is a temperature sensitive resistor. When the temperature changes, resistance of thermistor will change. With this feature, we can use thermistor to detect temperature intensity. Thermistor and symbol are as follows.



The relationship between resistance value and temperature of thermistor is:

Rt=R*EXP[B*(1/T2-1/T1)]

Where:

Rt is the thermistor resistance under T2 temperature;

R is in the nominal resistance of thermistor under T1 temperature;

EXP[n] is nth power of E;

B is for thermal index;

T1, T2 is Kelvin temperature (absolute temperature). Kelvin temperature=273.15+celsius temperature.

Parameters of the thermistor we use is: B=3950, R=10k, T1=25.

The circuit connection method of the thermistor is similar to photoresistor, like the following method:



We can use the value measured by the analog pin of UNO to obtain resistance value of thermistor, and then can use the formula to obtain the temperature value.

Circuit

Use A0 port on Freenove UNO to detect the voltage of thermistor.

Schematic diagram	Hardware connection
	

Sketch

Sketch 10.1.1

Now, write the code to detect the voltage value of thermistor, calculate the temperature value, and send it to Serial Monitor window.

```
1  void setup() {
2    Serial.begin(9600);                  // Initialize the serial port, set the baud rate
   into 9600
3    Serial.println("UNO is ready!");     // Print the string "UNO is ready!"
4  }
5
6  void loop() {
7    // Convert analog value of A0 port into digital value
8    int adcVal = analogRead(A0);
```

```
9     // Calculate voltage
10    float v = adcVal * 5.0 / 1024;
11    // Calculate resistance value of thermistor
12    float Rt = 10 * v / (5 - v);
13    // Calculate temperature (Kelvin)
14    float tempK = 1 / (log(Rt / 10) / 3950 + 1 / (273.15 + 25));
15    // Calculate temperature (Celsius)
16    float tempC = tempK - 273.15;
17
18    // Send the result to computer through serial port
19    Serial.print("Current temperature is: ");
20    Serial.print(tempK);
21    Serial.print(" K, ");
22    Serial.print(tempC);
23    Serial.println(" C");
24    delay(500);
25  }
```

In the code, we obtain the ADC value of A0 pin, and convert it into temperature value, then send it to the serial port.

Verify and upload the code, open the Monitor Serial, then you will see the temperature value sent from UNO board.



Chapter 11 Motor

Before, we have done a series of interesting projects with Freenove UNO and basic electronic components. Now, let's study some movable electronic modules. In this chapter, we will learn to control the motor.

Project 11.1 Control Motor by Relay

First, use relay to control the Motor.

Component list

Freenove UNO x1 			Breadboard x1 		
USB cable x1 			Jumper M/M x8 		
AA Battery holder x1 			Resistor 10kΩ x2 	Resistor 1kΩ x1 	Resistor 220Ω x1 
NPN transistor x1 	Relay x1 	Motor x1 	Push button x1 	LED x1 	Diode x1 

Component knowledge

Motor

Motor is a device that converts electrical energy into mechanical energy. Motor consists of two parts: stator and rotor. When motor works, the stationary part is stator, and the rotating part is rotor. Stator is usually the outer case of motor, and it has terminals to connect to the power. Rotor is usually the shaft of motor, and can drive other mechanical devices to run. Diagram below is a small DC motor with two pins.



When motor get connected to the power supply, it will rotate in one direction. Reverse the polarity of power supply, then motor rotates in opposite direction.



Capacitor

The unit of capacitance(C) is farad (F). 1F=1000000μF, 1μF=1000000pF.

Capacitor is an energy storage device, with a certain capacitance. When capacitor voltage increases, the capacitor will be charged. And capacitor will discharge when the voltage drops. So capacitor voltage of both ends is not transient. According to this characteristic, capacitor is often used to stabilize the voltage of power supply, and filters the signal. Capacitor with large capacity can filter out low frequency signals, and small-capacity capacitor can filter out high frequency signals.

The capacitor has a non-polar capacitor and a polar capacitor. Generally, non-polar capacitor has small capacitance, and a ceramic non-polar capacitor is shown below.

For polar capacitor, it usually has larger capacitance, and an electrolytic polar capacitor of that is shown below:



When the motor rotates, it will generate noise. As the contact of coil connects and disconnects the electrode constantly, it will cause the supply voltage unstable. Thus, a small capacitor is often connected to motor to reduce the impact on power supply from motor.

Relay

Relay is an electrical switch, which consists of coils and contacts. When the coil is energized, it will form the electromagnet, attracting contacts to close. Coils and contacts are independent of each other, so other independent circuit can be controlled by relay, through using a small current to control the circuit with large current. Diagram below is a relay with control voltage of 5V.



Pin 5 and pin 6 are connected to each other inside. When the coil pin3 and 4 get connected to 5V power supply, pin 1 will be disconnected to pin 5&6 and pin 2 will be connected to pin 5&6. So pin 1 is called close end, pin 2 is called open end.

Inductor

The unit of inductance(L) is the henry (H). 1H=1000mH, 1mH=1000μH.

Inductor is an energy storage device that converts electrical energy into magnetic energy. Generally, it consists of winding coil, with a certain amount of inductance. Inductor will hinder the changing current passing through the inductor. When the current passing through inductor increases, it will attempt to hinder the increasing trend of current; and when the current passing through the inductor decreases, it will attempt to hinder the decreasing trend of current. So the current passing through inductor is not transient.

The reference circuit for relay is as follows. The coil of relay can be equivalent to inductor, when the transistor disconnects power supply of the relay, the current in the coil of the relay can't stop immediately, causing an impact on power supply. So a parallel diode will get connected to both ends of relay coil pin in reversing direction, then the current will pass through diode, avoiding the impact on power supply.



Circuit

Use D12 of Freenove UNO to detect the state of push button, and D9 to control the relay. As motor running needs larger power, we will use two AA batteries to supply power for the motor alone.

Schematic diagram



Hardware connections



Sketch

Sketch 11.1.1

Now, write code to detect the state of push button. Each time you press the button, the switching status of relay will change. So we control the motor to rotate or stop in this way.

```
int relayPin = 9;      // the number of the relay pin
int buttonPin = 12;    // the number of the push button pin

int buttonState = HIGH;      // Record button state, and initial the state to high level
int relayState = LOW;        // Record relay state, and initial the state to low level
int lastButtonState = HIGH; // Record the button state of last detection
long lastChangeTime = 0;     // Record the time point for button state change

void setup() {
  pinMode(buttonPin, INPUT);  // Set push button pin into input mode
  pinMode(relayPin, OUTPUT);  // Set relay pin into output mode
  digitalWrite(relayPin, relayState); // Set the initial state of relay into "off"
  Serial.begin(9600);                 // Initialize serial port,and set baud rate to 9600
}

void loop() {
  int nowButtonState = digitalRead(buttonPin); // Read current state of button pin
  // If button pin state has changed, record the time point
  if (nowButtonState != lastButtonState) {
    lastChangeTime = millis();
  }
  // If button state changes, and stays stable for a while, then it should have skipped the bounce area
  if (millis() - lastChangeTime > 10) {
    if (buttonState != nowButtonState) {  // Confirm button state has changed
      buttonState = nowButtonState;
      if (buttonState == LOW) {      // Low level indicates the button is pressed
        relayState = !relayState;            // Reverse relay state
        digitalWrite(relayPin, relayState); // Update relay state
        Serial.println("Button is Pressed!");
      }
      else {                         // High level indicates the button is released
        Serial.println("Button is Released!");
      }
    }
  }
  lastButtonState = nowButtonState; // Save the state of last button
}
```

In this code, we used a new method to detect button state. In the loop() function, the level state of button pin is detected constantly. When the level is changed, record this time. If the level has not changed after a while, it will be considered bounce area has already been skipped. Then, judge whether the button is pressed or released according to button pin state.

First, define two variables to record the state of button and relay.

```
4  int buttonState = HIGH;      // Record button state, initial the state into high level
5  int relayState = LOW;        // Record relay state, initial the state into low level
```

Define a variable to record button pin state of last detection.

```
6  int lastButtonState = HIGH; // Record the button state of last detection
```

Define a variable to record the time of the last button pin changes.

```
7  long lastChangeTime = 0;     // Record the time point for button state change
```

In the loop() function, the detected pin state of button will be compared with the last detected state. If it changes, record this time.

```
16 void loop() {
17   int nowButtonState = digitalRead(buttonPin); // Read current state of button pin
18   // If the state of button pin has changed, record the time point
19   if (nowButtonState != lastButtonState) {
20     lastChangeTime = millis();
21   }
...  ...
36   lastButtonState = nowButtonState; // Save the state of last button
37 }
```

If the level stays unchanged over a period of time, it is considered bounce area has already been skipped.

```
23   if (millis() - lastChangeTime > 10) {
...    ...
35   }
```

After the pin state stays stable, the changed state of button is confirmed, then it will be recorded for the next comparison.

```
24     if (buttonState != nowButtonState) {  // Confirm button state has changed
25       buttonState = nowButtonState;
...      ...
34     }
```

Judge whether the button is pressed or released according to button pin level, print button information to serial port, and reverse relay when the button is pressed.

```
26       if (buttonState == LOW) {      // Low level indicates the button is pressed
27         relayState = !relayState;            // Reverse relay state
28         digitalWrite(relayPin, relayState); // Update relay state
29         Serial.println("Button is Pressed!");
30       }
31       else {                         // High level indicates the button is released
32         Serial.println("Button is Released!");
33       }
```

This button detecting method does not put program into the state of delay waiting, you can increase the efficiency of code execution.

millis()
Returns the number of milliseconds since the Arduino board began running the current program.

Verify and upload the code, every time you press the push button, the state of relay and motor changes once.

Project 11.2 Control Motor by L293D

Now, we will use dedicated chip L293D to control the Motor.

Component list

Freenove UNO x1 	Breadboard x1 		
USB cable x1 	Jumper M/M x10 		
AA Battery holder x1 	Motor x1 	L293D x1 	Rotary potentiometer x1 

Component knowledge

L293D

L293D is a chip integrated with 4-channel motor drive. You can drive a unidirectional motor with 4 ports or a bi-directional motor with 2 port or a stepper motor.



Port description of L293D module is as follows:

Pin name	Pin number	Description
In x	2, 7, 10, 15	Channel x digital signal input pin
Out x	3, 6, 11, 14	Channel x output pin, input high or low level according to In x pin, get connected to +Vmotor or 0V
Enable1	1	Channel 1 and channel 2 enable pin, high level enable
Enable2	9	Channel 3 and channel 4 enable pin, high level enable
0V	4, 5, 12, 13	Power cathode (GND)
+V	16	Positive electrode (VCC) of power supply, supply voltage 4.5~36V
+Vmotor	8	Positive electrode of load power supply, provide power supply for the Out pin x, the supply voltage is +V~36V

For more details, please see datasheet.

When using L293D to drive DC motor, there are usually two kinds of connection.
Following connection uses one channel, and it can control motor speed through PWM, but the motor can only rotate in one direction.



Following connection uses two channels: one channel outputs PWM wave, and another channel connects GND, so you can control the speed of motor. Whe n these two channel signals are exchanged, the current direction of the motor can be reversed, and the motor will rotate in reverse direction. This can not only control the speed of motor, but also can control the steering of motor.



In actual use, motor is usually connected to the channel 1 and 2, output different level to in1 and in2 to control the rotation direction of the motor, and output PWM wave to Enable1 port to control the motor rotation speed. Or, get motor connected to the channel 3 and 4, output different level to in3 and in4 to control the motor's rotation direction, and output PWM wave to Enable2 pin to control the motor rotation speed.

Circuit

Use A0 of Freenove UNO to detect the voltage of rotary potentiometer; D9, D10 to control the motor's rotation direction, D11 to output PWM wave to control motor speed.

Schematic diagram



Hardware connection



Sketch

Sketch 11.2.1

Now, write the code to control speed and rotation direction of motor through rotary potentiometer. When the potentiometer stays in the middle position, motor speed will be minimum, and when deviates intermediate position, the speed will increase. Also, if the potentiometer deviates from the middle position potentiometer clockwise or counterclockwise, the rotation direction of the motor is different.

```
int in1Pin = 10;        // Define L293D channel 1 pin
int in2Pin = 9;         // Define L293D channel 2 pin
int enable1Pin = 11;    // Define L293D enable 1 pin

boolean rotationDir;    // Define a variable to save the motor's rotation direction, true and false are represented by positive rotation and reverse rotation.
int rotationSpeed;      // Define a variable to save the motor rotation speed

void setup() {
  // Initialize the pin into an output mode:
  pinMode(in1Pin, OUTPUT);
  pinMode(in2Pin, OUTPUT);
  pinMode(enable1Pin, OUTPUT);
}

void loop() {
  int potenVal = analogRead(A0);   // Convert the voltage of rotary potentiometer into digital
  // Compare the number with value 512, if more than 512, clockwise rotates, otherwise, counter clockwise rotates
  rotationSpeed = potenVal - 512;
  if (potenVal > 512)
    rotationDir = true;
  else
    rotationDir = false;
  // Calculate the motor speed, the far number of deviation from the middle value 512, the faster the control speed will be
  rotationSpeed = abs(potenVal - 512);
  // Control the steering and speed of the motor
  driveMotor(rotationDir,map(rotationSpeed, 0, 512, 0, 255));
}

void driveMotor(boolean dir, int spd) {
  // Control motor rotation direction
  if (rotationDir) {
    digitalWrite(in1Pin, HIGH);
    digitalWrite(in2Pin, LOW);
  }
  else {
    digitalWrite(in1Pin, LOW);
    digitalWrite(in2Pin, HIGH);
  }
  // Control motor rotation speed
  analogWrite(enable1Pin, constrain(spd, 0, 255));
}
```

In the code, we write a function to control the motor, and control the speed and steering through two parameters.

```
29  void driveMotor(boolean dir, int spd) {
30    // Control motor rotation direction
31    if (rotationDir) {
32      digitalWrite(in1Pin, HIGH);
33      digitalWrite(in2Pin, LOW);
34    }
35    else {
36      digitalWrite(in1Pin, LOW);
37      digitalWrite(in2Pin, HIGH);
38    }
39    // Control motor rotation speed
40    analogWrite(enable1Pin, constrain(spd, 0, 255));
41  }
```

In the loop () function, detect the digital value of rotary potentiometer, and convert that into the motor speed and steering through calculation.

```
15  void loop() {
16    int potenVal = analogRead(A0);   // Convert the voltage of rotary potentiometer into digital
17    // Compare the digital number with middle value 512, if more than 512, clockwise rotates, otherwise,
      counter clockwise rotates
18    rotationSpeed = potenVal - 512;
19    if (potenVal > 512)
20      rotationDir = true;
21    else
22      rotationDir = false;
23    // Calculate the motor speed, the far number of deviation from the middle value 512, the faster the
      control speed will be
24    rotationSpeed = abs(potenVal - 512);
25    // Control the steering and speed of the motor
26    driveMotor(rotationDir, map(rotationSpeed, 0, 512, 0, 255));
27  }
```

abs(x)

Computes the absolute value of a number.

Verify and upload the code, turn the shaft of rotary potentiometer, then you can see the change of the motor speed and direction.

Chapter 12 Servo

Before, we have used Freenove UNO and L293D module to control the motor speed and steering. Now, we will use another motor, servo, which can rotate to a certain angle.

Project 12.1 Servo Sweep

First, let's get the servo to rotate.

Component list

Freenove UNO x1 	USB cable x1 
	Jumper M/M x3 
	Servo x1 

Component knowledge

Servo

Servo is an auto-control system, consisting of DC motor, reduction gear, sensor and control circuit. Usually, it can rotate in the range of 180 degrees. Servo can output larger torque and is widely used in model airplane, robot and so on. It has three lines, including two for electric power line positive (2-VCC, red), negative (3-GND, brown), and the signal line (1-Signal, orange).





We use 50Hz PWM signal with a duty cycle in a certain range to drive the servo. The lasting time 0.5ms-2.5ms of PWM single cycle high level corresponds to the servo angle 0 degrees - 180 degree linearly. Part of the corresponding values are as follows:

High level time	Servo angle
0.5ms	0 degree
1ms	45 degree
1.5ms	90 degree
2ms	135 degree
2.5ms	180 degree

When you change the servo signal, servo will rotate to the designated position.

Circuit

Use D3 of Freenove UNO to drive the servo.

Pay attention to the color of servo lead wire: VCC (red), GND (brown), and signal line (orange). The wrong connection can cause damage to servo.

Schematic diagram	Hardware connection
	

Sketch

Sketch 12.1.1

Now, write the code to control servo, making it sweep in the motion range continuously.

```
#include <Servo.h>

Servo myservo;                  // create servo object to control a servo

int pos = 0;                    // variable to store the servo position
int servoPin = 3;               // define the pin of servo signal line

void setup() {
  myservo.attach(servoPin); // attaches the servo on servoPin to the servo object
}

```

```
12  void loop() {
13    for (pos = 0; pos <= 180; pos += 1) { // goes from 0 degrees to 180 degrees
14      // in steps of 1 degree
15      myservo.write(pos);              // tell servo to go to position in variable "pos"
16      delay(15);                       // waits 15ms for the servo to reach the position
17    }
18    for (pos = 180; pos >= 0; pos -= 1) { // goes from 180 degrees to 0 degrees
19      myservo.write(pos);              // tell servo to go to position in variable "pos"
20      delay(15);                       // waits 15ms for the servo to reach the position
21    }
22  }
```

Servo uses the Servo library, like the following reference to Servo library:

```
1  #include <Servo.h>
```

Servo library provides the Servo class that controls it. Different from previous Serial class, the Servo class must be instantiated before you use:

```
3  Servo myservo;              // create servo object to control a servo
```

The code above defines an object of Servo type, myservo.

Servo Class

Servo class must be instantiated when used, that is, define an object of Servo type, for example:

Servo myservo;

Most Arduino control board can define 12 objects of Servo type, namely, it can control up to 12 servos.

The function commonly used in the servo class is as follows:

myservo.attach(pin): Initialize the servo, the parameter is the port connected to servo signal line;

myservo.write(angle): Control servo to rotate to the specified angle; parameter here is to specify the angle.

After the Servo object is defined, it can refer to the function, such as initializing the servo:

```
9    myservo.attach(servoPin); // attaches the servo on servoPin to the servo object
```

After initializing the servo, you can control the servo to rotate to a specific angle:

```
15     myservo.write(pos);              // tell servo to go to position in variable "pos"
```

In the loop () function, we use the loop to control the servo to rotate from 0 degrees to 180 degrees, and then from 180 degrees to 0 degrees, then repeat the cycle all the time.

Verify and upload the code, the servo starts to sweep continuously.



Project 12.2 Control Servo by Potentiometer

In the last section, we've made the servo sweep continuously. Now, we will use potentiometer to control the servo angle.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	Rotary potentiometer x1 	Servo x1 
Jumper M/M x6 		

Circuit

Use A0 of Freenove UNO to detect the voltage of rotary potentiometer, and D3 to drive the servo.

Schematic diagram	Hardware connection
	

Sketch

Sketch 12.2.1

Now, write the code to detect the voltage of rotary potentiometer, and control servo to rotate to a different angle according to that.

```
#include <Servo.h>

Servo myservo;              // create servo object to control a servo

int servoPin = 3;           // define the pin of servo signal line
int potPin = 0;             // analog pin used to connect the potentiometer
int potVal;                 // variable to read the potValue from the analog pin

void setup() {
  myservo.attach(servoPin); // attaches the servo on servoPin to the servo object
}

void loop() {
  potVal = analogRead(potPin);          // reads the potValue of the potentiometer
  potVal = map(potVal, 0, 1023, 0, 180);// scale it to use it with the servo
  myservo.write(potVal);                // sets the servo position
  delay(15);                            // waits for the servo to get there
}
```

In the code, we obtain the ADC value of A0 pin, and map it to the servo angle.

Verify and upload the code, turn the potentiometer shaft, then the servo will rotate to the corresponding angle.



Chapter 13 LCD1602

In the previous chapter, we have used the LED matrix to display images and characters. Now, let us use a screen module LCD1602 with a higher resolution to display more content.

Project 13.1 Display the string on LCD1602

Firstly, use LCD1602 to display some strings.

Component list

Freenove UNO x1 	Breadboard x1 
USB cable x1 	Jumper M/M x16 
LCD1602 x1 	Rotary potentiometer x1 

Component knowledge

LCD1602

LCD1602 can display 2 lines of characters in 16 columns. It can display numbers, letters, symbols, ASCII code and so on. As shown in the following is a monochrome LCD1602 display screen:



Circuit symbol and pin descriptions of LCD1602 are shown as follows:



Pin name	Pin number	Description
VSS	1	Negative electrode of power supply
VDD	2	Positive electrode of power supply, the voltage is 5V
V0	3	Contrast and adjust the display effect
RS	4	Data/Command selection
RW	5	Read/Write selection
E	6	Enable pin
D0-D7	7-14	Data pin
LED+	15	Positive electrode of backlight LED, the voltage is 5V
LED-	16	Negative electrode of backlight LED

For more details, please refer to the dataheet.

Circuit

The connection of Freenove UNO board and LCD1602 is shown below. And use a rotary potentiometer to adjust the contrast of LCD1602.

Schematic diagram



Hardware connection



Sketch

Sketch 13.1.1

Now write code to make LCD1602 display a string and changing numbers.

```
#include <LiquidCrystal.h>

// initialize the library with the numbers of the interface pins
LiquidCrystal lcd(12, 11, 5, 4, 3, 2);

void setup() {
  // set up the LCD's number of columns and rows:
  lcd.begin(16, 2);
  // Print a message to the LCD
  lcd.print("hello, world!");
}

void loop() {
  // set the cursor to column 0, line 1
  // (note: line 1 is the second row, since counting begins with 0):
  lcd.setCursor(0, 1);
  // print the number of seconds since reset:
  lcd.print("Counter:");
  lcd.print(millis() / 1000);
}
```

Use LiquidCrystal library to control the LCD:

```
#include <LiquidCrystal.h>
```

LiquidCrystal library provides a specific class used to control LCD1602. We instantiate a LiquidCrystal object, and we can input some parameters which is related to pins of the LCD1602:

```
LiquidCrystal lcd(12, 11, 5, 4, 3, 2);
```

Initialize the LCD1602 in the setup () function, and the parameters are the number of columns and rows of characters which LCD can display:

```
  lcd.begin(16, 2);
```

And then print a string:

```
  lcd.print("hello, world!");
```

Print a changing number in the loop () function:

```
void loop() {
  // set the cursor to column 0, line 1
  // (note: line 1 is the second row, since counting begins with 0):
  lcd.setCursor(0, 1);
  // print the number of seconds since reset:
  lcd.print("Counter:");
  lcd.print(millis() / 1000);
}
```

Before printing characters, we need to set the coordinate of the printed character, that is, in which line and which column:

```
16    lcd.setCursor(0, 1);
```

If we don't set the coordinate, the string will be printed behind the last printed character.

LiquidCrystal class

The LiquidCrystal class can manipulate common LCD screens. The first step is defining an object of LiquidCrystal, for example:

LiquidCrystal lcd(12, 11, 5, 4, 3, 2);

when instantiate the object, we need to write the pins connected to the LCD. There are many different ways for instantiation LiquidCrystal class. The way we use is shown below:

LiquidCrystal(rs, enable, d4, d5, d6, d7) ;

The common function of LiquidCrystal is shown below：

lcd.begin(cols, rows): Initialize the LCD, and the parameters are the number of columns and rows of characters which LCD can display;

lcd.setCursor(col, row): set the coordinate of the printed character, and the parameters is the row and the column (starting from 0, the number 0 represents first line or column);

lcd.print(data): print the number and letters in the coordinate we set before. If we haven't set the coordinate, the string will be printed behind the last printed character.

Verify and upload the code, then you will see the LCD1602 display the string and changing number.
If the display of character is not normal, shift the rotary potentiometer to adjust the contrast.

Project 13.2 LCD1602 Clock

In the last chapter, we have used LCD1602 to display some strings, and now let us use LCD1206 to make a clock.

Component list

Freenove UNO x1 	Breadboard x1 	
USB cable x1 	Jumper M/M x19 	
LCD1602 x1 	Rotary potentiometer x1 	LM35 x1 

Code knowledge

Timer

Timer can be set to produce an interrupt after a period of time. When the timer interrupt occurs, the processor will jump to the interrupt function to process the interrupt event. And after completion the processing, execution will return to the interrupted place to go on. If you don't close the timer, interrupt will occur at intervals you set.



Circuit

The connection between Freenove UNO board and LCD1602 is shown below, and a rotary potentiometer is used to adjust the contrast of LCD1602. A4 port is used to detect the voltage of LM35 output pin.

Schematic diagram



Hardware connection



Sketch

Sketch 13.2.1

Before starting to write code, we need to import the library file we need. In the Arduino Software menu bar, click on the Add.ZIP Library, and add the FlexiTimer2.zip under the Libraries folder. The FlexiTimer2 library can help manipulate the timer.

Now write code to make LCD1602 display the time and temperature, and the time can be modified through the serial port.

```
#include <LiquidCrystal.h>    // Contains LiquidCrystal Library
#include <FlexiTimer2.h>      // Contains FlexiTimer2 Library

// initialize the library with the numbers of the interface pins
LiquidCrystal lcd(12, 11, 5, 4, 3, 2);

int tempPin = 4;                // define the pin of LM35 temperature sensor
float tempVal;                  // define a variable to store temperature value
int hour, minute, second;       // define variables stored record time

void setup() {
  lcd.begin(16, 2);     // set up the LCD's number of columns and rows
  startingAnimation();  // display a dynamic start screen
  FlexiTimer2::set(1000, timerInt);  // configure the timer and interrupt function
  FlexiTimer2::start();              // start timer
  Serial.begin(9600);                // initialize serial port with baud rate 9600
  Serial.println("UNO is ready!");   // print the string "UNO is ready!"
  Serial.println("Input hour,minute,second to set time.");
}

void loop() {
  // read digital value of LM35 pin and convert the temperature to Celsius
  tempVal = analogRead(tempPin) / 1023.0 * 5.0 / 0.01;
  if (second >= 60) {       // when seconds is equal to 60, minutes plus 1
    second = 0;
    minute++;
    if (minute >= 60) {     // when minutes is equal to 60, hours plus 1
      minute = 0;
      hour++;
      if (hour >= 24) {     // when hours is equal to 24, hours turn to zero
        hour = 0;
      }
    }
  }
  lcdDisplay();             // display temperature and time information on LCD
```

```
36    delay(200);
37  }
38
39  void startingAnimation() {
40    for (int i = 0; i < 16; i++) {
41      lcd.scrollDisplayRight();
42    }
43    lcd.print("starting...");
44    for (int i = 0; i < 16; i++) {
45      lcd.scrollDisplayLeft();
46      delay(300);
47    }
48    lcd.clear();
49  }
50
51  // the timer interrupt function of FlexiTimer2 is executed every 1s
52  void timerInt() {
53    second++;       // second plus 1
54  }
55
56  // serial port interrupt function
57  void serialEvent() {
58    int inInt[3];  // define an array to save the received serial data
59    while (Serial.available()) {
60      for (int i = 0; i < 3; i++) {
61        inInt[i] = Serial.parseInt();  // receive 3 integer data
62      }
63      // print the received data for confirmation
64      Serial.print("Your input is: ");
65      Serial.print(inInt[0]);
66      Serial.print(", ");
67      Serial.print(inInt[1]);
68      Serial.print(", ");
69      Serial.println(inInt[2]);
70      // use received data to adjust time
71      hour = inInt[0];
72      minute = inInt[1];
73      second = inInt[2];
74      // print the modified time
75      Serial.print("Time now is: ");
76      Serial.print(hour / 10);
77      Serial.print(hour % 10);
78      Serial.print(':');
79      Serial.print(minute / 10);
```

```
80      Serial.print(minute % 10);
81      Serial.print(':');
82      Serial.print(second / 10);
83      Serial.println(second % 10);
84    }
85  }
86
87  // function used by LCD1602 to display time and temperature
88  void lcdDisplay() {
89    lcd.setCursor(0, 0);  // set the cursor to (0,0) (first column,first row).
90    lcd.print("TEMP: ");  // display temperature information
91    lcd.print(tempVal);
92    lcd.print("C");
93    lcd.setCursor(0, 1);  // set the cursor to (0,1) (first column,second row)
94    lcd.print("TIME: ");  // display time information
95    lcd.print(hour / 10);
96    lcd.print(hour % 10);
97    lcd.print(':');
98    lcd.print(minute / 10);
99    lcd.print(minute % 10);
100   lcd.print(':');
101   lcd.print(second / 10);
102   lcd.print(second % 10);
103 }
```

In the code, we define 3 variables to represent time: second, minute, hour.

```
9   int hour, minute, second;       // define variables to store hour,minute,seconds
```

Defines a timer with cycle of 1000 millisecond (1 second). And each interrupt makes the second plus 1. When setting the timer, you need to define a function and pass the function name that works as parameter to FlexiTimer2::set () function.

```
14    FlexiTimer2::set(1000, timerInt);   // configure timer and timer interrupt function
15    FlexiTimer2::start();               // start timer
```

After every interrupt, the second plus 1.

```
52  void timerInt() {
53    sec++;   // second plus 1
54  }
```

:: operator

"::" is scope operator. The function behind "::" belongs to the scope of the front. If we want to call the function defined in the FlexiTimer2 scope outside, we need to use the "::". It can be global scope operator, class scope operator and namespace scope operator. It is a namespace scope operator here. Because functions of FlexiTimer2 library is defined in the namespace of FlexiTimer2, so we can find them in FlexiTimer2 library file.

In the loop () function, the information on the LCD display will be refreshed at set intervals.

```
21  void loop() {
…       …
35    lcdDisplay();             // display temperature and time information on LCD
36    delay(200);
37  }
```

In the loop function, we need to control the second, minute, hour. When the second increases to 60, the minute adds 1, and reset the second to zero; when the minute increases to 60, the hour adds 1, and reset the minute to zero; when the hour increases to 24, reset it to zero.

```
24    if (second >= 60) {       // when the second increases to 60, the minute adds 1
25      second = 0;
26      minute++;
27      if (minute >= 60) {     //when the minute increases to 60, the hour adds 1
28        minute = 0;
29        hour++;
30        if (hour >= 24) {     // when the hour increases to 24, turn it to zero
31          hour = 0;
32        }
33      }
34    }
```

We define a function lcdDisplay () to refresh the information on LCD display. In this function, use two bit to display the hour, minute, second on the LCD. Such as hour/ 10 is the units, hour% 10 is the tens.

```
88  void lcdDisplay() {
89    lcd.setCursor(0, 0);  // set the cursor to (0,0) (first column,first row).
90    lcd.print("TEMP: ");  // display temperature information
91    lcd.print(tempVal);
92    lcd.print("C");
93    lcd.setCursor(0, 1);  // set the cursor to (0,1) (first column,second row)
94    lcd.print("TIME: ");  // display time information
95    lcd.print(hour / 10);
96    lcd.print(hour % 10);
97    lcd.print(':');
98    lcd.print(minute / 10);
99    lcd.print(minute % 10);
100   lcd.print(':');
101   lcd.print(second / 10);
102   lcd.print(second % 10);
103 }
```

Serial port interrupt function is used to receive the data sent by computer to adjust the time, and return the data for confirmation.

```
57  void serialEvent() {
58    int inInt[3];  // define an array to save the reveived serial data
59    while (Serial.available()) {
60      for (int i = 0; i < 3; i++) {
```

```
61          inInt[i] = Serial.parseInt();  // receive 3 integer data
62        }
63        // print the received data for confirmation
64        Serial.print("Your input is: ");
65        Serial.print(inInt[0]);
66        Serial.print(", ");
67        Serial.print(inInt[1]);
68        Serial.print(", ");
69        Serial.println(inInt[2]);
70        // use the received data to adjust time
71        hour = inInt[0];
72        minute = inInt[1];
73        second = inInt[2];
74        // print the modified time
75        Serial.print("Time now is: ");
76        Serial.print(hour / 10);
77        Serial.print(hour % 10);
78        Serial.print(':');
79        Serial.print(minute / 10);
80        Serial.print(minute % 10);
81        Serial.print(':');
82        Serial.print(second / 10);
83        Serial.println(second % 10);
84      }
85    }
```

We also define a function that displays a scrolling string when the UNO has been just started.

```
39  void startingAnimation() {
40    for (int i = 0; i < 16; i++) {
41      lcd.scrollDisplayRight();
42    }
43    lcd.print("starting...");
44    for (int i = 0; i < 16; i++) {
45      lcd.scrollDisplayLeft();
46      delay(300);
47    }
48    lcd.clear();
49  }
```

Verify and upload the code. The LCD screen will display a scrolling string first, and then displays the temperature and time. We can open Monitor Serial and enter time in the sending area, then click the Send button to set the time.



Chapter 14 Ultrasonic Ranging

In this chapter, we learn a module which use ultrasonic to measure distance, HC-SR04 ultrasonic ranging module.

Project 14.1 Ultrasonic Ranging

In this project, we use ultrasonic ranging module to measure distance, and print out the data in the serial port.

Component List

Freenove UNO x1 	USB cable x1 
	Jumper F/M x4 
	Ultrasonic ranging module x1 

Component Knowledge

Ultrasonic ranging module

Ultrasonic ranging module use the principle that ultrasonic will reflect when it encounters obstacles. Ultrasonic module integrates a transmitter and a receiver. The transmitter is used to convert electrical signals (electrical energy) into sound waves (mechanical energy) and the function of the receiver is opposite.





Start counting the time when ultrasonic is transmitted. And when ultrasonic encounters an obstacle, it will reflect back. The counting will end after ultrasonic is received, and the time difference is the total time of ultrasonic from transmitting to receiving. Because the speed of sound in air is constant, and is about v=340m/s. So we can calculate the distance between the modle and the obstacle: S=vt/2.



Pin description:

Pin name	Pin number	Description
Vcc	1	Positive electrode of power supply, the voltage is 5V
Trig	2	Triger pin
Echo	3	Echo pin
Gnd	4	Negative electrode of power supply

Instructions for use:

Output a high-level pulse in Trig pin lasting for least 10us. Then the the module begins to transmit ultrasonic. At the same time, the Echo pin will be pulled up. When the module receives the returned ultrasonic, the Echo pin will be pulled down. The duration of high level in Echo pin is the total time of the ultrasonic from transmitting to receiving, s=vt/2, which is used to operate the HC-SR04 in Arduino.

Circuit

The connection of Freenove UNO board and HC-SR04 is shown below.

Schematic diagram



Hardware connection



Sketch

Sketch 14.1.1

First, we use the HC-SR04 communication protocol to operate the module, get the range of time, and calculate the distance.

```
#define trigPin 12 // define TrigPin
#define echoPin 11 // define EchoPin.
#define MAX_DISTANCE 200 // Maximum sensor distance is rated at 400-500cm.
// define the timeOut according to the maximum range. timeOut= 2*MAX_DISTANCE /100 /340 *1000000 = MAX_DISTANCE*58.8
float timeOut = MAX_DISTANCE * 60;
int soundVelocity = 340; // define sound speed=340m/s

void setup() {
  pinMode(trigPin,OUTPUT);// set trigPin to output mode
  pinMode(echoPin,INPUT); // set echoPin to input mode
  Serial.begin(9600);     // Open serial monitor at 9600 baud to see ping results.
}

void loop() {
  delay(100); // Wait 100ms between pings (about 20 pings/sec). 29ms should be the shortest delay between pings.
  Serial.print("Ping: ");
  Serial.print(getSonar()); // Send ping, get distance in cm and print result (0 = outside set distance range)
  Serial.println("cm");
}

float getSonar() {
  unsigned long pingTime;
  float distance;
  digitalWrite(trigPin, HIGH); // make trigPin output high level lasting for 10μs to triger HC_SR04,
  delayMicroseconds(10);
  digitalWrite(trigPin, LOW);
  pingTime = pulseIn(echoPin, HIGH, timeOut); // Wait HC-SR04 returning to the high level and measure out this waitting time
  distance = (float)pingTime * soundVelocity / 2 / 10000; // calculate the distance according to the time
  return distance; // return the distance value
}
```

First, define the pins and the maximum measurement distance.

```
1  #define trigPin 12 // define TrigPin
2  #define echoPin 11 // define EchoPin.
3  #define MAX_DISTANCE 200 // Maximum sensor distance is rated at 400-500cm.
```

If the module does not return high level, we can not wait forever. So we need to calculate the lasting time over maximum distance, that is, time Out. timOut= 2*MAX_DISTANCE/100/340*1000000. The constant part behind is approximately equal to 58.8.

```
5  float timeOut = MAX_DISTANCE * 60;
```

Then, in the setup (), set the pin to input or output, and set the serial port. In the loop(). We continue to use serial to print the value of subfunction getSonar (), which is used to return the measured distance of the HC HC_SR04. Make trigPin output a high level lasting for at least 10μS, according to the communication protocol.

```
24   digitalWrite(trigPin, HIGH); // make trigPin output high level lasting for 10μs to
     triger HC_SR04,
25   delayMicroseconds(10);
26   digitalWrite(trigPin, LOW);
```

Then the echoPin of HC_SR04 will output a pulse. Time of the pulse is the total time of ultrasonic from transmitting to receiving. We use the pulseIn () function to return the time, and set the timeout.

```
27   pingTime = pulseIn(echoPin, HIGH, timeOut); // Wait HC-SR04 returning to the high level
     and measure out this waitting time
```

Calculate the distance according to the time and return the value.

```
28   distance = (float)pingTime * soundVelocity / 2 / 10000; // calculate the distance
     according to the time
29   return distance; // return the distance value
```

Finally, the code above will be called in the loop ().

pulseIn(pin, value) / pulseIn(pin, value, timeout)

Return the length of the pulse (in microseconds) or 0 if no pulse is completed before the timeout (unsigned long).

Verify and upload the code to the UNO. Open the serial port monitoring window. Turn the HC-SR04 probe towards the object plane, and observe the data in the serial port monitoring window.



Sketch 14.1.2

We can also use the library function to directly obtain the measuring distance. We need import the file NewPing.zip before using the library.

```
#include <NewPing.h>
#define trigPin 12 // define TrigPin
#define echoPin 11 // define EchoPin.
#define MAX_DISTANCE 200 // Maximum sensor distance is rated at 400-500cm.

NewPing sonar(trigPin, echoPin, MAX_DISTANCE); // NewPing setup of pins and maximum distance.

void setup() {
  Serial.begin(9600); // Open serial monitor at 9600 baud to see ping results.
}

void loop() {
  delay(50); // Wait 50ms between pings (about 20 pings/sec). 29ms should be the shortest delay between pings.
  Serial.print("Ping: ");
  Serial.print(sonar.ping_cm()); // Send ping, get distance in cm and print result (0 = outside set distance range)
  Serial.println("cm");
}
```

First, include the header file of library, and then define the HC SR04 pin and the maximum measurement distance. And, write these parameters when we define the NewPing class objects.

```
#include <NewPing.h>
#define trigPin 12 // define TrigPin
#define echoPin 11 // define EchoPin.
#define MAX_DISTANCE 200 // Maximum sensor distance is rated at 400-500cm.
```

And then, in the loop (), use sonar.ping_cm () to obtain the the ultrasonic module detection distance with unit of centimeter. And print the distance out. When the distance exceeds range of 2cm~200cm, the printed data is zero.

NewPing Class

NewPing class can be used for SR04, SRF05, SRF06 and other sensors. An object that needs to be instantiated when the class is used. The three parameters of the constructor function are: trigger pin, echo pin and maximum measurement distance.

NewPing sonar(trigger_pin, echo_pin [, max_cm_distance])

Some member function:

sonar.ping() - Send a ping and get the echo time (in microseconds) as a result.

sonar.ping_in() - Send a ping and get the distance in whole inches.

sonar.ping_cm() - Send a ping and get the distance in whole centimeters.

For more details, please refer to the NewPing.h in the NewPing library.

Verify and uploaded the code to UNO. Open the serial port monitoring window. When you make ultrasonic probe toward a plane of an object, you can observate the distance changes.



What's next?

Thanks for your reading.

This book is all over here. If you find any mistakes, missions or you have other ideas and questions about contents of this book or the kit and ect, please feel free to contact us, and we will check and correct it as soon as possible.

If you want to learn more about Arduino, Raspberry Pi, smart cars, robots and orther interesting products in science and technology, please continue to focus on our website. We will continue to launch cost-effective, innovative and exciting products.

Thank you again for choosing Freenove products.

Appendix

ASCII table

Dec	Hex	Char	Dec	Hex	Char	Dec	Hex	Char	Dec	Hex	Char
0	00	Null	32	20	Space	64	40	@	96	60	`
1	01	Start of heading	33	21	!	65	41	A	97	61	a
2	02	Start of text	34	22	"	66	42	B	98	62	b
3	03	End of text	35	23	#	67	43	C	99	63	c
4	04	End of transmit	36	24	$	68	44	D	100	64	d
5	05	Enquiry	37	25	%	69	45	E	101	65	e
6	06	Acknowledge	38	26	&	70	46	F	102	66	f
7	07	Audible bell	39	27	'	71	47	G	103	67	g
8	08	Backspace	40	28	(	72	48	H	104	68	h
9	09	Horizontal tab	41	29	)	73	49	I	105	69	i
10	0A	Line feed	42	2A	*	74	4A	J	106	6A	j
11	0B	Vertical tab	43	2B	+	75	4B	K	107	6B	k
12	0C	Form feed	44	2C	,	76	4C	L	108	6C	l
13	0D	Carriage return	45	2D	-	77	4D	M	109	6D	m
14	0E	Shift out	46	2E	.	78	4E	N	110	6E	n
15	0F	Shift in	47	2F	/	79	4F	O	111	6F	o
16	10	Data link escape	48	30	0	80	50	P	112	70	p
17	11	Device control 1	49	31	1	81	51	Q	113	71	q
18	12	Device control 2	50	32	2	82	52	R	114	72	r
19	13	Device control 3	51	33	3	83	53	S	115	73	s
20	14	Device control 4	52	34	4	84	54	T	116	74	t
21	15	Neg. acknowledge	53	35	5	85	55	U	117	75	u
22	16	Synchronous idle	54	36	6	86	56	V	118	76	v
23	17	End trans. block	55	37	7	87	57	W	119	77	w
24	18	Cancel	56	38	8	88	58	X	120	78	x
25	19	End of medium	57	39	9	89	59	Y	121	79	y
26	1A	Substitution	58	3A	:	90	5A	Z	122	7A	z
27	1B	Escape	59	3B	;	91	5B	[	123	7B	{
28	1C	File separator	60	3C	<	92	5C	\	124	7C	|
29	1D	Group separator	61	3D	=	93	5D	]	125	7D	}
30	1E	Record separator	62	3E	>	94	5E	^	126	7E	~
31	1F	Unit separator	63	3F	?	95	5F	_	127	7F	□

Resistor color code



COLOR	1ST BAND	2ND BAND	3RD BAND	MULTIPLIER	TOLERANCE
Black	0	0	0	1Ω	
Brown	1	1	1	10Ω	± 1% (F)
Red	2	2	2	100Ω	± 2% (G)
Orange	3	3	3	1KΩ	
Yellow	4	4	4	10KΩ	
Green	5	5	5	100KΩ	± 0.5% (D)
Blue	6	6	6	1MΩ	± 0.25% (C)
Violet	7	7	7	10MΩ	± 0.10% (B)
Grey	8	8	8		± 0.05%
White	9	9	9		
Gold				0.1Ω	± 5% (J)
Silver				0.01Ω	± 10% (K)