hackerearth

Signup and get free access to 100+ Tutorials and Practice Problems

Start Now

All Tracks > Algorithms > Dynamic Programming > Introduction to Dynamic Programming 1 > Problem



Roy and Ropes

Attempted by: 1870 / Accuracy: 82% / Maximum Score: 20 / ★★★★☆ 14 Votes


Tag(s): Ad-Hoc, Dynamic Programming, Easy, Implementation

EDITORIAL PROBLEM ANALYTICS

Roy has a rope of length

L meters. This rope has several other ropes attached to it at the end of every meter (except for the end of the rope).

At each meter there are two ropes attached to this main rope, let's call them upper and lower ropes. See the following example.



Roy lit the rope on fire from the left end. This fire burns down the rope by 1 meter/minute.

Your task is to find how much time (in minutes) will the fire take to burn down the entire rope.

Input:

First line contains

T - number of test cases.

First line of each test case contains

L - length of the rope.

Second line of each test case contains

L-1 integers separated by space denoting lengths of all the upper ropes at each meter.

Third line of each test case contains

L-1 integers separated by space denoting lengths all the lower ropes at each meter.

Output:

Output the time (in minutes) required to burn down the entire rope for each test case in a new line.

Constraints:

$$1 \le T \le 10$$

$$2 \le L \le 1000000$$

$$0 \leq upper[i] \leq 1000000$$
 where


$$1 \le i \le L - 1$$


$$0 \leq lower[i] \leq 1000000$$
 where

$$1 < i < L - 1$$

Sample Explanation:

Follow the nature of fire. Note that after 1 min. Fire can go in all three directions. Hence after 2 mins fire burnt 1meter in all 3 directions. Rest is explained in the image below.






Time Limit:	1.0 sec(s) for each input file.
Memory Limit:	256 MB
Source Limit:	1024 KB
Marking Scheme:	Marks are awarded when all the testcases pass.
Allowed Languages:	C, C++, Clojure, C#, D, Erlang, F#, Go, Groovy, Haskell, Java, Java 8, JavaScript(Rhino), JavaScript(Node.js), Lisp, Lisp
	(SBCL), Lua, Objective-C, OCaml, Octave, Pascal, Perl, PHP, Python, Python 3, R(RScript), Racket, Ruby, Rust, Scala,
	Scala 2.11.8, Swift, Visual Basic

CODE EDITOR

Initializing Code Editor								
Your Rating:								
PROGRAMMERS WHO SOLVED THIS PROBLEM ALSO SOLVED								
Tower Of Hanoi Attempted By: 577 / Accuracy: 92	Tablets Attempted By: 827 / Accuracy: 91							

Once Upon A Time In Time-Land

Attempted By: 1559 / Accuracy: 58



CONTRIBUTOR




AUTHOR Ravi Ojha



TESTER

Deepankar Anil Kumar



ABOUT US	HACKEREARTH	DEVELOPERS	EMPLOYERS	REACH US
Blog	API	AMA	Developer Sourcing	Ground Floor, Salarpuria Business Center,
Engineering Blog	Chrome Extension	Code Monk	Lateral Hiring	4th B Cross Road, 5th A Block,
Updates & Releases	CodeTable	Judge Environment	Campus Hiring	Koramangala Industrial Layout, Bangalore, Karnataka 560095, India.
Team	HackerEarth	Solution Guide	Hackathons	
Careers	Academy	Problem Setter	FAQs	contact@hackerearth.com
In the Press	Developer Profile	Guide	Customers	+91-80-4155-4695 +1-650-461-4192
	Resume	Practice Problems		11-030-401-4192
	Get Badges	HackerEarth		f in G.
	Campus Ambassadors	Challenges		
		College Challenges		
	Get Me Hired	College Ranking		

Organise Hackathon Privacy

Terms of Service Hackathon

Handbook

Competitive Programming

Open Source



© 2017 HackerEarth