



Signup and get free access to 100+ Tutorials and Practice Problems

Start Now

[All Tracks](#) > [Algorithms](#) > [Dynamic Programming](#) > [Introduction to Dynamic Programming 1](#) > Problem

5

LIVE EVENTS

Xsquare And Coin Collection

Attempted by: **1143** / Accuracy: **65%** / Maximum Score: **20** / ★★★★★ 0 Votes

Tag(s): Ad-Hoc, Easy, Implementation

PROBLEM

EDITORIAL

ANALYTICS

Xsquare loves to play with the coins very much. Today , he has N stacks of coins . Each stack of coins has some non zero height H_i equal to the number of coins on that stack (considering all the coins are identical and each coin has a height of **1 unit**) .

In one move, Xsquare can select any number of consecutive stacks of coins such that the height of each selected stack of coins $H_i \leq K$. Once such a sequence of stacks is chosen , Xsquare can collect any number of coins from the chosen sequence of stacks .

Xsquare wonders what is the maximum number of coins that he can collect this way ?

INPUT

First line of input contains a single integer T denoting the number of test cases . First line of each test case contains two space separated integers N and K where N being the number of stacks of coins. Second line of each

test case contains **N** space separated integers denoting the number of coins H_i on each stack .

OUTPUT

For each test case , Print the maximum number of coins Xsquare can collect following the above gaming strategy.

CONSTRAINTS

$$1 \leq T \leq 10^5$$

$$1 \leq N \leq 10^5$$

$$1 \leq K \leq 10^9$$

$$1 \leq H_i \leq 10^9$$

Note :

sum of **N** over all the test case will not exceed 10^6 .

SAMPLE INPUT

```
2
8 1
3 2 2 3 1 1 1 3
8 2
3 2 2 3 1 1 1 3
```

SAMPLE OUTPUT

3

4

Explanation

Test 1 : $N = 8$, $K = 1\ 3\ 2\ 2\ 3\ 1\ 1\ 1\ 3$ We can collect coins from stacks numbered 5 , 6 and 7 .

Test 2 : $N = 8$, $K = 2\ 3\ 2\ 2\ 3\ 1\ 1\ 1\ 3$ We can collect coins from stacks numbered 2 and 3 .

Time Limit: 3.0 sec(s) for each input file.

Memory Limit: 256 MB

Source Limit: 1024 KB

Marking Scheme: Marks are awarded when all the testcases pass.

Allowed Languages: C, C++, Clojure, C#, D, Erlang, F#, Go, Groovy, Haskell, Java, Java 8, JavaScript(Rhino), JavaScript(Node.js), Lisp, Lisp (SBCL), Lua, Objective-C, OCaml, Octave, Pascal, Perl, PHP, Python, Python 3, R(RScript), Racket, Ruby, Rust, Scala, Scala 2.11.8, Swift, Visual Basic

CODE EDITOR

Initializing Code Editor...

Your Rating:

PROGRAMMERS WHO SOLVED THIS PROBLEM ALSO SOLVED

Xsquare And Balanced Strings

Attempted By: **990** / Accuracy: **57**

Samu And Shopping

Attempted By: **2882** / Accuracy: **40**

Prime Numbers Again

Attempted By: **521** / Accuracy: **54**

BEST SUBMISSIONS

LANGUAGE: **C**

 TIME (sec)

0.806668

 MEMORY (KiB)

64

by [RAJAT PRAKASH](#)

[VIEW BEST SUBMISSION](#)

[VIEW ALL SUBMISSION](#)

CONTRIBUTOR



AUTHOR

[ma5termind](#)



TESTER

[Prateek Gupta](#)

THIS PROBLEM WAS ASKED IN

 CHALLENGE NAME



SOCIAL SHARE



ABOUT US

[Blog](#)
[Engineering Blog](#)
[Updates & Releases](#)
[Team](#)
[Careers](#)
[In the Press](#)

HACKEREARTH

[API](#)
[Chrome Extension](#)
[CodeTable](#)
[HackerEarth Academy](#)
[Developer Profile](#)
[Resume](#)
[Get Badges](#)
[Campus Ambassadors](#)
[Get Me Hired](#)
[Privacy](#)
[Terms of Service](#)

DEVELOPERS

[AMA](#)
[Code Monk](#)
[Judge Environment](#)
[Solution Guide](#)
[Problem Setter Guide](#)
[Practice Problems](#)
[HackerEarth Challenges](#)
[College Challenges](#)
[College Ranking](#)
[Organise Hackathon](#)
[Hackathon Handbook](#)

EMPLOYERS

[Developer Sourcing](#)
[Lateral Hiring](#)
[Campus Hiring](#)
[Hackathons](#)
[FAQs](#)
[Customers](#)

REACH US

Ground Floor, Salarpuria Business Center,
4th B Cross Road, 5th A Block,
Koramangala Industrial Layout,
Bangalore, Karnataka 560095, India.

✉ contact@hackerearth.com

☎ +91-80-4155-4695

☎ +1-650-461-4192



Competitive
Programming
Open Source



© 2017 HackerEarth