
R13-260 □□-□□-□□□□-□□□□





21A 14V DC
10 A 28V DC

FUNCTION

A	OFF ON 2P SPST	I	ON (ON) 3P SPDT
B	ON ON 6P DPDT	K	(ON) OFF (ON) 6P DPDT
C	ON ON 3P SPDT	M	ON OFF (ON) 6P DPDT
D	ON OFF ON 3P SPDT	N	(ON) OFF 2P SPST
E	ON OFF ON 6P DPDT	P	ON (ON) 6P DPDT
F	ON OFF 4P DPST	Q	ON (OFF) 4P DPST
G	(ON) OFF (ON) 3P SPDT	R	ON (OFF) 2P SPST
H	ON OFF (ON) 3P SPDT	S	(ON) OFF 4P DPST

ROCKER

1		7	Laser mark Illuminated only for SPST/DPST
2		8	Waterproof Illuminated only for SPST/DPST
4	Illuminated only for SPST/DPST	9	LOCK With lock only for SPST/DPST
5	Illuminated only for SPST/DPST	9B	LOCK With lock only for SPST/DPST & Illuminated only for SPST/SPDT
6			

TERMINAL

01	.250" SQ
04	SAE SQ
05	SO
08	SC 6-32UNC

FRAME COLOR

ROCKER COLOR

LENS COLOR(TERMINAL 1-4)

LENS COLOR(TERMINAL 3-6)

COLOR

A	AMBER
B	BLACK
G	GREEN
U	BLUE
R	RED
W	WHITE
N	NONE








LEGEND

N	NONE
1	 SCI Logo

BULBS

N	NONE
1	1PC
2	2PCS

LIGHT CIRCUIT

1	
2	
3	
4	
5	
6	
7	
9	

ACTUATOR MARKING

Optional legend on actuator, see page A1.

Cut-out



	X	Y
0.75~2.5	36.6+0.1	21.2+0.1
2.5~3.5	36.8+0.1	21.2+0.1
3.5~4.5	37.0+0.1	21.2+0.1

FEATURES

▶ For wire connector, please refer to page 84 (R4-50)



