

R13-527 ■■■ - 0 2






20A 12V DC
10A 24V DC

Cut-out




0.7~3 mm max

Cut-out for X2 BUTTON



0.7~2.5 mm max

BUTTON





FUNCTION	TERMINAL
Non-illuminated button	0 2 .187" SQ

B — ON 4P DPST OFF

D — ON 2P SPST OFF

Illuminated / Different button

B L — ON 4P DPST OFF (LED)

B 5 L — ON 4P DPST OFF (LED dependent)

D 5 B — ON 3P SPST OFF (LED dependent)

D B — ON 3P SPST OFF (LED)

Momentary / Non-illuminated button

A — (ON) 4P DPST OFF

C — (ON) 2P SPST OFF

Momentary / Non-illuminated / Different button

A L — (ON) 4P DPST OFF (LED)

A 5 L — (ON) 4P DPST OFF (LED dependent)

C B — (ON) 3P SPST OFF (LED)

C 5 B — (ON) 3P SPST OFF (LED dependent)

Independent circuit

C L — (ON) 4P SPST OFF (LED independent)

C 5 L — (ON) 4P SPST OFF (LED independent)

D L — ON 4P SPST OFF (LED independent)

D 5 L — ON 4P SPST OFF (LED independent)

Waterproof

A 2 — (ON) 4P DPST OFF

A 2 L — (ON) 4P DPST OFF (LED)

B 2 — ON 4P DPST OFF

B 2 L — ON 4P DPST OFF (LED)

C 2 — (ON) 2P SPST OFF

C 2 B — (ON) 3P SPST OFF (LED)

C 2 L — (ON) 4P SPST OFF (LED independent)

D 2 — ON 2P SPST OFF

D 2 B — ON 3P SPST OFF (LED)

D 2 L — ON 4P SPST OFF (LED independent)

THE DRAWING IS FOR REFERENCE ONLY.