

Cassandra Aggregation Examples

1. COUNT

The COUNT function returns the number of rows in a query.

Example:

```
SELECT COUNT(*) FROM users WHERE age > 30;
```

Cassandra Aggregation Examples

2. SUM

The SUM function returns the sum of the values of a numeric column.

Example:

```
SELECT SUM(salary) FROM employees WHERE department = 'Sales';
```

Cassandra Aggregation Examples

3. AVG

The AVG function returns the average value of a numeric column.

Example:

```
SELECT AVG(salary) FROM employees WHERE department = 'Sales';
```

Cassandra Aggregation Examples

4. MAX

The MAX function returns the maximum value of a column.

Example:

```
SELECT MAX(age) FROM users;
```

Cassandra Aggregation Examples

5. MIN

The MIN function returns the minimum value of a column.

Example:

```
SELECT MIN(age) FROM users;
```

Cassandra Aggregation Examples

6. GROUP BY

The GROUP BY clause groups rows that have the same values into summary rows.

Example:

```
SELECT department, AVG(salary) FROM employees GROUP BY department;
```

Cassandra Aggregation Examples

7. ORDER BY

The ORDER BY clause is used to sort the result set in ascending or descending order.

Example:

```
SELECT * FROM users WHERE age > 30 ORDER BY age DESC;
```

Cassandra Aggregation Examples

8. ALLOW FILTERING

The ALLOW FILTERING clause allows more complex queries but should be used with caution as it can lead to performance issues.

Example:

```
SELECT * FROM users WHERE age > 30 ALLOW FILTERING;
```