1. INF265: Project 3: Transformers

1.1. Part 1: Encoder-only model for Movie Review Sentiment Classification

In this task we are asked to train an encoder only model, to classify movie reviews as positive or negative.

1.1.1. Pre-processing / tokenization

In order to use the data for this task, some pre-processing was required. Initially, we removed html tags, special characters, and made text lowercase. By lowering the amount of different characters, the model has to learn understanding between less tokens. If we were to keep the upper and lowercase of many words, we would essentially be doubling the different types of tokens the model could encounter. Preprocessing was done to make it easier for the model to learn.

After making the data less complex, we tokenized the text. Firstly, we add the `[CLS]` "start"-token. Then we run it through our tokenizer. Now we have turned our text into tokens. The model expects inputs to be of a certain size, so we truncate the ids to a set `max_length`, or adding padding to `max_length` if the text is too short.

1.1.2. Transformer model (encoding block)

The encoder block consists of two main layers.

Layer 1 includes normalization, followed by multi-head attention, and then dropout.

`Layer Norm` -> `Multi-Head attention` -> `Dropout`

The magic in this layer is what happens in the `Multi-head attention`. This part linearly projects queries, keys and values some arbitrary `n` times. Attention is performed on each of these projections, which are then added together, and projected a final time. If one were to use only one head for attention, it would be harder for the model to remember multiple parts of the input text simulatenously. The idea is that each of the heads can remember different representations of the input information.

The attention mechanism works by mapping a query and key-value pairs to some output. Each value is assigned a weight, computed by a function between the query and the key. For scaled dot-product attention, the dot product of the query with all the keys is taken, scaled and ran through a softmax function. The softmax function provides the weights for each value.

Between layer 1 and 2, a skip connection is used, adding the output from layer 1, and the initial input together, before feeding this new output into layer 2.

Layer 2 includes normalization, an MLP block, and dropout.

`Layer Norm` -> `MLP` -> `Dropout`

The MLP block linearly projects the data up 4 times its original dimensions, before applying the `GELU` activation function, adding non-linearity. `GELU` is chosen because it can handle both positive and slightly negative values. `GELU` may work well in this case, because a typical network with `RELU` can suffer <u>if many neurons in a network become zero</u>. The output is scaled back down again, before being output.

Finally, another skip connection is used, adding the output of layer 2(including its skip connection) to the final output.

1.1.3. Results



Figure 1: Loss over time

The loss for the training set reduces smoothly, slowing down slightly between epoch 2 to 3. The loss decreases linearly over epochs for the validation set, a sign of generalization.



Figure 2: Accuracy over time

The accuracy for the training set gradually increases, slowing down between epoch 2 to 3. The accuracy increases linearly over epochs for the validation set, a sign of generalization.

Data set	Accuracy
Train	0.875
Validation	0.845
Test	0.847

Table 1: Final performance on datasets

Based on the performance on the three datasets, the model generalizes quite well. The drop in accuracy on both the validation and test set is small, and proves our model manages to classify reviews it has not yet seen.



Figure 3: Confusion matrix on test data

Based on the above confusion matrix, the model seems to mostly manage to guess correctly wether a review is negative or positive, but it tends to prefer guessing positive, as it has twice as many False Positives (2000~) as False Negatives (1000~).

1.1.4. Interesting movie reviews

Title	Review	Sentiment	Score
The Matrix	The timeless classic. This film doesn't age, it will be contemporary even in 2030 or 2040. Wachowski's best one, by far.	Positive	0.93
Police Academy 4: Citizens on Patrol	There is not much good about the movie. The acting is bad. The writing is vomitous...	Negative	0.0096
Neil Breen, Fateful Findings	In all seriousness this movie is only enjoyable if you have a group of friends and a large amount of alcohol...	Positive	0.59
RuPaul's Drag Race	Groundbreaking TV and total eye-candy	Negative	0.019
Twilight 1	Catherine Hardwicke, please put the camera down...	Negative	0.47

Table 2: Model predictions on selected movie reviews

The model somewhat manages to correctly predict the movie reviews given in the above table. However, sometimes the model is quite sure about its answer, and sometimes it is very unsure about its answer.

The review of “The Matrix” is extremely positive, and the model gave it a score accordingly (0.93).I was unsure if certain words like names (wachowski) or years (2030, 2040) was going to make the model less sure about its prediction, since these words may not exist in the training set, but this was not the case.

The model nails “Police Academy 4”, understanding that the review claims it is a bad movie. The way the review is written is very “straightforward”, not using many metaphors, being direct in its criticism, making it an easy guess for the model.

The review for “Twilight 1” is very negative, but instead of being direct in its cristicsm it says things like “You have no talent” and “Please put the camera down”. This less direct review may make the model less sure about the prediction, causing it to predict 0.47. Correctly guessing this as a negative review, but just by a little bit.

One of the most interesting reviews is the review for “RuPaul’s Drag Race”. The model guesses this review as very negative, even though the review is very positive. Perhaps some of the words like “Groundbreaking” and “Eye candy” are a bit too abstract to understand as having positive meaning. Perhaps the training data has few examples of words like this, causing the model to shoot towards a negative prediction.

1.1.5. Custom model predictions

Title	Review	Sentiment	Score
Custom review a1	not good	Positive	0.99
Custom review a2	not not good	Positive	0.97
Custom review a3	not not not good	Positive	0.77

Table 3: Custom model predictions a

It was Interesting to see how the model would perform on negations of words, like “not good”. Interesting, the model considers “not good” to be positive! But when we add more “not”, the model eventually leans towards the review being negative. This is a great example of how transformers do not actually care about the “directon” of text, and really look at the text as a whole. Perhaps the model has learned “good” is positive, but “not” is negative, and that is why adding more “not”‘s makes the model lean more negativley.

Title	Review	Sentiment	Score
Custom review b1	not bad	Negative	0.0011
Custom review b2	not not bad	Negative	0.0013
Custom review b3	not not not bad	Negative	0.0015

Table 4: Custom model predictions b

Much like earlier, the model is fooled by negations. In this case "not bad" is scored very negativley, but adding more "not" to the review causes the model to be slightly less negative. Somewhat opposite of what we saw earlier. Perhaps the model has different associations when "not" is used with "good" and "bad".

The two examples above show that the model struggles heavily with negations.

1.2. Part 2: Decoder-only Model for Text Generation

In this task we are asked to train an decoder only model, to produce text when given some input text. This is a "many" to "many" machine learning situation.

1.2.1. Transformer model (decoder block)

The encoder block consists of two main layers.

Layer 1 includes normalization, followed by multi-head attention, and then dropout.

`Layer Norm` -> `Multi-Head attention` -> `Dropout`

The magic in this layer is what happens in the `Multi-head attention`. This part linearly projects queries, keys and values some arbitrary `n` times. Attention is performed on each of these projections, which are then added together, and projected a final time. If one were to use only one head for attention, it would be harder for the model to remember multiple parts of the input text simulatenously. The idea is that each of the heads can remember information from different represenations.

The attention mechanism works by mapping a query and key-value pairs to some output. Each value is assigned a weight, computed by a function between the query and the key. For scaled dot-product attention, the dot product of the query with all the keys is taken, scaled and ran through a softmax function. The softmax function provides the weights for each value.

Between layer 1 and 2, a skip connection is used, adding the output from layer 1, and the initial input together, before feeding this new output into layer 2.

Layer 2 includes normalization, an MLP block, and dropout.

`Layer Norm` -> `MLP` -> `Dropout`

The MLP block linearly projects the data up 4 times its original dimensions, before applying the `GELU` activation function, adding non-linearity. `GELU` is chosen because it can handle both positive and slightly negative values. `GELU` may work well in this case, because a typical network with `RELU` can suffer <u>if many neurons in a network become zero</u>. The output is scaled back down again, before being output.

Finally, another skip connection is used, adding the output of layer 2(including its skip connection) to the final output.

1.2.2. BPE Tokenizer

This project uses the byte-pair encoding tokenizer, to encode input text. Initially it buiilds an "alphabet" of all symbols in the total text input. Using this alphabet, we merge together pairs in the alphabet such that it matches those that were often present in the total text input. Now we add the merged pair back into the alphabet, and keep going. After a while, often used peices of text will have merged together, while rarer tokens will be smaller. We keep merging until we reach a preset vocabulary size, and those are our tokens.

1.2.3. Results



Figure 4: Training loss for decoder model

As the graph above shows, the model learns smoothly on training data. Perhaps given more time it would be benefical to train the model even longer, as it seems like training loss could go lower. However, we do not have a validation dataset to compare, so overfitting would be hard to detect.

A conversation with the bot is somewhat funny, yet interesting. It seems to generally understand the "feeling" or "vibe" of the conversation, but fails to come up with any actual reasonable, or even syntaxically correct answer. Below are some interesting conversations.

Seems like the model has difficulties with negations, much like the earlier model.

1.2.4. Interesting responses

Greedy	Top-p
	

Table 5: Model responses, Greedy VS Top-p

In the table above, answers from greedy and top-p models differ for the same question. For the question "who is the president of the usa", the greedy model seems to be stuck in a loop, repeating "is the oldest person to assume to presidency of the united states" over and over. This is perhaps a good example of how a greedy model picks only the most likeley word, but that sometimes fails to produce novel responses. On the other hand, the slightly more random top-p model, answers the question a little longer and provides more information (still very much gibberish), but it is a more "useful" answer.

In the table above, The answers to "how are you?" are similar for both greedy and top-p, the answers both trying to define what a "person" is.

Greedy	Top-p
	

Table 6: Model responses, Greedy VS Top-p

For this second experiment (seen in the above table), it was attempted to use the chatbot as a sort of "logic machine", to see its output.

Much like the earlier example, the greedy model gets stuck repeating the same words over and over again, a good example of how "short sighted" it is in its responses. However, it actually vaugely answers using boolean logic. It answers "False" for "True and False" (correct) and "False" for "True or False" (wrong).

The top-p model on the same task does not manage to answer using boolean logic, instead it talks about the terms used, or starts talking about objecrs and null types. This is a good example of how the random answer is more diverse, but sometimes misses the mark.

The Top-p model

Temperature = 2	Temperature = 0.1
	

Table 7: Model responses, Temperature experiments (Top-p = 0.95 for both)

In the above models, we compare two top-p models, temperature 2 and temperature 0.1.

The model with temperature = 2 produces competely random garbage that has nothing to do with the question. This is to be expected because a higher temperature makes more tokens more likely. It essentially "flattens" the token distribution, making those that are very likely, less likely, and those who were not so likely, more likely.

The model with temperature = 0.1 produces more coherent output, but suffers much the same as the greedy models, since it starts repeating itself. This again makes sense since a low temperature causes the most likely tokens to be even more likely, (peaking the token distribution). Therefore it acts much like the greedy model.

Top-p = 0.1	Top-p = 0.5	Top-p = 0.95
		

Table 8: Model responses, Top p experiments (Temperature = 0.7 for all 3)

In the above table, we see the model answering "how old are you" with differing levels of "top-p". Top-p is a parameter which decides the threshold for how many tokens should be included in our selection (based on their cumulative probability).

When top-p is small (0.1), less tokens are picked, and we see our top-p model acting much like our greedy model, repeating itself. As top-p increases (0.5), the model starts to be more varied in its answers, but still repeats itself somewhat. At top-p 0.95, the model gives a varied answer, without repeating itself, due to the token distribution it is drawing from is now diverse. It goes without saying, but none of the answers really make any sense, regardless of settings used.

1.3. Issues

I ran into an issue when first training the model, so I accidentally trained a parrot. By forgetting to add `.bool()` to the casual mask, the result was that the model was able to see the next token in the sequence! The model then managed to acheive a perfect performance on training data, as it learned to just repeat the last token in the sequence. I had trained a parrot basically.

```
> model.py
```

```python
def generate_causal_mask(self, seq_len):
    matrix = torch.ones(seq_len, seq_len)
    matrix = torch.triu(matrix, diagonal=1) # forgot .bool()!
    return matrix
```

It was easy to see that something was wrong because the model achieved an astonishing almost 0 loss on the training data.



Figure 5: Parrot model

Here is an example of a conversation with a parrot:

Cursed Chatbot
Who is the president of USA?
??
Who is the president of USA?
??
Who is the president of USA
usa usa usa