

Los pergaminos del engaño ninja

El primer fichero parece contener datos codificados en base64, pero los valores solo contienen mayúsculas y finalizan con tres "=", esto no puede suceder en base64. Los datos están codificados en base32.

```
1 MI4WKY3FGE4GG0JVGBQWMTGME3GEMDGMRRGMYJUMZTDOMZRMQZQU===
2 GI2TCDDGM4TAMJRM2WEZJXGA2DCOBSGQZDGZJTME3DSNLFHEYQU===
3 MUYTMNZRG44TOYZVGJSTCNLGG43DGMZYGBRDINLFHA2DCZLDGMZAU===
4 HAYDANRRHA4TIMZQGI2TGMJVMY4DMOLFGRSTCZRQHE2DOMJQGEZAU===
5 GJSGE0JVMU4GKMLBHEZDMN3CG5QTCMJYHA2TKNTCGIYDCM3CGMZQU===
6 GBRWGMJXGVRDSYZQMYWENTBHAZTCYZTHE4WKMRWHE3TOMRWGYQU===
7 MIZGMNLGMY2DONBTGY3DOMLCGZSTKMZTMQ4GIYZTGYYTIOBUGVSAU===
8 MRSDONJTG3TSNDCGYZWEZRZGBSWGY3GMQZTOZRZMIY TIN3EG5TAU===
9 GAZWGN3DGBQWGZJT HE2WIOBQGE4DEZDCGA3WCZJSMMZTAZRQGM2AU===
10 MMYWIOLGUYGMOBWHAZDKYJRMEZDGMBSMVRTENBUHFRTCNZRHE3AU===
11 HA3DKYZQMMYGENDBMIYGKMBWGNSTKY3BMEZTG0BXMMYWCOBXGQYQU===
12 HAZDON3FGA4TCMDEG42TAMJZGVRDINBYG44TONRRGZSTA0JRMFSAU===
13 HAZDON3FGA4TCMDEG42TAMJZGVRDINBYG44TONRRGZSTA0JRMFSAU===
14 MUYTMNZRG44TOYZVGJSTCNLGG43DGMZYGBRDINLFHA2DCZLDGMZAU===
15 G5RDQYRZGY2WCZBUMJRWCMDFGQYWCYRVGFSGKN3CGMYTGNRTMEYQU===
16 MRSDONJTG3TSNDCGYZWEZRZGBSWGY3GMQZTOZRZMIY TIN3EG5TAU===
17 G5RDQYRZGY2WCZBUMJRWCMDFGQYWCYRVGFSGKN3CGMYTGNRTMEYQU===
18 GAZWGN3DGBQWGZJT HE2WIOBQGE4DEZDCGA3WCZJSMMZTAZRQGM2AU===
19 HA3DKYZQMMYGENDBMIYGKMBWGNSTKY3BMEZTG0BXMMYWCOBXGQYQU===
20 HAZDON3FGA4TCMDEG42TAMJZGVRDINBYG44TONRRGZSTA0JRMFSAU===
```

Lo decodificamos:

```
import base64

with open("message1.txt", "r") as fin, open("b32decode.txt", "w") as fout:
    for line in fin:
        line = line.strip()
        if not line:
            continue
        line += "=" * (-len(line) % 8)
        decoded = base64.b32decode(line)
        fout.write(decoded.decode("utf-8", errors="ignore"))
```

```
(vfric@vfric) [~/.../CTF-cybermin]
$ cat b32decode.txt
b9ece18c950afbfa6b0fdbfa4ff731d3
2510c39011c5be704182423e3a695e91
e1671797c52e15f763380b45e841ec32
800618943025315f869e4e1f09471012
2db95e8e1a9267b7a1188556b2013b33
0cc175b9c0f1b6a831c399e269772661
b2f5ff47436671b6e533d8dc3614845d
dd7536794b63bf90eccfd37f9b147d7f
03c7c0ace395d80182db07ae2c30f034
c1d9f50f86825a1a2302ec2449c17196
865c0c0b4ab0e063e5caa3387c1a8741
8277e0910d750195b448797616e091ad
8277e0910d750195b448797616e091ad
e1671797c52e15f763380b45e841ec32
7b8b965ad4bca0e41ab51de7b31363a1
dd7536794b63bf90eccfd37f9b147d7f
7b8b965ad4bca0e41ab51de7b31363a1
03c7c0ace395d80182db07ae2c30f034
865c0c0b4ab0e063e5caa3387c1a8741
8277e0910d750195b448797616e091ad
e1671797c52e15f763380b45e841ec32
```

El archivo creado contiene un montón de valores ilegibles, pero haciendo uso de hash-identifier comprobamos que se trata de hashes MD5.

```
(vfric@vfric)-[~/.../CTF-cyberminds-1er-Edici-n/Crypto/Los Pergaminos del Er]
$ hash-identifier
#####
#                                     #
#      ^   ^   ^       ^   ^         ^   ^   ^   ^   ^   ^   ^   ^   ^   ^   #
#     / \ / \ / \    / \ / \        / \ / \ / \ / \ / \ / \ / \ / \ / \ / \  #
#    /   X   V   ,   /   ,           /   X   V   ,   /   ,           /   X   V   #
#   /_____\___\___\_/_____\___\___\_/_____\___\___\_/_____\___\___\_/_____#
#  /         \         \         \         \         \         \         \         \ v1.2 #
#                                                     By Zion3R #
#                                             www.Blackexploit.com #
#                                         Root@Blackexploit.com #
#####

HASH: b9ece18c950afbfa6b0fdbfa4ff731d3

Possible Hashs:
[+] MD5
[+] Domain Cached Credentials - MD4(MD4(($pass)).(strtolower($username)))
```

Mediante el uso de la herramienta John the Ripper obtenemos el valor de los hashes contenidos en el fichero.

```

└─$ john --format=raw-md5 b32decode.txt
Created directory: /home/vfric/.john
Using default input encoding: UTF-8
Loaded 306 password hashes with no different salts (Raw-MD5 [MD5 256/256 AVX2 8x3])
Warning: no OpenMP support for this hash type, consider --fork=16
Proceeding with single, rules:Single
Press 'q' or Ctrl-C to abort, almost any other key for status
Almost done: Processing the remaining buffered candidate passwords, if any.
Proceeding with wordlist:/usr/share/john/password.lst
1          (?)
1          (?)
1          (?)
1          (?)
1          (?)
1          (?)
1          (?)

```

```

└─$ cat /home/vfric/.john/john.pot
$dynamic_0$c4ca4238a0b923820dcc509a6f75849b:1
$dynamic_0$0cc175b9c0f1b6a831c399e269772661:a
$dynamic_0$e1671797c52e15f763380b45e841ec32:e
$dynamic_0$865c0c0b4ab0e063e5caa3387c1a8741:i
$dynamic_0$8277e0910d750195b448797616e091ad:d
$dynamic_0$03c7c0ace395d80182db07ae2c30f034:s
$dynamic_0$2db95e8e1a9267b7a1188556b2013b33:l
$dynamic_0$cfcfd208495d565ef66e7dff9f98764da:0
$dynamic_0$b2f5fff47436671b6e533d8dc3614845d:g
$dynamic_0$7b8b965ad4bca0e41ab51de7b31363a1:n
$dynamic_0$2510c39011c5be704182423e3a695e91:h
$dynamic_0$dd7536794b63bf90eccfd37f9b147d7f:I
$dynamic_0$b9ece18c950afbfa6b0fdbfa4ff731d3:T
$dynamic_0$c1d9f50f86825a1a2302ec2449c17196:H
$dynamic_0$800618943025315f869e4e1f09471012:F
$dynamic_0$853ae90f0351324bd73ea615e6487517::

```

Representamos las cadenas de hashes md5 a ascii(puedes usar crackstation)

```

import hashlib
import string

# Archivo con hashes MD5 (uno por línea)
FILE = "b32decode.txt"

# Conjunto de caracteres a probar (ajusta si es necesario)
charset = (
string.ascii_lowercase +
string.ascii_uppercase +
string.digits +
string.punctuation +
" "
)

```

```
def md5(s):
    return hashlib.md5(s.encode()).hexdigest()

decoded = ""

with open(FILE, "r") as f:
    for line in f:
        hash_line = line.strip()
        found = False

        for c in charset:
            if md5(c) == hash_line:
                decoded += c
                found = True
                break

        if not found:
            decoded += "?"

print("Frase decodificada:")
print(decoded)
```

```
$ python3 hashmd5.py
Frase decodificada:
TheFlagIsHiddenInsideThis:01010011001110110010001100001101001000010110011000101100110001010010010101111100010110001
1001101110001010000101100100010000111000101010011100011001010101001111110001000110000010101101101110010010101100100
001100100011000010011001011001010100001101100001101001010110001010110010101101110010
```

Hacemos un xor entre el codigo binario anterior y el message2.txt.

Recipe

From Binary

Delimiter

Space

Byte Length

8

XOR

Key

0000011101...

BINARY

Scheme

Standard

☐ Null preserving

Input

```
01010011001110110010001100001101001000010110011000101100110001010010010101111100010110001100110111000101000010110
01000100001110001010100111000110010101010011111100010001100000101011011011100100101011001000011001000110000100110
01011001010100001101100001101001011000101011001010110010
```

Output

TheFlagIs:BeThePersonWhoLovesCrypto