



# Mac OS X Roxen installation guide

Thank you for installing Roxen for Mac OS X. This guide will explain how to do further configurations and where files related to Roxen are installed.

## Further configuration

By default, a newly installed Roxen sever will listen to the following URL:s:

**http://localhost/** – the default site.

**http://localhost/edit/** – Go to the Content Editor of the default site. Access this URL with the administrator username and password and go to the “Access Control” tab to add new users.

**http://localhost:22202/** – the administration interface. Access this URL with the administrator username and password to load Roxen modules, upload license files and make further configuration changes to the server.

## Roxen files and directories

The following directories and files are created when Roxen is installed. To uninstall, remove any of these files and directories as necessary.

**/etc/roxen/default/** – the configuration directory for the default Roxen server configuration. Several server instances can be installed in parallel, in which case each will have a unique configuration directory (e.g. **/etc/roxen/mysite/**).

**/var/roxen/default/** – The data directory for the default Roxen server. It contains the database, site repository, local modules, cache subdirectories etc.

**/var/log/roxen/default/** – The log directory for the default Roxen server, including both the access log in Common Log Format as well as the debug log.

**/var/pid/roxen/default/** – The pid (process id) directory for the default Roxen server.

**/etc/hostconfig** – Contains the line “ROXEN=YES-” used for the Startup Items.

**/Library/StartupItems/Roxen/** – The script to automatically start Roxen servers on machine boot.

**/Applications/Roxen/** – Various helper applications for Roxen.

**/usr/local/lib/roxen-x.y.z-abc/** – The binary directory for the Roxen server.

## Upload license files

To upload a license file, go to the administration interface. Select the tabs **Tasks > Maintenance > Upload license**. To apply a license for a site, select the site and then select the tab **Settings**. The setting is called **License file**.