

Skstronghold's Blog

Algorithms, Implementations, Programming and Linux

- [Home](#)
- [Algorithms](#)

- [Data Structures](#)
- [Linux](#)

- [Mathematics](#)
-



[Home](#) > [Greedy](#) > Huffman coding and decoding

Huffman coding and decoding

January 10, 2012 [skstronghold](#) [Leave a comment](#) [Go to comments](#)

Huffman codes are a widely used and very effective technique for compressing data; savings of 20% to 90% are typical, depending on the characteristics of the data being compressed. We consider the data to be a sequence of characters. Huffman's greedy algorithm uses a table of the frequencies of occurrence of the characters to build up an optimal way of representing each character as a binary string.

We assume that C is a set of n characters and that each character $c \in C$ is an object with a defined frequency $f[c]$. The algorithm builds the tree T corresponding to the optimal code in a bottom-up manner. It begins with a set of $|C|$ leaves and performs a sequence of $|C| - 1$ "merging" operations to create the final tree. A min-priority queue Q , keyed on f , is used to identify the two least-frequent objects to merge together. The result of the merger of two objects is a new object whose frequency is the sum of the frequencies of the two objects that were merged.

My C++ implementation of Huffman coding(according to CLRS) is:

```
1 #include <iostream>
2 #include <queue>
3 #include <string>
4 #include <algorithm>
5
```

Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.

To find out more, including how to control cookies, see here: [Cookie Policy](#).

Close and accept

```

12     node* right;
13
14     node( char c = ' ', int f = -1 )
15     {
16         ch = c;
17         freq = f;
18         left = NULL;
19         right = NULL;
20     }
21
22     node( node* c1, node* c2 )
23     {
24         ch = ' ';
25         freq = c1 -> freq + c2 -> freq;
26         left = c1;
27         right = c2;
28     }
29
30     bool operator()( const node& l, const node &r)
31     {
32         return l.freq > r.freq;
33     }
34
35     void traverse( string code = "" ) const;
36
37 };
38
39 void node::traverse( string code ) const
40 {
41     if( left ) {
42         left->traverse( code + '0' );
43         right->traverse( code + '1' );
44     } else {
45         cout << ch << "\t" << freq << "\t" << code << endl;
46     }
47 }
48
49 int main() {
50     string str;
51     int cnt;
52     char c;
53     priority_queue< node, vector<node>, node > q;
54
55     cin >> str;
56
57     for( int i = 65; i <= 90 ; i++ ) {
58         c = (char)i;
59         cnt = (int)count( str.begin(), str.end(), c );
60         if( cnt ) {
61             q.push( node( c, cnt ) );
62             cnt = 0;
63         }
64     }
65
66     for( int i = 97; i <= 122 : i++ ) {

```

Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.

To find out more, including how to control cookies, see here: [Cookie Policy](#).

Close and accept

```

73     }
74
75     while( q.size() != 1 ) {
76         node *left = new node( q.top() );
77         q.pop();
78         node *right = new node( q.top() );
79         q.pop();
80         q.push( node( left, right ) );
81     }
82
83     cout << "Encoding " << endl;
84     cout << "Word" << "\t" << "freq" << "\t" << "code" << endl;
85     q.top().traverse();
86 }

```

We can decode a coded string using simple string matching, below is a similar implementation:

```

1  #include<iostream>
2  #include<map>
3
4  using namespace std;
5
6  int main()
7  {
8      int i,j,k,a,b,n;
9      char c;
10     string s,t,ans;
11     map <string, char> mymap;
12     map <string, char> :: iterator it;
13
14     cout << "Enter the no. different types of characters: ";
15     cin >> n;
16
17     for( i = 0; i < n; i++ ) {
18         cout << "Enter the " << i+1 << " character and its c";
19         cin >> c >> s;
20         mymap[s] = c;
21     }
22
23     cout << "Enter the encoded string: ";
24     cin >> s;
25
26     t = "";
27     ans = "";
28     for( i = 0; i < s.size(); i++ ) {
29         t += s[i];
30         it = mymap.find(t);
31         if( it != mymap.end() ) {
32             c = mymap[it];
33             ans += c;
34             t = "";
35         }
36     }

```

Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.

To find out more, including how to control cookies, see here: [Cookie Policy](#).

Close and accept

```

42     return 0;

```

43 | }

Sample input for the above implementation of Huffman decoding can be:

```
1 | 10
2 | A 00
3 | E 010
4 | F 011
5 | B 100
6 | C 101
7 | D 110
8 | G 1110
9 | H 11110
10 | I 111110
11 | J 111111
12 | 00100100001000100001111001000110
```

Advertisements



REPORT THIS AD



REPORT THIS AD

Share this:

Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.
To find out more, including how to control cookies, see here: [Cookie Policy](#).

Close and accept

B

Related[Greedy algorithms](#)

In "Algorithms"

[Kruskal's minimum spanning](#)[tree](#)

In "Graph Theory"

[Prim's minimum spanning tree](#)

In "Graph Theory"

Categories: [Greedy](#) Tags: [c++](#), [coding](#), [decoding](#), [greedy](#), [huffman](#)
[Comments \(0\)](#) [Trackbacks \(0\)](#) [Leave a comment](#) [Trackback](#)

1. No comments yet.

1. No trackbacks yet.

Leave a Reply

Enter your comment here...

[Closest pair of points](#) [Depth first search](#)
[RSS feed](#)

Sunil Kumar



Undergraduate Student
Indian Institute of Information
Technology
Allahabad, India

Recent Posts

- [Introduction to lex](#)
- [Downloading with wget](#)
- [Prim's minimum spanning tree](#)
- [Bucket sort](#)
- [Treaps](#)
- [Dijkstra's single source shortest path algorithm](#)

Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.

To find out more, including how to control cookies, see here: [Cookie Policy](#).

Close and accept

Archives

- [January 2012](#) (28)
- [April 2011](#) (1)

Blog Hits

- 14,424

Subscribe

Enter your email address to subscribe to this blog and receive notifications of new posts by email.

Join 8 other followers

Categories

- [Algorithms](#) (18)
 - [Computational Geometry](#) (1)
 - [Dynamic Programming](#) (1)
 - [Graph Theory](#) (5)
 - [Greedy](#) (1)
 - [Sorting](#) (6)
 - [String Matching](#) (1)
- [Data Structures](#) (5)
- [Linux](#) (5)
 - [Lex and Yacc](#) (1)
 - [Sudo](#) (1)
 - [Vim](#) (2)
 - [Wget](#) (1)
- [Mathematics](#) (1)

[Twitter Updates](#)

Error: Twitter did not respond. Please wait a few minutes and refresh this page.

Advertisements



Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.

To find out more, including how to control cookies, see here: [Cookie Policy](#).

[Top](#)
[Blog at WordPress.com.](#)



Privacy & Cookies: This site uses cookies. By continuing to use this website, you agree to their use.
To find out more, including how to control cookies, see here: [Cookie Policy](#).

Close and accept