3/12/2026

Website Audit Report

Target URL: **https://lexes.co.in**

59	82	84	100
PERFORMANCE	SEO	ACCESSIBILITY	BEST PRACTICES

Web Vitals & Metrics

First Contentful Paint	Speed Index	Largest Contentful Paint
1.3 s	**2.8 s**	**1.4 s**

Time to Interactive	Total Blocking Time	Cumulative Layout Shift
2.3 s	**810 ms**	**0**

Performance Opportunities

Reduce unused CSS **Est savings of 18 KiB**

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn how to reduce unused CSS.

Reduce unused JavaScript **Est savings of 248 KiB**

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. Learn how to reduce unused JavaScript.

Diagnostic Findings

Document does not have a meta description

Meta descriptions may be included in search results to concisely summarize page content. Learn more about the meta description.

Network dependency tree

Avoid chaining critical requests by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load.

Largest Contentful Paint

Largest Contentful Paint marks the time at which the largest text or image is painted. Learn more about the Largest Contentful Paint metric

LCP breakdown

Each subpart has specific improvement strategies. Ideally, most of the LCP time should be spent on loading the resources, not within delays.

Use efficient cache lifetimes

A long cache lifetime can speed up repeat visits to your page. Learn more about caching.

Total Blocking Time

Sum of all time periods between FCP and Time to Interactive, when task length exceeded 50ms, expressed in milliseconds. Learn more about the Total Blocking Time metric.

Reduce JavaScript execution time

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to reduce Javascript execution time.

Document does not have a main landmark.

One main landmark helps screen reader users navigate a web page. Learn more about landmarks.

LCP request discovery

Optimize LCP by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading

Max Potential First Input Delay

The maximum potential First Input Delay that your users could experience is the duration of the longest task. Learn more about the Maximum Potential First Input Delay metric.

Passed Audits

Metrics
Collects all available metrics.

Allows users to paste into input fields
Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers.Learn more about user-friendly input fields.

Avoids requesting the geolocation permission on page load
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission.

`[user-scalable="no"]` is not used in the `` element and the `[maximum-scale]` attribute is not less than 5.
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more about the viewport meta tag.

Server Backend Latencies
Server latencies can impact web performance. If the server latency of an origin is high, it's an indication the server is overloaded or has poor backend performance. Learn more about server response time.

Document request latency
Your first network request is the most important. Reduce its latency by avoiding redirects, ensuring a fast server response, and enabling text compression.

Script Treemap Data
Used for treemap app

Optimize viewport for mobile
Tap interactions may be delayed by up to 300 ms if the viewport is not optimized for mobile.

Mitigate DOM-based XSS with Trusted Types
The `require-trusted-types-for` directive in the `Content-Security-Policy` (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. Learn more about mitigating DOM-based XSS with Trusted Types.

`[aria-hidden="true"]` is not present on the document ``
Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document ``. Learn how `aria-hidden` affects the document body.

Form elements have associated labels

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more about form element labels.

Minify JavaScript

Minifying JavaScript files can reduce payload sizes and script parse time. Learn how to minify JavaScript.

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn how to use a CSP to prevent XSS

Network Requests

Lists the network requests that were made during page load.

Minimizes main-thread work

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to minimize main-thread work

Use a strong HSTS policy

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. Learn more about using a strong HSTS policy.

Touch targets have sufficient size and spacing.

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets.

Initial server response time was short

Keep the server response time for the main document short because all other requests depend on it. Learn more about the Time to First Byte metric.

Minify CSS

Minifying CSS files can reduce network payload sizes. Learn how to minify CSS.

`` element has a valid value for its `[lang]` attribute

Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the `lang` attribute.

Avoids requesting the notification permission on page load

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications.

Links are distinguishable without relying on color.

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. Learn how to make links distinguishable.

Layout shift culprits

Layout shifts occur when elements move absent any user interaction. Investigate the causes of layout shifts, such as elements being added, removed, or their fonts changing as the page loads.

Page has successful HTTP status code

Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more about HTTP status codes.

No issues in the `Issues` panel in Chrome Devtools

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more about heading order.

Avoid long main-thread tasks

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn how to avoid long main-thread tasks

Tasks

Lists the toplevel main thread tasks that executed during page load.

Document has a `