

Edmonds' algorithm

From Wikipedia, the free encyclopedia

In graph theory, **Edmonds' algorithm** or **Chu–Liu/Edmonds' algorithm** is an algorithm for finding a spanning arborescence of minimum weight (sometimes called an *optimum branching*). It is the directed analog of the minimum spanning tree problem. The algorithm was proposed independently first by Yoeng-Jin Chu and Tseng-Hong Liu (1965) and then by Jack Edmonds (1967).

Contents

- 1 Algorithm
 - 1.1 Description
- 2 Running time
- 3 References
- 4 External links

Algorithm

Description

The algorithm takes as input a directed graph $D = \langle V, E \rangle$ where V is the set of nodes and E is the set of directed edges, a distinguished vertex $r \in V$ called the *root*, and a real-valued weight $w(e)$ for each edge $e \in E$. It returns a spanning arborescence A rooted at r of minimum weight, where the weight of an arborescence is defined to be the sum of its edge weights, $w(A) = \sum_{e \in A} w(e)$.

The algorithm has a recursive description. Let $f(D, r, w)$ denote the function which returns a spanning arborescence rooted at r of minimum weight. We first remove any edge from E whose destination is r . We may also replace any set of parallel edges (edges between the same pair of vertices in the same direction) by a single edge with weight equal to the minimum of the weights of these parallel edges.

Now, for each node v other than the root, find the edge incoming to v of lowest weight (with ties broken arbitrarily). Denote the source of this edge by $\pi(v)$. If the set of edges $P = \{(\pi(v), v) \mid v \in V \setminus \{r\}\}$ does not contain any cycles, then $f(D, r, w) = P$.

Otherwise, P contains at least one cycle. Arbitrarily choose one of these cycles and call it C . We now define a new weighted directed graph $D' = \langle V', E' \rangle$ in which the cycle C is "contracted" into one node as follows:

The nodes of V' are the nodes of V not in C plus a *new* node denoted v_C .

- If (u, v) is an edge in E with $u \notin C$ and $v \in C$ (an edge coming into the cycle), then include in E' a new edge $e = (u, v_C)$, and define $w'(e) = w(u, v) - w(\pi(v), v)$.
- If (u, v) is an edge in E with $u \in C$ and $v \notin C$ (an edge going away from the cycle), then include in E' a new edge $e = (v_C, v)$, and define $w'(e) = w(u, v)$.
- If (u, v) is an edge in E with $u \notin C$ and $v \notin C$ (an edge unrelated to the cycle), then include in E' a new edge $e = (u, v)$, and define $w'(e) = w(u, v)$.

For each edge in E' , we remember which edge in E it corresponds to.

Now find a minimum spanning arborescence A' of D' using a call to $f(D', r, w')$. Since A' is a spanning arborescence, each vertex has exactly one incoming edge. Let (u, v_C) be the unique incoming edge to v_C in A' . This edge corresponds to an edge $(u, v) \in E$ with $v \in C$. Remove the edge $(\pi(v), v)$ from C , breaking the cycle. Mark each remaining edge in C . For each edge in A' , mark its corresponding edge in E . Now we define $f(D, r, w)$ to be the set of marked edges, which form a minimum spanning arborescence.

Observe that $f(D, r, w)$ is defined in terms of $f(D', r, w')$, with D' having strictly fewer vertices than D . Finding $f(D, r, w)$ for a single-vertex graph is trivial (it is just D itself), so the recursive algorithm is guaranteed to terminate.

Running time

The running time of this algorithm is $O(EV)$. A faster implementation of the algorithm due to Robert Tarjan runs in time $O(E \log V)$ for sparse graphs and $O(V^2)$ for dense graphs. This is as fast as Prim's algorithm for an undirected minimum spanning tree. In 1986, Gabow, Galil, Spencer, and Tarjan produced a faster implementation, with running time $O(E + V \log V)$.

References

- Chu, Y. J.; Liu, T. H. (1965), "On the Shortest Arborescence of a Directed Graph", *Science Sinica*, **14**: 1396–1400
- Edmonds, J. (1967), "Optimum Branchings", *J. Res. Nat. Bur. Standards*, **71B**: 233–240, doi:10.6028/jres.071b.032
- Tarjan, R. E. (1977), "Finding Optimum Branchings", *Networks*, **7**: 25–35, doi:10.1002/net.3230070103
- Camerini, P.M.; Fratta, L.; Maffioli, F. (1979), "A note on finding optimum branchings", *Networks*, **9**: 309–312, doi:10.1002/net.3230090403
- Gibbons, Alan (1985), *Algorithmic Graph Theory*, Cambridge University press, ISBN 0-521-28881-9
- Gabow, H. N.; Galil, Z.; Spencer, T.; Tarjan, R. E. (1986), "Efficient algorithms for finding minimum spanning trees in undirected and directed graphs", *Combinatorica*, **6**: 109–122, doi:10.1007/bf02579168

External links

- Edmonds's algorithm (edmonds-alg) (<http://edmonds-alg.sourceforge.net/>) – An open source implementation of Edmonds's algorithm written in C++ and licensed under the MIT License. This source is using Tarjan's implementation for the dense graph.

Retrieved from "https://en.wikipedia.org/w/index.php?title=Edmonds%27_algorithm&oldid=749169657"

Categories: Graph algorithms

-
- This page was last modified on 12 November 2016, at 21:16.
 - Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.