

Codex Contexts

Set up once on each computer

A project's **.envrc** selects one **CODEX_HOME**. That home keeps its login, provider settings, and sessions. Several projects can share one identity.

1 Get ready

Follow [Installation](#) to install prerequisites and clone the repository. Then, in the clone:

```
cd "$HOME/Developer/codex-contexts"
./tests/test.sh
export PATH="$PWD/bin:$PATH"
```

Adjust the clone path as needed. The export sets PATH for this shell; see [Installation](#) to make it persistent, or use **./bin/codex-home** from the clone.

Admin rights: none for the helper. Initial Homebrew installation or Linux **apt** may need an administrator. Run the helper without sudo.

2 Add ChatGPT accounts

```
codex-home create-subscription personal
codex-home login personal
codex-home create-subscription work
codex-home login work
codex-home run work login status
```

Check the account and workspace in each browser login. **login status** checks the CLI auth method; identity names are local labels.

Or use the U-M GPT Toolkit

```
codex-home model-settings
codex-home create-umgpt
codex-home set-key umgpt
```

For broader text models, use **create-umgpt-low** and **set-key umgpt-low**: **LOW-SENSITIVITY ONLY**. Follow [U-M setup](#) for discovery and the tool-call test. After setup, [change defaults and picker order](#).

Keep it local. Credentials belong in the identity home, outside Git and cloud sync. Generated project files contain local paths; review them before **direnv allow**. Repeat setup on every computer.

3 Select an identity for a project

Use your project path and an existing identity, such as **work**.

```
P="/path/to/project"
codex-home project work "$P"
```

Read the generated **.envrc** and workspace, then approve and open VS Code:

```
direnv allow "$P"
codex-home vscode work "$P"
```

Title: **[CODEX: WORK]**. Start a new chat. Check the extension's profile menu for sign-in and its model picker. [Verification](#).

Or add a custom API provider

```
codex-home create-api lab-api \
  https://api.example.org/v1 \
  MODEL_ID LAB_API_KEY
codex-home set-key lab-api
```

Use your provider's URL and MODEL_ID. It must support bearer keys, streaming Responses, and Codex tool calls.

[API providers](#): tool-call test, Azure, and billing. A model list alone does not prove compatibility.

Terminal only

```
cd "/path/to/project"
codex-home run work
```

CLI **/status** shows model/session configuration. **[CODEX: WORK]** stays in the title. No direnv or VS Code needed.

Codex Contexts

Everyday commands and quick fixes

codex-home run uses the active context selected by direnv. Add **NAME** for an explicit choice. Set **P="/path/to/project"** below. Commands assume **codex-home** is on PATH.

Open and check

```
cd "$P"
codex-home run
codex-home vscode-project
codex-home current
codex-home show NAME
codex-home list
```

Local config: **current/show**. CLI model/session: **/status**.
IDE: profile menu + model picker. [Verification](#).

Change or remove a project context

Close the project's VS Code window first:

```
codex-home project-change NAME "$P"
codex-home project-review "$P"
```

Read and close the review window, then approve and open:

```
direnv allow "$P"
codex-home vscode-project "$P"
```

```
codex-home project-reset "$P"
```

Reset removes untouched generated files and local Git exclusions. It keeps identity homes and credentials.

Optional: share personal skills

```
codex-home share-skills-all
```

Requires existing **~/codex/skills**; links skills and skips conflicts. Rerun after additions. Codex also discovers skills outside each home. [Guide](#).

Provider checks and API keys

```
codex-home doctor NAME
codex-home models NAME
codex-home set-key NAME
```

doctor may use the network; **models** needs a /models route. **set-key** hides your input. Revoke replaced keys with the provider.

Wrong ChatGPT login? Reauthenticate only that identity:

```
codex-home run NAME logout
codex-home login NAME
```

Quick fixes

Wrong account: relaunch with **codex-home vscode** and start a new chat.

Change refused: files may be edited, tracked, or incomplete. Follow [manual recovery](#).

HTTP 401/403: check the key, URL, access, and network. Never print the key.

/responses fails: confirm streaming Responses and tool-call support. Chat Completions alone is insufficient.

Finder on macOS

Install from the clone directory:

```
./bin/install-macos-open-with
```

Right-click a folder: **Quick Actions > Open in Codex Project** (or **Services**). Dock hover label: **VS Code - NAME**. After quitting, use Finder or the helper again; do not pin the editor copy. [Uninstall instructions](#).

Before using research data: confirm approval for your provider, model, and workflow. Separate identities are not a security sandbox. [Full commands](#) | [Troubleshooting](#) | [Security](#)