

Codex Contexts

Set up once on each computer

A project's **.envrc** selects one **CODEX_HOME**. That home keeps its login, provider settings, and sessions. Several projects can share one identity.

1 Get ready

Follow [Installation](#) to install prerequisites and clone the repository. Then, in the clone:

```
cd "$HOME/Developer/codex-contexts"
./tests/test.sh
export PATH="$PWD/bin:$PATH"
```

For future zsh shells, put this line in **~/.zshrc**:
export PATH=~/.Developer/codex-contexts/bin:\$PATH
 Open a new terminal. Adjust the path if your clone is elsewhere, or use **./bin/codex-home** from the clone.

Admin rights: none for the helper. Initial Homebrew installation or Linux **apt** may need an administrator. Run the helper without **sudo**.

2 Add ChatGPT accounts

```
codex-home create-subscription personal
codex-home login personal

codex-home create-subscription work
codex-home login work
```

Check the account and workspace in each browser login. **personal** and **work** are labels, not verified plan names.

Or use the U-M GPT Toolkit

```
codex-home create-umgpt MODEL_ID
codex-home set-key umgpt
```

Get an exact model ID and API key from the [U-M GPT guide](#). Toolkit API calls incur usage charges. Test tool calls before using research data.

3 Select an identity for a project

Replace the path below with your project. Use an identity you have already created, such as **work**.

```
P="/path/to/project"
codex-home project work "$P"
```

Read the generated **.envrc**, then approve it and open VS Code:

```
direnv allow "$P"
codex-home vscode work "$P"
```

Check **[CODEX: WORK]** in the window title. Start a new chat and use **/status** to confirm the account and provider.

Or add a custom API provider

```
codex-home create-api lab-api \
  https://api.example.org/v1 \
  MODEL_ID LAB_API_KEY
codex-home set-key lab-api
```

Replace the example URL and **MODEL_ID**. The provider must support bearer keys, the Responses API, streaming, and Codex tool calls.

Follow [API providers](#) for a tool-call test, Azure setup, and billing details. A model list alone is not a compatibility test.

Terminal only

```
cd "/path/to/project"
codex-home run work
```

The tab/window title shows **[CODEX: WORK]**. Check the account with **/status**. No **direnv** or VS Code needed.

Keep it local. Credentials belong in the identity home, outside Git and cloud sync. Generated project files contain local paths; review them before **direnv allow**. Repeat setup on every computer.

Codex Contexts

Everyday commands and quick fixes

codex-home run uses the active context selected by direnv. Add **NAME** for an explicit choice. Set **P="/path/to/project"** below. Commands assume **codex-home** is on PATH.

Open and check

```
cd "$P"
codex-home run
codex-home vscode-project
```

```
codex-home current
codex-home show NAME
codex-home list
```

Confirm the account with **/status** in Codex.

Change or remove a project context

Close the old VS Code window first. To select another identity:

```
codex-home project-change NAME "$P"
codex-home project-review "$P"
direnv allow "$P"
codex-home vscode-project "$P"
```

Read and close the review window before approval. Start a new Codex chat.

```
codex-home project-reset "$P"
```

Reset removes untouched generated files and local Git exclusions. It keeps identity homes and credentials.

Share personal skills

```
codex-home share-skills-all
codex-home share-skills NAME
```

Links **~/codex/skills** and skips conflicts. Rerun after adding skills; review shared updates.

Provider checks and API keys

```
codex-home doctor NAME
codex-home models NAME
codex-home set-key NAME
```

doctor may use the network; **models** needs a **/models** route. **set-key** hides your input. Revoke replaced keys with the provider.

Wrong ChatGPT login? Reauthenticate only that identity:

```
codex-home run NAME logout
codex-home login NAME
```

Quick fixes

Wrong account: relaunch with **codex-home vscode** and start a new chat.

Change refused: files may be edited, tracked, or incomplete. Follow [manual recovery](#).

HTTP 401/403: check the key, URL, access, and network. Never print the key.

/responses fails: confirm streaming Responses and tool-call support. Chat Completions alone is insufficient.

Finder on macOS

From the clone directory:

```
./bin/install-macos-open-with
./bin/uninstall-macos-open-with
```

Install or remove the app in **~/Applications**; no admin rights needed. In Finder, Control-click a folder, then **Open With > Codex Project**.

Before using research data: confirm approval for your provider, model, and workflow. Separate identities are not a security sandbox. [Full commands](#) | [Troubleshooting](#) | [Security](#)