The Charlotte Operating System

An async-first, capability-based microkernel
for critical, high-performance software

2026-11-11

Scope and status

This manual describes both the implemented CharlotteOS prototype and its intended architecture. Unless a section explicitly says otherwise, statements about security, performance, transport independence, hardware support, or failure recovery are design goals rather than production guarantees. The implementation-status appendix records the repository's currently verified scope; source code and tests remain authoritative when the manual and implementation differ. Repository paths in this manual are clickable links to the corresponding file or directory on the public `main` branch; begin with the `docs/README.md` documentation index.

Reading the implementation notes.

Boxes labelled **Optional detail** expand on allocation, publication and cleanup mechanics. They can be skipped on a first reading. The surrounding text gives the main sequence, ownership rules and caller-visible failure behaviour; the boxes retain the detail needed for implementation review.

Contents

I Why CharlotteOS **20**

1 The Problem. 21

1.1 A mismatch at the operating-system boundary 21

1.2 Sources of the retrofit tax 21

1.2.1 Async over blocking 21

1.2.2 Ambient authority 21

1.2.3 Hardware asynchrony disguised as software synchrony 21

1.2.4 Fault propagation across trust boundaries 22

1.3 Why Rust ownership is not enough 22

1.4 What we are trying to build 22

2 Design Philosophy. 24

2.1 Our starting point 24

2.1.1 CharlotteOS: the protection, scheduling, and interrupt substrate 24

2.1.2 Sitas: the shard-per-core execution discipline 24

2.1.3 Xous: the isolated userspace service model 25

2.2 How they fit together 25

2.3 The three kernel primitives 26

2.3.1 Capabilities: “May I?” 26

2.3.2 Endpoints: “With whom?” 28

2.3.3 Memory Objects: “Where is the data, and who owns it?” 28

2.4 An explicit design rule 28

2.5 What “asynchronous throughout” means 28

2.5.1 Blocking is still useful 29

2.5.2 Immediate operations remain immediate 29

2.5.3 No asynchronous userspace upcalls 29

2.6 Safety consequences and open bounds 30

3 Vocabulary 31
3.1 Protection domain 31
3.2 Execution context 31
3.3 Logical processor (LP) 31
3.4 Sitas shard 32
3.5 Capability 32
3.6 Endpoint 32
3.7 Connection capability 32
3.8 Message 32
3.9 Reply token 33
3.10 Resource capability 33
3.11 Operation and completion queue 33
3.12 Notification 33
3.13 Rust Waker 33
3.14 Distinctions that matter 34
3.15 Quick reference: acronyms 34

II The Kernel Architecture **35**

4 Capabilities: Authority Without Ambiguity 36
4.1 What a capability is 36
4.2 Object types and their rights 38
4.3 Delegation and attenuation 38
4.4 Generation-safe lookup 38
4.5 Bootstrap: how capabilities enter a domain 39
4.6 Authority and audit consequences 39

5 Endpoints: Communication as a First-Class Primitive 40
5.1 Server and connection model 40
5.1.1 Namespace publication 40
5.1.2 Endpoint storage admission 40

5.1.3 Connection, call and reply record admission. 41
5.1.4 Receive and reply waiter admission 44
5.2 Message classes. 44
5.2.1 Scalar messages 44
5.2.2 Memory-based messages 45
5.3 Message envelope. 45
5.4 Call and reply. 46
5.4.1 Synchronous-looking futures. 46
5.4.2 Deferred replies 46
5.4.3 Reply token semantics 46
5.5 Connection delegation. 47
5.6 Service identity and discovery 47
5.6.1 A client with explicit recovery scopes 49
5.7 Two kernel data paths 53
5.8 Authority, concurrency, and restart. 53
6 Memory Objects: Ownership That Crosses Boundaries 54
6.1 The problem with copying. 54
6.2 First-class memory objects 54
6.3 Aggregate admission and sponsorship. 54
6.3.1 Reserve backing and principal capacity. 55
6.3.2 Keep sponsorship through ownership changes 55
6.3.3 Prepare metadata before publication. 55
6.3.4 Account for retained metadata and catalogs 56
6.3.5 Keep snapshots and pins through maintenance. 58
6.3.6 Refund only after confirmed release. 59
6.3.7 Understand the remaining policy boundaries 59
6.3.8 Stack capacity admission.. 59
6.3.9 Translation-table lifetime. 60

6.4 Four transfer modes . . . 64
6.4.1 Copy . . . 64
6.4.2 Move . . . 64
6.4.3 BorrowRead . . . 65
6.4.4 BorrowWrite . . . 65
6.5 Why hardware enforcement matters . . . 66
6.6 Control plane versus data plane . . . 66
6.7 DMA as a third ownership dimension . . . 66
6.8 Transfer guarantees and limits . . . 67
7 Completion Queues and Non-Lossy Results . . . 68
7.1 When to use a completion queue . . . 68
7.2 The CQ ring: a shared-memory completion buffer . . . 68
7.3 The non-lossy invariant . . . 69
7.4 Per-shard CQ partitioning . . . 69
7.5 Operation lifecycle . . . 69
7.6 Checked waiting on a CQ . . . 70
7.7 LP affinity for CQ waits . . . 70
7.8 Operation IDs versus per-operation capabilities . . . 71
7.9 Completion-record admission . . . 71
7.9.1 Reserve capacity . . . 71
7.9.2 Prepare the complete operation . . . 72
7.9.3 Publish into the captured namespace . . . 73
7.9.4 Retain charges through delivery and teardown . . . 74
7.9.5 Manage the timer lifetime separately . . . 74
7.10 Completion-queue admission . . . 76
7.10.1 Prepare and publish a queue . . . 76
7.10.2 Replace an existing queue . . . 76
7.11 Owning endpoint-close and thread-exit registrations . . . 77
7.11.1 Watch an endpoint close . . . 78
7.11.2 Watch an external thread exit . . . 78

7.11.3 Retain a completion worker until exit . . . 78
7.11.4 Kernel completion callbacks . . . 79
7.12 Owned completion and CQ waiters . . . 79
7.12.1 Admit before parking . . . 79
7.12.2 Keep the registration with the waiter . . . 79
7.12.3 Distinguish waiting failure from operation completion . . . 80
7.12.4 Close the lost-wake window . . . 80
7.12.5 Apply the same rule to other scheduler sources . . . 81
7.13 Cancellation and buffer ownership . . . 81
7.14 Reliability and latency consequences . . . 82

III The Execution Discipline **83**

8 Shards and Logical Processors . . . 84
8.1 The logical processor (LP): the hardware unit of scheduling . . . 84
8.2 The shard: the userspace unit of ownership . . . 84
8.3 The usual mapping: one shard per LP . . . 85
8.4 `PerLp<T>`: interrupt-safe shared data . . . 86
8.5 `ShardLocal<T>`: lock-free single-owner data . . . 86
8.6 Ownership and placement consequences . . . 87

9 The Sitas Executor . . . 88
9.1 One executor per shard . . . 88
9.2 The polling loop . . . 88
9.3 The unified wait: three event sources, one wait point . . . 89
9.3.1 Kernel completions (CQ entries) . . . 89
9.3.2 Endpoint readiness (coalesced wake) . . . 89
9.3.3 Device interrupts (coalesced wake) . . . 89
9.4 Task wakeup: from CQ entry to future poll . . . 90
9.5 Cross-shard messaging without the kernel . . . 90
9.6 The ShardParker: blocking on native state . . . 90

9.7 Concurrency and execution consequences 91
9.8 A worked example: the mailbox index build 92
9.8.1 The workload 92
9.8.2 Kernel and userspace responsibilities 92
9.8.3 The mailbox path 93
9.8.4 Coordination and joining 93
9.8.5 Verification 93
9.8.6 What the demo establishes 94
10 Scheduling and Backpressure 95
10.1 The kernel scheduler 95
10.2 The block-yield-wake cycle 95
10.2.1 Block 95
10.2.2 Wake 96
10.2.3 Resume 96
10.3 Wake coalescing 96
10.4 The quantum timer 96
10.5 The deferred reaper 97
10.6 Load rebalancing 97
10.6.1 Protected-domain resource feedback 97
10.6.2 Generation-safe retirement 98
10.7 Synchronization and lock ordering 101
10.7.1 Lock families 101
10.7.2 Interrupt-masking discipline 102
10.7.3 Lock ordering 102
10.8 Backpressure and queue bounds 102
10.9 Scheduling guarantees and remaining bounds 103
10.10 Scheduler observability 104

IV Building Systems **105**

11 Service Architecture 106

11.1 Protection domains as failure boundaries 106

11.2 The supervisor: domain lifecycle manager 106

11.3 The name service: discovery without the kernel 107

11.4 Service restart and recovery 107

11.5 The overall system topology 108

11.6 Failure containment and recovery 110

12 Userspace Drivers 111

12.1 The problem with kernel drivers 111

12.2 The DriverGrant 111

12.3 MMIO delegation 111

12.4 Interrupt delivery 112

12.5 The reference UART driver 112

12.6 DMA and the IOMMU 113

12.7 Driver service layering 114

12.8 Isolation and device access 114

13 Networking 115

13.1 Sockets as a compatibility interface 115

13.2 The native protocol stack 116

13.2.1 Ethernet: generic frame transport 116

13.2.2 Reliable message layer 116

13.2.3 RPC layer 117

13.2.4 Distributed objects 120

13.3 TCP/IP as a compatibility service 120

13.4 Cluster-wide TCP ingress and direct server return 123

13.5 UTC time as an internal service 126

13.6 Capability-scoped external data services 126

13.6.1 S3 client service 127

13.6.2 Kafka client service . . . 128
13.7 Transport independence . . . 131
13.8 Zero-copy networking . . . 132
13.9 Network authority and transport . . . 132
14 Consensus and Replication . . . 133
14.1 Raft as a capability service . . . 133
14.2 Intended properties relative to socket-based Raft . . . 134
14.2.1 Peer access through capabilities . . . 134
14.2.2 Transport transparency . . . 134
14.2.3 Zero-copy log replication . . . 134
14.2.4 Capability-based security . . . 134
14.2.5 Failure isolation . . . 135
14.3 Persistence and launch configuration . . . 135
14.4 Cluster bootstrap: the seed problem . . . 135
14.4.1 Ethernet discovery and deterministic admission (current) . . . 136
14.4.2 Pre-shared cluster capability (small kernel change) . . . 136
14.4.3 Ethernet broadcast discovery (zero-configuration) . . . 136
14.4.4 Distributed name service (implemented) . . . 136
14.5 The generic StateMachine trait . . . 136
14.6 Relationship to the name service . . . 138
14.7 Election timers as first-class completions . . . 138
14.8 Replication consequences . . . 138
15 Persistent Storage . . . 140
15.1 The storage stack . . . 140
15.2 NVMe block driver . . . 140
15.2.1 Initialization . . . 140
15.2.2 I/O path . . . 141
15.2.3 Lessons from bringup . . . 141

15.3 Block device protocol . . . 141
15.4 Object store . . . 142
15.4.1 On-disk layout . . . 142
15.4.2 Current durability boundary . . . 142
15.4.3 Operations . . . 143
15.4.4 Object authority . . . 143
15.4.5 The initial service-artifact store . . . 144
15.5 Managed object storage through S3 . . . 144
15.6 Raft persistence . . . 145
15.7 Native filesystem . . . 145
15.7.1 Directory encoding . . . 145
15.7.2 Path resolution . . . 146
15.7.3 Host inspection . . . 146
15.8 Isolation and durability limits . . . 146

16 Live Service Upgrade . . . 148
16.1 The four primitives . . . 148
16.2 The handoff protocol . . . 148
16.3 Executable source . . . 148
16.4 Shared Kernel Preparation . . . 150
16.5 What the service must implement . . . 150
16.6 What clients see . . . 151
16.7 Restart-with-state vs. zero-downtime . . . 151
16.8 Relationship to crash recovery . . . 151
16.9 Upgrade guarantees and limits . . . 152

V Research Directions **153**

17 Server-Class Cluster Vision . . . 154
17.1 The cluster is the computer . . . 154
17.1.1 Nodes as resources . . . 154

17.1.2 Workloads are signed execution objects . . . 155
17.1.3 Assignment is declarative and cluster-wide . . . 155
17.2 Kubernetes and OpenShift as a counterpoint . . . 156
17.2.1 What the container stack constructs . . . 156
17.2.2 Two sources of complexity . . . 156
17.2.3 The control plane may survive the execution stack . . . 157
17.3 Target architecture . . . 158
17.3.1 The minimal node . . . 158
17.3.2 The cluster executive . . . 158
17.3.3 Placement, routing, and migration as native operations . . . 158
17.4 Implemented foundation . . . 159
17.5 Current bootstrap and node model . . . 162
17.5.1 Discovery and membership . . . 162
17.6 Software ingress and deployment . . . 162
17.6.1 The target pipeline . . . 162
17.6.2 The implemented pipeline . . . 164
17.7 Placement: contract, observation, and movement . . . 164
17.7.1 Executable variants and architecture eligibility . . . 164
17.7.2 Declared policy and bounded scheduler . . . 166
17.7.3 Runtime observation: local substrate only . . . 167
17.7.4 A keyhole into the cluster . . . 167
17.7.5 Focused stateless-handoff validation . . . 168
17.7.6 Future stateful cross-node migration . . . 168
17.8 Deployment, rollout, and reassignment . . . 168
17.8.1 Replicated deployment manifest . . . 170
17.8.2 Cross-node hosting and generation fencing . . . 170
17.8.3 The deployment agent . . . 170
17.8.4 `clusterctl` and the test console . . . 171
17.8.5 Serve deployment requests without replay . . . 172
17.8.6 Apply independently signed descriptors . . . 173

17.8.7 Admit an atomic release . . . 174
17.8.8 Observe readiness and reconcile placement . . . 175
17.8.9 Retire an application under its signed grace . . . 176
17.8.10 Coordinate a whole-node shutdown . . . 176
17.8.11 Artifact naming . . . 179
17.8.12 Cryptographic boundary . . . 180
17.8.13 Validated properties . . . 183
17.9 Remaining implementation boundary . . . 183
17.10 Related work . . . 184
17.10.1 Historical distributed operating systems . . . 184
17.10.2 Cluster control planes and placement . . . 185
17.10.3 Capabilities and constrained execution . . . 185
17.10.4 Trust, signing, and bootstrap . . . 185
17.10.5 Membership and artifact stores . . . 185
17.11 Research test . . . 186
18 Application Generation Vision . . . 187
18.1 The application thesis . . . 189
18.2 Durga's present application model . . . 189
18.3 Three distinct languages . . . 190
18.3.1 The business and process language . . . 190
18.3.2 The Durga semantic execution model . . . 190
18.3.3 The execution substrate . . . 191
18.4 The Charlotte backend and its target architecture . . . 191
18.4.1 Generated activity boundary . . . 192
18.4.2 A deliberately narrow runtime interface . . . 192
18.5 From process graph to capability graph . . . 193
18.5.1 Security graph and communication graph . . . 193
18.6 The signed process bundle . . . 194
18.6.1 Generated desired state . . . 195

18.7 Process topology as placement information. 196
18.8 Logical activities and physical executables 197
18.9 Native messages and durable event logs 197
18.10 Preserving application intent 199
18.11 Comparison with Kubernetes and OpenShift 200
18.12 Developer experience and the compatibility boundary 201
18.13 Current implementation and next experiment. 202
18.13.1 Experiment input 202
18.13.2 Generated output 202
18.13.3 Execution and verification 203
18.13.4 Questions the experiment should answer. 203
18.14 Remaining work. 203
18.15 Next experiment. 204

VI Working with CharlotteOS **205**

19 Programming Model. 206
19.1 Invariants. 206
19.1.1 Only the owning LP mutates its state 206
19.1.2 Messages are owned values 206
19.1.3 References to shard-local state must not escape 206
19.1.4 Work stays on its assigned LP 206
19.1.5 Observability returns owned snapshots 206
19.2 Kernel-side primitives. 207
19.2.1 `PerLp<T>` 207
19.2.2 `ShardLocal<T>` 207
19.2.3 `ShardMailboxSet<M>` 207
19.2.4 IPI closures. 208
19.2.5 Completion API. 209
19.2.6 CQ ring 209

19.3 Userspace programming model . . . 209
19.3.1 The launch contract . . . 209
19.3.2 Resource ownership in Rust . . . 210
19.3.3 Bootstrap authority . . . 210
19.3.4 Caller identity is kernel authority . . . 211
19.3.5 Backpressure is normal . . . 211
19.3.6 Sitas integration . . . 211
19.4 Rule-of-thumb guidance . . . 212
19.5 The syscall ABI . . . 212
19.6 Enforcement and audit . . . 213

20 Configuration . . . 214
20.1 Configuration sources and authority . . . 214
20.2 Selecting the compile-time resource policy . . . 215
20.2.1 Select a reviewed profile . . . 215
20.2.2 Interpret the metadata pools . . . 215
20.2.3 Rebuild service capacities with their consumers . . . 216
20.2.4 Tune entropy deadlines and buffers together . . . 216
20.2.5 Keep publication and device-polling budgets distinct . . . 217
20.3 Related limits and tuning consequences . . . 217
20.4 Management TLS configuration . . . 218
20.5 Planning and validating a policy change . . . 220
20.6 Extending configuration toward boot resources . . . 220

21 Development Workflow . . . 221
21.1 Prerequisites . . . 221
21.2 Build targets . . . 221
21.2.1 Kernel build . . . 221
21.2.2 Userspace service programs . . . 222
21.3 Booting in QEMU . . . 222
21.3.1 AArch64 . . . 222
21.3.2 x86-64 . . . 223

21.4 Booting in VMware . . . 224
21.5 Expected boot output . . . 224
21.6 Dependency advisories . . . 224
21.7 Self-tests . . . 225
21.8 The async-syscall demo . . . 225
21.9 CI pipeline . . . 227
21.10 Codebase reading guide . . . 227
21.11 Troubleshooting . . . 228

22 Formal Safeguards with TLA+ . . . 229
22.1 Why model functionality as a state machine? . . . 229
22.2 The safeguarding loop . . . 230
22.3 What is modeled . . . 231
22.3.1 Use the inventory to find a functional boundary . . . 231
22.3.2 Resource sponsorship and retirement projections . . . 234
22.3.3 Deployment request lifecycle projections . . . 235
22.4 Model-driven findings . . . 236
22.4.1 Authorization is controlled capability issuance . . . 237
22.4.2 Boot verification and installation are separate . . . 237
22.4.3 Local publication owns its death watch . . . 238
22.4.4 IPC attachments are cross-registry transactions . . . 238
22.4.5 DMA availability and completion . . . 239
22.4.6 Two-phase service publication . . . 239
22.4.7 Reliable-message session identity . . . 239
22.4.8 Restart-safe Raft admission . . . 240
22.4.9 Membership changes preserve the tested Graft contract . . . 240
22.4.10 A delayed acknowledgement belongs to its original term . . . 241
22.4.11 Each read carries a fresh quorum fence . . . 241
22.4.12 Elapsed time comes from the kernel counter . . . 242
22.4.13 Snapshot chunks belong to one leader and term . . . 242
22.4.14 Rejected application snapshots leave known ground intact . . . 242

22.4.15 Cluster placement and DSR ingress . . . 242
22.4.16 Retained regression patterns . . . 243
22.5 Concrete conformance and atomicity . . . 248
22.6 Validation . . . 249
22.6.1 Running TLC . . . 249
22.6.2 Implementation validation . . . 250
22.7 What a successful check means . . . 250
22.8 Workflow for changes . . . 251
A Glossary . . . 252
B Implementation Status . . . 254
B.1 Boot validation and test selection . . . 254
B.2 Implementation phases . . . 254
B.3 Success criteria . . . 256
B.4 Verified scope . . . 256
B.5 Known limitations . . . 257
C Lessons Learned . . . 263
C.1 Bugs found on hardware . . . 263
C.1.1 Panic handler recursed through heap-dependent logging . . . 263
C.1.2 Blocked threads lost their execution context . . . 263
C.1.3 RwLock held-across-call deadlocks . . . 263
C.1.4 Quantum timer grew without bound . . . 263
C.1.5 A thread cannot free its own kernel stack . . . 263
C.1.6 LA57 paging-mode mismatch . . . 264
C.1.7 ASID-0 collision . . . 264
C.1.8 x86-64 trampoline halted on thread return . . . 264
C.1.9 Hypervisors that strip TTBR0 ASIDs break TLB isolation . . . 264
C.2 Engineering lessons . . . 264

D Research Lineages and Their Afterlives 265
D.1 Capability kernels and confined Unix 265
D.1.1 CharlotteOS inheritance 265
D.2 IPC, typed channels, and ownership 266
D.2.1 CharlotteOS inheritance 266
D.3 Multicore systems, runtimes, and fast I/O 266
D.3.1 CharlotteOS inheritance 267
D.4 Service recovery 267
D.5 From distributed operating systems to cluster managers 267
D.5.1 Clean-break and compatibility counterpoints 268
D.6 Cluster-native placement, ingress, and lifecycle 268
D.6.1 Desired state and replica placement 268
D.6.2 Cluster service identity and Direct Server Return 269
D.6.3 Remote calls and explicit failure 269
D.7 Operational trust and managed-service authority 269
D.7.1 Software supply chain and role separation 269
D.7.2 Connector-confined managed services 270
D.8 AI-assisted adaptation and the POSIX question 270
D.8.1 CharlotteOS inheritance 270
D.9 The synthesis and the rejected inheritances 271
E Architectural Redirections 272
E.1 Retained mechanisms 272
E.2 What to reframe 272
E.3 Replacements adopted 273
E.3.1 Stop expanding raw mailbox syscalls 273
E.3.2 Do not allocate one completion capability per service request 273
E.3.3 Separate readiness, notification, and completion 273
E.3.4 Replace arbitrary cross-LP closures 273
E.3.5 Do not equate shard wake with IPI delivery 273
E.3.6 Introduce memory objects before rich IPC payloads 273

E.3.7 Treat service discovery as userspace policy 273

Part I

Why CharlotteOS

1 The Problem

1.1 A mismatch at the operating-system boundary

CharlotteOS is an attempt to address a particular mismatch. Asyncronous runtimes, least-privilege services, and isolated components are often built above interfaces organized around blocking calls, ambient namespaces, and machine-wide policy. This manual calls the resulting adapters, duplicated concurrency models, and policy layers the **retrofit tax**.

1.2 Sources of the retrofit tax

1.2.1 Async over blocking

Many operating systems expose synchronous calls: `read()` may block the calling thread until data arrives. Applications use `epoll`, `kqueue`, or `io_uring` for concurrency without dedicating one thread per operation. These interfaces are effective, but applications may still need adapters when a kernel or library operation blocks. Runtimes then translate blocking work into readiness or completion notifications.

That translation can introduce:

- Async-signal-safety problems: the kernel may deliver a completion while userspace holds a lock, requiring elaborate signal-handler discipline or a dedicated thread pool.
- Thread-pool overhead: many async runtimes spawn a pool of OS threads to convert blocking syscalls into futures, undoing the resource benefits of asynchronous execution.
- Two concurrency models: the application uses async/await; the kernel uses threads and blocking. The mismatch forces every boundary crossing to bridge the two models.

1.2.2 Ambient authority

A process on a conventional OS commonly begins with access to broad filesystem and network namespaces. Security policy then removes authority with mechanisms such as `chroot`, `seccomp`, and namespaces. This approach requires the developer to enumerate what the process must not reach. Programs that omit a restriction retain more authority than they need, which increases the effect of a compromise.

1.2.3 Hardware asynchrony disguised as software synchrony

Hardware is inherently asynchronous with respect to the CPU. A disk controller signals completion via an interrupt. A network card delivers packets on its own schedule and a timer fires after a programmed interval. Yet the operating system interface presents these as synchronous calls: `read()` returns when the data is ready, blocking the calling thread in the meantime.

A thread blocked on I/O cannot do other work. High-concurrency servers compensate with thread pools; real-time systems may use carefully tuned polling loops.

1.2.4 Fault propagation across trust boundaries

A bug in a device driver can crash a monolithic kernel. In a system without hardware-enforced isolation, a memory corruption in one application can corrupt another. Address-space isolation contains faults between drivers and applications, but it also puts IPC on performance-critical paths. A design that cannot keep that path cheap may be tempted to move services (back) into the kernel.

A common compromise is to isolate untrusted code in virtual machines while keeping trusted code in the kernel, but kernel defects can still cross that boundary.

1.3 Why Rust ownership is not enough

Safe Rust prevents many data races, use-after-free errors, and null-pointer dereferences. Still, unsafe code, hardware interfaces, and logic errors remain. Safe Rust is a substantial improvement for systems programming, but Rust programs run on operating systems that do not share Rust's ownership discipline.

- A Rust program cannot protect itself from a C driver that corrupts kernel memory. Isolation must be enforced by the hardware (MMU, IOMMU) rather than by the language.
- A Rust `Mutex<Vec<T>>` crossing a syscall boundary is still a shared-memory lock with all the contention, priority inversion, and deadlock risks that implies. The kernel does not know the lock exists.
- Rust's `async`/`await` compiles to a state machine driven by a userspace executor, but the executor must still interact with the kernel's blocking I/O model. The `Future` trait and the kernel's wait queue speak different languages.

Rust prevents some bug classes within an address space. The OS still defines the rules between address spaces. If authority is ambient until restricted, then the language's guarantees remain local.

1.4 What we are trying to build

We want to see how an operating system can support these programs more directly. The design starts with a few requirements:

1. Asynchronous by construction: operations that may wait for external progress should let the caller submit work and observe its completion later. The thread should be able to do other work while it waits.
2. Capability-based, instead of ambient, authority: a process should be able to perform an operation only if it holds a capability authorizing it. Capabilities are unforgeable and must be explicitly granted.
3. Isolation by default: every protection domain should run in its own address space. Communication across boundaries are kernel-mediated, so a fault in one domain should not propagate to another.
4. Ownership that crosses boundaries: data movement between domains should support ownership transfer. The kernel should be able to move page mappings, so the sender loses access and the receiver gains it.
5. Bounded resource consumption: every queue, table, and buffer should be bounded. Backpressure should propagate explicitly. No unbounded allocation should be a correctness requirement.

6. The OS and the language runtime should agree: the kernel's model of concurrency (asynchronous, completion-driven) should match the language's model of concurrency (futures, wakers). No translation layer should be needed.

2 Design Philosophy

In CharlotteOS, we bring together ideas from three projects.

2.1 Our starting point

> **Hardware is asynchronous, so the operating system and the userspace runtime should be too.**

The three projects approach this design space from different directions. We want to keep the distinctions that make each useful and give them clear ways to work together.

2.1.1 CharlotteOS: the protection, scheduling, and interrupt substrate

CharlotteOS contributes the mechanisms that *must* be privileged:

- Address-space isolation through page tables and the MMU.
- Kernel scheduling of threads across logical processors (LPs).
- LP-local state and interrupt routing.
- Page-table manipulation and physical-memory management.
- MMIO and DMA authority delegation.
- Per-domain capability tables.
- Event observation and thread wakeup.
- Syscall dispatch and asynchronous completion delivery.

Its design rule is: **the kernel provides the minimum set of primitives from which everything else can be composed.** If a facility can be built in userspace without compromising isolation, it belongs in userspace.

2.1.2 Sitas: the shard-per-core execution discipline

Sitas (`https://github.com/FrodeRanders/sitas`) contributes an execution discipline, i.e. a set of rules about how state is owned and mutated:

> Only the owning shard mutates shard-local state. Cross-shard interaction occurs through bounded typed messages carrying owned values.

Sitas provides:

- One executor per shard: cooperative task scheduling within a shard; preemption between shards.
- Futures as userspace state machines: every operation that may wait is a `Future`, driven by the shard's executor.
- Bounded backpressure: every queue has fixed capacity; senders must handle `WouldBlock`.

- Shard-local ownership: mutable state belongs to exactly one shard; no locks, no atomics for shard-internal data.
- Explicit placement: the caller chooses where a task runs.
- Typed command/reply APIs: what a shard receives is a specific Rust type.
- Structured shutdown and cancellation: tasks can be cancelled, and cancellation has defined ownership semantics.
- Observability through owned snapshots: diagnostics capture state by value, never by borrowed reference into runtime internals.

The Sitas discipline is enforced by Rust's type system within a single protection domain and CharlotteOS extends it across domains through the kernel.

2.1.3 Xous: the isolated userspace service model

Xous (https://xous.dev), a microkernel OS for Precursor and Betrusted hardware, contributes the protection-domain service model:

- Services are userspace servers: drivers, filesystems, and protocol stacks run in their own protection domains rather than in the kernel.
- Clients connect to servers and receive connection identifiers: a connection *is* authority; possessing one means you may communicate with that server.
- IPC is a kernel primitive: the kernel mediates and validates communication between protection domains.
- Scalar messages are distinct from memory-based messages: small control-plane operations (opcodes, handles, status codes) travel in fixed-size messages; bulk data travels as memory-object attachments.
- Memory IPC distinguishes ownership transfer from borrowing: move transfers ownership permanently. Borrow grants temporary access, revoked on reply or cancellation.
- A userspace name service maps human-readable names to opaque server identities.

CharlotteOS adopts Xous's userspace-server model and combines it with the Sitas execution discipline and an async-native kernel. The detailed co-design is maintained in docs/architecture/sitas-xous.md.

2.2 How they fit together

The three systems do not collapse into one and compose at well-defined boundaries:

Layer	Provided by
Shard-local async execution	Sitas
Cross-domain protection and IPC	CharlotteOS kernel (Xous-inspired)
Completion delivery for kernel/device ops	CharlotteOS kernel
Service discovery and policy	Userspace (name service, supervisor)

The layers are:

Client process

- typed protocol library
- endpoint connection capabilities
- futures backed by IPC replies or completion records
- owned buffers whose transfer mode is explicit

Userspace service process


- one or more externally visible IPC endpoints
- protocol-specific request/reply handling
- one Sitas executor per assigned shard
- shard-local state
- typed in-process commands
- driver or service implementation

CharlotteOS kernel

- protection domains
- threads and LP scheduling
- capabilities and endpoint connections
- interrupt routing
- memory objects and page mappings
- operation submission and completion queues

2.3 The three kernel primitives

Three orthogonal kernel abstractions form the foundation:



Every other kernel facility, including completion queues, reply tokens, device grants, and DMA mappings, is a **composition** of these three primitives.

2.3.1 Capabilities: “May I?”

A capability answers one question: **“May I perform this operation?”** It grants permission to act and operations describe the work. Examples include endpoint capabilities, connection capabilities, memory-object capabilities, interrupt capabilities, DMA-domain capabilities, and timer capabilities.



Figure 2.1: CharlotteOS layering from hardware and kernel mechanism through isolated services and generated application logic to managed external systems.

2.3.2 Endpoints: “With whom?”

An endpoint answers: **“Who am I communicating with?”** It provides bounded rendezvous between protection domains. Endpoints know nothing about packet buffers, futures, DMA, or ownership. They just carry requests and replies.

2.3.3 Memory Objects: “Where is the data, and who owns it?”

A memory object answers: **“Where is the data, and who currently owns it?”** It represents page-backed storage whose ownership can move independently of communication. Its responsibilities include page ownership, mappings, transfer modes, DMA state, and lifetime.

2.4 An explicit design rule

> **When adding a new subsystem, first ask whether it can be expressed using capabilities, endpoints, and memory objects. New kernel primitives should be introduced only when they cannot be naturally composed from the existing ones.**

This rule limits the kernel interface and keeps the ABI and trust model reviewable.

2.5 What “asynchronous throughout” means

“Asynchronous throughout” means:


1. Operations that may wait for external progress have submission/completion semantics.
2. No subsystem boundary forces the caller to dedicate a thread to waiting for one operation.
3. A userspace shard can wait on one aggregated kernel source (the CQ).
4. Completions are retained until observed.
5. Buffers and capabilities have explicit ownership during an operation.
6. Cancellation and teardown have defined state transitions.
7. Bounded queues preserve backpressure across layers.
8. Service implementations can suspend one task while continuing other work on the shard.

This leaves some things outside the model:

- Every syscall is asynchronous.
- Every call returns a newly allocated completion capability.
- No thread ever blocks.
- Every wake sends an IPI.
- All waitable objects have identical semantics.
- Userspace code is interrupted by arbitrary asynchronous callbacks.

2.5.1 Blocking is still useful

When no Sitas task is runnable, the shard's execution context should block in one kernel wait operation:




The shard parks directly on native completion and message state; no helper-thread pool is required merely to convert blocking kernel interfaces into futures.

2.5.2 Immediate operations remain immediate

Operations that cannot meaningfully block, such as capability duplication, metadata queries, nonblocking CQ drain, and closing a quiescent object, they complete synchronously. The ABI does not force asynchronous ceremony onto inherently synchronous work.

2.5.3 No asynchronous userspace upcalls

Completions do not inject callbacks into userspace at arbitrary instructions. The path is:



The kernel may preempt threads, but it does not inject arbitrary task callbacks into userspace. Task scheduling therefore remains cooperative and reviewable.

2.6 Safety consequences and open bounds

Every design decision in CharlotteOS traces back to one or more of the six principles from Chapter 1:

- Capabilities replace ambient authority: a compromised service cannot access resources it was never granted. The set of things a process can do is enumerable and auditable by construction.
- Endpoints make communication authenticated: a client that holds a connection capability has proven (at grant time) that it is authorized to communicate and the kernel enforces this on every message.
- Memory objects constrain stale cross-domain access: ownership moves through the kernel and is enforced by page tables, which of course puts a dependency on MMU, TLB, and DMA handling.
- Composition limits the privileged code footprint: most system functionality lives in userspace, where faults can be contained to a service domain.
- The async model reduces adaptation: the kernel and runtime share submission, completion, and wake semantics.
- Bounded ingress makes pressure visible: endpoint and hardware queues apply explicit backpressure. Chapter 10 records the implemented family limits and remaining aggregate-accounting gaps.

3 Vocabulary

This chapter defines specific terms used in this manual.

3.1 Protection domain

A **protection domain** is an address space and authority boundary. It owns:

- A capability table.
- Memory mappings.
- One or more execution contexts (threads).
- Resource accounting.
- Failure and teardown state.

A *process* is the concrete implementation of a protection domain, but architectural discussion prefers the semantic term.

3.2 Execution context


An **execution context** is a kernel-scheduled thread. It may have:

- Logical processor (LP) affinity.
- Priority or scheduling class.
- A current protection domain.
- A wait state.
- An associated userspace executor.

3.3 Logical processor (LP)

A **logical processor** is CharlotteOS' representation of a schedulable hardware execution context, typically one CPU core or one hyperthread.

An LP is not a shard (in the Sitas sense). A typical mapping is:



The architecture makes this distinction so that CPU hotplug, oversubscription, migration, asymmetric CPUs, and multiple sharded processes remain possible.

3.4 Sitas shard

A **shard** is a userspace ownership and execution domain:

- One executor runs its tasks.
- At most one task at a time mutates shard-owned state.
- Cross-shard access occurs through typed messages carrying owned values.
- Placement is explicit and remains separate from the shard's identity.

3.5 Capability

A **capability** is an unforgeable reference to a kernel object, carrying rights. It answers the question: "May I perform this operation?"

Capabilities are scoped to a protection domain's capability table. A process cannot fabricate a capability; the kernel issues one through an authorized creation, bootstrap, or delegation operation.

3.6 Endpoint

An **endpoint** is a bounded server-side IPC receive object. It has:

- An owning protection domain.
- A queue capacity.
- A protocol/interface identity.
- Receive rights.
- Lifecycle and closure state.

3.7 Connection capability

A **connection capability** is a client-side authority to send or call an endpoint. A name service resolves a name and conditionally returns a connection capability associated with that name.

3.8 Message

A **message** is a kernel-validated IPC envelope consisting of:

- Interface or protocol identifier.
- Opcode.
- Flags.
- Inline scalar words.
- Zero or more memory-object attachments.
- Zero or more delegated capability attachments.

- Optional reply authority.

The kernel understands the envelope structure while arbitrary Rust types remain a userspace concern.

3.9 Reply token

A **reply token** is one-shot authority to complete a blocking or deferred call. It is:

- Created by the kernel.
- Bound to the caller's pending call.
- Consumable exactly once.
- Invalidated by cancellation, caller death, or endpoint teardown.
- Owned by the receiving service; the current userspace API does not provide general reply-token delegation.

3.10 Resource capability

A **resource capability** authorizes operations on a kernel-managed object such as a memory object, endpoint, connection, interrupt, MMIO region, DMA domain, or a completion for an operation or timer. The unified namespace also holds mailbox and system-observer authority. Completion queue (CQ) identifiers select domain-local queues and are not a separate capability family.

3.11 Operation and completion queue

An **operation** is submitted work whose progress may depend on the kernel, hardware, or a privileged service.

A **completion queue (CQ)** is the aggregated, per-shard or per-process destination for operation results. It is waitable (with `checked CQ wait`) and has non-lossy terminal completion semantics.

3.12 Notification

A **notification** means: "State may have changed; inspect the corresponding object or queue." It may be coalesced, but is itself not a result.

3.13 Rust Waker

A Rust `Waker` means: "Poll this userspace future again." It is a userspace scheduling hint, is not a kernel completion record, and it should not cross the ABI directly.

3.14 Distinctions that matter

Several concepts sound similar but must be kept separate. Confusing them leads to architectural mistakes.

Concept	Is	Is not
Capability	Unforgeable authority to act	An event, a file descriptor, a handle
Endpoint	Server-side bounded receive queue	A socket, a pipe, a channel
Completion	A result of an async operation	A Waker, a notification
Waker	A hint to repoll a future	A kernel completion record
Shard	A userspace ownership domain	An LP, a core, a thread
LP	A schedulable hardware context	A shard
Notification	"Inspect state"	A result, a data payload
IPC call	Cross-domain service invocation	A kernel operation submission

3.15 Quick reference: acronyms

ASID Address Space Identifier. 0 = kernel; >0 = user address space.

CQ Completion Queue. Shared-memory ring buffer for async operation results.

EL0 Exception Level 0 on AArch64. CharlotteOS also retains `EL0` as an architecture-neutral source and test label for userspace execution, including ring 3 on x86-64.

EL1 Exception Level 1 (AArch64). Kernel execution.

HHDM Higher Half Direct Mapping. Linear mapping of all physical memory into kernel virtual address space (provided by the Limine bootloader).

IPI Inter-Processor Interrupt. Signal from one LP to another.

LP Logical Processor. One schedulable hardware execution context.

MMU Memory Management Unit. Hardware that enforces page-table permissions.

IOMMU / SMMU I/O Memory Management Unit. Enforces DMA access permissions from devices, analogous to the MMU for CPU access.

Part II

The Kernel Architecture

4 Capabilities: Authority Without Ambiguity

A capability is the answer to one question: **"May I perform this operation?"** It grants permission to act. Operations describe the work. CharlotteOS capabilities are unforgeable, delegable, and attenuable.

4.1 What a capability is

A capability is a per-address-space handle that names a kernel object and carries a rights mask. The kernel maintains a **capability table** for each protection domain. An entry in this table is the only way a userspace process can reference a kernel object.

Capabilities have four key properties:

- Unforgeable: a process cannot create a capability through computation. The kernel must issue it through an authorized creation, bootstrap, or delegation operation.
- Scoped: a capability is valid only in the domain that holds it. Capability index 3 in domain A refers to a different object (or nothing) than capability index 3 in domain B.
- Righted: a capability carries a rights mask specifying which operations are permitted. A client connection might carry only `SEND | CALL` rights without connection-minting authority.
- Revocable: when a kernel object is destroyed, all capabilities referencing it become invalid. Subsequent use returns an error.




Figure 4.1: The capability boundary: the kernel owns enforcement and opaque objects; userspace owns policy, protocols, and typed resource lifetimes.

4.2 Object types and their rights

The unified namespace records six authority families. Their payload registries distinguish subtypes and enforce the relevant rights or ownership checks. The table gives current operations; only the named IPC and memory masks are rights bits. A CQ identifier is a domain-local queue selector, rather than a separate capability kind, and timers produce completion capabilities.

Family	Checks or operations	What it authorizes
IPC	SEND, CALL, RECEIVE, MINT_CONNECTION	Endpoint, connection, pending-call and one-shot reply authority
Memory	MAP_READ, MAP_WRITE, TRANSFER	Page-backed objects; transfer mode also checks ownership, mappings and loans
Completion	Poll, wait, cancel, close	Submitted operation, timer or event-watch result
Device	Typed map, bind, acknowledge and DMA operations	MMIO region, interrupt or DMA domain; no general Device reset capability
Mailbox	Typed send or receive	Domain-local LP word queue
SystemObserver	Authorized telemetry read	Non-secret system-wide kernel snapshot

4.3 Delegation and attenuation

Capabilities can be **delegated** to another protection domain through IPC. When delegating, the sender may **attenuate** the rights: the receiver gets a subset of the rights the sender held. A service manager that holds a connection with `SEND | CALL | MINT_CONNECTION` rights can delegate a client-facing connection with only `SEND | CALL`, keeping minting authority for itself.

Delegation happens in the kernel, mediated by the IPC path. The sender specifies the target domain, the capability to delegate, and the reduced rights mask. The kernel validates that the sender actually holds the capability with at least the rights being transferred.

4.4 Generation-safe lookup

Capability values are opaque serials consumed monotonically within one namespace. Closing an entry does not make its serial available again; exhaustion rejects creation instead of wrapping. Lookup checks the owning namespace and object family. A removed serial therefore cannot name a later object in that namespace.

Address-space slots have a separate generation. A replacement namespace can reuse numeric values, so pending kernel owners capture the original namespace identity and root generation. A scalar ASID or handle alone cannot authorize delayed cleanup. These rules are implemented in `crates/catten/src/capability.rs` and its record preparation.

4.5 Bootstrap: how capabilities enter a domain

A newly created protection domain starts with an empty capability table. It receives its initial capabilities through the **config-page contract**: a mapped page that the supervisor populates with typed entries before the domain begins execution. The records depend on the launch policy:

- Ordinary deployed applications borrow a grant-controller connection and their immutable signed deployment descriptor through `Context`.
- Trusted platform services may receive a name-service connection.
- Drivers receive the selected MMIO, interrupt and DMA grants.
- Services normally create and own their listening endpoint.

The launch header separately describes the default CQ mapping. Launch-owned connections are borrowed through `Context`; applications must not adopt them as new owners. Section 5.6.1 shows a complete client.

After bootstrap, additional capabilities arrive through IPC: the name service delegates service connections; the supervisor delegates device grants; other services delegate whatever the protocol authorizes.

4.6 Authority and audit consequences

1. A process starts without ambient authority. Every capability it holds was explicitly granted by a trusted component (the supervisor, the name service, or another service under a protocol). There is no ambient authority to strip away and the default is none.
2. Kernel-mediated authority is enumerable: a process' capability table records the kernel objects it may use. This makes authority easier to audit, but does not by itself account for device side effects, protocol state, or implementation defects.
3. Delegation is mediated: a process cannot grant authority it does not hold; it cannot grant rights beyond what it possesses; and as every delegation crosses the kernel, the kernel enforces both constraints.
4. Teardown revokes the destroyed domain's capabilities and closes its endpoint relationships. Existing tests cover stale connections and pending-call reconciliation.
5. Completion submissions share a bounded per-domain operation budget; an exhausted budget results in `WouldBlock`. Completion timers also have separate event limits: at most the domain's completion capacity, currently clamped to 1,024, and 8,192 events across the node. Ordinary domains may use 6,144 of those events, leaving a share for kernel-designated platform work. A cancelled event stays charged until its LP removes the queue node. Shared capability-record admission additionally covers all six families: 4,096 records per namespace, 65,536 per node and 49,152 for ordinary domains. These bounds do not account for every kernel allocation or aggregate principal usage.

Timer cancellation produces a terminal cancelled result without waiting for the original deadline. The completion record owns cancellation, while the event owns its admission charge. Teardown can therefore release the record without falsely reclaiming a still-queued event's capacity. Timer callbacks verify the exact original completion object under the registry lock before publishing a result; a delayed callback cannot complete a replacement merely because it reused the same ASID and numeric handle.

5 Endpoints: Communication as a First-Class Primitive

An endpoint answers: **"Who am I communicating with?"** It is CharlotteOS' primary primitive for calls between protection domains.

5.1 Server and connection model

An **endpoint** is a bounded server-side IPC receive object. A service creates one through which it receives messages. A **connection capability** is a client-side authority to send to that endpoint. Connections are minted from the endpoint (typically by the name service) and delegated to clients.

```
Service creates endpoint:   endpoint_create(interface="ns", capacity=16)
Name service mints conn:    connection_mint(endpoint, SEND | CALL)
Client receives conn:       name_service.lookup("ns") -> ConnectionCap
```

Ordinary clients do not mint arbitrary connections. The name service or a policy service normally delegates them after an access check.

5.1.1 Namespace publication

An IPC namespace belongs to one exact root generation. It must be prepared before ordinary IPC can use it, and retirement prevents new publication into it.

Optional detail: Namespace publication and retirement

Root registration prepares the IPC namespace node and both budget accounts fallibly before taking publication guards. It captures an exact-generation root lease, releases lifecycle/table guards, then links that prepared storage under IPC alone. Cleanup cannot pass the retained lease during this handoff. Missing or retired namespaces reject; ordinary IPC never recreates them.

After fenced loan and capability drain, cleanup detaches the empty namespace node and disposes it outside IPC. Outstanding delegated endpoint/record charges keep their original accounts through ASID reuse. This covers namespace storage; guarded per-capability payload factories, account byte/principal admission and wider destructor contexts remain audit work. See `docs/reference/ipc-namespace-publication.md`.

5.1.2 Endpoint storage admission

Endpoint records and queue backing have generation-scoped sponsorship. The current kernel admits at most 64 endpoint records and 8,192 queue slots per domain, and 1,024 records and 32,768 slots per node. Ordinary domains share 768 records and 24,576 slots; the remainder is available to kernel-designated platform domains. These are initial kernel policies, independent of socket capacity, rather than deployment-descriptor settings.

Create the queue.

Creation admits the endpoint record and queue capacity before publishing authority. A queue admits at most 4,096 messages.

Optional detail: Fallible endpoint preparation

A single queue admits at most 4,096 messages. Creation retains its captured root, reserves record and slot counts atomically, then prepares endpoint storage, queue backing and observer lists fallibly outside IPC. Slots round up to a power of two with a minimum of four. Revalidation precedes authority publication and allocation-free endpoint relinking. Ordinary unused preparation finishes after local guards, root last; abandonment retains every field.

Resize with temporary headroom.

Growth retains that exact root and the original endpoint sponsor and classification, then reserves and allocates a second queue outside IPC. Both backings count at the temporary peak. Revalidation checks root, capability, endpoint, closing state and available backing before moving messages in FIFO order. A competing larger resize can make private preparation unnecessary; concurrent close rejects it. Replaced or unused backing frees after IPC unlock, before its charge returns. Promotion cannot reclassify the original endpoint. Shrinking reduces message admission and retains backing and its charge.

Release after the last retained reference.

Closing the owner drains the queue after confirmed cleanup. Delegated or queued connections can keep a closed endpoint record alive, so its admission is returned only after the final retained storage has been freed.

Optional detail: Endpoint retirement and metadata publication

Owner closure drains the queue and frees its backing after confirmed cleanup. Delegated, queued and unobserved returned connections can retain a closed endpoint. Final-reference removal detaches its complete node into the existing cleanup owner for post-IPC disposal; record admission returns after actual payload and node free. Late cleanup after ASID reuse credits the original account. Fallback retains the complete node, without cleanup or replay authority. Endpoint shared-authority metadata now prepares outside IPC; count admission revalidates the captured namespace under IPC, then payload allocation leaves the guard again. Publication relinks prepared storage. Linear scans and sustained pressure/IRQ hold time remain unqualified. See `docs/reference/endpoint-budgets.md`.

5.1.3 Connection, call and reply record admission

Choose the sponsor.

Each sponsoring namespace generation can retain 512 connection capabilities, 512 pending calls and 512 outstanding reply tokens. Each dimension has a node ceiling of 8,192 and an ordinary-domain share of 6,144. These initial kernel policies are separate from endpoint queue capacity and waiter limits.

The grantor sponsors direct grants and re-delegations. The requesting caller sponsors both its pending call and the server's reply token, and pays for a connection returned in that solicited reply. Repeated lookups

therefore cannot consume the serving grantor's connection allowance. A recipient can hold connections sponsored by several namespaces; 512 is not its total capability-table limit. Sponsorship does not change capability authority. Completed and observed calls remain charged until closed, while reply-token charges return on reply or cancellation.

Admit before consuming inputs.

Connection-bearing calls and replies admit their connection before copying memory, consuming the token or revoking a loan. Kernel rejection leaves the inputs intact. The consuming Rust `ReplyToken::reply_connection*` methods close/cancel their token on an error and preserve the borrowed grant source; they do not return a retryable token.

Optional detail: Call record preparation and rollback

Calls reject invalid handles and unavailable queues before preparing record storage, then recheck them before mutation. They retain their exact caller root and reserve both record counts atomically before preparing record storage, waiter metadata or attachments. Pending and reply-token nodes allocate fallibly outside IPC and publish by relinking. Their containing owner explicitly finishes unused preparation after IPC unlock, root last; abandonment retains every field. Reply, close and confirmed cancellation carry detached record nodes outside IPC and free payload/storage before refunding the original record charge. Scalar completion retains its detached notification batch with the node until explicit finish; fallback retains both. Claim sources use the original token classification through promotion and ASID reuse. See `docs/reference/ipc-record-budgets.md`.

Call preparation uses the same three-phase authority boundary with its existing root retained, and pending waiter-list construction also leaves IPC. Call staging only revalidates prepared metadata. Shared quota rejects before payload/list allocation. Unused shared preparation disposes after local guards, root last; abandonment retains the complete prefix. See `docs/reference/ipc-capability-storage.md`.

Retain admission through teardown.

Retirement fences new capability publication before taking the cleanup snapshot. Existing records keep their original sponsor through delegation and ASID reuse; removing authority does not by itself refund retained storage.

Optional detail: Capability publication and teardown

Teardown fences admission before taking its capability snapshot. Receive and connection-publication paths reject a retiring namespace, preventing late capabilities from escaping that snapshot. Charges retain the original generation after delegation or ASID reuse. Per-capability payload nodes now prepare fallibly after shared count admission and before authority publication. Installation only relinks prepared storage. Existing owners keep unused preparation and detached payload/authority pairs through post-IPC disposal; connection counts return after actual payload/node free. Speculative receive rollback keeps queue/token/loans intact and disposes only its reply capability. Complete fallback retains metadata and charges. See `docs/reference/ipc-capability-storage.md`.

Optional detail: Payload-node backing budgets

Capability, endpoint, pending-call and reply-token payload nodes reserve their requested heap layouts before allocation from `ipc_nodes`. The same node retains backing beside its optional logical record reservation through actual deallocation. Capability backing borrows the recipient authority namespace's captured storage class; grantor/requester logical sponsorship stays independent. Endpoint/call/reply backing uses its original resource reservation class. The expanded pool allows 12/16 MiB and 73728/98304 ordinary/total nodes, sized for all four layouts while preserving existing logical ceilings. The current 24-pool inventory uses statistics version 11, including separate store-image admission; header/record widths and runtime ABI remain unchanged. Complete containing operations and detached lists retain both charges under unknown guards; nested buffers and broader heap/principal admission remain separate. See `docs/reference/ipc-node-admission.md`.

Optional detail: Attachment and cleanup buffer admission

Attachment retirement catalogs also reserve exact capacity from that pool's byte dimension, with zero node slots and the original requester class. A 136-byte retirement entry gives a maximum 255-entry catalog of 34680 bytes. Call rejection and successful receive keep this storage in their complete owner until explicit disposal after IPC unlock. FIFO child handoff preserves full capacity and charge through every callback; interruption retains remaining owners. Buffer deallocation precedes refund. The inline reservation adds 24 bytes per queued-message payload slot.

Parsed-descriptor, capability-ID, transfer-staging and reply-token loan vectors share byte-only admission through an allocator carrying the original class. Growth admits the full candidate while old capacity remains charged; pop/clear retain capacity until deallocation. The capability-vector allocator adds another 8 inline bytes per message slot.

Descriptor snapshots also reserve 4082 requested bytes through the captured IPC allocator, before parsing or preparing transfers. Quota rejection returns `ResourceLimit` and preserves the descriptor and source; successful submission retains its existing descriptor-consumption rule. The byte charge ends after actual temporary-buffer disposal, before submission roots complete.

Reply/cancellation work also shares byte admission, cloning the accepted token's allocator class. Each entry is 200 bytes; 255 entries request 51000 bytes. Empty work allocates nothing. Capacity survives the final pop and is freed after child cleanup, before root completion. Complete parents retain returned-memory escrow, detached storage and notifications on abandonment. Quota rejection precedes the claim and preserves accepted authority. Cleanup headroom is not reserved at call acceptance, so saturation can postpone cleanup. No numerical defaults change; general heap/principal admission and integrated progress qualification remain open.

Optional detail: Mixed capability and memory publication

Direct-grant, receive and returned-connection factories still run under IPC. The memory/authority gate now borrows its existing reservations/transfers and validates the complete set before mutation under one capability hold, without a temporary vector. Complete prepared scalar call commit can publish, install admitted nodes and enqueue with heap held. Global memory-object records now also relink prepared storage, with identities claimed before publication. Target memory-capability, object and read-loan maps relink prepared admitted nodes after authority publication under the same registry hold. Complete mixed commit is heap-free in the documented maximum-batch control; preparation and outer disposal remain separate contexts. See `docs/reference/ipc-publication-batches.md`. Other capability kinds, byte/principal admission, wider con-

Optional detail: Mixed capability and memory publication (continued)

texts and comprehensive heap accounting remain incomplete.

5.1.4 Receive and reply waiter admission

Register before parking.

Threads waiting for endpoint readiness or a pending-call reply use removable, generation-sponsored registrations. Each source links at most 64 entries. They share the completion/CQ waiter pools: 1,024 entries per waiting domain, 8,192 per node and an ordinary share of 6,144. Sponsorship follows the waiting thread, not the endpoint owner. Admission precedes scheduler parking; message or reply state that is already ready returns without retaining an entry.

Cancel the registration when waiting ends.

Ready admission or thread reaping cancels the owning registration. IPC detaches message, reply and source-closure notifications under its registry lock and invokes them only after releasing that lock. Endpoint closure can combine receiver and queued-call batches without allocating a callback vector. Entries remain charged until their detached storage is actually freed. Detached batches no longer occupy the source's linked count; they still occupy the shared domain/node pools while a reusable readiness list is rearmed.

Keep the call and loan through rejected waits.

Untimed receive and reply waits retry cooperatively when admission is full. A reply wait preserves the pending call and its memory loan until reply or explicit cancellation revokes receiver access. The existing Rust owners need no manual unregister step. Kernel timed reply waits can return without a reply on deadline or admission rejection; neither event by itself ends a loan.

Optional detail: Waiter-list preparation

Readiness lists and pending-call lists are prepared fallibly before source publication. Call preparation precedes memory transfer, lending and delegated connection attachments, so failure at this stage leaves those inputs untouched. Connection, reply-token and pending-call counts use the separate record budgets above. List control blocks and other kernel metadata still need comprehensive admission and fallible allocation.

5.2 Message classes

The ABI distinguishes two message classes:

5.2.1 Scalar messages

A scalar message carries an opcode, one 64-bit argument word, and optionally a reply token. It fits in registers. It is suitable for:

- Opcodes and request types.
- Capability handles.
- Status values and queue indices.
- Compact control-plane operations where the payload is a single word.

Scalar messages require no memory-object allocation, page-table change, or TLB invalidation.

5.2.2 Memory-based messages

A message can carry one or more **memory-object attachments** with explicit transfer modes (see Chapter 6). These are suitable for:

- Structured requests and responses.
- Strings, names, and configuration structures.
- Packet payloads and block I/O buffers.
- Larger replies that exceed register width.

The kernel validates each attachment: the sender must hold the referenced memory object with sufficient rights for the declared transfer mode. The receiver gets a new capability to the memory (or a temporary mapping, for borrows).

Scalar copy/move sends and copy/move/read/write-loan calls capture both exact roots and prepare memory outside IPC, then revalidate the captured connection, namespaces and endpoint before publication. A single send retains its transfer, attachment storage and pending delivery in one containing owner. Explicit finish runs after IPC unlock, notifies before completing the roots, and restores an unpublished source or releases private copy backing on ordinary rejection. Complete single/vector-send and claimed-reply parents retain all fields on abandonment, including returned-memory escrow and work capacity. Explicit known unstarted rejection still restores its preparation. Other active transfer parents and enclosing IRQ contexts require separate qualification.

5.3 Message envelope

The kernel validates a fixed-width message envelope. It does not understand Rust enums, `serde` formats, or protocol-specific types:

```
struct MessageHeader {
    interface: u128,       // protocol identity
    version: u32,
    opcode: u32,
    flags: u32,
    inline_len: u16,
    segment_count: u16,
    capability_count: u16,
    reserved: u16,
    user_tag: u64,
}
```

Constraints on the ABI:

- Fixed-width fields: no `usize`, no pointer-sized values.

- Explicit alignment: no compiler-dependent layout.
- Checked offsets and lengths: the kernel rejects out-of-bounds.
- Explicit protocol versioning: forward compatibility is negotiated.
- Maximum attachment counts: bounded kernel work per message.
- No arbitrary userspace pointers as durable message identity.

5.4 Call and reply

The most common IPC pattern is **call/reply**: a client sends a request and expects a response.

5.4.1 Synchronous-looking futures

At the Rust level, a client writes:

```
let response = network_service.connect(address).await?;
```

Underneath, the runtime:

1. Sends a call message through the connection capability.
2. The kernel creates a one-shot **reply token** bound to this call.
3. The caller task becomes pending (the `Future` returns `Poll::Pending`).
4. The caller shard continues running other tasks: no thread is dedicated to this request.
5. The server receives the message on its endpoint.
6. The server replies (immediately or later).
7. Reply arrival wakes the client future, which returns `Poll::Ready(response)`.

5.4.2 Deferred replies

A server may retain a reply token and complete it later while continuing to serve other requests on the same shard. This supports device-driven operations:

```
async fn handle_read(pending: PendingRequest) {
    // Submit a DMA read, retaining the reply token.
    // Continue serving other clients while the read is in flight.
    let buffer = device.read(address, len).await?;
    pending.reply_with_buffer(buffer);
}
```

The shard's executor polls other tasks while the read completes.

5.4.3 Reply token semantics

A reply token is:

- Created by the kernel when a call message is enqueued.
- Bound to the pending call: it completes exactly that caller's future.

- Consumable exactly once: a second reply attempt returns an error.
- Closed by confirmed cancellation. A wait timeout alone leaves the pending call and reply authority live; the caller must retain the owner until reply observation or completed cancellation.
- Endpoint teardown can complete a call with `IPC_REPLY_ENDPOINT_CLOSED`. The client below maps this to its own `ServiceRestarted` recovery decision. The kernel must finish required loan cleanup before publishing that terminal result; uncertain cleanup can leave the call pending.
- The receiving service owns the reply token. It can call a second service while retaining that authority and the new pending call. General reply-token delegation is not exposed by the current API.

5.5 Connection delegation

A connection capability can be delegated to another domain with attenuated rights. This is the mechanism by which the userspace name service returns service-level connections. The following pseudocode illustrates delegation; the compiling client API is shown in Section 5.6.1:

```
// The registrar retains the publisher's mintable connection:
let source = registration_connection.as_ref();
// Ordinary lookup returns SEND | CALL and cannot supply this source.

// After authorizing the client, attenuate its reply:
reply.reply_connection_ref(
    source, IpcRights::SEND | IpcRights::CALL, generation,
)?;
// The client receives SEND | CALL only.
```

The kernel mediates. The name service never sees raw endpoint identities; it holds the publisher's mintable connection grant. Ordinary lookup removes minting authority, so a client cannot re-delegate that returned connection. Each authorized delegation step can only reduce rights. DNS placement lookup returns catalog metadata; application authority comes from the local name or policy grant path.

5.6 Service identity and discovery

The kernel uses opaque endpoint identities. A userspace **name service** maps human-readable names to re-delegable connection capabilities:

- Registration: a service registers as `"driver.nic.v1"` with a specific endpoint. The name service stores the endpoint's connection.
- Generation tracking: replacement registrations advance the name's generation. A connection continues to identify its original endpoint; re-registration alone does not revoke it or redirect it to a replacement. Endpoint death closes that instance's communication path.
- Authorization: policy-published services use default-deny rules checked against the kernel-authenticated caller identity. Ordinary applications acquire a connection through the capability-grant controller using their signed deployment descriptor. Bearer access-key lookup is retired; public lookup cannot bypass a protected publication.
- Lookup: an application requests a complete name such as `"driver.nic.v1"` and the rights it needs. The owning Rust API returns a `Connection` or an error; capability handles stay inside that owner. No network address or port is needed for local IPC.




Figure 5.1: A service creates and registers its endpoint before a client resolves an attenuated connection and performs a capability-safe IPC call.

The name service runs in userspace. The kernel provides the endpoint and connection primitives; userspace provides the naming policy.

5.6.1 A client with explicit recovery scopes

The following is a complete, compiling userspace example. It uses the existing `greet` service's read-only `deploy::OP_GET` protocol so that the business operation has a concrete implementation. The deployment descriptor must grant `CALL` on `greet`, and the service must be published and allowed by policy. A NIC client would use its own signed service grant and versioned protocol in those two places.

Keep the recovery scopes nested in this order:

1. The application borrows its launch authority and owns its business progress and current operation deadline.
2. Discovery creates one owned connection for a session.
3. The session performs business operations through a borrow of that connection. A confirmed result advances application progress.
4. Each operation owns its pending call until reply observation or confirmed cancellation. This owner ends before the session connection.

The complete source is `crates/catten-services/examples/reconnecting_client.rs`. It depends on `catten-rt`, `catten-services`, `catten-syscall` and `charlotte-launch`. The listings below include that source directly; the conditional attributes only allow its host tests to use Rust's test harness.

Application lifetime.

The launch contract supplies borrowed authority. Terminal exit and cooperative shutdown happen after `run` has returned and its owned resources have left scope. Failed cancellation has a separate retaining abort path below.

```
#![cfg_attr(not(test), no_std)]
#![cfg_attr(not(test), no_main)]

use catten_rt::{
    Context,
    ShutdownRequest,
    owned::{
        CallResult,
        Connection,
        IpcError,
        PendingCall,
    },
};
use catten_services::{
    deadline::Deadline,
    deploy,
    grant_client,
};
use catten_syscall::{
    IPC_REPLY_CANCELLED,
    IPC_REPLY_ENDPOINT_CLOSED,
    ipc_status,
```

```
};
use charlotte_launch::deployment::RIGHT_CALL;

const READS: usize = 3;
const MAX_SESSIONS: usize = 3;
const JOB_BUDGET_MS: u64 = 5_000;

#[derive(Debug)]
pub enum Failure {
    LaunchContract,
    Discovery(grant_client::Error),
    Ipc(IpcError),
    WaitAdmissionRejected,
    OutcomeUnknown,
    ServiceRestarted, // Application policy for a closed endpoint.
    Rejected(i64),
    InvalidReply,
    RecoveryLimit,
    Shutdown(ShutdownRequest),
}

#[cfg(not(test))]
fn main(ctx: Context) -> ! {
    // run() releases its owned resources before any terminal action here.
    match run(&ctx) {
        Ok(()) => unsafe { catten_syscall::thread_exit() },
        Err(Failure::Shutdown(request)) => request.complete(),
        Err(error) => {
            catten_rt::logln!("client stopped: {:?}", error);
            catten_rt::domain_abort()
        }
    }
}

#[cfg(not(test))]
catten_rt::entry!(main);
```

Discovery and session lifetime.

`Work` outlives every connection. When the session reports endpoint loss, `continue` drops that old connection before discovery acquires another. There are at most three sessions. The deadline belongs to the current business operation and survives reconnection; repeated discovery cannot renew its budget. Authorization, resource and malformed-request errors return to application policy. There is no fallback to public lookup.

```
struct Work {
    completed: usize,
    deadline: Deadline,
}

pub fn run(ctx: &Context) -> Result<(), Failure> {
    // These are borrowed launch grants, not newly adopted capabilities.
    let controller = ctx.bootstrap_connection().ok_or(Failure::LaunchContract)?;
    let descriptor = ctx.profile_memory().ok_or(Failure::LaunchContract)?;
    let mut work = Work {
        completed: 0,
        deadline: Deadline::after(JOB_BUDGET_MS),
    };

```

```
    for _ in 0..MAX_SESSIONS {
        check_shutdown(ctx)?;
        let connection = grant_client::acquire_until(
            controller,
            &descriptor,
            b"greet",
            RIGHT_CALL,
            &work.deadline,
        )
        .map_err(Failure::Discovery)?;

        // The session borrows this owner. Its pending call ends first.
        match session(ctx, &connection, &mut work) {
            Err(Failure::ServiceRestarted) => continue,
            result => return result,
        }
        // continue drops the old connection before the next acquisition.
    }
    Err(Failure::RecoveryLimit)
}

fn check_shutdown(ctx: &Context) -> Result<(), Failure> {
    match ctx.lifecycle().shutdown_requested() {
        Some(request) => Err(Failure::Shutdown(request)),
        None => Ok(()),
    }
}
```

Business operation.

The inner scope contains only use of this session. Its `ServiceRestarted` variant is an application-defined classification of the current endpoint-closure status or terminal reply code. The runtime does not export an error variant with that name, and closure alone does not establish that a replacement is available. All other failures step out to the application. Progress and the next deadline advance only after a validated reply.

```
fn session(ctx: &Context, connection: &Connection, work: &mut Work) -> Result<(),
    Failure> {
    while work.completed < READS {
        check_shutdown(ctx)?;
        if work.deadline.expired() {
            return Err(Failure::RecoveryLimit);
        }
        let pending = connection.call(deploy::OP_GET, 0).map_err(admission_error)?;
        let value = decode(observe(pending, &work.deadline)?)?;

        // Business use: a confirmed, read-only greeting observation.
        catten_rt::logln!("observation {}: {}", work.completed, value);
        work.completed += 1;
        // Only a new business operation receives a new deadline.
        work.deadline = Deadline::after(JOB_BUDGET_MS);
    }
    Ok(())
}

fn admission_error(error: IpcError) -> Failure {
    match error {
        IpcError::Status(ipc_status::ENDPOINT_CLOSED) => Failure::ServiceRestarted,
```

```
        other => Failure::Ipc(other),
    }
}

fn decode(reply: CallResult) -> Result<u64, Failure> {
    // All unexpected returned owners are still disposed on this error path.
    if reply.connection.is_some() || reply.memory.is_some() {
        return Err(Failure::InvalidReply);
    }
    match reply.result {
        IPC_REPLY_ENDPOINT_CLOSED => Err(Failure::ServiceRestarted),
        IPC_REPLY_CANCELLED => Err(Failure::OutcomeUnknown),
        value if value < 0 => Err(Failure::Rejected(value)),
        value if value as u64 == deploy::GREET_VALUE => Ok(value as u64),
        _ => Err(Failure::InvalidReply),
    }
}
```

Accepted-call lifetime.

A timeout and rejected waiter admission are different outcomes. Both leave an accepted pending call owned here. Explicit cancellation closes that owner before returning an error; rejected cancellation returns the owner, which stays live through terminal domain abort. Cancellation can wait for loan cleanup, so the five-second observation budget is not a guaranteed teardown deadline.

```
fn observe(mut pending: PendingCall<'_>, deadline: &Deadline) -> Result<CallResult,
     Failure> {
    match pending.wait_timeout(deadline.remaining_ms()) {
        Ok(Some(reply)) => Ok(reply),
        Ok(None) => {
            cancel(pending);
            Err(Failure::OutcomeUnknown)
        }
        Err(IpcError::Status(ipc_status::RESOURCE_LIMIT)) => {
            // Wait admission failed; the accepted call still has an owner.
            cancel(pending);
            Err(Failure::WaitAdmissionRejected)
        }
        Err(error) => Err(Failure::Ipc(error)),
    }
}

fn cancel(pending: PendingCall<'_>) {
    if let Err((retained, error)) = pending.close() {
        // Rejected cleanup returns the owner, including any Rust memory loan.
        // Keep it and the enclosing session live through terminal abort.
        let _retained = retained;
        catten_rt::logln!("call cleanup rejected: {:?}", error);
        catten_rt::domain_abort();
    }
}
```

This example can repeat an unconfirmed greeting read after endpoint loss because the operation is read-only. A write, payment, device command or other mutation needs its own recovery contract: for example a durable request ID, deduplication and a query for the recorded outcome. Successful cancellation does not undo an effect already performed by the service. Timeout, cancelled replies and rejected wait admission therefore stop this example; they never enter its reconnect path. Its progress counter survives connection

replacement within this process only. Durable application progress belongs outside the session and needs its own commit and recovery rules.

The single-call wait suits a dedicated client that has no inbound work needed to produce the reply. A service reactor must bind the pending call and its other interests to one CQ and continue serving them; see `docs/reference/cq-wait.md`. Shutdown is checked between acquisitions and calls, so an accepted RPC may occupy the observation budget before that check. Grant acquisition still uses bounded availability backoff because applications have no publication-readiness subscription. It returns authorization and other rejections immediately. This example demonstrates ownership and recovery policy; it does not establish production readiness of the operating system.

5.7 Two kernel data paths

A central distinction is that endpoint IPC is for **cross-domain service calls**. Completion queues are for **kernel and device operations**.

Endpoint IPC path	Completion queue path
Application → network service	Timer expiry
Network service → NIC driver	DMA completion
Application → filesystem service	IRQ-derived device completion
Service → name service	Waiting for thread/process exit

A userspace driver may compose both: receive an endpoint message (data path), then submit a hardware operation and await a CQ entry (control path). The endpoint message and the hardware completion are related *in the service's logic*, but they are different kernel abstractions with different semantics.

5.8 Authority, concurrency, and restart

1. Communication carries authority: a client that holds a connection capability was authorized (at grant time, by the name service or policy service) to communicate with the target. Every message is authorized by possession of a kernel-mediated capability rather than by an address or UID alone.
2. Scalar and memory messages are distinct: the kernel does not copy arbitrary data between address spaces by default. Small control messages stay small. Bulk data moves as memory objects (Chapter 6) with explicit ownership semantics.
3. Deferred replies enable efficient concurrency: a server is never forced to block waiting for one slow client. It retains reply tokens for in-flight work and continues serving other requests. The shard's executor multiplexes naturally.
4. Endpoint loss is observable: clients classify the endpoint-closure status and terminal reply, as in Section 5.6.1. A replacement cannot inherit the old instance's reply tokens.
5. The kernel provides endpoints and connections. The userspace name service decides who can register what name, who can look up what service, and which rights policy permits. The kernel remains small; policy is replaceable without a kernel rebuild.

6 Memory Objects: Ownership That Crosses Boundaries

A memory object answers: **"Where is the data, and who owns it?"** It lets page-backed data cross protection-domain boundaries with explicit ownership and, for move and borrow modes, without copying the payload.

6.1 The problem with copying

In a conventional OS, moving data between processes typically means copying: the kernel reads from the sender's address space and writes to the receiver's. For large payloads (packet buffers, file blocks, IPC messages), this copy dominates the cost of the operation.

Unrestricted shared memory avoids the copy but permits multiple processes to modify the same pages. Correctness then depends on synchronization rather than page-table exclusivity.

CharlotteOS adopts a third approach: **ownership transfer through page-table manipulation.** When a memory object moves from one domain to another, the kernel changes the page-table mappings. The sender loses access; the receiver gains it, while no bytes are copied, under MMU-enforced ownership.

6.2 First-class memory objects

A memory object is a dedicated kernel object representing page-backed storage with explicit ownership and capability semantics. The kernel manages:

- Physical frames: the backing storage.
- Mappings: which domains have virtual addresses pointing to the pages, and with what permissions.
- Ownership: which domain currently holds the master capability.
- Transfer state: whether the object is idle, in transit, borrowed, or undergoing DMA.
- Lifetime: when the object is freed, all mappings are revoked and all capabilities to it are invalidated.

Userspace never exchanges raw pointers across protection domains. Instead, IPC messages attach **memory-object capabilities** with declared transfer modes.

6.3 Aggregate admission and sponsorship

The capacities in this section are compile-time defaults, adjustable through the central resource policy described in Chapter 20. Adjusting capacity does not change ownership, sponsorship or physical completion rules.

Read admission in three parts: which budgets an allocation must pass, who keeps the charge when authority moves, and what permits the charge to be returned. Metadata has its own retained storage and follows the same sequence.

6.3.1 Reserve backing and principal capacity

The kernel reserves backing pages and one object-accounting unit before each allocation. One generation may sponsor at most 64 MiB and 1,024 backing objects, with the page ceiling reduced on smaller nodes. The node's memory-object pool is at most one quarter of usable RAM and 8,192 objects. Ordinary domains may consume three quarters of that pool; the remainder is available to supervisor-designated platform domains. Allocation must also leave one eighth of usable physical frames free. Platform domains still obey per-domain and node-wide limits.

One verified artifact principal also shares a ceiling of 16,384 pages across memory-object, committed heap, ELF/runtime, private-table backing and maximum user-thread stack capacity, plus 1,024 memory-object allocations. Every instance and generation consumes that same counter in the existing principal-history record. The signed loader prepares its immutable sponsor before architecture root construction and validates that binding before optional preparation and thread publication. A new instance, ASID reuse or platform promotion cannot reset it. Existing generation and node pools still apply. See `docs/reference/principal-backing-admission.md`.

6.3.2 Keep sponsorship through ownership changes

Sponsorship is distinct from ownership. A move transfers the authority to use or destroy an object, while its charge stays with the creating generation until the physical frames and object record are released. A copy reserves new backing storage against the copying caller, even when another domain receives it. Borrowing and pinning retain the existing charge. This prevents a sender from shedding its budget merely by filling a privileged receiver's queue.

Charges survive sponsor retirement, mapping shootdown and delayed DMA or copy completion. A reused ASID receives a separate generation budget; late releases apply only to the retired generation and original principal. Staged-allocation owners roll back failed admission and allocation. A failed physical release quarantines its charge rather than creating fresh headroom.

6.3.3 Prepare metadata before publication

Before public state changes, the kernel prepares the object, capability and mapping metadata fallibly. Publication rechecks the captured generation and links prepared storage. Unused storage is disposed of after local guards; abandoned preparation retains its fields and charges.

Optional detail: Object and capability preparation

Global object-record storage is prepared fallibly with private backing after page/object admission. Direct allocation and copies claim a non-reused kernel object identity before authority publication; publication only relinks prepared storage. Cancellation leaves identity gaps. Read-loan, memory-capability and namespace records prepare before mutation and relink at publication. Mapping records and frame-snapshot capacity prepare fallibly outside the memory registry. Scratch namespace and extent nodes prepare outside their local registry, with exact-generation/current-space revalidation.

Memory capability preparation owns its partial payload/namespace nodes, exact authority/account reference and captured handle in inert fields before factories. Ordinary success/rejection explicitly frees unused nodes before authority cancellation, after local memory guards. The existing containing transfer consumes remaining destination storage after source/borrower work. Bare preparation abandonment enters no registry, allocator or account destructor. Namespace teardown may drain hidden

Optional detail: Object and capability preparation (continued)

authority while payload metadata retains its original byte/count admission; late finish after ASID reuse cannot affect a successor. Containing transfer destructors and broader IRQ/guard contexts remain separate; the backing owner's inert fallback is described below.

Optional detail: Capability publication and retirement

Direct allocation, copies, moves and loans now prepare both payload and namespace nodes fallibly after exact shared authority reservation. Factories leave memory serialization; captured namespace generation is checked before publication. Commit only relinks prepared nodes. Unused namespace candidates remain with the containing preparation for post-guard disposal. Ordinary loan cancellation drops unused borrower storage before its destination reservation refunds.

Retired capability nodes retain their exact authority. Explicit disposal frees payload metadata before authority metadata and original admission. Moves carry the detached source payload with the same source escrow; loan cleanup pairs the full payload/authority node with its borrower. Direct close and final-pin cleanup retain these nodes in the complete object/backing receipt through physical proof. Failed release retains original backing and authority charges. Namespace cleanup detaches and drains its complete node after memory unlock, without a snapshot or new recovery ticket. Source-escrow and wider factory/destructor/IRQ contexts, general metadata-byte admission and sustained pressure remain open.

Optional detail: Mapping preparation and prefix rollback

After preflight, one preparation allocates an empty mapping node and frame-snapshot capacity outside memory serialization. No frame identity or pin crosses that factory interval. Captured object/size and every admission predicate revalidate before snapshot fill, node relink and existing pin acquisition. Page-table walking and prefix rollback keep their previous serialization; unused snapshot disposal leaves both local guards.

Rejected-prefix rollback carries its original detached node and exact published prefix in the same pin until invalidation and required scratch completion. Explicit unmap keeps its live record through those proofs, then frees the detached node before pin decrement/backing release. Revocation uses that pin too. Namespace retirement retains complete admitted mapping nodes and exact peer leases on failure/abandonment; physical success permits node disposal, then peer completion. No new physical proof, recovery registry or retry authority is added. General metadata-byte admission, concurrent unused preparations and broader enclosing contexts remain separate qualification work.

6.3.4 Account for retained metadata and catalogs

Backing pages are only part of an allocation's footprint. Node storage, frame catalogs, snapshots and shared accounts have additional budgets. Their charges follow allocated capacity until deallocation, including storage whose logical entries have already been removed.

Optional detail: Memory-capability node capacity

Object, capability payload, namespace and read-borrower nodes share requested-layout admission: 4 MiB and 32768 nodes total, with 3 MiB and 24576 nodes available to ordinary callers. These are compile-time defaults for the memory-capability node pool. Direct allocation and copy need three candidate nodes, including their object record; moves and write loans need two, and read loans three. The namespace candidate is prepared even when a namespace already exists. Capability/namespace/borrower nodes capture destination class before escrow. Object records capture the exact original backing sponsor (the source on copy), separately from their current owner. Moves, promotion and root reuse cannot reclassify them. Object-node quota rejection cancels the complete prefix before frame allocation/publication. Original admission follows published, detached and abandoned storage until actual node deallocation, before independent authority disposal. Promotion, logical retirement and ASID reuse supply no refund. Allocator overhead, other nested allocations and aggregate principals remain separate; see `docs/reference/memory-capability-node-admission.md`.

Optional detail: Object and root frame catalogs

Object frame catalogs also use that pool's byte dimension, contributing zero node slots. The same captured backing class admits exact pointer-vector capacity before allocation and physical frame creation. The retaining catalog owner moves with the object and exposes only borrowed slices and bounded push/pop. Popping every identity never proves physical release or refunds allocated capacity. Confirmed cleanup frees the vector before refund; failure retains it with the physical charge and complete object node. A maximum catalog is 128 KiB at the default 16384-page object bound; the 24-byte inline owner is included in the 248-byte object-node layout. Numerical defaults remain unchanged, and profile validation requires a maximum catalog to fit ordinary metadata and snapshot byte ceilings. General heap/principal admission and sustained fairness remain open.

Root heap/image frame catalogs use a separate retaining `FrameTracker` with byte-only admission from this same metadata pool and the signed principal's 16 MiB kernel-buffer allowance shared with diagnostics. Full old/candidate capacity overlaps before growth; constructor-captured class survives promotion. Initial identity binding admits any existing unidentified capacity before physical binding commits. Only a completely successful owning release walk may free the catalog and refund its bytes. Failure or abandonment retains capacity even after its identities have been drained, without granting physical retry. See `docs/reference/page-table-lifetime.md`. General metadata/principal coverage, allocator overhead and sustained progress remain separate gates.

Optional detail: Shared account backing

Shared account storage has separate principal funding: capability/IPC/mailbox accounts share a 1 MiB allowance; waiter, scheduler/completion timer and record/CQ/watch accounts share another 1 MiB. Both fund actual Arc and private holder layouts through final weak or allocator reference release. Root and namespace preparation capture the original principal before allocation; promotion, root close and ASID reuse cannot redirect refunds. These policies remain separate from resource grants and the 16 MiB buffer allowance. Enclosing reference fields, allocator excess and joint heap capacity still need their own accounting. See `docs/reference/completion-account-admission.md`.

Optional detail: Mapping-node and snapshot capacity

Mapping-record nodes now reserve their complete requested layout/count before allocation: 1 MiB/8,192 total and 768 KiB/6,144 ordinary. The exact calling root's trusted classification is captured once. Original admission follows the same node through preparation, publication and selected/whole-map retirement; actual node free precedes refund and peer-root completion. Unused/uncertain abandonment retains node and charge without counter or allocator entry. Existing physical proofs remain required; see `docs/reference/mapping-node-admission.md`. Aggregate principals and sustained concurrent progress remain open.

Mapping/copy/DMA frame snapshots now share requested buffer-byte/count admission: 4 MiB/8,192 total and 3 MiB/6,144 ordinary. The exact calling namespace's trusted classification is captured before allocation. One inert buffer owner carries its original charge through preparation, publication, root retirement and abandonment; actual buffer free precedes refund. Late promotion and ASID reuse cannot reclassify that reservation. Empty source-escrow pins have no buffer allocation or quota. Allocator overhead, inline metadata, aggregate principals and sustained concurrent progress remain separate; see `docs/reference/snapshot-buffer-admission.md`.

6.3.5 Keep snapshots and pins through maintenance

Mapping, copying and DMA retain the frame identities needed for their own completion boundaries. Rejection or removal from a registry does not permit a backing pin to be released before the required maintenance has completed.

Optional detail: Mapping and copy-pin preparation

Mapping preparation now owns its partial node and shared snapshot in inert fields before either factory. Ordinary constructor rejection and every constructed completion/rejection explicitly dispose after local memory/table guards. Abandonment retains partial, complete unpublished and published-snapshot storage without allocator entry. Final admission checks the captured full namespace generation before mapping/pin publication. Existing root and physical completion policies remain required; no retry owner or cleanup authority is added.

Copy-pin frame snapshots likewise prepare fallibly outside memory serialization, before any frame identity or source pin is retained. Final namespace-generation, object/size and rights/loan/DMA/mapping checks precede snapshot fill and pin publication under one hold. Ordinary rejection disposes unused capacity after unlock. Bare preparation/pin abandonment retains snapshot metadata without allocator entry; explicit unpin frees it before decrementing the backing fence. Empty source-escrow retention pins use this same owner without a snapshot. Aggregate principal admission, automatic scoped/source-transfer destructors and wider IRQ/guard contexts remain separate qualification.

Optional detail: DMA snapshot preparation

DMA snapshots now use the same inert vector preparation outside memory serialization. Full namespace/source and direction/rights/loan/exclusion checks revalidate before allocation-free snapshot fill and shared/exclusive counter publication. The infallible clone after counter mutation is removed. Bare DMA pin fallback retains snapshot and original backing fences; explicit snapshot free precedes unpin. Existing backend operation/maintenance owners still supply the hardware completion proof. No readiness, recovery family or replay authority is added. Aggregate principal snapshot budgets and broader

Optional detail: DMA snapshot preparation (continued)

outer contexts remain open.

6.3.6 Refund only after confirmed release

Retirement retains the complete object and its original charge until physical release and metadata disposal have both completed. Uncertain release retains that state; it supplies no authority to retry physical cleanup.

Optional detail: Backing retirement and disposal order

Retirement keeps the complete detached object node in the existing backing receipt, with its original frame vector, charge and metadata. Physical release uses sixteen-frame batches; a started/failed fence precedes allocator entry. Only confirmed physical completion and actual payload/node disposal permit charge refund. The backing owner's Drop now retains charge-only, private and published fields without physical/heap allocator, registry, accounting or logging work. Ordinary construction and allocation/copy rejection consume that same owner explicitly after local guards leave. Publication keeps its original guard through consuming handoff. Last-pin release is explicit; the containing transfer destructor also explicitly releases cancelled copy backing after destination metadata/authority. That outer destructor remains active and separately unqualified. Failed physical release retains every original charge and node; no physical retry or new recovery owner is added. Wider caller/IRQ contexts retain their separate qualification. See `docs/reference/memory-object-storage.md`.

6.3.7 Understand the remaining policy boundaries

These are initial kernel admission policies, independent of telemetry filtering and placement feedback. Signed deployment fields and a userspace policy API for these limits remain future work. Demand-backed heaps and ELF/runtime pages have independent generation-owned accounts and node pools, alongside the shared principal ceiling. Capability records, IPC operations and several completion/observer families also have separate admission. Private translation tables also consume that same principal allowance, including initial roots and cached sparse branches. They retain owning-root limits and a node pool; fresh shared runtime kernel tables have a separate node pool. Inherited boot tables/stacks, IOMMU tables, general kernel heap and comprehensive metadata accounting remain open.

6.3.8 Stack capacity admission.

Before backing allocation, each runtime user-thread slot reserves its configured maximum user pages plus sixteen kernel pages in a separate node stack pool. The pool uses one eighth of usable RAM; ordinary domains may consume three quarters, leaving trusted-platform headroom. A root has at most 64 exclusive slots and at most 64 user pages per slot. User backing still grows on demand. The complete maximum user-plus-kernel data footprint consumes the shared signed principal allowance before frame allocation. A typed share remains with the original slot/root owner through uncertain cleanup; only unused cancellation or confirmed pair release refunds it. Data growth pays once, while new private table branches still have their own charge. One owning transaction retains both stack ranges, the original root lease and the reservation through physical cleanup. Refund requires confirmed release of both ranges; failed or abandoned cleanup retains the entire maximum charge and slot even if other pages were freed. Kernel-only threads reserve sixteen pages from trusted admission. Inherited boot/CPU stacks remain outside this runtime pool.

6.3.9 Translation-table lifetime.

Removing a page mapping clears the leaf while retaining empty intermediate tables in their owning hierarchy. Subsequent mappings reuse those tables; quiescent address-space teardown releases the complete private tree. Hardware page walks do not take software locks, so an empty table cannot be recycled merely because its last leaf was removed. New table backing is initialized before its parent link becomes valid.

There are three distinct boundaries: remove a mapping, complete translation invalidation, and release physical backing. Closing an entire address space also fences new work and waits for existing operation leases. The sequence below keeps those boundaries separate.

Remove mappings before releasing backing.

Clearing a leaf does not prove that hardware has stopped using the old translation. Mapping retirement therefore retains its pin, frame identities, loan restrictions and original sponsorship through invalidation. Failed or abandoned maintenance keeps that state retained.

Optional detail: Retained tables and invalidation acknowledgements

Retained tables follow the hierarchy's high-water footprint and consume their own admission limits. Shared physical data still requires independent user translation trees in each domain. Kernel trees are shared and must be accounted for once. Automatic promotion of an empty subtree to a large-page leaf is not implemented. Returning an unmapped data frame likewise does not authorize reuse before translation invalidation has completed. Kernel-range cleanup now retains removed data in an owning retirement receipt, releases its arena/page-table guards, then invalidates before recycling. Failed preparation retains its installed prefix through the same boundary. Forgotten or incomplete cleanup quarantines backing. On x86, checked invalidation uses bounded, epoch-qualified acknowledgement and rejects masked post-bootstrap initiators. Failed delivery cannot count as acknowledgement. Retained owners permit invalidation retry only before physical release starts; broader caller-context qualification and recovery of abandoned owners remain hardening work.

Optional detail: Mapping pins and rejected prefixes

Memory-object mappings carry a separate retirement pin through invalidation. A returned map rejection before acquiring that pin made no mapping publication or table change in that call. It returns unused scratch without TLB maintenance. Admitted calls still invalidate after rejected/rolled-back prefixes; the error alone cannot permit early pin release. Kernel errors retain the per-call invalidation cause. x86 timeouts include their owned epoch and a sampled first missing target, which supplies no release or retry authority. The syscall still reports uncertain status 9. See `docs/reference/memory-object-retirement.md`.

The final DMA or copy unpin cannot release backing during that interval, and borrower cleanup retains loan restrictions until the fence completes. Failed detach or abandoned cleanup retains both backing and its original sponsorship charge. Partial installation records only the published prefix; cleanup checks leaf identity and leaves a foreign collision mapping untouched.

Domain cleanup moves existing mapping records one object at a time, without temporary teardown vectors. It prepares the records under the object registry, then releases that guard before detaching leaves. The retained pin supplies borrowed frame identities in fixed stack batches, so ordinary unmap, loan revocation and domain cleanup no longer nest the object registry across address-space table walks. Larger objects use successive batches without allocating a teardown snapshot.

Optional detail: Mapping pins and rejected prefixes (continued)

These owners retain exact-generation root operations through physical completion. Loan revocation, IPC reply/cancellation and staged namespace close compose those owners so invalidation leaves their local lifecycle/IPC guards first. An unrelated outer masking guard can still prevent progress; this local separation does not qualify every caller or destructor. See `docs/reference/live-address-space-operations.md` and `docs/reference/hardware-quiescence.md`.

Complete virtual-range retirement.

Scratch ranges have their own retirement boundary. Completed ranges may be reused, while a rejected range stays reserved; translation invalidation alone does not finish scratch retirement.

Optional detail: Scratch reservation and retirement

Scratch reservation metadata is prepared fallibly before publishing a virtual range. Namespace and sorted live-extent records use admitted nodes prepared outside scratch serialization; gaps are implicit. Release detaches one exact reservation without allocating a free-list node, then frees it after unlock. Partial, combined or duplicate releases are rejected. Bulk mapping retirement retains its backing pin and loan restrictions if any scratch completion fails, even after successful translation invalidation. Completed ranges may be reused; rejected ranges remain reserved. This strengthens completion without introducing a live-generation lease or a comprehensive kernel-metadata budget. MMIO retains its existing root/descriptor claim while scratch preparation also leaves the device registry; mapped-state admission rechecks atomically with that claim. Whole-root sealing carries the complete scratch namespace and extent nodes in its existing metadata/root receipt through final invalidation. Failure or abandonment retains them; confirmation permits post-guard node disposal before root backing/slot completion. No separate recovery ticket or physical/replay proof is added. Scalar range matching still supplies no allocation nonce, and general metadata-byte/principal admission and wider caller contexts remain open.

Optional detail: Scratch metadata capacity

Scratch namespace and extent layouts now share 512 KiB/8,192 nodes in total, with ordinary preparation limited to 384 KiB/6,144 nodes. Admission precedes each allocator, capturing the exact root's trusted classification once. Partial and unused candidates, live reservations and detached metadata retain their original requested bytes/counts through actual node deallocation. Later promotion and ASID reuse cannot reclassify the refund. Ordinary rejection disposes explicitly; abandonment retains node and charge without counter entry. Allocator overhead, aggregate principal metadata and sustained concurrent progress remain separate.

Fence new operations and drain existing leases.

A live-operation lease keeps the exact root generation available while mapping, loan or device work finishes. A staged close fences new leases and retains its owner while existing leases drain. Deadline expiry or a terminal failure does not authorize reclamation.

Optional detail: Root leases and loan revocation

A separate live-operation lease retains an exact software generation before detachment. Its linear table/slot/generation token survives moving metadata. Root close rejects outstanding leases before subsystem retirement; only explicit completion of the last lease permits normal close. Abandonment retains the live root, tag and charges.

Public memory-object and MMIO map, map-any and unmap calls retain an operation lease through page-table changes and TLB invalidation. MMIO also holds a capability claim so close cannot consume it midway through mapping. Explicit device close detaches its authority under lifecycle/device serialization and retains a root lease while invalidating after releasing those guards. Direct loan revocation retains leases for both owner and borrower. Its transaction owns the existing borrower state and a backing pin until leaf removal, invalidation, scratch completion and borrower-capability removal succeed. A failed or abandoned transaction retains its backing charge and revocation fence. Successful revocation preserves the object's other read borrowers.

Read-borrower records use admitted nodes retained in the existing prior-state owner. Failed completion or abandonment keeps the complete map with its fence and backing pin. Confirmed removal carries the detached borrower node and exact shared authority past the memory guard; node disposal precedes authority metadata and original charge release. Namespace cleanup uses that same pairing. Final object release drains remaining borrower nodes only after physical completion. Memory capability/namespace and mapping maps, wider containing contexts and aggregate metadata budgets remain separate qualification work.

Optional detail: Staged close and cross-subsystem cleanup

An owned staged-close request fences new operation leases while older leases drain. Pending poll returns the request owner without subsystem retirement; once ready, cleanup proceeds through the detached-root boundary. Dropping the request or exhausting its lease-drain waiting budget retains the closing root, tag, slot and charges. Later completion cannot reopen admission. The fence applies to operation leases, not all existing resource paths, and the waiting budget does not bound hardware rendezvous.

All existing borrowed-memory reply variants retain both namespace leases and a reply claim across IPC-unlocked invalidation. Returned authority remains hidden until publication. Explicit call/reply cancellation also owns both roots through unlocked loan cleanup. Bulk endpoint/domain IPC cleanup borrows its existing close owner and retains one complete cancellation at a time across unlocked loan revocation. Whole-domain device cleanup prepares its typed receipt under lifecycle, then releases local guards for device invalidation and cleanup. Deployment and node-shutdown supervisors retain a teardown owner across polls and refuse to report reclamation after a terminal error. They do not reclaim a root whose close failed or whose leases did not drain.

Detach and invalidate the final root.

Final user-root destruction now follows a separate two-phase boundary. Logical cleanup detaches the private hierarchy into an owner that leases its software slot. After lifecycle and table guards are released, that owner invalidates translations, destroys backing and completes the slot lease. ARM uses the owned hardware tag rather than looking up the detached software entry. A replacement cannot reuse the slot or tag before completion; failed or abandoned cleanup retains the hierarchy and its charges. This corrects the final root boundary, while earlier mapping, loan and device invalidations still need lock-safe retirement phases. Domain supervision must establish thread quiescence first.

Optional detail: Pending observations and close diagnostics

Namespace cancellation now rechecks the exact token after rejected preparation. A peer close may have consumed the selected token while IPC serialization was released. Confirmed absence permits rescan through the same closing owner; every still-present token or claim remains Pending. This check supplies no physical or whole-namespace completion proof, adds no busy-token retry and restarts no deadline. A deterministic control reproduces the earlier stale Pending result; its connection to the historical live timeout remains unproven. See `docs/reports/audits/2026-10-22-ipc-namespace-selection.md`.

Each closing owner keeps its last actual Pending observation inline: the checked preflight's root-lease count and stage, the selected IPC token/call and claim epoch, or the memory object's transfer/revocation flags and pin counts. The supervisor logs its captured root ID/generation, error and last observation on terminal failure, after local guards leave and before abandoning the owner. IPC selection precedes cancellation preparation and can become stale across an episode change. These diagnostics grant no cleanup or retry authority, and do not change the five-second policy. The earlier cancellation-stress reclamation timeout remains unresolved. See `docs/reports/audits/2026-10-22-root-retirement-diagnostics.md`.

Release backing and settle its charges.

Physical teardown makes heap, image and private-table charges nonrefundable before releasing any owned frame. Both architecture destructors attempt the bounded private-tree and data-frame cleanup; only complete success permits account refund. If one release fails, the whole charge remains consumed, even if other frames were returned. There is no automatic retry of a partially destroyed hierarchy. After proven translation quiescence, the software slot and hardware tag can be reused independently of these retained charges. Failed invalidation instead retains the complete root, tag and slot. Successful private-tree teardown excludes previously quarantined provisional table charges from its refund. Shared kernel charges are independent of that private teardown and remain consumed.

Optional detail: Heap and image preparation rollback

Heap and image preparation jointly own the provisional frame, its reservation and an exclusive borrow of the original address space. The caller retains the table guard through initialization, mapping and ownership transfer. Rollback refunds only after confirmed physical release. A rejected release continues to consume the original domain ceiling and node pool; successful root destruction excludes those quarantined pages from its refund. Slot reuse and platform promotion cannot recover or reclassify the retained charge. If publication is unconfirmed, cleanup retains backing without attempting deallocation. These are fixed account counters; recording a failure does not grow a recovery queue.

Optional detail: Translation-table preparation and capacity

Translation roots and intermediate tables also have an owning preparation through publication. Private lower-half tables preserve the physical progress floor on each allocation; shared higher-half kernel tables may consume that reserve. Mapping failure can leave a partial linked tree, which remains owned for retry or quiescent destruction. ARM allocates the root before acquiring a hardware tag, releasing the unpublished frame if tag admission fails. This preparation reserves private frames against the original root account and fresh shared kernel frames against a separate node pool before physical allocation. Private roots admit at most 1,024 table frames; their node pool uses one sixteenth of usable RAM with one quarter reserved from ordinary domains. Shared runtime tables use one sixty-fourth

Optional detail: Translation-table preparation and capacity (continued)

of usable RAM and retain their charges for the kernel lifetime. Copying shared links does not charge again, and user-root destruction cannot refund them. Rejected release and unconfirmed publication retain backing and admission. Inherited boot tables remain outside runtime admission. This does not resolve remaining lock-held invalidations or general metadata admission.

6.4 Four transfer modes

CharlotteOS defines four transfer modes. Transfer publishes capability authority; the receiver maps the delivered object separately. Queued attachments and unobserved returned objects stay inaccessible until receive/result observation. Moves and write loans require unmapped source backing. Read loans permit existing read-only mappings, but reject writable mappings. The owning runtime separates `OwnedMemory` from `MappedMemory` so normal callers unmap before moving or lending rather than relying on an implicit mapping change.

6.4.1 Copy

The receiver gets a byte-for-byte duplicate while the sender retains the unmodified original.

- **Use when:** the data is small, the sender needs to keep using it, or the receiver is not trusted with the original.
- **Kernel work:** allocate charged private frames, copy a protected source snapshot and publish a destination memory capability. The receiver maps its copy when needed.
- **Semantics:** simplest; both domains can read their respective copies independently.

The kernel performs the potentially large byte copy without holding the interrupt-masking memory-object or frame-allocator locks. Before releasing the registry lock it acquires a shared-read copy pin on the source object. That pin keeps the frames alive and rejects every tracked operation that could introduce a writer until the snapshot is complete. Rejected operations include a writable CPU mapping, an in-kernel write, a writable or exclusive DMA pin, a write lend, a move, and ownership rollback. Read-only mappings and DMA pins may coexist. If the source domain exits during the copy, destruction is deferred until both the copy-pin and DMA-pin counts reach zero; physical frames are freed only after the registry lock is released.

6.4.2 Move

Ownership transfers to the receiver. The source must already be unmapped; the sender's capability is consumed. The receiver becomes the new owner, responsible for subsequent transfer or destruction.

- **Use when:** the sender is finished with the data and wants to hand it off without copying.
- **Kernel work:** validate ownership and unmapped/unpinned state, reserve destination authority, escrow the source and commit the capability transfer with IPC publication.
- **Semantics:** physical pages stay in place. The sender's old capability cannot map them again; the receiver owns subsequent access.

6.4.3 BorrowRead

The receiver gets temporary read-only mapping authority. The sender retains ownership. Confirmed reply/cancellation cleanup revokes the loan, including any receiver mapping; failed cleanup retains its fence and backing.

- **Use when:** the receiver needs to inspect data but must not modify it.
- **Kernel work:** reserve exact destination authority and prepare a fallible borrower node before source escrow, outside the memory registry. Commit relinks the node and publishes the read-only capability. A later receiver mapping must be read-only.
- **Semantics:** writable aliases in the receiver are forbidden by the page-table permissions. The receiver cannot write even through unsafe code. Revocation at reply time unmaps the pages.

6.4.4 BorrowWrite

The receiver gets exclusive writable mapping authority while the sender retains ownership. The source must be unmapped before admission; the active loan rejects new lender access. Confirmed revocation ends that restriction. A reply or timeout without successful cleanup cannot restore access.

- **Use when:** the receiver needs to write into a buffer the sender will later read (e.g., a read-into-user-buffer pattern). This is *mutable lending*.
- **Kernel work:** validate unmapped, exclusive source state, publish borrower authority and retain the revocation contract. The receiver may map writable until confirmed cleanup revokes it.
- **Semantics:** the hardware enforces mutual exclusion. The sender cannot map the pages while they are lent out. Access through a revoked mapping faults even from unsafe Rust; a stale pointer grants no authority.

Borrowed-memory replies, including returned connections or memory, retain both namespace generations, the loan revocation receipts and an exclusive reply claim in one kernel operation owner. Loan detachment, TLB invalidation and scratch release then run without the global IPC lock. A concurrent close of the pending-call or reply capability waits outside that lock until cleanup finishes; it cannot release the caller's borrow early. Successful loans are recorded individually, so a later failure keeps only the remaining loans for cancellation. Only unstarted preparation may restore loan state: uncertain cleanup retains its backing pin and revocation fence. An abandoned reply retains its claim and both roots, with no forced reclamation. Returned connections keep their destination authority hidden until publication and retain the minting source through the reply claim. Source-close waits outside IPC as well. Queued connections and unobserved returned connections cannot serve as retained minting sources: an earlier operation can still reclaim them. Delivery or observation must precede the reply. An unrelated endpoint-owner domain may close, making the service unavailable, while the delegated source keeps the closed endpoint record alive. Failure refunds unpublished grants; abandonment retains the source claim and both roots.

Returned memory retains its source escrow, backing pin and hidden destination reservation in the same operation owner. The output must be owned and unmapped; queued or unobserved-result memory must first be delivered or observed. Memory close waits outside the registry for the transfer owner. Rollback restores source authority and releases its pin under one registry hold, so close never observes restored authority with an unfinished transfer pin. Serialized cleanup uses a nonwaiting busy check instead of parking beneath IPC. After input-loan cleanup, the output move and any returned connection publish jointly before result visibility. Ordinary failure restores the unstarted output move; abandonment can also restore that output, but retains uncertain input-loan backing and the reply/root claims. No-loan replies remain atomic under IPC.

Explicit close of a pending call or delivered reply composes both namespace leases, every loan receipt and an exclusive completion claim in a cancellation owner. A queued message stays in place while its loans are detached and invalidated outside IPC: receive reports Pending, and endpoint close waits outside the lock. Success records all revocations before consuming authority or notifying the caller. Failed cleanup leaves the capability live and reports no terminal result; untouched preparations roll back, while uncertain backing stays fenced. Abandonment retains the queue, claim and both roots. Endpoint readiness excludes claimed or failed queue fronts. Removing queued work re-signals receivers and their bound completion queue after unlocking, so later work can proceed. A failed request remains fenced from delivery/reply.

The runtime's explicit `PendingCall::close` returns its owner on error, preserving the Rust borrow. Drop and consuming waits cannot return an owner; if close fails, they abort the domain instead of ending a potentially unsafe borrow. The domain terminates, but that alone does not establish that resources can be reclaimed. Bulk endpoint/domain cleanup remains serialized. Its reply-token cleanup must retain failed loans without reporting them as completed; full bulk ownership and failure recovery remain work in progress.

6.5 Why hardware enforcement matters

Page tables enforce the transfer modes across protection domains:

- A C program running in a protection domain cannot violate the constraints any more than a Rust program can.
- A buffer overrun cannot read pages that are not mapped.
- An unsafe block cannot write to a `BorrowRead` buffer.
- A use-after-drop cannot resurrect a moved memory object.

Rust's ownership complements the kernel enforcement by catching errors within a domain at compile time. The kernel is the ultimate guarantor for cross-domain safety, so non-Rust or buggy-Rust processes are still contained by page tables and capability checks.

6.6 Control plane versus data plane

Endpoint IPC belongs to the **control plane**: it configures connections, carries opcodes, sets up device queues.

Memory objects belong to the **data plane**: they carry the actual bytes (packets, blocks, buffers, strings).

For networking specifically:

- Control plane: endpoint IPC configures NIC queues, sets MTU, registers buffer pools.
- Data plane: descriptor rings coordinate producer/consumer state; packet payloads move as memory objects.

This separation avoids turning every packet into a copied IPC payload while preserving strict ownership.

6.7 DMA as a third ownership dimension

When a device performs DMA, a memory object enters a third ownership state:

- CPU ownership: the CPU reads and writes the pages normally.
- DMA ownership: the device is reading or writing the pages; the CPU must not access them.
- Rust/API ownership: the domain holds the capability.

The AArch64 SMMUv3 and x86-64 VT-d/AMD-Vi paths track an explicit DMA pin per mapped memory object. The kernel validates access direction, installs only the object's frames in a device-private translation context, and releases the pin only after a synchronous IOTLB invalidation. Drivers receive IOVAs rather than physical addresses. CPU mappings are not automatically revoked at the raw syscall layer, so coherent descriptor rings remain an explicit driver protocol. Ordinary Rust applications should instead use `catten_rt::owned`: calling `unmap` on `MappedMemory` consumes the CPU mapping, and only the resulting `OwnedMemory` can create a `DmaTransfer`. The memory cannot be mapped or exposed as a Rust slice again until the transfer's `finish` method has synchronously removed the IOMMU mapping.

A failed DMA unmap retains the Rust owner. Only an explicit `OPERATION_IN_FLIGHT` admission rejection permits another submission; other failures retain the original status without repeating DMA unmap from `finish` or `Drop`. The attempt is recorded before kernel entry. For shared coherent memory, confirmed DMA completion is retained across a later CPU-unmap failure. Best-effort local teardown does not release uncertain kernel DMA pins or their backing charges.

Both DMA-map syscall forms return status, IOVA and a per-call diagnostic stage/cause. Backend rejection includes admission and started maintenance and does not prove rollback or authorize retry. A shared-DMA setup failure retains its existing CPU mapping in `FailedSharedDmaMemory`, which exposes no slices or pointers. Its consuming CPU-unmap operation cannot discharge an uncertain kernel DMA pin or authorize backing reuse.

6.8 Transfer guarantees and limits

1. Page transfer without payload copying: for aligned, page-backed objects, ownership can move by changing mappings rather than copying bytes. Whether this is faster depends on payload size and mapping/TLB costs.
2. Cross-domain stale access is constrained by mappings: when a memory object is moved, the sender's mappings are removed. Any later access through those mappings faults. When a borrow is revoked, the borrower's mappings are removed. This does not rule out bugs in unsafe code, page-table maintenance, or DMA.
3. Borrows have defined lifetimes: a borrow is always tied to an IPC call. When the call completes (reply, cancellation, or server death), the borrow ends. A wait timeout alone does not cancel the call or end its loan; explicit cancellation is needed before reusing the borrowed storage. There is no "I forgot to return it."
4. DMA ownership is tracked on the reference platforms: AArch64 SMMUv3 and x86-64 VT-d/AMD-Vi pin mapped memory and restrict each requester to its DMA domain. The ownership-aware Rust API prevents ordinary CPU mappings from overlapping a transfer; raw coherent-ring implementations remain responsible for volatile/atomic access and the device protocol.
5. Page tables enforce access. With correct MMU setup and TLB maintenance, unmapped CPU pages remain inaccessible even when a program uses unsafe code or C FFI, or contains a compiler bug. The implemented SMMUv3, VT-d, and AMD-Vi paths provide the corresponding DMA boundary for explicitly mapped objects.

7 Completion Queues and Non-Lossy Results

A completion queue (CQ) carries asynchronous kernel-operation results to userspace. Its central safety rule is that a full userspace ring must not silently discard a terminal result.

7.1 When to use a completion queue

Use submission/completion for operations handled by the **kernel or a hardware-facing mechanism**:

- Timer expiry.
- Thread-exit and endpoint-close observation.
- Driver IRQ readiness, followed by inspection of the device's own completion state (for example a disk or network used ring).
- Kernel worker completion and the prototype buffer read/write operations.

There is no general asynchronous page-operation API or CQ entry that by itself proves DMA quiescence.

Use endpoint IPC (Chapter 5) when one protection domain invokes another. Confusing these two paths leads to architectural mistakes: a service call is not a kernel operation, and a reply token is not a completion record.

7.2 The CQ ring: a shared-memory completion buffer

A completion queue is a **shared-memory ring buffer** between the kernel (producer) and userspace (consumer). A single 4 KiB page contains a header and a circular array of fixed-size entries.

Each entry is 32 bytes:

```
struct CompletionEntry {
    operation: u64,     // operation identifier (e.g., timer id)
    cookie: u64,        // opaque value set by the submitter
    status: u32,        // completion status code
    flags: u32,         // per-entry flags
    result: i64,        // operation result (e.g., bytes read)
}
```

The ring page is mapped read-write in userspace because the consumer advances its tail; the kernel accesses the same frame through its privileged mapping. The ABI assigns each side its own fields:

- Userspace drains entries without syscalls: advancing the consumer tail is a store to a shared page; reading entries is a load. No kernel crossing needed for the common fast path.
- The kernel publishes entries with a release fence: the consumer sees coherent data without additional synchronization.
- Overflow is detected and counted: an overflow counter in the header lets userspace detect when entries were produced faster than consumed.

7.3 The non-lossy invariant

> **A terminal operation result must never be silently lost because the userspace CQ ring is full.**

The implementation pre-allocates a kernel backlog and bounds accepted operations by submission admission. A retained detached result keeps its original slot until delivery; a capability-backed result remains tied to its live completion owner. Closing that owner may discard its redundant queued notification. Queue registration separately admits backlog bytes and any heap-backed ring. New submissions reject at capacity. A checked CQ wait reports readiness, deadline, or wait-admission failure; ring pressure is not a wait error.

Advancing the userspace tail alone does not run kernel backlog reconciliation. Completion production and kernel poll/wait paths refill the ring after space becomes available. Consumers must enter the checked wait/reconciliation path when the mapped ring is empty, rather than spin on it.

The overflow counter is pressure telemetry: it tells the consumer that it is falling behind.

In a critical system, a lost completion for a disk write or a timer expiry is a correctness bug with potentially severe consequences. CharlotteOS treats each completion as a datum that must be delivered at least once.

7.4 Per-shard CQ partitioning


Each address space owns a set of completion queues, keyed by `CqId`. Queue 0 is the default. For a service with multiple Sitas shards, **per-shard CQ rings** enable targeted wakes:

- Shard A's executor waits on CQ 0.
- Shard B's executor waits on CQ 1.
- A completion destined for Shard A is posted to CQ 0.
- Only Shard A's executor is woken; Shard B is undisturbed.

This prevents cross-shard completion stealing (a pathological behavior where one busy shard drains entries intended for another) and keeps wakeup latency proportional to the number of entries, independently of the number of shards.

7.5 Operation lifecycle

Every asynchronous operation transitions through a defined state machine:



Each transition is explicit and observable:

Created The operation descriptor exists in userspace but has not been submitted to the kernel.

Submitted `submit()` has been called. The kernel has the operation record but has not yet validated it.
Accepted / Rejected The kernel has validated the operation. It may be rejected immediately (invalid parameters, insufficient rights, queue full) with a synchronous error.
InFlight The operation is being processed. The kernel or device owns any associated buffers.
Completed / Failed / Cancelled A terminal state. The result is posted to the CQ. Buffer ownership returns to userspace.
ResultObserved The consumer has read the CQ entry.
ResourcesReclaimed The operation's capability-table slot has been freed (via `close`).

7.6 Checked waiting on a CQ

When a shard's executor has no ready tasks, it calls `checked CQ wait` on its assigned queue. The kernel blocks the calling thread until one of three things happens:

1. A completion entry is posted to the CQ.
2. An explicit `CQ_WAKE` arrives (from another shard or the kernel).
3. A deadline elapses (timeout variant: a finite checked wait).

The current syscall is 88, with timeout milliseconds, queue ID and an explicit finite/event-only flag. The safe runtime returns readiness or deadline expiry, or a distinct admission/invalid-request error. Syscalls 12/42 and their ignored entry-count threshold are retired. Rejection cannot advance a protocol clock or end a pending borrow; the caller retains the original operation and deadline.

For the owning reactor, the sequence closes the lost-wakeup window:

1. Capture the exact CQ list identity and compare its work generation with the reactor's last-seen generation; old ring occupancy is not readiness.
2. Register a waiter against the CQ's generation counter.
3. Recheck the captured generation after registration; readiness closes the lost-wakeup window without observing or discarding a result.
4. Park with the original deadline. Unrelated wakes recheck and repark; completion cancels unused source/watchdog interests and revalidates queue identity before advancing the seen generation.

This is the **single wait point** for the entire shard. Three event sources converge on it:

- Kernel completions (CQ entries from `submit` operations).
- Endpoint readiness (a coalesced wake when messages arrive on a bound endpoint).
- Device interrupts (a coalesced wake from a bound interrupt object).

The shard does not need separate wait operations for timers, IPC messages, and device events. One aggregated wait covers all of them.

7.7 LP affinity for CQ waits

A thread that blocks in `checked CQ wait` is assigned an affinity LP. When woken, the scheduler returns it to the same LP rather than scanning for the least-loaded one. This has three benefits:

1. Timer events stay on the same LP's queue, eliminating cross-LP migration races (observer-not-found when a completion is posted on a different LP than the one where the waiter was registered).
2. Cache warmth is preserved: the waking thread finds its data in the LP's local caches.
3. Shard-to-LP affinity is maintained: the Sitas shard that blocked on CQ 0 on LP 2 wakes up on LP 2, where its shard-local state lives.

7.8 Operation IDs versus per-operation capabilities

An earlier experimental design returned a `CompletionCap` for every submission. The final ABI uses **operation IDs** for the common path:

- `submit()` returns an `OperationId` (a lightweight identifier).
- The result arrives in the CQ with the same operation ID.
- No capability-table slot is consumed for common operations.
- A first-class operation capability is created only when independent waiting, cancellation, delegation, inspection, or policy requires it.

This avoids capability-table pressure for high-rate operations (timer events, network packet completions) while preserving the capability model for operations that need first-class authority.

Optional detail: Boot-wide operation identities

Operation identities use one checked counter for the lifetime of a boot, shared by capability-backed and detached submissions. It issues values from one through `u64::MAX - 1`; zero and the syscall submission-failure sentinel `u64::MAX` are excluded. Exhaustion permanently rejects new submissions with the existing `WouldBlock`/submission-failure result before reserving record, watch, timer or capability resources. Existing operations remain usable. Failed preparation never refunds an identity, and namespace replacement never resets the counter. Admission failure therefore does not promise retry progress.

7.9 Completion-record admission

A completion record follows four stages: reserve capacity, prepare private state, publish into the captured namespace, and retain that state until it can be released. Timers add a separate lifetime because cancellation can outlast the operation. The following subsections follow that sequence.

7.9.1 Reserve capacity

Capability-backed and detached operations share the namespace's submission-slot limit. A separate record budget also counts retained state, so a completed or closed operation can still occupy admission while its storage remains live.

Optional detail: Record limits and platform reserve

Capability-backed and detached operations share a namespace's configured submission-slot limit. A separate record budget counts retained state: at most the smaller of that capacity and 1,024 records per namespace, and 8,192 per node. Ordinary domains share 6,144 records; kernel-designated platform domains may use the remaining pool. The service loader currently configures 16 slots.

Observer entries have separate admission, but general weak-only Arc/control-block allocations and the entire kernel heap still require broader accounting. Timer events have their own charges because deferred cancellation can outlive the operation record.

7.9.2 Prepare the complete operation

Preparation keeps the buffer, identity and reservations together through each fallible step. Rejection must leave a complete owner that can dispose of the unused state after local guards have been released.

Optional detail: Record and submission preparation

The containing capability-submission owner now captures the original buffer and target before operation-ID and record/watch admission too. Early watch rejection retains its assigned operation and original record charge with that buffer. Record factories borrow the complete transaction; successful transfer enters the complete-record helper before its first fallible phase. Ordinary pre-record rollback disposes buffer before reservation refund. Captured, record-admitted and watch-admitted abandonment retains every field and original account without cleanup, including across namespace replacement. Public ID exhaustion, hidden authority and publication revalidation remain unchanged; target capture, timer/observer factories and wider containing contexts remain separate qualification work.

Completion record preparation captures its original buffer, operation ID and reservation before shared holder and waiter-list allocation. Holder preparation borrows the reservation; rejected allocation retains it with the original buffer. List allocation receives only captured classification. Ordinary rejection disposes buffer and unused list before either installed or uninstalled admission; abandonment at all three phases retains every field without cleanup. Success transfers the same buffer and identity into the shared Arc helper. Published completion destruction, outer factories and broader guard/IRQ contexts remain separate; no physical receipt, retry owner or registry is added.

Optional detail: Observer and callback preparation

Shared observer-entry preparation now retains its exact weak observer and original waiter/watch charge outside empty Box allocation. The allocator owns no payload; rejection cancels explicitly after callback return, freeing empty backing and weak reference before admission. Private initialization consumes that same storage once without allocation or disposal. Both partial phase fallbacks retain every field without cleanup. This is no registered waiter, readiness, physical proof or retry owner. Active linked-entry/token/source disposal, other containing owners and broader guards/IRQ contexts remain separate.

Completion callback preparation now captures its exact record/account/source and weak observer before watch/list/entry admission in one inert containing owner. Entry factories borrow that owner. Ordinary allocation/publication errors and successful or ready publication explicitly dispose transient fields after local guards, releasing the exact target last; ready notification follows unused disposal. All four phase fallbacks retain complete fields, including the original buffered record and charges across

Optional detail: Observer and callback preparation (continued)

namespace replacement. Published observation/token/source destruction and wider caller contexts remain separate; this creates no physical root lease, quiescence proof or recovery interface.

7.9.3 Publish into the captured namespace

Publication rechecks the exact namespace and queue captured during preparation. Prepared storage is linked into place under serialization. A reused numeric identifier does not make a replacement namespace or queue the original target.

Optional detail: Capability-backed publication

Capability-backed completion submission prepares records, waiter lists, optional watch admission and shared authority storage outside the completion registry. Hidden authority admission and final joint publication each revalidate the exact namespace and original accounts under serialization. Timer node and producer preparation also leave that guard. Ordinary rejection retains the complete owner until explicit post-guard disposal; abandonment retains every field. Capability timers capture one absolute deadline before preparation and preserve it through publication and enqueue. Namespace teardown can cancel a prepared node before insertion, retaining its event charge until actual disposal. Capability payload nodes now prepare in that same transaction before hidden authority reservation. Publication relinks them without allocation after the authority batch. Logical close, abort and event rollback retain detached payload and authority in the same node until post-registry disposal. A charged completion Arc survives both node releases; final strong/weak backing still determines record admission. Shared authority release also retains its charge until its node is actually freed. Namespace close drains those complete nodes; abandonment retains all fields. All three individual withdrawal paths remove the exact retained CQ row before returning its slot, including full-ring terminal abort. Global namespace/account admission and wider timer/observer/caller contexts remain open; no physical completion or replay proof is added.

Optional detail: Detached submission and record storage

Detached plain/timer submissions capture exact namespace root, record/event accounts, trusted classification, capacity and CQ source before preparation. Record/event admission and timer node/observer allocation run outside the completion registry. Borrowed publication rechecks that capture and retirement; a replaced queue rejects even if its numeric ID still exists. Rejected owners retain their fields through unlock for unstarted rollback, with no public retry owner. Accepted nodes enqueue exactly once afterward; teardown in between flags the retained event and keeps its charge until cancelled insertion is discarded. Map/authority metadata, backlog reconciliation, capability-backed construction and outer caller/IRQ contexts remain separate. Captured identity is no physical pin or cleanup receipt.

Detached-record metadata uses the shared admitted map: fallible node storage is prepared outside the completion registry, then relinked after exact namespace and CQ validation. Terminal removal transfers its owning node to the direct receipt or backlog. Explicit namespace close drains all remaining nodes after local unlock. Namespace, detached-preparation and terminal-receipt abandonment retain their complete fields, accounts and sources; ordinary rejection uses an explicit unstarted finish. Global namespace/account admission and wider caller contexts remain open. None of these owners is a physical completion receipt or permission to replay accepted work.

7.9.4 Retain charges through delivery and teardown

A completion retains its charge while a kernel waiter or callback holds a strong reference, even after capability closure or domain teardown. A detached operation moves its charge into the CQ backlog until its result reaches the ring or is discarded during teardown. A fresh generation receives a fresh budget owner; old releases cannot credit a replacement. Closing a captured object also verifies its identity under the registry lock before revocation.

Putting a result in the CQ and releasing the operation's remaining storage are separate steps. A failed ring write keeps the backlog entry and its charge; a delivered result can still leave timer or observer state to be disposed of.

Optional detail: Backlog publication and refunds

Backlog-to-ring publication retains delivered detached-record charges in a fixed two-class owning batch until the completion registry is unlocked. Ordinary/platform charges retain their original accounts; no disposal storage is allocated. Full FIFO flushing and logical slot updates remain serialized. The same admitted detached nodes relink into the shared retirement list and free after local unlock, before either accounting class refunds. Checked batch refunds finish before CQ parking or producer notification; failed ring writes retain the complete backlog entry. Registry-map metadata and broader outer-context qualification remain separate work.

Optional detail: Detached terminal delivery

Detached terminal publication returns the complete remaining timer-bearing record beyond registry unlock before destroying its observer/cancellation fields. Direct-ring delivery leaves the original record charge with that owner; only actual backlog retention transfers it into the retained entry. Notification then uses the exact published CQ source, even if the queue was replaced during the intervening phase. A firing timer still owns its event/node and producer reference during notification, retaining separate event admission until queue processing finishes. Map removal, backlog draining, construction and outer queue/IRQ contexts remain separate. This is logical terminal disposal, not a physical cleanup receipt or a retry owner.

7.9.5 Manage the timer lifetime separately

Cancelling an operation does not prove that its timer payload has been released. Timer preparation, queue removal and delivery therefore carry their own owners and charges. Exact retained object identity distinguishes a timer from any successor; a matching deadline or LP is insufficient.

Optional detail: Cancellation identity and address reuse

Timer cancellation borrows the handle's retained state allocation and removes only a queue entry with that exact object identity. No private numeric cancellation counter remains. Retained strong ownership prevents address reuse during lookup; equal LP, deadline or cancellation flags grant no authority over a successor. Weak-only backing remains charged to its original sponsor. This adds no admission failure and is separate from public operation IDs.

Optional detail: Event and shared-charge preparation

Timer event preparation now retains its original source/callback before reservation, its uninstalled charge through holder allocation, and installed admission through cancellation-state allocation. Rejection explicitly disposes the original payload before uninstalled admission; completion transfers the same event into raw-event or node ownership without changing deadline policy.

Shared charge-holder preparation allocates empty Arc storage without handing the allocator an owning charge. Private initialization occurs once; owning rejection cancels after callback return, while parent-borrowed rejection retains the original reservation for ordered payload disposal. Phase abandonment is inert and retains every field. The same primitive serves records, timers and observer lists, preserving layout, one-allocation allowance and strong/weak accounting.

Shared payload preparation now also retains the complete value and original admission outside empty Arc allocation. The allocator owns no payload; private initialization consumes the same storage once, ordinary rejection disposes payload before backing and admission after callback return, and phase abandonment retains every field without heap work. Published Arc/Weak finalization, completed raw-event destruction, outer payload factories and wider containing contexts remain separate work; no physical proof, retry/custody or new registry is added.

Optional detail: Private timer nodes and unused preparation

Timer node construction captures its already charged event/source/callback and outside admission before allocating empty uninitialized Box storage. The allocator receives no payload; rejection leaves it with the same inert owner until explicit cancellation after callback return. Successful storage initializes once into completed private ownership without allocation or deadline changes. Unused empty backing frees before event/source disposal and outside admission; abandonment at either phase retains every field and original charge. The node layout and single allocation stay unchanged. This creates no queue publication, physical proof, retry interface or custody registry. Completed raw-event destruction, payload assembly before the shared helper and broader caller contexts remain separate.

Completed unpublished timer nodes have the same inert ownership policy: enqueue consumes the complete preparation, and ordinary unused preparation consumes `cancel_unpublished` after local publication/registry guards leave. Scheduler sleep prepares admission and node storage before its local publication mask; timed-wait rejection/expired preparation and both completion submission families explicitly dispose unused nodes. Caller-owned masks remain intact. Abandonment retains node, cancellation backing, callback/source and original charge without cleanup. Final strong/weak cancellation references can outlive explicit node disposal. Completed raw-event destruction, waiter preparation and broader IRQ/outer contexts remain separate work; no queue cancellation, physical proof, recovery custody or replay authority is created by private-node disposal.

Optional detail: Queue removal and cancellation handback

Queue filtering, cancelled-event purging, expiry and rejected enqueue now detach complete event nodes into an owning retirement batch without allocation or destruction under the local queue borrow. Duplicate/removed keyed events move into its one inline slot. Callers release the queue before explicit, iterative disposal; abandoned receipts or queue storage retain all remaining nodes, sources, callback references and original charges. This supplies no physical completion, root-quiescence or replay proof.

Cancellation likewise returns one complete must-use handback containing the exact handle and any removed node/source. Queue mutation and comparator updates finish before return; callers retain

Optional detail: Queue removal and cancellation handback (continued)

that owner through enclosing queue/registry guards and explicitly finish afterward. Finish disposes payloads before releasing the handle. Its Boolean records only queue removal, including false for selected, unpublished, stale, busy or remote cases.

The bare handle has inert abandonment and explicit reference-only release; abandonment does not fabricate cancellation. Complete-handback abandonment retains every field and original charge. No new allocation, admission, registry, physical proof or replay authority is added. Raw Arc/Weak finalization and wider caller/destructor contexts remain separate qualification work.

Optional detail: Expiry selection and delivery

Processing captures its already-due prefix against one monotonic cutoff, preserving anonymous FIFO and quantum-first ties. A complete local delivery owner retains selected and purged payloads after queue unlock; callbacks, waiter notifications, temporary observer destruction and payload disposal then run on the original LP with IRQs masked. One inline queue claim prevents nested drains. Callback enqueue and newly due deadlines wait for the next pass; comparator reconciliation occurs before delivery and against current state at handback. Shared cancellation is rechecked before each signal starts; selected queue absence and a false queue-removal result are not completion or replay permission. Fired diagnostics describe expiry selection, not notification proof. Abandonment retains every field and leaves the claim fenced. The delivery owner cannot be sent/shared across LPs; runtime checks also enforce LP and IRQ policy. No allocation, extra reservation or new registry is introduced. IRQ execution, unrelated outer guards, completed raw-event destruction, raw cancellation references and arbitrary blocking callbacks remain separate qualification work.

7.10 Completion-queue admission

Queue admission covers both the registered queue and its kernel-owned backing. The normal path prepares both before publication. Replacement adds a second requirement: enough temporary capacity for the old queue and its candidate to coexist.

7.10.1 Prepare and publish a queue

Preparation reserves a queue registration and its kernel-owned backing before publication. The pages of a physical ring remain owned by their address-space mappings. If CQ preparation fails during domain loading, the loader tears down the partially mapped domain and any queues already installed.

7.10.2 Replace an existing queue

Preparation is fallible and precedes publication. Replacement must admit both old and staged backing; failure preserves the original queue and its pending results. Physical-ring initialization follows admission and allocation, and a frame already registered to another queue is rejected. Reusing the same queue's frame requires a quiescent consumer. Successful replacement discards undelivered results rather than migrating them.

Optional detail: Queue limits and backing layout

Queue preparation reserves a registration count and kernel-owned backing bytes. Each namespace may register 32 queues with at most 256 KiB of backing; node limits are 2,048 queues and 4 MiB. Ordinary domains share 1,536 queues and 3 MiB, leaving a reserve for kernel-designated platform domains. Backlogs are pre-allocated from the namespace's submission capacity, clamped to 1,024 and rounded with checked arithmetic. Heap rings use aligned 4 KiB backing. Physical rings remain owned by their address-space mappings; their pages are outside this heap-byte budget.

Optional detail: Loader rollback and platform classification

An owning loader guard tears down the partially mapped domain if a CQ cannot be prepared, including any queues already installed. Trusted ambient supervisor paths designate platform domains before preparation; scoped and syscall preparation use ordinary admission. General page allocation, observer storage and kernel metadata still require further admission and fallible cleanup.

Optional detail: Prepared queue storage and publication

CQ map-node, source-list, backlog and heap-ring admission/allocation run outside the completion registry, including partial-error disposal. Preparation retains the exact namespace root, CQ account, submission capacity and trusted classification; publication rechecks identity and retirement. Physical frames remain untouched until alias checks and initialization under the same registry hold as queue publication. Rejection retains prepared backing and original charges until unlock. Whole-namespace preparation includes its fallibly prepared CQ map node. Fresh queue publication relinks admitted storage without allocation. Replacement detaches the complete old node and payload into one retaining owner; explicit finish frees the node before payload destruction and original charge refund. Namespace disposal explicitly drains these owners too. Unpublished and retired queue abandonment retains every field without cleanup. The registration count covers the one prepared node; backing-byte admission still counts ring/backlog storage, not aggregate metadata bytes.

Optional detail: Namespace storage and default-queue setup

Global namespace metadata also uses the shared admitted map. One preparation retains its fallibly allocated node and four original accounts with the private namespace/default queue before registry access. Captured retirement and physical alias validation precede initialization; no later admission can reject a physical-ring publication. Close/replacement detaches the complete node and payload without freeing metadata under the registry. Explicit finish frees that global node before payload/source/account disposal; unpublished and retired fallback retains every field. Runtime CQ setup returns typed allocation errors; mandatory bare kernel/demo/fixture setup shares the same preparation through a panic wrapper. This adds no separate aggregate count/byte budget for global namespace/account storage, including empty namespaces. Sorted global lookups are linear in live namespaces; no new scan ceiling is claimed. Wider timer/observer disposal and outer caller/IRQ contexts remain separate. A captured identity supplies no physical pin or permission to retry accepted work; frame owners must quiesce consumers.

7.11 Owning endpoint-close and thread-exit registrations

Lifecycle watches observe a source's end without taking ownership of that source. Endpoint and external thread watches can be cancelled independently. Worker-backed completions have a stronger obligation:

retain the producer until it exits.

7.11.1 Watch an endpoint close

An endpoint-close watch owns a one-shot callback and a removable registration. Dropping its completion cancels locally without closing the source endpoint or waiting for endpoint death. Message arrival remains a readiness event and does not complete a lifecycle watch.

Optional detail: Close-watch capacity and notification disposal

Each endpoint accepts at most 128 close registrations across callers. The submitting completion namespace may retain its configured capacity, clamped to 1,024 entries; node admission is 8,192 with an ordinary share of 6,144. Entries are individually allocated fallibly, with no retained vector capacity, and keep their original generation's charge until actually released. Registration failure rolls back the unpublished completion through one owning guard.

Endpoint close detaches notifications without allocation. Callbacks run after the IPC and list locks are released; token destruction enters only the independent list lock. A detached entry retains its charge even if its token is cancelled before notification. Late callbacks cannot change a cancelled terminal result or complete a replacement with the same numeric capability. List destruction is iterative to bound kernel-stack use.

7.11.2 Watch an external thread exit

External thread-exit watches share the namespace and node registration pools with endpoint-close watches. Each target thread accepts at most 128 entries. Cancelling such a watch removes only the subscription; the target remains alive. Lookup, generation checking and insertion are serialized with thread retirement. An absent or stale target completes immediately, while admission failure rolls back the unpublished completion and reports failure rather than pretending that the thread exited. Reaping invokes callbacks outside observer and master-table locks, before releasing the thread's stack.

Optional detail: Thread-exit watch preparation

Thread-exit preparation captures its original candidate list, weak observer and already-admitted watch charge in one inert owner before list/entry allocation. The scheduler preparation hook borrows that owner. Ordinary allocation and publication outcomes finish explicitly after local guards, with candidate source release last; all four phase fallbacks retain every field. Published token/source and active linked-entry destruction, initial capture/admission and wider caller contexts remain separate. A retained list grants no target-thread/root lease, physical quiescence proof or recovery authority.

7.11.3 Retain a completion worker until exit

Worker-backed completions bind their callback and registration to the fresh thread before publication and execution. Cancellation remains pending until that worker actually exits; this preserves producer lifetime instead of treating work as a removable observation. Terminal completion and namespace teardown release the registration. Installing a late observer is fenced against exact completion-object replacement, including when a kernel owner retains the old object. Kernel thread construction and general control-block allocation still need broader admission and fallible cleanup.

7.11.4 Kernel completion callbacks

Non-scheduler completion callbacks return an owning registration token and share the event-watch account, with at most 128 entries per completion. Cancelling the token removes only the subscription: it neither terminates the producer nor releases the operation's buffer. Asynchronous callers holding an existing completion reference use exact-object registration to reject a replacement with the same numeric address-space and capability identifiers.

Terminal checking and insertion share the operation's state lock. A callback registered after completion or result consumption is invoked immediately, outside registry/source guards and without retaining an entry. Otherwise, notification follows CQ publication. Entries remain charged while detached and are released before their callbacks run. Teardown and unpublished-record rollback discard entries even when an old completion or token remains retained. Lists allocate fallibly on first subscription. Empty control blocks and arbitrary callback capture sizes remain outside these entry counters.

Optional detail: Terminal subscription transitions

Event and worker subscriptions detached by terminal completion stay in one transition owner through terminal-state and CQ-result publication. Disposal follows both local registry and state unlock, before notification. The exact CQ source is captured at publication: a reentrant destructor replacing the queue cannot redirect the old wake to its successor. Installation returns replaced or rejected subscriptions for disposal after both guards. Cancellation rejects a late event watch but retains the worker-exit subscription; terminal installation retains neither. Timer cancellation, record/authority/map metadata and outer producer/IRQ contexts remain separate qualification work. These subscription transitions grant no physical cleanup proof or permission to replay accepted work.

7.12 Owned completion and CQ waiters

Waiting has three steps: admit a registration, publish the blocked state while closing the lost-wake window, then cancel the registration when the wait ends. Admission rejection is a waiting outcome; it does not finish the operation.

7.12.1 Admit before parking

Completion and CQ scheduler waiters use fallible registration before a thread is removed from its Ready queue or published as Blocked. Rejection preserves its state, queue membership and migration constraints; an already-ready source does not park it. Each source links at most 64 registrations, each waiting domain generation 1,024, and the node 8,192 with an ordinary share of 6,144. The waiting domain sponsors the entry independently of the source's owner. These are kernel policy limits, separate from records, close watches, timers and CQ backing.

7.12.2 Keep the registration with the waiter

The Waker owns the registration. Ready admission cancels it even if a competing watchdog wins and another strong Waker survives; reaping a Blocked thread also cancels it. Detached notification storage remains charged until actually freed. Token destruction enters only the independent list lock. Notifications run after source locks are released, and CQ notification lists can be drained and rearmed without growing

an unbounded observer queue. Retirement closes the generation's sponsor, while late cleanup cannot credit a replacement ASID.

Endpoint-readiness and pending-call waiters share these admission pools and owning cancellation, as described in Chapter 5. Untimed IPC waits also retry under pressure rather than returning while a server still holds a live loan. IPC source callbacks run after its registry is released.

7.12.3 Distinguish waiting failure from operation completion

A timed completion wait reports `WAIT_ADMISSION_FAILED` when parking is rejected, retaining the operation and its Rust owner for retry or safe Drop. The untimed completion-wait ABI instead yields cooperatively and retries until terminal completion, preserving borrowed-buffer safety. This overload fallback does not guarantee efficient idle waiting or producer progress. CQ waits retain their existing return shape and can return without parking when admission fails.

7.12.4 Close the lost-wake window

Timed parking publishes the blocked state and its watchdog under one local interrupt mask, then rechecks the condition. The mask preserves the caller's entry interrupt state and ends before yielding.

Optional detail: Timed-wait publication ordering

Timed waits mask local interrupts across Blocked publication, watchdog enqueue and the condition recheck. Without that interval, a quantum interrupt could switch out the waiter before its deadline wake exists. An owning local mask restores the entry interrupt state on rejection and is dropped before yielding; it holds no lock across a context switch. Watchdog storage still needs admission.

Optional detail: Waiter-source and entry preparation

Lazy waiter-source initialization retains original sponsor, weak observer, candidate, first published winner and shared waiter child in one inert owner. Losing candidate disposal remains after the slot guard and before entry admission. Ordinary results finish explicitly; all six handoff-stage fallbacks retain every field. Published tokens retain their independent entry authority. Inner list construction, active source/token/batch destruction and wider caller contexts remain separate; metadata ownership supplies no physical proof or root lease.

Completed private observer-entry preparation retains its complete entry on abandonment. Direct registration and callback/exit-watch/waiter containing owners consume explicit child finish after local guards. Publication transfers the same entry once, so finishing an emptied preparation cannot refund it. Ordinary private disposal keeps weak/node-before-charge order. Active linked entry, token/source/batch destruction and broader contexts remain separate; this is terminal retention, not physical proof or recovery custody.

Shared waiter preparation captures its exact source, original sponsor and weak observer before admission in one inert owner. Entry factories borrow it, and ordinary preparation/publication outcomes finish explicitly after local guards. Transient entry/admission disposal precedes source release, with sponsor last. All three phase fallbacks retain complete fields through source closure and sponsor retirement. Published token/source/batch destruction, active linked entries, initial source acquisition and wider caller contexts remain separate. These metadata owners supply no thread/root lease or physical quiescence proof.

7.12.5 Apply the same rule to other scheduler sources

Kernel blocking locks and scheduler timers also use admitted registrations. Rejected registration leaves the thread runnable; it must preserve the resource owner while following that wait family's retry policy.

Optional detail: Blocking mutex and read/write-lock waiters

Kernel scheduler-blocking mutex and read/write-lock waiters also share these budgets. Each mutex source and each reader/writer source links at most 64 entries. Uncontended acquisition allocates nothing; first contention prepares the list fallibly. Rejected admission leaves the thread runnable to yield and retry. Local interrupt masking spans park and the lost-wake recheck, then ends before yield; an unlock preceding list insertion must not strand a preempted caller. Unlock releases ownership and detaches all candidates before callbacks; the final reader releases an RwLock's writer waiters. Notifications do not reserve ownership, and broadcast does not guarantee fairness or writer priority. The blocking family is currently used only by kernel tests; existing registry/allocator spin locks are unchanged.

Optional detail: Scheduler timers and preemption storage

Scheduler timer observers also use owning admission. Non-scheduler producers install one callback in an embedded slot rather than an unbounded weak queue. Rejected sleep admission leaves the caller runnable to yield until its counter deadline, preserving the requested interval without queuing an event. Sleep/watchdog events have separate generation-owned admission: 1,024 per generation, sharing the 8,192-event node pool and its 6,144 ordinary share with completion timers. Each has its own domain account. Cancellation state, watchdog callback and fixed-size queue node preparation precede parking. Queue insertion allocates nothing; anonymous nodes form a sorted owning list with iterative reclamation. The quantum/idle-wake event has one inline queue slot per LP, outside anonymous admission. Rejection therefore cannot consume scheduler preemption storage. Charges remain until the actual event/node backing and cancellation references are released, including an aborted sleeper awaiting its deadline and detached retirement batches.

Every scheduler Observable source now requires fallible owning registration; there is no weak-only default. Steady-state publication and self-test results use the same bounded waiter source, with notification outside source guards and no stale-entry pruning after timeout. Non-scheduler completion callbacks have separate event-watch sponsorship. General weak-only/control-block backing and kernel heap accounting remain incomplete. CQ replacement still requires a quiescent consumer; discarding registrations is not live reactor migration. Silently rejecting an old void registration would lose a blocked thread's wake source.

7.13 Cancellation and buffer ownership

When a userspace task drops a completion handle or explicitly cancels an in-flight operation:

1. The kernel marks the operation as `Cancelling` but **retains any transferred buffer** since the buffer may still be the target of DMA or kernel access.
2. A terminal `Cancelled` completion is eventually posted to the CQ, returning buffer ownership to userspace.
3. On domain teardown (process exit), outstanding buffers may be leaked rather than freed while the kernel or a device may still touch them. Reclamation goes through explicit operation and device teardown.

Under this contract, a buffer is retained while the kernel or device may still reach it. The safe Rust wrapper consumes the owned value on submission and returns it on terminal completion.

7.14 Reliability and latency consequences

1. Non-lossy completions are a correctness requirement: a disk-write confirmation, a timer expiry, or a sensor reading is a fact and losing it is a bug. The backlog retains terminal results when the ring is full.
2. The single aggregated wait eliminates a class of race conditions: a shard that must wait on "timer or IPC message or device interrupt" in a conventional OS must manage three separate wait objects, with potential lost-wake races between checking one and arming another. One CQ means one atomic check-and-arm sequence.
3. Per-shard CQ rings enable predictable latency: no shard wakes another shard's executor to deliver a completion. Wakes are targeted, bounded, and proportional to the actual work.
4. Reading mapped CQ entries needs no syscall. Observing a particular operation's result or returned resources can still require its typed poll/wait API. An empty ring needs kernel reconciliation before parking; it does not prove that no retained backlog exists.
5. Cancellation has explicit states. These determine when the caller can reclaim the buffer. Uncertain cancellation must retain ownership; a timeout alone cannot end the borrow. We can test those transitions.

Part III

The Execution Discipline

8 Shards and Logical Processors

CharlotteOS separates the hardware execution context (logical processor, or LP) from the userspace ownership domain (shard).

8.1 The logical processor (LP): the hardware unit of scheduling

An LP is CharlotteOS' representation of a schedulable hardware execution context. In most configurations, one LP equals one CPU core (or one hyperthread). The kernel shards its own state per-LP, meaning each LP has:

- Its own run queue of ready threads.
- Its own timer queue and quantum timer.
- Its own scheduler instance (e.g., `RoundRobin`).
- Its own IPI command queues for receiving work from other LPs.
- Per-LP data structures accessible through `PerLp<T>`.

An LP is a **place**: threads are pinned to an LP at creation and, by default, stay there. Migration is opt-in and restricted.

Affinity makes a deliberate locality choice possibly, without actually establishing a NUMA allocation policy. Page-table memory can be remote even when the data it translates is local. Mitosis and Hydra study the benefits and coherence costs of page-table migration and replication. Charlotte retains its existing affinity policy while treating translation metadata as a separate accounting and future placement concern. The present physical allocator is not NUMA-aware, and x86-64 has no PCID policy: CR3 reloads flush non-global translations. Affinity alone therefore does not promise that translations remain cached across context switches.


8.2 The shard: the userspace unit of ownership

A shard is a userspace ownership and execution domain. The rules of the shard are the Sitas discipline:

1. Only the owning shard mutates shard-local state: *we don't need locking of shard-local data* because there is no concurrent access. The executor runs one task at a time on the shard.
2. Cross-shard interaction goes through bounded typed messages: a value that moves from shard A to shard B is sent through a typed channel (`ShardSender<M>`), where the sender loses the value and the receiver gains it.
3. Placement is explicit: code that needs to be shard-local is accessed through `ShardLocal<T>`, which verifies at runtime that the calling thread belongs to the owning LP.
4. Observability returns owned snapshots: diagnostics and introspection capture state by value. No borrowed reference into shard internals escapes the shard.

8.3 The usual mapping: one shard ↔ one LP

In the typical configuration:



The userspace thread and its executor are pinned to one LP. `ShardLocal<T>` state is valid only while that LP's owning thread runs.

The architecture retains the distinction (shard $\neq$ LP) so that more complex configurations remain possible:

- Multiple sharded processes: one LP might host shards from multiple protection domains, time-sliced by the kernel scheduler.
- CPU hotplug: an LP can be taken offline; its shards can be migrated (when migration-safe) or torn down.
- Oversubscription: a test can run N shards on $M < N$ LPs to exercise migration and scheduling paths.

CPU hotplug or live shard migration is not (yet) implemented and belongs at best among the extension scenarios. Current local Ready-thread migration requires explicit certification and architecture CPU-ownership qualification. Arm has the assembly handoff; x86 permits only never-dispatched contexts until an equivalent handoff exists. Pinned userspace shards remain ineligible.

Ready membership uses fixed links in each complete thread payload rather than a growable per-LP ring. Under the existing LP-pair and thread-table guards, migration validates the exact source and destination before changing either queue, then publishes state and affinity without allocation. Owner-LP abort unlinks before detaching the thread; linked owners cannot release their stack. This does not complete general thread-table, waiter/timer or kernel-heap admission. See `docs/reference/scheduler-run-queues.md`.

Scheduler waits capture their exact thread generation, state and sponsor before preparing waker/source storage outside local LP and thread-table guards. Publication revalidates that capture before changing queue membership. Each waker remembers early notifications and later callbacks match the installed wait itself; an older wait cannot wake a new park on the same thread. Ready admission carries the old subscription past guard exit before cancellation. Callers retain their existing IRQ policy, condition rechecks and absolute deadlines. Lazy list allocation leaves its source initialization mutex; IPC/CQ entries prepare outside their registries and revalidate the exact retained source before readiness and allocation-free publication. Losing or rejected storage stays owned until post-guard disposal. Source teardown, other observer allocation and wider outer-guard contexts remain qualification work. See `docs/reference/scheduler-waiter-budgets.md`.

Non-scheduler completion callbacks likewise capture their original record and watch account before allocation outside registry/inner guards. Publication revalidates that target and terminal state; immediate callbacks run after unused preparation is disposed. Successful completion-namespace/CQ replacement carries its entire detached payload past registry unlock before destruction. These local boundaries do not establish root/consumer quiescence or qualify every staging, producer-disposal or outer IRQ context. See `docs/reference/completion-callback-budgets.md`.

8.4 PerLp<T>: interrupt-safe shared data

For kernel data that must be accessible from multiple LPs (including from interrupt context), CharlotteOS uses `PerLp<T>`: a boxed slice of per-LP cells, each wrapped in a lock. Access is:

```
{
    let mut lp_data = per_lp_data.get_mut();
    lp_data.do_something();
} // Release the guard before blocking or yielding.
```

`get` returns a read guard and `get_mut` a write guard for the current LP. The guard retains the lock until scope exit. This is interrupt-safe (the lock masks interrupts during the critical section where necessary).

Use `PerLp<T>` for data that is:

- Accessed from interrupt handlers (timers, device IRQs).
- Modified by an IPI from another LP.
- Part of the scheduler, memory allocator, or other kernel subsystem that must be LP-safe.

8.5 ShardLocal<T>: lock-free single-owner data

For kernel data that is accessed only from one LP and never from interrupt context, CharlotteOS provides `ShardLocal<T>`: a lock-free per-LP container using `UnsafeCell<T>` with runtime owner-check and borrow-flag guard. Access is:

```
shard_local.with(|val| { *val = 42; });
```

The `with` closure:

1. Checks that the calling thread belongs to the owning LP (panics if not).
2. Checks that the borrow flag is clear (panics on re-entrant access).
3. Sets the borrow flag.
4. Calls the closure with `&mut T`.
5. Clears the borrow flag.

The closure must not:

- Store the `&mut T` reference anywhere (it must not escape).
- Send it to another thread or LP.
- Cross an `.await` point.

A scoped `BorrowGuard` clears the flag on ordinary return and on unwind where unwinding is enabled. The kernel's aborting panic policy does not promise normal scope cleanup after a panic. This mechanism is a re-entrancy check, not a poisoned-state recovery policy.

8.6 Ownership and placement consequences

1. Single-owner mutation: the intended shard path does not access shard-local state concurrently. Runtime owner and borrow checks complement Rust's type rules.
2. Placement is deliberate: sending work to a specific LP is an explicit operation (`try_run_on_lp`, `ShardSender::try_send`) and it is not at the mercy of a global work-stealing scheduler. This makes it possible to reason about locality, cache behavior, and latency.
3. The two container types force a design choice: when you reach for shared data, you must decide: is this accessed from interrupt context? Use `PerLp<T>` with locking. Is it thread-only? Use `ShardLocal<T>` without locking. The choice is explicit.
4. Cross-shard communication is typed and bounded: A `ShardSender<M>` carries a specific Rust type (neither `Box<dyn Any>` nor a byte buffer). The receiver knows what it will get. The channel has fixed capacity; senders handle backpressure. There is no unbounded message queue that can exhaust memory.

9 The Sitas Executor

The Sitas executor drives futures on one shard and parks on the shard's completion queue when no task is ready. The short loop, future and channel listings below explain that architecture; they are not complete runtime APIs. The deployed integration and mailbox-index example live in `crates/catten-user/src/main.rs` and its companion Sitas checkout.

9.1 One executor per shard

Each Sitas shard has:

- One executor: a cooperative scheduler that polls ready futures within a budget.
- One ready queue: tasks whose futures returned `Poll::Pending` and whose wakers have since been invoked.
- One timer wheel: futures awaiting deadlines.
- One CQ partition: the completion queue on which this shard waits (`checked CQ wait`).
- Shard-owned service state: mutable data that only this executor touches.

The executor runs on one LP-affine thread. When that thread is scheduled onto its LP by the kernel, the executor runs. When the thread blocks (no ready tasks), the LP is free to run another domain's thread.

9.2 The polling loop

The executor's main loop is:

```
loop {
    // 1. Poll ready tasks within a budget.
    while budget_remaining > 0 && ready_tasks.not_empty() {
        let task = ready_tasks.pop();
        match task.future.poll(task.waker) {
            Poll::Ready(output) => { /* task done */ }
            Poll::Pending => { /* will be re-awoken by waker */ }
        }
        budget_remaining -= 1;
    }

    // 2. If tasks remain but budget exhausted, re-queue and yield.
    if ready_tasks.not_empty() {
        ready_tasks.requeue_for_next_tick();
    }

    // 3. No ready tasks? Block in the unified wait.
    if ready_tasks.is_empty() && timer_wheel.is_empty() {
        reactor.wait_for_events(); // -> checked CQ wait
    }
}
```

The budget prevents one task (or a tight loop of always-ready tasks) from starving other tasks on the shard. If

the budget is exhausted with work remaining, the executor re-queues the remaining tasks and yields (either to other threads on the same LP via the kernel scheduler, or to idle).

9.3 The unified wait: three event sources, one wait point

When the executor has no ready tasks and no pending timers, it calls `checked CQ wait` on the shard's completion queue. This is the **only** blocking point in the shard's execution.

Three event sources converge on this one wait point:

Timed completion waits use one absolute-deadline loop for kernel and syscall callers. An unrelated wake rechecks readiness and reparks with the remaining budget. Admission rejection is distinct from timeout: both retain the pending operation and any buffer borrow. Neither permits releasing its resources or replaying an accepted operation.

9.3.1 Kernel completions (CQ entries)

When a submitted operation completes (timer expired, DMA finished, device interrupt processed), the kernel posts a `CompletionEntry` to the shard's CQ ring and wakes the blocked thread. The executor drains the ring:

```
fn drain_cq(&mut self) {
    while let Some(entry) = self.cq_ring.read() {
        let waker = self.waker_registry.take(entry.user_data);
        if let Some(waker) = waker {
            waker.wake(); // task becomes ready
        }
    }
}
```

9.3.2 Endpoint readiness (coalesced wake)

An endpoint can be bound to a CQ. When a message arrives on the endpoint, the kernel posts a coalesced wake to the bound CQ. The executor, on waking, calls the endpoint's receive path to drain the pending messages.

Coalescing means: if 10 messages arrive before the shard wakes, the kernel delivers one wake instead of 10. The executor drains all 10 messages in one batch.

9.3.3 Device interrupts (coalesced wake)

A device interrupt object can be bound to a CQ. When the interrupt fires, the kernel posts a coalesced wake. The executor, on waking, calls the device's interrupt handler (or the driver's polling function).

9.4 Task wakeup: from CQ entry to future poll

When the executor drains a CQ entry, it looks up the registered waker for that entry's `user_data` cookie. The cookie was set by the task when it submitted the operation. The waker marks the task ready:

```
// Inside a task's Future::poll:
fn poll(mut self: Pin<&mut Self>, cx: &mut Context<'_>) -> Poll<u64> {
    match self.cap.poll() {
        Ok(Some(completed)) => Poll::Ready(completed.result),
        Ok(None) => {
            // Register waker so we are notified when this completes.
            self.cap.register_waker(cx.waker().clone());
            Poll::Pending
        }
        Err(e) => Poll::Ready(/* error */),
    }
}
```

When invoked, the `ShardWaker` sets the task's ready flag and signals a blocked reactor to re-enter the polling loop. The reactor then polls the task, which finds its completion ready.

9.5 Cross-shard messaging without the kernel

Within one protection domain, tasks on different shards communicate through Sitas typed mailboxes rather than kernel endpoint IPC:

```
// Shard A: send work to Shard B.
let sender: ShardSender<Command> = shard_b.mailbox();
sender.try_send(Command::Process { data: owned_buffer })?;

// Shard B: receive work.
let receiver: ShardReceiver<Command> = shard_b.receiver();
loop {
    let cmd = receiver.recv().await?;
    match cmd {
        Command::Process { data } => { /* handle */ }
    }
}
```

The `ShardSender/ShardReceiver` pair is a bounded, typed, MPSC channel within userspace. Sending does not cross the kernel boundary. The receiving task registers its waker on the channel; when a message arrives, the waker fires and the task re-enters the executor's polling loop.

This is **internal** cross-shard communication (same protection domain, different shards). External communication (different protection domains) uses endpoint IPC (Chapter 5).

9.6 The ShardParker: blocking on native state

When the executor has no ready tasks, it must block its OS thread. The mechanism is the `ShardParker` trait:

```
trait ShardParker {
```

```
    fn park(&self, timeout: Option<Duration>); // Block the current thread.
    fn unpark(&self);  // Wake the blocked thread (from another shard).
}
```

On CharlotteOS, private shard reactors use the checked CQ wait (syscall 88), with an explicit timed flag and separate readiness, deadline and admission-rejection outcomes. For a queue with one waiter, the safe runtime boundary is:

```
let outcome = catten_rt::cq::wait(timeout_ms, cq_id)
    .unwrap_or_else(|_| catten_rt::domain_abort());
// Recheck all sources; readiness does not observe a result.
catten_syscall::cq_wake(cq_id); // Peer notification.
```

The sibling Sitas backend uses that same runtime ABI 3 contract. Its reactor retains one monotonic deadline; wakeups cannot restart it. Runtime sleep also rechecks its original deadline, so an unrelated completion cannot shorten sleep. Rejected waiter admission logs and aborts the domain, preserving uncertain operation ownership rather than becoming a fake wake or an executor retry loop.

Mapped per-shard CQ rings isolate reactor wakes. Public parkers sharing a CQ retain a 5 ms timer backstop because another reader can consume its shared work-generation cursor. This is bounded timer recovery, not a per-waiter readiness contract. Removing that backstop requires the corresponding notification proof.

This native mapping needs no intermediate thread pool or condition variable. The checked CQ source covers endpoint, completion and explicit peer readiness; the removed unchecked syscalls 12/42 have no compatibility adapter.

9.7 Concurrency and execution consequences

1. Cooperative scheduling means no data races on shard-local state: within a shard, only one task runs at a time. The executor polls tasks sequentially. There is no preemption within the shard. This means shard-local mutable state never needs locks.
2. The single wait point eliminates a class of race conditions: the executor does not wait on “timer or CQ or endpoint” through three separate blocking calls with three separate check-and-arm sequences. One CQ, one wait, one drain loop. The kernel guarantees the wake is not lost between checking and arming.
3. No thread-pool overhead: the executor uses exactly one kernel thread per shard. When that thread blocks, it blocks on the CQ, the same object that will deliver its wake. There is no need for a pool of threads to convert blocking syscalls into futures.
4. Budgeting prevents starvation: the polling budget ensures that a shard with many ready tasks makes progress on all of them, including the ones that finish slowly. This prevents priority-inversion-like behavior within a shard.
5. Internal messaging avoids unnecessary kernel crossings: shards within the same process communicate through typed channels in userspace. Only cross-process IPC crosses the kernel boundary. This keeps the fast path fast and the trusted computing base small.

9.8 A worked example: the mailbox index build

The mailbox index build is an end-to-end Sitas demo at EL0. It is the `no_std` counterpart of the host-side `sharded_index_mailbox` example: scanners route generated records to logical assembler work units through typed mailboxes; assemblers sort the records; and a coordinator merges and verifies the runs.

The demo is implemented by `sitas_core::mailbox_index` and runs inside `catten-user`, the EL0 Sitas image that the kernel's `el0_sitas` self-test loads and verifies.

9.8.1 The workload

The demo uses 1024 synthetically generated records over two shard threads and three logical assembler work units. A record's key is a pure function of its index (a SplitMix64 avalanche over `seed` XOR `index`), so any thread can re-derive any key without storing the data set. An index entry is a `(key, offset)` pair.

- Scanners: two producer threads, one per shard. Each generates its contiguous partition of records, routes every key to an assembler with a key hash, batches the entries, and sends the batches as owned messages.
- Assemblers: three logical work units. Two are placed on shards 0 and 1; the third is deliberately placed on shard 0 so that logical naming and physical placement are visibly separate. Each assembler receives its entries, sorts them into a run, and hands the completed run to the coordinator as an owned value.
- Coordinator: the main thread. It spawns the shard threads, waits for all three runs, k-way merges them, verifies the final index, and writes the verified record count to the status page.

9.8.2 Kernel and userspace responsibilities

The demo separates kernel and userspace responsibilities.

The kernel supplies:

- An address space with mapped user pages (code, heap, CQ ring, status page) and nothing else: no file, network, or mailbox syscalls are used anywhere in the demo.
- `spawn_thread` via SVC, which pins each shard thread to its LP.
- The completion queue: a ring mapped read/write into user memory, with `checked CQ wait`/`CQ_WAKE` as the only blocking primitive.

Userspace (the Sitas `no_std` lane) supplies:

- One `ShardExecutor` per shard, polling its futures and blocking in the unified wait (Section 9.3).
- The typed mailboxes (`ShardSender`/`ShardReceiver`) that carry work between shards without ever crossing the kernel boundary (Section 9.5).
- All of the logic: routing, batching, backpressure, sorting, the merge, and the verification.

The kernel never sees a message, key, or run. It sees threads being spawned and blocking on the completion queue. The division is explicit: the kernel provides authority isolation, thread placement, and wakeups; userspace owns the workload state and message discipline.

9.8.3 The mailbox path

The typed channel carries `IndexMessage`:

```
enum IndexMessage {
    Entries { from: ShardId, batch: Vec<IndexEntry> },
    ProducerDone { from: ShardId },
}
```

Senders are cloned into every scanner; each receiver moves into its assembler shard, and assemblers are started before scanners so receivers exist before producers begin. The `no_std` channel exposes a non-blocking `try_send`; a producer whose mailbox is full parks briefly on the runtime's `ShardParker` and retries, rather than spinning. The assembler task awaits `receiver.recv()`; the await parks the shard in its reactor wait, and the sending side's channel waker re-queues exactly that task and releases the reactor. This is the same channel-waker-to-reactor chain as the sharded KV service (Section 9.5).

9.8.4 Coordination and joining

The demo coordinates like the sharded KV requester: the coordinator parks and polls the result mailbox until all three runs arrive, then verifies. A parked coordinator consumes no CPU, and a stolen or coalesced wake costs at most one park interval.

Joining shard threads is also real on CharlotteOS now. A shard thread terminates itself with `thread_exit` once its closure completes (a user thread has no "returned" trap, so the trampoline must ask the kernel to reap it), and the kernel's `ObserveThreadExit` syscall registers a completion capability as an exit-observer of that thread: when the kernel reaps the thread, the capability fires through the ordinary completion ABI. The backend's `CharlotteJoinHandle` wraps this behavior. `join` blocks in the kernel's completion wait and then reads the closure's return value from a per-spawn result slot, and `is_finished` polls the capability. The `catten-user` join probe exercises it: it spawns two shard threads that return 40 and 41, joins both, and writes the sum (81) to the status page. The coordinator of the mailbox demo itself does not join because work completion (all runs arrived) already implies that the shards are done. A caller that must observe thread exit can use the kernel-backed primitive.

9.8.5 Verification

The tests check the result:

1. Every run is internally sorted.
2. A k-way merge over the runs is globally sorted and contains all 1024 records.
3. Every entry's key equals the deterministic key of its offset, and the offsets form a complete bijection of the record range (checked with an XOR invariant).
4. Exactly one run arrives per work unit.

On success the demo writes 1024 (the number of records) to status-page offset 1 and the join probe writes 81 to offset 2, next to the `basic_kv` result at offset 0. The kernel's deferred verifier polls all three words and reports:

```
[sitas] SUCCESS: basic_kv total_len=3,
mailbox index verified 1024 records,
```

```
join probe sum 81
```

A failed demo writes the failure sentinel `0xBADC0DE` instead, which the verifier turns into a failed self-test.

9.8.6 What the demo establishes

The mailbox index build exercises owned state, owned-value transfer, and lock-free cross-shard communication while the kernel provides only scheduling and completion primitives. The demo targets the `no_std` `ShardRuntime`, so the identical code path runs on a Unix host through `sitas-unix` with a plain `cargo test` and on CharlotteOS through the kernel syscall backend.

10 Scheduling and Backpressure

The kernel schedules threads through a block–yield–wake cycle. Bounded ingress propagates pressure, although not every internal queue has a hard memory bound.

10.1 The kernel scheduler

CharlotteOS uses a pluggable scheduler architecture. The system scheduler (`SYSTEM_SCHEDULER`) delegates to per-LP `LpScheduler` instances. The reference implementation is `RoundRobin`:

- A FIFO run queue per LP.
- A per-LP quantum timer (10 ms by default) that drives preemption.
- Operations: `spawn_thread`, `block_thread`, `submit_ready_thread`, `yield_lp`, `abort`.

The scheduler is pluggable: a different scheduling policy (EDF, CFS, fixed priority) can be provided by implementing the `LpScheduler` trait. The rest of the kernel interacts with the scheduler only through the abstract interface.

10.2 The block-yield-wake cycle

This cycle underlies asynchronous operations. Every async primitive in CharlotteOS, including `sleep()`, `wait()`, and `checked CQ wait`, is implemented through it.

10.2.1 Block

A thread blocks by calling `block_thread(tid, &observable)`:

1. The kernel marks the thread `Blocked` in the scheduler.
2. The thread's `Waker` is registered as an observer on the observable event (a completion, a timer, an endpoint, or a CQ).
3. The thread is removed from the LP's run queue.
4. `yield_lp()` saves the thread's register state and stack pointer to its `ThreadContext`.
5. The scheduler selects the next ready thread (if any) and restores its context. The blocked thread is suspended at the point of the yield.

For a timer sleep, steps 1–2 include creation of the wake source itself. Publishing `Blocked` and inserting the timer into the local queue must therefore be one local non-preemptible transaction. `sleep()` masks local interrupts across both operations; otherwise a scheduler-quantum interrupt can switch out the newly blocked thread before any event exists to wake it. The previous interrupt state is restored before `yield_lp()`, and no lock is held across the yield.

10.2.2 Wake

An event fires (timer expired, completion posted, message arrived):

1. The event's observable fires, calling `Waker::notify(tid)`.
2. `notify` calls `submit_ready_thread(tid)`, which marks the thread `Ready` and adds it to its affinity LP's run queue.
3. If the target LP is idle, a reschedule IPI is sent to wake it. If the target LP is already running, no IPI is needed; the thread will be picked up at the next scheduling point (quantum expiry or voluntary yield).

10.2.3 Resume

At the next scheduling opportunity on the target LP:

1. The scheduler selects the woken thread from the run queue.
2. The thread's saved `ThreadContext` (registers, stack pointer) is restored.
3. Execution resumes immediately after the `yield_lp()` call that originally blocked the thread.
4. From the thread's perspective, `block_thread` returned normally and the event has fired.

10.3 Wake coalescing

Wakes are **idempotent**: calling `submit_ready_thread` on an already-`Ready` or `Running` thread is a no-op. This enables coalescing:

- If 10 messages arrive on an endpoint before the shard wakes, the kernel posts one wake instead of 10.
- If 3 timer events fire before the LP processes the timer queue, the kernel delivers them in one batch during the next `process_events`.
- The unified shard wait (Chapter 9) aggregates multiple wake sources onto a single thread. Re-waking that thread is harmless.

The rule is: **enqueue before signaling.** The work is placed in a queue (CQ ring, endpoint queue, timer queue) first; then a wake is delivered. The woken thread finds the work when it drains the queue.

10.4 The quantum timer

Each LP's `RoundRobin` scheduler arms a periodic quantum timer (10 ms default). When it fires:

1. The timer IRQ handler sets a context-switch-pending flag.
2. At the next `yield_lp()` (or at the IRQ handler's tail), the scheduler checks the flag.
3. If set and another thread is runnable, the current thread's context is saved and the next thread's is restored.

An `armed` flag ensures exactly one quantum event is in flight at any time, preventing unbounded timer-queue growth from manual yields.

10.5 The deferred reaper

A thread cannot free its own kernel stack (it is executing on it). When a thread exits:

1. `abort()` marks the exact executing lifetime for retirement, retaining its scheduler handle, thread-table entry and saved context.
2. The scheduler selects another thread and saves the outgoing context. Arm also releases its assembly CPU-ownership flag.
3. On the incoming stack, before restoring its register frame, shared switch completion extracts requested off-CPU threads into their owning LP's `DEAD_THREADS` head and delivers queued readiness after scheduler/table guards leave. Fresh kernel and user entries use the same boundary as resumed threads, with interrupts still masked.
4. A pinned, IRQ-enabled reaper releases the exact stack pair outside IRQ tails. Failed or abandoned release retains the complete owner and original charges; it cannot be retried from a numeric thread ID.

Deferred reclamation is required because threads own their stacks. The incoming FP/SIMD image is restored after switch-completion callbacks, preserving initial userspace isolation. Readiness delivery supplies no physical completion proof.

10.6 Load rebalancing

By default, threads are pinned to their affinity LP. Migration is opt-in:

- A thread must be marked `migration_safe`.
- Migration is rejected while the thread holds timer events, endpoint waiters, CQ registrations, or other LP-affine ownership constraints.
- Rebalancing uses a **sustained-imbalance window**: per-LP load is sampled over a runtime-adjustable interval rather than reacting to a single instantaneous queue-depth observation.

This conservative approach preserves cache warmth and eliminates migration races (observer-not-found when a completion is posted on a different LP than the one where the waiter was registered). Stable affinity is the correctness default; migration is an opt-in optimization.

10.6.1 Protected-domain resource feedback

The scheduler and memory manager also provide the sensors for deliberately slow resource feedback. The versioned `CCOSTAT` record reports generation-qualified domain frame ownership, live and high-water thread and stack use, heap capacity and allocation peaks, node free/usable frames, online logical processors, and a monotonic machine-wide CPU-busy counter. Retired threads contribute permanently to that counter, so interval utilization does not fall when a short-lived worker exits. The `observe` service samples the aggregate once per second into a bounded in-memory history and writes the same resource fields asynchronously to a bounded object-store ring.

New threads reserve a signed stack budget but initially commit one physical page. A stack translation fault may commit all pages down to the fault address only after preflighting the complete growth against both that budget and the node's free-frame reserve. Domain heap pages are likewise demand committed. For an

unsigned kernel-launched service, a later generation may grow its stack or heap budget from the preceding generation's high-water mark, but never past the platform maximum. The heap policy keeps the historical 4 MiB capacity as a floor: demand commitment already saves physical memory, whereas shrinking the virtual claim would turn an ordinary workload change into an allocation failure. Signed deployment limits remain authoritative over feedback.

These loops are intentionally separated by timescale. Fault handling enforces hard local bounds immediately; creation-time feedback changes only a later generation; cluster placement consumes a separate five-second control stream, applies an EWMA and bucket hysteresis, and requires a stable candidate plus a relocation cooldown. Raw one-second telemetry remains unfiltered for diagnosis. The arrangement applies cybernetic feedback without allowing short-lived noise to rewrite authority or oscillate execution continuously.

10.6.2 Generation-safe retirement

Thread retirement proceeds from identifying the exact generation, through leaving the old stack, to releasing backing and metadata. Deferred reapers wait for work on their own LP; a readiness signal never substitutes for stack or translation quiescence.

Identify the generation.

A numeric thread identifier names a table slot that can be reused. Every queued scheduler handle, waker, deferred verifier callback, and asynchronous retirement request therefore carries the thread generation. `abort_thread_generation` and the LP scheduler's removal operation validate both values before changing state. A delayed cleanup request for an exited thread consequently cannot abort a newer thread that reused the same numeric identifier. The scheduler-lifecycle boot test exercises stale wake rejection and remote owner-LP retirement.

Retain the complete thread until stack release.

Deferred retirement owns the complete thread in its prepared node until the owner LP is off that stack and explicit stack-pair release succeeds. Only then does consuming metadata disposal destroy the context and release the node. `Thread` fallback retains its complete `ManuallyDrop` payload: it cannot publish exit, cancel waits, refund usage or invoke field destructors under an unknown guard. An atomic abandonment counter supplies diagnostics, never recovery authority. Failed or abandoned physical retirement remains terminal; outer constructor/syscall masks and stack-growth guards still need separate qualification. See `docs/reference/thread-retirement.md`.

Optional detail: Kernel stack ownership

The kernel half of each pair now carries a non-copyable `KernelStack` owner with the exact base, page count and one-shot release fence. Teardown borrows that owner; no numeric base/length adoption is exposed. Its unmapped guard pages need no registry entries, eliminating the former guard-map allocations beneath stack-arena serialization. Failure retains the containing pair's root and original admission; dropping the range owner performs no physical cleanup.

Release metadata before refunding admission.

The thread allocation charge stays in the same node through staging, delayed reaping, failed retirement and abandonment. Confirmed pair release permits context disposal, then node deallocation, then refund to the original principal. Root retirement, ASID reuse and trusted promotion cannot refund live metadata. Allocation/limit rejection remains `ThreadPreparationFailed`. Table-vector capacity, observer/weak storage, allocator overhead and general metadata admission remain separate. See `docs/reference/thread-metadata-admission.md`.

Optional detail: Thread and principal-history capacity

Before either heap allocation, thread creation now reserves exact requested bytes for its stable context Box and prepared retirement node, plus one bundle unit. All generations of a verified signed principal share 1 MiB and 128 bundles; the node admits 8 MiB/4,096 bundles, with ordinary work limited to 6 MiB/3,072. The existing principal-history record holds the counter. Published history and root candidates also have a separate 1 MiB/4,096-node pool, with ordinary preparation limited to 768 KiB/3,072. Trusted preparation captures classification before allocation. Published records stay charged for the boot lifetime; losing candidates stay in the existing root receipt through failed invalidation and refund only after actual node disposal. See `docs/reference/principal-history-admission.md`.

Optional detail: Root-bound waiter and timer sponsors

Waiter and scheduler-timer sponsors are now prepared fallibly with each root's memory-budget registry node before address-space publication locks. One owner retains the unpublished root and both namespace preparations; publication binds the account to the exact assigned generation without allocating its metadata. The kernel account is prepared on the BSP before scheduler/AP startup. Runtime sponsor capture cannot lazily allocate or substitute a successor's account; old memory charges and outstanding waiter/timer owners retain their original lifetimes independently.

Optional detail: Root limit, usage and signed-authority metadata

Launch-limit and domain-usage nodes now prepare in the same registration owner and publish without allocation. Their detached nodes follow the exact closing/final-root receipt through failed invalidation; confirmed invalidation releases them outside local guards before backing and slot completion. The signed-authority slot now prepares with those nodes. It initially grants no identity; the signed loader fills the exact assigned generation without allocation. The populated principal/roles/descriptor binding remains in the same final-root receipt through rejected invalidation. Limits, usage and authority nodes now reserve their exact requested layouts in a shared 4 MiB/12,288-node pool; ordinary preparation is limited to 3 MiB/9,216 nodes. A root needs all three; partial rejection frees unused nodes before refund and publishes no ASID. Original charges follow detached nodes through failed invalidation until actual post-proof deallocation. Promotion cannot reclassify an existing charge.

Optional detail: IPC metadata during root publication and cleanup

IPC namespace storage and both budget accounts also prepare fallibly in the same registration owner. Its first exact-root operation lease spans lifecycle/table unlock and prepared namespace publication under IPC alone; missing namespaces reject instead of recreating. Empty drained namespace nodes dispose after IPC unlock.

Optional detail: IPC metadata during root publication and cleanup (continued)

Pending and reply-token nodes likewise prepare outside IPC with original call/reply counts and a retained caller-root lease. Their complete containing owner explicitly finishes ordinary outcomes; abandonment retains all fields, and detached node disposal precedes count refund. Reply/cancellation owners retain token nodes through post-IPC disposal; serialized close reuses those nodes as its bounded retirement list, while scalar completion fallback retains the node and detached notifications together.

Endpoint storage and queue growth now also prepare outside IPC while retaining their exact root and original sponsor/classification. FIFO replacement relinks without allocation; old backing and final closed endpoint nodes dispose after IPC unlock. Complete fallback retains their fields.

Per-capability payload nodes now prepare fallibly before authority mutation and publish by relinking. Detached payload and shared authority records leave IPC together in the existing cleanup owners; original connection counts follow node free.

Call/endpoint shared-authority storage now prepares outside IPC with exact roots retained, admission revalidates/relinks under IPC, and payload allocation leaves it again. Call pending waiter-list construction also leaves IPC. Other guarded factories and memory capability/loan maps, namespace/account byte/principal admission and outer contexts remain separate. See `docs/reference/endpoint-budgets.md`. See `docs/reference/root-metadata-admission.md`. See `docs/reference/memory-object-retirement.md`.

Wait for retirement work.

Each pinned reaper waits on its LP retirement head instead of polling a timer. Staging queues admitted waiter nodes; producer-LP scheduler and idle boundaries deliver detached callbacks after guards leave. An owned generation-bound subscription and a durable readiness recheck prevent lost publication. Failed stack pairs remain fenced and do not keep the worker runnable. Only rejected waiter admission uses the recorded 10 ms backoff; readiness does not prove quiescence or authorize physical retry.

Optional detail: Deliver callbacks before parking

Guard-free park setup drains the producer LP's pending deferred callbacks before publishing Blocked, under an IRQ-state-preserving local mask. Restoring IRQs can switch the producer away before its subsequent yield; that yield cannot be the only delivery path for a dependent worker's wake. Timed waits recompute the remaining absolute budget after delivery. Event-only waits, sleep and untimed completion waits preserve the same ordering. This dispatch supplies readiness and metadata disposal, never physical cleanup authority. The bounded negative control detects omitted precursor delivery; historical IPC exact-exit timeouts remain subject to separate causal verification.

Compose with memory and IPC close.

The same event-only pattern lets close operations retain their exact roots and accepted work while waiting. Rejected waiter admission leaves authority and pins intact, and an observed transition grants no physical retry authority.

Optional detail: Memory transfer-fence waiting

Explicit memory close likewise waits on an owned interest in the source transfer fence, retaining that transfer's captured root while parked. Its charged source and disposal node are prepared before memory-registry publication. Transfer completion closes the exact interest and uses the shared producer-LP transport for callbacks and metadata disposal after guard exit. Another LP cannot consume that transport beneath the producer's IPC hold. Wait admission rejection leaves authority and pins intact; ordinary loan, DMA, copy and mapping pin rejection retains its existing policy. Readiness supplies no hardware completion or physical retry authority.

Optional detail: IPC claim waiting

IPC close waits use the same event-only policy for reply/cancellation and endpoint-close claims. A contended close retains its exact root; source publication revalidates the capability and checked claim epoch after fallible preparation outside IPC. Rollback followed by another claim on the same token is a separate episode. Owned endpoint front waiting borrows its existing server lease and retains its interest with that owner. Completion, ordinary rejection and failure close the exact source through producer-LP deferred notification and metadata disposal. Rejected wait admission preserves authority and loan fences; abandonment supplies no wake or physical retry. The serialized namespace/fixture adapter returns Pending on an unexpected claim instead of parking beneath lifecycle. Namespace and operation-lease drains retain separate notification work. See `docs/reference/ipc-record-budgets.md`.

10.7 Synchronization and lock ordering

Shared kernel state is synchronized by a small, deliberate set of primitives. Their full semantics and the cross-subsystem ordering rules are maintained in `docs/reference/locking.md`, which is authoritative over this overview.

10.7.1 Lock families

- **Interrupt-masking spin `Mutex`** guards the frame allocator, memory-object registry, address-space table, kernel address space, domain-authority table, address-space lifecycle, scratch-window allocator, and the global allocator. It attempts acquisition with maskable IRQs disabled and keeps them disabled while owned. A failed attempt restores the caller's interrupt state before spinning, then retries with IRQs masked. The ownership masking exists to prevent a preemption deadlock: these locks are taken from both preemptible kernel threads and synchronous EL0 exception paths, so a timer-preempted owner could otherwise be starved forever.
- **Interrupt-masking spin `RwLock`** is the workhorse. It protects the master thread table, the deferred-dead table, the system scheduler, the IPC registry, the completion registry, the userspace mailbox table, and each per-LP slot. Failed reader and writer attempts likewise restore `INT_STATE` while contending. A `waiting_writers` counter gives writers preference only during the masked atomic acquisition attempt; retaining that preference while waiting could deadlock a same-LP interrupt reader.
- **The external `spin` crate** is used only by the stack allocator, which wraps its arena mutex in explicit `mask_interrupts!`/`unmask_interrupts!` calls. Its guard-page map is touched only from thread context, never from IRQ context.
- **Lock-free structures** cover the rest: `ShardLocal` and `PerLp` for per-LP data, `ConcurrentQueue`

for the IRQ-to-thread deferred-wake handoff, and plain atomics for the `on_cpu` ownership handshake and generation counters.

A scheduler-blocking lock family exists under `cpu/scheduler/sync` that parks a contended caller via `block_thread` instead of spinning. It currently has no callers and does not participate in any ordering guarantee.

10.7.2 Interrupt-masking discipline

Both spin locks mask IRQs while owned, but leave IRQs in the caller's original state while waiting for another LP. This is required for synchronous TLB-shootdown rendezvous: a contender must remain able to acknowledge the lock owner's IPI. Only the `RwLock` is nesting-aware. It routes through a per-LP `INT_STATE` record that counts save depth and re-enables interrupts exactly once on the outermost restore. This lets a thread take several different `RwLock`s, or a read after a read, without prematurely re-enabling IRQs. The `Mutex` records its pre-acquire interrupt bit on the lock object itself. Both guard types are non-sendable; acquiring different mutexes still nests correctly, but re-acquiring the same lock on one LP deadlocks.

10.7.3 Lock ordering

The scheduler's chain is fixed:

```
SYSTEM_SCHEDULER.read() -> lp_scheduler.lock() -> MASTER_THREAD_TABLE.write()
```

Cross-subsystem rules hold today:

- **Never take address-space or frame-allocator locks while the heap lock is held.** The heap's growth reserve is pre-mapped at boot so allocation can extend within mapped memory without those locks.
- **Never hold the memory-object registry across the address-space table lock.** Teardown takes table-then-frame-allocator while allocation takes allocator-then-registry; registry-then-table would close an AB-BC-CA cycle.
- **Dropping the memory-object registry for a bulk copy requires a shared-read copy pin.** While such a pin exists, writable CPU mappings, in-kernel writes, writable or exclusive DMA pins, write lends, moves, and ownership rollback are rejected. Owner teardown is deferred until both the DMA-pin and copy-pin counts reach zero. The final release removes the object under the registry lock and frees its frames only after dropping that lock.
- **Never block or yield while holding any lock.** A spin lock also masks IRQs, so parking the thread would abandon the lock and the LP could not schedule its successor. All guards are dropped before `switch_ctx`.
- **IRQ context takes no locks and never blocks.** Interrupt delivery uses atomics and MMIO only; a deferred wake crosses into thread context through a lock-free queue.

10.8 Backpressure and queue bounds

Endpoint and hardware rings are bounded. CQ overflow retention is preallocated and bounded by accepted submission slots, with separate queue count/backing-byte admission. A slow consumer retains those slots

and eventually prevents new submissions. General kernel-heap bytes and aggregate principal budgets remain incomplete; these family limits do not form a complete resource ledger.

Layer	Bounded object	Backpressure signal
Application request	Service endpoint queue	`QueueFull`
Service shard mailbox	`ShardSender<M>`	`Err(m)` returned
Driver endpoint/ring	NIC descriptor ring	Descriptor exhaustion
Kernel submission	Capability table	`WouldBlock`
Hardware	DMA descriptor ring	Ring full

The following pseudocode sketches possible protocol policies; it is not a shared runtime enum or a promise that every source supports capacity notification:

```
enum SendPolicy {
    Try,               // Fail immediately if full.
    Wait,              // Wait for capacity.
    Deadline(Instant), // Wait until a deadline.
    // Merge a pending "data available" notification.
    DropIfCoalescible,
}
```

Rules:

- Terminal completions are never dropped: the CQ backlog guarantees this (Chapter 7).
- Coalescible notifications may be merged: two “data available” signals before the consumer wakes become one.
- Control messages normally fail or wait explicitly: a service registration request that cannot be queued fails with `QueueFull`.
- Data-plane producers should stop before unbounded allocation: a NIC driver should stop accepting TX packets when its descriptor ring is full.
- Critical control work needs its own progress contract. The generic 256-entry IPI queue has rejecting `try` admission, but no reserved mandatory-message slots. Its legacy force-push path can evict the oldest entry when full. Current x86 synchronous shootdown instead uses a separate epoch and acknowledgement channel; queue size alone proves neither lossless delivery nor freedom from starvation.

10.9 Scheduling guarantees and remaining bounds

1. The block-yield-wake cycle is exercised across subsystems: the same mechanism handles sleep, IPC wait, CQ wait, and timer wait. A bug fixed in one path fixes all paths. The cycle is exercised by the async demo and by self-tests that call `wait()`. These tests give us evidence for the path; they do not provide a formal proof.
2. Idempotent wakes eliminate lost-wake races: re-waking an already-ready thread is a no-op. This means the kernel can be aggressive about delivering wakes without worrying about double-delivery.
3. Bounded ingress limits some exhaustion paths: endpoint and descriptor-ring capacities reject excess work with backpressure. Family quotas cover capability records, completions and CQ backing, among other resources. General heap and aggregate principal admission remain incomplete, so this is not a general denial-of-service guarantee.

4. Stable LP affinity prevents migration races: completion delivery is LP-local. A waker registered on LP 2 is signaled on LP 2. There is no window where a completion is posted on LP 1 while the thread is migrating to LP 2 and the observer is not found.
5. The scheduling interface is pluggable: `RoundRobin` is the implemented policy. Other policies would require their own implementation and validation behind the same interface.

10.10 Scheduler observability

The prototype records integer running statistics for each thread at scheduler context switches. A snapshot includes the thread identity and generation, address-space owner, scheduler state, LP affinity, dispatch count, and the count, minimum, maximum, total, and sum of squares of completed on-CPU slices. The active slice start tick is reported separately. The counter frequency in the snapshot header permits conversion from ticks to time.

The accumulator uses integer arithmetic and reports saturation. Mean and sample variance are exported as exact rational components; standard deviation and coefficient of variation are calculated in userspace. This avoids using floating-point/SIMD state in the kernel. Accumulators are mergeable so future hot-path metrics can be gathered per LP rather than through a global lock.

The `THREAD_STATISTICS` syscall is address-space-scoped by default: callers see only their own threads and receive the snapshot as a memory-object capability. At boot the supervisor starts exactly one `observe` EL0 service and delegates a typed system-observer capability through its launch vector. Presenting that capability authorizes a machine-wide snapshot; a fabricated or wrong-type handle fails closed. The service publishes snapshots through endpoint IPC and registers itself with the node name service. Machine-wide observation is therefore explicit authority rather than an ambient privilege.

Diagnostic thread/domain capture and encoding share an unchanged 1 MiB per-request working bound. Their vector allocations also use the existing 16/12 MiB total/ordinary snapshot-byte pool and a separate 16 MiB requested-byte allowance in the signed principal's boot-lifetime record. Principal and trusted class are captured from the verified root before source locks or allocation; the observer capability does not change either. Original charges survive promotion, root retirement and ASID reuse until actual buffer deallocation. Full old/candidate growth overlap is admitted before allocation. This introduces no new metadata pool or preallocated heap reserve and does not complete general metadata/principal accounting or sustained-pressure qualification. See `docs/reference/telemetry-snapshots.md`.

An HTTP `GET /metrics` adapter is a reasonable userspace consumer of this IPC protocol, but it is not implemented yet. The present TCP/IP service does not supply the complete server-side bind/listen/accept path needed to host it. See `docs/reference/observability.md` for the wire format, security boundary, and suggested next metrics.

Part IV

Building Systems

11 Service Architecture

Protection domains contain service faults and authority. Naming and protocol policy remain in userspace; privileged code manages lifecycle and resources.

11.1 Protection domains as failure boundaries

A protection domain (Chapter 3) is the unit of both authority and failure. When a service crashes, retirement stops its threads and closes admission before physical cleanup:

- Its capability table is destroyed, invalidating its handles: client connections to the closed endpoint fail through the IPC lifecycle.
- Borrowed mappings are revoked before lender access can return. Failed invalidation or cancellation retains the loan fence and backing.
- Its threads are aborted on their owning LPs; reaping and exact-root operation drain must complete before stack or address-space reuse.
- Device teardown requires its own quiescence/invalidation proof. Failed or uncertain cleanup retains grants, pins and original charges rather than making them available to a replacement.

The MMU and capability checks are intended to contain the fault to that domain; kernel, hardware, and DMA defects remain outside this guarantee.

11.2 The supervisor: domain lifecycle manager

The **supervisor** is a kernel-side component that creates and destroys protection domains. It does not understand service protocols, but it does understand ELF images, memory mappings, and capability grants.

Its operations are:

Load Parse an ELF image, validate its segments, create a new address space, map `PT_LOAD` segments at their linked virtual addresses, set up a stack with a guard page.

Grant Populate the domain's config-page with the bootstrap capabilities it needs:

- For deployed applications, a grant-controller connection and immutable signed descriptor; trusted platform services may instead receive a name-service connection.
- For driver domains: an `MmioRegion` capability, an `Interrupt` capability and a protected DMA domain as needed.
- A default CQ layout in the launch header. Services normally create their listening endpoint through the owned runtime API.

Spawn Create the initial thread with the domain's entry point and its affinity LP.

Monitor Register to be notified when the domain exits.

Teardown Close admission, stop threads and retain an owning transaction through mapping, IPC and device cleanup. Only confirmed completion permits physical release and address-space-slot reuse; abandonment can retain the entire root indefinitely.

Grants are minted kernel-side by the supervisor and never through a syscall. A driver does not ask the kernel for MMIO; the supervisor grants it at creation time based on the device topology it enumerated during boot.

11.3 The name service: discovery without the kernel

The kernel does not know about service names. A userspace **name service** maps human-readable names to connection capabilities:

Registration A service publishes a name such as `"driver.nic.v1"` with a delegated connection to its endpoint. An ordinary application uses the grant controller and its signed deployment descriptor; trusted mediation services have a private connection to the name service.

Generation tracking Each registration bumps a generation counter. If the service restarts and re-registers with the same name, the new generation replaces the old binding. Existing connections still target the original endpoint. Re-registration alone does not revoke or redirect them; endpoint death closes that instance's communication path.

Lookup An application requests the complete name and required rights from the grant controller, supplying its immutable signed descriptor. Policy checks the kernel-authenticated caller identity and returns an attenuated owned connection. Public bootstrap lookup cannot grant a policy-published service.

Authorization Bearer access-key operations are retired. Access uses default-deny principal/service policy and signed deployment grants.

The name service runs as a `no_std` EL0 service process. Boot starts exactly one node-local instance and the supervisor retains its registry endpoint. Deployed applications receive an attenuated connection to the grant controller through their bootstrap page. Trusted node-local services may instead receive a name-service connection. Those paths use the same node-local registry. Registering another name does not create another name-service process. A separate registry is appropriate only for an explicitly isolated namespace, such as a test or a future tenant domain.

The supervisor's endpoint handle remains kernel-private. Possessing a bootstrap connection permits the operations granted on that connection; it does not permit an application to mint arbitrary registry connections or inspect another process's capability table.

11.4 Service restart and recovery

When a service crashes and the supervisor restarts it:

1. Device quiescence and reset: a driver can restart only after its hardware-specific cleanup contract permits new grants. Failed or uncertain cleanup retains its fences and backing; a new service name or generation cannot supply the missing completion proof.
2. Generation increment: the name service advances the replacement's publication generation. Existing connections keep their old target.
3. Stale connections: clients connected to the old instance observe endpoint closure when that target dies. They dispose of the old session and request another connection through their original authority. Section 5.6.1 provides a compiling Rust example, including outcomes that must stop rather than replay an operation.
4. Outstanding operation reconciliation: the supervisor retains the old domain's operation owners until cancellation, loan revocation and hardware completion are confirmed. Uncertain work can prevent

reclamation and restart. Application effects still need their protocol's own reconciliation; teardown does not undo them.

5. Fresh bootstrap: the new domain receives a fresh config-page with freshly minted capabilities. It does not inherit the previous instance's capability table, reply tokens, or DMA ownership.

A restarted service receives fresh authority. Tests cover stale connections and operation reconciliation; the status appendix records the verified scope.

11.5 The overall system topology

At steady state, a CharlotteOS system consists of:

- The kernel: capabilities, endpoints, memory objects, CQs, scheduling, interrupt routing.
- The supervisor (kernel-side): domain lifecycle, ELF loading, device enumeration.
- The node name service (one userspace instance): the shared registry for service registration, principal-policy lookup, and generation tracking.
- Service processes: one or more per logical function, such as a NIC driver, TCP/IP stack, UTC time service, filesystem, Raft consensus, or application server.
- Client processes: application code that looks up services and invokes them through capabilities.




Figure 11.1: Steady-state userspace composition around the name service, capability delegation, network stack, storage, and external-service connectors.

Every component beyond the kernel, supervisor, and name service is a replaceable userspace process. We can choose a different NIC driver, filesystem, or network stack through configuration without modifying the kernel.

11.6 Failure containment and recovery

1. Failure containment is architectural: a service fault closes its endpoints and affects clients through defined errors rather than direct memory corruption. Availability still depends on the failed service and its dependants.
2. Recovery follows a defined sequence: the restart sequence (device reset, generation bump, connection invalidation, operation reconciliation) is the same for every driver. A new driver implemented to the same endpoint protocol replaces the old one without any special-case recovery code.
3. Policy lives in userspace: the kernel enforces mechanism (capabilities, endpoints, memory objects). Userspace enforces policy (who can register what name, who can look up what service, how many restarts are allowed, what log level to use). The kernel stays small; policy is auditable and replaceable.
4. The bootstrap contract is explicit and minimal: every domain starts with exactly the capabilities it needs and no more. The config-page contract defines what a domain receives; there is no ambient authority to discover or exploit.

12 Userspace Drivers

CharlotteOS runs device drivers as userspace processes with delegated device resources and endpoint interfaces.

12.1 The problem with kernel drivers

In a monolithic kernel, a driver has access to everything: all physical memory, all interrupt vectors, and all kernel data structures. A buffer overflow, use-after-free error, or race in a driver can corrupt the kernel and crash the system.

The microkernel solution is to move drivers to userspace. But simply moving them is not enough: a userspace driver that can still map arbitrary physical memory or receive arbitrary interrupts is still dangerous. The driver must be **granted** only what it needs, and the grants must be mediated by the kernel.

12.2 The DriverGrant

When a driver domain is created, the supervisor delivers a `DriverGrant` through the config-page contract:

```
struct DriverGrant {
    device: DeviceCap,        // identity and lifecycle of the device
    mmio: Vec<MmioRegionCap>, // register windows, page-granular
    interrupts: Vec<InterruptCap>, // IRQ sources for this device
    // DMA translation, if an IOMMU is present.
    dma_domain: Option<DmaDomainCap>,
    // Endpoint on which to serve clients.
    bootstrap_endpoint: EndpointCap,
}
```

The driver receives **exactly** the MMIO register windows and interrupt vectors it needs. It cannot:

- Map arbitrary physical memory.
- Receive interrupts not assigned to its device.
- Access other devices' MMIO regions.
- Perform DMA without explicit pinning into its DMA domain.

12.3 MMIO delegation

An `MmioRegion` capability represents a page-granular device register window. The driver maps it into its address space as Device-nGnRnE memory (user-accessible, execute-never, strongly ordered on AArch64; uncacheable on x86-64).

The mapping is a kernel-mediated operation: the driver calls `mmio_map(region_cap, addr)`. The kernel validates the capability, creates the page-table entries with the correct memory attributes, and returns. The driver then performs **direct EL0 MMIO**: load and store instructions to the mapped virtual addresses, with no kernel involvement on the fast path.

The common MMIO access therefore avoids a syscall or context switch.

12.4 Interrupt delivery

An `Interrupt` capability represents a routed interrupt source. The driver binds it to its completion queue:

```
interrupt_bind(int_cap, cq_id);
```

When the interrupt fires:

1. The IRQ dispatcher reads the per-interrupt route table atomically.
2. It masks the source at the interrupt controller (GICv3 on AArch64, x2APIC on x86-64).
3. It atomically bumps a coalescing counter.
4. It marks the route's statically initialized readiness mailbox. Repeated deliveries coalesce without consuming another route's slot. Thread context in `yield_lp` and the LP idle loop performs the deferred CQ publication.
5. The driver's shard wakes.
6. The driver reads the device's status register (direct EL0 MMIO) to determine the interrupt cause.
7. The driver processes the interrupt and unmasks the source.

The interrupt path uses atomics and controller MMIO, without allocation or registry locks. Each route's mailbox retains a generation watermark after readiness is claimed, preventing a delayed old publisher from replacing a new lifetime's wake. Thread context validates the route and publishes CQ work under the device-management guard, detaches the exact queue's waiters and releases all subsystem guards before notification. Route teardown precedes release of source ownership. Exhausted binding identities fail closed rather than wrapping. This establishes storage and deferred-publication guarantees. We have not proved every cross-LP controller mask/rearm interleaving.

Boot hardware launch separates grant preparation from thread start. The supervisor retains each loaded driver root and its exact operation lease in a consuming `PreparedDriver`. Storage, entropy and network grants finish before any sibling driver can submit DMA and own the shared IOMMU engine. ARM embeds signed RNG and NIC images in the hardware bootstrap set so batch preparation cannot wait for its own unstarted storage driver to serve the store. The owner starts its thread and then completes its lease; fallback retains all fields without physical cleanup. This ordering needs no polling or grant replay. Independent dynamic creation still rejects busy admission. Per-return creation errors preserve stream/backend/reset cause and confirmed or retained cancellation outcome, which supplies diagnostic evidence rather than retry authority. See `docs/reference/iommu-table-admission.md`.

12.5 The reference UART driver

The PL011 UART driver demonstrates the full lifecycle:

- Direct MMIO writes to the transmit FIFO: no syscalls.
- Interrupt-driven deferred reads: the driver retains a reply token for a pending read. When the RX interrupt fires, the driver reads the receive register and completes the deferred reply.
- Cooperative shutdown: on graceful exit, the driver unmaps its MMIO region and closes its interrupt.

- Crash recovery: if the driver terminates without releasing its device caps (panic, infinite loop, killed by supervisor), the teardown path:
  1. Reclaims the MMIO region (unmaps it, returns to the kernel).
  2. Unroutes the interrupt.
  3. Reconciles outstanding operations: any pending reply tokens are invalidated; any borrowed memory is returned to lenders.
  4. Resets the device hardware.

  A restarted instance with fresh grants resumes under a bumped generation.

12.6 DMA and the IOMMU

For DMA-capable devices (network cards, storage controllers), a userspace driver needs more: the ability to tell the device "read from physical address X" or "write to physical address Y." Without an IOMMU, this is a safety gap: a malicious or buggy driver could program the device to DMA into kernel memory or another domain's pages.

The current storage/network driver path requires a supported IOMMU/SMMU. It skips or rejects protected-DMA startup when that facility is unavailable; there is no supported trusted-driver physical-address fallback. This is why HVF compatibility boot omits storage rather than weakening DMA isolation.

A DMA-domain capability binds the device to its requester-specific translation table. The driver maps explicitly owned memory through that domain; the kernel checks the capability and retains a backing pin. Isolation still depends on the backend, firmware topology and actual hardware honoring those translations.


On the implemented AArch64 ACPI path, `dma_map(domain, memory, direction)` returns an IOVA and `dma_unmap(domain, iova)` synchronously invalidates the IOTLB before releasing the memory pin. QEMU's coherent SMMUv3 is boot-tested with the userspace NVMe driver. Each PCI requester receives a private stage-1 context containing only explicitly mapped memory objects and its MSI doorbell page. SMMU event-queue faults are handled by the kernel.

On x86-64, ACPI DMAR selects Intel VT-d and IVRS selects AMD-Vi. Both backends create per-requester DMA domains, validate domain and requester limits, map and unmap IOVAs, and require synchronous IOTLB invalidation before pin release. Partial attachment failure retains its complete operation if rollback cannot be confirmed; an error is not permission to reuse frames. QEMU boots validate NVMe, AHCI, virtio-blk, and virtio-net through these domains. VT-d supports `INCLUDE_PCI_ALL` units and directly attached endpoint scopes; multi-hop bridge scopes remain rejected. AMD-Vi fault events are polled until post-topology MSI delivery is implemented. Non-coherent SMMUv3, ATS/PRI, and multi-IOMMU topologies remain future work.

DMA map and map-exclusive syscalls may wait for the existing fixed unit slot before their first claim on the domain and command engine. The same operation retains its exact address-space generation, public capability claim, original memory pin, and transient interest. Source storage is prepared outside backend guards; restoration signals through producer-LP deferred delivery only when the actual engine and all domain cells are present. Admission rechecks and transfers the domain, engine, and pin together, then mapping work runs once. Waiting requires an already interrupt-enabled scheduled context; masked or non-scheduled busy callers reject explicitly, and serialized kernel fixtures keep the rejecting path. No adapter enables interrupts beneath an inherited mask. Admission failure releases only the unstarted preparation; hardware or physical uncertainty keeps its existing retention policy. Map readiness does not change unmap's separate admission/completion distinction or authorize hardware or physical cleanup replay. See `docs/reference/dma-map-readiness.md`.

12.7 Driver service layering

Complex I/O stacks decompose into separate failure and authority domains:



The NIC driver knows about hardware registers and descriptor rings, the network service knows about protocols and sockets, and the application knows about its business logic. When a driver's endpoint closes, the network service can discard its old session and discover a replacement. Endpoint loss alone cannot authorize replaying an uncertain device command or reclaiming DMA backing. The client recovery scopes in Section 5.6.1 show that distinction for a read-only operation.

12.8 Isolation and device access

1. CPU-side driver faults are contained: a buffer overflow in a NIC driver is confined by its address space, assuming correct kernel, MMU, and DMA isolation.
2. The privilege model is grant-by-grant: a driver receives exactly the resources it needs. There is no "driver has access to everything because it's in the kernel" default.
3. Direct MMIO keeps the fast path fast: reading a device register uses a direct load rather than a syscall or context switch.
4. Restart follows a defined path: the supervisor handles driver restart (device reset, grant re-issuance, generation bump). The supervisor supplies the common lifecycle sequence instead of requiring each driver to invent restart coordination.
5. Hardware-isolated DMA is implemented on the reference AArch64 SMMUv3 platform and on x86-64 with Intel VT-d or AMD-Vi. Advanced facilities and more complex IOMMU topologies remain future work.

13 Networking

CharlotteOS treats networking as an extension of its message-passing and capability model. TCP/IP is available for interoperability, while native communication remains capability-based.

The guiding principle is:

> **Remote IPC is local IPC with a different transport.**

13.1 Sockets as a compatibility interface


The Berkeley socket API (`socket()`, `connect()`, `send()`, `recv()`) remains useful for compatibility. CharlotteOS places it in a TCP/IP service; native service interfaces use capabilities:

- Network addresses do not define Charlotte service identity: `10.2.3.17:443` locates an endpoint. DNS or another directory can associate that address with a service, while the association remains outside the socket handle.
- TCP sockets expose byte streams: an application protocol must add its own message boundaries. Charlotte's native IPC preserves them.
- Socket authority usually comes from process and network policy: sandboxes, firewalls, and namespaces restrict reachability, while the socket API does not require a delegated capability naming the target service. Charlotte's native path does.
- TCP-specific code needs an adapter to use shared memory for local communication or RDMA for a high-performance interconnect. Charlotte's service API keeps that choice below the application protocol.

CharlotteOS therefore separates the stack into layers with distinct responsibilities.

The stack below describes the target architecture. The repository already contains userspace virtio-net and Intel 82574L/E1000E drivers, the "frouter" frame demultiplexer, and a reliable-message service with fragmentation. It also contains a distributed name service that replicates a `name → {node, generation}` catalog across cluster members, a smoltcp TCP/IP service, and a catalog-routed remote invocation path. The NIC/TCP path is runtime-validated on macOS QEMU TCG with both supported NIC models (`-relmsg-test`, `-disco-test`, `-dns-test`, and `-tcpip-test`). The current remote-call prototype carries scalar arguments and results; general remote capability delegation remains future work.

13.2 The native protocol stack



13.2.1 Ethernet: generic frame transport

The NIC driver exports raw Ethernet frames. It knows about MAC addresses, MTU, and frame CRCs. It knows **nothing** about IP, TCP, RPC, or services. Its endpoint protocol has two operations:

- `OP_SEND(frame_buffer)`: transmit a frame via a moved memory object.
- `OP_RECV`: the caller retains a reply token for a deferred receive; the driver replies with a frame buffer.

Ethernet is a generic frame transport. It can carry IP, ARP, LLDP, custom protocols, or CharlotteOS native messages; higher layers interpret the frames.

13.2.2 Reliable message layer

This layer provides sequenced, acknowledged delivery of **messages** over the raw frame transport. It handles:

- Sequencing (each message has a monotonic sequence number).
- Acknowledgements (the receiver confirms delivery).
- Retransmission (unacknowledged messages are resent).
- Fragmentation (messages larger than MTU are split and reassembled).
- Batching (multiple messages in one frame, one ACK for multiple messages).
- Congestion control (bounded in-flight windows).

The exported abstraction is a **reliable message**. It is the transport for RPC, consensus protocols, and distributed objects.

Fragmentation is implemented: a message larger than one frame's payload (1454 bytes in wire protocol v3) is split across frames that share the message's sequence number. Every data frame carries a 32-bit total message length; each fragment additionally carries a 32-bit byte offset and a `FLAG_FRAG`/`FLAG_MORE` pair. The receiver validates those bounds, buffers fragments by offset, and reassembles a contiguous message.

The 32-bit fields separate representation from resource policy. The initial application-level ceiling is 1 MiB, as configured by `relmsg::MAX_MSG`. This limits allocation and head-of-line blocking without another protocol revision when experience supports increasing it. Application IPC no longer packs a MAC and 16-bit length into one scalar: transferred memory begins with a typed 16-byte v3 envelope containing a magic value, a 32-bit payload length, and the peer MAC. The per-frame payload length remains 16-bit because it describes only one Ethernet frame.

Wire protocol v3 carries a 64-bit sender-session identifier. Data and acknowledgement frames assert it with `FLAG_SYN`. A receiver accepts only a strictly newer session when resetting receive ordering, so one reliable-message service can restart while its peer remains running and old delayed frames cannot roll state backward. Receive-message count, queued bytes, fragment count, aggregate reassembly bytes, and retained outbound bytes are bounded; a full delivery queue withholds sequence advancement and its acknowledgement, applying retransmission-based backpressure. An incomplete fragmented message does not emit one useless cumulative acknowledgement per fragment, and retransmission grace scales with retained fragment count up to a fixed cap; one-frame RPCs retain the 200 ms retry. The transport permits one in-flight message per peer and retains fragments for retry. Bulk data belongs in a streaming or object-store protocol, while reliable messages remain bounded and easy to account for.

13.2.3 RPC layer

The RPC layer provides request/reply semantics over the reliable message layer:

- Synchronous-looking futures: `service.call(opcode, args).await?`
- Asynchronous invocation: a pending RPC call backs the `Future`, allowing the shard to continue while it waits.
- Object references: the target architecture can represent delegated remote authority; general remote capability delegation remains future work.
- Serialization: typed protocol crates encode and decode Rust values on the wire.

13.2.3.1 Identify an invocation and retain its deadline

The implemented DNS v4 remote-call path is narrower than this target model. It carries scalar opcode/argument calls. A request is identified by caller node, caller DNS-session generation, and call ID, and a reply is accepted only from the expected peer. The implementation bounds outstanding calls at 64, returns `ERR_UNCERTAIN` after five seconds (execution may already have occurred), and retains 128 completed results to suppress duplicate execution within that window. The replicated catalog assigns a monotonically advancing service generation; requests and replies carry it, and the target rejects stale generations before execution. Remote object-capability delegation remains future work.

The local caller retains one operation across routing and invocation. Its original monotonic deadline covers both phases. Once invocation has been accepted, timeout or observation failure can report uncertainty but cannot permit replay.

Optional detail: Invocation frames and reply preparation

Invocation frames use tags `0x26/0x27`, complete 32-bit caller/name lengths bounded to 4 KiB each, and exact frame termination. Retired `0x10/0x11` frames reject. The caller prepares request bytes before publishing in-flight state, with its deadline captured beforehand. The target prepares the fixed reply buffer before admitting a local operation and retains it with that operation; result encoding uses

Optional detail: Invocation frames and reply preparation (continued)

the same allocation. A follower carries its original query deadline into invocation instead of restarting the budget, and rejects expired routing results before admission.

Optional detail: Local call ownership and CQ waiting

DNS v4 client calls move a mandatory `CDNSCL01` memory frame containing an exact byte length, complete 1–256-byte name, opcode and signed argument. Retired packed-name/12-byte calls reject. The local operation owns both RPC phases and its returned connection; each pending RPC binds reply readiness to the reactor CQ. One kernel-monotonic deadline begins before decoding and survives routing, lookup and invocation. The reactor waits for the earliest remaining operation deadline while retaining its separate clock/transport interests. Admission rejection after an accepted invocation is uncertain and never permits replay.

13.2.3.2 Publish a service in two phases

Registration uses two replicated phases. A `prepare` command allocates the next generation while keeping it invisible. After the owner publishes its node-local endpoint, a generation-fenced `activate` command makes the entry visible. Failed local publication leaves an inactive tombstone rather than a remotely resolvable ghost. Explicit unregistration and automatic endpoint-death retraction are implemented. The replicated tombstone must match the owning node and distributed generation, and local removal must match the generation captured before the proposal. A delayed operation therefore cannot remove a replacement instance.

Optional detail: Registration relay framing

Follower registration now uses tags `0x28/0x29`; automatic retraction uses `0x2a`. Complete 32-bit lengths carry nonempty owner identities bounded to 4 KiB and service names bounded to 256 bytes. The old `0x14/0x15/0x16` records reject, including missing deployment-generation suffixes, shortened prefixes, and trailers. A registration reply must match the captured leader, DNS session, and request ID before consuming the pending operation; generation zero explicitly reports failure. The leader prepares its reply buffer before the first Raft command and retains that allocation through activation or rejection. Local registration phases retain owned connections and reply authority, and use full-name local publication helpers. Service registration requires a live publication or attached connection; catalog-only fixture markers use the explicit event operation. Retraction still requires the exact owner and generation; failed encoding keeps the existing publication owner for its one-second protocol retry interval and exact-generation termination policy. Transport metadata, raw close-watch readiness, and other local scalar adapters remain separately qualified. See `docs/reference/dns-registration-relay.md`.

13.2.3.3 Retract only the captured generation

Retirement requires the exact registered generation and the registrar's or manager's authority. Endpoint death is confirmed through a retained watch before the matching publication is removed; lookup alone grants no retirement right.

Optional detail: Generation observation and retirement requests

Node-local generation observation and retirement now require the `CNSGEN01` frame under NS interface 2: exact total length, complete 1–256-byte name and explicit generation. Observation requires zero; retirement requires a positive generation and the exact registrar principal or a service manager. Retired scalar observation and packed-name retirement reject. Cleanup owns its accepted pending call, binds reply readiness to the CQ and carries its original five-second monotonic deadline into the reactor's earliest wait. Submission/storage rejection follows the existing fail-closed domain policy; rejected reply binding retains the accepted owner through abort. Timeout, rejection and wakes never permit replay or establish physical cleanup. Raw receive/transport adapters, other endpoint-close watches and broader cleanup contexts remain separate gaps. A lookup of somebody else's publication does not grant DNS retirement authority.

Optional detail: Endpoint-death watches and local retraction

NS now owns each registry connection and its persistent endpoint-death completion together, admitting the watch before policy mutation. It binds request intake to the same default CQ signaled by the kernel watches and waits event-only, rechecking lifecycle requests. A CQ entry is only a hint: NS confirms its retained watch's exact endpoint-close result before internally unpublishing the current full name and generation. Replaced watches cannot clear a new generation; caller registrar/manager checks remain. Cancellation precedes source disposal. Unexpected watch results or rejected CQ waits retain the registry through terminal abort, without claiming physical cleanup. The trusted NS constructor prepares 65 completion slots before threads/events for 64 live publications plus one replacement; ordinary launch budgets and normal node admission retain their existing policy. The native fixture observes both DNS-owned and Echo-owned names disappearing after death with read-only lookups. Raft completion and the publication scan still share one cleanup-submission claim for their captured episode. See `docs/reference/name-service-generations.md`.

13.2.3.4 Route queries through the leader

A follower forwards lookup and routing queries to the known leader. The leader answers only after its quorum-contact read barrier succeeds. Catalog and status dumps remain diagnostic observations.

Optional detail: Correlated query and catalog protocols

Lookup and call-routing decisions do not use follower-local catalog state. A follower sends a correlated query to the known leader, and the leader answers only when Graft's quorum-contact read barrier succeeds. Correlated query frames now use tags `0x24/0x25` and full 32-bit identity lengths, with a 4 KiB bound per caller, name, or returned owner. Missing lookup results retain an explicit empty owner and zero generation; identities are never shortened. Retired `0x12/0x13` frames, wrong tags, truncation, and trailing bytes reject. The follower prepares the complete request before publishing pending query state and carries the same deadline through that preparation. Source, session, query-ID, expected-leader, and generation checks remain required; readiness does not publish authority. Query failure returns a safely retryable `ERR_NOT_LEADER`; a timeout after remote execution may have begun remains `ERR_UNCERTAIN`. Raft time is supplied by a persistent detached-timer completion, preventing sustained endpoint traffic from freezing the lease clock. Catalog and status dumps are diagnostic local observations, not linearizable reads.

The catalog dump now uses one complete `CDNSCAT1` record set, bounded to 64 KiB, with explicit total length, row count, full identity lengths, and generations. A result above that bound rejects in-

Optional detail: Correlated query and catalog protocols (continued)

stead of returning a one-page prefix or shortening names. DNS retains one owned reply transaction through output allocation, mapping, and consuming publication. HTTP validates the whole set before rendering an array of rows, preserving replicas that share a name; unavailable or rejected catalogs render as `null`. Both node and cluster views resolve a fresh owned DNS connection per request, so a missed startup publication is not permanent absence. The separate registered-count field remains status metadata. See `docs/reference/dns-catalog.md`.

Optional detail: Local name-service status format

Local NS status uses the complete `CNSSTAT1` observation, bounded to 17,176 bytes for all 64 supported active publications. Its fixed header carries the exact total length, active row count, and number of retained lookup requests; each row carries a full 1–256-byte name and positive generation. Tombstones are excluded, and multiple pending requests for one missing name count separately. Retired `NSST` pages, inconsistent counts, partial sets, and duplicate or unsorted names reject before rendering. NS owns the incoming transaction, output mapping, and consuming reply; HTTP reports invalid or unavailable observations as `ns:null` and preserves every identity byte. This diagnostic listing supplies no application authority or physical cleanup proof. See `docs/reference/name-service-status.md`.

13.2.4 Distributed objects

At the top of the stack, applications use the same **capability** abstraction as local IPC:

```
let payroll: Capability<PayrollService> = lookup("Payroll")?;
payroll.call("calculate_salary", employee).await?;
```

The intended API hides whether a service uses local endpoint IPC or remote RPC. The implemented remote path is limited to the scalar DNS v4 call contract described above.

13.3 TCP/IP as a compatibility service

TCP/IP is provided by a userspace compatibility service. The frouter owns the NIC's deferred `OP_RECV` and routes IPv4 (`0x0800`) and ARP (`0x0806`) frames to the `tcpip` service's `OP_FRAME` ingress. A smoltcp `phy::Device` adapter consumes those frames and transmits through `OP_SEND`:

```
// smoltcp adapter (receive is fed by the frouter's OP_FRAME ingress):
fn receive(&mut self, now: Instant) -> Option<(IpPacket, ...)> {
    self.rx.pop_front() // frames queued by the tcpip service
}

fn transmit(&mut self, now: Instant) -> Option<...> {
    // Calls OP_SEND with a memory object.
}
```

The stack uses smoltcp 0.13. It runs in a userspace service registered as `"tcpip"` and serves clients through a socket protocol (`OP_SOCKET`, `OP_CONNECT`, `OP_BIND`/`OP_LISTEN`, `OP_ACCEPT`, `OP_SEND`/`OP_TRY_SEND`, `OP_RECV`, and `OP_CLOSE`). Software that requires TCP/IP connects to this service.

TCP/IP obtains fresh entropy before creating its interface and rejects startup if that entropy is unavailable. Ephemeral-port selection uses an independent 32-byte key, a nonwrapping counter and HMAC-SHA-256 over the fixed domain label and little-endian counter. It selects the same unbiased 49152–65535 range. The port helper now uses the shared erasing HMAC: key pads, hash state, intermediates and the digest have erasing owners. Initialization also owns its 40-byte entropy scratch before filling. Ordinary Drop erases those named fields; compiler/register copies, forced termination and physical-memory erasure remain separate. The change preserves the existing port sequence; public deterministic seeds appear only in opt-in validation, never production initialization. See `docs/reference/secret-state-lifetimes.md`.

`OP_ACCEPT` (15) retains the complete request until the listening socket reaches Established or CloseWait, then returns scalar zero without attachments. Listen and SynReceived remain pending; terminal states or explicit close return an error. `OwnedSocket::accept_call` can bind the accepted call to a CQ. `OP_TRY_ACCEPT` (5) is a separate immediate state observation used by the existing nonreactor callers. Deferred receive drains buffered bytes before reporting peer EOF. Deployment input uses these deferred notifications; HTTP keyhole input remains serial.

Deferred TCP `OP_SEND` (16) carries the full socket ID and one exact 4096-byte moved `CSOCKTX1` frame: eight magic bytes, a little-endian 32-bit length, four zero reserved bytes, 1–4080 payload bytes and a zero tail. Untagged, incomplete or extended frames reject. The complete request retains its read-only mapping through handshake or buffer pressure. A positive scalar receipt acknowledges one locally enqueued prefix. Only then may a caller submit its remainder. Terminal states and explicit close settle the request with an error; timeout or observation failure grants no replay authority. `OwnedSocket::send_call` returns the pending owner for CQ binding. Deployment response sends use it with an original five-second output deadline. The distinct immediate TCP/UDP operation `OP_TRY_SEND` (6) now uses that same exact frame and the full socket ID. `try_send_call` prepares the caller-owned frame; NTP and the smoke client use the same grammar. Its complete incoming owner retains the read-only mapping through one enqueue attempt, then releases mapping/backing before replying. It retains no send waiter. Retired untagged/packed pages reject without a low-half lookup or format fallback. Both operations carry 1–4080 payload bytes. A positive TCP prefix receipt permits the remainder; timeout or uncertain observation permits no replay. The NIC's send opcode belongs to a separate protocol. TCP/IP still progresses on its 50 ms timed reactor cadence; deferred receipts do not make the whole transport event-driven.

Reactor logical close uses `OwnedSocket::into_closing`, consuming the socket into `ClosingSocket`. It retains that socket and its accepted `OP_CLOSE` (8) call through CQ observation. Only typed scalar receipts Started (0) or Unavailable (1), without attachments, disarm the owner. Deployment ingress keeps its client position and one original five-second admission/observation budget until confirmation. Queue-full rejection permits 50 ms admission backoff; accepted close is never resubmitted. Uncertain failure or deadline retains the complete scope through domain abort. Incomplete operation Drop aborts before field cleanup, without another close. Unavailable identifies an absent full ID below the service's reservation watermark; it attests to no former owner or physical cleanup. Foreign live entries and unreserved IDs reject. Opaque serial reservations are consumed once by publication, including failed attempts. IDs never repeat within this connection's service incarnation; exhaustion rejects before backend allocation. Ordinary `OwnedSocket::close`/Drop now consume the same private typed lease and close owner. One original five-second budget covers admission and one checked pending-call wait. Queue-full rejection permits 50 ms admission backoff during the first second. Final unstarted rejection returns its actual IPC error and terminally retains the complete driver; Drop cannot start another close. Accepted timeout, rejected wait admission or invalid/service/ observation outcome aborts with the owner live. No scalar ID is restored. The shared Started/Unavailable decoder grants no physical or charge-refund proof. This policy remains synchronous in setup/shutdown destructors; whole-scope latency remains unqualified.

`OP_RECV` and `OP_STATUS` require one writable 4096-byte caller-supplied memory object moved into

the call. The reply returns that same backing; retained pages remain charged to the original allocating generation, including after a move or that sponsor's root closes. These paths allocate no TCP/IP-sponsored reply pages and reject missing or oversized buffers. An owning pending receive retains the request, buffer and transient mapping together; local mapping access ends before reply or cancellation. This removes the identified receive-retention starvation path without claiming aggregate principal/heap admission or complete hostile-network fairness. See TCP/IP caller-buffer audit.

Scalar-call admission exposes exact IPC errors. HTTP retains its existing `OwnedSocket` listener through `QUEUE_FULL` rejection and checks shutdown between retries. Socket close no longer restores an ID after accepted-call error or submits again from Drop. The one-second admission limit lies within its original five-second overall budget. Request deadlines and queue capacity remain unchanged. The HTTP test profile enables phase traces. Failed packet captures and scoped pressure validation are recorded in `docs/reports/audits/2026-10-10-security-http-progress.md`; broader flood fairness remains open.

Deployment ingress shares owned listener preparation and retains its listener through queue-full accept rejection. Bounded request storage grows fallibly; completed POST bodies transfer their backing without a second body allocation. Static 400/503 responses handle framing/allocation rejection. Its five-second header and thirty-second total deadlines remain unchanged. Shared node-identity initialization writes only after exact successful object creation; a losing creator waits for complete owner publication without weakening shared-read ownership. Scoped readiness observes namespace generation metadata without receiving invocation authority; legacy lookups remain denied. The bootstrap catalogue admits a bounded 32 KiB verification stack through its existing account. Signed release/readiness validation and retained failed runs are in `docs/reports/audits/2026-10-11-security-deployment-ingress.md`.

NIC and frame-router publication retain the same owned endpoint through delegated queue-full rejection with a 1000 ms submission retry budget. Accepted calls are observed once. NIC startup publishes its first failure category/detail; the earlier AMD exit remains unattributed. Explicit NIC endpoint close returns any rejected owner for terminal retention. See `docs/reports/audits/2026-10-12-security-network-publi` `md`.

TCP/IP, time, cluster control, reliable messaging and discovery share that admission policy. Accepted registration observation has a separate five-second deadline; timeout cancels the pending owner without replay and does not prove that remote publication never happened. Discovery and reliable messaging retain typed endpoint owners throughout their reactors. General dependency/controller progress remains separate. See `docs/reports/audits/2026-10-12-security-publication-deadlines.md`.

The service allocates its smoltcp socket table once at launch. Its launch manifest supplies bounded `sockslot`, `sockquot`, and `bufquot` policy values; the defaults are 64 total slots, 64 sockets per authenticated domain, and 2 MiB of TCP/UDP buffers per domain (policy ceilings are 1024, 1024, and 32 MiB). The effective socket capacity is clamped to the heap granted to the TCP/IP domain, so a normal 4 MiB domain remains at 64 slots while a larger launch budget can support more. The current virtual layout yields roughly 140 TCP-sized slots at its maximum heap window; reaching 1024 concurrent TCP sockets requires moving that window or using shared buffers outside the domain heap. DHCP consumes one table slot, so application capacity is derived from the actual table rather than from a second hard-coded limit. Every request is received through the authenticated IPC envelope, and each socket is owned by the sender's address-space generation and artifact principal. Other domains cannot operate the socket, and their socket and buffer allocations cannot exhaust a neighbour's quota. These are service-side quotas; the backing pages remain part of the TCP/IP domain's memory accounting until the socket is released. The status snapshot exposes the configured capacity and quotas. Reclaim on domain death remains an explicit lifecycle integration point; generation checks prevent stale access while that notification path is completed. Graceful closes are reclaimed when smoltcp reaches a terminal state; a peer that leaves a connection in FIN-WAIT/TIME-WAIT is force-aborted after a bounded five-second grace period. This keeps reconnect churn from pinning a do-

main's quota indefinitely. Admission retries use bounded backoff and rate-limited diagnostics so temporary pressure does not flood the service log. Kernel launch code can select a different bounded policy through `launch_network_appliance_with_policy` where ordinary boots use these defaults.

The architecture runners attach a NIC by default. Hardware discovery starts the driver and frame router, followed by discovery, cluster services, and the DHCP-configured TCP/IP service. The `-no-network` option explicitly selects an isolated boot. Options ending in `-test` add verification workloads and result reporting; they do not enable the runtime services.

13.4 Cluster-wide TCP ingress and direct server return

Charlotte can expose a bounded table of launch-authorized IPv4 TCP services as cluster `VIP:port` identities. This gives clients two complementary addressing modes. A node's DHCP or static address names that machine and suits intentionally node-specific traffic. A VIP names a service in the cluster, so the client need not know which node admits the packet or owns the connection. Those roles can change without changing the service address.

Direct Server Return is often introduced as a load-balancing technique, and Charlotte uses it to distribute five-tuples across eligible execution nodes. It also provides a cluster facade: the stable external identity belongs to the service, while node addresses and MAC routes remain internal placement and delivery details. The VIP thus lets clients address the cluster as a whole.

One such platform identity can front the cluster observability keyhole. Its DSR advertiser normally follows leadership, while any eligible member may serve a fresh applied cluster snapshot and identify itself in the reply. The consistency and access-control contract is described in Section 17.7.4.

The frame router does not proxy the TCP stream. It parses the external frame's five-tuple and uses deterministic rendezvous hashing to select an execution node. A local winner follows the ordinary `OP_FRAME` path into smoltcp. For a remote winner, the router changes the Ethernet delivery into a compact one-hop Charlotte envelope and moves the same memory object back through `net::OP_SEND`. The envelope carries the original source MAC and EtherType; the selected backend validates the outer source against its committed member routes and removes the envelope in place. IP, TCP options, sequence numbers, and payload bytes remain unchanged. The backend smoltcp instance owns the only TCP state and sends its VIP response directly to the client.

Eligibility comes from the DNS-owned Raft member's committed configuration, with discovery supplying the associated MAC routes. DNS materializes an immutable snapshot that distinguishes admitted members from those eligible for new flows. The router refreshes this snapshot asynchronously; consensus never runs on the packet path. During joint consensus, only voters common to the old and new sets accept new flows. A joiner therefore waits for finalization, while a departing node is removed from the committed projection promptly. The router adopts the change after a successful refresh.

An operator-signed, committed node-shutdown intent removes its target from new flow selection before local teardown, while retaining its route for observed flows during the grace interval. Each service has an independent load-balancing epoch: a stable fingerprint of the committed configuration index, service name, deployment and registration generations, ready-node set, and replicated drain generations. Each router retains four recent sets and a bounded 1,024-entry `FlowKey` $\rightarrow$ `epoch` table. Existing connections retain their epoch across additions; when a backend is removed, only bindings that selected it are released for reconnection. Because rendezvous selection is independent of member ordering, a replacement participant with the same epoch makes the same choice without shared connection tracking.

A complete refresh grants a five-second monotonic lease for VIP advertisement and unbound-flow admission; the normal one-second poll renews it. A failed or incomplete refresh may leave the last complete snapshot available to existing bindings, but lease expiry suppresses ARP replies and rejects unbound traffic. DNS answers a refresh only while the local Raft state has current cluster evidence: a leader has recent quorum contact, or a follower matched and applied its recognized leader's log within the previous second. Rejected replication does not renew this witness. Source evidence therefore expires within one second of lost contact, followed by at most the router's five-second admission lease. Snapshot history and flow bindings are bounded independently. If a live binding names an epoch that has left history, it remains as a fail-closed tombstone and its packets are dropped rather than reinterpreted through the current snapshot. Ordinary flow-table pressure can still discard old local state, an availability limit that cannot be eliminated without shared connection tracking or additional packet metadata.

VIP acceptance and advertisement are separate. Every participating node installs each configured VIP as a `/32` smoltcp address, while DSR admits new flows only to ready backends. One admitted, non-draining ingress participant answers VIP ARP requests. It normally follows the current Raft leader and need not run the application. A newly selected advertiser emits gratuitous ARP, so ingress ownership can move without changing backend membership. No node advertises a VIP when its backend set is empty. The current launch-manifest transport supports 16 IPv4/TCP service assignments and the packet policy supports at most 64 admitted members; IPv6 neighbour discovery, a service-only drain operation, automatic failed-member removal, and transparent TCP-state migration are future work. The precise bounds, failure semantics, and status fields are documented in `docs/architecture/distributed-l2-ingress.md`.

The operations-owned bootstrap policy may bind each VIP and TCP port to a deployed application name. DNS evaluates each assignment independently, intersecting admitted membership with the application's committed replica set and exact-generation readiness registrations. After movement or replacement, the stale generation is excluded from the derived eligibility set; that set remains empty until the target node publishes the matching generation. Routers keep separate leases, histories, and flow bindings for each service and adopt new results after a successful refresh. Retained epochs continue to route observed flows during the drain window. Omitting the application name preserves the platform-service policy in which every admitted, non-draining member serves the platform service. Fixed replica counts and *every eligible node* placements widen a service's backend set as agents publish readiness. A leader-side controller reconciles automatic assignments after membership or drain-state changes. The runner accepts repeatable `-cluster-service [NAME=]VIP:PORT` options. The paired name flag and singleton VIP/port/name build variables are retired. Builds consume only the semicolon-separated `CATTEN_CLUSTER_SERVICES` table. Address-specific socket binds allow distinct VIPs to use the same conventional TCP port.

The bootstrap table ceases to be authoritative after the first committed ingress policy. The variable-length `CINGPOL1` envelope binds a complete replacement table, monotonic sequence, cluster identity, and UTC validity interval under the independent operations signing key. It may enter through any member; the leader re-verifies the signature and trusted UTC before proposing it to Raft. Exact retries are idempotent, stale or conflicting sequences fail, and an empty signed table withdraws all VIPs. Catalog-v17 snapshots retain the envelope and replay fence. DNS serves the applied table, frame routers reconcile service state by stable packed identity, and TCP/IP reconciles its `/32` addresses without restarting nodes. Applications using exact-address listeners poll their typed assignments and rebind after an address change.




Figure 13.1: Cluster management supplies DSR with an exact-generation eligible-backend set; packet steering remains outside the consensus path.

Figure 13.1 separates the replicated control loop from the packet path. Signed policy and committed membership determine desired placement, node agents contribute exact-generation readiness, and DNS derives the immutable epoch snapshot consumed asynchronously by the frame router. DSR then chooses only among authorized ready replicas; the selected replica owns TCP and replies directly. An empty ready set suppresses VIP advertisement. The joint TLA+ model in Section 22.4.15 checks this control-plane-to-packet-path composition. It records counterexamples for router-freshness and history regressions, both of which the implementation rejects.

Operational Vote, AppendEntries, and InstallSnapshot RPCs use private EtherType `0x88b7`, while admission and DNS application/control traffic remain on the reliable-message layer. Joining durably fences and resets the standalone consensus history before accepting the selected anchor's log. Append retries that overlap a compacted snapshot skip the compacted prefix; they cannot duplicate it behind the retained suffix. Forwarded data frames use EtherType `0x88b8`. This is an isolation marker rather than cryptographic link authentication, so the first version assumes a trusted or administratively isolated cluster L2 segment.

The host-visible `scripts/run-distributed-ingress-test.sh` fixture forms a stable three-voter cluster, establishes flows across all three backends, kills the Raft leader and VIP advertiser, observes the replacement's gratuitous ARP, and completes an HTTP request over a surviving established flow. It then opens fresh five-tuples and requires another HTTP exchange with a live backend, covering reconnect after the failed advertiser also took one backend connection with it. Failed voters are not removed automatically, so some new hashes may continue to select the failed node until an explicit committed membership change removes it; the recovery probe therefore tries a bounded family of new flows.


13.5 UTC time as an internal service

The userspace `time` service is a client of the TCP/IP socket API. It waits for local boot readiness and a nonzero DHCP address, then samples an NTPv4 server over connected UDP. It calibrates the monotonic counter, estimates drift and uncertainty across samples, prevents time from moving backwards within a service lifetime, and persists calibration in the object store for holdover.

Applications do not speak NTP. They resolve `"time"` through the local name service and call its endpoint protocol for a full snapshot, scalar Unix seconds, or a fixed-width UTC ISO 8601 value. Synchronization state and uncertainty are explicit so callers can reject unsynchronized or weak holdover time. This service starts during an ordinary networked boot; no test option is required. The detailed wire contract and security limitations are recorded in `docs/reference/time-service.md`.

13.6 Capability-scoped external data services

CharlotteOS provides narrow S3 and Kafka compatibility services on top of the userspace TCP/IP stack. They preserve the capability model at the application boundary while communicating with conventional external systems:



An application receives neither a generic network capability nor the remote credentials and protocol state. Each service instance is provisioned with one bounded profile, and its connection grants only that profile's endpoint, namespace, and operation rights. Application-side helpers build on `catten_rt::owned`: moved memory pages carry payloads, and every remote stream, delivery, consumer, or transaction has an explicit consuming teardown with a best-effort `Drop` fallback.

These services are not launched unconditionally. A trusted provisioning path must supply their profiles, including secrets and trust anchors. The `-s3-test` and `-kafka-test` runner options create disposable Docker fixtures, generate short-lived test certificates, launch test profiles, and add guest verifiers. They validate integration; production provisioning does not conceptually depend on those switches.

13.6.1 S3 client service

One `s3` service instance is fixed at launch to an IPv4 endpoint and DNS name, port, region, bucket, key prefix, credential identity, optional Dell EMC ECS namespace, and a GET/PUT/DELETE rights mask. Applications use keys relative to the granted prefix. The service rejects absolute paths and `./..` path segments, constructs path-style S3 requests, and signs them with AWS Signature Version 4. The secret key remains inside the service address space.

The data plane provides streaming GET and PUT, HEAD, DELETE, ranged GET, and create-only PUT. Object bodies cross the application boundary as moved, bounded memory chunks; response metadata includes length, ETag, version ID, and request ID. The HTTP/1.1 adapter accepts fixed-length and chunked responses. Bucket listing, multipart upload, presigned URLs, automatic region discovery, and a general AWS API are outside the current scope. The profile format reserves a LIST right, but no LIST operation exists yet.

TLS profiles require an explicit DER trust anchor, a matching server name, system entropy, and synchronized UTC from the time service. Certificate verification or entropy failure aborts the connection; there is no downgrade to plaintext. The S3 request date also comes from synchronized UTC, so a TLS or signed request fails closed while the clock is unsynchronized.

The AArch64 integration test starts RustFS behind verified TLS and performs a PUT/HEAD/GET/DELETE round trip. The same client API is intended for centrally managed S3-compatible stores. The optional `x-emc-namespace` header specifically supports Dell EMC ECS namespace profiles, but ECS interoperability has not yet been runtime-qualified in this repository.

The transport-independent Signature V4 and HTTP code lives in `crates/charlotte-s3`, the application protocol in `crates/charlotte-protocol-s3`, the owned client in `crates/catten-services/src/s3_client.rs`, and the service adapter in `crates/catten-services/src/bin/s3.rs`.

13.6.2 Kafka client service

One `kafka` service instance has a stable profile-selected identity and grants access to at most 32 explicitly provisioned broker endpoints, a fixed consume topic/partition, an ordered allow-list of produce routes, a consumer group, a transactional ID, and a connector rights ceiling. It owns the broker socket, producer IDs and epochs, per-route sequence numbers, and consumer-group membership. Applications can produce idempotently, open a fixed-partition group consumer at the group's committed offset (or the earliest retained offset), poll with `read_committed` isolation, commit or release a delivery, and close the consumer.

The complete version-7 broker profile is serialized into one immutable object, covered by a SHA-256 integrity digest, and transferred to `kafka` with a kernel-enforced `MAP_READ`-only launch capability. Typed capability metadata carries the exact meaningful byte length rather than overloading a generic flags field. The service validates the size, version, digest, UTF-8 DNS host-label syntax, field bounds, route and broker counts, configurable ceilings, and duplicate routes or endpoints before opening a broker connection. The hard ceiling is 64 produce routes, while deployment policy may select a lower limit. Metadata for all distinct declared topics is requested in one broker exchange. The digest detects corruption; authenticity and provenance come from the trusted launcher and the read-only capability.

The kernel prepares a profile-backed launch transactionally. An owning launch object retains the not-yet-running domain, delegated connection, and transient kernel profile object until read-only transfer succeeds. Ordinary rejection consumes explicit cancellation after helper guards leave. Cleanup stops on its first failure, retaining remaining roots, profile, and authority; abandonment retains the complete transaction without a second destructor cleanup pass.

The fixed 112-byte `CHKAFP7` header declares one authentication choice: none, SCRAM-SHA-256, P-256 mTLS, or both. Four explicit lengths delimit the username, password, client certificate, and private key; fields for disabled mechanisms must be empty. Unknown choices, missing required material, retired profiles, and trailing data reject before broker connection. The encoder returns the complete frame under an erasing owner, installed before copying borrowed credentials. The launcher borrows that owner through profile memory preparation; no separate credential-section allocation is needed. The profile and authentication types omit aggregate Debug formatting. Individual fields and output bytes can still be copied or logged. Authentication policy and secret ownership remain behind the connector's read-only launch capability. The profile has no optional authentication sections or compatibility fallback.

Kernel operational launch validates through the shared borrowed profile parser, using 3840 bytes of fixed list scratch with a 4096-byte compile-time ceiling and no heap allocation. Credential bytes remain borrowed. Userspace decoding materializes its three vectors only after complete validation. The full 64 KiB frame and existing route, broker, and authority limits remain unchanged.

The same digest covers a non-empty printable-ASCII instance name and a bounded set of separately published authority endpoints, whose names are each at most 256 bytes. Every endpoint carries a Kafka-rights ceiling that must be a subset of the connector ceiling. The service maps every received opcode to its required produce, consume, and transaction rights and rejects a missing right before decoding request memory or creating resources. A producer-only capability therefore cannot open a consumer or transaction even when the same connector also publishes a transactional endpoint. Short names use the scalar name-service path and longer names use its copied-memory path. Applications cannot create or rename access points through the Kafka ABI.

Only the broker-facing service receives this profile. Producer, consumer, and transactional-step logic receives a connection capability to one provisioned authority endpoint, never its broker address, trust material, SASL/SCRAM credentials, or mTLS identity. Credential rotation can therefore replace the connector profile without rebuilding application or procedure artifacts.

The transaction owner supports the consume–transform–produce path. An application can produce records, move one consumed delivery's next group offset into the same Kafka transaction, and then commit or abort. Committing consumes the transaction resource; dropping an unfinished transaction attempts an abort. Dropping an uncommitted delivery releases it for redelivery rather than silently advancing the group offset. These linear owners make the local lifecycle explicit. They do not make arbitrary application side effects outside Kafka part of an exactly-once transaction.

The connector joins its configured group with the bounded `charlotte-fixed-v1` assignor. Each member advertises exactly the topic/partition authorized by its immutable profile. The group leader assigns each partition once; duplicate connectors remain heartbeating standbys with an empty assignment and can take ownership after membership changes. One connector admits one local consumer because it owns one membership. Ordinary offset commits carry the active generation and member ID. Transactional offset commits use Kafka's flexible version-3 schema and carry the same fencing identity. A rebalance revokes outstanding deliveries, aborts a touched transaction, synchronizes the new assignment, and reloads its committed offset before polling resumes. The service loop uses monotonic deadlines to heartbeat even without application calls. Conventional consumers that do not advertise this assignor cannot share the group.

The connector's bounded status page reports metadata refresh count and age, reconnects, retries, terminal failures, fences, group state, consumer lag, and cumulative records per route. Monitoring derives throughput by sampling these counters; ordinary application capabilities do not expose the operational view.

For procedures that only implement business behavior, the generic `kafka_step` service owns that lifecycle instead. Its separate, read-only profile names one connector and one procedure endpoint, admits only specific output-route indices, identifies the DLQ route, and bounds output count, attempts, timeout, backoff, and polling. The procedure receives borrowed input bytes and an attempt number but no Kafka capability. The runner validates the complete output batch before beginning a transaction, produces admitted records, includes the input offset, and commits. Retry replies and procedure timeouts release the delivery for redelivery; terminal or malformed replies and retry exhaustion transactionally copy the original record to the DLQ. Transport and commit failures abort and redeliver without consuming the business-attempt budget. One owning operation aggregates the call, input memory, delivery token, and transaction, so cancellation and early-return cleanup follow the owned-resource rules rather than a manual cleanup ladder.

The wire crate negotiates `ApiVersions` and implements a deliberately small set of stable Kafka request versions. Metadata selects partition leaders and group/transaction coordinators only from the profile's hostname/port and IPv4 allow-list. Authorized endpoints are alternate metadata seeds, and retriable produce/fetch failures refresh leader metadata before retry. Group and transactional operations rediscover a moved coordinator within a bounded retry budget. The service does not implement topic-pattern subscriptions, cooperative assignor interoperability, client-certificate chains, record compression, topic administration, or arbitrary partition assignment. Records and the number of simultaneous consumers, deliveries, and transactions are bounded.

TLS uses the same explicit trust-anchor, synchronized-time, and entropy path as S3. Optional SCRAM-SHA-256 authenticates `kafka` to every selected broker after TLS establishment. Optional mTLS uses one DER X.509 client certificate and an ECDSA P-256 private key; both mechanisms may be required together. The bounded SCRAM exchange validates broker challenges, minimum and maximum iteration counts, and the server signature. Passwords, client private keys, and derived keys use zeroizing owners and remain outside the application ABI.

The shared transport now uses pinned Embassy-based TLS and crypto-driver revisions. Startup transfers its dedicated owned entropy connection into a one-shot domain context before publishing TLS/SCRAM consumers. Each entropy operation checks that owner out, releases its metadata guard, and retains the connection through RPC, returned-memory mapping and copy. Ordinary completion returns the same owner.

Duplicate installation returns the new owner; busy checkout rejects without waiting on an outstanding RPC. Architectural-only randomness requires explicit installation. No borrowed launch connection is stored globally.

Entropy requests now carry one positive startup-configured observation budget, default `5000` ms, with their source. One consuming read retains its pending call and source/output borrows through timeout or wait-admission rejection; completion owns returned resources and mapping. Exact byte counts and memory without a connection attachment are required. Late results are disposed, and explicit cancellation returns its complete owner if rejected. Timeout, submission and exact observation rejection remain distinct; none grants replay or device-quiescence authority. RNG interface version 2 uses opcode 2 and an exact caller-moved buffer, currently one 4096-byte page. The service fills and returns that object; no producer-allocated reply fallback remains, and retired scalar opcode 1 rejects. Returned or unobserved backing keeps its original caller charge through sponsor retirement. The shared server transaction ends mapping access before reply or loan cancellation. Dependency lookup, kernel cleanup latency, queue/metadata pressure and authorized flooding remain separate audit work. The bounded DNS boot-nonce collection also uses this client, with one 100 ms deadline for lookup and fill. See the entropy protocol reference.

The RNG server binds its request endpoint to the default completion queue before using shared bounded publication. With no queued request it parks on event-only CQ readiness, rechecking lifecycle and endpoint state after every wake; no idle 10 ms timer remains. Rejected publication/binding/wait aborts with the device and endpoint owners live. This does not replace the bounded hardware-status poll or establish hardware shutdown or uncertain-descriptor recovery.

The descriptor owner now arms terminal retention before queue mutation and requires the exact next used index, descriptor zero and valid length before advancing. Short completions continue only confirmed progress. Timeout or a backend fault retains the complete MMIO/CPU/DMA fields and captured attempt; later calls cannot touch hardware, even after a late completion. Checked completion survives later copy failure. Retained fallback runs no nested destructors. A fenced shutdown keeps device, endpoint and shutdown request without reset, unmap or a device-quiesced acknowledgement. This fences reuse; real hardware recovery and the ordinary healthy-shutdown path need separate qualification. See the descriptor contract.

One nonblocking handshake admission owns the static verification clock through completion. Overlap rejects before changing the clock, and completion clears it. mTLS retains typed P-256 SEC1 validation and constructs its Embassy signing key from a zeroizing scalar temporary. A missing source rejects before the handshake; failure inside the infallible RNG callback stops the domain rather than inventing bytes or replaying an accepted entropy request. Host randomness exists only in the unit-test source. Exact revisions and contracts are in `docs/reference/tls-client.md`.

The sole registered Embassy AES-GCM driver retains the previously qualified erasing cipher context; the pinned stock driver would retain a plain key array. The SHA-256/HMAC-SHA-256 drivers likewise use the shared erasing hash owners through opaque Drop/Clone forwarding, including unfinished contexts. Normal and test dependency graphs exclude duplicate stock registrations; link-time symbol collisions reject their reintroduction. Returned digest/tag arrays, other hash families and enclosing key-schedule fields retain separate lifetimes. The shared TLS dependency enables erasure of AES expanded round keys on ordinary cipher Drop, with build-time checks for its AES-128 owner types. GCM authentication-key scratch also erases after construction. The current AArch64 software POLYVAL backend clears its state on ordinary Drop; its build guard rejects a backend without a destructor, including optional PMULL. The freestanding x86 target now selects that same erasing software state instead of the pinned non-dropping dispatcher. Its production guard rejects a missing backend flag or erasure feature. This disables PCLMUL authentication acceleration; the TLS cipher and AES selection remain unchanged, and throughput impact is not qualified. Hosted x86 outside this target policy, TLS traffic keys, IVs, HKDF state and compiler copies need separate work; complete-session or physical-memory erasure is not established.

The SCRAM exchange uses consuming phases. Username escaping writes directly into the reserved erasing initial transcript, without a separate scratch string. The initial phase owns its password and nonce copies; processing the server challenge releases both on success or rejection. One final phase owns the proof and expected server signature through success or rejection. Neither phase can be reused after its consuming transition.

The opt-in AArch64 test uses a three-broker Apache Kafka fixture over TLS with required mTLS and SCRAM. It places three-replica input and output routes on different leaders and verifies idempotent production, read-committed consumption, atomic production plus generation-fenced group-offset commit, group generation advance and heartbeat, transaction abort, filtering of the aborted record, and the generic step runner's success, retry, timeout, and terminal-DLQ paths. It also checks metadata refreshes, terminal authorization errors, output-route production, coordinator refreshes, and non-negative consumer lag in the bounded status page. After initial route discovery, the host hard-stops the output-route leader, keeps it down beyond the connector's bounded receive timeout, and restarts it. The verifier requires a routing retry and a second successful metadata refresh, so the result demonstrates replacement-leader recovery rather than merely steady-state multi-broker connectivity. The fixture selects group and transactional identifiers coordinated away from the killed broker, isolating partition-leader recovery from the separate coordinator-migration case. Because broker exchanges are currently synchronous, the connector requests a 45-second group session while heartbeating every two seconds. The membership lease therefore exceeds bounded dead-peer detection and route refresh, so recovering a partition leader does not by itself expire and fence the transaction's group generation. A companion fault scenario reads the transaction coordinator selected by Kafka from the connector's startup diagnostics and hard-stops that broker after connector bootstrap. It requires transaction-coordinator rediscovery before the same transaction and generic-step sequence may pass. A fencing scenario launches a second, independently named connector with the same transactional identifier. Kafka advances the producer epoch; a private probe then requires the stale connector to return `ERR_FENCED`, publish a non-zero fencing counter, and enter its diagnostic fault state. Neither the second connector capability nor either connector's credentials are delegated to the probe.

The bounded Kafka wire implementation is in `crates/charlotte-kafka`, the application protocol in `crates/charlotte-protocol-kafka`, the linear client owners in `crates/catten-services/src/kafka_client.rs`, and the broker adapter in `crates/catten-services/src/bin/kafka.rs`.

13.7 Transport independence

The reliable-message interface is designed to be transport-agnostic. Candidate transports include:

- Ethernet: for inter-machine communication.
- Shared memory: for co-located processes on the same machine, where the kernel can set up shared memory regions instead of going through the NIC.
- Loopback: for same-machine same-stack communication.
- RDMA: for high-performance cluster interconnects.
- PCIe NTB: for backplane communication in multi-socket systems.

The RPC layer and everything above it should remain unchanged across these transports. The same principle makes local IPC transparent when communication moves from within a process to another machine.

13.8 Zero-copy networking

The intended network stack avoids copying whenever practical:

- Receive path: the NIC driver receives a buffer from hardware. That buffer (a memory object) is passed up the stack by transferring ownership: first to the message layer (for reassembly), then to the RPC layer (for deserialization), then to the application. No intermediate copies.
- Transmit path: the application creates a buffer. It is passed down by moving ownership. The NIC driver DMA's it directly from the application's pages.
- Buffer recycling: after the application consumes a received buffer, it returns the (now empty) memory object to the driver's RX pool. The driver reuses it for DMA and the cycle repeats. IOMMU-backed pinning is implemented with AArch64 SMMUv3 and x86-64 VT-d/AMD-Vi.

This is the memory-object transfer model (Chapter 6) applied to networking.

13.9 Network authority and transport

1. Remote invocation follows the local call shape: the target API keeps transport choices out of application protocols. This permits:
   - Services can be relocated without application changes.
   - Testing can substitute a local mock for a remote service.
   - A common interface can reduce environment-specific application code, although the network boundary still introduces failures absent from local IPC.
2. Service access requires authority: an application invokes a service capability rather than relying on `host:port` reachability. Network access alone does not mint that capability.
3. Copy avoidance is a design goal: page ownership transfer can avoid intermediate payload copies. CPU mappings are MMU-enforced; DMA isolation uses SMMUv3, VT-d, and AMD-Vi. A performance comparison with conventional sockets remains to be established.
4. Message boundaries are preserved: the native abstraction is a message with identity, ownership, metadata, and boundaries. There is no need for an additional stream-framing layer. This can simplify protocol implementations, but does not eliminate parsing or framing defects.
5. TCP/IP is available but not mandatory: legacy software connects to the TCP/IP service. Native software uses the capability-based stack. The transition is incremental: a service can expose both a native endpoint and a TCP/IP socket through the compatibility service.

14 Consensus and Replication

CharlotteOS exposes distributed consensus as a capability service: a replicated state machine reached through the same endpoint IPC used by local services.

Validation covers several scales. Unit tests exercise quorum accounting with up to five configured voters, while TLA+ safety models exhaustively explore three-node elections and membership transitions within their bounds. QEMU fixtures cover single-voter NVMe recovery, focused two-guest catalog and deployment paths, and three-guest discovery, membership, and ingress failover. These are validation topologies; the Raft membership representation and quorum logic are generic.

Each operational node runs exactly one durable Raft member inside `dns`; membership, names, deployments, keys, and cluster events share that member's ordered log. Multi-guest admission observes it through discovery and exercises `JOIN`, joint consensus, and `FINALIZE`. The separate `raft.elf` process is network-disabled and retained only by the NVMe term-recovery fixture. Power-loss behavior within a live quorum is not yet validated end to end.

The core follows the shared Graft model for normalized peer identity, voters and learners, joint-consensus quorums, replicated `JOIN`/`JOINT`/`FINALIZE` commands, leader no-op entries, current-term commit rules, linearizable-read contact quorums, and membership-bearing snapshots. These paths have focused regression tests. The `dns` service exposes both client commands and membership administration end to end through one concrete state machine and log.

14.1 Raft as a capability service

The Raft consensus protocol provides a replicated, fault-tolerant state machine across a cluster of nodes. In CharlotteOS, the operational Raft node is owned by the per-node DNS EL0 process, which:

- Registers the DNS endpoint and a `"raft-<id>"` administration/status endpoint backed by the same in-process node.
- Learns transient peer MAC routes through discovery; voter authority changes only through committed membership commands.
- Carries VoteRequest, AppendEntries, InstallSnapshot, and admission messages through the reliable-message service.
- Uses completion-queue waits for time: a bounded `checked CQ wait` drives election and heartbeat checks without a detached timer completion or a busy polling loop.
- Applies membership commands and DNS catalog commands to the same durable log and state-machine snapshot.

The Raft core (`catten-graft`) is a generic, transport-agnostic library. It implements the `RaftTransport` trait, which abstracts peer communication behind a few methods:

```
trait RaftTransport {
    fn send_vote_request(&self, request: VoteRequest);
    fn send_append_entries(&self, request: AppendEntries);
    fn send_install_snapshot(&self, request: InstallSnapshot);
    fn poll_completions(&self) -> Vec<RpcCompletion>;
}
```

The operational CharlotteOS implementation uses the reliable message layer between DNS replicas; the consensus core does not change.

14.2 Intended properties relative to socket-based Raft

14.2.1 Peer access through capabilities

Once the cluster is running, committed peer identities resolve through the name service. A joined node receives connection capabilities for the current voter and learner set:

```
for peer_name in committed_members {
    let peer = name_service.lookup(peer_name)?;
    transport.install(peer_name, peer)?;
}
```

The capability carries communication authority; an IP address alone does not.

14.2.2 Transport transparency

The transport is behind the `RaftTransport` trait. A connection capability routes through local IPC (same machine), Ethernet frames (same network), or a future RDMA transport (high-performance cluster). The consensus core does not change. This permits:

- Development and testing can run a multi-node Raft cluster on one machine with local IPC.
- Deployment can switch to cross-machine networking by changing how peers are resolved without changing the Raft code.
- The cluster can be heterogeneous: some peers communicate via shared memory, others via Ethernet.

14.2.3 Zero-copy log replication

Locally, log payloads can transfer via Move memory objects: the kernel flips page-table ownership instead of copying bytes. A follower that receives a Move attachment gets the same physical pages the leader held, without an intermediate buffer or copy.

The current local transport uses one moved page per RPC and batches the largest AppendEntries prefix whose protobuf encoding fits. This is a 4 KiB transport attachment limit. Persistent objects and Raft logs have separate limits. A network transport can use different framing without changing the protobuf contract.

14.2.4 Capability-based security

A client invokes the Raft service only if it possesses a connection cap. The service manager attenuates rights: a typical client receives only `CALL` for `OP_CLIENT_COMMAND`. Membership changes through `OP_ADD_SERVER` or `OP_REMOVE_SERVER` require separate rights. Network reachability alone grants neither right.

14.2.5 Failure isolation

Each DNS/Raft replica runs in a separate protection domain. A crash in one node does not affect the others. The isolated storage fixture demonstrates recovery of term/vote state across explicit process teardown and restart; restarting a DNS replica and recovering its catalog inside a live quorum remains future integration work. The generic service lifecycle separately demonstrates that stale connections fail and clients can relookup a replacement generation.

14.3 Persistence and launch configuration

The operational DNS node requires persistent storage. One jointly opened pair of stable objects derived from cluster/node identity holds tagged `CRFTSTA4` term/vote/join-admission state and `CRFTLOG4` snapshot/log state. Only two absent objects authorize initialization; incomplete, corrupt and unsupported records reject without reset or a volatile fallback. Older layouts are not migrated. Mutations are followed by an NVMe flush; snapshot bytes and their retained suffix share one record replacement. There are no production stores to migrate now. Future deployed-store format changes must ship an explicit, interruption-tested migration preserving election, admission and committed state. See `docs/reference/raft-persistence.md`.

The catalog accepts only its complete version-19 snapshot, identified by `CATALOGJ`. It retains mandatory execution profiles and per-replica signed variant indices, without redundant object IDs, primary nodes or variant-zero digests. Earlier snapshot decoders and synthesized generations, digests, descriptors, replica sets and authorization signatures are removed. Every registration command carries an explicit deployment generation: zero for system services, or the exact desired generation for applications. Missing suffixes reject before catalog mutation; all callers use one encoder. Pair-v4 and catalog-v19 tags reject earlier logs and snapshots before replay. The current catalog also persists a bounded ingress-availability projection: generation, leader term, membership epoch, leader identity and eligible voters. The leader derives it from recent successful replication of current-term entries and publishes it through the same quorum log. A term or membership mismatch fences the projection until a replacement commits. Availability does not remove a voter, authenticate a peer or prove quiescence. Unsupported or malformed application snapshots reject explicitly before Raft publishes snapshot progress or membership. Recovery stops on rejection; network installation returns failure and retains the existing applied state. See `docs/reference/catalog-snapshots.md`.

The cluster mnemonic and election timeout remain in the launch manifest. A fresh identity bootstraps as a durable singleton. Discovery supplies MAC routes, the lexicographically larger singleton applies to the smaller anchor, and active membership changes only through the Raft log and snapshot envelope. The distinct storage fixture verifies one generic node across process restart. Focused two-guest tests cover catalog and deployment exchanges, and the three-guest ingress fixture covers discovery-driven admission, leader failover, and continued cluster operation. None of these fixture sizes bounds membership.

14.4 Cluster bootstrap: the seed problem

A new node must contact at least one existing cluster member. CharlotteOS expresses the seed as a service name or capability rather than an IP address.

14.4.1 Ethernet discovery and deterministic admission (current)

Probes and responses carry one complete version-1 advertisement: node identity, service name, cluster role and Raft/leader IDs. Its header declares the exact payload length. Old zero-length headers and missing or truncated cluster fields reject before learning or response; Ethernet padding cannot synthesize them. All nodes must rebuild together. The current wire contract is documented in `docs/reference/discovery-protocol.md`.

Nodes broadcast their durable identity on the local Ethernet segment. DNS records every discovered identity-to-MAC route in its relmsg transport. Among fresh singletons, only the lexicographically larger identity applies to the smaller anchor. Before sending the request it durably enters a non-voting joining posture; the anchor then commits `JOIN`, catches the node up, commits the joint configuration, and finalizes it.

14.4.2 Pre-shared cluster capability (small kernel change)

A cluster administrator provisions a connection to a known cluster member as a "cluster capability" and delivers it to new nodes via the config page. No name lookup required; the node already holds a first-class connection.

14.4.3 Ethernet broadcast discovery (zero-configuration)

On a single Ethernet segment, a joining node broadcasts a frame with a well-known EtherType carrying a "Raft peer discovery" payload. Existing members respond with their service names. The joining node looks them up through the name service to obtain attested connection caps. This works without any seed configuration.

14.4.4 Distributed name service (implemented)

The `dns` service realizes this end state: its `CatalogMachine` is a `StateMachine` implementation on the Raft substrate, and a new node needs only a single seed to discover all peers through the consistent name registry. There remains one process-facing name-service instance per machine; those instances apply the same committed registry state. The `ns` node-local registry and the `dns` cluster catalog remain distinct services.

14.5 The generic StateMachine trait

Raft replicates an opaque command log. The meaning of those commands is provided by a pluggable `StateMachine` trait:

```
trait StateMachine: Send + Sync {
    fn apply(&self, term: u64, command: &[u8]);
    fn apply_with_result(&self, term: u64, command: &[u8]) -> Vec<u8>;
    fn snapshot(&self) -> Vec<u8>;
    fn restore(&self, snapshot: &[u8]) -> Result<(), SnapshotError>;
    fn reset(&self);
}
```

Restore errors leave application state unchanged. `RaftNode::new` returns a result; callers must handle rejection before exposing a voter.

Different services are different state machines on the same Raft substrate:

- Distributed name service: commands are "register(name, owner, route, generation)" and "unregister(name, owner, generation)". Unregistration is rejected unless both owner and generation still match the active entry. The owning DNS process watches the local endpoint through a waitable kernel completion. Endpoint death proposes this same fenced tombstone; a follower forwards an owner-and-generation-fenced, idempotent request to its known leader and retries across leadership changes. Peer/MAC and session checks provide correlation, but the inter-node transport has no cryptographic peer authentication. A stale death notification therefore cannot remove a replacement generation. Service registration retains an attached or existing node-local connection in an owning operation; full-name lookup and registration use memory-carried calls. Missing local publication rejects before a leader proposal. Catalog-only markers use the explicit event operation, rather than becoming remotely resolvable services without endpoints. This preserves endpoint observation without granting ordinary lookup clients minting rights. The state maps names to owning-node identities, routable service identities, generations, and policy metadata. Replicated, it makes service discovery available cluster-wide; this is the implemented `dns` service.
- Distributed lock service: commands are "acquire(lock_id)" and "release(lock_id)". The state is a set of held locks.
- Cluster configuration store: commands are arbitrary key-value writes. The state is a key-value map.

None of these state machines know about sockets, IP addresses, or TCP. They implement `apply()` and `snapshot()`. The Raft substrate handles replication, leader election, and fault tolerance.

Raft RPCs and DNS control messages use one serialized relmsg queue per peer. Because QEMU may acknowledge that queue slowly, consecutive queued AppendEntries requests and their serially ordered responses are coalesced, and heartbeats are generated only at a bounded fraction of the election timeout. Non-Raft control messages retain their relative FIFO order but pass queued, supersedable append traffic. A two-second stop-and-wait retry lease is shorter than the DNS remote-call deadline, preventing one lost heartbeat from holding the peer's only transmission slot long enough to starve service retraction, placement, or invocation traffic.

The DNS process also never waits synchronously for an arbitrary local service while running this reactor. Name lookup and local invocation are retained as bounded owning operations whose two RPC phases bind reply readiness to the shared CQ; later reactor turns observe ready replies without blocking on one service. Their original kernel-monotonic deadline bounds routing and execution. Consequently a failed service cannot stop Raft heartbeats or relmsg receive draining. A timeout before execution is reported as a retryable lookup failure; after invocation has been submitted, timeout or reply-binding rejection is reported as an uncertain outcome. Duplicate remote calls are suppressed both while pending and in the acknowledged-result window. Node-local cleanup now owns its exact-generation retirement RPC and binds reply readiness to that CQ as well. Preparation begins one monotonic deadline; uncertainty never submits it again. Metadata observation uses an owned timed RPC to the independent NS process and keeps rejection distinct from confirmed absence before a catalog tombstone is submitted. Endpoint watches and raw receive/transport contexts retain their separate notification gaps.

14.6 Relationship to the name service

The node-local `ns` registry and replicated `dns` catalog are separate services. DNS applies committed catalog state and resolves remote routes; NS holds machine-local endpoint capabilities:

- Cluster registrations are submitted through the Raft leader and applied to each DNS replica; local endpoint publication remains an NS operation.
- Service generations are replicated consistently. A restart on node 3 cannot create a split-brain where node 1 sees generation 5 and node 2 sees generation 3.
- Replicated policy metadata and tombstones propagate through the log; local delegation still depends on machine-local authority.

Kernel capability identifiers and endpoint objects are machine-local and are not Raft state. For a local registration, lookup delegates a connection to the local endpoint. For a remote registration, the local name-service instance must return a local proxy connection whose transport reaches the owning node. Raft replicates the metadata needed to choose that route; the capability object itself remains local.

14.7 Election timers as first-class completions

In a traditional Raft implementation, election timeouts are implemented with `sleep()` or a polling loop:

```
// Traditional: busy wait or sleep
while !timeout_elapsed() {
    sleep_ms(10); // or just spin
}
```

CharlotteOS uses detached timer completion cookies and a checked CQ watchdog. Endpoint readiness and completion notifications release the same reactor wait:

```
let outcome = catten_services::reactor::wait(
    Some(remaining_ms), cq_id);
// Ready: drain completions and recheck all endpoint sources.
// Deadline: evaluate the original protocol deadline.
// Admission rejection: abort, retaining pending resources.
```

The timer is a kernel-managed operation. The shard parks on its CQ; when its cookie arrives, the reactor drains the entry and advances the protocol clock. The checked timeout remains an independent watchdog because accepting a detached timer does not prove that its cookie will arrive promptly. Its original watchdog deadline survives unrelated reactor wakes; only a clock event or expiry starts the next period. Wait admission rejection is distinct from deadline expiry and must not manufacture a clock tick. Neither path needs a dedicated sleeping thread or a spinning timeout loop.

14.8 Replication consequences

1. Consistency primitives can be exposed as services: a replicated service implements `StateMachine` and uses the shared Raft, transport, timer, and storage interfaces.
2. Peers are reached through capabilities. The cluster configuration uses these connections independently of transport addresses. A network reconfiguration (new NIC, new subnet, move to RDMA)

need not change the replicated peer identities.

3. Timers are first-class and reliable: an election timeout that is lost because the polling loop missed its window is a correctness bug (it can cause spurious leader changes or extended unavailability). Kernel-managed timers use the non-lossy CQ delivery path exercised by the local-election test.
4. Failure isolation can extend to the consensus layer: a Raft node is a userspace process. It can crash, restart, and recover without affecting the kernel or other Raft nodes. The supervisor handles the lifecycle; the Raft protocol handles the consensus.
5. A distributed name service is implemented: the `dns` service runs the `CatalogMachine` state machine on the Raft substrate; all other services that need cluster-wide consistency can use the same `StateMachine` pattern and shared consensus implementation.

14.8.0.0.1 Configuration entries and recovery.


Election eligibility is reconstructed from the snapshot and retained configuration entries before a restarted node can vote. Recovering that membership does not claim application commitment or application replay. The joint entry requires both old and proposed voter majorities; proposed voters remain replication targets before commitment. Local peer discovery uses that same replication peer set. Finalization retains the joint-majority requirement until its fence commits, including when a later no-op would otherwise cover that fence.

The 29 October 2026 native qualification passed the 17-test no-network boot and both 20-test socket-LAN guests, including catalog replication and remote invocation. A targeted QEMU kill after durable term 1 recovered and advanced to term 2 on the reused virtual NVMe disk. Host caches remained live; this does not qualify physical power loss, interrupted log/snapshot publication, or simultaneous multi-voter restart.

15 Persistent Storage

CharlotteOS treats storage as a layered stack of userspace services, each speaking a well-defined protocol through endpoint IPC. The block driver, object store, and filesystem services run in userspace. The kernel still participates through capability, memory-mapping, physical-address, interrupt, and PCI/MSI-X setup paths.

15.1 The storage stack



15.2 NVMe block driver

The NVMe driver is a userspace EL0 prototype implementing the subset needed for QEMU bring-up: controller and namespace identification, queue creation, and basic read, write, and flush operations. NVMe 1.4 compliance has not been established. It receives an `MmioRegion` capability covering the controller's BAR0 register window, an `Interrupt` capability for I/O completion signalling, and a `DmaDomain` capability bound to the controller's PCI requester ID. Queue and data memory are mapped with `dma_map`; the driver receives contiguous IOVAs rather than physical addresses. The kernel pins the backing frames and removes each translation with a synchronous SMMU invalidation before unpinning.

15.2.1 Initialization

The driver follows the standard NVMe initialization sequence:

1. Controller reset: disable CC.EN, wait for CSTS.RDY = 0.
2. Admin queue setup: allocate physically contiguous memory for the Admin Submission Queue (ASQ, 32 entries) and Admin Completion Queue (ACQ, 32 entries). Write AQA, ASQ, and ACQ registers. Enable the controller and wait for CSTS.RDY = 1.
3. Identify controller: submit an Identify command (CNS=1) through the admin SQ. Read capabilities, version, and supported features.
4. Set Features (Number of Queues): declare how many I/O queue pairs the driver intends to use. QEMU's NVMe controller requires this before accepting I/O queue creation commands.

5. Identify namespace: submit an Identify command (CNS=0, NSID=1) to read the namespace size (NSZE) and the active LBA format (FLBAS), which determines the block size.
6. Create I/O Completion Queue: allocate memory, submit a Create I/O CQ admin command. The CDW11 register must set bit 0 (PC = Physically Contiguous) to 1. The NVMe specification and enforced by QEMU's device model.
7. Create I/O Submission Queue: allocate memory, submit a Create I/O SQ admin command, associating it with the I/O CQ created in the previous step.

After initialization the driver registers `"blk0"` with the name service and enters its main loop, blocking on `cq_wait` for endpoint messages and I/O completions.

15.2.2 I/O path

OP_READ receives a BorrowWrite memory attachment from the caller. The driver maps it into the controller's DMA domain, builds a PRP chain from the returned IOVA range, and submits an NVM Read. On completion it unmaps the DMA translation, replies, and lets the kernel revoke the borrow and return the filled buffer to the caller.

OP_WRITE receives a Move memory attachment, maps it for DMA, builds the PRP chain, and submits an NVM Write. On completion the driver removes the mapping and replies; the moved buffer is consumed.

OP_FLUSH submits an NVM Flush command to ensure all previously written data reaches durable media before replying.

15.2.3 Lessons from bringup

The NVMe driver exposed several non-obvious requirements:

- CDW11 bit 0 (PC) must be 1: QEMU's NVMe device model requires physically contiguous queues. Without this bit, the Create I/O CQ command returns status 0x4002 regardless of all other parameters.
- SQE layout is exacting: the Command Identifier occupies bits 31:16 of DW0, the opcode occupies bits 7:0. The NSID shares DW0's high bits with DW0 in the first u64. PRP1 is at byte offset 24, CDW10-11 at byte offset 40. Getting any of these wrong produces silent failures.
- Doorbell stride must be derived from CAP.DSTRD: on QEMU this is 0 (stride = 4 bytes), but the architecture supports strides up to $4 \ll 15$ bytes.
- MMIO mapping must cover the doorbell region: the NVMe controller registers occupy offsets 0x0000–0x003F within BAR0, but doorbell registers start at offset 0x1000. A single-page MMIO grant is insufficient; at least two pages are needed.
- On TCG, `cq_wait` is required for VM exits: a pure spin-loop prevents QEMU from processing I/O because the guest never yields. The driver must block on `cq_wait` to let the host process NVMe commands.

15.3 Block device protocol

The block protocol (`charlotte-protocol-block`) is a minimal `no_std` crate defining the endpoint IPC interface between block device consumers and drivers:

Opcode	Name	Description
1	OP_INFO	Query block size and total block count. Scalar call/reply.
2	OP_READ	Read blocks into a BorrowWrite memory object.
3	OP_WRITE	Write blocks from a Move memory object.
4	OP_FLUSH	Flush write cache to durable media.
5	OP_TRIM	Discard a block range (optional).

The protocol is device-independent: consumers speak `OP_READ`/`OP_WRITE` without knowing the underlying hardware. Three userspace implementations are present. NVMe is exercised on AArch64 and x86-64; x86-64 additionally runs AHCI and virtio-blk implementations through the same protocol. The QEMU matrix validates identify/capacity discovery, bounded read and write requests, flush completion, controller timeouts, and the persistent object-store/Raft restart path. On x86-64 all three transports are tested behind VT-d or AMD-Vi DMA domains. Ramdisk and network block drivers would still require separate implementations.

15.4 Object store

The persistent object-store prototype (`charlotte-protocol-objstore`) provides dynamically sized blob storage on top of a block device. Ordinary objects receive monotonically increasing 64-bit IDs; service-owned objects can use stable IDs through `OP_CREATE_AT`. Stable IDs let a replacement Raft process reopen state derived from its cluster and node identity.

15.4.1 On-disk layout

```
LBA 0--1:  checksummed superblock slots
next:      device-sized allocation bitmap
next:      two device-scaled directory banks:
             id | flags | generation | header_lba |
             header_blocks | crc32
data:      object headers and up to 16 data extents per object
```

15.4.2 Current durability boundary

Both superblock reads must finish successfully before their absence or validity can select mounting or formatting. Allocation, IPC, device or mapping rejection fails startup; unreadable metadata is not evidence of a blank disk. Only two successfully read zero-filled superblock slots permit first-boot formatting. Retired format tags reject even alongside a current copy. A valid current copy can recover a blank or corrupt peer; nonblank metadata with no current copy and incompatible layouts fail without reformatting.

The store publishes explicit Starting, Serving, Draining and Failed states. Serving follows mount and endpoint registration; kernel local readiness acquires and revalidates that milestone. Diagnostic stages and

ordinary I/O errors are separate. The marker records startup completion; later I/O can still fail. First-failure diagnostics retain state, operation, LBA/count, phase and available status/result without retry. See docs/reports/audits/2026-10-12-security-object-store-readiness.md.

Each object header is versioned and carries explicit header length and block count, object generation, exact and allocated data lengths, data offset, extent information, and a mandatory FNV-1a content hash. The fixed header rejects extension lengths rather than filling absent fields. It records up to 16 extents, so fragmented free space does not require one large contiguous run.

Replacement is copy-on-write. New data, header, and allocation state are flushed before the directory locator changes, and the old allocation is freed afterward. Mount reconstructs the bitmap from validated reachable headers, reclaiming pre-commit allocations. Whole-object transfers use multi-page memory objects and are divided into block requests of at most 512 KiB. Objects and files can be larger than a single request. The current service API's 32-bit length limits an individual object to 4 GiB and available disk space. Directory records are checksummed and mirrored. Each update goes to the generation-selected bank, and mount chooses the newest valid copy per record; versioned tombstones prevent deleted records from reappearing. This recovers from one torn directory-sector write. Full device-level sudden-power-loss guarantees still depend on truthful flush/FUA behavior. FNV-1a detects accidental corruption, but is not cryptographic authentication.

15.4.3 Operations

- **CREATE**: allocate a directory slot, return a new object ID.
- **CREATE_AT**: create a caller-selected stable object ID, or report that it already exists.
- **WRITE**: replace the object's content. The caller moves a suitably sized memory object; the store writes it in bounded chunks.
- **SET_SIZE**: set the exact byte length consumed by the next whole-object write.
- **READ**: return the object's data as a moved memory object.
- **DELETE**: mark the directory entry as free, return the extent blocks to the free bitmap.
- **FLUSH**: flush the underlying block device.

15.4.4 Object authority

The store authenticates each sender through the kernel IPC envelope and records the creating principal in the object header. Ordinary objects are private to that principal and the kernel, including across service replacement. Shared-read objects permit other authenticated readers while retaining owner-only mutation. Reserved artifact and executable namespaces are publicly readable but mutable only by the kernel and the signed `clusterctl` administration service. A persisted operator table admits at most 64 principal/range grants for read or write access; grants cannot extend the reserved mutation allowlist. Node/operator enrollment and management-channel authentication remain separate requirements.

Authorization and data access consume one validated locator/header snapshot. Missing objects return NotFound; metadata I/O or validation failure returns an error rather than adopting public ownership defaults. Automatic creation searches for an unused positive scalar ID with a directory-sized bound, preserving explicitly created objects. Mount rejects duplicate live IDs. Current format v4 uses COBJSTR4 superblocks and fixed 384-byte CCOBJHD4 headers with explicit nonzero owners, known attributes and zero reserved/unused fields. Host-staged artifacts use the kernel principal. Owner-zero metadata and older stores reject before mutation; deployed format changes will require explicit migration. See docs/reference/security-remediation.md for current disposition and validation limits.

15.4.5 The initial service-artifact store

The host build produces an architecture-qualified service bundle and blesses every ELF according to `crates/catten-services/artifact-policy.tsv`. AArch64 embeds naming, storage, UART, observation and grant mediation, plus the boot entropy/network driver images needed to prepare grants before starting storage. The exact sets are listed in Chapter 17 and `crates/catten/src/service/store.rs`; `scripts/make-nvme-image.py` writes the remaining services into an initial version-4 object-store image. The QEMU x86-64 runner can use the same host-preseeded model.

The x86-64 kernel also carries an immutable signed installation bundle for the blank-disk appliance path. Once NVMe and the object store are available, it checks the stable object ID for every bundled logical name. A valid stored artifact is retained, including a newer deployed version; a missing artifact or one that fails identity and signature verification is replaced from the bundle. The installer flushes the store before dependent services start, so the operation is idempotent across reboot. Services are subsequently resolved by logical name, read through the object-store protocol, identity-checked, and cached for the boot. Denied, malformed or unreadable responses stop seeding; they cannot authorize replacement. The cache reserves fixed publication entries before I/O, owns immutable admitted vectors for the kernel lifetime, and has a separate 16 MiB/64-entry image budget. It does not consume temporary snapshot headroom. The ordinary loader independently enforces ELF and signature policy before mapping. See `docs/reference/service-launch-ownership.md`.

The signature record is CLS2, an identity-bearing ELF note. Besides signing the complete bytes, it binds the logical service name, artifact class, release and rollback counter, policy flags, signing-key id, and an optional provenance digest. Consequently a validly signed `dns` ELF cannot occupy the `raft` slot. A deployment generation also carries the complete ELF SHA-256, preventing an object replaced under the same logical name from changing already-committed code.

For preseeded QEMU images, the runner fingerprints the whole blessed bundle. It rebuilds an instance's initial NVMe image when that fingerprint changes, while `-reuse-storage` deliberately retains an older store and emits a staleness warning. `-fresh-storage` always recreates it. The image producer refuses an object-id collision rather than silently replacing an earlier service. The x86-64 options `-blank-storage` and `-build-only` instead support guest-side installation and appliance packaging without constructing a preseeded store.

15.5 Managed object storage through S3

The local `objstore` and the S3 client service solve different problems. The local store is part of node bootstrap and supplies service artifacts, Raft persistence, and the native filesystem without depending on a working network or external credentials. The `s3` service is an application-facing compatibility adapter for centrally managed object stores. It runs above TCP/IP and, when configured, verified TLS; it is described in Section 13.6.1.

An S3 service profile narrows authority to one endpoint, bucket, key prefix, credential identity, optional Dell EMC ECS namespace, and operation mask. Applications receive only the profile's endpoint capability and transfer object data as owned memory chunks. This makes external object storage usable without handing each application general socket access or raw S3 credentials.

Static provisioning and operational pickup both supply the complete immutable `CHS3PF1` profile through read-only launch memory. The service rejects missing or malformed profiles; it no longer reads per-field manifest aliases or synthesizes region and port defaults. The shared profile codec is the single validation

boundary. Encoded profiles and the service's local profile snapshot use erasing owners. The original read-only launch memory follows the kernel's separate teardown policy.

RustFS is the current integration fixture. Dell EMC ECS is an intended managed store and the adapter can emit its namespace header, but it has not yet been qualified against an ECS installation. The cluster deployment agent can use a separately provisioned S3 connector as an artifact source: it reads the opaque key from a signed deployment descriptor, streams the ELF, checks its pinned SHA-256 and name-bound CLS2 signature, and transfers both ELF and descriptor to the scoped kernel launch gate. Credentials, endpoint, bucket, prefix, and TLS identity remain outside both descriptor and application. Bootstrap services still come from the local store; the node can boot without central S3. Caching, availability policy, credential rotation, and an end-to-end managed-store qualification remain operational work.

15.6 Raft persistence

The Raft service selects memory (`storage=0`, or omitted) or required persistence (`storage=2`); retired mode 1 and malformed policy values reject. Required mode waits for `"obj"` through the name service. One jointly validated two-object pair holds `CRFTSTA4` term/vote/join-admission state and `CRFTLOG4` snapshot/log state. Only two absent records authorize initialization; existing empty, incomplete, corrupt or unsupported records reject without reset or a memory fallback. Older decoders and split-store migration are removed. Each mutation writes the complete object and flushes the underlying NVMe device before returning. Snapshot bytes and the retained log suffix share one replacement point in the log object. The two-object pair has no cross-object atomicity guarantee. Future deployed-store changes require an explicit version-directed migration. See `docs/reference/raft-persistence.md`.

The focused local election fixture runs two in-process Raft members with memory stores, keeping consensus behavior testable on a multicore machine without NVMe. We chose its peer count for the fixture; Raft is not limited to that count. A separate storage test starts a single voter with required persistence, records its elected term, tears down that process, restarts the same identity, and requires the new election term to be greater. A repeated term 1 would fail, so the test distinguishes recovery from a fresh in-memory start.

Launch configuration (node identity, peers, election timeout, cluster name, and storage policy) remains in the supervisor-provided manifest. The persistent objects hold Raft protocol state, log entries, and snapshots. Cross-machine catalog replication is provided separately by the `dns` state machine described in Chapter 14 and Chapter 17; this generic Raft persistence test remains a single-voter restart test.

15.7 Native filesystem

The filesystem (`charlotte-protocol-fs`) builds hierarchical naming on top of the object store. Directories and files are stored as objects; the root directory is a fixed object ID (100).

15.7.1 Directory encoding

Each directory object stores entries as a packed sequence:

```
[name_len: u32 LE][name: UTF-8]
[file_id: u64 LE][flags: u32 LE][size: u64 LE]
```

A `name_len = 0` marker terminates the list. Flags distinguish directories (bit 0 set) from files (bit 0 clear).

15.7.2 Path resolution

Paths are walked client-side by chaining `OP_LOOKUP` calls. The filesystem service does not understand path strings; it resolves only single-component lookups within a given directory. This keeps the filesystem protocol minimal: six operations (LOOKUP, CREATE, READ, WRITE, DELETE, LIST) plus FLUSH.

15.7.3 Host inspection

A Python tool (`scripts/fs-inspect.py`) reads the raw disk image and walks the object store and filesystem on-disk structures. It understands both v4 directory banks and multi-extent headers, selects the newest valid directory record, checks CRCs and allocation overlap, compares reachable blocks with the bitmap, and verifies object contents against their FNV-1a hashes. It provides tree, dump, raw, cat, object-list, metadata, information, and format commands, enabling post-mortem debugging without booting CharlotteOS:

```
scripts/fs-inspect.py <image> info
scripts/fs-inspect.py <image> objects
scripts/fs-inspect.py <image> metadata
scripts/fs-inspect.py <image> metadata OBJECT_ID
scripts/fs-inspect.py <image> metadata /path/to/file
scripts/fs-inspect.py <image> tree
scripts/fs-inspect.py <image> cat /raft/state
```

Metadata output includes numeric and symbolic object/filesystem flags, generation, header location, logical and allocated lengths, integrity hash, and every extent. Filesystem flag bits remain visible; unsupported object-store flags reject validation. The `format` command creates a blank v4 store and destructively replaces the image contents.

15.8 Isolation and durability limits

1. Storage policy lives in userspace: a bug in a block driver, the object store, or the filesystem corrupts that service's address space. The kernel grants MMIO and interrupts; the storage implementation stays in userspace.
2. Device-independent protocol: the object store and filesystem use one block protocol over the implemented NVMe, AHCI, and virtio-blk userspace drivers. Further backends can implement the same protocol without moving storage policy into the kernel.
3. Crash-safety mechanism under development: process-restart persistence is boot-validated. Copy-on-write object replacement and mirrored directory records recover from one torn directory-record write. Broader power-loss guarantees still require validation of device atomicity and truthful flush/FUA ordering.
4. Capability-based access: a client that holds a connection to `"blk0"` can read and write blocks. A client that does not hold that connection cannot. There is no ambient filesystem namespace to escape.

5. Host-inspectable: the included Python inspector reads the raw disk image and reports its documented object and filesystem structures.

16 Live Service Upgrade

CharlotteOS has a tested prototype for replacing a reference service while transferring its state. We describe this as **restart-with-state**: in-flight requests may fail during handoff. Clients reacquire a connection and apply their protocol's outcome/replay policy before continuing.

16.1 The four primitives

The prototype builds on four primitives implemented in the kernel and name service:

1. Memory-object ownership transfer: the kernel's `memory::object::move_to` moves a page-backed memory object from one address space to another. The sender loses access; the receiver gains it. This is the vehicle for service state.
2. Generation tracking: the userspace name service records an publication generation. Rebinding a name does not revoke a still-live old endpoint. Once that endpoint closes, its connections reject; a new lookup can return the replacement generation and connection.
3. EndpointClose and Cancelled: when a service domain exits, the kernel closes its endpoint. Queued requests that were never delivered complete as `EndpointClosed`. Delivered calls whose server exited before replying complete as `Cancelled`. Clients receive the corresponding failure result.
4. Bootstrap capability delivery: the supervisor writes initial capabilities to the config page before a domain starts. For a live upgrade, the bootstrap contract is extended: in addition to the name service connection, the new domain receives the old service's state as a memory object. The current reference replacement creates and registers a fresh endpoint.

16.2 The handoff protocol

The reference echo service receives `OP_HANDOFF` from the userspace service manager. Its single serving loop serializes its counter into an unmapped memory object and returns that object through a consuming moved-memory reply before exiting. The manager unregisters the old publication before requesting replacement launch. A general service needs its own admission/drain protocol; this counter handoff does not establish that arbitrary in-flight work is drained.

The supervisor then spawns the new service instance with an extended bootstrap contract containing the name service connection and handoff state. The new service deserializes the state, creates a fresh endpoint, and re-registers under the same name. The name service bumps the generation. Teardown of the stopped old domain invalidates its stale client connections.

16.3 Executable source

Embedded service images are bootstrap and recovery inputs. They are not the only executable source. The service manager first tries the object store and reads the well-known executable object for the target service. The returned multi-page memory-object capability and exact byte length are passed to the `SpawnUpgrade` syscall. If storage is absent or the object is not installed, the manager selects the embedded recovery image.




Figure 16.1: The live-upgrade handoff: the supervisor drains and transfers the old service's state, spawns the replacement with the handoff state and a fresh generation; clients reacquire a connection and decide whether replay is safe.

The kernel snapshots the capability-backed bytes into kernel-owned memory before parsing them. It then checks the ELF class, architecture, program-header bounds, segment bounds, page congruence, W^X ("write xor execute")[1], integer overflow, and whether the entry point lies in an executable load segment. This prevents a mutable userspace image from changing between validation and mapping.

Executable artifacts carry an Ed25519 CLS2 note that binds the complete ELF to its logical service name, artifact class, release metadata, rollback counter, policy flags, and signing-key identifier. The loader snapshots the bytes and verifies the note before mapping. The FNV-1a object checksum remains corruption detection; the CLS2 signature supplies executable authority. Rollback policy, key rotation, and measured boot remain future policy work.

16.4 Shared Kernel Preparation

The live syscall uses the supervisor's complete preparation path:

```
pub(crate) fn try_spawn_upgrade_from(
    image: &[u8],
    name_service: &NameServiceHandle,
    rights: ConnectionRights,
    old: AddressSpaceHandle,
    source: AddressSpaceHandle,
    grant: UpgradeGrant<'_>,
) -> Result<ServiceDomain, UpgradeSpawnError>;
```

`UpgradeGrant` borrows source IDs from the captured namespace. The syscall supplies its authorized manager and at most one state object; the old endpoint's exact root generation supplies replacement classification before loading. Naming, source, old-service and replacement roots remain retained.

`PreparingUpgrade` owns the launch transaction, every prepared transfer and both byte-admitted transfer/target-ID vectors. Reserve both arrays before escrow or delegation. Ordinary failure explicitly disposes the prefix after guards leave, frees arrays, then cancels the unstarted domain once. The first cleanup error stops; abandonment retains all fields and original charges. Commit publishes the move batch before destination IDs enter the bootstrap page and the initial thread starts. No implicit physical cleanup or reverse-move reconstruction runs on parent abandonment.

Native controls qualify original classes, prefix/quota rejection, guarded parent retention, maximum 31-entry array layouts and real single-state persistent upgrade. They do not establish 31 simultaneous physical transfers or an end-to-end multi-state endpoint handoff. See `docs/reference/service-launch-ownership.md`.

16.5 What the service must implement

The old service must handle `OP_HANDOFF`:

```
OP_HANDOFF => {
    // Stop accepting new work.
    // Serialize all mutable state into memory objects.
    // Unmap the state before transferring it.
    // Consume reply authority with reply_move(state, result).
    // Leave the owning serving scope, then exit.
```

[1] A memory page may be writable or executable, but never both simultaneously

```
}
```

The following sketch describes the launch inputs, rather than an ownership-safe application listing. The current reference implementation is `crates/catten-services/src/bin/echo.rs`; handoff memory is adopted once at that documented launch boundary, while the bootstrap connection is borrowed.

```
fn main(ctx: Context) -> ! {
    let ns_connection = ctx.bootstrap_connection();
    let state_count = ctx.handoff_count();
    let state = ctx.handoff_state_cap();

    // Deserialize state, create and register a fresh endpoint
    // under the same name (NS bumps generation), start serving.
}
```

16.6 What clients see

A closed old endpoint rejects further calls. Queued, undelivered calls return the endpoint-closed result; delivered calls that lose their server before a reply return cancellation. A timeout or cancelled reply does not prove that a delivered request had no effect. Name rebinding alone supplies no such proof.

The copyable client in Section 5.6.1 keeps business progress outside its session connection, maps endpoint closure to an application-defined restart decision, and preserves one operation deadline across reconnection. It stops on an uncertain accepted call. Its read-only business operation can be repeated safely; a mutating protocol needs durable request identity, duplicate suppression and outcome reconciliation before replay. Grant-mediated discovery must also authorize the replacement publication.

16.7 Restart-with-state vs. zero-downtime

This design is **restart-with-state**: in-flight requests to the old instance can fail during the handoff window, and clients need a recovery policy. It is potentially suitable for services whose protocols define retry and state recovery. No general latency bound has been measured, and clients must explicitly handle transient failures through name-service re-lookup.

True zero-downtime would require one of:

- Queue migration: the old service's endpoint queue would need to be transferred to the new service atomically, so no request is ever rejected. This is a future kernel feature.
- Sidecar model: the new service starts alongside the old one, both sharing the same endpoint, and the old service stops accepting new work. The kernel does not currently support multiple owners for one endpoint.

16.8 Relationship to crash recovery

The live upgrade path is the graceful variant of the crash-recovery path already exercised by the UART driver test (Chapter 12). In both cases, the supervisor arranges a replacement and a fresh publication. Driver recovery also requires confirmed device quiescence/reset before grants can be reused; uncertain cleanup

may retain backing and prevent restart. The difference is that live upgrade transfers state explicitly through memory objects before the old instance exits, rather than starting the new instance from scratch.

16.9 Upgrade guarantees and limits

1. The reference path transfers service state: the self-test demonstrates handoff for the reference service. Filesystems, network stacks, and consensus nodes would each need protocol-specific serialization, compatibility, and recovery work.
2. The upgrade sequence is explicit: the old service drains in-flight work, serializes state, and exits. The new service starts and registers. Clients reconcile failed work. A hard time bound is not currently enforced or benchmarked.
3. Failure recovery has an ownership model: if the new service fails to start, a future supervisor could restart the old service or a fallback. Before transfer, the manager retains the state capability; after transfer, it belongs to the replacement. Recovering state after that replacement fails requires an explicit policy, beyond capability cleanup.
4. The building blocks are covered by self-tests: memory-object transfer, generation tracking, deterministic teardown, and bootstrap delivery are exercised by the existing self-test suite. This evidence does not establish crash consistency, arbitrary-service compatibility, or production readiness.

Part V

Research Directions

17 Server-Class Cluster Vision

CharlotteOS explores an operating-system boundary at which the cluster is the primary administrative and computational unit. An operator assigns a signed workload to the cluster, declares its resources, authority, multiplicity, and placement constraints, and leaves physical placement to cluster policy. Nodes supply processors, memory, devices, and failure domains; replacing one should not require rebuilding a machine-specific application installation.

This chapter draws on three distinct kinds of evidence. The generic Raft core exercises quorum rules with configurations including five voters, and the safety models explore three-node elections and membership transitions. Operational QEMU validation ranges from focused two-guest scenarios to a three-guest cluster with discovery-driven admission, joint-consensus membership, replica placement, and cluster-wide TCP ingress. We choose the number of guests to test a particular behavior. Those fixtures do not establish a cluster-size limit or target.

The implemented system now includes replicated naming and deployment state, signed ELF artifacts, central-S3 artifact pickup, per-node deployment agents, remote invocation, deterministic replica placement, basic affinity and anti-affinity, membership and drain reconciliation, exact-generation readiness, and a DSR-backed service VIP. Capacity-aware scheduling, stateful cross-node migration, rolling replacement, and a production administration plane define the next engineering boundary.

This chapter first develops the cluster-level model and then uses Linux containers and Kubernetes/OpenShift as a counterpoint. The comparison separates the intrinsic cost of distributed computation from machinery needed to adapt general-purpose, machine-centered operating systems to isolated, reproducible, movable workloads. With CharlotteOS, we want to test that separation. This is still a research prototype.

17.1 The cluster is the computer

17.1.1 Nodes as resources

The central proposition is simple:

> The Charlotte cluster is the administrative unit; nodes contribute replaceable execution and storage resources.

A node boots, discovers or is directed to a cluster, establishes its identity, joins shared state, advertises resources, and receives work. Its useful description consists of properties such as processor architecture, memory, accelerators, attached devices, trust domain, and failure domain. If a node fails, the operator should replace the resource and let the cluster reconstruct the intended placement. If a workload moves, clients should continue to address its cluster name.

That indirection now has an external TCP counterpart. Node addresses serve protocols that intentionally target one machine. A cluster service VIP instead addresses functionality placed somewhere in Charlotte. Direct Server Return both distributes load and hides ingress and execution nodes behind a stable cluster network identity. The implemented data path and its current placement-policy boundary are described in Section 13.4.

Consensus membership, failure detection, routing, and ownership fencing still use stable node identities. Those identities remain mechanisms below the operator's application-deployment model. Interchangeability also permits heterogeneous hardware: schedulable properties and failure-domain constraints express relevant differences without turning nodes into hand-maintained machine personalities.

The same idea already appears one level down in CharlotteOS. The shard-per-core model of Chapter 9 treats cores as executors over explicitly owned state, while the scheduler in Chapter 10 moves work between them. The cluster vision scales this relationship outward: a cluster node is analogous to a core, cluster-visible storage is analogous to owned persistent state, and the cluster becomes the unit within which execution is placed.

17.1.2 Workloads are signed execution objects

In the target model, cluster software is a signed execution object with a logical identity and a deliberately small execution environment. Its signed metadata can bind, among other things, its name, class, release, rollback counter, permission to run concurrent instances, and a digest linking to retained provenance.

Signature validity establishes the artifact identity and accepted origin. Capability delegation independently determines what a running workload may do. Each workload executes in its own address space and receives a deliberate set of service endpoints, storage objects, devices, or administration capabilities.

CharlotteOS therefore combines an immutable, name-bound identity at the loading boundary with explicit authority at the execution boundary. Signing without confinement accepts an over-powerful program; confinement without authentication accepts code of unknown origin.

This boundary also changes what installing software means. Build systems resolve third-party code and produce a self-contained, blessed artifact with its evidence. Nodes avoid installation scripts and machine-local dependency state. Reproducible builds, vulnerability policy, SBOMs, source attestation, and signing-key custody remain supply-chain responsibilities.

17.1.3 Assignment is declarative and cluster-wide

The desired operation makes version 71 of a claims engine active in the cluster with a desired number of instances and declared resource, authority, affinity, anti-affinity, and failure-domain constraints.

That declaration becomes replicated desired state. A cluster controller compares it with observed state and chooses assignments. An assigned node obtains the immutable artifact, verifies its identity and signature, creates an isolated execution domain, and supplies its delegated capabilities. Rollback is another desired-state change to an earlier accepted artifact, not a sequence of machine-repair commands.

Placement maps a component to one or more eligible nodes. A component explicitly blessed as safe for parallel execution may have several instances. Closely interacting components may be co-located to reduce communication cost, while replica anti-affinity and minimum failure-domain rules keep latency optimization from defeating availability. Node capacity, architecture, devices, policy domains, and actual load all constrain the decision.

Routing follows the same abstraction. Clients address a logical service through the cluster name service. The runtime may choose local delivery when caller and callee are co-located and network delivery when they are not. If placement changes, the name's generation changes, stale endpoints are invalidated, and clients resolve again.

Migration is consequently a cluster operation. Stateless reassignment starts an equivalent instance at the new location and retires the old one under generation fencing. Stateful migration additionally requires an explicit transfer of owned mutable state and a single, fenced change of ownership. CharlotteOS has demonstrated only the stateless cross-node case; the stateful protocol remains a target.

17.2 Kubernetes and OpenShift as a counterpoint

17.2.1 What the container stack constructs

A Linux container is not a new kernel object equivalent to a virtual machine. It combines ordinary Linux processes with several existing facilities. Namespaces determine which resources and identifiers are visible; cgroups account for and limit resource use; Linux capabilities divide some root privileges; seccomp restricts the system call interface; and an LSM such as SELinux constrains object access. A prepared filesystem and network configuration provide the process's apparent environment. An OCI image and runtime turn those facilities into a repeatable execution contract. Kubernetes adds scheduling, desired-state reconciliation, service naming, failure recovery, rolling change, and many other cluster functions. OpenShift adds an integrated security, policy, build, registry, identity, networking, and operations environment around that model.

This machinery exists for good reasons. Linux is a general-purpose, machine-centered operating system with broad compatibility obligations. Conventional applications expect filesystems, shared libraries, package contents, users, process APIs, network interfaces, and often a distribution userspace. Container platforms must package enough of that environment to make a program reproducible, then construct boundaries that let mutually distrustful workloads share a kernel. OCI images need not contain a complete distribution, but they commonly carry a substantial userspace precisely because existing software was written as if it ran inside a machine.

Kubernetes can therefore be understood partly as a distributed operating-system layer over machines whose native abstractions stop at the node. It translates the operator's model of cluster workloads into Linux processes on machines, and gains enormous practical value from orchestrating the software and operating systems that already exist.

CharlotteOS asks a different question: what becomes possible when the controlled distributed execution environment is the operating system, rather than something assembled above a set of general-purpose hosts?

17.2.2 Two sources of complexity

The comparison is useful only if it separates two kinds of complexity.

17.2.2.1 Distributed-systems complexity is intrinsic

CharlotteOS retains the intrinsic responsibilities of distributed systems: scheduling, consensus, placement, replication, health management, service discovery, upgrades, resource accounting, storage, networking, observability, failure detection, load balancing, and recovery from partial failure. Network partitions require consistency rules; persistent state requires ownership, durability, repair, and backup; rolling change requires compatibility and rollback; and secrets require secure creation and delegation. Moving these responsibilities into the operating system changes where we handle them. We still have to do the work.

17.2.2.2 Compatibility and boundary-construction complexity may change

Some machinery exists because a cluster platform must turn a general-purpose Unix/Linux environment into a constrained, reproducible, movable unit. A clean-break system with signed, self-contained artifacts, separate address spaces, explicit capabilities, cluster-native names, and no per-node application installation may eliminate or radically simplify:

- OCI filesystem images as the normal application-delivery unit;
- CRI/OCI container-runtime and low-level container-launch layers;
- per-workload namespace construction and much container-specific seccomp, Linux-capability, and LSM policy scaffolding;
- the attempt to remove ambient machine authority from a process that began in a conventional Unix environment;
- per-node application package management, configuration drift, and machine-centered deployment procedures; and
- host-oriented workload mobility assembled from process, filesystem, and network emulation.

These are hypotheses about mechanisms and their location. Resource accounting, memory protection, and policy enforcement remain essential even when Charlotte expresses them through native resource objects, address spaces, and capability possession instead of cgroups, Linux namespaces, and SELinux labels.

17.2.3 The control plane may survive the execution stack

CharlotteOS explores absorbing cluster orchestration into the operating system and shortening the machinery required to manufacture a controlled execution environment above Linux.

Kubernetes's strongest control-plane ideas may survive remarkably well: declarative desired state, reconciliation, scheduling from constraints, generation-aware updates, health-driven replacement, replicated control state, and separation between specification and observation. A CharlotteOS cluster executive may therefore look recognizably Kubernetes-like at the level of intent and convergence.

The execution path beneath that controller could, however, be much shorter. Instead of a desired workload becoming a Pod, an OCI image, a container runtime request, a low-level runtime invocation, a namespace/cgroup/LSM configuration, and finally Linux processes, a cluster assignment can become a verified Charlotte execution object loaded directly into a capability-constrained address space. Discovering that reconciliation and scheduling survive while Pods, OCI, CRI, and much container security scaffolding do not would identify which platform ideas are consequences of distributed computation and which are consequences of the substrate.

Existing Linux software needs adaptation to run on CharlotteOS. We give up that compatibility to explore a smaller, more explicit execution contract. The question we want to study is how applications might change when cluster execution, artifact trust, and explicit authority are part of the operating system from the start.

17.3 Target architecture

17.3.1 The minimal node

The production target is an appliance-like node with no shell, no per-node application package manager, and no manually curated repository of installed software. Its stable local environment is just enough to boot, establish trust and identity, reach storage and the network, join cluster state, observe resources, and load assigned artifacts. Application differences belong in signed workload objects and replicated cluster policy rather than in mutable node configuration.

A target node lifecycle is:

1. boot a known CharlotteOS image and establish the node's execution and hardware trust boundary;
2. discover a cluster or contact a configured seed;
3. authenticate, learn cluster identity and policy, and join the relevant replicated state;
4. advertise resources and failure-domain properties;
5. receive assignments, fetch immutable artifacts, validate them, and instantiate only their delegated authority; and
6. on failure or retirement, surrender ownership under fencing while the cluster reconciles desired state elsewhere.

Secure Boot, measured boot, or remote attestation can extend the hardware-to-cluster trust chain. Artifact signing establishes executable identity; node attestation remains future work.

17.3.2 The cluster executive

The target cluster executive holds desired software state and observes actual execution state. It knows accepted artifact identities, placement policies, node resources, assignments, active service generations, and enough health and communication data to converge the two. Its responsibilities include:

- admitting nodes and maintaining consensus membership;
- accepting authorized, generation-fenced desired-state changes;
- ensuring that referenced artifacts are available and valid;
- choosing placements from resource, trust, affinity, anti-affinity, and failure-domain constraints;
- realising replica counts and routing among active owners;
- observing failure and load and initiating replacement or movement;
- coordinating upgrades, rollback, and mutable-state ownership; and
- exposing cluster-wide status, accounting, logs, metrics, and administrative audit.

This is substantial orchestration work. CharlotteOS seeks a shorter control path that acts directly on native execution objects, removing the intermediate machine-shaped compatibility environment while retaining the hard distributed systems problems.

17.3.3 Placement, routing, and migration as native operations

The first placement controller can begin with declared rules. Desired replicas, maximum instances per node, minimum distinct nodes, every eligible node, affinity groups, anti-affinity groups, required resources, and

policy domains form a constraint problem over advertised node capacity. Admission must reject combinations the artifact did not authorize: in particular, concurrent replicas are invalid unless signed metadata blesses parallel instances.

Declared affinity is only an initial estimate. The runtime should aggregate actual message counts, byte flow, queue pressure, and executor load across the cluster. Sustained evidence can then influence placement, just as the per-node scheduler's sustained-window rebalancing replaces a static assignment with a load-observed one. Communication-aware placement remains subordinate to correctness constraints: co-location must not collapse required failure diversity, violate trust boundaries, or create ambiguous state ownership.

Routing is the indirection that makes placement change tolerable. A logical name resolves to an active generation and one or more owners. A local owner may be reached through a local endpoint and a remote owner through cluster transport without changing the caller's authority. When an owner is replaced, generation fencing prevents the retiring instance from deleting or overwriting its successor's registration.

Stateful migration is explicit. The old instance exports only the mutable state it owns; the target accepts that state under a transfer protocol; ownership changes exactly once; the new endpoint becomes active; and stale clients are forced to re-resolve. Every transfer therefore carries a consistency and fencing model.

17.4 Implemented foundation

The following implemented and verified mechanisms make the cluster vision concrete. The remaining controller responsibilities are collected later in this chapter.

- **Cross-machine consensus.** The Graft core implements generic voter sets, learners, quorum decisions, and joint-consensus membership. Unit tests exercise configurations including five voters; TLA+ models explore three-node safety; and operational QEMU fixtures replicate the `dns` catalog over Ethernet with up to three guests (Chapter 14). The catalog carries membership, names, deployments, the set-once cluster signing key, signed placement rules, concrete replica sets, and per-node readiness.
- **Reliable cluster messaging.** Protocol v3 represents message lengths and fragment offsets with 32 bits and initially admits messages up to a bounded 1 MiB policy ceiling. They are fragmented across Ethernet frames and reassembled at the receiver (Chapter 13). Remote name-service calls, deployment coordination, and the demonstrated assignment handoff use this transport.
- **Persistent per-node object stores.** The NVMe-backed object store uses generation-selected directory records and copy-on-write replacement (Chapter 15) for service artifacts and persistent Raft state. The current image producer places the same signed bundle on each node for bootstrap. Signed application deployments may instead name an opaque key in a centrally managed S3 store; the assigned node pulls through its locally provisioned connector. Repair and cluster-wide artifact replication are not implemented.
- **Capability-scoped external data planes.** Separately provisioned S3 and Kafka services run above the userspace TCP/IP and verified-TLS path (Section 13.6). An S3 capability confines an application to one managed endpoint, bucket, prefix, credential identity, and rights mask. A Kafka capability confines it to an explicit broker-destination allow-list, fixed consume partition, bounded produce-route allow-list, group, transactional identity, and operation mask while keeping TLS/SCRAM and mTLS credentials inside the connector and offering idempotent production, read-committed consumption, and transactional offset commits. These adapters make externally managed infrastructure usable through Charlotte's capability model. Cluster-native storage and messaging are separate research questions.
- **Role-separated operational deployment.** Development signs an immutable release and its deploy-

ment descriptors, while operations independently signs HPKE-encrypted S3 or Kafka connector profiles bound to that exact release, target connector, cluster, expiry, and central object-store key. The host sealing tool accepts a nonempty regular plaintext file of at most 64 KiB and retains one bounded erasing destination through reads and sealing, including partial read failure. Unix input opens reject symlinks and non-regular sources; source-file permissions and host custody remain the operator's responsibility. Ciphertext verify/open inputs are bounded to 66,044 bytes; bundle verify/notify inputs to 1,048,064 bytes. Bundle signing checks its one-to-eight bindings before reading the referenced release (at most 3,584 bytes) or envelopes. These Unix file opens also reject symlinks and non-regular sources before output or ingress connection. The leader verifies both authorities and trusted UTC, then places only compact references and replay fences in Raft. On the assigned node, the authorized agent retrieves the digest-pinned ciphertext through a bootstrap S3 capability and moves a bounded pickup object to the kernel. The kernel repeats release, descriptor, artifact, envelope, and expiry verification, decrypts into transient zeroizing memory, validates the connector-specific profile, and transfers it as a read-only launch capability. Application IPC receives only attenuated connector endpoints, never infrastructure credentials. Production key custody, rotation, audit, and readiness-driven generation cutover remain future work.

- **Local stateful replacement.** Live service upgrade transfers a service's state as a memory object, tracks generations, invalidates stale connections, and re-registers the replacement through the name service (Chapter 16). This has not yet been extended to mutable state crossing the network.
- **Service isolation and routing.** Services execute in separate address spaces with delegated capabilities (Chapter 11). The name service is replicated across nodes and provides the routing indirection for a service somewhere in the cluster.
- **Certified work migration.** The scheduler migrates threads between LPs with generation-validated handoff and sustained-window load rebalancing (Chapter 10). This per-node mechanism supplies design evidence for future cluster-wide load rebalancing.
- **Observation substrate.** The Sitas executor exposes task counts, poll counts, queue depth, and shard snapshots (Chapter 9). Shard-to-shard message flow can be measured. Cluster-wide collection and use of those measurements by a placement controller remain future work.
- **Signed binaries at the loading boundary.** The EL0 loader validates ELF structure, rejects writable-executable segments, maps images with page-level permissions, and requires an Ed25519 CLS2 note bound to the requested service name (Chapter 15 and Chapter 16). Store lookup, administration ingress, and deployment recheck that identity.




Figure 17.1: Secret-bearing S3 and Kafka connectors receive infrastructure profiles; applications receive only named, role-attenuated service capabilities.

17.5 Current bootstrap and node model

The ordinary AArch64 kernel embeds eight signed bootstrap services: `ns`, `nvme`, `rng`, `net`, `objstore`, `uart`, `observe`, and `grantctl`. All boot hardware-driver images must be available while grants are prepared, before any sibling driver thread starts. Otherwise preparation could wait on its own unstarted storage driver. Other staged services load on first use from the signed bundle in the initial object-store image and remain cached in kernel memory.

The x86-64 configuration embeds its larger tested service set as well as staging it on disk. AArch64 HVF compatibility and selected test features add recovery or fixture images. `crates/catten/src/service/store.rs` defines these configuration-specific sets; eight is not a cross-platform total.

This establishes the minimal-node bootstrap shape. The current `-deploy-test` serial command loop remains a kernel-side validation and administration shim; production management enters through userspace deployment ingress and still needs further hardening.

17.5.1 Discovery and membership

The operational DNS-owned Raft group now admits members discovered on the cluster Ethernet through replicated `JOIN`, joint consensus, and `FINALIZE`. The three-guest ingress fixture exercises that path before driving placement and VIP failover. A smaller two-guest fixture remains useful for focused catalog and deployment checks; its topology is not a membership restriction.

A production node joining shared cluster state must complete three distinct operations:

1. **Discover the cluster.** The node uses broadcast discovery or a configured seed as discussed for Raft peers in Chapter 14. Discovery exists as a service, supplies MAC routes and cluster posture, and locates the anchor in the generic admission test. Discovery alone does not grant voting authority.
2. **Receive cluster identity.** The replicated catalog can distribute the set-once public signing key. Today that key must equal the build-time bootstrap anchor. Establishing trust from a genuinely blank start and rotating keys are not implemented.
3. **Join shared state.** The node becomes a member of the replicated state machine and begins receiving assignments. The leader resolves signed singleton, fixed-replica, every-eligible-node, affinity, and anti-affinity policy into concrete node sets and reconciles them after membership or drain changes.

The target may allow a node to discover peers and participate in a restricted bootstrap before cluster key material is established, but it cannot validate executable artifacts without an accepted public key. An authorized administrative operation would establish or rotate that trust through replicated state. The current prototype instead uses a build-time anchor and a set-once, idempotent key ceremony.

17.6 Software ingress and deployment

17.6.1 The target pipeline

CharlotteOS gives the software supply chain an explicit cluster boundary. The intended pipeline is:

1. build a self-contained workload from reviewed source and dependencies;
2. evaluate policy and retain provenance, SBOM, test, and attestation evidence;




Figure 17.2: Privileged operational-profile pickup keeps ciphertext references in Raft and decrypts directly into immutable connector launch memory.

3. bless and sign the immutable workload identity off-cluster;
4. make the signed artifact available to the cluster; and
5. change replicated desired state so the cluster validates, places, and runs the accepted version.

The signing private key remains off-cluster, and placement fetches complete artifacts instead of executable dependencies from the Internet. The same immutable object can consequently run on any eligible node without reconstructing a userspace installation there.

17.6.2 The implemented pipeline

The current deployment pipeline has three stages:

1. **Blessing and signing.** Version-controlled policy admits an artifact and the host-side build and `cluster-sign` tooling sign it with the cluster key. CLS2 metadata binds the logical name, class, release, rollback counter, parallel-instance permission, and an optional SHA-256 link to retained SBOM/build-provenance evidence. Nodes receive only the public key.
2. **Validation.** Each node validates every loaded ELF against the public bootstrap anchor and, in the deployment path, the matching replicated key. The loader, object-store resolver, administration ingress, and agent enforce signature, logical-name, and digest checks. The present ceremony can distribute only the build-time anchor; it is not a general enrollment or rotation protocol.
3. **Assignment.** A Raft-committed record directs a concrete replica set to load an exact signed variant per node, including its immutable ELF digest. Each selected node's agent fetches the opaque object key through its locally provisioned S3 capability, then validates and runs those exact bytes. Endpoint and credential details remain inside that privileged connector rather than the descriptor or application.

The replicated catalog records a sorted concrete node set and variant pins per artifact and an independently generation-fenced readiness registration for each active owner. The leader resolves *somewhere*, fixed replicas, and *every eligible node* against admitted, non-draining voters and reconciles the assignments when that set changes. DSR routes new cluster-VIP flows across the ready subset. The boundary between this management loop and the DSR packet path is shown in Figure 13.1: placement and readiness determine the eligible set, while each packet uses an already materialized snapshot.

17.7 Placement: contract, observation, and movement

17.7.1 Executable variants and architecture eligibility

Each `CDEPLOY6` component revision carries up to eight signed binary variants. Every variant binds an immutable object key and SHA-256 to ELF architecture, exact runtime ABI, required CPU features and selection priority. One release descriptor still represents one logical component, even when its ARM and x86 replicas execute different binaries.

The kernel reports AArch64 or x86_64, runtime ABI 3 and the intersection of integer features across all configured LPs. The current optional bits cover ARM LSE/CRC32 and x86 CMPXCHG16B/POPCNT. Missing profiles are ineligible. Placement filters compatible, non-draining voting members before memory, replica and affinity ranking; explicit pins undergo the same checks. An ARM-only revision therefore cannot count x86 nodes toward its replicas.




Figure 17.3: A signed multi-component release is admitted atomically to desired state; artifact retrieval, launch, publication, and readiness then reconcile per component.

Selection uses signed priority, feature specificity and descriptor order. Raft commits the chosen variant index beside each replica node; catalog-v19 snapshots and queries preserve that pin. A later CPU report cannot change an existing generation's executable. If a new node incarnation loses support for its pin, the controller commits a compatible replacement in a new generation, even when the node set stays the same. The agent fetches the pinned key/digest and rechecks local compatibility. Kernel admission rechecks actual ELF machine, signed requirements, digest and identity before creating the domain. Profile reports bind an observation to a node identity; they do not attest to its hardware. CPU hotplug and vector context contracts remain separate work.

The signer reads an ELF path instead of accepting a supplied digest. Additional `-variant` options supply object key, ELF path, feature mask, priority and ABI. Required instruction extensions must match the reviewed build configuration. The descriptor has a 152-byte header; retired descriptor and catalog formats reject without defaults. See `docs/reference/execution-targets.md` for exact encoding, signing examples and future-store migration requirements.

17.7.2 Declared policy and bounded scheduler

The shared `PlacementPolicy` type expresses desired replicas, maximum instances per node, minimum distinct nodes, *every eligible node*, an affinity group, and an anti-affinity group. A request for concurrent replicas is invalid unless the artifact's signed CLS2 metadata contains `PARALLEL_INSTANCES`. `CDEPLOY6` signs this policy, the leader resolves it to concrete assignments, and catalog-v19 snapshots retain both the desired set and per-node readiness. Affinity groups share a stable ranking seed; anti-affinity groups require unused nodes and fail closed when the eligible set cannot satisfy the separation. A policy that needs more distinct nodes than the current eligible set fails admission.

The scheduler remains intentionally bounded, but it now accounts for a useful minimum of node capacity. Each node reports free and usable frames plus recent CPU occupancy through the cluster's existing identity-checked peer path. The leader rejects replayed epochs and low-pass filters free memory and CPU with an integer EWMA before committing placement input through Raft. After three missed reporting intervals it treats a sample as unknown. A new boot incarnation resets the filter rather than blending unrelated processes.

This does not filter observability history. Raw one-second samples in memory, and in the optional disk archive, retain short-lived spikes for diagnosis; the five-second report, EWMA, bucket hysteresis, and freshness lease form a distinct control signal. The descriptor's stack budget and fixed runtime pages form a memory promise. The leader reconstructs promises held by other catalog deployments before admitting a release, and every selected component debits projected dynamic and static headroom. If a report expires while a node retains commitments, those promises remain visible with no additional headroom instead of turning into an apparently empty node. Hard memory admission preserves a one-sixteenth reserve, while CPU pressure remains a soft ranking signal.

Pressure may now change an existing replica set, but only when the same candidate survives a 30-second dwell; another pressure move is held for a 60-second cooldown. Membership loss and committed drain bypass dwell because the old target is no longer eligible. The result is still committed as a generation-fenced reassignment, so replacement readiness and DSR eligibility advance together rather than following an uncommitted local judgment.

The policy does not yet express heap, processor, or storage requests, labels, named failure domains, or more than one instance of an artifact on a node. Reassignment advances the whole deployment generation, so retained replicas restart rather than participating in a rolling surge/unavailability protocol.

17.7.3 Runtime observation: local substrate only

Declared relationships are guesses. Shard-level message counts, byte flow, queue depth, and task snapshots are already observable inside a node (Chapter 9), and the distributed name service can identify which components call which. The target controller should aggregate these signals across nodes and base placement changes on sustained behavior.

The node-capacity path is the first cluster-wide feedback loop, deliberately limited to slow memory and CPU pressure. Detailed executor and communication metrics are not yet aggregated across nodes or used for placement; extending the controller requires similarly explicit filtering, dwell, authority bounds, and decision telemetry rather than feeding raw measurements directly into an actuator.

17.7.4 A keyhole into the cluster

The node HTTP keyhole remains useful for diagnosis, but placement and ingress need an operator view whose subject is the cluster. The implemented `/cluster` dashboard and `/cluster/metrics` JSON endpoint join the Raft leader, term, commit index, and membership epoch with admitted and draining nodes, filtered capacity freshness, desired and ready replicas, and the advertiser and eligible backend set for each VIP. The schema is explicitly versioned as `charlotte.cluster.v2`.

DNS constructs the underlying, bounded `CLOBSV2` record from one locally applied catalog view. It serves the record only while the same bounded-read lease used by DSR is valid; httpd decodes it and returns HTTP 503 when no fresh record is available. Raw one-second observations remain in the node's memory history and optional diagnostic archive. The cluster view instead exposes the slower signals and decisions that drive placement, while retaining a per-node freshness marker so a committed resource promise is not confused with a recent capacity measurement.

An unnamed operations VIP on port 443 can identify the built-in TLS keyhole. An enrolled reader or administrator certificate is required. The leader normally advertises that VIP, but DSR may deliver the connection to any admitted, non-draining member in the committed availability projection. Recent current-term replication acknowledgements supply the leader's receive-time evidence; followers use the replicated set rather than local peer timers. Missing or stale term/membership projections admit no new VIP flows. Health changes commit a new generation and flow epoch while retaining the full voter set and previous flow bindings. Existing TCP/TLS traffic is not rehashed or replayed to make another backend complete it. Consequently each reply names both the leader and the serving node. Leadership movement changes the advertiser without making browser polling part of consensus or requiring the leader to terminate every connection.

Discovery supplies identity-to-MAC routes, and Raft commits membership. These routes have no cryptographic peer authentication; session and expected-peer checks reject mismatched messages but do not establish a peer's identity. Neither supplies management IP addresses. The dashboard therefore does not manufacture drill-down links from MAC addresses. A future signed, leased management-endpoint record can support an authenticated `/cluster/nodes/{node-key}/metrics` proxy, keeping node drill-down behind the same policy as the cluster view.

The current native adapter requires mutual TLS on port 443 for both direct node and VIP access. Its signed, encrypted boot resource supplies the server identity, client roots and exact leaf/role enrollments; neither credentials nor private keys belong in the application descriptor or Raft log. A browser uses an operations-issued PKCS#12 client identity with `clientAuth`, not the cluster signing key. The complete boundary and browser setup are documented in `docs/architecture/cluster-observability.md`. Public

development trust is not protected enrollment; live-session retirement, protected custody and broad pressure remain separately unqualified.

17.7.5 Focused stateless-handoff validation

The focused two-guest fixture starts the signed `greet` artifact on one node, verifies exact-generation readiness and the selected architecture variant, reassigns it, and checks cooperative and forced retirement. An identical signed submission through the follower preserves its generation. Legacy DNS proxy access remains denied for this scoped application; public echo separately proves cross-node RPC. Generation fencing protects the replacement. Load-driven and stateful migration require additional protocols described below.

17.7.6 Future stateful cross-node migration

Stateful migration must extend the local live-upgrade protocol from Chapter 16:

1. the cluster instructs the target node to obtain, validate, and prepare the component in a new address space;
2. the old instance exports explicitly owned mutable state and the cluster transfers that state to the prepared instance;
3. the target accepts ownership under a fencing protocol;
4. the new instance registers through the distributed name service, advancing the name generation;
5. clients resolving the name reach the new owner, while clients with stale connections observe `EndpointClosed` and re-resolve; and
6. after the new owner is committed and reachable, the old instance is retired and its resources reclaimed.

Generation tracking, endpoint invalidation, name-service re-registration, and local memory-object state transfer are verified primitives. Network transport and ownership fencing for mutable service state are not implemented. The demonstrated cluster handoff starts the same immutable artifact with fresh state.

17.8 Deployment, rollout, and reassignment

The deployment-test QEMU flow uses two guests to isolate one source-to-target handoff. A signed artifact is assigned through replicated state; the remote agent obtains and verifies it; the service is invoked across the network; and the assignment moves without losing the logical name. Both guests complete with zero failed or pending self-tests. The operational membership, replica, and ingress paths also run in a three-guest fixture, and the underlying Raft membership is generic. These fixture sizes describe test coverage only.




Figure 17.4: A focused two-guest deployment fixture combines Raft-held desired state, local reconcilers, capability-routed services, and central object pickup; the architecture admits larger voter and replica sets.

17.8.1 Replicated deployment manifest

The distributed name service's Raft catalog (Chapter 14) also holds a **deployment manifest**:

```
artifact -> {replica nodes, replica variant pins,
generation, signed descriptor}.
```

The map is committed through the same log as name registrations. Deployment is therefore ordered, replicated, generation-fenced cluster state rather than per-node configuration. The descriptor-only deployment operation (DNS 33) admits a current signed descriptor; the named query (DNS 16) reads a replica's applied state. Packed deploy/query operations and the redundant named admission envelope are retired. The signed descriptor alone supplies object keys, digests and requested placement. Queries use the tagged `CDEPQR01` record with exact replica variant pins.

The signed descriptor authorizes the deployment decision and binds artifact identity, placement policy, and resource limits. Raft orders and replicates the result. Production ingress still needs a separately delegated online administrator identity and audit policy in addition to the offline signature.

17.8.2 Cross-node hosting and generation fencing

A service hosted away from the leader registers through a **remote-register relay**, because only the leader may commit catalog entries. The leader returns the committed generation. The two-phase register/activate sequence and generation-fenced endpoint-death unregister are preserved across the relay, so a retiring host cannot clobber a replacement's registration.

Cross-node invocation uses the existing `OP_CALL` relay. A client on any member reaches the service at its current owner through the replicated name service rather than through a node-specific application address.

17.8.3 The deployment agent

Each networked node with durable local storage runs an `agent`. It polls the manifest for assignments to its node key. Each assignment pins a variant from the signed descriptor. The agent pulls that variant's opaque key through the provisioned S3 connector; when no connector is registered, the local test cache must satisfy the same selected digest and signed name. Architecture, runtime ABI and required CPU features are checked before launch. The agent then invokes the scoped deployment-authority syscall with both owned memory objects; no descriptor-less record or launch fallback remains.

The sole scoped runtime API is `launch_scoped_artifact`: it consumes the ELF and descriptor owners with their exact lengths and returns an owning `DeployedArtifact`. Syscall 76 takes four arguments and returns both the ASID and the principal derived by the kernel from the verified signed descriptor. Packed-name input, named aliases and a caller-supplied retirement name are removed. Rejection returns two zeroes and consumes submitted inputs; local length rejection releases the two Rust owners before submission. Retirement requires an explicit nonzero principal; zero cannot select a lone deployment. See `docs/reference/scoped-deployment-launch.md`.

The kernel snapshots and revalidates the exact ELF and descriptor, maps the ELF into a fresh address space, gives the application only the grant controller and its immutable descriptor, and starts it. A descriptor-authorized service publishes its endpoint through `grantctl`; the agent supervises the assignment. When

the manifest assigns the artifact elsewhere, the agent retires the service and causes its address space to exit. Endpoint closure is observed by `dns`, whose generation check prevents a stale unregister.

The supervisor-designated agent authority is the one narrow kernel mechanism: only that agent may start or retire a verified, name-bound ELF memory object. The desired placement and administration logic remains a userspace coordination concern.

17.8.4 `clusterctl` and the test console

`clusterctl` is the prototype outside administration interface. It wraps the DNS manifest operations and object store behind:

- `upload`, which stores a note-signed artifact under its derived cluster-wide id after checking that CLS2 blesses the requested name;
- `status`, which carries a full artifact name in moved memory and returns the complete committed descriptor and replica variant pins; and
- `notify`, which verifies a signed `CDEPLOY6` descriptor and commits its executable variants with their object keys, digests and execution targets, sequence, per-thread stack pages, maximum active-thread count, and cooperative shutdown grace period and capability grants without copying an ELF through Raft.

Controller interface version 3 requires full-name status queries. The status and rollout names use the signed descriptor's 1–48-byte printable ASCII grammar. Malformed names return -3 without attachments before DNS forwarding; a valid absent name returns -1. Notification validation retains its separate -13 result. The unsigned `deploy` command and packed DNS deploy/query operations are removed, as is descriptor-less launch syscall 64. The serial test console provides `upload` for short names and `status` for full names; deployment uses the host's `cluster-sign deployment-notify` command. Signed scoped launch remains the application launch contract. Retired opcodes reject rather than translating their old payloads.

The normal service set also starts `deployd`. Its bounded, mutually authenticated TLS endpoint accepts a `POST` to `/v1/deployments` on guest port 7444 with exactly one signed descriptor as the body. The client must be an enrolled administrator before controller dispatch; the signature remains the descriptor's authorization and integrity envelope. Readers can observe status but cannot mutate. Missing management credentials disable network admission without a plaintext fallback; see Chapter 20. Lower sequences are rejected, different bytes at an existing sequence conflict, and identical notifications are idempotent. QEMU's user network forwards host port 8081 by default; `cluster-sign deployment-notify` is the corresponding host client.

The client may contact any member. A follower relays the bounded submission to the current Raft leader over a source-validated peer route and correlates the committed result back to the ingress request. The management client therefore does not need a separate leader-discovery protocol.

An interactive kernel serial console in the `-deploy-test` flow issues these commands against the live cluster for validation. Production operations use the userspace notification endpoint, whose remaining hardening includes network-level denial-of-service controls, an online audit identity distinct from the signing key, and production transport policy. The raw mutation path and serial shim remain test-only privileged interfaces.

17.8.5 Serve deployment requests without replay

Deployment ingress progresses through listener setup, input, controller calls, output and logical close. Each accepted phase keeps its owner and original deadline; advancing one client must leave the other clients observable.

Optional detail: CQ positions and listener setup

All seven deployment HTTP controls use owning controller operations bound to the default CQ. Each operation retains its accepted pending call, socket, receipt-validation envelope and one five-second deadline captured before request preparation. The reactor keeps accepting/parsing inputs and observing other replies while one controller request remains outstanding. Listening, input, control, output and close phases share four positions, including listener setup. Creation, listen and accept operations bind their exact pending owners to the same CQ. Listener observation rotates alongside input, controller, output and close work, waiting for the earliest original deadline.

Listener setup retains one five-second deadline from reservation through creation, listen and accept admission/binding. Only rejected queue-full submission permits 50 ms backoff and another attempt of that phase; accepted requests are never replayed. Confirmed rejection or unstarted preparation failure moves any known socket into the existing close pool. Uncertain observation, malformed reply, binding rejection or expiry aborts with the complete owner live. An admitted idle accept has no timer. See `docs/reports/audits/2026-10-22-security-deployment-listener.md`.

Timeout cancels the exact pending owner and returns HTTP 503 with error -22 (`clusterctl::ERR_RPC_TIMEOUT`) Accepted mutations are never replayed. Observation failure after acceptance reports uncertainty (-5), rather than a routing rejection. The receiver may already have committed or may still own its moved request and original memory charge. Local cancellation proves neither remote rollback nor physical cleanup. Rejected accepted-call CQ binding or wait admission retains the whole owning scope through domain abort.

Optional detail: Controller relay and DNS ownership

The controller server forwards those seven HTTP controls and named status in eight owning CQ positions. Original incoming backing plus one copied DNS request reserve at most 2,098,176 bytes; returned records, decoder allocations and copies retained by DNS after earlier completion remain separate. One server-side five-second deadline starts before validation and spans notification preflight and mutation. It is separate from the caller's unchanged deadline. Only an explicit absent record or a checked older revision permits submission; a failed, malformed or foreign query cannot stand in for absence. Identical signed bytes return the existing generation, and stale/conflicting revisions reject.

Each DNS phase submits once and binds before parking. A server turn receives at most eight requests and rotates relay observation before checking lifecycle. Timeout cancels the DNS owner, ends the source mapping and only then publishes the upstream timeout. A delivered DNS copy may retain its original charge. Accepted uncertainty permits no replay. Shutdown disposes pending DNS calls before mappings and incoming reply/loan authority; binding/wait rejection retains the pool through abort. Legacy upload/join/key handlers still block on this endpoint, and bounded validation remains synchronous. See `docs/reports/audits/2026-10-22-security-controller-relay.md`.

17.8.5.1 Read input and send confirmed output prefixes

Input headers retain five seconds and complete input thirty seconds from observed accept completion. Progress and unrelated wakes do not restart those budgets. Retained prefixes and active controller request reservations share 1,049,088 bytes, including rounded moved-request pages and retained release envelope capacity. Temporary preparation copies, receive/reply pages, allocator overhead and TCP buffers are separate. Rejection preserves other owners; ending a logical reservation does not refund receiver-owned backing.

Response outputs retain complete backing, socket and a pending moved send page on the same CQ, with one original five-second deadline. Owned response capacity is capped at 64 KiB per position. A positive TCP prefix receipt permits sending only the remainder; timeout, invalid receipt or observation failure ends output without resending uncertain bytes. Enqueue is no peer-delivery or rollback proof. Each service turn advances input, controller, output and close work before waiting.

17.8.5.2 Close before releasing the client position

Logical close retains the socket and accepted call until a checked receipt. Uncertain close retains the whole scope through abort. A receipt does not prove peer delivery or physical release.

Optional detail: Logical-close receipts and admission backoff

A consuming logical-close owner retains the socket and accepted pending call on the same CQ. Its client position releases only after a checked Started (0) or Unavailable (1) scalar receipt without attachments, under one original five-second admission/observation budget. Only queue-full rejection permits 50 ms admission backoff and another submission. Accepted close is never replayed. Deadline, binding/wait rejection or uncertain observation retains the whole scope through domain abort; incomplete close Drop also aborts before field cleanup. Unavailable concerns an absent, nonreused full ID within the captured service incarnation. It proves neither former ownership nor peer delivery or physical release. Foreign live entries and unreserved IDs reject; exhausted ID reservation rejects before backend allocation. Existing close operations drain on shutdown under their original deadlines while other client owners remain live.

DNS execution, legacy controller handlers, response rendering, blocking destructors and all-positions admission pressure can still delay healthy clients. HTTP keyhole serving remains serial. See `docs/reports/audits/2026-10-22-security-deployment-close.md`.

17.8.6 Apply independently signed descriptors

For a release made from several independently signed components, `cluster-sign deployment-apply` prevalidates all descriptor files, rejects duplicate artifact names and retains the positive generation returned for each admitted descriptor. A complete ready record must match that exact generation; older observations remain pending, while a newer generation reports supersession. Malformed acknowledgement or readiness records stop observation without replaying accepted work. Apply captures one checked monotonic deadline before file preparation and carries it through every admission and readiness query. Connect, partial writes and response fragments use the remaining budget; the polling interval is shortened to the time left. Ingress endpoints must use numeric `IPv4:port` or `[IPv6]:port` with a nonzero port; hostnames and URLs reject before network access. Zero apply timeouts and values outside the clock range reject. Blocking host file I/O and stdout are not preempted, and readiness still uses status polling. Artifacts must already be signed and uploaded; object-store credentials remain outside the generated application and its descriptors.

`deployment-apply` orchestrates independent descriptor admissions. Each descriptor occupies a separate Raft entry, so a later failure can leave an accepted prefix committed. The client does not replay notifications; reconcile accepted work before an explicit retry. Identical descriptor admission remains idempotent. The atomic alternative is described next.

Optional detail: Notification and standalone status validation

All signer notification commands validate their complete HTTP-202 success body before reporting acceptance. Deployment, operations-bundle, shutdown and ingress policy use one positive generation; release uses its digest-bound receipt. Malformed success is uncertain because the request may already be committed; the client does not replay it. Every response reader preserves the complete body after the first HTTP separator and trims only JSON whitespace. Ingress-policy status validates its five current fields, bounded assignment count and signed validity span before output. This is structural observation, without a local UTC admission or peer-authentication decision.

The standalone `deployment-status` command uses the same complete rollout codec. Zero or omitted wait prints a valid current pending or ready record; a positive wait requires validated readiness. Missing, duplicate, nested, trailing or inconsistent records reject immediately. The shared status reader preserves the complete declared body after the first HTTP separator and trims only JSON whitespace. Extra separators and Unicode whitespace cannot hide invalid data from status or apply. Invalid artifact names reject before waiting or connecting. Named status observes the current record, which may change while it waits; it supplies no binding to an earlier admission.

17.8.7 Admit an atomic release

A signed `CRELEASE` envelope produced with `cluster-sign release-sign` and submitted with `release-apply`. Its outer signature binds a release name, monotonic sequence, and the exact ordered bytes of up to 16 distinct nested descriptors; the complete envelope is bounded to 3,584 bytes. The cluster verifies both the outer signature and every nested deployment signature. Every nested descriptor must use `CDEPLOY6`; retired formats reject even when correctly signed. A follower relays the request to the current leader, which resolves all signed placement policies against admitted, non-draining voters and proposes the concrete replica sets as one Raft command. The state machine preflights every release and component revision before changing the deployment map, so desired state changes all at once or not at all. A commit receipt captures the release generation and each component deployment generation in signed-envelope order. An exact retry returns a receipt while every component still has those signed descriptor bytes; a superseded component rejects without changing live state. The signed release record survives catalog snapshots.

Atomic admission changes desired state in one command. Fetching, launching and readiness still progress independently for each component. The client retains the receipt's exact component generations and the original deadline; uncertain submission is not replayed.

Optional detail: Release receipts, startup retries and readiness

After atomic admission, agents fetch, launch, and publish independently. `release-apply` validates a complete `CRLADM01` receipt bound to the exact signed envelope digest and descriptor count, then retains each component's own deployment generation. Older observations stay pending, matching ready observations complete, and supersession fails. Malformed receipts or status records leave the operation unconfirmed without replaying its notification. Release apply carries the same original deadline through startup, receipt admission and component observation.

A startup attempt can repeat only after a connection failure before any HTTP write, or a complete

Optional detail: Release receipts, startup retries and readiness (continued)

HTTP 409 response with the single numeric error `-23`. That checked incompatible-target result comes before release/component/operational publication; its negative result may itself be committed to Raft. The client retains the exact signed bytes and uses at most one second of backoff within its original budget. Other errors, uncertain submission and failures after receipt acceptance stop the command.

Both QEMU deployment-ingress workers first wait for the guest listener and initial DNS leader markers in their existing bounded serial loop, then invoke it once with the original fixture budget left. QEMU forwarding may accept TCP before the guest listener exists. A failed worker ends the run; it cannot conceal a lost response or an accepted but unready release by restarting admission. An operator must reconcile the exact release and component state before choosing a further attempt. Standalone `release-notify` still submits once.

Host polling, blocking host file I/O, and ingress peer authentication remain separate work. Coordinated rollback, progress policy, and a semantic process bundle that also binds BPMN, schemas, and provenance remain controller work.

17.8.8 Observe readiness and reconcile placement

The same endpoint accepts `GET /v1/deployments/{percent-encoded-name}`. It reports `committed`, `replacing`, or `ready`, together with desired and ready replica counts. A ready observation is generation-safe: all desired nodes must have active registrations carrying the exact deployment generation. A stale endpoint with the same name cannot make a replacement rollout appear ready.

The signed descriptor may carry node key zero to request automatic placement. A singleton prefers the current Raft leader and uses a deterministic fallback when that node is draining; fixed replica counts and *every eligible node* select distinct admitted, non-draining voters. The leader continuously reconciles that set after membership changes. A nonzero key remains an explicit singleton pin. Replica policy is admitted through a `CRELEASE`, giving affinity decisions the complete component context. Full signed artifact names up to the 48-byte CLS2 limit travel in memory-backed catalog operations rather than the historical eight-byte scalar encoding.

The node agent now reconciles the complete replicated deployment-name set, rather than polling only `greet`. A node can own up to 64 independently named application domains. Each domain is fenced by the principal derived from its signed artifact name, so a generation change retires only the matching application even if address-space identifiers have been reused. This bound is kernel admission policy, rather than a naming or descriptor-format limit.

Automatic placement now covers singletons, fixed distinct-node replica sets, every eligible voter, stable affinity/anti-affinity ranking, cumulative memory-capacity admission, CPU-pressure ranking, rescheduling, and exact-generation readiness. The controller commits desired assignments through Raft while node agents remain mechanism-only reconcilers. It still needs explicit heap/CPU/storage requests, labels and named failure domains, multi-instance-per-node execution, rollout surge/unavailability, and rollback.

The development runner's `-deployment-ingress-test -timeout 240` option proves the complete host upload to TLS RustFS, signed atomic release admission, S3 pull, scoped launch, and generation-safe readiness path. It is an integration fixture; production still needs a release controller that manages policy approval, progress deadlines, rollback, and operator audit identity.

17.8.9 Retire an application under its signed grace

Retirement is nevertheless bounded locally. On the first reconciliation poll, the kernel publishes a drain request and monotonic deadline in the domain's read-only launch page. A lifecycle-aware application stops new work, completes or aborts external transactions, returns from its resource-owning scope, and then exits. If any domain thread remains, the kernel forces termination on the agent's first retirement poll at or after the signed deadline and reclaims the address space only after generation-safe reaping. While retirement is active, the agent polls at most ten milliseconds apart. Figure 17.5 shows this path.

17.8.10 Coordinate a whole-node shutdown

Production whole-node shutdown begins off-cluster as a fixed-size, signed `CSHUTDN1` intent. It binds one nonzero target node, a per-node monotonic sequence, a UTC validity interval, whole-node and per-phase grace budgets, and the power-off reason. There is deliberately no broadcast target: an operations controller can drain nodes in an order that preserves Raft and application quorum. The operator creates the record with `cluster-sign shutdown-sign` and submits it to `POST /v1/shutdowns`; no private key enters CharlotteOS.

Any member may receive the bounded envelope. A follower relays it over the reliable-message channel, while the leader verifies the committed cluster key and trusted UTC before proposing it. The catalog state machine verifies the signature again, fences stale and conflicting per-node sequences, and retains the exact envelope in snapshots. The target agent consumes only locally applied state, re-verifies the envelope, and moves its memory capability into the kernel. The kernel admits only its designated deployment agent, independently checks the signature and target node, derives a local monotonic deadline from the signed duration, and transfers the service graph to a kernel worker. Thus retiring the agent cannot orphan a partially completed node drain.

The same lifecycle mechanism then propagates the node drain through the deployment plane. On receiving a kernel-authenticated `NodeShutdown` lifecycle request, the agent stops reconciliation and launches no new work. It marks every ordinary deployment and privileged operational connector as retiring, then retains and polls their owners until reclamation completes. Each child receives the earlier of its descriptor-signed grace deadline and the enclosing node deadline: the node transition may shorten an allowance but cannot extend it. Ordinary applications drain before their privileged operational connectors, so an application retains Kafka/S3 authority while it finishes or aborts external work. The agent acknowledges and exits only after both child sets are empty.

17.8.10.1 Drain consumers before their providers

The kernel's next shutdown layer transfers the published steady-state handles out of the launch registry and retires high-level node services in reverse dependency order: deployment ingress, deployment control, deployment agent; HTTP and time; cluster catalog, reliable messaging, and discovery; TCP/IP; and the frame router; and finally the object store. Each phase must be generation-safely reclaimed before the next receives its request. Per-phase grace is capped by the enclosing node deadline.




Figure 17.5: Bounded cooperative shutdown for deployment retirement or an enclosing node drain, followed by generation-safe forced retirement. The application can acknowledge but cannot clear or extend a kernel-published lifecycle request.

Optional detail: Deployment, HTTP and time service drain

Deployment ingress, HTTP ingress, and the UTC time service also implement the cooperative path. Deployment ingress checks lifecycle on each reactor turn and on default-CQ wakes. On shutdown it stops listener replenishment, observes accepted creation/listen under their original budgets and moves their known sockets into the close pool. Idle accepts cancel before moving their sockets; no further setup is submitted. Logical closes drain under their original deadlines, then the other client owners drop together. Cancelled accept grants no remote rollback or physical release proof. Synchronous preparation/rendering and other phases' socket destructors remain separate shutdown latency boundaries.

Ordinary socket close and Drop share the consuming close owner, one original five-second budget and one accepted reply wait. Queue-full admission backoff stops after one second; unstarted failure retains the complete driver without a second destructor attempt. Accepted uncertainty aborts with its owner live, without ID restoration or remote replay. These budgets do not establish whole-service shutdown latency.

Controller calls are cancelled through their exact owners without proving remote rollback. HTTP ingress retains bounded lifecycle checks around its current accept/receive operation. Its receive timeout uses an explicit cancellation exchange with TCP/IP: closing only the local call capability would leave the server's deferred reply slot occupied and could discard later input if that socket were reused. Deployment input instead closes the whole socket owner.

Time closes its public endpoint and unwinds any pending NTP call, UDP socket, and persistence connection as one owning scope. Already admitted ingress work may finish inside the signed grace, but none of these services begins new work after observing the lifecycle request.

Optional detail: Transport, startup gates and cluster-core drain

The transport phase is cooperative too. TCP/IP runs after every socket consumer has drained; it closes admission, completes retained receive calls, stops residual protocol sockets, and releases its endpoint and owned NIC connection. The frame router then drops one owning scope containing the single NIC receive, deferred name lookups, routed service connections, and in-flight moved-frame calls. The NIC driver cannot transfer to device quiescence until both transport domains have exited.

Startup gates obey the same lifecycle contract. Long-lived services poll the node-ready name through bounded non-blocking lookups, checking the authenticated lifecycle page between attempts. HTTP, time, and TCP/IP can consequently acknowledge a node drain even if shutdown begins before local readiness is published. Before reclaiming a domain, the coordinator records per-phase counts for acknowledged, unacknowledged, and forced exits.

The deployment plane and cluster core participate in cooperative shutdown. Deployment ingress closes its listening and receiving sockets, cluster control drops its endpoint and service connections, and the agent interrupts startup or reconciliation waits before draining applications and then their operational connectors. DNS stops the Raft/catalog reactor and cancels pending transport and catalog work. Reliable messaging rejects retained sends, completes its deferred receive, and releases queued messages before discovery stops probing and settles pending cluster-status waiters. Bounded lifecycle-aware sleeps ensure a configured retry interval does not become shutdown latency.

Optional detail: Shutdown plan ownership and preparation

The plan uses inline storage for eleven single-domain service phases and three hardware domains. Construction and owner transfer allocate no plan backing. Abandoning either coordinator retains every unfinished teardown owner without root lookups, thread aborts, logging, or nested field destruction; explicit polling remains the only way to advance reclamation. This does not establish shutdown under heap exhaustion. Kernel worker context, stack, retirement node and table preparation now reject before roster transfer. Fresh pinned admission and inline input publication share a short local IRQ mask; first dispatch cannot precede publication. Losing unstarted preparation is cancelled after local guards leave; uncertain cleanup retains its complete owner. Later cleanup admission, the agent's fail-closed rejection policy and sustained progress still require separate qualification.

17.8.10.2 Require device quiescence before reclamation

The NIC, block and entropy domains transfer once to a device-quiescence coordinator. Each driver must publish `DEVICE_QUIESCED` and exit before its address space and launch-owned device grants can be reclaimed. A deadline or thread death cannot prove that DMA stopped; failed quiescence retains the domain and IOMMU state in quarantine.

Optional detail: Driver-specific quiescence

The remaining NIC, block, and entropy domains transfer exactly once to a device-quiescence coordinator. It never converts a deadline into an unconditional driver abort. Ordinary lifecycle readiness is insufficient: a driver must publish the distinct `DEVICE_QUIESCED` state and exit before the kernel reclaims its address space and launch-owned device grants. Otherwise the domain and IOMMU state remain quarantined for diagnosis. Every in-tree hardware adapter implements the driver side of this contract. VirtIO entropy resets the device before dropping its shared-DMA mappings. NVMe adapter closes admission, drains outstanding replies and DMA, observes a final NVM Flush completion, masks interrupts, clears `CC.EN`, and waits for `CSTS.RDY=0`. VirtIO block flushes before device reset; AHCI flushes, masks port interrupts, and stops its command and FIS receive engines; VirtIO net and E1000E close ingress and deferred receives, release queued frames, drain transmit descriptors, and then reset or halt the receive/transmit engines. A failed flush or drain still stops DMA where possible but withholds `DEVICE_QUIESCED`. Thread death alone is never treated as evidence that DMA stopped.

After verified device quiescence, AArch64 selects the FADT-advertised PSCI SMC or HVC conduit, masks interrupts, and invokes `SYSTEM_OFF`. It must not return: scheduling cannot resume past terminal drain. The fixture accepts QEMU exit only after the authoritative success and poweroff records.

17.8.11 Artifact naming

Artifact names are currently bare cluster-global names such as `greet`. The local staging object id is derived from the name using a `0xfffe...` tag over FNV-1a, while signed descriptors carry the opaque per-variant central-S3 object keys and full content digests. Resolved replica node/variant pins appear in the replicated deployment record.

The host image producer detects and rejects collisions in the complete bundle. Production should replace the truncated 48-bit name hash with a collision-resolving or fully content-addressed namespace.

17.8.12 Cryptographic boundary




Figure 17.6: Independent artifact, deployment, operations, and recipient-key roles converge only at cluster admission and the privileged connector launch gate.

Artifact validation uses Ed25519 signatures embedded in the ELF. The private cluster key remains off-cluster in the tools/cluster-sign host tool. The signature is stored in a standard ELF SHT_NOTE section named .note.charlotte-sig, with note type "CLS2". Its descriptor contains the logical name, artifact class and flags, release, rollback counter, signing-key id, optional provenance digest, and the 64-byte signature.

The signature covers the SHA-256 digest of the complete file with only the signature field treated as zero, making the signed representation deterministic. The matching public key enters the prototype in two ways: it is embedded in the kernel at build time as the bootstrap trust anchor and passed to services in the launch manifest; and the key ceremony commits it to replicated state through OP_KEYCEREMONY and OP_SET_KEY. This demonstrates a distribution path for dynamically joining nodes. The replicated value must currently equal the build-time anchor; blank-start trust establishment remains future work.

The EL0 loader verifies the note before mapping a domain. Signing is mandatory: unsigned or invalidly signed images are rejected. The runtime scoped launch gate rejects failed preparation; mandatory boot-fixture launch may still panic. By default the build signs staged services using the version-controlled development keypair at tools/cluster-sign/dev-key.hex, whose public half is the embedded CLUSTER_PUBLIC_KEY. A different key can be supplied through CLUSTER_SIGN_KEY_FILE; its value is a restricted key-file path, never the private bytes. Changing the signing file does not change the kernel's bootstrap root. Signing commands read private files through bounded, zeroizing buffers and enforce owner-only Unix permissions, except for the exact publicly known fixtures. Key generation writes a new mode-0600 file without printing private material. Hexadecimal key text and its trailing newline share one reserved erasing buffer through file writing. Private-key input retains an erasing vector through partial reads and errors; its full capacity is cleared on ordinary Drop. Normalized key text returns with its own erasing owner through permission checks and decoding. Source files, OS buffers and forced termination have separate lifetimes. Public-key file arguments share one bounded reader and hex parser across operational, ingress-policy and trust-policy commands. The complete file, including comments, is limited to 4096 bytes; Unix opens reject final-component symlinks and non-regular sources. These public file checks supply no key provisioning authority. Commands with public hex arguments keep that interface. Structured deployment and release files are bounded to 3,584 bytes, shutdown files to 144 bytes and ingress policies to 1,184 bytes before verification, notification or apply. Release signing checks its one-to-sixteen descriptor references before reading those files. Unix opens reject final-component symlinks and non-regular sources. Artifact sign/verify and deployment image inputs use the launch ABI's 4 MiB maximum; adding a note must keep the output within that bound. Deployment signing checks its one-to-eight variants before image reads. The host file-hash command streams regular files through a 16 KiB erasing buffer, with no artifact-size cap. ELF signing retains one read/write file owner and prepared image through a consuming rewrite. It writes the opened file if renamed and does not recreate an unlinked path; replacements are left untouched. Success refers to that opened file. Pathname continuity, concurrent content changes, partial writes and durable atomic publication remain separate boundaries.

Deployment, release and shutdown signing create new output files exclusively. Existing files and final-component symlinks reject before writing; use a fresh name for each signed record. Boot fixtures keep those records in fresh private run directories, preserving earlier runs. A failed new-file write closes its captured descriptor and leaves any output alone, including empty or partial files. All three key generators report incomplete generation and retain an already written private file if public output fails. Inspect files within the secured directory and use fresh paths before another generation. Diagnostics identify original paths without guaranteeing their current binding. Durable atomic publication and disk erasure remain separate work.

Build output and boot logs explicitly identify the current images as development images. The build refuses production trust mode (CATTEN_TRUST_MODE): protected bootstrap trust and recipient-key provisioning are not implemented. Independently generated role keys and protected boot remain prerequisites for production; file-based signing alone does not establish those properties.

Store resolution and deployment additionally check the signed logical name, and the descriptor pins each variant's full ELF SHA-256. The demonstrated `greet` service is a signed architecture-specific binary fetched from S3 or the validated local fixture cache, mapped, launched and reassigned. Exact-generation readiness and retirement are verified. Legacy DNS proxying of this policy-published service remains denied; authorized remote invocation is separate work. Public echo fixtures retain positive cross-node RPC coverage. Raft orders assignment, while signed admission authorizes deployment.

The local fixture helper closes a complete staging bundle in its fresh private run directory before replacing the named output. Link targets and earlier open readers keep their bytes; staging-write failure preserves prior output and retains failed staging for inspection. This host publication step supplies no fsync/durability or namespace-integrity guarantee.

17.8.13 Validated properties

The focused deployment fixture validates that:

- an explicit node assignment can be represented as replicated, generation-fenced cluster state;
- a signed, name-bound ELF can be obtained, independently revalidated, and launched by a node agent;
- a scoped service can become ready away from the Raft leader while legacy proxy access remains denied, and a public service remains reachable through the distributed name service;
- generation fencing protects a stateless reassignment from a stale owner's unregister; and
- deployment and administration have protocol shapes rather than requiring direct machine configuration.

Separate multi-guest fixtures validate dynamic DNS/Raft admission, replica placement, and DSR failover. Capacity-aware admission has unit and protocol coverage; multi-node pressure and freshness scenarios still need a dedicated fixture. Evidence is also required for rolling replacement, stateful cross-node migration, artifact-store recovery, production key establishment and rotation, and production administrative authorization.

17.9 Remaining implementation boundary

The gap between the demonstrated functionality and the target cluster operating system contains the following substantial coordination and trust work:

- **Dynamic membership recovery.** Discovery-bridged admission performs replicated `JOIN`, joint consensus, and `FINALIZE` in the durable DNS-owned group. Partition behavior, restart and rejoin within a live quorum, automatic failed-voter removal, and longer-running fault injection remain.
- **Trust establishment and key rotation.** The present key ceremony is set-once, idempotent, and limited to the build-time anchor. Authenticated blank-start establishment, overlapping rotation, revocation, and recovery remain.
- **Durable artifact availability.** Signed descriptor deployment pulls digest-pinned artifacts through a separately provisioned S3 connector; the legacy path uses per-node NVMe staging. Production work includes integrity-checked repair, retention, garbage collection, connector bootstrap recovery, and replication policy.
- **Cluster-wide observation.** Per-executor metrics must be collected and interpreted across nodes without turning transient telemetry into unstable placement decisions.

- **Placement and rollout depth.** The leader currently resolves fixed and every-node replica policy, basic affinity/anti-affinity, drain-aware membership, cumulative frame demand, and soft CPU pressure into assignments. The next scheduler adds typed heap/CPU/storage requests, trust labels, named failure domains, health and communication signals, multi-instance-per-node execution, and rolling surge/unavailability and rollback policy.
- **Replica health and failure convergence.** Exact-generation readiness gates DSR and replica counts converge after committed membership or drain changes. Health-driven replacement, automatic failed-member removal, and state-aware recovery remain controller work.
- **Stateful cross-node migration.** The stateless handoff must be extended with network state transfer, explicit ownership acceptance, fencing, failure recovery, and a consistency model.
- **Production administration authority.** The userspace `clusterctl` protocol exists, but the raw mutation endpoint and kernel serial shim do not enforce the intended separately delegated cluster-administrator capability. Authentication, authorization, audit, and safe concurrent administration remain.
- **Operational cluster services.** Production health management, upgrades, resource accounting, persistent storage policy, networking policy, secrets, logging, metrics, tracing, backup, and disaster recovery remain necessary even where their mechanisms differ from Kubernetes/OpenShift.

Most of this belongs in userspace coordination over the existing capability, messaging, storage, and consensus primitives. Future work must retain the discipline of the current mechanisms: explicit ownership, bounded communication, immutable artifact identity, generation fencing, and replicated decisions instead of per-machine mutation.

17.10 Related work

The vision combines ideas from distributed operating systems, capability systems, cluster schedulers, immutable software stores, and artifact-trust systems. The comparisons below identify intellectual neighbours; they are not claims of equivalent guarantees or implementation maturity.

17.10.1 Historical distributed operating systems

- **Amoeba** (Vrije Universiteit Amsterdam) is a close ancestor of the processor-pool model. Work can run on processors in a pool, dedicated machines provide file and directory services, and network-wide RPC uses capability-based access. Amoeba deliberately did not migrate processes; explicit cross-node migration is an extension in the CharlotteOS target.
- **Plan 9** (Bell Labs) separates terminals, CPU servers, and file servers, and centralizes authentication and key handling in `factotum`. Its machine roles and network-transparent names challenge the assumption that every node is an independent Unix installation.
- **Inferno** continues the Plan 9 line with a portable virtual machine and code distributed as data over the network.
- **Jini and JavaSpaces** contribute a discovery pattern in which services locate a lookup service, register, and provide clients with a proxy. JavaSpaces' tuple-space model resembles work or software being placed in shared space for an eligible participant to take.
- **MOSIX** explores a single-system-image cluster with resource discovery and transparent process migration. Its work on communication-aware placement, including Keren and Barak, *Opportunity Cost Algorithms for Reduction of I/O and Interprocess Communication Overhead in a Computing Cluster*, IEEE TPDS 2003, is a precedent for using interoperation cost in placement.

17.10.2 Cluster control planes and placement

- **Borg, Omega, and Kubernetes** established the modern cluster-management shape: desired software is submitted to a pool of machines, scheduling is a cluster decision made from constraints and packing, and controllers reconcile observation with desired state. Burns, Grant, Oppenheimer, Brewer, and Wilkes describe this lineage in *Borg, Omega, and Kubernetes: Lessons from Three Decades of Platform-as-a-Service*, ACM Queue 2016.
- **Kubernetes and OpenShift** are also the central counterpoint of this chapter. CharlotteOS is not attempting to wish away their distributed control responsibilities; it is testing whether a native execution and authority model can substantially shorten the machinery underneath them.
- **HashiCorp Nomad and Consul** pair cluster scheduling with service discovery, membership, and affinity or anti-affinity constraints.
- **VMware DRS and vMotion** demonstrate the full operational arc of declared placement rules, load-observed rebalancing, live movement, and network-level switchover, though for virtual machines rather than Charlotte execution objects.
- **Erlang/OTP distribution** provides node discovery, named processes, supervision, hot code loading, and patterns resembling load, register, redirect, and retire.

17.10.3 Capabilities and constrained execution

CharlotteOS also belongs in the lineage of capability-oriented and least-authority systems. The relevant distinction is between possessing an explicit reference that confers authority and inheriting a broad machine environment whose authority must be denied by policy. Capability systems, microkernels, language sandboxes, WebAssembly runtimes, and unikernels make different trade-offs along this boundary. CharlotteOS combines a capability-constrained service model with signed native artifacts and a cluster-level placement objective; similarity in one dimension does not imply identical isolation or compatibility guarantees in the others.

17.10.4 Trust, signing, and bootstrap

- **The Update Framework (TUF)** defines signed, versioned metadata and key roles for secure update systems. Its separation of root trust, online roles, expiration, and rotation is relevant to the blank-start and key-lifecycle work not yet implemented.
- **Uptane** applies secure-update principles in the automotive setting and illustrates offline and provisioned-key patterns.
- **Sigstore/Cosign and Notary** provide related approaches to signing, identity, provenance, and policy for deployable artifacts.
- **Measured boot and remote attestation**, including TPM-, ARM CCA-, and confidential-VM-based mechanisms, can complement artifact validation by establishing properties of the node on which the artifact will run.

17.10.5 Membership and artifact stores

- **SWIM** (Gupta, Birman, and van Renesse, DSN 2002) and implementations such as **memberlist** provide scalable membership and failure-detection techniques relevant to discovery. Failure detection and Raft voting admission remain distinct responsibilities.

- **Nix** demonstrates immutable, hash-derived software-store paths and reproducible dependency closure, closely related to the goal that software be an identified object rather than a mutation of a node.
- **OCI registries with signed manifests** demonstrate content-addressed distribution and integrity for today's container delivery model. A CharlotteOS artifact service needs analogous availability and lifecycle properties even if it does not store OCI filesystem images.

17.11 Research test

The cluster vision can be summarized as the following proposition:

> Containers are partly an artifact of retrofitting isolation, reproducibility, software distribution, and workload mobility onto general-purpose operating systems whose primary administrative boundary remains the machine. If immutable artifact identity, capability-based authority, constrained execution, cluster-wide naming, and placement were native operating-system abstractions, much of the contemporary container execution stack could become unnecessary, while the essential distributed control plane would remain.

CharlotteOS is an experimental vehicle for testing that proposition. Evidence now spans signed and name-bound loading, capability-separated services, replicated naming and deployment state, dynamic membership, deterministic replica placement, central artifact pickup, remote invocation, generation-safe stateless handoff, and cluster-wide TCP ingress. Focused two-guest tests isolate particular transitions; three-guest fixtures exercise membership, placement, and failover; generic tests and safety models cover larger or exhaustively explored configurations.

The next decisive evidence concerns richer resource declarations, stable feedback-driven movement, rolling placement, state transfer, production trust lifecycle, failure recovery, administration, and sustained operations. Observing those mechanisms will show which complexity genuinely disappears and which merely moves.

18 Application Generation Vision

The server-class cluster vision (Chapter 17) asks what an operating system might look like if signed execution objects, explicit capabilities, and cluster-level placement were native mechanisms rather than layers constructed above general-purpose Linux. That direction creates an immediate application problem: a deliberately small, non-POSIX userspace does not run the existing body of server software, and asking ordinary application developers to program directly against a new kernel interface would make the platform impractical.

This chapter develops a proposed answer. A process-oriented generator such as Durga (`https://github.com/FrodeRanders/durga`) can mediate between application intent and the Charlotte execution environment. Developers describe a process in BPMN and implement business rules against a narrow generated contract. A Charlotte backend supplies executable wrappers, capability requirements, communication structure, and cluster desired state. The tools and domain model absorb most platform-specific knowledge.

The implementation already crosses both project boundaries. Durga's `charlotte` target emits a `no_std` adapter, Cargo and AArch64 build inputs, capability requests, named Kafka connector profiles, explicit stack and thread limits, signed replica and affinity policy, and deployment metadata for each BPMN component. A developer-owned `charlotte/resources.yaml` is created once, preserved across later regeneration, and must be reviewed before deployment output becomes usable. The same retained values drive descriptor-signing options.

Generated adapters compile into Charlotte ELFs. After CI builds, signs, and uploads them, Charlotte admits their descriptors atomically in a signed `CRELEASE`, resolves replica placement through Raft, fetches artifacts from central S3, mediates grants, launches isolated domains, and reports exact-generation readiness. Business handlers and schemas remain developer-owned completion points. A richer semantic bundle that binds the BPMN model, schemas, and provenance, together with a production release controller, remains the next boundary.





Figure 18.1: Durga turns process intent into Charlotte-native adapters, capability and connector requirements, signed release inputs, and cluster desired state.

18.1 The application thesis

The conventional response to a new operating system is to reproduce a familiar application interface. POSIX compatibility, a C library, sockets, a filesystem hierarchy, dynamic linking, language runtimes, and ports of common packages provide a path for existing programs. This effective compatibility also recreates execution assumptions from which Charlotte is trying to depart: ambient access to a machine-like namespace, software assembled from mutable packages, and a process API designed around one host.

The alternative considered here is compatibility at a higher level:



Compatibility moves into libraries, data formats, external-system connectors, diagnostics, testing, and developer tools. For a useful class of process-oriented business applications, developers may never need to see the operating-system interface. The generator and its runtime support can be the only code that understands such details as message endpoints, capability handles, service registration, memory objects, lifecycle events, supervision, and deployment metadata.

The resulting thesis complements Chapter 17:

> A constrained execution environment need not imply a difficult application environment when infrastructure code is generated from a higher-level model. CharlotteOS need not expose a familiar operating-system API if familiar tools can generate Charlotte-native applications.

The scope is deliberately narrower than all applications or existing software: it covers domains where the process graph is already an important source of truth and the surrounding infrastructure is regular enough to generate.

18.2 Durga's present application model

Durga is presently a BPMN-driven Kafka scaffolding and monitoring system. The BPMN model is executable input to a generator rather than documentation added after implementation. Durga derives workers, gateways, orchestration, topic setup, process lifecycle events, and monitoring structure from that model. The application developer completes or supplies the task-specific business behavior while generated code implements much of the surrounding protocol.

Three current backends demonstrate that the process description need not be tied to one implementation language:

- The Java target generates a Quarkus application using SmallRye Reactive Messaging. Tasks, gateways, and orchestration become CDI components wired to Kafka channels, with shared runtime support.
- The Rust target generates a Cargo crate. Tasks and gateways become binaries under `src/bin`, with common code in a generated library and shared Durga runtime support.
- The prototype Charlotte target generates minimal `no_std` activity adapters and a deployment plan. Kafka broker credentials stay in separately named connector profiles; applications receive only granted service endpoints.

The Java and Rust targets use the same process-event wire model and topic layout, so their components interoperate through the generated protocol. The Charlotte target consumes the same process topology and generates Kafka connector intent. Its current adapters establish the platform and deployment boundary; the complete process-event runtime is the next semantic layer. The process model can therefore remain stable while code generation changes the language and runtime used to realize it.

The Java and Rust deployment paths remain conventional. A generated application can include a JAR or Rust binaries, Kafka configuration and topic provisioning, a container build, a Kubernetes Deployment and Service, health probes, resource limits, environment configuration, and deployment scripts. Scaling combines application replicas with Kafka consumer groups and topic partitions. In an OpenShift environment, image policy, registry access, security context, network policy, routes, secrets, monitoring integration, and organizational admission policy normally add further deployment concerns. The Charlotte target instead emits platform build and deployment-planning inputs; operating the release remains outside Durga.

These mechanisms supply real isolation, durability, routing, scaling, recovery, and operational control for conventional applications on general-purpose hosts. Their distance from the original business process motivates a more direct generated representation for Charlotte.

18.3 Three distinct languages

The proposed architecture is easier to reason about if three layers are kept separate.

18.3.1 The business and process language

The upper layer contains BPMN and developer-owned business rules. It describes activities, gateways, events, participants, message flows, data objects, timers, failures, and process completion. Handwritten code supplies domain behavior such as validating an invoice, calculating an entitlement, or selecting a payment route.

This layer should remain largely independent of Charlotte. A developer should understand the business domain, the supported BPMN subset, and the Durga task contract. Charlotte-specific message buffers, deployment calls, signing notes, and capability handles should not leak into ordinary rule code unless the application deliberately requests a platform-specific facility.

18.3.2 The Durga semantic execution model

The middle layer gives execution meaning to the process. Its concepts include:

- process definitions and versioned process instances;

- activity entry, completion, failure, cancellation, and retry;
- gateways, branch selection, fan-out, joining, and correlation;
- messages, signals, timers, call activities, and subprocess scopes;
- typed or schema-identified inputs and outputs;
- state transitions and lifecycle observations; and
- delivery, replay, idempotency, and failure semantics.


Some of these semantics are explicit in BPMN. Others are Durga runtime choices or policies that must be made explicit before an alternative backend can claim equivalence. For example, a sequence flow orders two activities. Delivery durability, repeated execution, acknowledgement, and recovery of a partially completed external side effect require additional explicit policy.

The semantic model must therefore be a real intermediate representation rather than a renaming of Kafka topics. A Charlotte backend should consume concepts such as activity, event, correlation, retry, and durable boundary.

18.3.3 The execution substrate

The lower layer realizes the semantic model. The established Durga backends use Java or Rust workers and Kafka communication. The prototype Charlotte target starts to use Charlotte execution objects, capabilities, names, and cluster desired state, while retaining an external event log where its semantics are required. Supervision and the complete process runtime remain target work.

The intended relationship is therefore:



Each lower-layer mapping must preserve the process contract. When the available substrate lacks a required semantic, the generator retains a suitable service such as Kafka or rejects the build. Moving bytes between activities is only one part of backend correctness.

18.4 The Charlotte backend and its target architecture

The working generator establishes the source, build, authority, connector, and deployment skeleton described at the start of this chapter. The target architecture fills that skeleton with completed business-rule bindings and a semantic process runtime, then adds bundle-level admission, resource-aware rolling placement, lifecycle supervision, and rollback. Charlotte's existing release path already supplies fixed replica sets and exact-generation DSR readiness below that semantic layer.

18.4.1 Generated activity boundary

For a simple activity, the developer-owned interface might be no broader than:

```
fn calculate_entitlement(
    claim: Claim
) -> Result<Decision, RuleError>
```

We have not settled the Rust interface or implemented this ABI. Around that function, the Charlotte backend could generate a wrapper that:

1. receives a typed activity invocation through a delegated endpoint;
2. validates the process, activity, instance, schema, and correlation identities carried by the invocation;
3. deserializes input into the developer-facing type;
4. emits an activity-entered observation;
5. invokes the business rule within its assigned protection domain;
6. converts success or failure into the Durga execution result;
7. serializes the result and sends it only through generated output capabilities;
8. emits completion, failure, and resource observations; and
9. participates in generated supervision, shutdown, and upgrade protocols.

The generated wrapper owns platform mechanics: receiving Charlotte messages, accepting capabilities, allocating shared memory, re-registering after replacement, responding to endpoint closure, and attaching telemetry. The developer-facing business contract remains suitable for unit tests on an ordinary development host.

The source layout enforces the same boundary. Regeneration replaces generated files and preserves developer-owned business modules. Specialized services may use explicit escape hatches; ordinary rules remain free of raw Charlotte handles.

18.4.2 A deliberately narrow runtime interface

The generated runtime would target a small Charlotte service interface rather than POSIX. A candidate operation set might include:


- receive from and send to delegated message endpoints;
- allocate, transfer, and release bounded memory objects;
- access a delegated clock, random source, or cryptographic service;
- invoke a named service through an explicit capability;
- emit structured observations;
- checkpoint explicitly owned state; and
- cooperate with supervision, replacement, and cancellation.

This list is proposed. The experiment should discover the minimum viable interface rather than declare it in advance. In particular, external protocols, TLS, databases, object storage, and durable logs will require trusted connectors or Charlotte-native services. Code generation cannot make those integrations disappear; it can make authority to use them explicit and can keep their mechanics outside the business rule.

18.5 From process graph to capability graph

Charlotte workloads begin with no ambient authority and receive only delegated capabilities. Durga has information from which a first capability request can be generated: which activity receives which input, which activity can send to which successor, which participant communicates with which other participant, and which declared data or external service an activity uses.

For a simple process fragment:



the backend could derive a graph in which:

- `ValidateClaim` may send validated claims to `CalculateEntitlement`;
- `CalculateEntitlement` may invoke `RulesService` and send decisions to `IssueDecision`;
- `IssueDecision` receives decisions but cannot invoke the rules service; and
- no activity receives a generic network, filesystem, or cluster administration capability.

The process communication graph can thus become an input to the Charlotte capability graph. BPMN message flows, pools, participants, and explicitly annotated external interactions are particularly useful because they already express architectural boundaries. A message between a claims pool and a payments pool may justify an explicit cross-domain endpoint rather than ambient reachability between their executables.

Absence of a BPMN edge is useful negative information. A complete authority decision also accounts for implicit gateway and orchestration paths, monitoring and administration channels, and external systems declared by business-rule code. Capability inference therefore combines several sources:

- the supported BPMN topology and its scopes;
- typed task contracts and data declarations;
- explicit annotations for external services and durable resources;
- generator-known runtime and observation requirements;
- optional static analysis of the developer-owned code; and
- organization policy that may narrow, approve, or reject the inferred request.

The generator produces a reviewable authority request. A separate build or admission policy decides which capability bindings are acceptable. This retains the distinction from Chapter 17 between an artifact's signed claims and the cluster authority that admits and delegates them.

18.5.1 Security graph and communication graph

The execution graph, communication graph, and security graph are related but not identical:

- The execution graph says which semantic transition may follow which other transition.

- The communication graph says which generated component must exchange which message or object with which other component.
- The security graph says which protection domain is authorized to perform that exchange at runtime.

One logical sequence flow need not create one network-visible endpoint, and two activities fused into the same executable may still be kept behind separate logical interfaces for observation or future decomposition. Conversely, a shared orchestrator may require communication not drawn as a direct business edge. Keeping the three graphs distinct prevents a convenient compilation choice from silently becoming the security policy.

18.6 The signed process bundle

The proposed backend would produce more than executable code. Its natural deployment unit is a signed process bundle that preserves the relationship between model, rules, generated wrappers, and cluster policy. A bundle could contain:

- the original BPMN model and a canonical digest of the model;
- the Durga semantic intermediate representation and its version;
- one or more Charlotte-native executable artifacts;
- immutable identities and signatures for every executable;
- input, output, event, and state schemas with stable identities;
- the execution, communication, and requested capability graphs;
- signer, build, generator, source, dependency, and toolchain provenance;
- an SBOM or the signed digest of retained SBOM and attestation evidence;
- resource estimates, concurrency declarations, replication policy, placement hints, and failure-domain constraints;
- durable-log and external-connector requirements;
- observation metadata mapping runtime identities back to BPMN activities; and
- the proposed cluster desired state for this process release.

Execution resources and replica intent deserve special treatment among those estimates. Only the application and generator authors know the component's worst-case call depth, generated adapter frames, stack-resident data, safe concurrency, and intended replication. Durga therefore creates a developer-owned `charlotte/resources.yaml`. It specifies the per-thread stack (`stackPagesPerThread`), active-thread quota (`maxThreads`) and shutdown grace (`shutdownGraceMillis`), together with replica count, every-eligible-node selection, spread, affinity, and anti-affinity. It creates that file once and never overwrites it during regeneration. Operations may approve or reject the reviewed values when signing the deployment, but should not have to guess them from the ELF or silently rewrite them. Charlotte's `CDEPLOY6` descriptor signs all three values and placement policy; Durga derives the corresponding signing options and adds the CLS2 parallel-instance requirement whenever the policy permits concurrent instances. The kernel gives every thread in the protected domain the specified 4 KiB-page stack allocation and counts the bootstrap thread against the active-thread quota. It first requests cooperative application draining and then forcibly retires the domain at the signed deadline. Both execution-resource ranges are one through 64; shutdown grace is zero through 300,000 milliseconds. A quota-exceeding spawn rejects before stack construction and returns `ThreadError::SpawnFailed` through the owned runtime, leaving the caller running. Only `CDEPLOY6` is accepted; resource limits, shutdown grace and placement are explicit signed fields. There are no older-format defaults.

Chapter 17 already implements signed, name-bound ELF artifacts with release, rollback, class, flags, and an optional provenance digest, and it pins the complete ELF digest in a deployment record. A process bundle would build on those mechanisms; it would not replace executable verification with trust in a container or archive. Each executable remains independently verifiable, while the signed bundle states that a specific set of artifact and schema identities collectively realizes one version of a process.

Bundle signing is proposed future work. It also introduces supply-chain questions. The generator and build toolchain become security-sensitive because they derive authority and create wrappers. Reproducible generation, separation between requested and granted capabilities, independent policy review, retained provenance, and verification of the bundle-to-artifact links are necessary. Signing generated output does not prove that the BPMN model or generator was correct.

18.6.1 Generated desired state

The bundle could carry a declarative target such as:

```
process: claims
release: 42

component validate:
    artifact: sha256:...
    stack-pages-per-thread: 4
    max-threads: 4
    shutdown-grace-millis: 15000
    replicas: 4
    parallel: true

component calculate:
    artifact: sha256:...
    stack-pages-per-thread: 8
    max-threads: 8
    shutdown-grace-millis: 30000
    replicas: 8
    parallel: true
    requires: service:entitlement-rules

placement:
    affinity: [validate, calculate]
    minimum-failure-domains: 2

durability:
    ClaimSubmitted: external-event-log
    validate-to-calculate: native-message
```

The example illustrates deployment intent generated from the same semantic model as the executable wrappers; a future format may use different syntax. Cluster admission can validate the requested replica counts, parallel-safety declaration, artifact identities, stack limits, capabilities, and placement constraints before committing desired state to the replicated manifest.

The Charlotte manifest accepts signed singleton, fixed-replica, and *every eligible node* policy. The `PlacementPolicy` contract described in Chapter 17 is stored in `CDEPLOY6`; a leader-side controller resolves it and commits concrete replica sets. A generated component set can be wrapped in `CRELEASE`, atomically admitted, and observed together with `cluster-sign release-apply`. This binds exact executable deployment descriptors and placement policy. The semantic bundle adds the BPMN digest, schemas, communication graph, and provenance. Consuming it also depends on resource-aware scheduling and the production administration authority identified there.

18.7 Process topology as placement information

A general-purpose cluster scheduler normally begins with deployable units, resource requests, and manually supplied affinity rules, then infers relationships from traffic and resource telemetry. Durga can additionally supply the application's semantic process graph before execution.

Durga knows useful structure before execution begins:

- which activities are adjacent and expected to exchange data;
- where the graph fans out, joins, waits, or selects one branch;
- which activities may execute concurrently;
- which events enter from or leave for external systems;
- which subprocesses and participants form natural boundaries; and
- which activities are expected to block on timers, people, or durable external events.

A Charlotte backend can translate this into an initial placement hypothesis. Frequently adjacent activities may receive a common affinity group; replicas of one parallel-safe activity may receive anti-affinity or minimum-failure-domain rules; an activity using a restricted service may be constrained to the same trust domain; a high-volume data edge may favor co-location.

The BPMN topology supplies a hypothesis rather than a measurement. A rarely selected branch may carry very large objects, an adjacent pair may spend almost all its time in an external service, and one process definition may serve different data distributions. Runtime evidence must refine incomplete or incorrect resource estimates and expected frequencies.

Charlotte's observation substrate can refine it. Runtime identities generated from the process model allow the cluster to measure message counts, bytes, latency, queue pressure, CPU time, memory pressure, failures, and retry rates per activity and edge. A future placement controller can compare declared structure with observed behavior, then move or replicate components when sustained evidence justifies the change. Availability and trust constraints remain hard constraints; observed affinity must not collapse replicas into one failure domain.

This gives the process compiler and cluster different roles:

```
Durga model       -> initial graph and declared constraints
Charlotte runtime -> measured graph and resource evidence
placement policy  -> admissible movement and replication
controller        -> assignments in replicated cluster state
```

Charlotte already resolves declared replica and affinity policy into automatic assignments. The proposed feedback loop adds cluster-wide observation and uses sustained runtime evidence to refine those assignments.

18.8 Logical activities and physical executables

BPMN describes logical units of work independently of protection domains, operating-system processes, containers, or scheduled artifacts. The current Rust generator maps activities and gateways to binaries. A Charlotte backend may instead choose physical granularity from authority, durability, placement, and performance constraints.

For a logical chain:

```
A -> B -> C
```

the backend might generate any of:

```
[A] -> [B] -> [C]
[A B] -> [C]
[A B C]
```

Fusion can remove serialization, endpoint, scheduling, and network overhead. It may also permit intermediate values to remain in one address space. Separation supports independent scaling, fault containment, least authority, different trust domains, independent upgrades, and placement near distinct resources.

Executable granularity should therefore be an explicit compiler and policy decision. Relevant constraints include:

- capability and participant boundaries;
- durable handoff points and replay requirements;
- independent scaling and parallel-safety declarations;
- failure and retry domains;
- state ownership and upgrade boundaries;
- expected message size and frequency;
- architecture or hardware requirements; and
- the cost of losing a fused group when one activity fails.

The logical activity identity must survive fusion. Observations, failures, schema versions, and business audit events should still be attributable to the corresponding BPMN activity. The signed bundle should state the mapping from logical activities to physical artifacts, so that the cluster can explain its placement and so that a later release can split or fuse components without renaming the business process.

Automatic re-fusion from runtime evidence is a later research topic. Because executable boundaries affect security, state, and upgrade semantics, the first implementation should require a new generated and signed release for every change.

18.9 Native messages and durable event logs

Kafka presently supplies more than byte transport to Durga. It offers durable logs, replay, partition ordering, consumer groups, offset tracking, integration with external producers and consumers, and transactional

options. A Charlotte message endpoint must not be treated as equivalent merely because it can carry the same payload.


CharlotteOS now has an implemented, capability-scoped Kafka compatibility service (Section 13.6.2). A provisioned instance exposes an explicit broker allow-list, a fixed consume partition, up to 64 allow-listed produce routes, a group, transactional identity, and separately named authority endpoints. Its owned Rust client supports idempotent produce, bounded read-committed consume, explicit delivery acknowledgement, and a transaction that atomically combines Kafka output with the consumed delivery's group-offset advance. This supplies a concrete external event-log boundary for a Durga backend.

The generated deployment should treat the broker connector and the behavioural role as separate authorities. Only `kafka` receives the immutable, digest-checked profile containing endpoint, trust, and authentication secrets. A producer, consumer, or transactional-step runner receives a connection capability to the corresponding profile-defined access point. The connector enforces that endpoint's Kafka-rights ceiling for every opcode, so a producer-only connection cannot be used to consume or transact. The activity procedure behind a step receives only the bounded invocation capability and no Kafka authority. Each connector profile fixes all bounded access-point names, so a deployment can provision several least-authority connections from one secret-bearing connector without replacing a global `kafka` publication. The runner resolves only the transactional access point declared by its step profile. The generic `kafka_step` runner now implements this split: it calls the procedure with borrowed input and an attempt number, validates its bounded output batch, and atomically produces admitted outputs with the consumed offset. It retries timeouts and explicit transient failures and writes terminal, malformed, or exhausted inputs to a configured DLQ. The remaining deployment work is direct capability injection, generated artifact construction, and controller-managed lifecycle/fencing rather than the transaction loop itself.

The useful distinction is between application events whose meaning is intrinsically durable and internal execution plumbing whose purpose is to advance a running process.

An externally meaningful event such as `ClaimSubmitted` may need a retained, replayable, independently consumable record. Kafka or another durable event-log service may remain the correct substrate. An internal instruction such as "activity A completed; make B runnable" may need only the delivery, deduplication, and recovery guarantees of the Durga runtime and could use native Charlotte messaging.

A proposed Charlotte deployment may therefore be hybrid:



This keeps Kafka where log semantics and ecosystem integration are required, while avoiding a broker round trip for every internal transition. It also makes the durable boundary visible in the process bundle and capability request.


The present Kafka adapter is intentionally narrower than a general client. It uses a profile-fixed partition and a Charlotte fixed-partition group assignor while routing among an explicit broker allow-list. It supports group join, heartbeat, standby failover, and generation-fenced ordinary and transactional offset commits, but not conventional/cooperative assignor interoperability, complete coordinator-migration recovery, client-certificate chains, or compression. It supports verified TLS, connector-only SCRAM-SHA-256 authentication, and connector-only P-256 mTLS, independently or together. A generated deployment would therefore need either to accept that bounded profile, extend the adapter under equally explicit authority, or retain a conventional connector outside Charlotte for requirements the native service cannot satisfy.

The distinction cannot be inferred reliably from sequence flow alone. The process author or policy must declare durability, ordering, replay, retention, and delivery requirements. The Charlotte runtime must define how it recovers an in-flight process when a node fails, when an acknowledgement is lost, or when a business rule completes twice. If native messaging does not yet satisfy those requirements, the backend must retain Kafka for that edge. Removing Kafka from internal paths is optional; the Charlotte backend can keep it where needed.

18.10 Preserving application intent

In a conventional deployment, semantic information is progressively lowered into infrastructure objects. A BPMN activity may eventually appear to the cluster as a container image, a Deployment, CPU and memory values, labels, and network endpoints. Those objects are operationally useful, but they retain little explanation of why two components communicate or what a latency measurement means to the business process.

Durga and Charlotte together could preserve an identity chain:



Every generated message and observation can carry or imply stable process, release, instance, activity, edge, and schema identities. The signed bundle binds those logical identities to executable digests. The cluster desired state binds artifact identities to admitted capability and placement policy. Runtime telemetry can then be mapped back to the BPMN diagram.

This allows questions at several levels to share one evidence chain:

- Which business activity accounts for the current queue pressure?
- Which capability edge carried the slow calls?
- Which artifact release implemented that activity?
- On which nodes and trust domains were its instances placed?
- Did the observed traffic support the generated affinity hint?
- Did an executable fusion decision improve latency while preserving the intended fault and security boundaries?

Durga already emits lifecycle events and uses the BPMN model as the background for process monitoring. Charlotte already exposes executor observations and generation-aware names. Joining those identities and feeding the result into cluster placement is proposed future work.

Telemetry must not become ambient surveillance authority. Generated observation channels should be explicit capabilities; payloads should avoid business data unless required and authorized; and retention and access belong to policy. Preserving intent is valuable only if the observation path preserves the same security discipline as execution.

18.11 Comparison with Kubernetes and OpenShift

The comparison asks which layer should own each orchestration responsibility and which deployment objects the generator should produce.

In the current conventional path, Durga may generate or depend on:

```
BPMN + rules
    -> Java/Rust application
    -> Kafka topics and configuration
    -> JAR or native executable
    -> container filesystem image
    -> image registry and image policy
    -> Kubernetes/OpenShift manifests
    -> Pods, Services, probes and NetworkPolicy
    -> container runtime
    -> Linux isolation and resource mechanisms
```

In the proposed Charlotte path:

```
BPMN + rules
    -> Durga semantic model
    -> signed process bundle
    -> Charlotte desired state
    -> Charlotte cluster
```

The shorter Charlotte path assigns each concern to the operating system, the signed bundle, or an explicit external service:

- An OCI filesystem image may become a signed, self-contained Charlotte execution artifact. Artifact storage, distribution, verification, and rollback remain necessary.

- A Kubernetes Deployment may become Charlotte replicated desired state plus replica and placement policy. Reconciliation, failure recovery, rollout, and admission remain necessary.
- A Service and service account may become a Charlotte name and explicitly delegated invocation capability. Naming, routing, identity, and key management remain necessary.
- NetworkPolicy may be replaced for generated internal communication by the admitted capability graph. Gateways to IP networks and external systems still require network security policy.
- Liveness and readiness endpoints may become native supervision and generated lifecycle state. The cluster must still distinguish work that is slow, blocked, failed, or safe to restart.
- Pod affinity may begin as a generated process communication graph and later be refined by Charlotte observation. Scheduling and failure-domain policy remain necessary.
- Charlotte may not need a container runtime or container-specific Linux policy. Namespaces, cgroups, and seccomp may also be absent because Charlotte starts with separate address spaces and delegated authority. Equivalent memory, CPU, and device accounting must nevertheless exist natively.
- Kafka topics used only for internal execution plumbing may become Charlotte message endpoints. Kafka remains where durable event-log and integration semantics are required.

OpenShift also supplies mature multi-tenancy, policy, secrets management, operators, ingress, storage integration, observability, upgrades, ecosystem compatibility, and operational practice. Charlotte must build corresponding operational maturity where its use cases require it. The research question is which mechanisms become smaller or more direct when the OS already has the desired trust and execution model.

Durga can generate Kubernetes manifests, container builds, and policy as well as Charlotte artifacts. Charlotte's proposed advantage is a direct target of native cluster and capability objects, avoiding the intermediate machine-like Linux userspace.

18.12 Developer experience and the compatibility boundary

If successful, the ordinary developer would work with:

- BPMN and domain-specific annotations;
- typed task inputs, outputs, errors, and business-rule interfaces;
- a host-side test harness for business behavior;
- generated local simulations or integration tests;
- process-level diagnostics mapped to the BPMN diagram; and
- a build command that selects a verified backend.

The generator and platform team would own:

- the Charlotte ABI and generated wrappers;
- serialization, schema evolution, correlation, and retry protocols;
- capability-request generation and policy integration;
- signing, provenance, and process-bundle construction;
- supervision, observation, deployment, and upgrade integration; and
- tested connectors to durable logs and external systems.

This division does not eliminate the need to learn Durga. It substitutes a domain and process programming model for an operating-system programming model. That is useful only if regeneration is predictable,

generated code is inspectable, errors name model elements, and debugging can cross the boundary between rule code and runtime without exposing every kernel detail.

Backend portability also requires restraint in the task API. A business rule that assumes a local path, arbitrary outbound socket, process environment, or Java-specific runtime facility is not automatically portable. The developer contract should make portable operations easy, platform-specific dependencies explicit, and unsupported dependencies visible at build time.

18.13 Current implementation and next experiment

The infrastructure experiment is complete enough to generate minimal Charlotte-native activities, build signed ELFs, admit a multi-component release atomically, resolve replica placement, pull artifacts through RustFS-backed S3, and observe exact-generation readiness. The next experiment adds one complete typed business-rule path and one transactional Kafka step, then binds their process semantics in a signed bundle.

18.13.1 Experiment input

Use a small BPMN process containing:

- a start event;
- one service activity with a typed request and response;
- one successor or completion event; and
- an explicit annotation for any clock, log, or external service the activity requires.

The handwritten Rust module should implement one pure or nearly pure business function. It must not call a Charlotte syscall or manually construct an IPC message.

18.13.2 Generated output

The next `charlotte` increment should add:

1. stable request and response schema identities with serialization code;
2. a typed business-handler contract used unchanged by host-side unit tests and the generated Charlotte wrapper;
3. process-instance, activity, correlation, and attempt identities in calls and observations;
4. a transactional-step binding that invokes the handler without exposing its Kafka connector capability;
5. retained provenance compatible with the existing CLS2 metadata; and
6. a signed semantic bundle binding the BPMN digest, activity and schema identities, generated artifacts, communication edges, capability plan, and executable deployment descriptors.

A compact fixture with one transactional activity and one successor is sufficient to test this boundary. Its components may use fixed or replicated placement over the available test cluster; guest count is incidental. Fusion, native durable process recovery, and general process-version migration remain later experiments.

18.13.3 Execution and verification

The experiment should verify the following end-to-end properties:

1. Regenerating the backend does not modify the developer-owned business rule.
2. The generated ELF is signed, name-bound, digest-pinned, loaded in a fresh Charlotte address space, and invocable through the distributed name service.
3. The activity receives only the generated capabilities. An attempted undeclared communication fails because no authority is present, regardless of any network deny rule.
4. Typed input reaches the rule. Its typed result reaches the generated successor or test driver.
5. Activity-entered, completed, and failed observations retain the BPMN process and activity identities.
6. The existing stateless assignment handoff can move the generated artifact between nodes without changing its logical activity identity.
7. The process-bundle metadata can be independently checked against the BPMN, schemas, generated source, executable digest, and retained provenance.

The experiment should also record the amount and kind of Charlotte-specific code that remains handwritten. Its success criterion is a developer-owned business rule with no Charlotte programming, surrounded by a generated and trusted runtime layer small enough to inspect and verify.

18.13.4 Questions the experiment should answer

The experiment is intended to expose design facts early:

- What is the minimum Charlotte ABI needed by a generated activity?
- Which capability requirements can be inferred, and which require an explicit annotation or policy decision?
- Which parts of Durga's current semantic contract accidentally depend on Kafka?
- Which schema and correlation identities must cross the wrapper boundary?
- How should a business failure differ from a wrapper, transport, or node failure?
- Can host-side tests and Charlotte execution use the same rule code without conditional platform logic?
- Which identities are required to map runtime telemetry back to the BPMN model and signed build?

Answers to these questions determine whether a larger backend is justified.

18.14 Remaining work

Substantial work remains in both projects:

- A substrate-neutral Durga semantic intermediate representation must distinguish process semantics from the present Kafka realization.
- A stable generated-task contract, schema evolution rules, and explicit delivery and failure semantics are required before backends can be compared meaningfully.
- The generated userspace ABI now covers launch, capability pickup, and lifecycle integration. Typed activity invocation, schema evolution, process observation, and durable recovery still need stable contracts.

- The Charlotte backend generates reviewable S3/Kafka profile requests without embedding credentials in developer-owned business code. Secret delivery, trust-anchor rotation, and profile replacement still need a production provisioning path.
- Generated capability plans and signed descriptor grants establish the request and admission shape. Inference rules, organizational review, policy evolution, and audit require a production model. The generator requests authority; a separate policy owner grants it.
- Process-bundle format, signatures, artifact and schema identity, provenance, and reproducible generation remain to be designed.
- The Charlotte cluster now has shared central-S3 artifact fetching and replica-set rollout observation and DSR routing. It still needs production administration authority, resource-aware placement, cluster-wide telemetry, and rolling update/rollback control (Chapter 17).
- Native Charlotte messaging needs defined delivery, back-pressure, cancellation, deduplication, and recovery semantics before it can replace Kafka on any process edge that depends on them.
- Durable state, process-instance recovery, timers, human tasks, external side effects, and rolling process-version migration remain application-runtime problems even on a cluster OS.
- Debugging, local simulation, test fixtures, incident analysis, and operational explanations must be usable without requiring application teams to understand Charlotte internals.

The integration makes these questions testable one layer at a time while keeping application semantics distinct from substrate mechanics.

18.15 Next experiment

The next falsifiable step is to take the generated prototype through a multi-activity release. The experiment should determine whether its developer can remain concerned with the business rule while generated code and the cluster account for deployment, authority, and the operating environment.

Part VI

Working with CharlotteOS

19 Programming Model

This chapter summarizes the kernel and userspace rules for the asynchronous, shard-per-core model. Short kernel listings explain the model and omit setup; Section 5.6.1 provides the compiled userspace starting point.

19.1 Invariants

The design relies on these rules:

19.1.1 Only the owning LP mutates its state

Per-LP data is accessed only from the LP that owns it. Cross-LP mutation goes through message dispatch (`ShardSender<M>`, IPI closure, or IPI RPC), never through a shared lock acquired from a foreign LP.

19.1.2 Messages are owned values

Everything that crosses a shard boundary is an owned value: a typed `M` in a `ShardSender<M>`, an IPI closure, or a memory object. No shared references, no `Arc<Mutex<...>>` as the normal programming model. `Send + 'static` boundaries enforce this at compile time.

19.1.3 References to shard-local state must not escape

`ShardLocal<T>::with(fn)` provides `&mut T` inside a closure. The closure must not store the reference, send it to another thread, or cross an `.await` point. The borrow is verified at runtime (owner-check plus re-entrancy flag).

19.1.4 Work stays on its assigned LP

A pinned thread stays on its assigned LP. Certified Ready-thread migration is a separate kernel policy with architecture-specific ownership restrictions (Chapter 8); pinned userspace shards remain ineligible. To submit work to another LP, use `try_run_on_lp` or `ShardSender::try_send`.

19.1.5 Observability returns owned snapshots

Never expose borrowed references into runtime internals. Diagnostic and introspection code captures state by value. Self-tests and the demo illustrate this pattern.

19.2 Kernel-side primitives

19.2.1 `PerLp<T>`

Lock-wrapped per-LP container. Use for data accessed from interrupt handlers, IPI handlers, or multiple LPs:

```
// Initialize after the LP count is available.
let counters = PerLp::new(|| 0u64);
{
    let mut counter = counters.get_mut();
    *counter += 1;
} // Release before any blocking operation.
```

The lock masks interrupts during the critical section on architectures that require it.

19.2.2 `ShardLocal<T>`

Lock-free per-LP container for single-LP, thread-only data:

```
// One value per LP, initialized after topology discovery.
let counters = ShardLocal::new(|| 0u64);
// Access from the owning LP's thread context only.
counters.with(|counter| {
    *counter += 1;
});
```

Panics on wrong-LP access or re-entrant access.

19.2.3 `ShardMailboxSet<M>`

A typed, bounded per-LP queue has cloneable `ShardSender<M>` producers and one `ShardReceiver<M>` consumer per LP. The kernel-side `ShardMailboxSet<M>` creates the per-LP queues:

```
let mailboxes = ShardMailboxSet::<Command>::new(256);
let sender = mailboxes.sender_to(target_lp);
let mut receiver = mailboxes.receiver_for_current_lp();
// Returns Err(data) if full.
sender.try_send(Command::Process { data })?;
```

The userspace word-mailbox syscall path is domain-local and has a separate sender/receiver capability-record budget: 512 records per domain, 8,192 per node and 6,144 for ordinary domains. The remaining node records form a shared reserve for kernel-designated platform domains. An over-limit open returns zero; closing handles restores capacity. Receiver lookup returns the existing per-LP capability without another charge or independent ownership. These record counts do not account for the separate 256-word-per-LP queue backing. That backing has its own captured-generation queue-set and requested-byte admission in the same mailbox family account; see `docs/reference/mailbox-capability-budgets.md`. Opens are serialized with domain retirement and checked against the exact generation, so a delayed open cannot publish into a reused ASID.

The unified capability namespace accounts for every object kind. Mailbox, completion, memory, IPC, device and system-observer publication all enforce shared limits: 4,096 records per namespace, 65,536 per

node, and 49,152 ordinary records. Staged identities and source slots held for rollback count toward these limits; staging does not grant public authority. Owning admission tokens capture the exact namespace, so cancellation cannot revoke a replacement's reused handle. Domain registration prepares the generation-bearing namespace, and teardown retires admission before releasing subsystem payloads.

Receive reserves reply authority before dequeuing a call or writing its vector result page. A shared-limit rejection preserves queued work, result bytes and active loans. An owning receive transaction removes speculative reply authority if result writing fails; successful writing and dequeue require no further admission. One-way messages need no reply slot and can drain a full namespace. Call-side IPC uses one owning transaction for metadata, fresh authority, memory attachments and loan tracking. Memory and pending/delegated IPC authority publish together before enqueue; no fallible IPC admission follows a memory ownership change. Connection-bearing replies reserve shared authority before loan revocation and compose their returned authority with memory publication. Individual loan revocation remains fallible; this publication contract does not provide atomic rollback of unmap or TLB-shootdown work.

The unbounded allocation bridge and policy bypass have been removed. Device grants serialize with domain teardown and reserve authority before DMA-domain creation. An owner destroys unpublished hardware on failure; unsuccessful hardware rollback quarantines reachable backing instead of freeing it. Observer startup owns an unstarted domain and a cancellable startup claim, reclaiming delegated authority if preparation fails. These record limits do not provide complete aggregate byte protection. All memory transfer modes use an owning prepared transaction. Copies hold private charged pages; moves and loans hold source escrow and backing-retention pins. Destinations remain hidden until the whole mixed-mode batch commits. Loan preparation creates no borrower state, and cancellation restores original source slots without fresh quota or receiver mapping cleanup. Late cancellation cannot alter reused ASIDs or successor handles. Scalar rollback and the vector alias-cleanup assertion have been removed. Reply tokens track every vector loan and revoke them on reply or cancellation; kernel buffer/DMA access enforces committed loan permissions. Demand-backed heap frames also have generation-owned admission: the embedded address-space account retains charges until physical teardown. The node heap pool is one quarter of usable RAM, with one quarter of that pool reserved for kernel-designated platform domains. First touch reserves before frame allocation, prepares ownership tracking fallibly, and refunds an unpublished frame on mapping failure. Repeated touches do not allocate replacement backing; retirement denies new commitment without refunding live pages. The virtual heap claim remains independent of physical commitment. ELF and runtime-page backing use an independent image account: 64 MiB per domain and a quarter-RAM node pool with shared platform headroom. Allocation and mapping errors unwind the unstarted preparation, returning frames and CQs. Layout validation uses fixed storage for at most 64 program headers, reserves the full adaptive heap window, and plans image plus runtime pages before namespace creation. These backing limits exclude translation-table frames. Stacks, private translation tables and fresh shared kernel tables have separate admission pools; those pools are not charged to the image account. General allocator bytes, aggregate principal usage and some namespace/account metadata remain incomplete. The implementation contract and migration scope are recorded in `docs/reference/capability-admission.md` and `docs/reference/heap-admission.md` and `docs/reference/loader-admission.md`.

19.2.4 IPI closures

`try_run_on_lp(target_lp, || { ... })`. Boxes arbitrary work and delivers it to the target LP's IPI queue. Returns the closure on full queue (backpressure). Use for kernel-level cross-LP work where typed mailboxes are not appropriate (e.g., TLB shootdown, scheduler commands).

19.2.5 Completion API

The API provides `submit`, `submit_worker`, `complete`, `poll`, `wait`, `cancel`, and `close`. The exit-observer path (`submit_worker`) is the intended default for fire-and-forget async kernel work:

```
let cap = submit_worker(|| {
    // Worker thread: do async work, then exit.
    // Completion fires automatically on exit.
});
let result = wait(cap)?; // Block until worker exits.
```

19.2.6 CQ ring

`CompletionQueueRing` for zero-syscall completion draining. Kernel side: `write(cap, result)`. Consumer side: `read() -> Option<CqEntry>`.

19.3 Userspace programming model

19.3.1 The launch contract

A CharlotteOS userspace program is a `no_std` ELF binary. It uses the `catten-rt` crate (the CRT, or C runtime) and the `entry!` macro:

```
#![no_std]
#![no_main]

use catten_rt::Context;

fn main(ctx: Context) -> ! {
    // The launch environment owns this bootstrap connection.
    let _controller = ctx.bootstrap_connection()
        .unwrap_or_else(|| catten_rt::domain_abort());
    // A deployed application also borrows ctx.profile_memory().
    // See the complete client in Section 5's discovery discussion.
    unsafe { catten_syscall::thread_exit() }
}

catten_rt::entry!(main);
```

Section 5.6.1 contains the complete application skeleton: signed-grant acquisition, an owned session connection, business progress outside that session, bounded reconnection and explicit accepted-call cancellation.

The program does not define `_start`, a panic handler, or an allocator. These are provided by `catten-rt`. The `entry!` macro wires them together, validates the launch ABI version, sets up the heap, and calls `main(ctx)`. A panic invokes the domain-abort syscall: every thread in the address space is retired, so no sibling can continue after shared Rust state or a userspace lock has been left inconsistent.

19.3.2 Resource ownership in Rust

The register-level syscall ABI deliberately exposes capability handles as integers. Application code should use the linear wrappers in `catten_rt::owned`:

- `OwnedMemory` closes its capability on drop and is neither `Copy` nor `Clone`.
- `MappedMemory<ReadOnly>` and `MappedMemory<Writable>` own both the mapping and capability; only the writable state can produce `&mut [u8]`.
- `DmaTransfer` is created only from unmapped `OwnedMemory` and returns CPU ownership after synchronous DMA unmapping.
- `ReadOperation<'a>` retains its `&'a mut [u8]` until completion, including the cancel-and-wait path in its destructor.
- `Completion` cancels, waits, and closes on drop; timeout does not consume the handle unless a terminal result was observed.
- `Endpoint`, `Connection`, and `PendingCall` close exactly once. A pending call retains any memory loan until reply observation or cancellation. A single-call deadline uses `PendingCall::wait_timeout`; a multi-source reactor uses `PendingCall::bind_cq` with endpoint interests on the same CQ. `cq_wait_checked` waits to the earliest remaining operation deadline with an owned kernel watchdog and no extra completion capability; idle waits need no timer. Admission rejection is distinct from timeout. Reply readiness does not observe its returned capabilities. Kernel lifecycle publication also wakes the default CQ after exact-root page access and local guard exit; the reactor rechecks all sources, including lifecycle, after waking.
- `CapabilityVector` owns moved entries and retains read/write loans across a vector call. Submission failure returns the builder intact, including every moved object.
- `MmioRegion`, `MappedMmio`, and `Interrupt` provide single-close device ownership. Register access remains unsafe because width, alignment, volatility, and ordering are device-specific.
- `ThreadHandle` stores both the recyclable TID and the spawn-time generation. Joining passes both values back to the kernel, so a replacement thread cannot satisfy a delayed join.

The raw `catten-syscall` interface remains available to runtimes and drivers. Coherent `dma_map` is explicitly unsafe because the driver must synchronize CPU references and device access itself. Mixing raw operations with an adopted ownership wrapper violates the wrapper's safety contract.

These wrappers have host-side failure injection for unmap, DMA/MMIO release, completion cancellation, IPC move rollback, vector descriptor rollback, and loan cancellation. The no-std `charlotte-lifecycle` crate supplies the pure generation classifiers used by both the kernel and runtime and exercises their bounded input spaces in host tests.

19.3.3 Bootstrap authority

The `Context` carries the domain's bootstrap capabilities:

- `name_service()`: a connection to the name service, for looking up other services.
- `default_cq()`: the CQ handle for submission and waiting.
- `device_grants()`: any `MmioRegion` or `Interrupt` capabilities granted to this domain.
- `heap_config()`: memory available for the allocator.

The `Context` is the only way a userspace program acquires capabilities at startup. There is no ambient

authority, no global filesystem, no `/dev` to explore.

19.3.4 Caller identity is kernel authority

Syscalls derive the caller's address space from trusted thread and trap context. Userspace cannot select another domain's address space or capability table. The signed loader also installs a stable artifact principal, exact address-space generation, and deployment roles in a kernel-only table. IPC enqueue snapshots that authentication data; every current receive operation returns it alongside the numeric sender ASID, so a delayed message cannot inherit the identity of a later occupant of the same slot. Runtime ABI 3 retains the twelve-register envelope for scalar, blocking and vector receives (syscalls 71–73); the old nine-register syscalls 22, 27 and 53 are retired. The canonical runtime methods are `Endpoint::receive` and `try_receive`. Error returns clear all eleven payload/identity registers; queued attachments remain owned until delivery. Checked CQ wait 88 uses an explicit timed flag; 12/42 are retired. The safe runtime returns typed readiness/deadline or admission/invalid-request errors. Ordinary service reactors abort on rejected waits rather than spin or advance protocol time; specialized recovery retains the original pending owners and deadlines. Timer-backed admission pauses likewise abort if timer submission or successful completion is rejected.

Security-sensitive discovery uses the name service's `OP_LOOKUP_AUTHORIZED` protocol. The request names a service and an explicit `SEND`/`CALL` rights set, but contains no caller identity. The co-located policy engine defaults to deny, evaluates the kernel-authenticated principal and exact generation, and delegates only an attenuated connection. `OP_SET_POLICY` and `OP_REGISTER_AUTHORIZED` separately require administrator and service-manager roles. Issuance, denial, and delegation failure enter a bounded administrator-readable audit stream. Public bootstrap naming is a separate namespace and cannot resolve or replace policy-published services. The former bearer-key opcodes 5/6, stored key fields and permissive key-memory decoder have been removed; unsupported requests retain their complete incoming owners through rejection. Security fixtures use the current CNSGEN01 metadata frame and explicitly reject earlier shapes. Policy/audit persistence and retroactive revocation of already-issued direct connections are not currently promised.

19.3.5 Backpressure is normal

Bounded queues and capability tables return `WouldBlock`. The correct response is to retry, yield, or propagate backpressure upstream. Do not assume an unbounded queue.

19.3.6 Sitas integration

When writing code that uses Sitas on CharlotteOS:

- A Sitas shard is an LP-affine CharlotteOS user thread.
- `CharlotteReactor::new(lp_id)` binds a reactor to the calling shard's LP.
- Async operations return kernel-owned completion handles. A completion handle is opaque: wait on it, poll it, close it, or pass it through a typed channel.
- Cross-shard work is an owned message. Prefer Sitas channels and futures over shared mutable state.
- The executor parks on `checked CQ wait` (via `ShardParker`), not on a busy-loop.

19.4 Rule-of-thumb guidance

- **Choose the right container:** `PerLp<T>` for interrupt-accessed or cross-LP data; `ShardLocal<T>` for single-LP, thread-only data.
- **Choose the right channel:** `ShardMailboxSet<M>` for typed cross-LP communication within the kernel. `ShardSender/Receiver` for typed cross-shard communication within userspace. Endpoint IPC for cross-domain communication.
- **Use `submit_worker` for fire-and-forget async work.** When the worker returns, the exit-observer completes the capability.
- **Register a CQ ring at address-space creation** so completions are visible to userspace without per-entry syscalls.
- **Accept backpressure.** `WouldBlock` or `Err(m)` means the receiver cannot accept the work yet. Retry according to the operation's policy or propagate the rejection upstream.
- **Buffers have one owner.** While an async operation owns a buffer, userspace must not mutate or free it. Cancellation still ends in a terminal completion.
- **Never accept ASID or page-table roots from userspace.** Caller identity comes from the trap frame. This is the security invariant.
- **Do not smuggle shared kernel state into userspace.** Shared pages (CQ ring, config page) are data queues with narrow layouts, not references to kernel objects.

19.5 The syscall ABI

Application code uses typed owners over the syscall boundary:

`Completion::submit` and `Completion::timer` Return an owning completion or a submission error. Buffer-backed reads use `ReadOperation`, which retains the buffer borrow.

`Completion::poll` and `wait_timeout` Observe the exact operation. A timeout or rejected wait admission retains the owner; neither is a terminal result.

`catten_rt::cq::wait` Waits on one CQ with an optional millisecond budget. It returns readiness or deadline, or an explicit wait error; it returns no vector of entries. Drain the mapped ring separately and observe resources through their owners.

Owned cancellation and release `ReadOperation` and `Completion` retain their cleanup policy; cancellation cannot release an uncertain buffer merely because a timer expired.

For IPC, `Endpoint::create(interface, version, capacity)` returns an owned server endpoint. Its minting methods return owned connections with selected `IpcRights`. Calling a connection returns a `PendingCall`, not the server's reply token. Receive creates an `IncomingMessage` containing the server-side one-shot `ReplyToken`. Its consuming reply methods finish that authority. Memory moves consume their owners; loans borrow them through the pending call's terminal cleanup. The complete example in Section 5.6.1 uses these APIs.

The raw register ABI lives in the syscall SDK and kernel dispatcher. The receive contract and checked CQ wait contract describe their current records and outcomes; the ABI evolution note preserves the broader design history.

19.6 Enforcement and audit

1. **Invariants have enforcement points.** `ShardLocal<T>` rejects wrong-LP and re-entrant access; `ShardSender<M>` moves values across the typed boundary. Unsafe code and incorrect primitive use remain review obligations.
2. **The launch contract is minimal.** A userspace program receives exactly what it needs and nothing more. There is no global state, no inherited file descriptors, no ambient filesystem. The bootstrap capabilities are the program's entire universe of authority.
3. **Use messages by default.** Send an owned value through a bounded channel. Reserve shared memory and locks for cases that need them. This reduces the number of places where concurrency bugs can hide.
4. **The ABI is auditable.** Userspace wrappers and the kernel dispatcher share the typed `SyscallNumber` enum, and dispatch is exhaustive. The source enum, rather than a duplicated count here, defines the current interface.
5. **The programming model is testable.** Self-tests exercise owner checks, re-entrancy guards, selected backpressure paths, and cancellation behavior. Coverage is substantial but not exhaustive.

20 Configuration

Configuration expresses the workload and capacity a node is intended to support. A security limit needs an owner, a unit and an admission rule, but its chosen capacity also needs an explanation and a way to change it. Resource ceilings are therefore collected in a typed kernel policy, separate from the allocation and cleanup code that enforces them.

This chapter describes current configuration mechanisms and how to qualify a change. The matching operator guide is `docs/guides/configuration.md`; the complete resource-policy inventory and dimensions are in `docs/reference/resource-policy.md`.

20.1 Configuration sources and authority

The following inputs have different authorities and lifetimes:

Management TLS. A complete signed, encrypted boot resource supplies server credentials, client roots, exact operator roles and all eleven TLS limits. The kernel verifies it against its selected admission policy before publishing trust, then supplies read-only launch profiles to both management services. Missing credentials disable network admission. Protected installation and authenticated time remain audit gaps.

Dependency advisory policy. CI/local validation reads `.cargo/audit.toml` and the scanner pin in `.cargo/audit-version`. These configure validation, not a running node. Database contents refresh at each invocation; a later advisory can reject the same lockfile.

Domain TLS entropy. Startup consumes one `EntropyConfig` containing an owned entropy connection (or explicit architectural-only source) and positive request budget. It cannot adopt a borrowed launch capability or replace installed source/limits. This is runtime authority and observation policy, not a kernel capacity-profile field.

Kernel resource policy. Trusted Rust build input selects capacity ceilings, ordinary shares and platform reserves. It is compiled into the kernel and remains fixed throughout that boot.

Diagnostic telemetry archive. Kernel build input `CATTEN_TELEMETRY_ARCHIVE_INTERVAL_MS` defaults to zero, disabling disk archiving. Values from 1000 through 86400000 enable the diagnostic archive with that partial-chunk flush interval in milliseconds; full chunks may flush sooner. The kernel supplies a read-only launch manifest. Live one-second sampling, bounded memory history and fresh placement reporting remain active. Changing the setting requires rebuild/restart; cached kernels must match it. Existing archive objects are preserved for offline inspection. This setting does not disable Raft/catalog durability or release committed resource promises.

Native telemetry export. Unset `CATTEN_OTLP_ENDPOINT` launches no exporter. An explicit HTTP/IPv4 collector, interval and timeout form one complete read-only profile whose hash is checked on kernel reuse. The separate userspace service exports latest-sample OTLP protobuf gauges with bounded memory and deadlines, independently of local archiving, sampling and placement. Initial transport excludes HTTPS, authentication headers and gRPC; unsupported schemes reject. See `docs/reference/otlp-export.md`.

Bootstrap assignments. The kernel build consumes `CATTEN_CLUSTER_SERVICES`. Boot runners accept repeatable `--cluster-service [NAME=]IPv4:PORT` assignments. The first committed signed ingress policy replaces the bootstrap assignments.

Trust policy. The kernel's one prepared boot-trust policy supplies launch and grant verification. Capacity configuration cannot install keys, grant platform classification or enable production trust. Production

remains disabled pending protected provisioning and custody.

Application launch policy. Signed deployment and kernel admission determine per-domain stack/thread limits, executable variants, delegated capabilities and protocol-specific launch profiles. An application's request does not enlarge a node-wide capacity pool.

Persistent state. A storage format tag and committed state are not disposable configuration. Changing capacity never authorizes silent reformatting, resetting election state or discarding retained charges.

Internal protocol fields, architectural address ranges, page granularity and hardware register widths are separate structural contracts. Changing their numbers requires a coordinated implementation and format review. They are not ordinary operator capacity settings.

20.2 Selecting the compile-time resource policy

20.2.1 Select a reviewed profile

The default settings are in `crates/catten/src/resource_policy/defaults.rs`. They select reviewed capacity values. Operators may edit this central file or select an external profile with `CATTEN_RESOURCE_POL` which must name an existing file by absolute path. Unset selects the default; empty, relative, missing and directory paths reject. The file is trusted Rust source and belongs in the reviewed build inputs, not in an application manifest or upload request.

A profile defines `POLICY: Policy` in the policy module's scope. It can start from `DEFAULT` and override related fields. The checked-in `crates/catten/src/resource_policy/larger.rs` demonstrates co-scaling scratch-node, snapshot-buffer and mapping-node byte/count capacities by one quarter while retaining their reserve proportions.

```
CATTEN_RESOURCE_POLICY="$PWD/ops/resource-policy.rs" \
  scripts/run-aarch64.sh --security-test --http-test
```

The runners pass this environment input through to the kernel build. Cargo tracks the selected path, its contents and environment selection. Changing or unsetting the selection rebuilds the kernel; userspace service images do not need rebuilding for these policy fields. Boot serial output identifies the selected policy name. Record the exact profile source and kernel artifact hashes with qualification evidence; the name alone is not an artifact identity.

There is currently no resource-policy boot-module parser, capability, syscall or live-resizing interface. The compiled policy does not change after charges exist. Boot-time resource input is a future installation mechanism, not an implemented fallback for an invalid build profile.

20.2.2 Interpret the metadata pools

Metadata pool limits bound retained requested storage in their own units. They do not add up to physical RAM usage, and changing capacity does not alter sponsorship or completion rules. Plan headroom for old and replacement storage to overlap during growth.

Optional detail: Pool inventory and observer statistics

The 23 admitted metadata pools share family-typed charge mechanics and an independent static counter lock per pool. Resource owners retain sponsorship, completion and disposal policy. Version-10 thread statistics append a read-only inventory for validated system observers; ordinary snapshots contain no pool records. HTTP status JSON exposes each pool's units, ordinary/total limits and usage in `threads.metadata_pools`. Busy samples have absent usage. Samples are independent, byte values describe requested layouts, and overlapping or count-only pools cannot be summed into physical RAM consumption. This consolidation changes no existing numerical limits or cleanup authority. The independent IPC node pool has its own requested-byte/count limits. See `docs/reference/metadata-admission.md` for the wire contract.

Optional detail: IOMMU nodes and table ledgers

DMA mapping/quarantine records and SMMU walker-cache nodes share the existing `iommu_nodes` byte/count limits with domain/requester/context metadata. They retain the original domain-grant class through actual deallocation; promoting the root cannot reclassify later metadata in that domain. No numerical limit or statistics grammar changes. The shared ceiling bounds retained storage but also makes these layouts compete for its capacity. Raise the reviewed central limits if workload planning requires more headroom. Table-ledger buffers share the byte dimension with zero node count and retain full old/replacement capacity through actual free. Domain-grant or trusted boot class is captured before allocation; uncertain physical cleanup retains both page and metadata budgets. Default maximum ledger capacity is 16 KiB per domain and 32 KiB per unit, with 24/48 KiB during the final doubling. General principal/heap admission remains separate work. See `docs/reference/iommu-node-admission.md`.

20.2.3 Rebuild service capacities with their consumers

TLS record and certificate capacities are grouped build constants in the shared TLS adapter. Each stream owns two `16640`-byte record buffers; the verifier admits a complete Certificate message up to `16384` bytes. These values are compile-time adjustable, with record-framing requirements, handshake stack usage and heap grants reviewed together. Increasing storage does not add intermediate-chain validation. Driver context layouts and backend erasure flags remain structural build contracts. Changing these inputs requires rebuilding and qualifying both service variants; the kernel resource profile does not resize them. See `docs/reference/tls-client.md`.

20.2.4 Tune entropy deadlines and buffers together

The entropy request deadline is a separate startup API setting in `EntropyLimits`. Bundled S3, Kafka and TCP/IP select its central `5000` ms default; startup Rust code can supply another positive budget. No manifest/config-page field or live update is added. Increasing the budget retains source checkout, pending metadata, output borrow and possible returned backing longer, so timeout/rejection and pressure need joint qualification. One original monotonic deadline survives preparation and observation without replay. This bounds reply observation, not dependency naming or kernel cleanup latency. Details and exact inputs are in the TLS configuration reference.

The shared entropy protocol groups `BUFFER_PAGES`, `BUFFER_BYTES` and `MAX_REQUEST`, currently one 4096-byte page. These compile-time dimensions control caller allocations and the driver's private

DMA buffer together; descriptor lengths must fit `u32`. Rebuild every caller and driver, then qualify maximum sizes, rejection, retention, cancellation and DMA before changing them. This adds no boot-resource parser or live resizing. DNS's separate `CAPACITY_NONCE_TIMEOUT_MS` groups its 100 ms lookup/fill observation budget in the capacity-report context. See the entropy configuration reference.

20.2.5 Keep publication and device-polling budgets distinct

RNG publication uses the shared platform-service compile-time policy: 1000 ms admission, 5000 ms accepted-call observation and 10 ms queue-full-only admission backoff. These are separate phase budgets. Tune all helper consumers and boot readiness deadlines together in the shared publication module; RNG adds no per-instance or live override. Its idle request/lifecycle wait is event-only, without a timer policy.

The hardware-polling policy is separate. The central RNG device limits allow 1000000 completion-index reads per descriptor; the typed constructor requires a positive bound. This is an iteration ceiling, not milliseconds or permission to retry. Each confirmed short completion may require another bounded step. The compile-time queue size is eight; page-rounded ring backing derives from its geometry, while bounce storage follows the protocol buffer. Larger queues do not increase outstanding descriptors. Rebuild and qualify layout, CPU cost, caller deadlines, short completion, timeout/late completion and retained cleanup together. No boot-resource or live override is added. Exact inputs are in the entropy configuration reference.

20.3 Related limits and tuning consequences

The policy groups domain/ordinary/total capacities and resource dimensions. For fixed pools, every ordinary dimension is positive and below the total; domain dimensions must fit the ordinary pool. A reserve is the difference between total and ordinary admission, not a guaranteed share for one service.

Selected kernel buffers share a signed-principal requested-byte ceiling, `Policy.memory.principal_kernel_buffer_bytes`, defaulting to 16 MiB. It covers diagnostic buffers, primitive syscall inputs/plaintext, CPU/copy/DMA frame snapshots, IPC working/retirement buffers and root heap/image frame catalogs. Diagnostics also retain their shared snapshot pool and 1 MiB local working bound; root catalogs consume the existing memory-metadata byte pool. It reserves no backing in advance and is not a general kernel-metadata limit. See `docs/reference/telemetry-snapshots.md`.

Namespace account payloads and their private Arc holders share a separate `Policy.memory.principal_namespace_account_bytes` ceiling of 1 MiB per signed principal, retained across generations and final weak release. It funds actual requested layouts without allocating RAM in advance. The 24576/32768 ordinary/total bundle ceilings remain independent. Allocator excess and other metadata still require joint sizing. See `docs/reference/namespace-account-admission.md`.

Examples of settings that require joint review include:

- Memory-object size, aggregate domain/principal backing and snapshot bytes. One maximum-sized object catalog must fit both ordinary metadata and frame-snapshot byte limits. Increasing object size can also increase mapping work and pin lifetime.
- Mapping nodes, scratch extents and snapshots. Concurrent preparations, live objects and uncertain cleanup all consume admission. Raising the live-object target without space for preparation can prevent progress.

- Endpoint counts, queue slots, completion queues, connections, pending/reply records, capabilities, waiter entries and observer lists. One outstanding RPC can consume several of these families together. Endpoint backing rounds queue capacity to a power of two.
- Lifecycle watches, publication counts and replacement overlap. A name-service replacement needs the new watch before disposing the old one; service minima must be tested as part of boot qualification.
- Unified memory authority and shared payload/namespace/read-borrower node bytes/counts. Every overlapping preparation needs two temporary nodes, or three for a read loan, including the namespace candidate for an already-established namespace. Published and retained metadata consumes its original quota until deallocation.
- Thread bundles, principal thread metadata, stacks and private tables. More runnable domains can encounter any of these ceilings before their individual thread limits, including while old generations remain retained.
- Requested metadata bytes, allocator overhead, kernel-heap backing and physical progress reserves. Independent logical pool totals do not form a complete physical-RAM ledger and cannot establish fairness by addition.

RAM-derived pools use documented ratios of discovered usable pages, with checked widened arithmetic. The heap reserve has a RAM divisor, aligned floor and aligned ceiling. It clamps before alignment rounding, including extreme reported RAM. The current launch ABI still bounds heap virtual capacity; the kernel checks policy against that contract and the actual allocator arena.

Capacity changes do not alter sponsorship or cleanup. A move keeps its original charge, and root retirement, ASID reuse or later platform promotion cannot refund live backing. Failed physical cleanup retains the original complete owner and charge. A larger budget never supplies proof of completion or permission to replay accepted work.

Raft election timing is selected by `RaftNodeConfig::timeout_millis`; native launch supplies 2000 milliseconds through the DNS `elect-ms` manifest entry. Initial and subsequent deadlines derive a jitter window of one configured timeout, rather than a fixed 150 milliseconds. Repeated-election backoff derives from the same timeout, and deadline/backoff arithmetic saturates instead of wrapping. Changing the native launch value requires rebuilding and restarting the nodes. Review election timing together with heartbeat frequency, persistence/transport latency, quorum read freshness and management request budgets; a larger timeout does not extend an accepted request's original deadline. See `docs/reference/raft-conformance.md`.

The frame router's shared refresh interval is 1000 milliseconds, selected by `SNAPSHOT_REFRESH_MS` in `crates/catten-services/src/lib.rs`. Route refresh, ingress projection queries and source freshness share that interval; the local VIP admission lease is five intervals. Backend eligibility uses replication contact no older than the source-freshness interval, with an acknowledged current-term log entry. Only a committed availability projection changes the new-flow backend set. These settings require a service rebuild/restart. Review election timing, replication latency, projection convergence and flow-history retention together; a readiness signal or availability change cannot authorize request replay.

20.4 Management TLS configuration

The server collects policy in `crates/charlotte-launch/src/management/limits.rs`. Defaults allow 8 client CA roots, 64 enrolled leaf/role entries, 4 certificates per chain and 8192 bytes per certificate or server key. Each session permits 65536 input bytes, 65536 output bytes and 16384 application

bytes. The send-fragment setting is 4096 bytes; the original handshake and session budgets are respectively 5000 and 60000 milliseconds. One engine step performs at most 32 local TLS transitions. These are fields of the complete boot profile, not scattered constants or live overrides. Construction validates and captures them; existing sessions cannot resize in place.

Generate a complete editable limits file with `cluster-sign management-limits-default`. The profile-creation command requires every named limit, server key/chain, client roots and explicit reader or administrator enrollments. Unknown, duplicate, missing and inconsistent settings reject. Seal the private profile with the selected policy's operations signing key and recipient public key; set `CATTEN_MANAGEMENT_TLS_RESOURCE` to its absolute file path when building the kernel. Only ciphertext is embedded. The resource is verified and decrypted at boot using the same prepared kernel trust owner; no service can select an independent authority. The current delivery mechanism requires a kernel rebuild and restart to replace the resource.

The exact formats are `CMGMTL01` inside `CMGTENC1`. Their central profile ceiling is 65536 bytes. Both native management services reserve 32 stack pages (131072 bytes), committed on demand. The management module's `USER_STACK_PAGES` selects this build-time reservation. Review both dimensions with credentials, buffers, concurrency and service admission.

Smaller fragments increase wire overhead: Rustls subtracts its five-byte header allowance, and each AES-GCM application fragment adds 22 wire bytes. Validation checks that maximum application output still fits the selected storage. Certificates, root hints and all concurrent session buffers must also fit the service heap/stack and original operation budgets. External buffers do not bound every Rustls allocation; its current internal handshake-message ceiling is 65535 bytes. Protocol dimensions and cipher safety ceilings are separate from workload policy. Exact fields, structural bounds and integration gates are in `docs/reference/management-tls.md`.

Status uses TLS on port 443; deployment ingress uses TLS on port 7444. Both require an enrolled client certificate. Readers can observe; mutations require an administrator before controller dispatch and still require their signed bodies. Verified host tools require explicit CA, certificate and private-key files, with an optional server-name override for certificate matching. There is no plaintext listener fallback.

Rotation or revocation replaces the complete resource, advances the installed policy revision and restarts both services; existing sessions are not hot reconfigured. Public development authorities do not establish protected custody or rollback resistance. Each client obtains a fresh positive time-service reading before its handshake, under the original deadline; this does not authenticate the underlying SNTP source. Full execution qualifications and remaining gates are recorded in `docs/reference/management-tls.md`.

Established sessions recheck nonzero UTC, the original monotonic budgets and the enrolled client chain before admitting further work. Chain verification is cached within one observed UTC second. Expiry, unavailable time or observed rollback terminates that connection's authority; restoring time does not revive it. Idle connections continue to wait on resource readiness rather than periodic expiry polling. This does not authenticate time or prove cancellation of an already accepted mutation: retain its pending owner and never replay an uncertain request. Decision logs include the checked UTC second as diagnostic evidence.

The x86 QEMU `boot_trust_test` fixture can compile a different exact installed signed-policy snapshot using the absolute file input `CATTEN_BOOT_TEST_INSTALLED_POLICY`. Its default is the public revision 7 fixture. The host commits the selected public snapshot before building the authenticated kernel; the separate boot module must match it exactly. This input rejects outside that development fixture. It supports restart and credential-rotation testing, but provides neither protected state nor platform rollback resistance: an older still-authorized kernel can carry its older snapshot. Production remains disabled.

20.5 Planning and validating a policy change

Use the following process before selecting a profile for a new workload:

1. State the workload: RAM, domains/principals, threads, service topology, maximum object sizes, outstanding RPCs and expected overlap during restart.
2. Inventory each consumed family, unit, sponsor, lifetime and rejection result. Include unused candidates, detached work, weak references and retained uncertain cleanup. Separate structural bounds from capacity policy.
3. Measure peak occupancy and rejection under the intended concurrency. Choose ordinary capacity and trusted headroom together, explaining dependencies and expected failure behavior. A previously passing default is not a capacity estimate for a larger workload.
4. Run the policy harness and strict kernel builds. The harness compiles the actual policy, exercises admission counters and rejects inconsistent profiles. Compile-time validation checks relationships and arithmetic; it does not establish boot viability or essential-service progress.
5. Boot the exact selected profile on the supported backends. Exercise success, exhaustion, allocation rejection, cancellation, restart/generation reuse, retained charges and confirmed cleanup. Measure management, timer/scheduler and teardown progress against deadlines fixed beforehand.
6. Preserve the profile, artifact hashes, occupancy/latency results and failure diagnostics. Keep failed or interrupted attempts separate from successful repeats. Requalify after changing the workload or profile.

```
CATTEN_RESOURCE_POLICY="$PWD/ops/resource-policy.rs" \
  python3 scripts/tests/test-resource-policy.py
cargo fmt --all -- --check
```

The policy harness checks both the default and larger example, plus an optional operator-selected file. Native evidence for those profiles is listed in the resource-policy reference. These are focused capacity and ownership controls; sustained concurrent pressure and essential-service fairness remain acceptance work under SEC-07/18.

20.6 Extending configuration toward boot resources

Boot-time installation should reuse this typed policy and its validation, but must also define a complete authenticated input, reject unknown or incomplete settings, and establish authority before the first relevant allocation. Kernel-heap sizing and statically initialized counters currently precede a general resource-policy installation point. A future implementation must order those initializations, validate discovered-memory and structural constraints, then publish one immutable policy before schedulers and services consume it.

Do not implement this by resizing live pools independently. Any future update mechanism would need a separate account-generation and original-charge contract. Until that work is implemented and tested, changing capacity means building a new kernel with a reviewed profile and booting it.

21 Development Workflow

This chapter gives the current build, boot, test, and code-reading workflow.

21.1 Prerequisites

- **Rust nightly**, installed via `rustup`. The exact toolchain is pinned in the repository's `rust-toolchain.toml`; do not copy a version from this manual.
- **QEMU** for AArch64 (`qemu-system-aarch64`) or x86-64 (`qemu-system-x86_64`). On macOS, TCG is the default and HVF is opt-in. Networking and network-backed services are enabled by default under TCG; the virtio-net smoke-test switch adds verification. HVF is unsuitable for the driver's direct EL0 device-MMIO path and therefore requires `-no-network`. KVM is an optional Linux accelerator; networking also works under TCG. **HVF also does not honor hardware ASIDs**. See the *AArch64 Port Status* write-up. HVF builds rely on the `hvf_compat` whole-TLB-flush-on-switch fallback. Do not assume ASID-based TLB isolation works when debugging under `-hvf`. HVF also exposes no SMMU for protected NVMe DMA, so its compatibility boot runs the 15-test non-storage suite. Use TCG for the full 18-test suite, object-store tests, persistent Raft, and live upgrade.
- **Build dependencies:** `cargo`, `just` (optional, for convenience targets in the `Justfile`), and `mtools` for constructing x86-64 FAT boot images. VMware appliance packaging also requires `qemu-img`, normally installed with QEMU.

21.2 Build targets

CharlotteOS has custom target JSON specs for three architectures in `target_specs`:

Target spec	Status
AArch64 custom target	Primary development target; reference TCG boot, services and opt-in integration fixtures have recorded validation. Feature combinations and physical platforms need their own qualification
x86-64 custom target	Four-LP ring-3 service, storage, IOMMU, discovery, distributed DNS, smoltcp TCP/IP, HTTP, deployment, migration, UTC time, and dynamic-membership paths pass under QEMU TCG; UEFI, VT-d, NVMe, and node-local services also pass under VMware Fusion
RISC-V custom target	Planned, not actively maintained

21.2.1 Kernel build

The commands below use the AArch64 target specification and the x86-64 target specification.

```
BUNDLES="$PWD/target/embedded-services"
# AArch64 (headless, serial console only):
scripts/build-catten-services.sh --embed
scripts/build-catten-user.sh --embed
export CATTEN_AARCH64_SERVICE_BUNDLE="$BUNDLES/aarch64-unknown-none"
cargo build --package catten \
  --target target_specs/aarch64-unknown-none-catten.json \
  --no-default-features --features acpi

# x86-64:
scripts/build-catten-services-x86_64.sh
export CATTEN_X86_64_SERVICE_BUNDLE="$BUNDLES/x86_64-unknown-none"
cargo build --package catten \
  --target target_specs/x86_64-unknown-none-catten.json \
  --no-default-features --features acpi
```

The `display` feature requires a C library for the flanterm framebuffer terminal. Headless boot uses serial output only (AArch64: PL011 UART; x86-64: 16550 COM1).

21.2.2 Userspace service programs

Service binaries use custom `no_std`/`no_main` targets and build-std. The helpers build, sign and stage the bundles consumed by the kernel:

```
# AArch64 EL0 service programs:
scripts/build-catten-services.sh --embed

# x86-64 ring-3 service programs:
scripts/build-catten-services-x86_64.sh

# Sitas user binary (requires external sitas crates):
scripts/build-catten-user.sh --embed
```

Run from the repository root with the pinned toolchain. The Sitas helper needs the sibling checkout described in `docs/guides/userspace-development.md`. The boot runners prepare these inputs automatically; a bare kernel Cargo build needs the corresponding bundle environment variable shown above.

21.3 Booting in QEMU

21.3.1 AArch64

The boot entry points are `scripts/boot-smp1.sh`, `scripts/boot-smp2.sh`, and `scripts/run-aarch64.sh`.

Both architecture runners attach a NIC by default. Charlotte acquires a DHCP lease and launches discovery, cluster, TCP/IP, HTTP, and time services without a test option. The `*-test` switches only register additional verifiers; `-no-network` is the explicit opt-out for an isolated boot.

```
# Single-LP self-test boot:
./scripts/boot-smp1.sh

# Two-LP self-test boot:
./scripts/boot-smp2.sh

# Or choose the profile, LP count, and timeout directly:
./scripts/run-aarch64.sh debug --smp 4 --timeout 180

# Supply bootstrap cluster identities for exact deployment generations;
# repeat the option for independently placed services. A committed CINGPOL1
# operations policy supersedes this table at runtime:
./scripts/run-aarch64.sh release \
  --cluster-service orders=10.0.2.42:8080 \
  --cluster-service payments=10.0.2.43:8080

# An unnamed platform service, eligible on every admitted non-draining node:
./scripts/run-aarch64.sh release --cluster-service 10.0.2.44:80

# Apple Silicon: accelerated 15-test non-storage compatibility suite:
./scripts/run-aarch64.sh debug --hvf --no-network --smp 4 --timeout 180
```

21.3.2 x86-64

The x86-64 runner is scripts/run-x86_64.sh; scripts/boot-x86.sh is its single-instance convenience wrapper. Both use mtools to construct the disposable FAT boot image, which avoids platform-specific mounted-image discovery on macOS.

```
# Requires -cpu max for RDTSCP/FSGSBASE support:
./scripts/boot-x86.sh

# Select storage/IOMMU and run the four-LP bounded suite directly:
./scripts/run-x86_64.sh debug --smp 4 --block nvme --iommu intel \
  --fresh-storage --timeout 90

# Serve and host-probe the HTTP state report through smoltcp:
./scripts/run-x86_64.sh release --http-test --timeout 90

# In two terminals, run the complete four-LP cluster suite on both guests:
./scripts/run-x86_64.sh release --deploy-test --smp 4 \
  --instance node-a --mac 52:54:00:12:34:01 \
  --net-listen 12002 --timeout 360
./scripts/run-x86_64.sh release --deploy-test --smp 4 \
  --instance node-b --mac 52:54:00:12:34:02 \
  --net-connect 127.0.0.1:12002 --timeout 360
```

Use `-tcpip-test` instead of `-deploy-test` for the smaller focused two-guest smoltcp exchange. `-live-upgrade-test` runs the isolated persistent service-manager handoff. The complete deployment suite is qualified with four LPs; two LPs are not a supported test configuration for that load.

21.4 Booting in VMware

The appliance builder uses the same x86-64 build path without launching QEMU, then converts the FAT boot image and a blank data image to VMware VMDKs:

```
./scripts/build-vmware-x86_64.sh release
```

Open `os-images/vmware/CharlotteOS.vmwarevm/CharlotteOS.vmx` in VMware Fusion or Workstation. The SATA boot disk is nonpersistent; the NVMe data disk is persistent. On first boot the guest formats that disk and installs the missing signed x86-64 service artifacts. Later boots retain valid artifacts, including deployed upgrades. The builder refuses to overwrite an existing appliance unless `-replace` is supplied. The default 1 GiB data disk requires the shared 4 MiB userspace heap so the object store can hold its allocation bitmap, directory, and mirrored-directory mount buffer.

The supplied VM attaches VMware's emulated Intel 82574L adapter to NAT. The userspace E1000E driver receives delegated MMIO, MSI-X, and protected-DMA authority, waits for link without occupying an LP, and publishes the same hardware-neutral `net0` service as virtio-net. Discovery, DNS, smoltcp, HTTP, and cluster code therefore require no VMware-specific branch. The E1000E path is qualified under Fusion, while paired VMware guests and VMXNET3 remain unqualified. The complete setup and qualification record is in the VMware x86-64 appliance guide.

21.5 Expected boot output

```
CharlotteOS booting...
[init] BSP initialization complete.
[init] Secondary CPUs brought online.
[init] Starting scheduler...
[async] coordinator: submitted worker, awaiting completion...
[async] worker on LP1: sleeping 50ms
[async] worker on LP1: exiting
[async] COMPLETION RECEIVED, result Ok(42)
[async] SUCCESS: async syscall round-trip complete
Testing Complete. All Tests Passed!
```

21.6 Dependency advisories

CI runs `scripts/check-dependency-advisories.py` against the complete root lockfile. Its scanner version is pinned in `.cargo/audit-version`; project policy in `.cargo/audit.toml` supersedes a developer's global defaults. Fresh RustSec/registry fetches and all architecture, severity, informational and yanked-package checks remain enabled, with no ignores. Scanner, network and configuration errors reject. A successful status still requires a complete, unfiltered JSON report without vulnerabilities or warnings, including notices that the pinned scanner can otherwise report without failing.

The 26 October 2026 scan first prompted a compatible `ctutils` update. The subsequent pinned Embassy-based TLS migration replaces the old curve API family with `crypto-bigint` 0.7.10 and `ctutils` 0.4.6. The complete 182-package root graph now passes the fresh advisory gate without ignores. This is

a point-in-time result, not proof of constant-time code generation on every platform or closure of SEC-14. License policy, protected release provenance and repository required-check settings remain separate. Current commands, exact source/database identities and evidence are in the dependency advisory reference.

21.7 Self-tests

The repository combines host-side library tests with boot-time kernel and EL0 self-tests. Host suites cover components such as `catten-graft`, `charlotte-protocol-msg`, and `charlotte-smoltcp`. Boot tests run from `self_test::run_self_tests()` after initialization; assertion or verifier failure fails the boot suite.

Deferred tests register an expected result bit. The `results::spawn_verifier` helper spawns the verifier and associates its single thread with that test in a fixed atomic table. If the verifier panics, the panic handler uses a best-effort non-blocking scheduler lookup and marks the associated test failed before emitting the panic. Consequently the authoritative reporter names the failed test instead of leaving it pending until the runner timeout. The panic path neither allocates nor waits for a scheduler lock.

Representative boot suites include:

- `completion.rs`: buffer ownership, cancel/deferred-reclaim, backpressure.
- `cq.rs`: CQ ring write/drain/overflow.
- `cq_completion.rs`: CQ ring integrated with completion subsystem.
- `syscall.rs`: dispatch table routing via synthetic TrapFrame.
- `ipi.rs`: bounded queue, backpressure, closure dispatch.
- `shard.rs`: `ShardLocal<T>` owner-check / re-entrancy guard, `ShardMailbox<M>` send/recv.
- `el0.rs`: real userspace thread (AArch64 EL0 and x86-64 ring 3).
- `el0_demo.rs`: EL0 userspace smoke test.
- `el0_ipc.rs`: EL0 endpoint IPC between domains.
- `el0_net.rs`: EL0 networking test.
- `el0_pingpong.rs`: bidirectional EL0 IPC.
- `el0_raft.rs`: focused two-member Raft election over local IPC.
- `el0_service.rs`: EL0 service lifecycle (spawn, IPC, teardown).
- `el0_uart.rs`: userspace UART driver (delegated MMIO + IRQ, crash recovery).
- `el0_sitas.rs`: sitas executor integration covering sharded KV, the mailbox index demo, and the thread-join probe (Section 9.8).
- `scheduler_lifecycle.rs`: spawn, block, wake, abort, migration-safe migration, timer-wait affinity.
- `ipc.rs`: IPC path tests (scalar, memory, delegation, reply tokens).
- `memory/allocator.rs`: heap allocator, stack allocator.
- `memory/object.rs`: memory object lifecycle tests.
- `adversarial.rs`: cancellation races, misuse paths, error-path testing.

21.8 The async-syscall demo

`crates/catten/src/demo.rs` is an end-to-end test of the async model. It:




Figure 21.1: Ordinary boot enables production networking and services; test switches add validators, while explicit negative switches remove runtime features.

1. Spawns a coordinator and worker from `bsp_main`.
2. The coordinator calls `submit_worker`, which spawns a worker thread and returns a capability that fires when the worker exits.
3. The worker sleeps 50ms (exercising the timer and block-yield-wake cycle).
4. The worker exits; the exit-observer fires; the capability completes.
5. The coordinator (blocked on `wait(cap)`) wakes and reads the result.

This exercises thread creation, scheduling, timer events, the block–yield–wake cycle, exit observation, and the wait/poll ABI. It gives us evidence for that path. We still need the wider self-test suite.

21.9 CI pipeline

GitHub Actions (`.github/workflows/ci.yml`):

1. Checks formatting for the complete workspace, including separately targeted EL0 and host-tool packages.
2. Runs warning-denied Clippy for both kernel targets, AArch64 services, and the signing tool.
3. Runs host-testable library suites and the signing self-test.
4. Runs bounded TLA+ safety models and their negative regressions with a pinned TLC artifact.
5. Builds AArch64 and x86-64 kernels and the AArch64 service bundle.
6. Boots four-LP AArch64 and x86-64 QEMU suites on macOS TCG and verifies their required success markers. The AArch64 job includes the security fixture.

The workflow runs on pushes and pull requests for its configured branches; the boot matrix has no additional main-only condition. This describes the checked-in workflow, not the result of a new hosted CI run.

21.10 Codebase reading guide

For new contributors, the recommended reading order:

1. `crates/catten/src/main.rs`: kernel entry point, init sequence.
2. `crates/catten/src/completion/mod.rs`: the completion subsystem: capability table, submit/complete/poll/wait/cancel/close, `submit_worker`, exit-observer.
3. `crates/catten/src/completion/cq.rs`: the CQ ring buffer.
4. `crates/catten/src/syscall/mod.rs`: syscall dispatch table.
5. `crates/catten/src/demo.rs`: the end-to-end async demo.
6. `crates/catten/src/cpu/scheduler`: threads, wakers, `RoundRobin`, `block_thread`.
7. `crates/catten/src/cpu/multiprocessor`: SMP facilities, per-LP state, typed mailboxes and IPI dispatch.
8. `crates/catten/src/cpu/isa`: ISA abstraction layer. Start with `interface/` (traits), then `aarch64/` (reference implementation).
9. `crates/catten/src/service`: supervisor, ELF loader, bootstrap.
10. `crates/catten/src/device_management`: device driver framework.
11. `crates/catten-services/src/bin`: reference EL0 services.

12. crates/catten-rt/src/lib.rs: userspace runtime.

21.11 Troubleshooting

Triple fault during boot Check that the panic handler is working. Early faults before heap initialization rely on `early_logln!` (direct serial writes). Ensure the serial port is configured correctly.

Blocked thread The block–yield–wake cycle requires that `block_thread` not clear `current_handle` before `yield_lp` saves the thread's context. Verify that the blocked thread is still the current thread at the point of the yield.

ASID-0 collision The first user address space must not receive ASID 0 (which equals `KERNEL_ASID`). The address-space table must be pre-populated with the kernel AS at index 0.

x86-64 LA57 mismatch Derive the address width from `CR4.LA57` (the active paging mode), rather than from CPUID capability. Limine boots with 4-level paging even on CPUs that support 5-level.

22 Formal Safeguards with TLA+

CharlotteOS uses executable TLA+ models to review stateful functionality. The models state each safety contract, explore action orderings in a finite instance, retain known-bad designs as counterexamples, and map abstract transitions back to Rust.

This is stronger than relying on selected test schedules, but narrower than a proof of the complete operating system. TLC proves invariants of the modeled state machine for the configured finite bounds. The repository supplements that result with an action-level conformance map, Rust regression tests, target builds, Clippy, and boot tests. Each layer answers a different question:

TLA+ model Is the protocol design safe under every modeled action ordering, crash point, retry, and stale event within the configured bounds?
Conformance map Which concrete Rust state and linearization point implement each abstract action?
Rust and boot tests Does the implementation exercise the intended transition on the host and on CharlotteOS targets?
Build and lint gates Does the integrated implementation remain type-correct and warning-free for the actual target?

The models and their configurations live in `docs/tla`. The concise model inventory is in `docs/tla/README.md`; the concrete-to-abstract mapping is in `docs/tla/CONFORMANCE.md`. Those files are maintained with the implementation and are authoritative over the overview in this chapter.

22.1 Why model functionality as a state machine?

Most failures addressed by these models are not computation errors. They are ordering errors: a stale cleanup arrives after a replacement, a thread is removed while it can still execute, a session identifier is reused after a restart, or a joiner forgets which cluster has authority over it. A unit test can exercise one such interleaving. A state-machine model asks TLC to enumerate all reachable interleavings in a deliberately small world.

A TLA+ safety specification has four essential parts:

1. **Variables** record only the state relevant to the property, such as an owner, generation, durable term, queue, or admission anchor.
2. **Init** defines every allowed initial state.
3. **Next** is a disjunction of named actions. Each action defines its enabling condition and complete next-state update.
4. **Invariants** state what must be true in every reachable state.

The common shape is:

```
VARIABLES phase, generation, owner
vars == <<phase, generation, owner>>

Init == ...
```

```
Next == Start \/ Replace \/ Stop \/ Crash \/ Restart
Spec == Init /\ [][Next]_vars

TypeOK == ...
Safety == ...
Invariants == TypeOK /\ Safety
```

The square temporal operator means that every step must be a `Next` step or a stuttering step and that the invariant must hold throughout the behavior. TLC constructs the reachable state graph rather than sampling it. Constants in a `.cfg` file bound identities, queue capacities, generations, terms, and log indices so that this graph is finite.

Small bounds are intentional. Many protocol violations need only two owners, two generations, or three Raft nodes. Exhaustive exploration of that small instance is often more revealing than a large randomized run because TLC systematically covers the orderings rather than hoping to encounter them.

22.2 The safeguarding loop

CharlotteOS applies the models as a feedback loop between design, implementation, and validation:

1. **Choose a safety boundary.** Identify the authority or resource whose invalid transition would be harmful: reply authority, memory ownership, an executing address space, a committed log entry, or a service generation.
2. **Project concrete state.** Remove bytes, addresses, and policy details that cannot affect the selected invariant. Preserve identity, ownership, durability, ordering, and lifecycle phases.
3. **Name the transitions.** Actions use implementation language. Names such as `Receive`, `Reap`, and `Restart` make review against Rust possible.
4. **State the invariant positively.** Examples are "a reaped thread is off-CPU," "a committed entry agrees at every replica," and "a stale generation cannot remove its replacement."
5. **Model crashes and stale work.** Durable and volatile state are separated where restart matters. Delayed messages, old handles, and retries are actions rather than assumptions that the environment is well behaved.
6. **Retain a negative specification.** When a faulty transition is understood, an `Unsafe...` action and configuration are kept. The check suite requires TLC to find the named invariant violation. This proves that the invariant and test harness are capable of seeing the regression rather than passing vacuously.
7. **Map back to code.** `docs/tla/CONFORMANCE.md` records the concrete function, persisted field, and linearization point for every modeled action. Disagreement is resolved by changing the model, changing CharlotteOS, or documenting behavior outside the abstraction.
8. **Validate both levels.** Run TLC, focused Rust tests, target builds and Clippy, and relevant boot or multi-node tests.

We use the executable model to check the safety contract alongside the implementation. A change is incomplete if the model claims an atomic or durable transition that the code does not provide.

22.3 What is modeled

The current suite checks forty-seven safe configurations across forty-four specifications. It also checks 143 expected-counterexample configurations. The models are divided by state ownership and failure boundary so that each remains reviewable. The Raft models are deliberately layered: election, log replication, membership, pre-membership admission, and snapshots have different state and different proof obligations.

22.3.1 Use the inventory to find a functional boundary

The table maps each model to the state it owns and the safety properties it checks. Read it as an inventory of separate boundaries. Detailed projection notes follow the table, grouped by resource accounting and request lifecycle.

Model	Functional boundary	Principal safety properties
`CharlotteDeploymentClose`	Logical socket-close admission and acknowledgement	Accepted close submitted once; owner and position retained until acknowledgement; failure retains scope through abort.
`CharlotteDeploymentOutput`	Confirmed output prefixes and original budgets	Once-only prefix submission; unchanged deadlines; wakes grant no enqueue or replay authority.
`CharlotteDeploymentControl`	Accepted controller calls, independent reply readiness, timeout and receiver backing	Complete wait interests; once-only submission; retained owners on rejected wait; timeout grants no receiver release authority.
`CharlotteDeploymentInput`	Four admitted HTTP inputs, rotating turns, shared prefix budget and original deadlines	Bounded retained prefixes; ready input turn bound; unchanged budgets; retained owners on rejected wait.
`CharlotteIPC`	Endpoint calls, reply tokens, memory move/copy/borrow, cancellation, endpoint close, domain teardown	Bounded queues; unique receiver-visible reply authority; exclusive write borrow; every remaining borrow backed by a live token; no dangling moved-memory capability.
`CharlotteIpcTransaction`	Multi-entry vector preparation, connection attachment, rollback, delivery, reply and non-terminal timeout	Failed preparation restores every affected registry; attached connections cannot escape their transaction; timeout cannot release a live call's loan.
`CharlotteIpcPublication`	Captured reservation, move escrow, hidden memory/connection delivery and namespace replacement	Publication validates the whole batch; receive/observation grants access once; late cleanup preserves successor authority and original metadata charges.
`CharlotteEndpointObservers`	Readiness observers and connection-close watches	Ordinary message arrival cannot falsely signal endpoint closure; closure wakes the appropriate observers.
`CharlotteCQ`	Completion operations, CQ ring/backlog, wait/wake, cancellation, timers	Non-lossy completion tracking; bounded visible ring; no lost wakeup; timer completion remains tied to its operation; a buffered operation retains its kernel loan through cancellation until terminal completion.
`CharlotteTimedWait`	Work-generation publication, delayed wake delivery, and watchdog expiry	A timer cannot report timeout after a new work generation has already been published.

Model	Functional boundary	Principal safety properties
`CharlotteCheckedWait`	Fallible watchdog/source admission, registration, park recheck, unrelated wakes and result observation	Pending owners and loans survive rejected admission and timeout; wakes cannot adopt results; retries preserve one deadline and accepted request.
`CharlotteScheduler`	Spawn, admission, execution, blocking, migration, cross-LP abort, reaping, address-space destruction	At most one execution per LP; only the owner LP retires an executing thread; reaping occurs off-CPU; domain abort prevents late sibling publication; destroyed address spaces have no live threads.
`CharlotteThreadJoin`	Recyclable TIDs, spawn generations, delayed exit-observer registration	A captured handle observes only its exact generation; a missing or recycled slot completes immediately; exhausted generation identity fails closed before wrap.
`CharlotteStackGrowth`	Demand-grown user stacks, admitted budgets, pressure reserve and domain exit	Growth stays within its committed-page budget and preserves the free-frame reserve; modeled exit releases frames.
`Charlotte AddressSpace`	Reusable numeric ASIDs and software-generation handles	A stale handle cannot close a replacement that reused the same numeric ASID.
`Charlotte NamespaceDrain`	Fenced namespace selection, peer close, rejected preparation and presence recheck	Missing selections rescan; Pending checks presence; live claims prevent namespace completion.
`Charlotte RootRetirement`	Exact-root leases, staged close, invalidation retry, abandonment and physical release	Complete owners survive uncertain invalidation; leases fence detachment; physical cleanup runs once after acknowledgement; rejected release retains original charges.
`Charlotte HardwareAsid`	Hardware-ASID allocation, retirement, cached translations, invalidation	A hardware tag is not reused while stale translations for its former owner remain.
`Charlotte InterruptRoute`	Interrupt binding, queued wake, unbinding, deferred drain	A queued wake cannot be delivered through a later route generation to the wrong owner.
`CharlotteCapability`	Unified per-address-space capability namespace and move rollback	Handles are fresh and authoritative; move revokes the source; rollback restores only the exact transaction; a closed namespace is empty.
`Charlotte Authorization`	Versioned subject/service policy, generation-fenced service bindings, decisions and capability issuance	Only authorized roles mutate policy or publication; decisions are bound to a subject, policy version, service generation and rights; redemption is single-use and cannot amplify authority.
`CharlotteName Publication`	Local public/policy classes, prepared death watches, replacement and retirement	Public paths cannot issue policy-published connections; watch admission precedes mutation; stale hints need the current producer's own result; disposal preserves watch/source order.
`CharlotteBootTrust`	Verifier, exact installed fixture, one-shot handoff and conditional protected installation	Signed verification does not install policy; boot uses committed identity; the slot cannot be replaced; bootstrap and later images use one selected authority; future commit/reboot ordering assumes protected atomic state.

Model	Functional boundary	Principal safety properties
`CharlotteDMA`	CPU mapping, IPC loans, coherent/exclusive SMMU mapping, invalidation, quarantine, driver exit, pin reclamation	Unique stream/domain ownership; exclusive DMA has no overlapping CPU authority, loan, or second pin; mapped memory stays pinned; failed hardware acknowledgement retains rather than prematurely frees authority.
`CharlotteDma Operation`	Fixed-unit readiness, retained map/unmap owners, typed rejection and CPU teardown	Availability grants no completion proof; started attempts cannot replay; confirmed DMA survives CPU-unmap failure; uncertain pins retain backing and its original charge.
`Charlotte ServiceLifecycle`	Signed artifact staging, loading, start, two-phase publication, lookup, fenced unregister, exit and teardown	Untrusted images never load; only activated generations resolve; stale activation/unregister cannot affect a replacement; teardown follows domain-wide reaping after cooperative exit or domain abort.
`CharlotteRaft`	Terms, durable votes, election, higher-term step-down, crash/restart	A voter records at most one durable vote per term and at most one leader can hold a term.
`CharlotteRaftLog`	Append, conflict repair, replication, commit, crash/restart	Log matching, committed-entry agreement, commit within the log, and leader completeness.
`Charlotte RaftResponse`	Delayed term replies, admitted peers and confirmed replication progress	An old prefix acknowledgement cannot commit a replacement; reordered replies and backoff preserve confirmed progress.
`CharlotteRaftRead`	Per-read log fences, delayed replies, ownership binding and query completion	Reads require a fresh quorum-confirmed index, application and exact node/domain, term and membership episode.
`Charlotte RaftMembership`	Voters/learners, joint consensus, finalization, decommissioning	Both voter majorities are required while joint; all proposed peers reach the joint fence before finalization; leadership and decommissioning follow active membership.
`CharlotteRaftJoin`	Selected-anchor admission before membership, JOIN fence, catch-up, crash/restart	A joiner accepts only the chosen anchor, cannot campaign, is promoted only after catch-up, and restores its durable admission fence after restart.
`Charlotte RaftSnapshot`	Chunk reception, durable installation, matching suffix, membership recovery	Stale snapshots cannot regress progress; the installed state and retained suffix agree; restart restores membership and application state before use.
`CharlotteRaftStream`	Leader/term-bound snapshot chunks and offset order	A replacement election discards partial bytes; installation uses one sender episode in strict offset order.
`Charlotte SnapshotRestore`	Application acceptance, rejected restore, persistence failure and restart exposure	Rejection preserves application, durable state, progress, membership and join admission; recovery must accept the snapshot before exposing its node.
`CharlotteCluster Ingress`	Joint membership, replica placement, exact-generation readiness, drain, immutable ingress snapshots, and retained flow epochs	New flows require a fresh snapshot lease; eligible backends are placed, ready, admitted, and non-draining; incomplete snapshots do not install; an unretained flow epoch cannot silently remap.

Model	Functional boundary	Principal safety properties
`Charlotte PlacementControl`	Filtered pressure, dwell, cooldown, eligibility loss and capacity reservations	Pressure-only moves respect stability gates; lost eligibility permits forced movement; reservations preserve the protected capacity reserve.
`CharlotteRemoteCall`	Call identity, target generation, duplicate suppression, timeout uncertainty, result eviction	At most one execution while tracked; stale targets never execute; uncertain outcomes are not reported as success; deduplication evidence remains until transport settlement.
`Charlotte ReliableMessage`	Wire sessions across retry abandonment and unilateral service restart	Logical epochs have unique ordered wire identities and delayed sessions cannot move receive state backwards.

This decomposition also states what is *not* silently being claimed. For example, Ethernet fragmentation and retry timing are not part of the Raft election proof; protobuf bytes and peer addresses are not part of joint consensus; cryptographic correctness is not part of the service-lifecycle trust-bit abstraction. Such omissions are recorded in the conformance map.

22.3.2 Resource sponsorship and retirement projections

These projections distinguish logical ownership from retained storage and physical release. Their negative controls check early refunds, successor billing and reuse of retired identities.

Optional detail: Principal backing

The principal-backing projection shares one ceiling across three root slots and unequal object/table/stack footprints. Reserved stack capacity pays before growth; a later commitment does not pay twice. One slot can restart under another principal. Moves, retirement and abandonment retain the original charge; explicit physical confirmation alone refunds it. Six negative controls include early reservation refund and double-charged growth. Object counts, allocator/node metadata, hardware and pressure fairness lie outside the projection. See `docs/tla/CharlottePrincipalBacking.tla`.

Optional detail: Thread metadata

The thread-metadata projection prepays unequal context/node bundles across two roots sharing one principal. Construction, context disposal, actual node free and refund remain separate actions. A reused root slot keeps its old charge bound to its original principal; abandonment retains admission. Four negative controls admit by generation, refund before node deallocation, refund abandonment or bill the replacement principal. The safe graph has 4,132 distinct states, 12,559 generated states and depth 15. Stack-release proof is an input; node reserve, allocator overhead, observer/table storage, IRQ contexts and pressure fairness lie outside the projection. See `docs/tla/CharlotteThreadMetadata.tla`.

Optional detail: Principal history

The principal-history projection follows prepared/root-attached nodes and boot-lifetime records through shared total/ordinary admission. Duplicate candidates retain their original classification; logical exit and abandonment cannot refund storage. Root confirmation and actual deallocation are inputs to release. Six negative controls restore early refunds, reclassification, eviction or reserve bypass. Its safe graph has 2,539 distinct / 5,410 generated states, depth 19. Exact bytes, allocator/hardware/generation proofs and pressure fairness remain outside it. The seven focused cases pass. The 24 October follow-up also completes the full 190-case suite: 47 safe configurations and 143 expected counterexamples across 44 modules. See `docs/tla/CharlottePrincipalHistory.tla`.

Optional detail: Namespace drain

The namespace-drain projection checks one poll with two nonreused token identities under an existing admission fence. A competing close can remove the selection before cancellation preparation. Rechecking absence permits rescan; every still-present claim remains Pending. Negative controls restore stale Pending or skip live work. Actual root, loan, backing and peer-completion proofs are boundary inputs, and later wakes/deadlines lie outside this projection. See `docs/tla/CharlotteNamespaceDrain.tla`.

22.3.3 Deployment request lifecycle projections

The deployment projections follow a request from listener setup through input, controller forwarding, output and close. They check ownership, accepted-once submission and original deadlines at each boundary. Each note states the assumptions and omitted behaviour of that projection.

Optional detail: Listener setup

The deployment listener projection checks two setup positions through creation, listen and idle accept. Each phase accepts once, all setup phases share their original deadline and parking covers every owner. Admitted idle accept has no timer. Negative controls replay a phase, restart its budget or park beside a ready reply. Binding, producer delivery and atomic turns are assumptions; shutdown, dynamic cross-phase admission, byte validation, TCP state and wall-clock fairness remain outside the projection. See `docs/tla/CharlotteDeploymentListener.tla`.

Optional detail: Input admission and turn rotation

The deployment input projection checks four admitted slots, aggregate input-byte bounds, unchanged request budgets and a ready healthy input's bound on intervening turns. Negative controls retain a busy input's cursor or restart its deadline. Atomic input turns and producer/CQ delivery are assumptions; controller calls, response transmission, close, new admissions and wall-clock fairness are outside this model. See `docs/tla/CharlotteDeploymentInput.tla` and its conformance map.

Optional detail: Controller calls

The deployment controller projection checks two admitted calls, binding before parking, observation beside an unanswered request, original deadlines and once-only submission. Receiver backing may survive caller cancellation until its own release action. Negative controls park on one silent call while another reply is ready or replay a timed-out request. Preparation, byte admission, controller-server execution, response latency and physical teardown are omitted. See `docs/tla/CharlotteDeploymentControl.tla`.

Optional detail: Controller-server relay

The controller-server projection checks a preflight/mutation relay beside a query. Only checked evidence permits mutation, every phase submits once and the original budget survives phase changes. Parking covers both owners; DNS backing may survive local termination until its receiver releases it. Negative controls turn unknown into absence, restart time, park beside a ready reply or replay mutation. Admission, signature/record validation, shutdown, legacy handlers and wall-clock fairness are outside the projection. See `docs/tla/CharlotteControllerRelay.tla`.

Optional detail: Output prefixes

The deployment output projection checks two admitted outputs with two abstract prefixes. Only a positive producer receipt advances the offset and admits its remainder. Wakes grant no progress, uncertainty permits no replay and all chunks retain the original deadline. Negative controls replay an uncertain prefix or restart its budget. Byte framing, capacity, actual TCP delivery, socket close, wall-clock scheduling and whole-service fairness are outside the projection. See `docs/tla/CharlotteDeploymentOutput.tla`.

Optional detail: Logical close

The logical-close projection starts with two owned sockets. It checks rejected admission backoff, accepted-once submission, original deadlines, acknowledgement before position release and complete ownership through abort. Both Started and Unavailable are logical receipts; neither models physical release. Negative controls replay an accepted close or release its owner before acknowledgement. Bound reply sources and atomic turns are assumptions; actual ID allocation/reaping, wire decoding, socket setup, dynamic admission, whole-shutdown timing and physical release remain outside the model. A one-owner blocking configuration also checks terminal unstarted admission retention. Its destructor-fallback negative control re-enables work after that state and violates `NoReentry`; accepted replay has its existing control. This is no recoverable custody, deadline-duration, field-destructor or runtime abort proof. See `docs/tla/CharlotteDeploymentClose.tla`.

22.4 How model reasoning changes CharlotteOS

The most valuable result is often a mismatch discovered while constructing the model. The correct response depends on which side was wrong: sometimes the manual or model overstated functionality; sometimes the code lacked a safety fence.

22.4.1 Authorization is controlled capability issuance

The local name service implements policy-controlled authorization alongside public bootstrap naming. Bearer-key lookup opcodes are retired. The signed loader binds an artifact-derived stable principal, exact address-space generation, and roles in a kernel-only table. IPC enqueue places that authenticated snapshot in the receive envelope; request memory cannot choose the caller identity.

The authorization model makes the intended boundary explicit. The catalog publishes a service generation and the maximum rights that may be delegated. A separate logical policy role maps a stable principal and service identity to an allowed-rights set and policy version. A decision is bound to the kernel-authenticated subject, requested rights, current service generation and policy version, and can be redeemed once for an attenuated connection. A co-located name/policy process performs decision and attenuated connection delegation as one serialized transition. Policy mutation and authorized publication require distinct roles, and issuance, denial, and delegation failure enter a bounded administrator-readable audit stream. A later split service needs an unforgeable single-use grant and must revalidate every binding at redemption. Policy and audit state are not yet durable or replicated. Public lookup cannot resolve a policy-published service, and public registration cannot displace one. These publication-class checks remain outside the authorization model and are projected separately below.

The model also prevents an attractive but false claim. A policy update blocks new issuance and invalidates unredeemed decisions, but cannot selectively retract a direct connection already delegated by the kernel. Hard revocation requires endpoint closure, a revocable proxy, or a future kernel lease object. This prospective revocation contract is safer than documenting authority that the implementation cannot enforce. The practical design is recorded in `docs/architecture/authorization-policy.md`.

22.4.2 Boot verification and installation are separate

`CharlotteBootTrust` distinguishes a signed verification receipt from boot authority. Installation verification accepts the current record or its direct successor. Shared `verify_for_boot` instead requires the exact installed revision and digest, rejecting enrollment and uninstalled successors. Kernel preparation requires a `VerifiedBootPolicy` receipt from this check. The x86 fixture uses the same path. Before the first platform domain, the BSP selects its artifact authority into the existing boot slot. Bootstrap and later platform images use that key; missing selection rejects. Composition takes the preparation once, leaving public authority intact, and publication requires the same policy and digest. It supplies the public policy used by both service manifests and the operational gate. A duplicate publication returns its unused preparation; development trust is selected explicitly and is never a fallback after verification failure.

The model has two configurations. The first projects those implemented fixture and development paths. The second is a conditional contract for the missing protected installer: it assumes an authenticated context, atomic rollback-resistant state commit and serialization through early authority selection and boot publication. Once selection starts platform loading, installation is fenced. Two signed successors may verify against one old expectation; only one can commit it. An interrupted commit may leave the whole old or new record durable, so the caller must read protected state again before publishing. Recovery must first settle or fence the original writer; reading old bytes alone proves no completion. Reboot preserves that committed state while discarding volatile verification and publication state.

These assumptions describe work still needed for production. The model adds no installer, firmware authentication, persistent-state adapter, key custody or production selector. Its twelve negative controls expose the weakened ordering, identity and handoff guards, including development-signed platform fallback and authority overwrite. Byte-level cryptography, actual storage atomicity, erasure, outer contexts and physical lifetime remain outside the projection.

22.4.3 Local publication owns its death watch

`CharlotteNamePublication` follows the node-local registry. A candidate owns its source connection before preparing a persistent endpoint-death watch. Watch rejection leaves the current publication authoritative. Successful policy publication and registry replacement are separate internal steps; the serialized reactor admits no request between them. Deferred replies use the installed publication, and only then is the previous watch disposed before its source. Public lookup rejects policy-published entries whether immediate or deferred. Public replacement requires an existing public entry from the same nonzero registrar. Authorized lookup still needs its policy decision; both publication classes have policy-store bindings.

A CQ entry supplies a readiness hint. Even when an old hint matches a current watch, retirement needs that current owner's own confirmed endpoint-close result. Pending or unrelated hints preserve the entry. Unexpected observation, rejected waiting and lifecycle abort retain the registry through terminal abort. Explicit retirement separately requires the exact generation and authenticated registrar or manager. These transitions establish logical unpublication and supply no physical cleanup proof.

Source comparison found a further exhaustion boundary. The policy store could publish an unsigned generation beyond the positive signed NS result range. The subsequent NS conversion rejected after policy mutation. Publication now checks the signed limit first, preserving an active binding or tombstone on exhaustion. Host regressions reproduced the earlier behavior and verify that `i64::MAX` can be published once before later attempts reject.

One finite instance checks two names, principals and candidates at live capacity one; a smaller three-candidate projection reaches generation exhaustion at two. Thirteen required counterexamples weaken the publication, retirement and ownership guards. Kernel authentication and watch-result provenance, trusted launch-budget preparation, wire parsing, allocation/destructor contexts and physical completion remain boundary assumptions.

22.4.4 IPC attachments are cross-registry transactions

The base IPC model intentionally collapses vector attachments. The `CharlotteIpcTransaction` refinement instead represents two or more moved entries, a live memory loan, an attached connection, the queue and the pending-call registry. Current vector calls carry the memory entries, whereas scalar calls carry connection attachments and may copy memory. The refinement deliberately composes these paths into a stronger rollback obligation; it does not claim that one current syscall carries every form. No request is visible until preparation commits, and every pre-commit failure restores all affected registries. Its unsafe rollback keeps one moved entry and a connection in the target after failure and must violate `RollbackRestoresAll`.

A reply-wait timeout is also modeled separately from terminal call completion. It reports only that no reply was observed during the wait and therefore cannot release a buffer still reachable by the kernel or receiver. The unsafe timeout transition releases that loan while the call remains pending and must violate `TimeoutRetainsLoan`.

`CharlotteIpcPublication` follows the owning outputs through a further boundary. A unified capability entry can be live while its memory or connection payload remains hidden in a queued request or unobserved reply. Receive commit and first reply observation make those resources usable. Readiness alone changes no ownership. Failed receive admission or result writing preserves the queued attachments, and repeated observation cannot revive a returned resource that its caller has already closed.

The same model retains captured namespace accounts through reservation, source escrow and detached

metadata disposal. Rollback restores the existing source slot without fresh admission, including at its record ceiling. A replacement may reuse the numeric ASID and handle values; late cleanup must still affect only its original account. Physical cleanup proofs, loans and actual allocator/IRQ/guard contexts remain separate obligations.

22.4.5 DMA availability and completion

`CharlotteDmaOperation` separates unit availability, backend acknowledgement and public completion. Readiness retains the original map owner until both the actual command engine and recorded domain cell can be claimed. Preparation may lose a race to restoration, and another claimant may win before a wake is processed. The owner rechecks the same unit and starts mapping work once. Busy waiting requires a qualified scheduled caller; masked ready paths can still complete without waiting.

Before entering unmap, the runtime records the attempt as retained. Only a typed rejection before backend claim can rearm it. A failure after work starts, including a busy-looking final completion error, grants no replay permission. Confirmed DMA completion survives failed CPU teardown, so a later finish can retry CPU unmap without repeating DMA unmap. Failed shared setup keeps its CPU mapping behind a restricted owner; local teardown cannot refund backing that an uncertain DMA pin still retains. Hardware acknowledgements, physical release and actual allocator/IRQ/guard contexts remain separate obligations.

Source comparison found a missing step in that abstraction. Consuming the restricted wrapper through `unmap` returns an unmapped memory owner. The kernel had fenced fresh CPU mappings only for exclusive DMA pins, so a retained coherent pin could still allow a fresh mapping with safe Rust access. A controlled kernel regression reproduced that path. Fresh read-only and writable mappings now require all DMA pins to be gone. Existing coherent mappings are installed before pinning and keep their volatile-access contract. The model includes fresh remapping and a required counterexample that removes this fence; the audit records the failing ARM run and passing ARM/Intel runs.

22.4.6 Two-phase service publication

An earlier lifecycle abstraction treated replacement publication as one atomic swap. The implemented distributed catalog instead performs three observable steps: commit an inactive prepared generation, publish the local connection, and commit activation. Lookup intentionally excludes the inactive generation, so replacement has a temporary unavailable interval.

The model was changed to describe that real contract rather than claim continuous availability. It also exposed the code-level obligation that generation allocation must fail closed. Distributed generation saturation and local unchecked increment were replaced with checked allocation that returns an error without mutating the catalog. A delayed unregister is accepted only when both owner and generation still match, which preserves a replacement.

The model records this availability limit while preserving the generation safety that the implementation enforces.

22.4.7 Reliable-message session identity

The reliable-message service formerly initialized a wire session from the service generation and incremented that number when abandoning a retry epoch. Generation N after one abandonment could therefore use the

same identity as generation $N + 1$ before abandonment. A bounded retired-session window also allowed a sufficiently old delayed SYN to replace newer receive state after it fell out of the window.

The session model represents a session as the ordered pair $(serviceGeneration, retryEpoch)$. The repaired wire encoding packs those values into disjoint 32-bit fields, accepts a replacement session only when the packed identity is well formed and strictly newer, and disables sends rather than wrapping at exhaustion. Two unsafe configurations retain the old flat-identity collision and receive-regression behaviors as required counterexamples.

22.4.8 Restart-safe Raft admission

Dynamic admission originally kept `joining` and `joining_from` only in process memory. A node could select an existing cluster as its authority, crash before membership became durable, restart from its launch-time singleton configuration, and campaign. The gap represented a behavior of the implementation that the model had not captured.

The repaired implementation persists a `JoinAdmission` record containing the selected anchor and the snapshot index that existed before admission. Construction restores the joining posture and disables elections. When the joint membership commits, the node first writes a newer membership-bearing snapshot and only then clears the durable admission record. This ordering covers both crash edges:

- before the membership snapshot is durable, restart retains the anchor fence and the node cannot campaign;
- after the snapshot is durable but before the fence-clear write, restart recognizes the strictly newer membership snapshot as completion evidence and safely clears the stale admission record.

Operational auto-join belongs to the durable DNS-owned Raft node. Volatile Raft nodes must not auto-join: without stable state, a process restart cannot prove which cluster has authority. The safe TLA+ specification includes crash and restart; an unsafe restart that forgets admission must violate `RestartPreservesAdmission`.

22.4.9 Membership changes preserve the tested Graft contract

Charlotte's Raft port derives from Graft, whose Java, C++ and Rust runtimes are intended to form mixed clusters. The upstream Jepsen harness exercises hostile schedules and membership changes. That evidence makes core and runtime parity an explicit review concern; a local model or host test does not replace it.

A source comparison found that Charlotte had replaced the Java/Rust automatic finalization catch-up gate with immediate proposal after JOINT committed. The port now waits for every proposed remote voter and learner to reach the committed JOINT fence. The leader owns that prefix locally. Committing FINALIZE still requires both voter majorities. A slow proposed member can delay automatic completion; explicit/manual finalization is a separate path.

A second regression finalizes the current leader as a retained learner. The previous Charlotte code kept it in the leader state. It now becomes a follower immediately, keeps its existing-term durable vote, and remains a member. The upstream Jepsen demotion scenario selects a non-leader, while leader removal has its own scenario; the new regression covers the retained-leader transition.

`CharlotteRaftMembership` checks 6,232 distinct states. It includes next-only voter elections with both majorities and rejects automatic finalization while a proposed member lags. Three counterexamples

remove the catch-up, leader-eligibility and dual-quorum guards. Durable vote persistence remains a source-test obligation. Native Charlotte checks do not establish Graft TCP interoperation, mixed implementation histories or read-lease correctness.

22.4.10 A delayed acknowledgement belongs to its original term

A source regression captured an honest term-one acknowledgement for index three, then replaced the local prefix under term two. On re-election in term three, a new no-op occupied index three. The old response incorrectly committed the replacement, although the responding voter still held the old bytes.

The core now requires exact current term and a matching admitted source before crediting an append or completed-snapshot response. Successful indices cannot exceed the local tail. Reordered successes retain the strongest confirmed prefix; append rejection cannot back off below it. Committed joiners can still replicate before promotion, while voter quorum rules remain unchanged.

`CharlotteRaftResponse` checks this boundary in 49,395 distinct states and retains four counterexamples. The source tests reproduce the unsafe commit before correction. Transport authenticity, request correlation, removal epochs and the timing assumptions of the existing quorum-contact read gate remain outside this proof.

22.4.11 Each read carries a fresh quorum fence

A recent reply cannot prove that a leader still has authority. The host audit reproduced this with three nodes: n2 and n3 committed value 2, then an honest term-one reply reached isolated n1 and reopened its receive-time query gate. n1 returned value 1. Current-term commitment alone did not prevent that read.

The query API now admits each request before appending a fresh no-op log entry. Its `PendingRead` owner captures exact node/domain identity, term, index and membership epoch. The reactor retains it while processing quorum traffic. Readiness observes commitment and application without executing the query; completion rechecks those conditions and consumes the owner once. Earlier acknowledgements cannot confirm its new index. Compaction preserves the proof through a newer committed current-term anchor.

DNS keeps the original monotonic deadline and typed reply destination with the fence. It admits bounded queue storage before publication. Placement lookup returns metadata; a local result carries no connection authority. Ordinary NS lookup strips delegation rights, so DNS does not attempt to re-mint that grant for a different caller. Invocation starts only after confirmed routing and another deadline check, using the existing owned NS lookup/call phases on the shared CQ. Timeout or drop abandons the query while its no-op may still commit; it cannot execute or replay the business call. Readiness-binding rejection aborts with accepted work live. No extra per-read timer or blocking reactor wait is added.

`CharlotteRaftRead` explores 9,916 distinct states, including delayed replies and external leader replacement unseen by the old node. Four controls remove commitment, application, fresh-fence or owner-binding checks. The former stale-read host schedule now rejects. A quorum may have confirmed a fence after admission and replied before a later election; the read proof concerns that confirmation within the request, rather than authority at delivery time.

The shared no-op wire grammar is unchanged. Each read adds a durable log entry and quorum commit, with corresponding storage and latency costs. No performance, Jepsen or mixed Charlotte/Graft execution claim is made. Bounded status/ingress observations retain receive-time freshness separately; this is not general lease qualification.

22.4.12 Elapsed time comes from the kernel counter

The reactors previously counted one 25 ms tick after waking even if seconds had passed. They now convert a kernel-monotonic counter from one fixed epoch, sampling after waits and before inbound or scheduled work. Fractional ticks accumulate; invalid or regressing samples abort with pending work live. Timers wake the service without manufacturing elapsed time. Clock conversion, resource readiness delivery and physical cleanup remain outside the read model.

22.4.13 Snapshot chunks belong to one leader and term

Snapshot chunk assembly also needs a sending identity. The old receiver matched only the snapshot boundary and offset: a new leader, or the same leader in a new election term, could complete an earlier buffer. Host regressions reproduced installation of a combined prefix and suffix. The buffer now captures the leader and RPC term, and elections and higher-term observations discard it. A replacement must begin at offset zero. `CharlotteRaftStream` checks this owner and strict ordering in 400 distinct states, with two weakened controls. It assumes one immutable byte image per sender/term/boundary; same-episode image replacement, transport authentication and general allocation failure remain outside this model.

22.4.14 Rejected application snapshots leave known ground intact

A complete snapshot stream can still contain an unsupported application format or a malformed late section. The catalog parses all sections into temporary collections before replacing live state. A rejected restore leaves those live collections intact. Raft propagates rejection before publishing the snapshot, commit/applied indices, membership or join completion. Construction returns an error before exposing the node or clearing durable admission.

`CharlotteSnapshotRestore` makes this boundary explicit alongside the existing chunk and suffix model. Its finite configuration explores 168 distinct states; seven weakened configurations must produce counterexamples. Separate streamed/recovery coverage requires both completed joins and retained admission. This corrects an earlier assignment-precedence omission that excluded join clearing while broader activation coverage still passed. An accepted newer membership snapshot can complete a join, while the original snapshot or membership excluding this node retains its admission fence.

Restore succeeds before the durable write. If persistence fails, the Raft caller terminates; a later caller must restore the whole durable image again. This ordering does not provide an atomic transaction across application and disk. The model assumes the existing whole-object storage contract and serialized Raft execution. It does not prove decoder correctness, fallible allocation, concurrent-reader isolation, endpoint withdrawal or sibling-thread termination.

22.4.15 Cluster placement and DSR ingress

The cluster-ingress model begins after a Raft application command commits. It then composes stable and joint membership, desired replica sets, deployment generations, per-node readiness, drain intent, discovery routes, asynchronous snapshot installation, VIP advertisement, and per-flow epoch retention. This keeps Raft quorum mechanics in their existing models while checking the point where replicated authority becomes packet-routing policy.

The safe specification derives every eligible backend as the intersection of active membership, committed placement, readiness for the exact deployment generation, and nodes not draining. A router installs only a

complete snapshot for which all member routes are known. New flows require the router's installed policy to hold a bounded local freshness lease. The policy may lag the latest global commit during asynchronous propagation; an abstract fair expiry action prevents an unrenewed lease from persisting forever. Established flows retain their selected policy while its snapshot remains present. After history eviction, the binding remains pinned but its packets fail closed instead of silently choosing a new backend. Concrete snapshot installation additionally requires a quorum-fresh Raft leader or a follower with a recent successful leader-log match, so a responsive but partitioned local DNS process cannot renew the lease indefinitely.

Three negative configurations expose cross-layer failures. One admits a new SYN through a stale snapshot after its freshness lease expires. Another evicts an epoch still named by a live flow and then remaps that flow through the current snapshot. The third admits readiness from an old deployment generation. Exact readiness is already enforced by the catalog. The router now enforces the other two contracts with a five-second monotonic snapshot lease and fail-closed missing-epoch tombstones. All three unsafe actions remain as regression witnesses.

22.4.16 Retained regression patterns

Other negative specifications preserve compact versions of repaired faults and present conformance obligations:

Unsafe action	Failure represented	Required violation
`UnsafeStalePending`	A consumed namespace selection returns Pending without presence revalidation.	`NoStalePending`
`UnsafeSkipLive`	Namespace drain skips a still-present token.	`CompleteOnlyDrained`
`UnsafeMessageWake`	Message readiness and endpoint-close observation share one observer queue.	`CloseSignalImpliesClosed`
`UnsafeRollback`	A failed abstract attachment transaction leaves one moved entry and its attached connection in target registries.	`RollbackRestoresAll`
`UnsafeTimeoutRelease`	Reply timeout releases a loan while the pending call can still access it.	`TimeoutRetainsLoan`
`UnsafeUseMemory`	A guessed memory handle is used before delivery.	`UseRequiresDelivery`
`UnsafeUseConnection`	A guessed connection handle is used before delivery.	`UseRequiresDelivery`
`UnsafePublishPrefix`	One attachment becomes live before the whole batch commits.	`AtomicPublication`
`UnsafeReuseSerial`	Cancelled staged authority returns its consumed serial to the allocator.	`SerialsConsumed`
`UnsafeCancelSuccessor`	A late reservation cancellation alters a replacement namespace.	`ReplacementIntact`
`UnsafeRestore Successor`	Source rollback overwrites a replacement's unrelated payload.	`ReplacementIntact`
`UnsafeRefundRetained`	A detached metadata node loses its charge before disposal.	`RetainedNodesCharged`

Unsafe action	Failure represented	Required violation
`UnsafeReadiness Delivers`	A readiness hint makes hidden attachments visible.	`VisibleRequiresDelivery`
`UnsafeRepublish Observed`	Repeated reply observation revives a resource already closed by the caller.	`ObservedCloseStaysClosed`
`UnsafeRollbackNeeds Admission`	Source restoration attempts fresh admission and strands escrow at the limit.	`RollbackRestores CapturedSource`
`UnsafeRemoteAbort`	A remote LP removes and reaps a context that may still execute.	`ReapOnlyOffCpu`
`UnsafeSpawn DuringAbort`	A sibling publishes after the domain-abort snapshot.	`AbortingThreadsDoomed`
`UnsafeCancelReleases Buffer`	Cancellation releases a mutable buffer before the operation becomes terminal.	`NonTerminalBuffer RemainsLoaned`
`UnsafeTimerFire`	A watchdog reports timeout without rechecking a concurrently published work generation.	`TimeoutObservedNoWork`
`UnsafeRejectedRelease`	Wait admission rejection releases a pending operation's owner and loan.	`PendingRetains OwnerAndLoan`
`UnsafeReplay`	A timed-out accepted operation is submitted again.	`OneSubmission`
`UnsafeRestartDeadline`	A wake starts a fresh timeout budget.	`DeadlineUnchanged`
`UnsafeWakeAdopts Result`	A readiness hint adopts a result before confirmed completion.	`ResultNeedsTerminalProof`
`UnsafeParkWithout Recheck`	Completion precedes registration and the caller parks without checking it.	`ParkedTerminalHasWake`
`UnsafeAdmission Timeout`	Rejected admission is reported as timeout before the deadline.	`TimeoutRespectsDeadline`
`UnsafeObserveJoin`	A delayed join attaches its old handle to the replacement occupying the same TID.	`ObserverMatches CapturedHandle`
`UnsafeSpawnWrap`	Exhausted thread generation wraps and aliases a previously allocated identity.	`GenerationNeverReused`
`UnsafeGrowOverBudget`	Stack growth passes the admitted limit.	`CommittedWithinBudget`
`UnsafeKillWithout Release`	A dead domain retains frames that the stack-budget model requires it to release.	`DeadDomainsReleaseFrames`
`UnsafeBeginExclusive Map`	Exclusive DMA begins while CPU or other transfer authority still exists.	`ExclusiveDmaHasNo CpuAuthority`
`UnsafeClaim DetachedCell`	An available engine is used while its domain cell is missing.	`ClaimNeedsCompleteUnit`
`UnsafeReadiness Completes`	Unit readiness is treated as DMA completion.	`ReadinessIsNotCompletion`
`UnsafeRejectDrops Preparation`	Rejected wait admission drops the original root, claim and pending pin.	`PreclaimRetains Preparation`

Unsafe action	Failure represented	Required violation
`UnsafeReplayMap`	A map error is used to authorize resubmission.	`MapSubmittedOnce`
`UnsafeRearmStarted Unmap`	A failure after backend claim rearms unmap.	`StartedFailureNotRearmed`
`UnsafeDropResubmits`	Drop repeats an uncertain unmap attempt.	`UncertainAttemptNot Resubmitted`
`UnsafeForgetDma Confirmation`	Failed CPU unmap forgets confirmed DMA completion.	`ConfirmationSticky`
`UnsafeFailedShared Access`	Failed shared setup exposes CPU access.	`FailedSharedRestricted`
`UnsafeCpuUnmap DischargesDma`	CPU teardown releases uncertain DMA backing.	`PossibleDmaRetainsBacking`
`UnsafeAbandonReleases`	Abandonment clears the complete owner and unit fence.	`AbandonmentRetainsOwner`
`UnsafeWaitMasked`	A busy masked caller parks on readiness.	`WaitNeedsQualifiedContext`
`UnsafeFinalBusyRearms`	A failed final public completion rearms unmap.	`PublicRejectionRetains Attempt`
`UnsafeCoherentRemap`	Fresh CPU mapping exposes Rust access while a coherent DMA pin remains.	`CpuOwnerNeedsNoDma`
`UnsafePublicLookup`	Public lookup issues a policy-published connection.	`PublicIssuance`
`UnsafeDeferredLookup`	A queued public lookup bypasses the publication class.	`PublicIssuance`
`UnsafePublic Replacement`	Public replacement displaces protected publication.	`ReplacementProtected`
`UnsafeMutationBefore Watch`	Policy changes before watch admission.	`BeforeWatchUnchanged`
`UnsafeHintRetires`	A readiness hint fabricates endpoint death.	`DeathNeedsExactResult`
`UnsafeStaleHint`	An old producer's result retires its replacement.	`DeathNeedsExactResult`
`UnsafeCloseSource First`	Source closes while its watch remains.	`WatchRetainsSource`
`UnsafeNewAtCapacity`	A new binding consumes replacement headroom.	`LiveBound`
`UnsafeAbortDisposes`	Abort disposes retained registry ownership.	`AbortRetainsOwners`
`UnsafeUnauthorized Retire`	Retirement skips its generation or actor check.	`RetirementAuthorized`
`UnsafeGenerationWrap`	Exhaustion reuses an earlier generation.	`GenerationNotReused`
`UnsafePublish Exhausted`	Publication mutates policy beyond the signed NS generation range.	`PolicyGeneration Representable`
`UnsafeLookupDuring Publish`	Lookup runs between policy and registry publication.	`GrantGenerationCoherent`

Unsafe action	Failure represented	Required violation
`UnsafeUninstalled Publish`	A valid successor publishes before its installed-state commit.	`InstalledBefore Publication`
`UnsafePlatform Fallback`	A platform image uses the development key after signed-policy selection.	`PlatformImagesUse SelectedAuthority`
`UnsafeSelection Overwrite`	Selected artifact authority changes within one boot.	`SelectedAuthority MatchesState`
`UnsafeStaleCommit`	A second installer reuses a stale expectation.	`NoForkedInstallation`
`UnsafeEnrollment Fallback`	An installed-state read failure becomes enrollment.	`NoEnrollmentFallback`
`UnsafeOverwrite`	The same boot publishes a second policy.	`OnePublicationPerBoot`
`UnsafeIndependent Manifest`	Manifest and kernel gate select different policies.	`SharedPolicy`
`UnsafeWrongRecipient`	Preparation accepts the wrong private-key binding.	`RecipientBound`
`UnsafeAuthenticate`	A record bypasses authentication.	`VerifiedAuthenticated`
`UnsafeDevelopment Fallback`	Failed verification selects development trust.	`ExplicitDevelopment`
`UnsafeFailedCommit Publishes`	A failed commit grants publication authority.	`InstalledBefore Publication`
`UnsafeUnsupported Production`	Publication bypasses the unavailable protected boundary.	`ConditionalBoundary`
`UnsafeStaleClose`	A recycled numeric ASID is closed through an old generation handle.	`ReplacementSurvives StaleHandle`
`UnsafeDetachWithLease`	A root detaches with a live operation lease.	`LeasesRetainRoot`
`UnsafeReleaseBefore Invalidation`	Backing is released without final invalidation acknowledgement.	`PhysicalRequires Invalidation`
`UnsafeRetryPhysical`	A partially rejected physical walk is retried.	`PhysicalOnce`
`UnsafeAdoptAbandoned`	A controller reconstructs an abandoned owner.	`TerminalAbandonment`
`UnsafeRefundPartial`	Retained backing loses its original charge.	`BackingCharged`
`UnsafeAllocate`	A hardware ASID is reassigned before stale translations are invalidated.	`NoDirtyTagReuse`
`DrainUnsafe`	A deferred interrupt wake ignores its route generation.	`NoStaleWakeDelivery`
`UnsafeStaleUnregister`	Cleanup from an old service generation removes its replacement.	`ReplacementSurvives StaleUnregister`
`UnsafeReplicate ToJoiner`	A non-selected peer supplies authority to a joining node.	`JoiningAcceptsOnly SelectedAnchor`
`UnsafeRestartForgets Admission`	Restart makes an incomplete joiner election-eligible.	`RestartPreservesAdmission`

Unsafe action	Failure represented	Required violation
`UnsafeFinalize BeforeCatchUp`	Automatic FINALIZE bypasses proposed-member catch-up.	`ProposedMembersCaughtUp`
`UnsafeFinalize LearnerLeader`	A finalized learner retains leadership.	`LeaderIsEligible`
`UnsafeFinalizeOldOnly`	FINALIZE commits without the new voter majority.	`FinalizationHas BothQuorums`
`UnsafeReceiveLease`	The retired receive-time query gate admits an obsolete leader.	`ReadHasFenceProof`
`UnsafeReadBinding`	A query consumes another node/domain, term or membership episode.	`ReadBoundToAdmission`
`UnsafeReadBefore Commit`	A new leader reads before committing in its term.	`ReadHasCurrentCommit`
`UnsafeReadBeforeApply`	A read precedes application through the commit.	`ReadHasAppliedCommit`
`UnsafeOldTermAck`	An old reply commits a replaced prefix.	`CommitHasCurrentPrefix`
`UnsafeRegressSuccess`	A delayed success discards confirmed progress.	`ConfirmedProgressRetained`
`UnsafeBackoff`	Rejection backs off below confirmed progress.	`BackoffRespects ConfirmedPrefix`
`UnsafeInvalidCredit`	An unqualified response gains credit.	`AcknowledgementsHaveProof`
`UnsafeReject Application`	Rejected restore changes application state.	`RejectionPreserves Application`
`UnsafeRejectDurable`	Rejected restore replaces durable bytes.	`RejectionPreservesDurable`
`UnsafeRejectProgress`	Rejected restore advances progress.	`RejectionPreserves Progress`
`UnsafeReject Membership`	Rejected restore changes membership.	`RejectionPreserves Membership`
`UnsafeRejectJoin`	Rejected restore clears join admission.	`RejectionPreservesJoin`
`UnsafeExposeRecovery`	Recovery exposes a rejected node.	`RecoveryExposure RequiresRestore`
`UnsafePublishBefore Restore`	Durable publication precedes restore.	`Publication RequiresRestore`
`UnsafeStartStaleFlow`	A router admits a new SYN through an old snapshot after its admission lease expires.	`NewFlowsRequireFreshLease`
`UnsafeFallback ExistingPacket`	Snapshot-history eviction makes an established flow select a different backend.	`FlowBackendStable`
`UnsafeAdmitStale Readiness`	Readiness from an old deployment generation authorizes its replacement.	`CommittedPoliciesAre Derived`
`UnsafeEarlyPressure Move`	Placement pressure bypasses dwell or cooldown.	`PressureRespectsStability`

Unsafe action	Failure represented	Required violation
`UnsafeAdmit`	Placement reservations consume the protected reserve.	`ReservationsPreserveReserve`
Flat session allocation	Retry and restart epochs alias one wire session.	`SessionIdentityUnique`
`AcceptDelayedSession`	An older delayed SYN regresses receive state.	`ReceiveSessionMonotonic`
`UnsafeSetPolicy`	A non-administrator changes a policy rule.	`PolicyMutationAuthorized`
`UnsafeRedeemOtherPrincipal`	A decision for one subject is redeemed for another.	`MintBoundToPrincipal`
`UnsafeRedeemStalePolicy`	A decision survives a policy-version change.	`MintUsesCurrentPolicy`
`UnsafeRedeemStaleBinding`	A decision for an old service generation reaches its replacement.	`MintTargetsCurrentBinding`
`UnsafeAmplifyRights`	Redemption mints rights absent from the decision.	`NoRightsAmplification`

The check suite expects all 143 negative configurations to fail for the named reason. If one unexpectedly satisfies its invariant, the regression harness has lost sensitivity and the suite fails.

22.5 Concrete conformance and atomicity

TLA+ actions are atomic. Rust code usually crosses several structures, locks, or persistent writes. The conformance review must therefore identify a linearization point or represent the concrete intermediate states explicitly.

The mapping uses two correspondence classes:

Direct The abstract action follows one concrete transition while omitting data irrelevant to the invariant. For example, a successful fenced unregister directly checks owner and generation.

Abstract Several concrete operations are collapsed. This is valid only when intermediate states are unobservable or separately guarded. For example, scheduler retirement spans multiple tables, so the concrete `RETIREMENTS_IN_FLIGHT` state prevents address-space teardown during that interval.

Persistent ordering deserves the same care. In Raft admission, “snapshot membership and clear join fence” is one model transition, but two durable writes in Rust. Safety depends on snapshot flush preceding fence removal. A crash between those writes must map to a modeled state that remains safe.

The conformance document is not yet a machine-checked refinement proof. It is a reviewable refinement *obligation*: it names the functions and state that must be re-examined when either side changes. Code review should reject a model update that merely hides a new concrete intermediate state.

22.6 Validation

22.6.1 Running TLC

The repository wrapper runs the complete bounded suite:

```
docs/tla/check.sh /path/to/tla2tools.jar
```

Alternatively, `TLA2TOOLS_JAR` may name the tools archive. The script:

- runs all forty-seven safe configurations;
- enables action coverage and requires selected actions to have a positive successor count;
- rejects structural TLC warnings about variables, `EXCEPT` expressions, or incomplete successor states;
- runs 143 negative configurations and requires each one to fail on the named invariant after exercising the named unsafe action; and
- writes checkpoints and traces into a temporary directory so generated state does not become part of the source tree.

An invariant can pass because a transition is accidentally disabled. Required action coverage detects this vacuity, although it does not prove that an action is correct.

At the 6 September 2026 implementation synchronization point, representative fast configurations produced the following complete state graphs:

Model	Generated	Distinct	Depth
`CharlotteIPC`	6,118,645	1,254,153	13
`CharlotteCQ`	1,586,249	302,659	12
`CharlotteTimedWait`	22	15	8
`CharlotteScheduler`	4,308,577	819,972	22
`CharlotteThreadJoin`	46	39	10
`CharlotteIpc Transaction`	71	26	11
`Charlotte ServiceLifecycle`	689,321	74,232	37
`CharlotteDMA`	19,331,379	2,092,882	26
`CharlotteAuthorization`	144,598	54,705	12
`CharlotteRaftJoin`	2,029	520	13
`Charlotte ReliableMessage`	30	21	5
`CharlotteCluster Ingress`	3,522,889	576,764	17

State counts tell us how much of one configuration was explored. A small model may encode the decisive identity argument, while a large model may contain substantial independent bookkeeping. The invariant, abstraction, and coverage matter more than graph size.

22.6.2 Implementation validation

TLC is followed by validation proportional to the affected code. The August synchronization work, including the 15 August domain-abort and memory-ownership repair, included:

- host tests for `catten-graft`, including restart before durable membership and restart between membership persistence and fence clear;
- host tests for `charlotte-protocol-msg`, including disjoint retry/restart sessions and fail-closed exhaustion;
- host tests for ownership-aware runtime cleanup and the shared `charlotte-lifecycle` thread-join and timed-wait classifiers;
- AArch64 release builds and warning-denied Clippy for the changed `raft`, `relmsg`, and `ns` services;
- AArch64 and x86-64 kernel checks, plus warning-denied AArch64 Clippy, for the domain-abort publication fence and memory-ownership paths;
- a four-LP AArch64 QEMU boot whose authoritative result reported all eighteen registered self-tests passing, including owner-LP retirement, DMA/SMMU, completion cancellation, and service crash/restart; and
- formatting, shell syntax, and diff-whitespace checks.

Boot and multi-guest tests remain necessary when a change affects the concrete scheduler, device, storage, or network integration. A TLC result cannot show that QEMU delivers an interrupt, that an object-store flush reaches the emulated disk, or that a manifest starts the intended services.

22.7 What a successful check means

A successful safe configuration means that TLC found no reachable violation of the declared invariants within that specification and its finite constants. It does *not* by itself establish:

- a proof that arbitrary larger bounds preserve the result;
- a mechanically checked refinement from Rust to TLA+;
- liveness, fairness, bounded latency, or eventual leader election unless explicitly expressed as temporal properties;
- correctness of omitted bytes, parsers, cryptography, memory mappings, hardware programming, or transport framing;
- correctness under storage failure modes below the modeled durable write interface; or
- freedom from ordinary implementation bugs such as arithmetic, aliasing, or unsafe-memory errors outside the modeled projection.

Conversely, a gap between code and model is actionable information. It can mean one of three things:

1. **Functionality is unsafe.** The Raft admission restart gap was of this kind and required a CharlotteOS change.
2. **The model overclaims.** Atomic service replacement was of this kind; the model was corrected to admit temporary unavailability.
3. **The behavior is outside scope.** It must be documented rather than silently attributed to the checked invariants.

22.8 Workflow for changes

Any change to ownership, generations, persistence, retry identity, lifecycle, or distributed membership should be checked against this chapter's method. A practical review checklist is:

1. Search `docs/tla/CONFORMANCE.md` for the changed Rust function or state field.
2. Decide whether the change adds an action, changes an enabling condition, moves a linearization point, or changes durable/volatile classification.
3. Update the safe model and bounds. If repairing a discovered fault, retain the old behavior as an unsafe action and named negative configuration.
4. Add the new action to the required-coverage list in `docs/tla/check.sh`.
5. Run the entire TLC suite, including modules you did not edit, because shared documentation claims and layered Raft assumptions can drift together.
6. Update the conformance map with exact Rust functions and ordering.
7. Add implementation tests at the crash, retry, or stale-generation edges identified by the model.
8. Run target validation and the relevant boot or multi-node suite.
9. Record deliberate omissions and avoid converting a safety result into an unsupported liveness or availability claim.

A Glossary

AS (Address Space) A page-table context identified by an `AddressSpaceId` (0 = kernel, >0 = user). Contains the `TTBR0_EL1` (user) and `TTBR1_EL1` (kernel) pointers on AArch64, or `CR3` on x86-64.

Block (verb) To remove a running thread from the scheduler and register its `Waker` on an `Observable`. The thread yields; when the event fires the waker re-admits it.

Capability An unforgeable per-domain handle that names a kernel object and carries rights. Answers: "May I perform this operation?"

Capability table A per-domain namespace mapping opaque serials to one of six authority families. A serial is not reused within that namespace. Thread and address-space slot tables have separate generation-qualified identities.

Completion The terminal result of an asynchronous operation. The kernel tracks operation state and delivers results through polling, waitable completion objects, or CQ entries.

Connection capability A client-side authority to send or call an endpoint. Minted from an endpoint, typically by the name service.

CQ ring (Completion Queue) A shared-memory ring buffer for zero-syscall completion delivery from the kernel to userspace.

EL0 Exception Level 0 on AArch64. In CharlotteOS source and test names, also used as the architecture-neutral label for userspace, including x86-64 ring 3.

EL1 Exception Level 1 (AArch64). Kernel execution.

Endpoint A bounded server-side IPC receive object. Has an owning domain, a queue capacity, and a lifecycle.

Exit-observer An `Observer` registered on a `Thread`; fires when the thread is dropped (exits). The ABI's intended completion mechanism: `submit_worker` registers the capability as the worker's exit-observer.

HHDM (Higher Half Direct Mapping) A linear mapping of all physical memory into the kernel's virtual address space, provided by the bootloader (Limine).

IdTable A sparse `Vec<Option<T>>` with generation-qualified slot reuse, used for threads and address spaces. The unified capability namespace instead uses admitted map nodes and consumed serials.

IOMMU / SMMU I/O Memory Management Unit. Hardware that enforces DMA access permissions from devices, analogous to the MMU for CPU access.

IPI (Inter-Processor Interrupt) A signal from one LP to another. The kernel's IPI queues are bounded per-LP queues carrying typed commands.

LP (Logical Processor) A schedulable hardware execution context, usually one core or hardware thread. It is distinct from a Sitas shard.

Memory object A page-backed kernel object with explicit ownership and capability semantics. Can be mapped, moved, lent, or copied between domains.

MMU Memory Management Unit. Hardware that enforces page-table permissions for CPU access.

Name service A userspace service that maps human-readable names to connection capabilities. The kernel does not understand service names.

Notification "State may have changed; inspect the corresponding object or queue." May be coalesced. Is not itself a result.

Observable / Observer The event-notification pattern. An `Observable` registers admitted `ObserverWeak` handles; dispatch retains a strong `ObserverRef` while borrowing `Observer::notify(&self)`.

PerLp<T> A boxed slice of per-LP cells with lock wrapping. Interrupt-safe (masks interrupts on acquire). Use for data accessed from interrupt handlers or multiple LPs.

Protection domain An address space and authority boundary. Owns a capability table, memory mappings,

threads, and failure state. Typically implemented as a process.

Quantum timer The per-LP periodic timer (10 ms default) that drives preemptive context switching in the `RoundRobin` scheduler.

Reaper The deferred-thread-cleanup mechanism: dead threads are moved to `DEAD_THREADS` and dropped from the next thread's context after the context switch.

Reply token One-shot authority to complete a blocking or deferred endpoint call. Created by the kernel, bound to the caller's pending call, consumable exactly once, invalidated by cancellation or teardown.

Shard A userspace ownership and execution domain. One executor runs its tasks; at most one task at a time mutates shard-owned state; cross-shard access goes through typed messages.

ShardLocal<T> A lock-free per-LP container using `UnsafeCell<T>` with owner-check and borrow-flag guard. Sitas-derived. Use for single-LP, thread-only kernel data.

ShardMailbox<M> A typed bounded per-LP queue with `ShardSender<M>` (cloneable, any LP can send) and `ShardReceiver<M>` (single-consumer). First-class backpressure.

Supervisor Kernel-side component that creates and destroys protection domains, loads ELF images, delivers bootstrap capabilities, and handles domain teardown.

TrapFrame An architecture-specific snapshot of user register state at an exception. Syscall dispatch combines it with trusted per-thread or per-LP state to identify the caller.

Waker An `Observer` wrapping a `ThreadId`. When notified, calls `submit_ready_thread(tid)`. In userspace, a Rust `Waker` asks the executor to poll a future again. It carries no kernel completion result.

Yield To voluntarily give up the LP by calling `yield_lp()`. Saves the thread's context and lets the scheduler run the next ready thread.

B Implementation Status

This appendix describes mechanisms and their recorded validation separately. The documentation/source comparison was refreshed on 18 October 2026; it did not repeat every runtime fixture. Scope and source anchors are recorded in the dated source comparison. Source, tests, and repository history remain authoritative.

B.1 Boot validation and test selection

Startup memory validation is mandatory and independent of native regressions. It checks physical availability, private-frame readback and accounting, heap reserve bounds and one aligned 8 KiB heap readback. Actual hardware discovery, IOMMU initialization, signatures, admission and service readiness remain normal boot requirements. The operational launcher seeds signed bootstrap service artifacts before publishing its service set, including when no NVMe verifier runs; valid installed artifacts are retained.

Both QEMU runners accept `-minimal` for an operational node without native fixtures or bundled probe applications. Their development default, `-tests`, enables the `kernel_tests` feature; integration features imply it. Optimization selection (`debug`/`release`) is independent. `-build-only` creates the selected images without starting QEMU. Minimal and development bundles/disks are separated and cached kernel modes are checked before image creation. Minimal completion follows confirmed local storage readiness and does not synthesize a self-test verdict. See `docs/reference/boot-modes.md` for the contract and retired exercises.

B.2 Implementation phases

Phase	Description	Status
1	Capability table, rights masks, object teardown	Done
2	Endpoint IPC v1: scalar send/call/receive/reply, connection delegation, reply tokens	Done
3	Userspace name/service manager, bootstrap delivery, ELF loader, supervisor, generation tracking	Done
4	First-class memory objects: allocate, map, unmap, close, ownership accounting	Done
5	Memory IPC: Copy, Move, BorrowRead, BorrowWrite, reply-bound revocation, cancellation, server-death recovery	Done
6	CQ subsystem normalization: operation IDs, detached submission, checked CQ wait/CQ_WAKE, per-shard CQ partitioning, backlog batching, 32-byte completion records	Done

7	Sitas endpoint/CQ backend: endpoint readiness binding, unified shard wait, ShardExecutor (budgeted polling), ShardParker (spin free), per-shard CQ rings	Done
8	Userspace UART driver: delegated MMIO + IRQ, EL0 MMIO writes, interrupt-driven deferred reads, crash recovery	Done
9	Virtio-net driver: PCI/MSI-X and protected DMA, RX/TX, used-ring descriptor reclamation, frame demultiplexing and smoltcp 0.13 TCP/IP. Broader hardware qualification and buffer-pool/batching optimization remain open.	Focused two-guest TCG network suite
10	Lock-free device interrupt delivery (deferred wake), idempotent scheduler wakes, sustained-window load rebalancing	Done
11	Userspace startup ABI: ELF `_start`, `entry!` macro, typed `Context`, fixed-width versioned launch header, explicit startup input	Done
12	x86-64 multi-LP ring-3 platform: shared service ABI, synchronous TLB shootdown, VT-d/AMD-Vi, NVMe/AHCI/virtio-blk, virtio-net/E1000E, discovery, and distributed DNS, smoltcp TCP/IP, HTTP reporting, signed deployment, migration, and dynamic membership	Four-LP and focused two-guest TCG suites
13	UTC time service: internal endpoint API, ISO 8601 formatting, connected UDP/NTP client, drift and uncertainty estimation, monotonic holdover, and object-store calibration persistence	Default boot-validated on both targets
14	Capability-scoped external data services: S3 Signature V4 over verified TLS with streaming object operations; Kafka idempotent producer, read-committed fixed-partition consumer, and transactional produce plus offset commit	Opt-in AArch64 Docker-fixture tests
15	Distributed L2 ingress and placement: up to 16 operations-assigned IPv4/TCP service VIPs, operations-signed Raft-committed complete policy replacement with replay, cluster, and UTC fences, committed-Raft membership intersected with signed fixed/every-node replica sets and per-node exact-generation readiness, policy epochs, continuous membership/drain reconciliation, signed-shutdown draining, deterministic rendezvous placement, leased new-flow admission, fail-closed epoch tombstones, one-hop L2 envelopes, direct backend replies, and exclusive ARP advertisement, per-service policy history, and address-specific listeners	Pure-policy tests, single-node SLIRP VIP, and three-guest host-visible established-flow failover plus backend-loss reconnect fixture

B.3 Success criteria

1. Two EL0 domains communicate through a bounded endpoint: **Verified.**
2. Deferred async call while a shard continues other tasks: **Verified.**
3. Moved memory object with the sender locked out until return: **Verified.**
4. Lending enforced by mappings, including death cleanup: **Verified.**
5. Single `checked CQ wait` for endpoint + completions + device interrupts: **Verified.**
6. Terminal CQ results survive ring overflow (non-lossy backlog): **Verified.**
7. Coalesced remote shard wakes (idempotent scheduler fix): **Verified.**
8. Userspace UART driver with only delegated MMIO + IRQ: **Verified.**
9. UART crash fixture: endpoint closure, device reset and operation reconciliation before replacement: **Verified in that fixture.** Name rebinding alone does not revoke connections to a live old endpoint.
10. Virtio-net data path with batched packet buffers: **Runtime-validated on macOS QEMU TCG.**
11. Fixed-width stable ABI representations (32-byte CQ entries): **Implemented; not formally audited.**
12. Capability misuse and cancellation race adversarial tests: **Partial; six IPC error-path tests.**

B.4 Verified scope

- **AArch64:** boots and the synchronous self-tests pass. The EL0 service suite starts one shared node name service; Raft peers, echo, the service manager, NVMe/object store, UART, and their clients receive delegated connections to that registry. The deferred boot tests exercise registration, waitable lookup, restart, and live upgrade through `crt0/cmain`; the harness may print its synchronous success banner before those deferred tests finish. The Sitas `basic_kv` binary runs with 2 shards on per-shard CQ rings.
- **x86-64:** boots with `-cpu max` on four LPs, enters ring 3, and runs native Rust service ELFs through the shared syscall and launch ABI. The tested service path includes naming, object storage, Raft persistence, service management, live upgrade, virtio-net, discovery, a focused two-guest distributed-DNS and smoltcp TCP exchange, the HTTP state report, signed deployment, cross-node invocation, migration, retirement, `clusterctl`, and dynamic membership. NVMe, AHCI, and virtio-blk run behind Intel VT-d or AMD-Vi. The full cluster suite is qualified with four LPs under QEMU TCG.
  A two-disk VMware Fusion appliance additionally qualifies UEFI boot, guest-visible VT-d, the virtual NVMe controller, blank-store formatting, idempotent installation of signed service artifacts, persistent restart, and the userspace E1000E path through link-up and hardware transmit completion. Paired VMware guests and VMXNET3 remain unqualified.
- **Completion subsystem:** submit, complete, poll, wait, cancel, close, `submit_worker` (exit-observer), CQ ring, CQ ring integrated with AS, non-lossy CQ overflow backlog, per-shard CQ partitioning, 32-byte entries.
- **Endpoint IPC:** bounded server queues, scalar messages, connection delegation with rights attenuation, memory-object attachments (move/lend/copy), deferred replies, reply-time connection delegation.
- **Device capabilities:** MmioRegion and Interrupt object types, user-accessible device mappings, GICv3 SPI and x86 MSI/MSI-X routing, and IRQ-to-CQ coalesced delivery (lock-free deferred wake).
- **Userspace drivers:** reference UART, NVMe, AHCI, virtio-blk, virtio-net, and E1000E drivers use delegated MMIO, interrupts, and DMA domains. The UART path additionally validates crash-test restart with device reset and operation reconciliation.

- **Syscall dispatch:** AArch64 SVC and x86-64 SYSCALL entry use the shared typed `SyscallNumber` enum. Caller identity comes from trusted thread and trap context, never a userspace parameter. Runtime ABI 3 retains the twelve-register IPC receive envelope canonical: scalar, blocking and vector receives return the captured sender generation, signed-artifact principal and roles. Nine-register syscalls 22/27/53 are retired; checked CQ wait 88 has an explicit timed flag and retired 12/42 adapters are removed. Signed components require exact ABI matching.
- **Authorization:** the local name service hosts a default-deny policy engine. Separate roles protect policy changes and service publication. Connection issuance is attenuated and generation-fenced; an administrator can read its bounded audit stream. Policy and audit persistence, distributed replication, and hard revocation remain future work.
- **Scheduler:** RoundRobin, quantum timer, block/yield/wake, generation-qualified wakes and retirement, deferred reaper, per-LP thread pinning, certified runtime migration, and remote owner-LP abort.
- **Sitas integration:** sitas-core compiles for aarch64-none. sitas-charlotte links against the kernel's syscall ABI. Per-shard CQ rings mapped by the loader contract. ShardParker retires busy-waiting.
- **Protocol crates:** `charlotte-protocol-net`, `charlotte-protocol-msg`.
- **Networking:** smoltcp 0.13 adapter and TCP/IP service runtime-validated over the frame demultiplexer; reliable-message v3 uses 32-bit lengths with an initial 1 MiB policy ceiling. Network capability, DHCP, discovery, cluster formation, HTTP, and time synchronization launch by default when a supported NIC is discovered; with local durable storage this also starts signed-descriptor ingress, cluster administration, and the node deployment agent. Test features only add verifiers. S3 and Kafka service instances are separately provisioned because their endpoint, trust, credential, and datascope profiles are not ambient machine configuration. Opt-in AArch64 tests validate RustFS and Apache Kafka over verified TLS with required P-256 mTLS and SCRAM-SHA-256 client authentication. Its profile publishes distinct producer, consumer, and transactional access points and verifies that the producer endpoint rejects consumer and transaction operations. The Kafka test also runs the generic transactional-step service through successful output, retry, procedure timeout, and terminal-DLQ paths while keeping broker authority out of the called procedure.
- **Raft:** generic voter and learner sets, quorum accounting tested with configurations up to five voters, three-node TLA+ safety models, persistent single-voter restart, discovery-led joint-consensus admission, focused two-guest catalog/deployment fixtures, and a three-guest operational membership and ingress fixture. Fixture sizes describe validation coverage rather than an architectural limit.
- **CI:** GitHub Actions builds both architectures with `-D warnings`, QEMU boot gates on AArch64 and x86-64, plus host tests and bounded formal-model checks.

B.5 Known limitations

- **Production trust and peer security:** production images remain disabled. Signed boot-policy verification and a kernel handoff exist, but platform authentication, rollback-resistant installation and private key custody are unfinished. Development boot uses public fixture trust. Discovery/reliable-message peer routes lack cryptographic authentication; session correlation and committed Raft membership do not supply it. Time synchronization is also not an authenticated security-time source. The security ledger is 29 corrected in scope, seven partial and two open findings out of 38; see `docs/reference/security-remediation.md`.
- **External data-service compatibility:** S3 is fixture-tested with RustFS, while Dell EMC ECS namespace support is implemented but not yet qualified against an ECS installation. Kafka is limited to profile-fixed partitions. Its connector joins, synchronizes, heartbeats, leaves, and generation-fences commits with a Charlotte fixed-partition assignor; replicas for the same partition become standbys.

It routes among explicitly provisioned brokers, refreshes leaders for produce/fetch, and rediscovers moved group and transaction coordinators. It still lacks conventional/cooperative assignor interoperability, additional SASL mechanisms, client-certificate chains and key algorithms, compression, and topic administration. Its versioned, digest-checked profile is already delivered only to the broker connector as read-only launch memory; production secret injection and trust-anchor rotation remain controller work. The generic step runner, named connector/procedure grants, scoped deployment launch, and generation-fenced Kafka commits are implemented. Deployed domains also share a fixed 64-slot node registry: preparation reserves capacity and principal identity before construction, and publication consumes that exact slot without allocation. Preparing retirement remains Pending; abandonment retains the fence. Deployed domains receive a kernel-authenticated cooperative drain request and a signed, bounded grace period before forced retirement. An off-cluster operator can submit a signed, node-targeted shutdown intent to any deployment ingress member. The Raft leader verifies its trusted-UTC window and replay-fences it in replicated state; the target agent then transfers the exact envelope to an independently verifying kernel launch gate. The resulting node-shutdown request propagates to ordinary applications and then their operational connectors, with the earlier of the child and node deadlines enforced. Deployment and HTTP ingress stop admission through bounded, remotely-cancellable socket waits, while the UTC time service closes admission and unwinds a pending NTP operation through owned resources. TCP/IP closes residual sockets and retained receive replies, and the frame router cancels its single NIC receive, deferred lookups, and in-flight moved-frame calls before NIC quiescence. Lifecycle-aware boot-gate polling also lets HTTP, time, and TCP/IP acknowledge while local readiness is still pending; the coordinator records acknowledged, unacknowledged, and forced outcomes per phase. Deployment ingress/control/agent and DNS/reliable-messaging/discovery now participate in the same bounded lifecycle. The production fixture requires all eleven high-level phases to acknowledge without a forced or unacknowledged exit before device ownership transfers. A kernel-owned coordinator implements the reverse-dependency high-level service plan through object-store drain and transfers hardware-root domains exactly once to a fail-closed device-quiescence coordinator. The object store performs a final durable flush, VirtIO RNG resets before releasing shared DMA, and NVMe drains operations, flushes, masks interrupts, disables the controller, and observes `RDY=0` before the stronger acknowledgement. AHCI and VirtIO block flush and stop/reset their controllers; VirtIO net and E1000E drain transmit descriptors and stop their DMA engines. AArch64 then selects the FADT-advertised SMC/HVC conduit and boot-validates a terminal PSCI `SYSTEM_OFF`; x86-64 ACPI poweroff remains open. Kernel-owned QEMU NVMe reset now precedes first DMA grant and requester reassignment. Intel VT-d draining, AMD-Vi strict completion stores and Arm SMMUv3 ASID invalidation retain backing on rejection; the three QEMU targets exercise failed teardown, retry and reset before reassignment. x86 CPU invalidation has bounded epoch-fenced retry, including global translations, and physical stack cleanup runs in scheduled same-LP reapers. Broader device/physical-platform reset verification, recovery of abandoned owners, controller-managed instance leases, rolling replica replacement and coordinated rollback remain future work.

- **HVF does not honor hardware ASIDs.** Apple's Hypervisor.framework strips the ASID bits from `TTBR0_EL1` on read and does not use them to isolate user translations, so the kernel's ASID-based TLB fast path is unsafe there. Under `hvf_compat`, `switch_ctx` flushes the whole TLB on every context switch (`tlbi vmalle1is`) and the SVC handler attributes syscalls from a per-LP tracked logical ASID rather than a `ttbr0_el1` readback. See *AArch64 Port Status* for the full diagnosis. HVF also exposes no guest SMMU for the protected-DMA NVMe path. Its compatibility boot therefore runs 15 non-storage tests; the full 18-test suite and persistent-storage workflows require TCG.
- **x86-64 architectural limitations:** PCID/INVPCID and SMAP are not enabled; TLB shootdowns conservatively reload CR3. SMEP is enabled. VT-d multi-hop bridge scopes are rejected, and AMD-Vi fault delivery is polled until post-topology MSI setup is implemented.
- **Virtio-net runtime:** the receive/transmit data path, used-ring TX descriptor reclamation, frame de-

multiplexing, reliable messages, distributed name service and TCP/IP have QEMU TCG fixture coverage. HVF remains unsuitable for direct EL0 device MMIO. Broader hardware qualification, buffer-pool and batching optimization remain open.

- **General process loader:** the ELF loader is fixed-address for reference service images. General argv/env/auxv-style setup is not implemented.
- **Resource accounting:** memory-object backing pages and counts have generation-scoped sponsorship budgets, node-wide admission and platform progress reserves. Completion-backed timer events have separate domain/node admission and retain their charge through deferred cancellation. Endpoint records and preallocated queue backing have domain/node admission with staged-growth rollback and original generation charges retained through delegation. Shared record admission covers all six capability families (4,096 per namespace, 65,536 per node, 49,152 ordinary). General observer/control-block bytes and kernel heap accounting, and aggregate principal limits, remain incomplete. Completion records now have separate domain/node admission, retained through strong references and undelivered detached results. CQ registration and kernel-owned backing have count/byte admission, fallible staging and loader rollback. Physical ring pages remain owned by mappings and outside the CQ heap-byte counter. Endpoint-close watches have bounded one-shot entries, locally cancellable owning tokens and transactional submission rollback. Completion/CQ and endpoint-readiness/pending-call scheduler waiters have bounded generation-sponsored entries, admission before parking and owning cancellation on competing wake or reaping. Generation-owned waiter-account bundles have separate count admission; their original backing charge survives root retirement and ASID reuse through final weak/allocator release. Scheduler/completion timer-account bundles have their own backing admission with the same final-release rule, independent of event reserve grants. Completion/CQ/watch account bundles share separate backing admission through final weak/allocator release, independent of their resource budgets. Capability/IPC/mailbox accounts share admitted backing through final weak/allocator release, with original classification captured before publication. Global namespace nodes have requested-byte/count admission through actual deallocation. Individual authority-record candidates and detached nodes also retain byte/count admission through actual deallocation, independently of capability resource counts and later promotion. Mailbox endpoint nodes separately admit candidate/retained backing and keep both backing and mailbox resource charges until node deallocation, including final-root invalidation rejection and guarded abandonment. IPC/memory-close/DMA-readiness disposal nodes retain separate byte/count admission from preparation through producer-LP queued delivery and actual deallocation, independently of retained observer-list backing. Wakers and callbacks use opaque admitted strong/weak handles and borrowed notification. Actual observer Arc-layout bytes and fixed holder bundles remain charged through final weak/private-holder release. Other payload metadata and aggregate heap/principal accounting remain gaps. Completion, detached-operation and CQ registry nodes have independent requested-byte/count admission through candidates, retained backlog and actual node deallocation, separately from their record/CQ resource limits. Device namespace and MMIO/IRQ/DMA payload nodes likewise retain separate backing admission through unused preparation and confirmed retirement, with generation-captured storage class distinct from resource privileges. IOMMU domain/requester/context registry nodes have separate backing admission; unit-owned fences and contexts retain original charges beyond domain destruction. Mapping/walker and ledger backing remain gaps. Connection, retained-call and outstanding-reply records have separate domain/node count admission. Grantors sponsor direct connections; callers sponsor call/reply pairs and solicited returned connections. Reservation precedes attachment transfer, and retirement fences receive and connection publication before teardown. Timed admission failures retain the completion owner; untimed waits preserve terminal-state and borrowed-buffer safety through cooperative retry. Untimed IPC admission retries preserve pending loans; source preparation precedes attachment transfer. Kernel blocking-lock waiters now share owning admission, runnable retry on rejection and broadcast notification after release. They have test users but no production callers; fairness and owner-death recovery are not provided. Scheduler timer observers share owning admission;

internal timer callbacks occupy one embedded slot. Sleep falls back to runnable deadline waiting on rejection. Sleep/watchdog events now have separate generation-owned domain admission and share the completion-timer node pool. Fallible queue-node preparation precedes parking; insertion allocates nothing and the quantum has an inline slot independent of anonymous admission. Thread-exit subscriptions and kernel completion callbacks share owning event-watch admission; worker registration precedes execution. Callback registration checks exact operation identity. All scheduler Observable sources require fallible owning registration, including boot publication/results; no weak-only trait fallback remains. General control-block storage and broader kernel heap/capability/shared-kernel-table accounting remain unfinished. Private translation roots and intermediates now have an embedded lifetime account: 1,024 frames per domain, a node pool of one sixteenth of usable RAM and reserved platform headroom. Partial linked trees and cached empty branches remain charged until confirmed physical teardown. Trusted platform classification precedes root allocation; failed release retains the original charge. Fresh shared kernel tables have a separate one-sixty-fourth-RAM node pool; inherited boot tables remain outside it. IOMMU tables/queues use a one-thirty-second-RAM pool with domain and unit ceilings. Runtime stacks reserve their maximum user/kernel extent in a separate one-eighth-RAM pool, retaining that charge through uncertain cleanup. These independent pools do not form a complete RAM ledger. Thread context and retirement-node layouts now reserve requested bytes and bundle counts against shared principal and node/ordinary ceilings, retaining charges through actual deallocation. Table capacity, observer/weak storage and other general metadata/principal families remain open. Principal-history records and root candidates now share a separate requested-byte/count pool with reserved platform headroom. Published records remain charged for the boot lifetime; duplicate candidates refund only after confirmed root metadata disposal. Limits/usage/authority nodes also have a separate byte/count pool whose charges survive partial preparation, publication and failed invalidation. IPC namespace nodes and both budget accounts now prepare fallibly before publication guards; an exact-root lease protects post-table publication under IPC alone. Empty-node disposal leaves IPC first. Pending and reply-token nodes reserve their original counts before fallible allocation outside IPC; the complete call owner retains its exact root through preparation, publication and ordinary rollback. Detached node disposal precedes count refund. Reply/cancellation retain detached nodes; scalar completion fallback also retains notifications. Endpoint node, backing and list preparation now leave IPC with an exact-root owner; growth keeps original sponsorship, old backing and revalidation through FIFO replacement. Final closed endpoint nodes dispose post-IPC before record refund. Per-capability nodes now prepare fallibly before authority publication; installation relinks them and detached payload/authority metadata disposes post-IPC before connection-count refund. Call/endpoint shared-authority storage and payload factories now leave IPC, as does the call pending waiter list, with original roots/sponsors retained. Other guarded capability factories, mixed memory payload maps, byte/principal admission, wider contexts and pressure fairness remain open. Borrowed authority batches remove the publication vector; complete prepared scalar call commit now needs no heap allocation. Global memory-object nodes now prepare with private backing and relink at publication. Complete detached object records remain in existing backing receipts through physical completion and post-registry disposal before original charge refund. Failed release retains the record/charge behind a pre-attempt fence. Read-loan borrower nodes now prepare fallibly before source escrow and relink at commit; confirmed cleanup carries borrower and exact authority past the memory guard, freeing the borrower node before original authority admission. Memory-capability and namespace nodes now also prepare before publication; complete mixed commit relinks all payloads without heap work. Retirement carries payload/authority nodes in the existing source, loan, namespace or complete object receipt through post-guard disposal. Memory capability preparation now retains its partial payload/namespace fields and exact authority/account reference inertly before factories; ordinary finish frees storage before authority cancellation after local guards. Direct/source/copy callers and containing transfer cleanup consume it explicitly. Guarded bare fallback and late cancellation after root reuse are qualified; namespace teardown can drain hidden authority

while payload metadata retains original requested-byte/count admission: 4 MiB and 32768 nodes total, 3 MiB and 24576 ordinary, shared with namespace and read-borrower nodes. A read loan needs three temporary nodes before source escrow; its borrower charge retains the original destination classification. Admission precedes allocation and follows actual node deallocation, including unused candidates and abandoned metadata after authority teardown. These defaults use the central compile-time policy. Broader outer transfer/backing and IRQ/destructor contexts remain separate. Mapping nodes and snapshot capacity now prepare outside memory serialization, then revalidate before relink/pin publication. Existing pins/receipts retain detached records and peer leases through uncertainty. Mapping preparation's partial node/shared-snapshot fields now retain storage inertly on abandonment; ordinary constructed returns explicitly finish after local memory/table guards. Full captured namespace generation also revalidates before mapping/pin publication. Broader contexts and aggregate metadata admission remain separate. Mapping/copy/DMA snapshot buffers now share requested-byte/count limits: 4 MiB/8,192 total and 3 MiB/6,144 ordinary. Original admission moves with each buffer and refunds after deallocation; captured classification survives promotion and root reuse. Empty escrow pins allocate no buffer. Inline metadata, allocator overhead, aggregate principals and concurrent essential-progress qualification remain open. Kernel resource capacities, RAM ratios, backing limits and local source ceilings now use one typed compile-time policy. An absolute-file build profile can override related settings; consistency/arithmetic validation precedes boot. Existing numerical defaults and original-charge lifetimes remain. Chapter 20 covers configuration, coupled tuning and qualification. Boot-resource installation remains future work. Mapping nodes now also reserve requested layouts/counts before allocation: 1 MiB/8,192 total and 768 KiB/6,144 ordinary. Captured classification and original admission follow the same node through preparation, publication and detached retirement until actual deallocation. Guarded fallback retains both without counter/allocator entry; no replacement teardown node, physical proof or retry owner is introduced. Principal/heap limits and concurrent progress remain separate. Copy-pin snapshot capacity also prepares outside memory serialization, with exact-generation/source revalidation before snapshot fill and pin publication. Bare preparation/pin fallback retains its allocation; explicit snapshot disposal precedes backing-fence decrement. Automatic scoped/source-transfer destructors and aggregate principal admission remain separate qualification. DMA snapshots now share that inert preparation before either pin counter changes, with full source/direction/rights/exclusion revalidation. Bare DMA-pin fallback retains metadata; explicit snapshot free precedes counter decrement. Existing backend completion and root/capability ownership remain required, without new readiness or replay permission. Scratch namespace/extent nodes now also prepare outside local guards, while MMIO retains its existing root/claim and rechecks mapped-state admission atomically. Complete scratch nodes stay in the final root receipt through invalidation, then dispose post-guard before root backing. Scratch layouts now reserve requested bytes/counts before allocation: 512 KiB/8,192 total and 384 KiB/6,144 ordinary nodes. Candidates and retained metadata keep their original charge until actual node free; captured classification survives promotion and ASID reuse. Scalar scratch identity, broader factories/destructors, aggregate principal metadata, allocator overhead and pressure progress remain open.

- **Cross-machine Raft boundary:** two TCG guests share a private QEMU LAN (stream backend on AArch64, socket backend on x86-64); the reliable-message frame transport and remote Raft peer routing are connected during ordinary networked boots; `-dns-test` adds the cross-node validation workload and pass/fail result.
- **Observability HTTP:** the httpd keyhole aggregates the `observe` snapshot and per-service status into a JSON report served over the TCP/IP service during ordinary boots. Its `/cluster` view renders a bounded, versioned snapshot of fresh applied Raft posture, capacity, placement/readiness, and DSR projection; an unnamed platform-service VIP can make it location-independent while identifying leader and serving node separately. Both views require an enrolled reader or administrator certificate over TLS on port 443; deployment TLS on port 7444 requires an administrator before mutation dispatch. One signed, encrypted boot resource supplies credentials, roles and adjustable TLS limits

to both services; missing credentials disable network admission. The management provider shares erasing incremental SHA-256/HMAC owners for keyed state and transcript forks, including unfinished Drop. Rustls output/key copies, connector-client state, forced termination and physical erasure remain separate SEC-15 boundaries. Status and deployment rotate four owned client positions across CQ-bound setup, TLS/header input, output and logical close. Status input keeps its original five-second deadline; responses retain at most 512 KiB and use the existing five-second output budget. Shutdown drains all client phases through consuming logical close. Snapshot collection/rendering remains synchronous; full-pool flood fairness is not established. Deployment ingress cancels incomplete input during shutdown, continues accepted controller/output work under original budgets, and requires all five client phases empty before acknowledgement. The signed ARM shutdown fixture checks held idle TLS clients and cooperative retirement; stalled controller/output and receiver-held cleanup remain separate. `-http-test` provisions disposable development credentials, adds QEMU forwarding and validates verified HTTPS. Protected enrollment, native rotation/failover and wider pressure qualification remain open; SEC-10 is partial. See Chapter 20.

- **IOMMU/SMMU integration:** coherent Arm SMMUv3 discovery via ACPI IORT, Intel VT-d via DMAR, and AMD-Vi via IVRS provide per-requester DMA-domain capabilities, memory pinning, IOVA map/unmap, synchronous invalidation, rollback, fault handling, and teardown. Storage and network drivers are QEMU-tested through these backends. Non-coherent SMMUv3, ATS/PRI, multiple-IOMMU topologies, VT-d multi-hop bridge scopes, and AMD-Vi MSI fault delivery remain incomplete.
- **Upgrade:** the EL0 service manager performs handoff and invokes the capability-checked replacement spawn path. It can fetch a replacement ELF from a well-known NVMe object, pass it as a memory capability, and fall back to the embedded recovery image. Structural ELF validation, immutable kernel snapshotting, and Ed25519 CLS2 signature and logical-name checks are implemented. Rollback and key rotation policy, multiple state objects in the reference manager, and manager-owned teardown remain future work.
- **Resource bounds:** endpoint queues, rings and CQ overflow retention have family admission limits; physical ring mappings keep their own backing owners. General heap and aggregate principal limits remain incomplete. The generic IPI queue has no reserved mandatory slots: legacy force-push may evict an older entry. Current x86 synchronous shootdown instead uses its checked epoch channel.

C Lessons Learned

Booting the asynchronous kernel under QEMU exposed integration faults that unit tests and static checks had missed. This appendix records the most instructive ones.

C.1 Bugs found on hardware

C.1.1 Panic handler recursed through heap-dependent logging

Symptom: any fault during early boot silently triple-faulted instead of printing a panic message. **Root cause:** the panic handler used the normal logging path, which allocated from the kernel heap. A fault before the heap was ready caused the panic handler to fault, re-entering itself, recursing until stack overflow and triple fault. **Fix:** the panic handler now uses `early_logln!` (direct serial writes, no heap dependency). This unmasked every subsequent bug.

C.1.2 Blocked threads lost their execution context

Symptom: a thread that blocked in `wait()` restarted from its entry point when woken. **Root cause:** `block_thread` cleared the scheduler's `current_handle` before `yield_lp` saved the thread's context, so the save was skipped. **Fix:** a self-blocking thread stays `current_handle` until the yield saves its context.

C.1.3 RwLock held-across-call deadlocks

Symptom: `sleep()` worked with logging but hung without it (a heisenbug). **Root cause:** an `if let` binding extended an RwLock read guard's lifetime across a call that tried to acquire the write lock. **Fix:** bind the value out of the scrutinee first, so the temporary guard drops before the re-locking call.

C.1.4 Quantum timer grew without bound

Symptom: the per-LP timer queue contained thousands of quantum events after extended operation. **Root cause:** manual yields enqueued a new quantum event each time. **Fix:** an `armed` flag keeps exactly one quantum event in flight.

C.1.5 A thread cannot free its own kernel stack

Symptom: a returning kernel thread hung during teardown. **Root cause:** `ThreadContext::Drop` deallocated the stack while the thread was still executing on it. **Fix:** a deferred reaper moves dead threads to a zombie list and drops them from the next thread's context after the switch.

C.1.6 LA57 paging-mode mismatch

Symptom: a `#GP` with a non-canonical address on x86-64. **Root cause:** the address width was derived from CPUID (57-bit capability) instead of `CR4.LA57` (the active mode, 48-bit under Limine). **Fix:** derive from the active paging mode.

C.1.7 ASID-0 collision

Symptom: the first user thread faulted at its entry point. **Root cause:** the first user address space received ASID 0, which equals `KERNEL_ASID`, so the thread was created as a kernel thread (EL1), where PXN forbade execution of user code. **Fix:** pre-populate the table with the kernel AS at index 0.

C.1.8 x86-64 trampoline halted on thread return

Symptom: the async demo's worker completed but the coordinator never resumed. **Root cause:** the x86-64 trampoline entered a `hlt` loop when a thread returned, instead of calling `abort()`. **Fix:** make the x86-64 trampoline call `abort` on return.

C.1.9 Hypervisors that strip TTBR0 ASIDs break TLB isolation

Symptom: under Apple's Hypervisor.framework, EL0 tests failed with apparently unrelated data aborts, wrong syscall results, and deadline panics; TCG remained green. **Root cause:** HVF did not preserve the ASID bits in `TTBR0_EL1`. Because context switches relied on those tags instead of a full TLB flush, low user virtual addresses could resolve through another domain's stale translation. **Fix:** `hvf_compat` performs a whole-TLB flush on each context switch and obtains syscall identity from trusted per-LP state. **Lesson:** revalidate translation-tag assumptions on every hypervisor. See *AArch64 Port Status* for the detailed diagnosis.

C.2 Engineering lessons

1. **Test transitions as well as interfaces.** The difficult failures occurred where block, yield, wake, context save, and reclamation met. Tests must cross those boundaries.
2. **Keep failure paths independent.** Panic reporting must work before the heap and scheduler; reclamation must run from a live stack.
3. **Validate platform assumptions at runtime.** CPU capability does not imply active paging mode, and a hypervisor may not preserve hardware translation tags.
4. **Treat lock lifetime as part of control flow.** Bind values out of guards before calling code that may acquire the same lock.

D Research Lineages and Their Afterlives

The systems cited throughout this manual did not share one fate. Some remain active, some became products or standards, some were absorbed into a larger platform, and some ended after demonstrating one useful mechanism. This appendix separates those outcomes from CharlotteOS' own inheritance.

A research operating system need not replace Unix or Windows to matter. Its usual afterlife is selective: a fast IPC path, an authority model, a queue discipline, or a deployment abstraction survives at a different layer while the original system and its stronger unifying thesis disappear. Conversely, the adoption of one mechanism does not validate every claim made by the original architecture.

D.1 Capability kernels and confined Unix

KeyKOS, EROS, and CapROS. KeyKOS was a commercial capability system; EROS carried its object-capability and persistence ideas into research, and CapROS continues EROS as a small open-source project. They did not displace conventional operating systems, but their account of authority (possession, delegation, attenuation, confinement, and persistence as properties of references rather than global names) remains foundational. The CapROS project explicitly identifies itself as the continuation of EROS (https://www.capros.org/).

L4 and seL4. This lineage achieved both assimilation and independent survival. Earlier L4 variants demonstrated that microkernel IPC could be fast and shipped commercially in mobile devices. seL4 added machine-checked functional correctness and security properties, became open source in 2014, and acquired a foundation and commercial high-assurance ecosystem in 2020. The project's history records research prototypes, the HACMS deployment, proof milestones, and the later ecosystem (https://sel4.systems/About/history.html).

Capsicum and CHERI. Capability mechanisms also entered conventional systems in narrower forms. Capsicum has shipped in FreeBSD since version 9.0 and treats file descriptors as attenuable capabilities inside Unix (https://man.freebsd.org/cgi/man.cgi?query=capsicum&sektion=4). CHERI moved bounds and permissions into tagged pointers and processor support. Arm's Morello board and CheriBSD established a substantial experimental stack, while CHERI-RISC-V work continues toward standardization (https://www.cl.cam.ac.uk/research/security/ctsrd/cheri/). These are complementary outcomes: Capsicum confines named Unix resources and CHERI constrains memory references; neither is by itself a complete object-capability operating system.

D.1.1 CharlotteOS inheritance

CharlotteOS adopts the strong local authority rule: an opaque, typed object capability is authority, may carry attenuated rights, and is not a name, notification, completion, or unit of work. Reply tokens are linear authority; memory, device, DMA, observer, and bootstrap access are explicitly delegated. The present kernel does *not* retain a general derivation tree, prove confinement, or provide CHERI-style protection for arbitrary pointers. This is an object model inspired by EROS and seL4. It provides neither an seL4 refinement nor a substitute for CHERI.

D.2 IPC, typed channels, and ownership

Mach. Pure Mach did not become the dominant Unix organization, but it was absorbed into Apple XNU. XNU retains Mach tasks, virtual memory, ports, and IPC while co-locating BSD, networking, filesystems, and I/O components in one kernel for performance. Apple's description is candid about this hybrid outcome (Apple's XNU architecture note). The lesson is double-edged: message-mediated authority survived, while the pure user-server decomposition did not.

Singularity. Microsoft ended the standalone research OS and evolved its design into the internal Midori project. Midori never became a commercial OS, although Microsoft reports that it ran part of the company's natural language search service (https://www.microsoft.com/en-us/research/project/singularity/). Typed channel contracts, software-isolated processes, manifest-checked components, and ownership transfer through an exchange heap outlived the platform as research ideas. Managed-language enforcement did not become a mainstream OS boundary, but ownership types and message-oriented runtimes became normal engineering tools.

Xous. Xous is a working Rust microkernel for embedded devices. Its userspace servers and distinct scalar, send, lend, and mutable-lend messages make it CharlotteOS' closest direct IPC ancestor (https://xous.dev/kernel/).

D.2.1 CharlotteOS inheritance

CharlotteOS takes Xous's isolated-server model and its separation of scalar from memory-bearing IPC. It takes Singularity's ownership-moving discipline but enforces it through capabilities, page mappings, tear-down state machines, and DMA rules rather than a managed-language verifier. Copy, move, read-only borrow, and writable borrow have explicit failure, cancellation, restoration, and rollback behavior. Typed protocol crates provide channel contracts above an ABI that still validates untyped words at the kernel boundary.

D.3 Multicore systems, runtimes, and fast I/O

Barrelfish and Arrakis. Barrelfish argued that a multicore machine should be treated as a distributed system with explicit messages and topology-aware state placement. The project now identifies itself as inactive (https://barrelfish.org/download.html). Arrakis gave applications virtualized device queues while leaving allocation and protection policy in the kernel; it merged back into Barrelfish in 2015. The code line ended, but per-core runtimes, hardware queue virtualization, and control/data-plane separation became widespread design patterns.

IX, DPDK, and Seastar. IX was a research dataplane OS. Its run-to-completion, per-core, batched approach continued in datacenter runtimes. DPDK succeeded by becoming a Linux Foundation userspace packet-processing project with production device support (https://www.dpdk.org/about/). Seastar remains an active shared-nothing, shard-per-core, futures runtime used by ScyllaDB (https://seastar.io/). In this family, the ideas prospered as libraries and queues on Linux more than as replacement operating systems.

Windows completion ports, BSD `kqueue`, Linux `epoll`, and Linux `io_uring` show the same selective adoption. Submission, retained completion, aggregation, and batching became normal interfaces without making notification, readiness, completion, IPC, and authority one thing.

D.3.1 CharlotteOS inheritance

Sitas is the direct shard execution discipline and is Seastar-like: one owner per shard, cooperative futures, bounded messages, and deliberate placement. Barrelfish supplies the analogy for explicit cross-LP coordination. IX, DPDK, and Arrakis inform userspace drivers, batched queues, IOMMU protection, and buffer ownership. CharlotteOS makes a different authority choice from Arrakis: devices are delegated to isolated driver services, rather than directly to ordinary applications. Completion queues retain terminal operation records and remain separate from endpoint IPC and Rust `Wakers`.

D.4 Service recovery

MINIX 3, CuriOS, and Pebble explored minimally privileged userspace services, drivers, supervision, and restart. Nooks and SafeDrive instead tried to contain faulty extensions while preserving compatibility with in-kernel drivers. MINIX remains a research and teaching system; the other projects are completed prototypes. Their broad result is now conventional: isolate components and supervise them. Their harder problem did not disappear: hardware, DMA, persistent state, and externally visible effects prevent arbitrary restart from being transparent.

CharlotteOS adopts the strong containment boundary and the honest recovery contract. The supervisor can revoke capabilities and borrows, reset a device, reconcile operations and DMA, start a fresh generation, and require clients to resolve it again. A stateful upgrade transfers explicitly serialized state; it does not inherit a process image or promise uninterrupted execution. This is closer to MINIX's supervision goal than to transparent recovery.

D.5 From distributed operating systems to cluster managers

Amoeba. Amoeba's last official release was 5.3 in 1996. Its processor pools, capability-protected objects, location-independent RPC, and FLIP network did not become a maintained product platform (https://www.cs.vu.nl/pub/amoeba/manuals/usr.pdf). The component ideas did become ordinary: pooled compute, object references, RPC, directories, and replicated services. The part modern systems mostly rejected was the promise that a distributed computer should look like one failure-free machine.

Plan 9 and Inferno. Bell Labs development ended, but Plan 9 has community descendants. Its 9P protocol remains in Linux, including a Virtio transport (https://www.kernel.org/doc/html/latest/filesystems/9p.html). Per-process namespaces and protocol-served resources stayed influential while Plan 9 and Inferno themselves remained niche.

Jini and MOSIX. Sun's Jini became Apache River; Apache retired River in 2022 (https://attic.apache.org/projects/river.html). The openMosix project officially ended in 2008 (https://sourceforge.net/p/openmosix/news/2008/02/openmosix-project-ends/). Discovery, leases, tuple spaces, automatic placement, and migration were not lost. They reappeared in registries, brokers, serverless platforms, and cluster schedulers. Modern systems usually reschedule a container or actor and reconstruct service state instead of migrating an arbitrary process image.

Borg, Omega, and Kubernetes. Borg remains Google's internal production cluster manager; Omega explored a concurrent control plane; and Kubernetes directly inherited their lessons about declarative desired state, scheduling, services, labels, and self-healing. Google's own account describes that lineage (https://kubernetes.io/blog/2015/04/borg-predecessor-to-kubernetes/). The

cluster became the deployment target, but above commodity kernels and containers rather than inside a distributed OS kernel.

Focused mechanisms. Raft succeeded as a reusable replicated-state- machine protocol with many implementations (https://raft.github.io/). SWIM-style gossip survived in memberlist and Consul. Nix made hash-identified immutable software stores practical. TUF and Uptane became maintained update security frameworks; Uptane is now a versioned standard under Linux Foundation governance (https://uptane.org/learn-more/about). In-toto, Sigstore, Cosign, and Notary brought supply-chain provenance and signed artifact identity into cloud deployment workflows.

D.5.1 Clean-break and compatibility counterpoints

Solaris MC extended Unix into a multi-computer single-system image while preserving the Solaris ABI (https://www.usenix.org/conference/usenix-1996-annual-technical-conference/solaris-mc-multi-computer-os). LegoOS reopened the operating-system boundary for disaggregated processor, memory, and storage components, while deliberately retaining common Linux system calls to ease adoption (https://www.usenix.org/conference/osdi18/presentation/shan). These systems make useful counterpoints to CharlotteOS. They move the operating system across hardware boundaries while preserving a machine-compatible application contract. CharlotteOS instead tests a smaller native contract of signed execution objects, messages, and explicit capabilities.

The comparison sharpens the research question. Compatibility is valuable because existing software, libraries, and operational knowledge are valuable. A clean-break system must demonstrate that its shorter policy and execution path compensates for the cost of adapting applications.

D.6 Cluster-native placement, ingress, and lifecycle

D.6.1 Desired state and replica placement

Borg, Omega, and Kubernetes established the modern control-plane pattern: declare desired state, schedule from constraints, observe actual state, and reconcile the difference. Kubernetes describes its controllers directly as control loops (https://kubernetes.io/docs/concepts/architecture/controller/). Ceph's CRUSH algorithm provides a related precedent for deriving deterministic placement from a compact topology and failure-domain map rather than storing one decision per object.

CharlotteOS now applies these ideas to native protected domains. Its `dns` catalog is a Raft state machine that commits membership, signed releases, replica policy, concrete assignments, deployment generations, operational bindings, shutdown intent, and per-node readiness. The leader resolves singleton, fixed-replica, and every-eligible-node policy against admitted, non-draining voters. Affinity and anti-affinity relate components, and node agents reconcile every assigned deployment.

Placement is also an authority decision. A selected node must publish readiness for the exact committed generation before the service can receive grants or new cluster-addressed flows. Capacity, trust labels, named failure domains, health-driven replacement, and rolling availability policy remain the next scheduler work.

D.6.2 Cluster service identity and Direct Server Return

Distributed object systems established location-independent service names. Modern software load balancers use deterministic connection mapping and retained flow state to limit disruption when backend sets change. Maglev is a production-scale example (https://www.usenix.org/system/files/conference/nsdi16/nsdi16-paper-eisenbud.pdf).

CharlotteOS derives its DSR backend set directly from Raft membership, committed application placement, exact-generation readiness, and drain intent. The frame router consumes an immutable epoch and applies rendezvous hashing to each five-tuple. A remote backend receives the original packet through one L2 envelope, owns the TCP connection, and replies directly. The VIP advertiser, execution owner, and public service identity may therefore be different.

The present implementation supports a bounded IPv4/TCP configuration and an administratively trusted cluster L2. Multiple services, hostile-fabric authentication, larger membership, and sustained churn remain experiments. The distinctive question is whether packet eligibility can remain a direct, inspectable consequence of application placement and lifecycle.

D.6.3 Remote calls and explicit failure

CharlotteOS retains Amoeba's common service model and accepts the critique in Waldo et al.'s *A Note on Distributed Computing*. Relmsg v3 carries 32-bit lengths, fragmentation, request and session identity, bounded duplicate handling, retries, and deadlines. Distributed calls include the target generation and can report an uncertain result. They do not promise that a network call has local latency, synchronous revocation, or a knowable outcome after reply loss. General cryptographic bearer capabilities, transitive distributed revocation, and durable exactly-once execution remain open.

Lifecycle uses the same generation discipline. Exact readiness gates publication and ingress; committed drain removes a node from new work; a signed grace period bounds cooperative service shutdown; and forced retirement closes the domain after the deadline. Stateful cross-node movement still needs an explicit, failure-safe transfer of mutable ownership.

D.7 Operational trust and managed-service authority

D.7.1 Software supply chain and role separation

TUF separates update roles, versions, thresholds, and expiry (https://theupdateframework.github.io/specification/v1.0.28/). In-toto binds artifacts to verifiable supply-chain steps (https://www.usenix.org/conference/usenixsecurity19/presentation/torres-arias). RFC 9180 defines Hybrid Public Key Encryption (https://www.rfc-editor.org/info/rfc9180/). CharlotteOS composes those ideas into a runtime-authority path:

- development signs executable behavior and release descriptors;
- operations independently signs an HPKE-encrypted Kafka or S3 profile bound to one cluster, release, connector, sequence, and expiry;
- the leader verifies both authorities against trusted UTC and commits only compact references and replay fences; and

- the selected node retrieves the ciphertext, after which the kernel re-verifies it, decrypts into transient zeroizing memory, and moves a read-only profile capability into the connector.

This gives the two organizational roles different powers. Development cannot select production credentials. Operations cannot replace the approved executable through a connector binding. Production KMS/HSM custody, measured boot or attestation, rotation, recovery, audit, and readiness-driven connector replacement remain necessary.

D.7.2 Connector-confined managed services

SPIFFE addresses a neighbouring problem by delivering platform-selected, short-lived identities through a privileged workload API (https://spiffe.io/docs/latest/spiffe-specs/spiffe_workload_api/). CharlotteOS often keeps the external identity one step farther away: Kafka and S3 credentials remain in a connector, while an application receives an attenuated endpoint for named routes, prefixes, or operations. Independently named connectors allow several roles and destinations. The Kafka-step service owns the transaction and invokes a business procedure that never receives the Kafka credential or delivery token.

The connector can consequently act as an authority firewall and an operations- owned integration point. Its value should be measured through credential exposure, policy review effort, reuse, revocation latency, failure isolation, and the effect of connector compromise.

D.8 AI-assisted adaptation and the POSIX question

Clean-break systems historically faced a severe software-adoption cost. That explains why LegoOS retained a Linux ABI and why capability systems such as Capsicum add confinement within Unix. Coding agents change this constraint by reducing some of the human work required to discover assumptions, translate APIs, generate adapters, and build tests. They do not make generated code correct by origin.

Recent migration benchmarks show both promise and substantial failure. The 2025 CODEMENV study evaluates package and environment adaptation (https://arxiv.org/abs/2506.00894); FreshBrew evaluates project-level Java migration and emphasizes semantic preservation under strong tests (https://arxiv.org/abs/2510.04852). These results make compatibility cost an empirical question, while reinforcing the need for conformance tests, review, reproducible generation, and provenance.

Durga provides a constrained CharlotteOS experiment. A BPMN process model and developer-owned procedure generate the Charlotte adapter, capability requirements, resource declarations, build inputs, replica and affinity policy, and deployment metadata. Platform mechanics remain in generated code; the business rule remains testable on a conventional host. The research test is whether this reduces adaptation cost without hiding authority, lifecycle, or failure semantics.

D.8.1 CharlotteOS inheritance

CharlotteOS separates a human-readable name from the connection capability returned by policy-controlled lookup. Its replicated catalog and relmsg path carry request identity, generation fencing, duplicate handling, deadlines, and explicit uncertain outcomes. Signed releases drive deterministic replica placement; exact-generation readiness gates publication and DSR; and assigned agents retrieve digest-pinned artifacts from

central S3. Applications obtain signed, attenuated grants, while independently authorized connector profiles retain infrastructure details and credentials.

The result is Amoeba-like in invocation, Borg/Kubernetes-like in desired-state control, Maglev/CRUSH-like in stable deterministic placement, and TUF/in-toto-like in trust decomposition. CharlotteOS applies those ideas directly to native capability-constrained execution objects. Its bounded implementation does not yet establish production scale, general distributed revocation, stateful migration, automatic health recovery, complete trust lifecycle, or production administration.

D.9 The synthesis and the rejected inheritances

Relationship	Source ideas	CharlotteOS status
Direct source	Xous IPC and memory messages; Sitas shard ownership and async execution	Implemented locally, combined with CharlotteOS capabilities, memory objects, completion queues, and teardown semantics
Adopted and changed	EROS/seL4 authority; Singularity ownership transfer; Barrelfish messages; MINIX recovery; completion-ring I/O	Implemented in bounded local forms; no compatibility or refinement claim
Focused protocol	Raft replication; rendezvous placement; Ed25519/SHA-256 verification; RFC 9180 HPKE	Implemented and tested in bounded forms across catalog replication, replica placement, DSR ingress, and role-separated connector launch
Architectural influence	Amoeba invocation; IX/DPDK/Arrakis fast paths; Borg/Kubernetes reconciliation; Maglev/CRUSH placement; Nix/TUF/Uptane/in-toto trust; SPIFFE identity	Implemented cluster foundations with production-scale policy, recovery, and trust lifecycle still open
Rejected or narrowed	Failure-transparent remote calls; arbitrary process migration; language-only isolation; direct device access by ordinary apps	Remote uncertainty is visible; migration is protocol-specific; MMU/IOMMU and capabilities enforce isolation; drivers retain device authority

E Architectural Redirections

This appendix documents a design research process, recording decisions that redirected earlier experiments from an initial "universal completion-capability" model to the three-primitive architecture that eventually became reality. The earlier chapters describe the resulting implementation.

E.1 Retained mechanisms

The following early mechanisms remain part of the architecture:

- AArch64 EL0/SVC path.
- Caller identity derived from the current trap/thread context.
- Per-address-space capability tables.
- Shared CQ ring.
- Non-lossy kernel CQ backlog.
- `checked CQ wait` blocking through scheduler/observer machinery.
- Bounded queues and explicit `WouldBlock`.
- No-std Sitas split and CharlotteOS backend.
- Per-shard executor model.
- Typed in-kernel `ShardMailbox<M>`.
- Closure-based `ShardLocal<T>` with restricted use.
- Segment-aware ELF loading.
- QEMU boot CI across AArch64 and x86-64.

E.2 What to reframe

These components are correct but their *role* in the architecture has shifted:

- **Completion capability work** belongs to the operation completion subsystem. Use completion queues for kernel and device operations; use endpoints for cross-domain service calls.
- **Observer/waker code** handles internal scheduling. A Waker is a hint to repoll a future; it is not a completion record.
- **IPI queue closures** remain a temporary mechanism for kernel work. Use typed mailboxes or closed kernel enums for subsystem-specific work.
- **The earlier mailbox syscall ABI** is a smoke-test interface only. The stable ABI is endpoint IPC.

E.3 Replacements adopted

E.3.1 Stop expanding raw mailbox syscalls

A mailbox tied directly to LP identity is not a complete userspace service abstraction: it exposes placement where authority should be exposed, lacks protocol identity, conflates shard transport with domain IPC, and lacks move/lend semantics. Endpoint and connection capabilities are therefore independent of LP identity. Clients address the service connection without choosing a target LP.

E.3.2 Do not allocate one completion capability per service request

For userspace service calls, the natural object is a reply token. For high-rate kernel operations, per-operation capabilities create unnecessary table pressure. The design uses reply tokens for endpoint calls; operation IDs plus CQ entries for ordinary kernel operations; first-class operation capabilities only where independent authority is required.

E.3.3 Separate readiness, notification, and completion

Their contracts differ: readiness means progress may be possible; notification means inspect state; completion means an operation changed state and has result data. Keep one aggregated wait mechanism, but define distinct object semantics.

E.3.4 Replace arbitrary cross-LP closures

Boxed `FnOnce()` work transported through the IPI layer is hard to account, difficult to inspect, and brittle under backpressure. The preferred direction is closed kernel enums for mandatory kernel RPCs and typed mailbox instances for subsystem-specific work.

E.3.5 Do not equate shard wake with IPI delivery

Remote wake mapping directly to `send_ipi(target_lp)` can generate excessive interrupts. The implemented rule is to queue first, mark pending, and send a coalesced reschedule IPI only when the target cannot otherwise observe the transition.

E.3.6 Introduce memory objects before rich IPC payloads

Move/lend semantics require durable object identity rather than transient pointers. CharlotteOS introduced memory-object capabilities, mapping, ownership transfer, temporary lending, lifecycle revocation, and DMA integration before promoting rich IPC payloads.

E.3.7 Treat service discovery as userspace policy

String-based lookup remains outside the kernel. The userspace name service receives bootstrap authority and delegates connection capabilities.