Public

No environment

Avocado

GET User Create

{{SCHEME}}://{{DOMAIN}}/api/user/create

Create an anonymous user

HEADERS

x-avocado-version

1.0

Client-ID

 $\{\{CLIENT_ID\}\}$

Example Request

```
User Create

curl --request GET \
   --url '{{SCHEME}}://{{DOMAIN}}/api/user/create' \
   --header 'Client-ID: {{CLIENT_ID}}' \
   --header 'x-avocado-version: 1.0'
```

Example Response

200 OK

```
{
  "token": "some_opque_token",
  "account_level": 0,
  "id": 0
}
```

GET User

```
{{SCHEME}}://{{DOMAIN}}/api/user
```

Get user info

HEADERS

x-avocado-version

1.0

Client-ID

{{CLIENT_ID}}

Example Request

```
Curl --request GET \
    --url '{{SCHEME}}://{{DOMAIN}}/api/user' \
    --header 'Client-ID: {{CLIENT_ID}}' \
    --header 'x-avocado-version: 1.0'
```

GET Podcast Favorites

```
{{SCHEME}}://{{DOMAIN}}/api/podcasts/favorites?limit=20&offset=0
```

Get user favorited podcasts

HEADERS

x-avocado-version

1.0

Client-ID

 $\{\{CLIENT_ID\}\}$

PARAMS

limit

20

offset

n

Example Request

```
Podcast Favorites

curl --request GET \
    --url '{{SCHEME}}://{{DOMAIN}}/api/podcasts/favorites?limit=20' \
    --header 'Client-ID: {{CLIENT_ID}}' \
    --header 'x-avocado-version: 1.0'
```

Example Response

```
200 OK
```

GET Podcast Recents

{{SCHEME}}://{{DOMAIN}}/api/podcasts/recents?limit=20&offset=0

Get user recent podcasts

HEADERS

x-avocado-version

1.0

PARAMS

limit

20

offset

U

Example Request

Podcast Recents

```
curl --request GET \
    --url '{{SCHEME}}://{{DOMAIN}}/api/podcasts/recents?limit=20' \
    --header 'x-avocado-version: 1.0'
```

Example Response

GET Podcast Popular

```
{{SCHEME}}://{{DOMAIN}}/api/podcasts/popular?limit=50&offset=0
```

Get popular podcasts

HEADERS

x-avocado-version

1.0

PARAMS

limit

50

offset

0

Example Request

```
Podcast Popular

curl --request GET \
    --url '{{SCHEME}}://{{DOMAIN}}/api/podcasts/popular?limit=50' \
    --header 'x-avocado-version: 1.0'
```

Example Response

```
200 OK

[
    "id": 3,
    "title": "Coffee Break French",
    "image": "https://is4-ssl.mzstatic.com/image/thumb/Music128/v4/b9/e3/bb/b9e3bb5d-1
    "description": "Learn French in coffee-break lessons from the Radio Lingua Network
    "plays": 0,
    "unplayed_episodes": 0
},
    /
}
```

GET Podcasts

```
{{SCHEME}}://{{DOMAIN}}/api/podcasts?id=3&id=4
```

Get podcasts by ids

Fields:

- ullet unplayed_episodes is only populated on the favorites endpoint response
- episodes is only populated on the root podcasts endpoint response

HEADERS

x-avocado-version

1.0

PARAMS

id

3

Avocado relative podcast IDs

id

4

Example Request

```
Podcasts

curl --request GET \
   --url '{{SCHEME}}://{{DOMAIN}}/api/podcasts?id=3,4' \
   --header 'x-avocado-version: 1.0'
```

Example Response

GET Podcast Episodes

Get episodes for a podcast
HEADERS
x-avocado-version
1.0
PARAMS
podcast_id
3
Podcast ID
offset
0
Result offset
limit
10
Result limit
order
descending
Ascending or descending (default)
episode_id
1

Episode ID (optional)

Example Request

```
Podcast Episodes

curl --request GET \
    --url '{{SCHEME}}://{{DOMAIN}}/api/podcasts/episodes?podcast_id=3&offset=0&limit=10&
    --header 'x-avocado-version: 1.0'
```

Example Response

```
[

[

"id": 1,

"podcast_id": 3,

"episode_id": 1,

"title": "French Fries",

"description": "Learn French and eat food.",

"plays": 0,

"progress": 0,

"position": 0
```