

readgeometry

July 16, 2001
13:05

Contents

1 External Geometry Interface

This program reads a geometry specification from an external file, and transforms it into the form required by DEGAS 2. Namely, the hierarchy of geometry-related objects in DEGAS 2 is, from the lowest level to the highest level is:

1. surface,
2. cell,
3. polygon,
4. zone.

Individual cells are composed of surfaces, as discussed in the documentation for the internal geometry (e.g., see *geometry.web*). The next level up is a polygon. The code automatically breaks up (non-convex) polygons into cells. Finally, a zone may consist of one or more polygons; properties are constant across a zone. For example, a single zone might be used to represent the vacuum region around the plasma which is comprised of several (possibly disconnected) polygons. Or, a plasma flux surface on which density and temperature are constant might be a single zone. Note that polygons are used only within external interfaces such as this code. Cells and surfaces are essentially used only by the code itself. Zones are used primarily for the specification of input and output data.

The interfaces between the plasma (or vacuum) and a solid surface (or exit) are represented by sectors, which are established for diagnostic purposes. In general, a sector is defined by a surface and a zone. This code makes an attempt to identify and label these sectors automatically.

Note first that the input files for `readgeometry` are not listed in `degas2.in`. Although this might be viewed as an omission, it is consistent in that `readgeometry` is, in principle, one of many different means of generating DEGAS 2 geometries and, thus, is not as fundamental as the other entries in `degas2.in`. At present, the only alternative approach is `boxgen`, but other options may soon be available.

Instead, the command line for the execution of `readgeometry` specifies the name of the main `readgeometry` input file. This file will contain a pointer to the second file which will provide externally generated, detailed information about the geometry. Presently, this file can be one of:

1. An input file for the original DEGAS code,
2. A geometry and plasma description (in a specific format) taken from UEDGE,
3. A `.elements` file of the sort generated by SONNET.

The details of these files will eventually be described elsewhere (e.g., in the DEGAS manual). Here, we describe the shorter, first file which provides the additional information required to transform the externally generated geometry data into a consistent DEGAS 2 geometry specification.

Because the UEDGE and SONNET geometries are relatively specific, the additional assumptions required to complete the DEGAS 2 geometry can mostly be hardwired into the **readgeometry** code. In this case, the main **readgeometry** input file is very simple.

However, the flexibility of the old DEGAS code makes it difficult to set up a generally applicable means of converting the geometry into DEGAS 2 form. Most of the keywords in the main **readgeometry** input file are concerned with manipulating the DEGAS geometry data.

Each line in the **readgeometry** input file is of the form:

keyword *arguments*

Some keywords have no arguments, however.

Here are the possible keywords and their arguments; keywords will be bold-faced, arguments will be italicized. The **symmetry** and one of the three keywords following it in the first list below must appear at the top of the **readgeometry** input file. As in the other DEGAS 2 input files, lines beginning with a # sign in column 1 are ignored (comments) as are blank lines.

symmetry *sym* describes the symmetry of the geometry with *sym* = **plane** or **cylindrical** (“toroidal symmetry”). This must be the first keyword in the file.

degasfile *filename* provides the name of a DEGAS input file.

uedgefile *filename* provides the name of a UEDGE-generated geometry / plasma file.

sonnetfile *filename* provides the name of a SONNET **.elements** file.

The keywords which apply only in the **degasfile** case are:

minx *min* tells the code to exclude grid indices for which the **gridx** value is less than *min*.

minz *min* tells the code to exclude grid indices for which the **gridz** value is less than *min*.

mindensity *min* excludes grid indices which corresponding to cells with plasma density less than the *min*.

grid *j1 j2 j3 j4 sense* is used to transform the DEGAS **gridx** and **gridz** arrays into DEGAS 2 zones using the following guidelines:

1. The vertical boundary (or horizontal zone, i.e., the first index of **gridx** and **gridz**) limits are *j1* and *j2*. The horizontal boundary (or vertical zone, the second index) limits are *j3* and *j4*.
2. For each pair of integer coordinates in this implied list, a separate DEGAS 2 zone of type **plasma** will be generated. Note that this includes points at [*j2*] + 1 and [*j4*] + 1 (hence, these integers would be more properly associated with DEGAS’s zone indices).
3. Zones can be excluded from this list by using **minx**, **minz**, or **mindensity** keywords in this input file. The code will also ignore zones in which the DEGAS arrays **kzone1** or **kzone2** are less than or equal to zero.

4. **sense** is optional. Allowed values are **sense** = 1 (default) and 2. A value of 1 indicates that a clockwise trip around a single cell requires incrementing the first index of **gridx** and **gridz** initially, then incrementing the second index to get the third point, etc. Likewise, a value of 2 implies that the index must be incremented first to make this clockwise trip.

new_zone **type** starts a new zone; **type** is a string that indicates the type of the zone. It can be **plasma**, **vacuum** or **solid**.

new_polygon starts a new polygon which will be added to the zone begun by the last **new_zone** keyword. This line should be followed by one or more lines which specify the polygon coordinates.

wall wall start stop direction takes points from wall number **wall** of the DEGAS **xwall** and **zwall** arrays and adds them to the current polygon.

1. **start** and **stop** can be replaced by a “*”, which will add the whole wall.
2. **direction** is optional. Use a positive value (default is +1) if **start** is less than **stop**; use a negative value to traverse the wall in the opposite direction.

outer i j k adds the *i*th *j*th and *k*th points of the bounding rectangle of the problem (minimum, maximum *x* and *z* used to define DEGAS 2’s “universal cell”) to the current polygon. The numbering of the corners is clockwise starting from 0 at $x_{\min}$, $z_{\min}$. There can be any number of arguments, although typical usage will be with three.

edge j1 j2 j3 j4 takes an “edge” (i.e., a section of a horizontal or vertical boundary) from the DEGAS **gridx**, **gridz** arrays and adds it to the current polygon. The arguments indicate the same things as in **grid** except that here we must have either $j1 = j2$ or $j3 = j4$ in order for the edge to lie on a single boundary.

define_polygon terminates the definition of the current polygon begun by the previous **new_polygon** and adds it to the current zone.

Keywords which apply only in the UEDGE and Sonnet cases (the only difference between the two is that double-null option is currently not available; the reason has been forgotten!) are:

mesh rmin rmax zmin zmax defines the plasma zones based on the UEDGE or Sonnet mesh. The input parameters are used to specify the universal cell. The corresponding rectangle, therefore, must completely enclose the mesh coordinates.

null_type j can be $j = 1$ (single-null) or 2 (double-null).

wallfile filename specifies a file with two wall segments which will be used to set up vacuum regions around the plasma zones established via a UEDGE file.

These keywords are used to label solid and exit polygons. They may be used with any of the three input file types:

stratum j sets the stratum label to be *j*. Polygons defined subsequently will be labeled with this stratum number until the label is changed again via this keyword. For DEGAS input files, **readgeometry** will use the DEGAS wall number as the stratum label, unless overridden by explicit use of this keyword.

material *symbol* sets the label for the current material to be that represented by *symbol* (an entry in the `materials_infile`; see Sec. ??). Polygons defined subsequently will be made of this material until the label is changed again via this keyword. For DEGAS input files, `readgeometry` will attempt to extract the material from the `kwmat` array, unless overridden by explicit use of this keyword. In other words, if the user wishes to set the current material explicitly, the **material** keyword should come *after* any **wall** keywords used in defining the polygon (and before **define_polygon**).

temperature *value* assigns the current temperature to *value* kelvin. This is used along with the material and stratum labels in defining the material surfaces (targets and walls) in the problem. If not set, a default temperature of 300 K is used. For DEGAS input files, `readgeometry` will attempt to extract the material from the `twall` array, unless overridden by explicit use of this keyword.

recyc_coef *value* assigns the current recycling fraction, handled in the same way as the current material and temperature, to *value*, which must be ≥ 0 and ≤ 1 . The absorbed fraction is $1 - \text{value}$. The default recycling coefficient is 1. While the DEGAS variable `frabsorb` specifies the fraction of the not-reflected atoms which are absorbed; i.e., the overall absorption fraction depends on the local reflection coefficient. Hence, we have not attempted to relate the DEGAS 2 recycling coefficient to `frabsorb`.

end terminates the input to `readgeometry`.

A typical main `readgeometry` input file for reading DEGAS input will have a structure similar to:

```

symmetry ...

degasfile ...

minx ...
minz ...
mindensity ...
grid

new_zone ...
  new_polygon
    wall ...
    outer ...
    edge ...
    material ...
    stratum ...
  define_polygon

  new_polygon
    .
    .
    .

new_zone
  .
  .
  .

end

```

The input files for the UEDGE cases are usually much simpler. This is possible since the UEDGE case is more specific and much of the topological information can be hard-wired into the code:

```

symmetry ...

uedgefile ...

null_type ...
wall_file ...
material ...
mesh ...
end

```

See the Examples section in the manual for additional examples of **readgeometry** input files.

```

$Id:  readgeometry.web,v 1.43 2000/04/01 17:34:30 dstotler Exp $

"readgeometry.f" 1 ≡
  @m FILE 'readgeometry.web'

```

The unnamed module.

```

"readgeometry.f" 1.1 ≡
  @f namelist integer

```

⟨ Functions and Subroutines #3 ⟩

The main program

```
"readgeometry.f" 1.2 ≡
  @m mem_delta 10
  @m xz_index 2
  @m num_points 200

      /* Code specific to a few geometries, e.g., for detector setup, appears in this file. Unless you
      know for a fact that your geometry corresponds to one of the other types, set GEOMETRY to
      GENERAL. */

  @m GENERAL 0
  @m UEDGE_RECT_SLAB 1 // Marv's single-null slab used in the EIRENE benchmark.
  @m BOX 2 // A 1 by 1 box, e.g., from boxgen.
  @m WISING_CMOD 3 // Fred Wising's UEDGE simulation of C-Mod.
  @m DEGAS_CMOD 4

  @m GEOMETRY GENERAL // Pick one of the above.

  @m next_surface #:0 // Statement label

  @m increment_num_polygon num_polygon++
  var_realloca(polygon_x)
  var_realloca(polygon_temperature)
  var_realloca(polygon_recyc_coef)
  var_realloca(polygon_points)
  var_realloca(polygon_zone)
  var_realloca(polygon_material)
  var_realloca(polygon_stratum)
  var_realloca(polygon_segment)

< Functions and Subroutines 1.2 > ≡
  program readgeometry
    implicit_none_f77
    implicit_none_f90
    character*FILELEN filename

    call readfilenames

    call command_arg(1, filename)
    call nc_read_materials
    call readgeomfile(filename)

    stop
  end
```

See also sections #4, #13, #17, #18, #19, and #20.

This code is used in section 1.1.

The main routine.

⟨Functions and Subroutines 1.2⟩ +=

```

subroutine readgeomfile(filename)

  define_dimen(poly_ind, num_polygon)
  define_dimen(xz_ind, xz_index)
  define_dimen(points_ind0, 0, num_points - 1)
  define_dimen(points_ind, num_points - 1)
  define_varp(polygon_x, FLOAT, xz_ind, points_ind0, poly_ind)
  define_varp(polygon_temperature, FLOAT, poly_ind)
  define_varp(polygon_recyc_coef, FLOAT, poly_ind)
  define_varp(polygon_points, INT, poly_ind)
  define_varp(polygon_zone, INT, poly_ind)
  define_varp(polygon_stratum, INT, poly_ind)
  define_varp(polygon_material, INT, poly_ind)
  define_varp(polygon_segment, INT, points_ind, poly_ind)

  implicit_none_f77
  gi_common
  sc_common
  zn_common
  ma_common
  implicit_none_f90
  integer mx, my
  parameter (mx = 120, my = 100)
  character*FILELEN filename, datafilename, wallfilename
  logical uedge, degas, sonnet, single_null, double_null
  integer length, p, b, e    // Local
  integer datafile_diskin, wallfile_diskin, zone, n, wall_no, wall_start, wall_stop, wall_direction, i, j,
    grid_startv, grid_stopv, j1, j2, grid_starth, grid_stoph, steph, stepv, h, v, num, nx, ny, nu,
    ixpt1, ixpt2, iysptrx, symmetry, ix_mirror, null_type, grid_sense, segment, segment1
  @#if (GEOMETRY  $\equiv$  UEDGE_RECT_SLAB  $\vee$  GEOMETRY  $\equiv$  DEGAS_CMOD)
    integer var, tab_index, spacing
    real var_min, var_max, mult
    integer grp_sectors1mx
  @#endif

  character*LINELEN line, keyword, new_zone_type
  logical complete, vacuum
  real xmin, xmax, ymin, ymax, zmin, zmax, vol, vola, vol_test
  real mindensity, minx, minz, current_temperature, current_recyc_coef
  real wall_recyc, target_recyc, pfr_recyc
  real rmmx, my, 0:4, zmmx, my, 0:4, x_test2, 0:4

  vc_decl(min_corner)
  vc_decl(max_corner)
  vc_decl(test_vec_1)
  vc_decl(test_vec_2)
  vc_decl(test_vec_3)
  vc_decl(yhat)

  declare_varp(polygon_x)
  declare_varp(polygon_temperature)
  declare_varp(polygon_recyc_coef)
  declare_varp(polygon_points)

```

```

declare_varp(polygon_zone)
declare_varp(polygon_stratum)
declare_varp(polygon_material)
declare_varp(polygon_segment)

integer num_polygon, current_material, current_stratum, temp_material
integer face1, zone1, zone2, stratum, sector1, sector2
integer xcorner1, xcorner2, xcorner3, xcorner4, zcorner1, zcorner2, zcorner3, zcorner4
character*100 plot

⟨Memory allocation interface 0⟩
st_decls
vc_decls
gi_ext

⟨pardef.h 0⟩
⟨combal.h 0⟩
⟨comst.h 0⟩
⟨comgeo.h 0⟩
⟨compls.h 0⟩
⟨comflg.h 0⟩
⟨comrfl.h 0⟩
⟨comrat.h 0⟩
⟨comsv.h 0⟩
⟨comstat.h 0⟩
⟨compar.h 0⟩

datafile_diskin = diskin + 1
wallfile_diskin = diskin + 2

open(unit = diskin, file = filename, status = 'old', form = 'formatted')

  /* read the file containing keywords that describe the way plotting has to be done */

  /* Defaults and other initializations */
uedge =  $\mathcal{F}$ 
degas =  $\mathcal{F}$ 
sonnet =  $\mathcal{F}$ 
single_null =  $\mathcal{F}$ 
double_null =  $\mathcal{F}$ 

num_polygon = 0

var_realloca(polygon_x)
var_realloca(polygon_temperature)
var_realloca(polygon_recyc_coef)
var_realloca(polygon_points)
var_realloca(polygon_zone)
var_realloca(polygon_stratum)
var_realloca(polygon_material)
var_realloca(polygon_segment)

symmetry = geometry_symmetry_cylindrical
zone = 0
current_temperature = const(3., 2)
current_recyc_coef = one
wall_recyc = const(0.99)
pfr_recyc = const(0.99)

```

```

    target_recyc = const(0.98)
loop1: continue
    assert(read_string(diskin, line, length))
    assert(length ≤ len(line))
    length = parse_string(line(: length))
    p = 0
    assert(next_token(line, b, e, p))
    keyword = line(b : e)
    assert(next_token(line, b, e, p))
    if (keyword ≡ 'symmetry') then
        if (line(b : e) ≡ 'cylindrical') then
            symmetry = geometry_symmetry_cylindrical
        else if (line(b : e) ≡ 'plane') then
            symmetry = geometry_symmetry_plane
        else if (line(b : e) ≡ 'oned') then
            symmetry = geometry_symmetry_oned
        else
            assert(line(b : e) ≡ 'cylindrical' ∨ line(b : e) ≡ 'plane')
        end if
        goto loop1
    end if
    assert(keyword ≡ 'degasfile' ∨ keyword ≡ 'uedgefile' ∨ keyword ≡ 'sonnetfile')
    datafilename = line(b : e)
    open(unit = datafile_diskin, file = datafilename, status = 'old', form = 'formatted')
    if (keyword ≡ 'degasfile') then
        degas = T
        call inpt(datafile_diskin, symmetry, xmin, xmax, zmin, zmax)
        call init_geometry
        close(unit = datafile_diskin)
    elseif (keyword ≡ 'uedgefile') then
        uedge = T
        nu = datafile_diskin
        vacuum = F
    elseif (keyword ≡ 'sonnetfile') then
        sonnet = T    /* everything is the same as for uedge for single null */
        uedge = T
    endif
    if (¬uedge) then
        min_corner1 = xmin
        min_corner2 = zero
        min_corner3 = zmin
        max_corner1 = xmax
        if (symmetry ≡ geometry_symmetry_cylindrical) then
            max_corner2 = two * PI
        else
            max_corner2 = one
        end if
        max_corner3 = zmax
        call universal_cell(symmetry, min_corner, max_corner, vol)
    end if
loop2: continue

```

```

if ( $\neg$ read_string(diskin, line, length))
    goto eof
assert(length  $\leq$  len(line))
length = parse_string(line(: length))
p = 0
assert(next_token(line, b, e, p))
keyword = line(b : e)
if (keyword  $\equiv$  'null_type') then
    assert(next_token(line, b, e, p))
    null_type = read_integer(line(b : e))
    if (null_type  $\equiv$  1) then
        single_null =  $\mathcal{T}$ 
    elseif (null_type  $\equiv$  2) then
        double_null =  $\mathcal{T}$ 
        ix_mirror = 0 // initialise only
    else
        print *, 'unknown_null_type'
        assert( $\mathcal{F}$ )
    endif
if (uedge  $\wedge$   $\neg$ sonnet) then
    call inpt_uedge(nu, nx, ny, ixpt1, ixpt2, iysptrx, rm, zm, mx, my, null_type, ix_mirror)
elseif (sonnet) then
    call inpt_sonnet(datafile_diskin, xmin, xmax, zmin, zmax, rm, zm, nx, ny, mx, my, ixpt1,
        ixpt2, iysptrx, null_type, ix_mirror)
    endif
    call init_geometry
elseif (keyword  $\equiv$  'new_zone') then
    zone++
@#if 0
    zn_volume(zone) = zero
@#endif
    assert(next_token(line, b, e, p))
    new_zone_type = line(b : e)
elseif (keyword  $\equiv$  'new_polygon') then
    n = 0
    increment_num_polygon
elseif (keyword  $\equiv$  'define_polygon') then
    polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
    polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
    polygon_points_num_polygon = n
    polygon_zone_num_polygon = zone
    polygon_stratum_num_polygon = current_stratum
    polygon_material_num_polygon = current_material
    polygon_temperature_num_polygon = current_temperature
    polygon_recyc_coef_num_polygon = current_recyc_coef
    call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
if (zn_volume(zone)  $\equiv$  real_undef) then
    zn_volume(zone) = zero
    if (new_zone_type  $\equiv$  'solid') then
        zn_type_set(zone, zn_solid)
    else if (new_zone_type  $\equiv$  'exit') then
        zn_type_set(zone, zn_exit)

```

```

    else if (new_zone_type ≡ 'vacuum') then
        zn_type_set(zone, zn_vacuum)
    else if (new_zone_type ≡ 'plasma') then
        zn_type_set(zone, zn_plasma)
    else if (new_zone_type ≡ 'exit') then
        zn_type_set(zone, zn_exit)
    else
        write(stderr, *) 'Unknown_zone_type:', new_zone_type
        assert( $\mathcal{F}$ )
    end if
    call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{T}$ )
else
    call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ )
end if
zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
elseif (keyword ≡ 'wall') then
    ⟨ Wall Keyword #5 ⟩

elseif (keyword ≡ 'outer') then
loop3: continue
    if (next_token(line, b, e, p)) then
        i = read_integer(line(b:e))
        if (i ≡ 0 ∨ i ≡ 4) then
            polygon_x1, n, num_polygon = xmin;
            polygon_x2, n, num_polygon = zmin
        else if (i ≡ 1) then
            polygon_x1, n, num_polygon = xmin;
            polygon_x2, n, num_polygon = zmax
        else if (i ≡ 2) then
            polygon_x1, n, num_polygon = xmax;
            polygon_x2, n, num_polygon = zmax
        else if (i ≡ 3) then
            polygon_x1, n, num_polygon = xmax;
            polygon_x2, n, num_polygon = zmin
        end if
        n++
        polygon_segmentn, num_polygon = 0    // i.e., not used
        assert(n ≤ num_points - 1)
        goto loop3
    end if
elseif (keyword ≡ 'grid') then
    ⟨ Grid Keyword #6 ⟩

elseif (keyword ≡ 'edge') then
    ⟨ Edge Keyword #7 ⟩

elseif (keyword ≡ 'mindensity') then
    assert(next_token(line, b, e, p))
    mindensity = read_real(line(b:e))
elseif (keyword ≡ 'minz') then
    assert(next_token(line, b, e, p))
    minz = read_real(line(b:e))
elseif (keyword ≡ 'minx') then

```

```

    assert(next_token(line, b, e, p))
    minx = read_real(line(b:e))

elseif (keyword ≡ 'wallfile') then
    assert(next_token(line, b, e, p))
    wallfilename = line(b:e)
    open(unit = wallfile_diskin, file = wallfilename, status = 'old', form = 'formatted')
    read(wallfile_diskin, *) nowals
    read(wallfile_diskin, *) SP(nosegsxzi, i = 1, nowals)
    do i = 1, nowals
        do j = 1, nosegsxzi
            read(wallfile_diskin, *) xwallj, i, zwallj, i
        enddo
    enddo
    vacuum = T
elseif (keyword ≡ 'mesh') then
    ⟨ Mesh Keyword #8 ⟩

elseif (keyword ≡ 'stratum') then
    assert(next_token(line, b, e, p))
    current_stratum = read_integer(line(b:e))

elseif (keyword ≡ 'material') then
    assert(next_token(line, b, e, p))
    current_material = ma_lookup(line(b:e))

elseif (keyword ≡ 'temperature') then
    assert(next_token(line, b, e, p))
    current_temperature = read_real(line(b:e))

elseif (keyword ≡ 'recyc_coef') then
    assert(next_token(line, b, e, p))
    current_recyc_coef = read_real(line(b:e))

    /* These three are presently used only for the UEDGE_RECT_SLAB geometry. */
elseif (keyword ≡ 'wall_recyc_coef') then
    assert(next_token(line, b, e, p))
    wall_recyc = read_real(line(b:e))
elseif (keyword ≡ 'target_recyc_coef') then
    assert(next_token(line, b, e, p))
    target_recyc = read_real(line(b:e))
elseif (keyword ≡ 'pfr_recyc_coef') then
    assert(next_token(line, b, e, p))
    pfr_recyc = read_real(line(b:e))

    /* insert additional keywords below this */

elseif (keyword ≡ 'end') then
    goto eof
else
    write(stderr, *) 'Unknown_keyword_', trim(keyword)
    assert( $\mathcal{F}$ )
end if
goto loop2
eof: continue
close(unit = diskin)

```

call *boundaries_neighbors*

```

/* Set up default sectors. These are taken to be at the interface between plasma / vacuum and solid
/ exit zones. The procedure consists of first cycling through all of the polygons of zone type solid
or exit and checking each surface to see if there is a plasma or vacuum zone on the other side. The
filter used here is that find_poly_zone arranges for the type of zone1 to match that of polygon i.
This is done so that, for example, a target sector is identified by having zone1 be a solid and
zone2 be plasma. The target sector is then associated with zone2 (and its corresponding face,
-face1); zone1 is passed to define_sector as a check. */
segment = 0    // UEDGE_RECT_SLAB
segment1 = 0   // Test of diagnostic sectors
do i = 1, num_polygon
  do j = 0, polygon_pointsi - 1
    if (polygon-x1, j, i ≠ polygon-x1, j+1, i ∨ polygon-x2, j, i ≠ polygon-x2, j+1, i) then
      call find_poly_zone(polygon-x1, j, i, polygon-x1, j+1, i, zn_type(polygon-zonei), zone1, face1,
        zone2)
      if (zone1 > 0 ∧ zone2 > 0) then
        @#if (GEOMETRY ≡ UEDGE_RECT_SLAB)
          if (polygon-x1, j, i ≤ zero ∧ polygon-x1, j+1, i ≤ zero ∧ (polygon-x1, j+1, i >
            polygon-x1, j, i) ∧ polygon-x2, j, i ≡ const(0.75) ∧ polygon-x2, j+1, i ≡ const(0.75)) then
            assert(zn_type(zone1) ≡ zn_plasma ∧ zn_type(zone2) ≡ zn_plasma)
            stratum = 6
            segment++
            sector1 = define_sector(stratum, segment, face1, zone1, 0)    // Null second zone
            temp_material = ma_lookup('mirror')
            define_sector_wall(sector1, temp_material, current_temperature * boltzmanns_const,
              current_recyc_coef)
            segment++
            sector2 = define_sector(stratum, segment, -face1, zone2, 0)
            define_sector_wall(sector2, temp_material, current_temperature * boltzmanns_const,
              current_recyc_coef)
            /* Designate the rest of the surfaces along z = 0.75 as diagnostic sectors. The sector
            numbers are stored in arrays for use in calls to diag_grp_init below. Note that in most
            instances, defining sectors on one side of an interface is sufficient. A second group of
            sectors with arguments -face1 and zone2 could have been defined, if needed. */
          else if ((polygon-x1, j+1, i > polygon-x1, j, i) ∧ polygon-x2, j, i ≡
            const(0.75) ∧ polygon-x2, j+1, i ≡ const(0.75)) then
            assert(zn_type(zone1) ≡ zn_plasma ∧ zn_type(zone2) ≡ zn_plasma)
            stratum = 7
            segment1++
            sector1 = define_sector(stratum, segment1, face1, zone1, 0)
            grp_sectors1segment1 = sector1
            /* Verify that dimension of grp_sector array is adequate. */
            assert(segment1 ≤ mx)
          end if
        @#elif (GEOMETRY ≡ DEGAS_CMOD)
          if ((zn_type(zone1) ≡ zn_vacuum ∧ zn_type(zone2) ≡ zn_plasma) ∨ (zn_type(zone1) ≡
            zn_vacuum ∧ zn_type(zone2) ≡ zn_vacuum ∧ ¬(sc_check(int_lookup(-face1,
              sector_surface1, nsectors)))))) then
            stratum = 6
            segment1++
            sector1 = define_sector(stratum, segment1, -face1, zone2, zone1)
            grp_sectors1segment1 = sector1

```

```

    end if
  @#endif
    stratum = polygon_stratumi
    if ((zn_type(zone1) ≡ zn_solid) ∧ (zn_type(zone2) ≡ zn_plasma)) then
      sector1 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2, zone1)
      assert(ma_check(polygon_materiali))
      assert(polygon_temperaturei > zero)
      define_sector_target(sector1, polygon_materiali, polygon_temperaturei * boltzmanns_const,
        polygon_recyc_coefi)
    @#if 0
      sector2 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2)
      define_sector_plasma(sector2)
    @#endif
    else if ((zn_type(zone1) ≡ zn_solid) ∧ (zn_type(zone2) ≡ zn_vacuum)) then
      sector1 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2, zone1)
      assert(ma_check(polygon_materiali))
      assert(polygon_temperaturei > zero)
      define_sector_wall(sector1, polygon_materiali, polygon_temperaturei * boltzmanns_const,
        polygon_recyc_coefi)
    @#if 0
      sector2 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2)
      define_sector_vacuum(sector2)
    @#endif
    else if ((zn_type(zone1) ≡ zn_exit) ∧ ((zn_type(zone2) ≡ zn_plasma))) then
      sector1 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2, zone1)
      define_sector_exit(sector1)
    @#if 0
      sector2 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2)
      define_sector_plasma(sector2)
    @#endif
    else if ((zn_type(zone1) ≡ zn_exit) ∧ ((zn_type(zone2) ≡ zn_vacuum))) then
      sector1 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2, zone1)
      define_sector_exit(sector1)
    @#if 0
      sector2 = define_sector(stratum, polygon_segmentj+1, i, -face1, zone2)
      define_sector_vacuum(sector2)
    @#endif
    else
      goto next_surface
    end if
  end if
end if next_surface continue
end do
end do
call diag_sector_setup
@#if (GEOMETRY ≡ UEDGE_RECT_SLAB ∨ GEOMETRY ≡ DEGAS_CMOD)
  /* Define this set of sectors as a separate "diagnostic group". No energy or angle distribution is to
    be computed on these sectors: */
  var = sc_diag_unknown
  tab_index = 0

```

```

    var_min = zero
    var_max = zero
    mult = zero
    spacing = sc_diag_spacing_unknown
    call diag_grp_init('Throat_sectors', segment1, var, tab_index, var_min, var_max, mult, spacing,
        grp_sectors1)
@#endif

    call end_sectors
    call rg_detector_setup
    call end_detectors
    call check_geometry
    call write_geometry
    vola = zero
    do i = 1, zn_num
        assert(zn_volume(i) > 0)
        vola = vola + zn_volume(i)
    end do
    write(stdout, *) 'vol_and_vola=', vol, vola
    call erase_geometry
    return end

```

Wall keyword section

```

⟨ Wall Keyword 1.4 ⟩ ≡
  assert(next_token(line, b, e, p))
  wall_no = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  complete = (line(b : e) ≡ '*')
  if (¬complete) then
    wall_start = read_integer(line(b : e))
    assert(next_token(line, b, e, p))
    wall_stop = read_integer(line(b : e))
  end if
  if (next_token(line, b, e, p)) then
    wall_direction = read_integer(line(b : e))
  else
    wall_direction = 1
  end if
  if (complete) then
    if (wall_direction > 0) then
      wall_start = 1
      wall_stop = nosegsxzwall_no + 1
    else
      wall_start = nosegsxzwall_no + 1
      wall_stop = 1
    end if
  end if
  if (wall_direction > 0) then
    if (wall_stop < wall_start)
      wall_stop = wall_stop + nosegsxzwall_no + 1
    else
      if (wall_stop > wall_start)
        wall_start = wall_start + nosegsxzwall_no + 1
      end if
    /* Use wall_no and kumat to set stratum and material numbers. This is intended as a
    default which can be superseded via the “stratum” or “material” keywords, if desired. Note that
    in general the material can vary from sector to sector. To allow that here would require a very fine
    polygon specification. Likewise, set temperature. Note that twall has a toroidal segment index,
    set to 1. There is an assertion on the temperature at the end. */
    current_stratum = wall_no
    current_material = ma_lookup(kumatwall_start, wall_no)
    if (twallwall_start, 1, wall_no > zero)
      current_temperature = twallwall_start, 1, wall_no    // set current_recyc_coef from frabsorb?
  do i = wall_start, wall_stop, wall_direction
    polygon_x1, n, num_polygon = xwallmod(i-1, nosegsxzwall_no+1)+1, wall_no
    polygon_x2, n, num_polygon = xwallmod(i-1, nosegsxzwall_no+1)+1, wall_no
    n++
    polygon_segmentn, num_polygon = mod(i - 1, nosegsxzwall_no + 1) + 1
    assert(n ≤ num_points - 1)    /* Check to see that other values of kumat for this polygon are
    consistent with the one set at wall_start. If not, set current_material to a special value which
    can either be trapped downstream, or superseded by use of the “current_material” keyword. */
    if (i ≠ nosegsxzwall_no + 1) then
      temp_material = ma_lookup(kumatwall_start, wall_no)
      if (current_material ≠ temp_material)
        current_material = -1

```

```
    end if  
  end do
```

This code is used in section 1.3.

Grid keyword section

```

⟨ Grid Keyword 1.5 ⟩ ≡
  assert(next_token(line, b, e, p))
  grid_startv = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  grid_stopv = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  grid_starth = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  grid_stoph = read_integer(line(b : e))
  if (next_token(line, b, e, p)) then
    grid_sense = read_integer(line(b : e))
  else
    grid_sense = 1
  end if
  do j2 = grid_starth, grid_stoph
    plot = '␣'
    do j1 = grid_startv, grid_stopv
      if (kzone1(j1, j2) ≤ 0 ∨ kzone2(j1, j2) ≤ 0) then
        plot(j1 : j1) = 'k'
        goto skip
      else if (denehvt(j1, j2, 1) ≤ mindensity) then
        plot(j1 : j1) = 'd'
        goto skip
      else if (gridx(j1, j2, 1) ≤ minx ∨ gridx(j1, j2 + 1, 1) ≤ minx ∨ gridx(j1 + 1, j2 + 1, 1) ≤ minx ∨ gridx(j1 + 1, j2, 1) ≤ minx) then
        plot(j1 : j1) = 'x'
        goto skip
      else if (gridz(j1, j2, 1) ≤ minz ∨ gridz(j1, j2 + 1, 1) ≤ minz ∨ gridz(j1 + 1, j2 + 1, 1) ≤ minz ∨ gridz(j1 + 1, j2, 1) ≤ minz) then
        plot(j1 : j1) = 'z'
        goto skip
      endif
      if (grid_sense ≡ 1) then
        x_test1, 0 = gridx(j1, j2, 1)
        x_test2, 0 = gridz(j1, j2, 1)
        x_test1, 1 = gridx(j1 + 1, j2, 1)
        x_test2, 1 = gridz(j1 + 1, j2, 1)
        x_test1, 2 = gridx(j1 + 1, j2 + 1, 1)
        x_test2, 2 = gridz(j1 + 1, j2 + 1, 1)
        x_test1, 3 = gridx(j1, j2 + 1, 1)
        x_test2, 3 = gridz(j1, j2 + 1, 1)
      else if (grid_sense ≡ 2) then
        x_test1, 0 = gridx(j1, j2, 1)
        x_test2, 0 = gridz(j1, j2, 1)
        x_test1, 1 = gridx(j1, j2 + 1, 1)
        x_test2, 1 = gridz(j1, j2 + 1, 1)
        x_test1, 2 = gridx(j1 + 1, j2 + 1, 1)
        x_test2, 2 = gridz(j1 + 1, j2 + 1, 1)
        x_test1, 3 = gridx(j1 + 1, j2, 1)
        x_test2, 3 = gridz(j1 + 1, j2, 1)
      else

```

```

    assert('Unexpected_value_of_grid_sense' == ' ')
end if
x_test1, 4 = x_test1, 0
x_test2, 4 = x_test2, 0
vol_test = polygon_volume(4, x_test)
if (vol_test ≤ epsilon) then
    if (vol_test < -epsilon)
        write(stdout, *) 'Ignoring_negative_volume_zone_at_', j1, j2
        goto skip
    end if
    /* write(stdout, '(5f10.4)') gridx(j1,j2,1),gridx(j1,j2+1,1), gridx(j1+1,j2+1,1), gridx(j1+
    1,j2,1), gridx(j1,j2,1)write(stdout, '(5f10.4)')gridz(j1,j2,1), gridz(j1,j2+1,1),
    gridz(j1+1,j2+1,1),gridz(j1+1,j2,1),gridz(j1,j2,1) */
    zone++
    increment_num_polygon
do n = 0, 4
    polygon_x1, n, num_polygon = x_test1, n
    polygon_x2, n, num_polygon = x_test2, n
end do
polygon_points_num_polygon = 4
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = current_stratum
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(4, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_plasma)
zn_volume(zone) = vol_test
zn_index(zone, 1) = j1
zn_index(zone, 2) = j2
/* This is only an approximation and assumes that the zone is convex */
vc_set(zone_center zone, const(0.25) * (polygon_x1, 0, num_polygon + polygon_x1, 1, num_polygon +
    polygon_x1, 2, num_polygon + polygon_x1, 3, num_polygon), zero,
    const(0.25) * (polygon_x2, 0, num_polygon + polygon_x2, 1, num_polygon + polygon_x2, 2, num_polygon +
    polygon_x2, 3, num_polygon))
call set_zn_min_max(4, polygon_x1, 0, num_polygon, zone, T)
skip: continue
end do
write(stderr, *) j2, ' ', plot(grid_startv : grid_stopv)
enddo

```

This code is used in section 1.3.

Edge keyword section

```

⟨ Edge Keyword 1.6 ⟩ ≡
  assert(next_token(line, b, e, p))
  grid_startv = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  grid_stopv = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  grid_starth = read_integer(line(b : e))
  assert(next_token(line, b, e, p))
  grid_stoph = read_integer(line(b : e))
  assert(grid_startv ≡ grid_stopv ∨ grid_starth ≡ grid_stoph)
  if (grid_startv ≡ grid_stopv) then
    stepv = 0
  else if (grid_startv < grid_stopv) then
    stepv = 1
    num = grid_stopv - grid_startv + 1
  else
    stepv = -1
    num = grid_startv - grid_stopv + 1
  endif
  if (grid_starth ≡ grid_stoph) then
    steph = 0
  else if (grid_starth < grid_stoph) then
    steph = 1
    num = grid_stoph - grid_starth + 1
  else
    steph = -1
    num = grid_starth - grid_stoph + 1
  endif
  h = grid_starth
  v = grid_startv
  do i = 0, num - 1
    polygon_x1, n, num_polygon = gridx(v, h, 1)
    polygon_x2, n, num_polygon = gridz(v, h, 1)
    n++
    h = h + steph
    v = v + stepv
  enddo

```

This code is used in section 1.3.

Mesh keyword section

⟨ Mesh Keyword 1.7 ⟩ ≡

```

    assert(uedge)
    assert(next_token(line, b, e, p))
    xmin = read_real(line(b : e))
    assert(next_token(line, b, e, p))
    xmax = read_real(line(b : e))
    assert(next_token(line, b, e, p))
    zmin = read_real(line(b : e))
    assert(next_token(line, b, e, p))
    zmax = read_real(line(b : e))
    if (next_token(line, b, e, p)) then
        ymin = read_real(line(b : e))
        assert(next_token(line, b, e, p))
        ymax = read_real(line(b : e))
    else
        ymin = zero
        ymax = two * PI
    end if
    min_corner_1 = xmin
    min_corner_2 = ymin
    min_corner_3 = zmin
    max_corner_1 = xmax
    max_corner_2 = ymax
    max_corner_3 = zmax
@#if 0
    call init_geometry
@#endif
    call universal_cell(symmetry, min_corner, max_corner, vol)
    /* (xcorner1,zcorner1) is the left bottom corner of a cell. (2,2) (3,3) and (4,4) are the other corners
       if you proceed in the clock-wise direction around the computational rectangle. The convention
       varies, hence the corners have to be set to conform with the data file being used */
    if (sonnet) then
        xcorner1 = 3;
        zcorner1 = 3
        xcorner2 = 1;
        zcorner2 = 1
        xcorner3 = 2;
        zcorner3 = 2
        xcorner4 = 4;
        zcorner4 = 4
    else
        xcorner1 = 1;
        zcorner1 = 1
        xcorner2 = 3;
        zcorner2 = 3
        xcorner3 = 4;
        zcorner3 = 4
        xcorner4 = 2;
        zcorner4 = 2
    endif
    /* A separate question is the direction around the physical rectangle. The polygon sent to
       decompose_polygon must be traversed in a clockwise direction in physical space. */

```

```

vc_set(yhat, zero, one, zero)
vc_set(test_vec_1, rm(1, 1, xcorner2) - rm(1, 1, xcorner1), zero, zm(1, 1, zcorner2) - zm(1, 1,
    zcorner1))
vc_set(test_vec_2, rm(1, 1, xcorner3) - rm(1, 1, xcorner2), zero, zm(1, 1, zcorner3) - zm(1, 1,
    zcorner2))
vc_cross(test_vec_1, test_vec_2, test_vec_3)
if (vc_product(test_vec_3, yhat) > zero) then
    grid_sense = 1
else if (vc_product(test_vec_3, yhat) < zero) then
    grid_sense = 2
else
    assert('First cell of mesh degenerate' ≡ ' ')
end if
do j1 = 1, nx
    do j2 = 1, ny
        zone++
        n = 0
        increment_num_polygon
        polygon_x_1, n, num_polygon = rm(j1, j2, xcorner1)
        polygon_x_2, n, num_polygon = zm(j1, j2, zcorner1);
        n++
        if (grid_sense ≡ 1) then
            polygon_x_1, n, num_polygon = rm(j1, j2, xcorner2)
            polygon_x_2, n, num_polygon = zm(j1, j2, zcorner2);
            n++
            polygon_x_1, n, num_polygon = rm(j1, j2, xcorner3)
            polygon_x_2, n, num_polygon = zm(j1, j2, zcorner3);
            n++
            polygon_x_1, n, num_polygon = rm(j1, j2, xcorner4)
            polygon_x_2, n, num_polygon = zm(j1, j2, zcorner4);
            n++
        else if (grid_sense ≡ 2) then
            polygon_x_1, n, num_polygon = rm(j1, j2, xcorner4)
            polygon_x_2, n, num_polygon = zm(j1, j2, zcorner4);
            n++
            polygon_x_1, n, num_polygon = rm(j1, j2, xcorner3)
            polygon_x_2, n, num_polygon = zm(j1, j2, zcorner3);
            n++
            polygon_x_1, n, num_polygon = rm(j1, j2, xcorner2)
            polygon_x_2, n, num_polygon = zm(j1, j2, zcorner2);
            n++
        else
            assert('grid_sense improperly set' ≡ ' ')
        end if
        polygon_x_1, n, num_polygon = polygon_x_1, 0, num_polygon
        polygon_x_2, n, num_polygon = polygon_x_2, 0, num_polygon
        polygon_points_num_polygon = n
        polygon_zone_num_polygon = zone
        polygon_stratum_num_polygon = current_stratum
        polygon_material_num_polygon = current_material
        polygon_temperature_num_polygon = current_temperature
        polygon_recyc_coef_num_polygon = current_recyc_coef
    
```

```

call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_plasma)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
zn_index(zone, 1) = j1
zn_index(zone, 2) = j2
vc_set(zone_center zone, rmj1, j2, 0, zero, zmj1, j2, 0)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)
enddo
enddo

/* Two cases: vacuum and  $\neg$ vacuum; for the former, wallfile data must be specified. In both cases,
we use assumed values for the stratum numbers:

```

1. Inner target,
2. Outer target,
3. Wall along main SOL,
4. Core region (treated as an exit here),
5. Wall below private flux region.

The stratum numbers for plasma and vacuum regions are set to *current_stratum*; these numbers are not used since the stratum for each sector is defined by the solid / exit stratum. The value of *current_material* is used everywhere (and is, hence, constant). */

```

@#if (GEOMETRY  $\neq$  UEDGE_RECT_SLAB)

```

```

    if ( $\neg$ vacuum) then

```

```

        ⟨Not-Vacuum Boundary Section #9⟩

```

```

    else

```

```

        ⟨Vacuum Boundary Section #10⟩

```

```

    endif

```

```

        ⟨Core Boundary Section #11⟩

```

```

@#else

```

```

        ⟨UERS Boundary Section #12⟩

```

```

@#endif

```

```

/* END OF "MESH" KEYWORD SECTION */

```

This code is used in section 1.3.

Not-Vacuum Boundary Section. I.e., Mesh itself is the problem boundary.

⟨Not-Vacuum Boundary Section 1.8⟩ ≡

```

zone++      /* Start from left lower corner of box and go clockwise along box till right lower corner.
              Return along outer edge of SOL to starting pt. */
n = 0
increment_num_polygon    // SINGLE NULL
if (single_null) then
    polygon_x1, n, num_polygon = xmin
    polygon_x2, n, num_polygon = zmin;
    n++
    polygon_x1, n, num_polygon = xmin
    polygon_x2, n, num_polygon = zmax;
    n++
    polygon_x1, n, num_polygon = xmax
    polygon_x2, n, num_polygon = zmax;
    n++
    polygon_x1, n, num_polygon = xmax
    polygon_x2, n, num_polygon = zmin;
    n++
    j1 = nx;
    j2 = ny
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
    n++
    do j1 = nx, 1, -1
        polygon_segment_n, num_polygon = j1
        polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
        polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
        n++
    end do    // DOUBLE NULL
elseif (double_null ∧ uedge) then    // Why uedge ???
    polygon_x1, n, num_polygon = xmin
    polygon_x2, n, num_polygon = zmin;
    n++
    polygon_x1, n, num_polygon = xmin
    polygon_x2, n, num_polygon = zmax;
    n++
    polygon_x1, n, num_polygon = xmax
    polygon_x2, n, num_polygon = zmax;
    n++
    polygon_x1, n, num_polygon = xmax
    polygon_x2, n, num_polygon = zmin;
    n++
    j1 = nx;
    j2 = ny
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
    n++
    j2 = ny
    do j1 = nx, ix_mirror + 1, -1
        polygon_segment_n, num_polygon = j1

```

```

    polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
    n++
enddo
j1 = ix_mirror + 1
do j2 = ny, 1, -1
    polygon_segment_n, num_polygon = j2
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
    n++
enddo
j1 = ix_mirror;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
n++
j1 = ix_mirror
do j2 = 1, ny
    polygon_segment_n, num_polygon = j2
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
    n++
enddo
j2 = ny
do j1 = ix_mirror, 1, -1
    polygon_segment_n, num_polygon = j1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
    n++
enddo
else
    print *, 'neither_single_nor_double_null'
    assert(F)
endif
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 3
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)
/* Start from left lower corner of box and to left top of SOL to right top of SOL. Cut down from
there to bottom of box and then close the polygon. Note that in a strange configuration, this
“cut” could slice back across previous polygon points, ruining its connectedness. */
n = 0
increment_num_polygon // SINGLE and DOUBLE NULL
polygon_x1, n, num_polygon = xmin

```

```

    polygon_x2, n, num_polygon = zmin;
    n++
    j1 = 1
    do j2 = ny, 1, -1
        polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
        polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
        n++
        polygon_segment_n, num_polygon = j2
    end do
    j2 = 1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
    n++
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zmin;
    n++
    polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
    polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
    polygon_points_num_polygon = n
    polygon_zone_num_polygon = zone
    polygon_stratum_num_polygon = 1
    polygon_material_num_polygon = current_material
    polygon_temperature_num_polygon = current_temperature
    polygon_recyc_coef_num_polygon = current_recyc_coef
    call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
    zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
    call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ )
    /* Start again at bottom of box and proceed straight up to right top; proceed along PFR to left
       bottom of SOL; go again straight down to bottom of box and then close the polygon. */
    n = 0
    increment_num_polygon
    j2 = 1;
    j1 = 1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zmin;
    n++
    do j1 = 1, ixpt1
        polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
        polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
        n++
        polygon_segment_n, num_polygon = j1
    end do
    do j1 = ixpt2 + 1, nx
        polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
        polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
        n++
        polygon_segment_n, num_polygon = j1
    end do
    j1 = nx
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++

```

```

polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 5
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ ) /* Pick up at the bottom of the box
and go back up to the left bottom of the SOL, then go across to the right bottom of the SOL, to
the lower right bottom of the box and then close the polygon. */
n = 0
increment_num_polygon
j1 = nx;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zmin;
n++
do j2 = 1, ny
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++
    polygon_segment_n, num_polygon = j2
end do
j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
n++

polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 2
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ )

```

This code is used in section 1.7.

Vacuum Boundary Section

⟨ Vacuum Boundary Section 1.9 ⟩ ≡

```

/* Specify a vacuum region // Start with top vacuum region */
if (single_null) then // SINGLE NULL
  zone++

  n = 0
  increment_num_polygon
  i = 2
  do j = nosegsxzi, 1, -1
    polygon-x1, n, num_polygon = xwallj, i
    polygon-x2, n, num_polygon = zwallj, i;
    n++
    polygon-segmentn, num_polygon = j
  end do
  j1 = nx;
  j2 = ny
  polygon-x1, n, num_polygon = rm(j1, j2, xcorner3)
  polygon-x2, n, num_polygon = zm(j1, j2, zcorner3);
  n++

  do j1 = nx, 1, -1
    polygon-segmentn, num_polygon = j1
    polygon-x1, n, num_polygon = rm(j1, j2, xcorner2)
    polygon-x2, n, num_polygon = zm(j1, j2, zcorner2);
    n++
  end do

  polygon-x1, n, num_polygon = polygon-x1, 0, num_polygon
  polygon-x2, n, num_polygon = polygon-x2, 0, num_polygon

  polygon-pointsnum_polygon = n
  polygon-zonenum_polygon = zone
  polygon-stratumnum_polygon = current_stratum
  polygon-materialnum_polygon = current_material
  polygon-temperaturenum_polygon = current_temperature
  polygon-recyc-coefnum_polygon = current_recyc-coef
  call decompose_polygon(n, polygon-x1, 0, num_polygon, zone, 1, 0)
  zn_type_set(zone, zn_vacuum)
  zn_volume(zone) = polygon_volume(n, polygon-x1, 0, num_polygon)
  call set_zn_min_max(n, polygon-x1, 0, num_polygon, zone, T) /* Do top wall // Start from left
    lower corner of box and go clockwise along box till right lower corner. Return along top wall,
    touching the plasma corners (to complete the wall) at either end. */
  zone++

  n = 0
  increment_num_polygon
  polygon-x1, n, num_polygon = xmin
  polygon-x2, n, num_polygon = zmin;
  n++
  polygon-x1, n, num_polygon = xmin
  polygon-x2, n, num_polygon = zmax;
  n++
  polygon-x1, n, num_polygon = xmax

```

```

    polygon_x2, n, num_polygon = zmax;
    n++
    polygon_x1, n, num_polygon = xmax
    polygon_x2, n, num_polygon = zmin;
    n++

    j1 = nx
    j2 = ny
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
    n++
    polygon_segment_n, num_polygon = 0

    i = 2
    do j = 1, nosegsxz_i
        polygon_x1, n, num_polygon = xwall_j, i
        polygon_x2, n, num_polygon = zwall_j, i;
        n++
        polygon_segment_n, num_polygon = j
    end do

    j1 = 1
    j2 = ny
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
    n++

    polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
    polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

    polygon_points_num_polygon = n
    polygon_zone_num_polygon = zone
    polygon_stratum_num_polygon = 3
    polygon_material_num_polygon = current_material
    polygon_temperature_num_polygon = current_temperature
    polygon_recyc_coef_num_polygon = current_recyc_coef
    call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
    zn_type_set(zone, zn_solid)
    zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
    call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T) /* Outer vacuum region. // Start at
        top (end) of outer wall segment (wall 2), go down to its beginning point, jump to right bottom
        of SOL. Go up along right side of mesh to mirror point and finish at end of wall 2. */
    else if (double_null ∧ uedge) then // DOUBLE NULL

        zone++

        n = 0
        increment_num_polygon
        i = 2
        do j = nosegsxz_i, 1, -1
            polygon_x1, n, num_polygon = xwall_j, i
            polygon_x2, n, num_polygon = zwall_j, i;
            n++
            polygon_segment_n, num_polygon = j
        end do
        j1 = nx;

```

```

j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
n++

do j1 = nx, ix_mirror + 1, -1
  polygon_segment_n, num_polygon = j1
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
  polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
  n++
end do

polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = current_stratum
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_vacuum)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)
  /* Inner vacuum region. // Start at bottom (end) of inner wall segment, go up to its beginning
  point, jump to inner mirror point of mesh, follow the mesh down to the left top. */
zone++

n = 0
increment_num_polygon
i = 3
do j = nosegsz_i, 1, -1
  polygon_x1, n, num_polygon = xwall_j, i
  polygon_x2, n, num_polygon = zwall_j, i;
  n++
  polygon_segment_n, num_polygon = j
end do
j1 = ix_mirror;
j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
n++

do j1 = ix_mirror, 1, -1
  polygon_segment_n, num_polygon = j1
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
  polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
  n++
end do

polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

polygon_points_num_polygon = n
polygon_zone_num_polygon = zone

```

```

polygon_stratum_num_polygon = current_stratum
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x_1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_vacuum)
zn_volume(zone) = polygon_volume(n, polygon_x_1, 0, num_polygon)
call set_zn_min_max(n, polygon_x_1, 0, num_polygon, zone, T)

/* Outer solid. // Start at top right of box, go to bottom right. Then, jump to right bottom of
   SOL. Connect to wall 2 and follow it from beginning to end. */

zone++

n = 0
increment_num_polygon
polygon_x_1, n, num_polygon = xmax
polygon_x_2, n, num_polygon = zmax;
n++
polygon_x_1, n, num_polygon = xmax
polygon_x_2, n, num_polygon = zmin;
n++

j1 = nx
j2 = ny
polygon_x_1, n, num_polygon = rm(j1, j2, xcorner3)
polygon_x_2, n, num_polygon = zm(j1, j2, zcorner3);
n++
polygon_segment_n, num_polygon = 0

i = 2
do j = 1, nosegsxz_i
    polygon_x_1, n, num_polygon = xwall_j, i
    polygon_x_2, n, num_polygon = zwall_j, i;
    n++
    polygon_segment_n, num_polygon = j
end do

polygon_x_1, n, num_polygon = polygon_x_1, 0, num_polygon
polygon_x_2, n, num_polygon = polygon_x_2, 0, num_polygon

polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 3
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x_1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x_1, 0, num_polygon)
call set_zn_min_max(n, polygon_x_1, 0, num_polygon, zone, T)

/* Inner solid. // Start at bottom left of box. Go to top left. Jump to start of wall 3 and follow
   along its length. Step to left top of SOL and then finish polygon. */

zone++

n = 0

```

```

increment_num_polygon
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmax;
n++

i = 3
do j = 1, nsegxz_i
  polygon_x1, n, num_polygon = xwall_j, i
  polygon_x2, n, num_polygon = zwall_j, i;
  n++
  polygon_segment_n, num_polygon = j
end do

j1 = 1
j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
n++

polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 3
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

/* Mirror boundary. // Start at top left of box and go to the top right. Pick up the last point of
wall 2 and proceed to the outer edge of the mirror cut on the mesh. Work along the mirror cut
(going across the core, too). Pick up the first point of wall 3 and finish the polygon. To avoid
having decompose_polygon trying to work with very oddly shaped polygons with segments from
the inner and outer leg, split this up into three pieces with connections to the universal cell, just
as is done below for the bottom wall. There shouldn't be nearly as much problem with it here.
Right piece */

zone++

n = 0
increment_num_polygon

polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmax;
n++

i = 2
j = nsegxz_i
polygon_x1, n, num_polygon = xwall_j, i
polygon_x2, n, num_polygon = zwall_j, i;

```

```

n++

j2 = ny
j1 = ix_mirror + 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
n++

j1 = ix_mirror + 1
do j2 = ny, 1, -1
    polygon_segment_n, num_polygon = j2
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++
enddo
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zmax;
n++

polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 6
polygon_material_num_polygon = ma_lookup('mirror')
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

/* Middle piece */
n = 0
increment_num_polygon

j1 = ix_mirror + 1;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zmax;
n++

polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++

j1 = ix_mirror;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
n++

polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zmax;
n++

```

```

    polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
    polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

    polygon_points_num_polygon = n
    polygon_zone_num_polygon = zone
    polygon_stratum_num_polygon = 6
    polygon_material_num_polygon = ma_lookup('mirror')
    polygon_temperature_num_polygon = current_temperature
    polygon_recyc_coef_num_polygon = current_recyc_coef
    call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
    zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
    call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ )

    /* Left piece */
    n = 0
    increment_num_polygon

    j1 = ix_mirror;
    j2 = 1

    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zmax;
    n++

    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++
    j1 = ix_mirror
    do j2 = 1, ny
        polygon_segment_n, num_polygon = j2
        polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
        polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
        n++
    enddo

    i = 3
    j = 1
    polygon_x1, n, num_polygon = xwall_j, i
    polygon_x2, n, num_polygon = zwall_j, i;
    n++

    polygon_x1, n, num_polygon = xmin;
    polygon_x2, n, num_polygon = zmax;
    n++

    polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
    polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon

    polygon_points_num_polygon = n
    polygon_zone_num_polygon = zone
    polygon_stratum_num_polygon = 6
    polygon_material_num_polygon = ma_lookup('mirror')
    polygon_temperature_num_polygon = current_temperature
    polygon_recyc_coef_num_polygon = current_recyc_coef
    call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
    zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
    call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ )

```

```

else
    assert('neither_single_nor_double_null' ≡ ' ')
end if /* Bottom wall // Start from left lower corner of box, go to left top of SOL, then to right
        top of SOL. At this point, we cut straight down to the bottom of the box. Note that this arbitrary
        cut between the strata makes some assumptions about the mesh shapes; a bizarre geometry could
        end up with this polygon cutting across itself. */
zone++

n = 0
increment_num_polygon // SINGLE and DOUBLE NULL
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmin;
n++

j1 = 1
do j2 = ny, 1, -1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
    n++
    polygon_segment_n, num_polygon = j2
end do
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 1
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T) /* Go straight up again to the right
        top SOL and proceed to the first wall; follow it and then touch the left bottom of the SOL. Here
        again we go straight down to the bottom of the box before completing the polygon. */
n = 0
increment_num_polygon
j1 = 1;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++
polygon_segment_n, num_polygon = 0

```

```

i = 1
do j = 1, nosegsxzi
  polygon_x1, n, num_polygon = xwallj, i
  polygon_x2, n, num_polygon = zwallj, i;
  n++
  polygon_segmentn, num_polygon = j
end do
j1 = nx;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
n++
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_pointsnum_polygon = n
polygon_zonenum_polygon = zone
polygon_stratumnum_polygon = 5
polygon_materialnum_polygon = current_material
polygon_temperaturenum_polygon = current_temperature
polygon_recyc_coefnum_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, F)
/* Pick up again at the bottom and return to the left bottom of the SOL. Follow along the bottom
   SOL; go to the bottom of the box and then close the polygon. */
n = 0
increment num_polygon
j1 = nx;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zmin;
n++
j1 = nx
do j2 = 1, ny
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
  polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
  n++
  polygon_segmentn, num_polygon = j2
end do
j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
n++

polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_pointsnum_polygon = n

```

```

polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 2
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_volume(zone) = zn_volume(zone) + polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ ) /* Private vacuum region */
zone++
n = 0
increment_num_polygon
j2 = 1
do j1 = 1, ixpt1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
    n++
    polygon_segment_n, num_polygon = j1
end do
do j1 = ixpt2 + 1, nx
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
    n++
    polygon_segment_n, num_polygon = j1
end do
j1 = nx
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
n++
i = 1
do j = nosegsxzi, 1, -1
    polygon_segment_n, num_polygon = j
    polygon_x1, n, num_polygon = xwallj, i
    polygon_x2, n, num_polygon = zwallj, i;
    n++
end do
polygon_segment_n, num_polygon = 0
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = current_stratum
polygon_material_num_polygon = current_material
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_vacuum)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{T}$ )

```

This code is used in section 1.7.

Core Section

⟨ Core Boundary Section 1.10 ⟩ ≡

```

zone++ /* Core region */
n = 0
increment_num_polygon
j2 = 1
if (single_null) then
  do j1 = ixpt1 + 1, ixpt2
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
    n++
    polygon_segment_n, num_polygon = j1
  enddo
  polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
  polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
  polygon_points_num_polygon = n
  polygon_zone_num_polygon = zone
  polygon_stratum_num_polygon = 4
  polygon_material_num_polygon = current_material
  polygon_temperature_num_polygon = current_temperature
  polygon_recyc_coef_num_polygon = current_recyc_coef
  call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
  zn_type_set(zone, zn_exit)
elseif (double_null ∧ uedge) then
  j1 = ix_mirror;
  j2 = 1
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
  polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
  n++
  j1 = ix_mirror + 1;
  j2 = 1
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
  polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
  n++
  j2 = 1
  do j1 = ix_mirror + 1, ixpt2
    polygon_segment_n, num_polygon = j1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++
  enddo
  j2 = 1
  do j1 = ixpt1 + 1, ix_mirror
    polygon_segment_n, num_polygon = j1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++
  enddo
  polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
  polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
  polygon_points_num_polygon = n

```

```

    polygon_zonenum_polygon = zone
    polygon_stratumnum_polygon = 4
    polygon_materialnum_polygon = current_material
    polygon_temperaturenum_polygon = current_temperature
    polygon_recyc_coefnum_polygon = current_recyc_coef
    call decompose_polygon(n, polygon-x1, 0, num_polygon, zone, 1, 0)
    zn_type_set(zone, zn_exit)
endif

zn_volume(zone) = polygon_volume(n, polygon-x1, 0, num_polygon)
call set_zn_min_max(n, polygon-x1, 0, num_polygon, zone, T)

```

This code is used in section 1.7.

UEDGE Rectangular Slab Boundary Zones

⟨ UERS Boundary Section 1.11 ⟩ ≡

```

/* These are the boundaries of Rensink's slab-ized single-null geometry (the outer half anyway).
   Each polygon can be associated with a portion of a real single-null geometry. This first piece would
   be the symmetry plane. */
zone++
n = 0
increment_num_polygon
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmin;
n++
j1 = 1;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++
do j2 = 1, ny
  polygon_segment_n, num_polygon = j2
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
  polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
  n++
end do
polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 1
polygon_material_num_polygon = ma_lookup('mirror')
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

/* Right piece - corresponds to the outer wall. */
n = 0
increment_num_polygon
polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmin;
n++
j1 = 1;
j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner2)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner2);
n++
do j1 = 1, nx
  polygon_segment_n, num_polygon = j1
  polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)

```

```

    polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
    n++
end do
polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmax;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 2
polygon_material_num_polygon = ma_lookup('mo')
polygon_temperature_num_polygon = const(2.5, -2) /* eV, from EIRENE */
*electron_charge / boltzmanns_const // convert to K
polygon_recyc_coef_num_polygon = wall_recyc
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_volume(zone) += polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone,  $\mathcal{F}$ )

/* Lower left piece - corresponds to core plasma (hence, is an exit). Note that this and the next
   piece are triangles overall instead of rectangles. This was done because of a roundoff error problem
   in matching surfaces with the universal cell. That task is now successfully accomplished with an
   additional (physically irrelevant piece). */
zone++

n = 0
increment_num_polygon
j1 = ixpt2;
j2 = 1
do j1 = ixpt2, 1, -1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++
    polygon_segment_n, num_polygon = j1
end do
j1 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 3
polygon_material_num_polygon = ma_lookup('Ex')
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_exit)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)

```

```

call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

/* Upper left piece - corresponds to the private flux boundary. */
zone++

n = 0
increment_num_polygon
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmax;
n++
j1 = nx;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
n++
do j1 = nx, ixpt2 + 1, -1
    polygon_segmentn, num_polygon = j1
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
    n++
end do
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_pointsnum_polygon = n
polygon_zonenum_polygon = zone
polygon_stratumnum_polygon = 4
polygon_materialnum_polygon = ma_lookup('mo')
polygon_temperaturenum_polygon = const(2.5, -2) /* eV, from EIRENE */
*electron_charge / boltzmanns_const // convert to K
polygon_recyc_coefnum_polygon = pfr_recyc
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

/* This polygon fills in between the previous two and the universal cell. This is needed just to make
the geometry complete. */
zone++

n = 0
increment_num_polygon
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmax;
n++
j1 = ixpt2 + 1;
j2 = 1
polygon_x1, n, num_polygon = rm(j1, j2, xcorner1)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner1);
n++
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmin;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_pointsnum_polygon = n

```

```

polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 4
polygon_material_num_polygon = ma_lookup('mirror')
polygon_temperature_num_polygon = current_temperature
polygon_recyc_coef_num_polygon = current_recyc_coef
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

/* Top piece - represents target plate. */
zone++

n = 0
increment_num_polygon
polygon_x1, n, num_polygon = xmax
polygon_x2, n, num_polygon = zmax;
n++
j1 = nx;
j2 = ny
polygon_x1, n, num_polygon = rm(j1, j2, xcorner3)
polygon_x2, n, num_polygon = zm(j1, j2, zcorner3);
n++
do j2 = ny, 1, -1
    polygon_segment_n, num_polygon = j2
    polygon_x1, n, num_polygon = rm(j1, j2, xcorner4)
    polygon_x2, n, num_polygon = zm(j1, j2, zcorner4);
    n++
end do
polygon_x1, n, num_polygon = xmin
polygon_x2, n, num_polygon = zmax;
n++
polygon_x1, n, num_polygon = polygon_x1, 0, num_polygon
polygon_x2, n, num_polygon = polygon_x2, 0, num_polygon
polygon_points_num_polygon = n
polygon_zone_num_polygon = zone
polygon_stratum_num_polygon = 5
polygon_material_num_polygon = ma_lookup('mo')
polygon_temperature_num_polygon = const(1., -1) /* eV, from EIRENE */
*electron_charge / boltzmanns_const // convert to K
polygon_recyc_coef_num_polygon = target_recyc
call decompose_polygon(n, polygon_x1, 0, num_polygon, zone, 1, 0)
zn_type_set(zone, zn_solid)
zn_volume(zone) = polygon_volume(n, polygon_x1, 0, num_polygon)
call set_zn_min_max(n, polygon_x1, 0, num_polygon, zone, T)

```

This code is used in section 1.7.

Geometry-specific code specifying detector views. Actual code sections follow immediately below (FWEB insisted things be arranged this way).

⟨ Functions and Subroutines 1.2 ⟩ +≡

@#if (*GEOMETRY* ≡ *BOX*)

 ⟨ Box Detector Setup #14 ⟩

@#elif (*GEOMETRY* ≡ *WISING_CMOT* ∨ *GEOMETRY* ≡ *DEGAS_CMOT*)

 ⟨ Wising C-Mod Detector Setup #15 ⟩

@#else

 ⟨ Null Detector Setup #16 ⟩

@#endif

Detector views for 1-by-1 box (e.g., from *boxgen*).

```
"readgeometry.f" 1.13 ≡
  @m box_views 5    // To be used as a local dimension

⟨ Box Detector Setup 1.13 ⟩ ≡
  subroutine rg_detector_setup

    implicit none
    de_common
    zn_common
    implicit none

    integer view, num, var, tab_index, spacing, i
    integer grp_views box_views
    real var_min, var_max, mult

    ⟨ Memory allocation interface 0 ⟩

    detector_total_views = box_views
    var_alloc(de_view_points)
    var_alloc(de_view_algorithm)
    var_alloc(de_view_halfwidth)
    var_alloc(de_zone_frgs)

    de_grps = 0
    de_view_size = 0
    var_alloc(de_view_tab)

    if (detector_total_views > 0) then
      do view = 1, detector_total_views
        de_view_algorithm_view = de_algorithm_uniform
        de_view_halfwidth_view = const(3.) * PI / const(1.8, 2) // arbitrary
        vc_set(de_view_points_view, de_view_start, one, zero, half)
      end do

      vc_set(de_view_points_1, de_view_end, half, zero, zero)
      vc_set(de_view_points_2, de_view_end, zero, zero, const(0.25))
      vc_set(de_view_points_3, de_view_end, zero, zero, half)
      vc_set(de_view_points_4, de_view_end, zero, zero, const(0.75))
      vc_set(de_view_points_5, de_view_end, half, zero, one)

      call detector_view_setup

      num = detector_total_views
      var = de_var_unknown
      tab_index = zero
      var_min = zero
      var_max = zero
      mult = zero
      spacing = de_spacing_unknown
      do i = 1, num
        grp_views_i = i
      end do
      call de_grp_init('Chord_integrals', num, var, tab_index, var_min, var_max, mult, spacing,
        grp_views)

      num = 1
```

```
    var = de_var_wavelength
    tab_index = 200
    var_min = const(6558.)
    var_max = const(6564.)
    mult = const(1., -10)
    spacing = de_spacing_linear
    grp_views1 = 3
    call de_grp_init('Halpha_spectrum', num, var, tab_index, var_min, var_max, mult, spacing,
                     grp_views)
end if

return
end
```

This code is used in section 1.12.

Detector views for Wising's UEDGE simulation of C-Mod.

```
"readgeometry.f" 1.14 ≡
  @m ctop_views 35    // To be used as a local dimension.

⟨ Wising C-Mod Detector Setup 1.14 ⟩ ≡
  subroutine rg_detector_setup

    implicit none_f77
    de_common
    zn_common
    implicit none_f90

    integer view, num, var, tab_index, spacing, i
    integer grp_views ctop_views
    real var_min, var_max, mult, r0ha, z0ha, r_end, z_end
    real theta ctop_views

    data (theta(i), i = 1, ctop_views) /const(-1.59500, 1), const(-1.50800, 1), const(-1.41000, 1),
      const(-1.32200, 1), const(-1.22200, 1), const(-1.12700, 1), const(-1.03200, 1),
      const(-9.35501), const(-8.39001), const(-7.46500), const(-6.54001), const(-5.51001),
      const(-4.48001), const(-3.48999), const(-2.50000), const(-1.66699), const(-8.34015,
      -1), const(2.63000, -1), const(1.35999), const(2.50500), const(3.64999), const(4.53000),
      const(5.41000), const(6.33499), const(7.26001), const(8.28500), const(9.31000),
      const(1.02650, 1), const(1.12200, 1), const(1.21700, 1), const(1.31200, 1), const(1.41000,
      1), const(1.50800, 1), const(1.59500, 1), const(1.69100, 1)/

    ⟨ Memory allocation interface 0 ⟩

    detector_total_views = ctop_views + 1    // Spectrum chord is different
    var_alloc(de_view_points)
    var_alloc(de_view_algorithm)
    var_alloc(de_view_halfwidth)
    var_alloc(de_zone_frgs)

    de_grps = 0
    de_view_size = 0
    var_alloc(de_view_tab)

    /* This is the vertex of the C-top array. In the coordinates used by the experimentalists,
       R0 = 0.7517, Z0 = 0.477; in these coordinates, the inner limiter is at Rlim = 0.44 and the top of
       the vacuum vessel is at Zmax = 0.60. Here, Rlim = 0.43, Zmax = 1.30115. */

    @#if (GEOMETRY ≡ WISING_CM0D)
      r0ha = const(7.417, -1)    // Vertex, from C-Mod guys
      z0ha = const(1.17815)

    @#elif (GEOMETRY ≡ DEGAS_CM0D)
      r0ha = const(7.517, -1)    // Shifted for old DEGAS Rlim = 0.44,
      z0ha = const(1.087)    // Zmax = 1.21.

    @#endif
    if (detector_total_views > 0) then
      do view = 1, ctop_views
        de_view_algorithmview = de_algorithm_uniform
        de_view_halfwidthview = half * PI / const(1.8, 2)    // roughly distance between chords
        vc_set(de_view_pointsview, de_view_start, r0ha, zero, z0ha)
        z_end = zero
        r_end = r0ha + (z0ha - z_end) * tan(thetaview * PI / const(1.8, 2))
      enddo
    endif
```

```

    vc_set(de_view_pointsview,de_view_end, r_end, zero, z_end)
end do

view = ctop_views + 1    // Old Spectrum view
de_view_algorithmview = de_algorithm_uniform
de_view_halfwidthview = const(3.) * PI / const(1.8, 2)    // bigger
vc_set(de_view_pointsview,de_view_start, r0ha, zero, z0ha)
z_end = zero    // Use chord no. 1 from above set
r_end = r0ha + (z0ha - z_end) * tan(theta1 * PI / const(1.8, 2))
vc_set(de_view_pointsview,de_view_end, r_end, zero, z_end)

call detector_view_setup

num = ctop_views
var = de_var_unknown
tab_index = zero
var_min = zero
var_max = zero
mult = zero
spacing = de_spacing_unknown
do i = 1, num
    grp_viewsi = i
end do
call de_grp_init('Chord_integrals', num, var, tab_index, var_min, var_max, mult, spacing,
    grp_views)

num = 4    // Old: 1
var = de_var_wavelength
tab_index = 200
var_min = const(6558.)
var_max = const(6564.)
mult = const(1., -10)
spacing = de_spacing_linear
grp_views1 = 1    // Old: ctop_views+1
grp_views2 = 4
grp_views3 = 6
grp_views4 = 9
call de_grp_init('Halpha_spectrum', num, var, tab_index, var_min, var_max, mult, spacing,
    grp_views)
end if

return
end

```

This code is used in section 1.12.

Default detector setup. Just allocates arrays; no views are defined.

```
⟨ Null Detector Setup 1.15 ⟩ ≡  
  subroutine rg_detector_setup  
    implicit_none_f77  
    implicit_none_f90  
  
    call null_detector_setup  
  
    return  
  end
```

This code is used in section 1.12.

subroutine to read inputs from sonnet file.

⟨ Functions and Subroutines 1.2 ⟩ +=

```
subroutine inpt_sonnet(nu, xmin, xmax, zmin, zmax, crx, cry, nx, ny, mx, my, ixcut1,
    ixcut2, iy, cut_type, ix_mirror)
    implicit_none_f77
    implicit_none_f90
    integer ix, iy, ixh, iyh, nxd, nyd, i, ixcut1, ixcut2, iy, nu, mx, my, nx, ny, j, corner_no4,
        cut_type, ix_mirror

    /* for /vesey/Sonnet/cmod.elm.779old */
    parameter (nxd = 120, nyd = 24)

    real crx(mx, my, 0 : 4), cry(mx, my, 0 : 4), pit(nxd, nyd), xmax, xmin, zmax, zmin, dummy1,
        fix_cornerx, fix_cornery
```

@#if 0

```
    real xcorner_old, ycorner_old, xcorner_new, ycorner_new
```

@#endif

```
    character dummy*80
```

```
    xmax = 0.0 · 100D
```

```
    xmin = 1. · 105D
```

```
    zmax = 0.0 · 100D
```

```
    zmin = 1. · 105D
```

```
    nx = nxd
```

```
    ny = nyd    /* read coordinates */
```

```
    read (nu, 3366) dummy
```

```
    read (nu, 3366) dummy
```

```
    read (nu, 3366) dummy
```

```
    read (nu, 3366) dummy
```

```
    do iy = 1, nyd
```

```
        do ix = 1, nxd
```

```
            read (nu, 3333) ixh, iyh, crx(ix, iy, 1), cry(ix, iy, 1), crx(ix, iy, 2), cry(ix, iy, 2)
```

```
            read (nu, 3344) pit(ix, iy), dummy1, dummy1
```

```
            read (nu, 3333) ixh, iyh, crx(ix, iy, 3), cry(ix, iy, 3), crx(ix, iy, 4), cry(ix, iy, 4)
```

```
            read (nu, 3366) dummy
```

```
            /* get max and min of crx and cry */
```

```
            do i = 1, 4
```

```
                if (crx(ix, iy, i) > xmax)
```

```
                    xmax = crx(ix, iy, i)
```

```
                if (cry(ix, iy, i) > zmax)
```

```
                    zmax = cry(ix, iy, i)
```

```
                if (crx(ix, iy, i) < xmin)
```

```
                    xmin = crx(ix, iy, i)
```

```
                if (cry(ix, iy, i) < zmin)
```


```
                    zmin = cry(ix, iy, i)
```

```
            enddo
```

```
        enddo
```

```
    enddo
```

```
    /* the cuts may depend on the number u choose for the difference. i should probably take a
       relative measure. the configuration seems to be:
```



along the x direction (iy=0 along the lower edge of inner PFR) , we compare the bottom corners. these should be equal for adjacent cells until we reach the cut. this is ixcut1. from here as x increases, it traces the outer edge of the core and returns along the lower edge of the outer PFR. this is ixcut2. these two points are the x coordinates of the x-pt if u look at the whole thing in rectangular geometry. */

```

ixcut1 = 0
ixcut2 = 0
do i = 1, nxd - 1
  if ((abs(cry(i, 1, 4) - cry(i + 1, 1, 3)) ≥ 1. · 10-1)) then
    if (ixcut1 ≡ 0) then
      ixcut1 = i
    else
      ixcut2 = i
    goto 5
  endif
endif
enddo
5: continue    /* print *, 'ixcut1,2=', ixcut1,ixcut2 */

/* here we compare cells on either side of the cut in the y direction till we reach the x-point.
   where one corner is common with the core. this gives the y coordinate of x point. */

do i = 1, nyd - 1
  if (abs(cry(ixcut1, i, 2) - cry(ixcut1 + 1, i, 1)) < 1. · 10-4) then
    iycut = i
    go to 6
  endif
endif
enddo
6: continue    /* print*, 'iycut', iycut */

corner_no1 = 3;
corner_no2 = 1;
corner_no3 = 2;
corner_no4 = 4

/* fix mismatch 6 for ix =30 in cmod.elm779old */

i = 30
do j = iycut + 1, nyd
  fix_cornerx = crx(i, j, 2)
  fix_cornerx = cry(i, j, 2)
  call replace_corners(i + 1, j, 2, fix_cornerx, fix_cornerx, corner_no, crx, cry, nx, ny, mx, my)
enddo

@if 0
  /* this is an example of how to exchange corners of two cells if required. here two corners ic1 and
     ic2 of [17,42] are exchanged.
  ic1 = 2

```

```

    ic2 = 3

    xcorner_old = crx17, 42, corner_noic1
    ycorner_old = cry17, 42, corner_noic1
    xcorner_new = crx17, 42, corner_noic2
    ycorner_new = cry17, 42, corner_noic2

    call replace_corners(17, 42, ic1, xcorner_new, ycorner_new, corner_no, crx, cry, nx, ny, mx, my)

    xcorner_new = xcorner_old
    ycorner_new = ycorner_old

    call replace_corners(17, 42, ic2, xcorner_new, ycorner_new, corner_no, crx, cry, nx, ny, mx, my)
@#endif

    call check_data(crx, cry, ixcut1, ixcut2, iycut, nxd, nyd, 3, 1, 2, 4, 3, 1, 2, 4, mx, my,
        null_type, ix_mirror)

@#if 0
    do i = 1, nxd
        do j = 1, nyd
            write(12, 3000) i, j, crx(i, j, 3), crx(i, j, 1), crx(i, j, 2), crx(i, j, 4), crx(i, j, 3)
            write(12, 3000) i, j, cry(i, j, 3), cry(i, j, 1), cry(i, j, 2), cry(i, j, 4), cry(i, j, 3)
        enddo
    enddo
@#endif

3000: format (2(i3, 2x), 5(e12.6, 2x))
3366: format (a)
3344: format (18x, e17.10, 14x, e17.10, 1x, e17.10)    // 333 format(19x,i3,1x,i3,4x,e16.10,1x,e16.10)
3333: format (19x, i3, 1x, i3, 4x, e17.10, 1x, e17.10, 8x, e17.10, 1x, e17.10)

    return
end

```

replace corner_i of cell ix,iy with [xcorner_{new}, ycorner_{new}].

⟨ Functions and Subroutines 1.2 ⟩ +=

```

subroutine replace_corners(ix, iy, corneri, xcorner_new, ycorner_new, corner_no, x, y, nx, ny,
    mx, my)
    implicit_none_f77
    implicit_none_f90
    integer ix, iy, corneri, corner_no4, nx, ny, mx, my
    real xcorner_new, ycorner_new, x(mx, my, 0 : 4), y(mx, my, 0 : 4)

    if (corneri  $\equiv$  1) then
        xix, iy, corner_no1 = xcorner_new
        yix, iy, corner_no1 = ycorner_new
        if (iy  $\equiv$  1)
            goto 1
        xix, iy-1, corner_no2 = xcorner_new
        yix, iy-1, corner_no2 = ycorner_new
    1: if (ix  $\equiv$  1  $\vee$  iy  $\equiv$  1)
        goto 2
        xix-1, iy-1, corner_no3 = xcorner_new
        yix-1, iy-1, corner_no3 = ycorner_new
    2: if (ix  $\equiv$  1)
        goto 9
        xix-1, iy, corner_no4 = xcorner_new
        yix-1, iy, corner_no4 = ycorner_new
    elseif (corneri  $\equiv$  2) then
        xix, iy, corner_no2 = xcorner_new
        yix, iy, corner_no2 = ycorner_new
        if (ix  $\equiv$  1)
            goto 3
        xix-1, iy, corner_no3 = xcorner_new
        yix-1, iy, corner_no3 = ycorner_new
    3: if (ix  $\equiv$  1  $\vee$  iy  $\equiv$  ny)
        goto 4
        xix-1, iy+1, corner_no4 = xcorner_new
        yix-1, iy+1, corner_no4 = ycorner_new
    4: if (iy  $\equiv$  ny)
        goto 9
        xix, iy+1, corner_no1 = xcorner_new
        yix, iy+1, corner_no1 = ycorner_new
    elseif (corneri  $\equiv$  3) then
        xix, iy, corner_no3 = xcorner_new
        yix, iy, corner_no3 = ycorner_new
        if (iy  $\equiv$  ny)
            goto 5
        xix, iy+1, corner_no4 = xcorner_new
        yix, iy+1, corner_no4 = ycorner_new
    5: if (ix  $\equiv$  nx  $\vee$  iy  $\equiv$  ny)
        goto 6
        xix+1, iy+1, corner_no1 = xcorner_new
        yix+1, iy+1, corner_no1 = ycorner_new
    6: if (ix  $\equiv$  nx)

```

```

      goto 9
       $x_{ix+1}, iy, corner\_no_2 = xcorner\_new$ 
       $y_{ix+1}, iy, corner\_no_2 = ycorner\_new$ 
elseif ( $corneri \equiv 4$ ) then
       $x_{ix}, iy, corner\_no_4 = xcorner\_new$ 
       $y_{ix}, iy, corner\_no_4 = ycorner\_new$ 
      if ( $ix \equiv nx$ )
      goto 7
       $x_{ix+1}, iy, corner\_no_1 = xcorner\_new$ 
       $y_{ix+1}, iy, corner\_no_1 = ycorner\_new$ 
7: if ( $ix \equiv nx \vee iy \equiv 1$ )
      goto 8
       $x_{ix+1}, iy-1, corner\_no_2 = xcorner\_new$ 
       $y_{ix+1}, iy-1, corner\_no_2 = ycorner\_new$ 
8: if ( $iy \equiv 1$ )
      goto 9
       $x_{ix}, iy-1, corner\_no_3 = xcorner\_new$ 
       $y_{ix}, iy-1, corner\_no_3 = ycorner\_new$ 
endif
9: return
end

```

input routine for uedge data

⟨Functions and Subroutines 1.2⟩ +≡

```

subroutine inpt_uedge(nu, nx, ny, ixpt1, ixpt2, iysptrx, rmu, zmu, m1x, m1y, null_type, ix_mirror)
  implicit none f77
  implicit none f90
  integer m1x, m1y    // parameter (mx=120,my=50)
  real rmum1x, m1y, 0:4, zmum1x, m1y, 0:4
  integer ix, iy, i, nu, nx, ny, ixpt1, ixpt2, iysptrx, ix_mirror, null_type

  read (nu, *)
  read (nu, *) nx
  read (nu, *) ny
  read (nu, *) ixpt1
  read (nu, *) ixpt2
  read (nu, *) iysptrx
  read (nu, *) SP(((rmu(ix, iy, i), ix = 1, nx), iy = 1, ny), i = 0, 4)
  read (nu, *) SP(((zmu(ix, iy, i), ix = 1, nx), iy = 1, ny), i = 0, 4)
  /* its a good idea to check that data before going further */

  call check_data(rmu, zmu, ixpt1, ixpt2, iysptrx, nx, ny, 1, 3, 4, 2, 1, 3, 4, 2, m1x, m1y,
    null_type, ix_mirror)
  return
end

```

general routine to check consistency of data for degas2 geometry.

⟨ Functions and Subroutines 1.2 ⟩ +=

```

subroutine check_data(x, y, ixcut1, ixcut2, iycut, nx, ny, xcorner1, xcorner2, xcorner3,
    xcorner4, ycorner1, ycorner2, ycorner3, ycorner4, m2x, m2y, null_type, ix_mirror)
    implicit_none_f77
    implicit_none_f90
    integer m2x, m2y
    real xm2x, m2y, 0:4, ym2x, m2y, 0:4 // input
    integer ix, iy, nx, ny, ixcut1, ixcut2, iycut, ix_mirror, null_type
    integer xcorner1, xcorner2, xcorner3, xcorner4, ycorner1, ycorner2, ycorner3, ycorner4
    logical single_null, double_null

    single_null =  $\mathcal{F}$ 
    double_null =  $\mathcal{F}$ 
    if (null_type  $\equiv$  1) then
        single_null =  $\mathcal{T}$ 
    elseif (null_type  $\equiv$  2) then
        double_null =  $\mathcal{T}$ 
        ix_mirror = nx / 2
    else
        print *, 'unknown_null_type'
        assert( $\mathcal{F}$ )
    endif

    /* —— check continuity of points —— check end points along x and top to bottom along y */
    if (ixcut1 > 0) then
        do ix = 1, ixcut1 - 1
            do iy = 1, iycut
                if (x(ix, iy, xcorner3)  $\neq$  x(ix + 1, iy, xcorner2)  $\vee$  x(ix, iy, xcorner4)  $\neq$  x(ix + 1, iy,
                    xcorner1)  $\vee$  y(ix, iy, ycorner3)  $\neq$  y(ix + 1, iy, ycorner2)  $\vee$  y(ix, iy,
                    ycorner4)  $\neq$  y(ix + 1, iy, ycorner1)) then
                    print *, 'mismatch_1, ix, iy', ix, iy, ix + 1, iy
                    print *, 'corners_of_adjacent_cells_along_x_dont_match'
                    stop
                endif
            if (iy  $\equiv$  iycut)
                goto 6
            if (x(ix, iy, xcorner2)  $\neq$  x(ix, iy + 1, xcorner1)  $\vee$  x(ix, iy, xcorner3)  $\neq$  x(ix, iy + 1, xcorner4))
                then
                    print *, 'mismatch_2, ix, iy', ix, iy, ix, iy + 1
                    print *, 'corners_of_top_of_lower_cell_and_bottom_of_upper_\
                        \cell_dont_match'
                    stop
                endif
        enddo
        6: continue
    enddo
    enddo
    end if // match end points along x and top to bottom along y from cut1 to cut2 for double nulls
    the mirror may come halfway in between, so dont check for continuity across it.

    do ix = max(1, ixcut1 + 1), ixcut2 - 1
        if (double_null  $\wedge$  ix  $\equiv$  ix_mirror)
            goto 70

```

```

do iy = 1, iycut
  if (x(ix, iy, xcorner3) ≠ x(ix + 1, iy, xcorner2) ∨ x(ix, iy, xcorner4) ≠ x(ix + 1, iy,
    xcorner1) ∨ y(ix, iy, ycorner3) ≠ y(ix + 1, iy, ycorner2) ∨ y(ix, iy,
    ycorner4) ≠ y(ix + 1, iy, ycorner1)) then
    print *, 'mismatch_3, ix, iy', ix, iy, ix + 1, iy
    print *, 'corners_of_adjacent_cells_along_x_dont_match\
      \between_xcut1_and_xcut2'
    stop
  endif
  if (iy ≡ iycut)
    goto 7
  if (x(ix, iy, xcorner2) ≠ x(ix, iy + 1, xcorner1) ∨ x(ix, iy, xcorner3) ≠ x(ix, iy + 1, xcorner4))
    then
      print *, 'mismatch_4, ix, iy', ix, iy, ix, iy + 1
      print *, 'corners_of_top_of_lower_cell_and_bottom_of_upper\
        \cell_dont_match_between_xcut1_and_xcut2'
      stop
    endif
7: continue
enddo
70: continue
enddo

if (ixcut1 > 0) then /* match across ixcut1 and ixcut2 in the x direction */
  do iy = 1, iycut
    if (x(ixcut1, iy, xcorner3) ≠ x(ixcut2 + 1, iy, xcorner2) ∨ x(ixcut1, iy,
      xcorner4) ≠ x(ixcut2 + 1, iy, xcorner1)) then
      print *, 'mismatch_5, ixcut1, iy', ixcut1, iy
      print *, 'cells_on_one_side_of_the_xcut1_and_other_side_of\
        \of_xcut2_along_x_dont_match'
      stop
    endif
  enddo
end if

/* match beyond ixcut1 along x and y */
do ix = ixcut2 + 1, nx - 1
  do iy = 1, iycut
    if (x(ix, iy, xcorner3) ≠ x(ix + 1, iy, xcorner2) ∨ x(ix, iy, xcorner4) ≠ x(ix + 1, iy,
      xcorner1) ∨ y(ix, iy, ycorner3) ≠ y(ix + 1, iy, ycorner2) ∨ y(ix, iy,
      ycorner4) ≠ y(ix + 1, iy, ycorner1)) then
      print *, 'mismatch_6, ix, iy', ix, iy, ix + 1, iy
      print *, 'corners_of_adjacent_cells_along_x_after_xcut2\
        \dont_match'
      stop
    endif
  if (iy ≡ iycut)
    goto 8
  if (x(ix, iy, xcorner2) ≠ x(ix, iy + 1, xcorner1) ∨ x(ix, iy, xcorner3) ≠ x(ix, iy + 1, xcorner4))
    then
      print *, 'mismatch_7, ix, iy', ix, iy, ix, iy + 1
      print *, 'corners_of_top_of_lower_cell_and_bottom_of_upper\
        \cell_after_xcut2_dont_match'

```

```

    stop
  endif
8: continue
enddo
enddo /* beyond irect in x and y direction */
do ix = 1, nx - 1
  if (double_null  $\wedge$  ix  $\equiv$  ix_mirror)
    goto 90
  do iy = irect + 1, ny
    if (x(ix, iy, xcorner3)  $\neq$  x(ix + 1, iy, xcorner2)  $\vee$  x(ix, iy, xcorner4)  $\neq$  x(ix + 1, iy,
      xcorner1)  $\vee$  y(ix, iy, ycorner3)  $\neq$  y(ix + 1, iy, ycorner2)  $\vee$  y(ix, iy,
      ycorner4)  $\neq$  y(ix + 1, iy, ycorner1)) then
      print *, 'mismatch_8, ix, iy', ix, iy, ix + 1, iy
      print *, 'corners_of_adjacent_cells_along_x_after_irect\
        \dont_match'
      stop
    endif
    if (iy  $\equiv$  ny)
      goto 9
    if (x(ix, iy, xcorner2)  $\neq$  x(ix, iy + 1, xcorner1)  $\vee$  x(ix, iy, xcorner3)  $\neq$  x(ix, iy + 1, xcorner4))
      then
        print *, 'mismatch_9, ix, iy', ix, iy, ix + 1, iy + 1
        print *, 'corners_of_top_of_lower_cell_and_bottom_of_upper\
          \cell_after_irect_dont_match'
        stop
      endif
    endif
9: continue
enddo
enddo
return
end

```

2 INDEX

abs: 1.16.
 assert: 1.3, 1.4, 1.5, 1.6, 1.7, 1.8, 1.9, 1.19.
 b: 1.3.
 boltzmanns_const: 1.3, 1.11.
 boundaries_neighbors: 1.3.
 BOX: 1.2, 1.12.
 box_views: 1.13.
 boxgen: 1.2, 1.13.
 check_data: 1.16, 1.18, 1.19.
 check_geometry: 1.3.
 command_arg: 1.2.
 complete: 1.3, 1.4.
 const: 1.3, 1.5, 1.11, 1.13, 1.14.
 corner_no: 1.16, 1.17.
 corneri: 1.17.
 crx: 1.16.
 cry: 1.16.
 ctop_views: 1.14.
 current_material: 1.3, 1.4, 1.5, 1.7, 1.8, 1.9, 1.10.
 current_recyc_coef: 1.3, 1.4, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
 current_stratum: 1.3, 1.4, 1.5, 1.7, 1.9.
 current_temperature: 1.3, 1.4, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
 datafile_diskin: 1.3.
 datafilename: 1.3.
 de_algorithm_uniform: 1.13, 1.14.
 de_common: 1.13, 1.14.
 de_grp_init: 1.13, 1.14.
 de_grps: 1.13, 1.14.
 de_spacing_linear: 1.13, 1.14.
 de_spacing_unknown: 1.13, 1.14.
 de_var_unknown: 1.13, 1.14.
 de_var_wavelength: 1.13, 1.14.
 de_view_algorithm: 1.13, 1.14.
 de_view_end: 1.13, 1.14.
 de_view_halfwidth: 1.13, 1.14.
 de_view_points: 1.13, 1.14.
 de_view_size: 1.13, 1.14.
 de_view_start: 1.13, 1.14.
 de_view_tab: 1.13, 1.14.
 de_zone_frags: 1.13, 1.14.
 declare_varp: 1.3.
 decompose_polygon: 1.3, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
 define_dimen: 1.3.
 define_sector: 1.3.
 define_sector_exit: 1.3.

define_sector_plasma: 1.3.
 define_sector_target: 1.3.
 define_sector_vacuum: 1.3.
 define_sector_wall: 1.3.
 define_varp: 1.3.
 degas: 1.3.
 DEGAS_CM0D: 1.2, 1.3, 1.12, 1.14.
 denehvt: 1.5.
 detector_total_views: 1.13, 1.14.
 detector_view_setup: 1.13, 1.14.
 diag_grp_init: 1.3.
 diag_sector_setup: 1.3.
 diskini: 1.3.
 double_null: 1.3, 1.8, 1.9, 1.10, 1.19.
 dummy: 1.16.
 dummy1: 1.16.
 e: 1.3.
 electron_charge: 1.11.
 end_detectors: 1.3.
 end_sectors: 1.3.
 eof: 1.3.
 epsilon: 1.5.
 erase_geometry: 1.3.
 face1: 1.3.
 file: 1.3.
 FILE: 1.
 FILELEN: 1.2, 1.3.
 filename: 1.2, 1.3.
 find_poly_zone: 1.3.
 fix_cornerx: 1.16.
 fix_corneri: 1.16.
 FLOAT: 1.3.
 form: 1.3.
 frabsorb: 1.4.
 GENERAL: 1.2.
 geometry: 1.
 GEOMETRY: 1.2, 1.3, 1.7, 1.12, 1.14.
 geometry_symmetry_cylindrical: 1.3.
 geometry_symmetry_oned: 1.3.
 geometry_symmetry_plane: 1.3.
 GEOMTRY: 1.2.
 gi_common: 1.3.
 gi_ext: 1.3.
 grid_sense: 1.3, 1.5, 1.7.
 grid_starth: 1.3, 1.5, 1.6.
 grid_startv: 1.3, 1.5, 1.6.
 grid_stoph: 1.3, 1.5, 1.6.
 grid_stopv: 1.3, 1.5, 1.6.
 gridx: 1.5, 1.6.
 gridz: 1.5, 1.6.
 grp_sector: 1.3.

- grp_sectors1*: [1.3](#).
grp_views: [1.13](#), [1.14](#).
h: [1.3](#).
half: [1.13](#), [1.14](#).
i: [1.3](#), [1.13](#), [1.14](#), [1.16](#), [1.18](#).
ic1: [1.16](#).
ic2: [1.16](#).
implicit_none_f77: [1.2](#), [1.3](#), [1.13](#), [1.14](#), [1.15](#), [1.16](#),
[1.17](#), [1.18](#), [1.19](#).
implicit_none_f90: [1.2](#), [1.3](#), [1.13](#), [1.14](#), [1.15](#), [1.16](#),
[1.17](#), [1.18](#), [1.19](#).
increment_num_polygon: [1.2](#), [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#),
[1.10](#), [1.11](#).
init_geometry: [1.3](#), [1.7](#).
inpt: [1.3](#).
inpt_sonnet: [1.3](#), [1.16](#).
inpt_uedge: [1.3](#), [1.18](#).
INT: [1.3](#).
int_lookup: [1.3](#).
integer: [1.1](#).
ix: [1.16](#), [1.17](#), [1.18](#), [1.19](#).
ix_mirror: [1.3](#), [1.8](#), [1.9](#), [1.10](#), [1.16](#), [1.18](#), [1.19](#).
ixcut1: [1.16](#), [1.19](#).
ixcut2: [1.16](#), [1.19](#).
ixh: [1.16](#).
ixpt1: [1.3](#), [1.8](#), [1.9](#), [1.10](#), [1.18](#).
ixpt2: [1.3](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#), [1.18](#).
iy: [1.16](#), [1.17](#), [1.18](#), [1.19](#).
iycut: [1.16](#), [1.19](#).
iyh: [1.16](#).
iysp: [1.3](#).
iysptrx: [1.3](#), [1.18](#).
j: [1.3](#), [1.16](#).
j1: [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
j2: [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
keyword: [1.3](#).
kumat: [1.4](#).
kzone1: [1.5](#).
kzone2: [1.5](#).
len: [1.3](#).
length: [1.3](#).
line: [1.3](#), [1.4](#), [1.5](#), [1.6](#), [1.7](#).
LINELEN: [1.3](#).
loop1: [1.3](#).
loop2: [1.3](#).
loop3: [1.3](#).
ma_check: [1.3](#).
ma_common: [1.3](#).
ma_lookup: [1.3](#), [1.4](#), [1.9](#), [1.11](#).
max: [1.19](#).
max_corner: [1.3](#), [1.7](#).
mem_delta: [1.2](#).
min_corner: [1.3](#), [1.7](#).
mindensity: [1.3](#), [1.5](#).
minx: [1.3](#), [1.5](#).
minz: [1.3](#), [1.5](#).
mod: [1.4](#).
mult: [1.3](#), [1.13](#), [1.14](#).
mx: [1.3](#), [1.16](#), [1.17](#).
my: [1.3](#), [1.16](#), [1.17](#).
m1x: [1.18](#).
m1y: [1.18](#).
m2x: [1.19](#).
m2y: [1.19](#).
n: [1.3](#).
namelist: [1.1](#).
nc_read_materials: [1.2](#).
new_zone_type: [1.3](#).
next_surface: [1.2](#), [1.3](#).
next_token: [1.3](#), [1.4](#), [1.5](#), [1.6](#), [1.7](#).
nosegsxz: [1.3](#), [1.4](#), [1.9](#).
nowals: [1.3](#).
nsectors: [1.3](#).
nu: [1.3](#), [1.16](#), [1.18](#).
null_detector_setup: [1.15](#).
null_type: [1.3](#), [1.16](#), [1.18](#), [1.19](#).
num: [1.3](#), [1.6](#), [1.13](#), [1.14](#).
num_points: [1.2](#), [1.3](#), [1.4](#).
num_polygon: [1.2](#), [1.3](#), [1.4](#), [1.5](#), [1.6](#), [1.7](#), [1.8](#), [1.9](#),
[1.10](#), [1.11](#).
nx: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.11](#), [1.16](#), [1.17](#), [1.18](#), [1.19](#).
nxd: [1.16](#).
ny: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.11](#), [1.16](#), [1.17](#), [1.18](#), [1.19](#).
nyd: [1.16](#).
one: [1.3](#), [1.7](#), [1.13](#).
p: [1.3](#).
parse_string: [1.3](#).
pfr_recyc: [1.3](#), [1.11](#).
PI: [1.3](#), [1.7](#), [1.13](#), [1.14](#).
pit: [1.16](#).
plot: [1.3](#), [1.5](#).
points_ind: [1.3](#).
points_ind0: [1.3](#).
poly_ind: [1.3](#).
polygon_material: [1.2](#), [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#),
[1.11](#).
polygon_points: [1.2](#), [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#),
[1.11](#).
polygon_recyc_coef: [1.2](#), [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#),
[1.11](#).

- polygon_segment*: 1.2, 1.3, 1.4, 1.8, 1.9, 1.10, 1.11.
polygon_stratum: 1.2, 1.3, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
polygon_temperature: 1.2, 1.3, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
polygon_volume: 1.3, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
polygon_x: 1.2, 1.3, 1.4, 1.5, 1.6, 1.7, 1.8, 1.9, 1.10, 1.11.
polygon_zone: 1.2, 1.3, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
r_end: 1.14.
read_integer: 1.3, 1.4, 1.5, 1.6.
read_real: 1.3, 1.7.
read_string: 1.3.
readfilenames: 1.2.
readgeometry: 1.2.
readgeomfile: 1.2, 1.3.
real_undef: 1.3.
replace_corners: 1.16, 1.17.
rg_detector_setup: 1.3, 1.13, 1.14, 1.15.
rm: 1.3, 1.7, 1.8, 1.9, 1.10, 1.11.
rmu: 1.18.
r0ha: 1.14.

sc_check: 1.3.
sc_common: 1.3.
sc_diag_spacing_unknown: 1.3.
sc_diag_unknown: 1.3.
sector_surface: 1.3.
sector1: 1.3.
sector2: 1.3.
segment: 1.3.
segment1: 1.3.
set_zn_min_max: 1.3, 1.5, 1.7, 1.8, 1.9, 1.10, 1.11.
single_null: 1.3, 1.8, 1.9, 1.10, 1.19.
skip: 1.5.
sonnet: 1.3, 1.7.
SP: 1.3, 1.18.
spacing: 1.3, 1.13, 1.14.
st_decls: 1.3.
status: 1.3.
stderr: 1.3, 1.5.
stdout: 1.3, 1.5.
steph: 1.3, 1.6.
stepv: 1.3, 1.6.
stratum: 1.3.
symmetry: 1.3, 1.7.

tab_index: 1.3, 1.13, 1.14.
tan: 1.14.
target_recyc: 1.3, 1.11.
temp_material: 1.3, 1.4.
test_vec_1: 1.3, 1.7.
test_vec_2: 1.3, 1.7.

test_vec_3: 1.3, 1.7.
theta: 1.14.
trim: 1.3.
trx: 1.3.
twall: 1.4.
two: 1.3, 1.7.

uedge: 1.3, 1.7, 1.8, 1.9, 1.10.
UEDGE-RECT-SLAB: 1.2, 1.3, 1.7.
unit: 1.3.
universal_cell: 1.3, 1.7.

v: 1.3.
vacuum: 1.3, 1.7.
var: 1.3, 1.13, 1.14.
var_alloc: 1.13, 1.14.
var_max: 1.3, 1.13, 1.14.
var_min: 1.3, 1.13, 1.14.
var_realloca: 1.2, 1.3.
vc_cross: 1.7.
vc_decl: 1.3.
vc_decls: 1.3.
vc_product: 1.7.
vc_set: 1.5, 1.7, 1.13, 1.14.
view: 1.13, 1.14.
vol: 1.3, 1.7.
vol_test: 1.3, 1.5.
vola: 1.3.

wall_direction: 1.3, 1.4.
wall_no: 1.3, 1.4.
wall_recyc: 1.3, 1.11.
wall_start: 1.3, 1.4.
wall_stop: 1.3, 1.4.
wallfile: 1.7.
wallfile_diskin: 1.3.
wallfilename: 1.3.
web: 1.
WISING-CMOD: 1.2, 1.12, 1.14.
write_geometry: 1.3.

x: 1.17, 1.19.
x_test: 1.3, 1.5.
xcorner_new: 1.16, 1.17.
xcorner_old: 1.16.
xcorner1: 1.3, 1.7, 1.8, 1.9, 1.10, 1.11, 1.19.
xcorner2: 1.3, 1.7, 1.8, 1.9, 1.11, 1.19.
xcorner3: 1.3, 1.7, 1.8, 1.9, 1.11, 1.19.
xcorner4: 1.3, 1.7, 1.8, 1.9, 1.10, 1.11, 1.19.
xmax: 1.3, 1.7, 1.8, 1.9, 1.11, 1.16.
xmin: 1.3, 1.7, 1.8, 1.9, 1.11, 1.16.
xwall: 1.3, 1.4, 1.9.
xz_ind: 1.3.
xz_index: 1.2, 1.3.

y: [1.17](#), [1.19](#).
ycorner_new: [1.16](#), [1.17](#).
ycorner_old: [1.16](#).
ycorner1: [1.19](#).
ycorner2: [1.19](#).
ycorner3: [1.19](#).
ycorner4: [1.19](#).
yhat: [1.3](#), [1.7](#).
ymax: [1.3](#), [1.7](#).
ymin: [1.3](#), [1.7](#).

z_end: [1.14](#).
zcorner1: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
zcorner2: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.11](#).
zcorner3: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.11](#).
zcorner4: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
zero: [1.3](#), [1.4](#), [1.5](#), [1.7](#), [1.13](#), [1.14](#).
zm: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
zmax: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.11](#), [1.16](#).
zmin: [1.3](#), [1.7](#), [1.8](#), [1.9](#), [1.11](#), [1.16](#).
zmu: [1.18](#).
zn_common: [1.3](#), [1.13](#), [1.14](#).
zn_exit: [1.3](#), [1.10](#), [1.11](#).
zn_index: [1.5](#), [1.7](#).
zn_num: [1.3](#).
zn_plasma: [1.3](#), [1.5](#), [1.7](#).
zn_solid: [1.3](#), [1.8](#), [1.9](#), [1.11](#).
zn_type: [1.3](#).
zn_type_set: [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
zn_vacuum: [1.3](#), [1.9](#).
zn_volume: [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
zone: [1.3](#), [1.5](#), [1.7](#), [1.8](#), [1.9](#), [1.10](#), [1.11](#).
zone_center: [1.5](#), [1.7](#).
zone1: [1.3](#).
zone2: [1.3](#).
zwall: [1.3](#), [1.4](#), [1.9](#).
z0ha: [1.14](#).

⟨Box Detector Setup 1.13⟩ Used in section 1.12.
⟨Core Boundary Section 1.10⟩ Used in section 1.7.
⟨Edge Keyword 1.6⟩ Used in section 1.3.
⟨Functions and Subroutines 1.2, 1.3, 1.12, 1.16, 1.17, 1.18, 1.19⟩ Used in section 1.1.
⟨Grid Keyword 1.5⟩ Used in section 1.3.
⟨Memory allocation interface 0⟩ Used in sections 1.14, 1.13, and 1.3.
⟨Mesh Keyword 1.7⟩ Used in section 1.3.
⟨Not-Vacuum Boundary Section 1.8⟩ Used in section 1.7.
⟨Null Detector Setup 1.15⟩ Used in section 1.12.
⟨UERS Boundary Section 1.11⟩ Used in section 1.7.
⟨Vacuum Boundary Section 1.9⟩ Used in section 1.7.
⟨Wall Keyword 1.4⟩ Used in section 1.3.
⟨Wising C-Mod Detector Setup 1.14⟩ Used in section 1.12.
⟨combal.h 0⟩ Used in section 1.3.
⟨comflg.h 0⟩ Used in section 1.3.
⟨comgeo.h 0⟩ Used in section 1.3.
⟨compar.h 0⟩ Used in section 1.3.
⟨compls.h 0⟩ Used in section 1.3.
⟨comrat.h 0⟩ Used in section 1.3.
⟨comrfl.h 0⟩ Used in section 1.3.
⟨comst.h 0⟩ Used in section 1.3.
⟨comstat.h 0⟩ Used in section 1.3.
⟨comsv.h 0⟩ Used in section 1.3.
⟨pardef.h 0⟩ Used in section 1.3.

COMMAND LINE: "fweave -f -i! -W[-ykw700 -ytw40000 -j -n/
/u/dstotler/degas2/src/readgeometry.web".

WEB FILE: "/u/dstotler/degas2/src/readgeometry.web".

CHANGE FILE: (none).

GLOBAL LANGUAGE: FORTRAN.