Steps to follow for HR account unlock in Oracle 19c

0. connect as sysdba account
CMD>SQLPLUS
USERNAME: SYS AS SYSDBA
PASSWORD: 123

1. Get information about database containers:
--show current containers:
SHOW CON_ID

--information about all containers
SELECT NAME, CON_ID, DBID, CON_UID, GUID FROM V$CONTAINERS ORDER BY CON_ID;

--information about pdbs
SELECT PDB_ID, PDB_NAME, STATUS FROM DBA_PDBS ORDER BY PDB_ID;

--show open status of pdbs
SELECT NAME, OPEN_MODE, RESTRICTED, OPEN_TIME FROM V$PDBS;

2. Change database status to open mode
ALTER PLUGGABLE DATABASE ORCLPDB OPEN;

3. Switch to pluggable database:
ALTER SESSION SET CONTAINER=ORCLPDB;

4. [NOT REQUIRED IF ONLY HR IS NEEDED] Create a new user for orclpdb and grant access;
CREATE USER LAB IDENTIFIED BY 123 DEFAULT TABLESPACE USERS ACCOUNT UNLOCK;

GRANT DBA TO LAB;

5. Save database state of pluggable db;
ALTER PLUGGABLE DATABASE SAVE STATE;

6. Unlock hr user:
ALTER USER HR IDENTIFIED BY HR ACCOUNT UNLOCK;

7. CONFIGURE tnsnames.ora file

C:\oracle19c\WINDOWS.X64_193000_db_home\network\admin

```
ORCLPDB =
 (DESCRIPTION =
  (ADDRESS_LIST =
   (ADDRESS = (PROTOCOL = TCP)(HOST = localhost)(PORT = 1521))
  )
  (CONNECT_DATA =
   (SERVICE_NAME = orclpdb)
  )
 )
```

Add TNS ORCLPDB like below-highlighted block

```
ORCL =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = localhost)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = orcl)
    )
  )
ORCLPDB =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = localhost)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = orclpdb)
    )
  )
```

Open CMD as Administrator and execute below command

```
C:\>lsnrctl reload
```

8. Test login

open sqlplus
username: hr@orclpdb
password: hr

username: lab@orclpdb
password: 123