

I/O Redirect

Redirecting standard o/p and error

1. Create a file called output.txt that contains the output of the date command
Note : run date cmd in the terminal and observe the o/p
2. Append the current user's name to a file called output.txt (use whoami)
3. Append the host name to a file called output.txt (use hostname)
4. Attempt to list a non-existent directory and redirect the error message to error.log
5. Run a cmd to get output and error and redirect only the output to file and display the error
 - a. Use ls -l existingdir non-existentfile → e.g. `ls -l CEO dir1 2>&1 > error.log`
 - b. Cat existingfile non-existentfile
6. Run a cmd to get output and error and redirect only the error to file and display the output
 - a. Use ls -l existingdir non-existentfile → e.g. `ls -l CEO dir1 2>error.log`
 - b. Cat existingfile non-existentfile
7. Run a cmd to get output and error and redirect both to combined.txt
 - a. Use ls -l existingdir non-existentfile → e.g. `ls -l CEO dir1 > combined.txt 2>&1`
 - b. Cat existingfile non-existentfile

Redirecting standard i/p

8. Create a file with numbers. Read the file using cat cmd .
9. Read the same file using cat and i/p redirect e.g cat < file.txt
10. Read the file /etc/passwd file and display only last 4 lines using i/p redirect and o/p to a file

Filters or text processor cmds.

1. Tee

- a. To output.txt echo "Hello world" using tee cmd
- b. Run the cmd uname -a and append it to output.txt using tee -a cmd
- c. Run tac filename | tee Newfile | tac and observe. (tac is opposite of cat)

2. Grep

- a. Create a text file named sample.txt with the following content


```
Hello World
Welcome to the world of Linux
Learning commands is fun
```
- b. Use grep cmd to find word 'world'
- c. Use grep cmd to find word 'world' case-insensitive
- d. Use grep to count how many lines contain the word "Linux" in sample.txt (use grep -c "keyword" filename)
- e. Use grep to display lines from sample.txt that do **not** contain the word "fun" (option -v)
- f. Use egrep (extended grep) to find world and fun from sample.txt
- g. Use ls -l | grep "keyword"
- h. Cat /etc/passwd | grep "yourname"
- i. Create a directory named test_dir and place sample.txt and more_sample.txt inside it. Use grep to search for the word "World" recursively in the directory using grep -r "World" test_dir/
- j. Try out the options grep -An , grep -Bn and grep -Cn

3. Sort

- i. Create a file with some contents and perform the following
- ii. Sort Filename , sort -r Filename ,sort -f filename (-f = ignore case)
- iii. Sort -k1 Filename (display column 1)
- iv. Sort -nk3 Filename (sort numeric data and display col 3)
- v. Sort -u Filename (sort and uniq)
- vi. Ls -l | sort -k9 | uniq
- vii. Use cat file1 file2 | sort (enter some relevant text in file1 and file2)

4. Uniq

- i. Create a file with some duplicate contents and perform the following
- ii. Uniq filename
- iii. Uniq -c filename
- iv. Use it with sort cmd and redirect the o/p to a file. (sort filename | uniq > filename)

5. WC

- i. Find the no of lines ,no of words and no. of chars in a file of your choice using wc cmd using wc filename ,wc -l ,wc -w ,wc -m

6. Cut

- i. Create a text file named data.txt with the following content

John,25,Engineer

Alice,30,Designer

Bob,22,Developer

Charlie,28,Manager

- ii. Use cut to extract and display the first field.use -d and -f option
- iii. Use cut to extract and display the names and ages (first and second fields)
- iv. Use cut to display the first 5 characters of each line in data.txt
- v. Use cut to extract the username in /etc/passwd file

7. Awk

- i. awk '{print \$1}' file = List 1st field from a file
- ii. ls -l | awk '{print \$1,\$3}' = List 1 and 3rd field of ls -l output
- iii. ls -l | awk '{print \$NF}' = Last field of the output
- iv. awk '/keyword/ {print}' file = Search for a specific word
- v. echo "Hello Tom" | awk '{\$2="Adam"; print \$0}' = Replace Tom with Adam