IntelliHire AI

Resume-based job recommendation, adaptive interviewing with a digital interviewer, and evidence-based competency feedback

---

Group 36 · AIS08 FT · Course start 17 August 2026
Du Ying Zeng Andrew (A0264354A)
Guo Lexin (A0356193X)
Luo Ziyu (A0351358B)
Sun Zhiquan (A0354826W)
Wang Shunyao (A0355565U)

Intelligent Reasoning Systems Practice Module, NUS-ISS, October 2026
Repository: github.com/Fujizzz/IRS-PM-2026-08-17-AIS08FT-GRP-9-IntelliHire-AI

Contents

1 Executive Summary

2 Introduction

2.1 Project Overview

2.2 Why This Matters

2.3 Goals and Research Questions

3 Project Background and Market Context

3.1 The Problem in Practice

3.2 Market Landscape

3.3 Target Users and Business Model

4 Literature Review

4.1 Structured Interviews and Rating Scales

4.2 Retrieval-Augmented Generation and Agents

4.3 Limits of LLM-as-a-Judge

4.4 Job Recommendation

4.5 Virtual Interviewers

5 Project Scope

5.1 What We Built

5.2 What We Deliberately Left Out

5.3 Changes Since the Proposal

6 Data and Knowledge Preparation

6.1 Resume Extraction and Preparation

6.2 The Technical Corpus

6.3 Privacy in Data Preparation

6.4 Recommendation and Completion Data

7 System Design

7.1 Platform Architecture and Module Interfaces

7.2 Choosing the Reasoning Techniques

7.3 Job Recommendation and Matching Research

7.4 The Interview Loop

7.5 Evidence-First Scoring

7.6 Retrieval for Technical Questions

7.7 Answer Completion and the Digital Interviewer

7.8 AI Safety Review

7.9 Platform State and Durable Result Delivery

8 Implementation

8.1 Technology Stack

8.2 Deployment

8.3 Challenges and How We Solved Them

9 Results and Evaluation

9.1 Platform Validation and Service Performance

9.2 Scoring Quality

9.3 Interview Behaviour

9.4 Retrieval

9.5 Job Recommendation and Matching Evaluation

9.6 Answer Completion Detection

9.7 AI Safety Review

9.8 Resume Processing and Isolation

10 Future Work

11 Conclusion

Appendix A Project Proposal

Appendix B Mapping of System Functions to Course Modules

Appendix C Installation and User Guide

C.1 Installation

C.2 Using the System

Appendix D Note on the Use of AI Tools

Appendix E Project Contributions

E.1 Acknowledgements

Appendix F References

1 Executive Summary

Preparing for a technical interview usually means doing two things that have little to do with each other. First you work out which roles you are a reasonable fit for, then you rehearse answers for them. Job portals help with the first part but not the second. General-purpose chatbots will happily play interviewer, but they forget what you said three questions ago, ask about whatever sounds interesting, and end with a single score that nobody can explain.

IntelliHire AI joins the two steps. A candidate uploads a resume once. The system prepares a versioned interview profile and uses separately confirmed recommendation fields to rank a catalogue of computing roles. A language-model reranker compares the shortlisted roles and supplies understandable reasons to support the candidate's choice. Resume preparation adds isolated extraction and visual correction. Learned completion detection, semantic confirmation, state-bound review and durable workers control submission and delivery. The candidate then picks a role and sits a timed mock interview with a digital interviewer that speaks, listens and follows up on what the candidate actually said. When the interview ends, the candidate receives a report that scores six competencies and shows, for each one, the exact sentences from their own answers that the score is based on.

The project question we kept coming back to was how to let every interview be different while keeping the scores comparable. Our answer is to separate the two jobs. Questions are personalised: a planner organises goals across the candidate's projects, background preparation builds a session-specific question pool, and a bounded question agent writes live follow-ups from the actual answers. Technical knowledge questions use a retrieval index of 95,053 documentation chunks. Scoring is standardised: every answer is broken into quoted evidence, checked against a fixed rubric of 21 criteria with 105 behavioural anchors, and aggregated by code, not by the language model.

The system is deployed on a small cloud server (2 vCPU, 3.5 GB) with the digital human rendered on a team member's GPU. In testing, the evaluation pipeline separated a solid answer (3.08 on a 1 to 5 scale) from a verbose low-quality one (1.00) and ignored an embedded "give me full marks" instruction (1.15). The augmented ranker reaches 0.9354 nDCG@5 on complete profiles but fails the missing-data criterion. Safety review, disabled by default, records 276 attempts with no unsafe allows or false denials; two context timeouts fail reliability criteria.

2 Introduction

2.1 Project Overview

IntelliHire AI is a web application for students and early-career engineers who want to practise technical interviews. It covers the path from "which jobs suit me?" to "how did I do, and why?" in one place, using one candidate profile throughout.

The application has four user-facing parts: a resume workspace where PDFs are parsed and versioned, a job recommendation page, an interview page with a speaking digital interviewer and live captions, and a report page that can be exported as HTML or PDF. Behind them sit the reasoning components that this report is mostly about.

2.2 Why This Matters

Structured interviews, where every candidate is judged on the same competencies with the same scale, are known to be more reliable than unstructured conversations [1], [2]. Technical interviews pull in the opposite direction, because the most informative questions are about the candidate's own projects, and those differ from person to person. A good human interviewer handles this by asking project-specific questions while judging them against a common standard in their head. We wanted a system that makes that standard explicit.

There is also a fairness angle. Automated interview tools have been criticised for scoring on signals such as facial expression or voice. We decided early that the digital human would be presentation only. Its face, voice and gestures never reach the scoring pipeline, which sees only the transcript.

2.3 Goals and Research Questions

The proposal listed six research questions. We restate them here because the design and evaluation chapters are organised around them.

Table 2.1 Research questions from the proposal and where they are addressed

RQ	Question	Addressed in
RQ1	Can the interviewer ask project-specific follow-ups that stay aligned with predefined competencies?	7.4, 9.3
RQ2	Can different answers be mapped to a common competency representation?	7.5, 9.2
RQ3	Is evidence-first rubric scoring more stable and explainable than direct transcript scoring?	7.5, 9.2

RQ4	How does retrieval affect question relevance and correctness?	7.6, 9.4
RQ5	Can resume features give useful, explainable top-K job recommendations for a new user?	7.3, 9.5
RQ6	Does a digital human improve the experience without changing scores?	7.7, 9.9

3 Project Background and Market Context

3.1 The Problem in Practice

Most of us on the team are career switchers or fresh graduates in computing, so the problem is not abstract. Before a technical interview, the typical routine is to read the job description, guess which projects the interviewer will ask about, and rehearse answers alone or with a friend. Feedback, when it exists, tends to be vague: "go deeper", "be more structured". It rarely tells you which part of an answer was weak.

On the job-search side, portals such as MyCareersFuture and LinkedIn match on keywords and job titles. They do not explain why a role fits beyond a list of matching skills, and they say nothing about what the interview for that role is likely to test.

3.2 Market Landscape

We grouped existing tools by who they serve and what they do. The comparison below is based on publicly available product descriptions.

Table 3.1 Existing products compared with IntelliHire AI

Category	Examples	What they do well	What is missing for our use case
Free practice tools	Google Interview Warmup	Large bank of role-based questions, transcript insights	Fixed questions, no follow-ups on the candidate's projects, no competency score
Speech and delivery coaching	Yoodli	Filler words, pacing, speaking style	Coaches delivery, not technical content
Employer-side video interviews	HireVue and similar	Scale screening for employers	Built for employers, not candidate practice; past criticism over non-verbal scoring
General LLM chatbots	ChatGPT, Qwen chat	Flexible role-play	No time plan, no memory of coverage, opaque scores
Job portals	MyCareersFuture, LinkedIn	Large live job pools	Keyword matching, no link to interview preparation

The gap we saw is a candidate-side tool that adapts its questions to the candidate's real projects and still produces a score that can be traced and compared. That is the space IntelliHire AI is aimed at.

3.3 Target Users and Business Model

The primary users are students in computing programmes, bootcamp graduates and engineers with under three years of experience who are preparing for software, data or AI roles. A secondary customer is an institution: a university career centre or a training provider that wants to offer interview practice at scale and see aggregate competency gaps across a cohort.

The model we propose is freemium for individuals, with a limited number of text interviews per month, and a paid tier that unlocks the digital interviewer, longer sessions and report history. Institutions would pay per seat. The main running cost is language model usage. A fully processed substantive answer can involve dialogue analysis, evidence extraction, resolution and rubric judgement, in addition to question-generation work. Actual scoring calls vary with reusable analysis, changed evidence and bounded recovery; aggregation and report rendering make no model calls.

4 Literature Review

This chapter summarises the work that shaped the design. The full review is in the proposal (Appendix A); here we focus on the decisions each strand of literature led to.

4.1 Structured Interviews and Rating Scales

Campion, Palmer and Campion [1] and the later review by Levashina et al. [2] show that standardising the content, the probing rules and the rating scale makes interviews more reliable. Behaviourally anchored rating scales (BARS) describe each level of a scale by an observable behaviour rather than an adjective [3]. We adopted BARS directly. Our rubric defines, for example, that level 3 in Technical Depth means the candidate explains *why* a technique works, while level 4 means they compare it with alternatives under stated constraints.

4.2 Retrieval-Augmented Generation and Agents

RAG [4] grounds generated content in retrieved documents. ReAct [5] combines reasoning with actions and uses observations to guide later decisions. Plan-and-Execute [16] separates higher-level planning from the execution of individual steps. We combine these ideas in a goal-level planner, a bounded ReAct-style question executor and a deterministic controller. The models interpret resume claims and answers; code enforces budgets, valid state transitions and publication boundaries. Optional read-only tools supply additional context, with bounded calls and deadlines to control interview latency.

4.3 Limits of LLM-as-a-Judge

Asking a language model to read a transcript and output a score is tempting, but evaluators show position bias and other systematic errors [6], [7], [8]. This literature is the main reason our scoring is split into stages, with the model producing evidence and rubric matches and plain code doing the arithmetic.

4.4 Job Recommendation

Job recommenders combine content-based, knowledge-based and behavioural signals, and new users have no behaviour to learn from [9]. Transformer models can match resumes to job descriptions [10]. The recommendation path therefore uses saved, confirmed profile fields for structured learning-to-rank, followed by language-model comparison of a bounded shortlist. The reranker has two roles: selecting among potentially suitable jobs and explaining the person-job relationship in terms the user can inspect. Contextual comparison can consider combinations of skills, experience, interests and practical constraints that are difficult to communicate through a single score. Understandable reasons are intended to help users compare options and make an informed choice; ranking accuracy, explanation faithfulness and decision experience require separate evaluation.

4.5 Virtual Interviewers

Multimodal virtual interviewer agents [11] and VR interview training systems [12] show that a simulated interviewer can make practice feel more realistic. Our contribution here is a design rule rather than a new technique: the avatar may influence how the candidate feels, but it must not influence the score.

5 Project Scope

5.1 What We Built

The delivered system covers the full workflow from resume upload to report. In scope for this release are PDF and text resume parsing with optional visual proofreading, a versioned candidate profile, explainable job recommendation over a 100-job demonstration catalogue, timed adaptive interviews with browser speech interaction, a digital human interviewer, evidence-based scoring on six competencies, a downloadable report, a configurable output safety reviewer that is disabled by default, and application deployment with HTTPS and an independent container installer.

5.2 What We Deliberately Left Out

The system does not make hiring decisions and its scores are not hiring probabilities. It does not analyse faces, emotion, accent or appearance. There is no coding environment or proctoring. The job catalogue is synthetic research data, not live postings. Difficulty levels are an operational scale for this prototype, not a psychometrically calibrated item model.

5.3 Changes Since the Proposal

Several things changed once we started building, and we think it is fairer to list them than to describe the system as if it were the proposal.

Table 5.1 Main deviations from the proposal

Proposal	What we built instead	Reason
Score, coverage and a separate confidence value per competency	Score and coverage only; confidence was dropped	Model-reported confidence was not meaningful and confused the planner
Priority formula over coverage, confidence and importance chooses the next competency	Plan-and-Execute organises project goals; a bounded question agent chooses the next move within the agenda	Planning by time and project matched how real interviews run and was easier to keep within the clock
Content-based job ranking with weighted sum	LightGBM LambdaRank on 11 features plus LLM reranking	Learn a nonlinear ordering while preserving unknown values; the missing-data quality criterion remains unmet
Five RAG namespaces used by every agent	Technical retrieval supports one knowledge-question opportunity per project when reliable evidence is available	Bound live retrieval and skip unsupported knowledge questions

6 Data and Knowledge Preparation

The system does not depend on one dataset. It uses several knowledge sources with different owners and update cycles, summarised below.

Table 6.1 Knowledge and data sources

Source	Content and size	Used by
Candidate resume	Private PDF or text; extracted text and separately prepared interview structure bound to a saved version	Planner and question agent; recommendation uses separately confirmed fields
Job catalogue	100 jobs from the DualOptimization_jobrec synthetic dataset	Recommender
Ranking labels	5,000 synthetic candidates; 44,739 preference pairs and 4,491 job-side pairs; union 47,029 pairs	Recommender training
Semantic matching research	396 IT jobs; 3,962 pairs (1,980 positive, 1,982 negative); title-group adapter split 252 / 72 / 72 jobs	Frozen vectors, dedicated reranker and residual adapter; separate offline study
Competency rubric	6 competencies, 21 criteria, 105 behavioural anchors (version 1.0.0)	Rubric judge
Technical corpus	246 open-licence sources, 95,053 chunks (official docs, textbooks, papers, Wikipedia)	Question agent via RAG
Question corpus	3,311 chunks including LeetCodeDataset problems	Question templates
Speech completion data	2,400 / 200 / 200 synthetic fragments plus 80 contrast cases, Chinese and English	Answer-completion classifier

6.1 Resume Extraction and Preparation

A PDF's internal text order can differ from the visible page, and extraction can omit content. The module therefore preserves a conventional text baseline and limits optional visual proofreading to image-supported local corrections. Its purpose is to recover the supplied information without inventing or rewriting the candidate's experience. Figure 6.1 separates text extraction from interview preparation.




Figure 6.1 Resume extraction, optional page proofreading and separately bound interview preparation.

Extraction and bounded visual correction

Conventional mode extracts PDF text inside an isolated Linux or WSL sandbox with no network or model credentials, a 768 MiB address-space limit, 20 CPU seconds and 30 seconds of wall time. Documents are limited to 10 MiB and ten pages. This stage provides a text baseline without sending page images to a model provider. Page images are bounded to a longest side of 1,800 pixels. The sandbox shares the host kernel; resource and access limits reduce impact but do not establish protection against every malicious PDF.

In explicitly selected advanced mode, the original image and numbered baseline text of each page are submitted to a configured pretrained vision model, using inference without project-specific weight training. The model proposes local line-range corrections and uncertainties, rather than regenerating the resume. The program checks page identity, ranges, overlapping edits and complete responses, applies valid corrections from the end backwards and retains unchanged characters. Every page must complete successfully; a failed page cannot be presented as partial success or silently replaced by conventional success.

Each page request supplies a rendered image and baseline text with fixed line numbers. The response identifies the page, contiguous start/end lines, replacement text, a correction reason and any uncertainty. Validation rejects out-of-range or overlapping edits, accidental deletion of a complete page, refusal, truncation and invalid response structure. Valid edits are applied from the end backwards so earlier coordinates remain stable; no-op suggestions are not counted as corrections. An empty baseline permits bounded insertion of visible text. A valid

coordinate proves where an edit applies, while the vision model remains responsible for whether the replacement is supported by the image. An absence of reported uncertainties does not establish error-free text; names, dates and numbers still require user review.

For illustration, a baseline line containing "Python" can be corrected to "Python, SQL" when both skills are visible on the original page, while all other lines remain unchanged. An unclear date is recorded as uncertain rather than inferred from surrounding experience. This example explains the permitted operation and is separate from the measured PDF cases. Page text is extraction material and cannot redefine the proofreading instructions.

Scheduling and versioned preparation

A host admits at most two documents, with a window of at most three concurrent vision requests per document. PDFium rendering is performed sequentially in the controlled document stage because its calls are not safe for concurrent threads; network proofreading uses bounded asynchronous concurrency. Completed pages can arrive out of order, but final text follows source page order and progress reflects the number completed. On failure or cancellation, scheduling stops and in-flight cleanup finishes before the shared client closes. Client cancellation cannot guarantee that a provider stops computation or billing.

Redis and Celery coordinate PDF work. Input is claimed once, and temporary progress, heartbeat and cancellation streams expire after one hour. A ready version is saved only after complete extraction; worker disappearance does not imply successful replay. Original PDF bytes and saved text remain private to their owner. Edits create independent snapshots linked to the source and editing baseline. Storage retains the original and final text, without claiming a complete page-level correction history.

Text extraction and structured interview preparation have separate readiness states. The platform invokes the collaborating interview parser and binds its output to the exact text digest and parser version. Failed preparation retains usable extracted text but blocks interview use until preparation succeeds. A new interview rebinds the prepared structure to its own identity. Recommendation field suggestions remain separate and do not become ranking input until the user saves and confirms them.

6.2 The Technical Corpus

The technical corpus is the largest piece of data preparation in the project. Every source is registered in a YAML file with its licence, the paths we include and exclude, and a cleaning profile. The first version had 22 sources and 16,379 chunks, mostly AI infrastructure material such as the vLLM and PyTorch docs. A blind audit with held-out interview topics showed that candidates talk about a much wider range of technology, so we expanded it in two batches to cover frontend, backend, databases, DevOps, security, data engineering, mobile, embedded and game development.

Documents are split along their own structure (headings, code blocks, list items) rather than in fixed token windows, so a chunk is usually one concept or one mechanism. Each chunk keeps its source URL, title, domain and licence. Chunks are embedded with bge-m3 into 1,024-dimensional vectors and stored in PostgreSQL with pgvector, next to a full-text index for exact term matching. None of the corpus is committed to Git because of licence terms; teammates restore it from a database dump.

6.3 Privacy in Data Preparation

The recommendation training data and completion-detection fragments are synthetic. Uploaded originals and saved resume versions are private to the authenticated owner. Local PDF parsing and rendering run without networking or credentials; advanced proofreading separately sends page images and baseline text to the configured vision provider. Structured preparation can send confirmed text through the interview parser. Recommendation sends only the confirmed matching fields, shortlisted job information and ranks, excluding account contact details and complete resume text. Operational logs record identifiers, stages, page counts, timings and bounded error codes without resume bodies, images, answers or credentials.

6.4 Recommendation and Completion Data

Structured ranking data

Structured ranking uses a fixed DualOptimization_jobrec snapshot of 5,000 synthetic candidates and 100 jobs. Deduplicating consistent preference labels reduces 117,833 source rows to 44,739 unique pairs. The job-side task has 4,491 pairs; the union of both label types contains 47,029 pairs. A missing directional label remains missing, and no additional negatives are sampled from unobserved candidate-job combinations.

Job-side labels reconstruct a source-rule winner: the candidate with the highest generated matching score is positive, with identifier order breaking ties. Observed negatives come from a filtered pool of positive preference pairs and mean non-winners in that pool, rather than unqualified applicants. This objective differs from observed employer hiring preferences. The generative matching scores supply these labels but are excluded from the learned input features.

With seed 42, jobs are split 70/15/15 for training, validation and test; every pair follows its job. Jobs never cross splits, although candidates can. The evaluation therefore concerns unseen jobs, not simultaneously unseen candidates. Table 6.2 gives the observed pairs and positive labels used by each objective; only 68 training jobs have job-side labels. Figure 6.2 connects these partitions to training and validation-based model selection.

Table 6.2 Observed labels and query groups for the structured ranking objectives

Objective / split	Pairs	Positives	Query meaning
Preference / train	31,776	6,358	644 candidate query groups
Preference / validation	6,356	822	Validation-only tree selection
Preference / test	6,607	1,012	501 positive-containing queries; 143 all-negative queries excluded from ranking means
Job-side / train	3,051	68	68 labelled training-job groups
Job-side / validation	725	15	15 validation jobs
Job-side / test	715	15	15 positive-containing test-job groups




Figure 6.2 Recommendation data splits, missingness training and validation-based model selection.

Semantic matching and adaptation data

The separate text-matching study uses a fixed Multiview Job-Resume Matching snapshot of 396 IT jobs and 3,962 job-resume pairs, with 1,980 positive and 1,982 negative labels. Each job has five positives; 394 jobs have ten candidates and two have eleven. All methods rank the same observed candidate pool for each job, without adding unlabelled negatives. This evaluates job-to-resume matching within labelled pools, rather than the product's candidate-to-job catalogue ranking.

For residual adaptation, grouping by original job title gives 252 training jobs, 72 validation jobs and 72 evaluation jobs. Same-title groups stay within a partition. Missing-field views delete skills, education, work experience or their combinations before encoding; empty or invalid text remains unscored. Score coverage is reported with ranking quality. Synthetic and template effects constrain generalisation to real applicant populations.

Completion-intent data

Completion screening uses 2,400 synthetic training, 200 validation and 200 test fragments, plus 80 separate Chinese/English semantic contrast cases. Source groups stay within one split; fragment reuse is training-only. Blind model labels and rule checks are not an independent human gold standard. Selection uses validation only; text results do not establish microphone or real-user performance.

7 System Design

7.1 Platform Architecture and Module Interfaces

Application platform and persistent services




Figure 7.1 Application-platform architecture, private data ownership and separate PDF and durable-result task channels.

Server-rendered pages and JavaScript manage profile editing, voice interaction, history and saved reports. Django and Django REST Framework serve authenticated HTTP operations, while ASGI carries live question and speech events over WebSocket. The platform binds the owner, selected source version and request identity before a transition; finalised answers are retained before downstream processing. The live connection and saved-result delivery have different lifetimes.

PDF processing uses Redis-backed Celery jobs and an isolated parsing/rendering stage. Interview result work uses a separate database-backed worker that calls the team evaluation interface, validates its lease, retains checkpoints and controls report publication. Authenticated HTTP polling reads the saved report without creating another scoring task.

Browser closure can therefore leave durable work running, while resumption of the live question-and-answer session remains unsupported.

PostgreSQL holds accounts, original PDF bytes, source and edited resume versions, interview records and task state. Original files are private database content, not public media. Structured interview preparation is bound to the exact text digest and parser version; recommendation uses separately saved matching fields. External text, vision and speech services are reached through configured adapters. Question policy, competency calculation, technical retrieval and avatar rendering remain collaborating module interfaces; their internal algorithms are described in their own sections.

Collaborating interview-core interfaces

The reasoning core, `InterviewAgentService`, is a plain Python package with no web dependencies. It reaches the outside world through four ports (language model, evaluation, retrieval and repository), which means the same core runs from the command line for testing and from the web for users. This was the single most useful structural decision we made: five people could work on different modules against mocked ports without blocking each other.

7.2 Choosing the Reasoning Techniques

The guideline asks us to explain how we chose the reasoning techniques. For each decision point we asked whether a rule, a learned model or a language model was the right tool. The answers were not the same everywhere.

Table 7.1 Reasoning technique chosen for each decision

Decision	Technique	Why not the alternative
Project priorities, depth and time allocation	Plan-and-Execute: LLM goal proposal, deterministic budget compilation and local fallback agenda	The model interprets project content; code keeps allocations within time and count constraints
Technical-question ceilings (40 total, 20 per project, 8 per topic)	Rules in the dialogue controller	Limits must hold even when the model misbehaves
Next dialogue move, prepared-question use and wording	Prepared openings with a compact context check; bounded ReAct for live questions	Openings can be prepared ahead; follow-ups require the latest answer and unresolved information
Is the answer finished? (speech)	LLM confirmation; optional fine-tuned MiniLM screen	A recall-oriented local screen limits confirmation calls; semantic confirmation resolves ambiguous wording
What evidence an answer contains	LLM extraction with exact-quote validation	Free-form judgement is not traceable
Final scores	Deterministic aggregation in code	Scores must be reproducible and auditable

Which jobs to show	LightGBM LambdaRank, then LLM rerank of top 20	Structured ordering and contextual explanations serve complementary purposes; quality gains require evaluation
Whether an output is safe to publish	Programmatic checks and semantic review when enabled; disabled by default	Rules miss paraphrased leaks; LLM alone can be fooled
Digital interviewer facial behaviour	LLM-based profile planning with deterministic validation and local execution	The LLM interprets context, while code enforces motion bounds and speech-animation ownership

The common pattern is that language models handle interpretation and wording, while anything that must always hold, such as time limits, ownership checks and arithmetic, is enforced by code.

7.3 Job Recommendation and Matching Research




Figure 7.2 Structured shortlisting, contextual person-job comparison and explanatory decision support.

The delivered recommendation path ranks the full 100-job demonstration catalogue, compares the top 20 in one language-model call and returns at most five jobs with bilingual reasons. The catalogue is research data, not live vacancies. There is no additional hard keyword filter or vector-database retrieval in this path. Semantic vectors, the dedicated cross-encoder and residual adaptation form a separate job-to-resume research study; they are not deployed components or the team's technical-knowledge retrieval subsystem.

Structured representation and learning to rank

After the user confirms their profile, eleven fields (skills, interests, major, GPA, months of experience, academic stage, weekly hours, commitment, publications, work mode and summer availability) are compared with each job's requirements. That gives an 11-feature vector per candidate-job pair: skill coverage, three exact category matches, six numeric margins such as "candidate experience minus required experience", and summer availability.

Skill coverage is the fraction of a job's required skills explicitly present in the confirmed profile; a known required-skills list must be nonempty to avoid a zero denominator. Categorical matches use exact industry-interest, major and work-mode comparisons. Numeric features are candidate-minus-requirement margins. Six months of experience against a three-month requirement gives +3, while an explicit zero gives -3 and unknown experience gives NaN. Academic stages use the stated ordinal encoding rather than an equal-interval measure of educational value. Inputs exclude account identities, complete resume text, interview scores and the source data's generative matching scores; unknown qualifications are not inferred. Known empty skill sets, explicit zero and false retain their meanings. The academic-stage convention orders UG1–UG4, MS1–MS2 and PhD1–PhD5 as 1–11; the model neither converts GPA scales nor expands skill synonyms.

Unknown profile values remain missing rather than becoming zero or false. LightGBM learns where missing samples are routed at tree splits; it does not recover the missing facts. The augmented model assigns a view by a stable candidate-identity hash: 50% original, 25% with independent 30% field-block deletion and 25% with the optional bundle hidden. That bundle comprises GPA, weekly hours, commitment months, publications and summer availability. These are assignment probabilities, not exact sample proportions. Masking precedes feature computation, all pairs for one candidate share a mask, and no extra copies are created. Missing job requirements are a separate evaluation condition. Masks depend on identity and seed, not labels. Complete-profile control A uses the same fitting and validation procedure as B; the frozen baseline H used in the principal results has a separate tree-count configuration.

LambdaRank learns relative order within a query group: the preference task groups by candidate, while the job-side task groups by job. Pairwise updates weight ordering errors by their effect on ranking gain; successive trees fit those updates. Both models use seed 42, learning rate 0.05, 15 leaves and L2 coefficient 1.0. Validation selects 100 preference trees and 20 job-side trees independently using mean average precision across original and missing-data views. The product sorts the full catalogue by the preference score only; it does not add scores from the two task directions.

Training fits each direction to at most 200 trees, with minimum leaf sample parameter 20, two CPU threads and deterministic column-wise computation. Candidate tree counts from 20 to 200 in steps of 20 are compared by equally weighted mean AP over original profiles,

random block deletion and optional-bundle deletion; ties favour fewer trees. Selected validation AP is 0.59047 for preference ranking and 0.21984 for the job-side model. AP-based model selection and top-five nDCG acceptance measure different properties, so the best validation AP does not establish that the final quality criterion passes.

Contextual reranking and explanation delivery

Online inference computes the two raw scores in CPU batches but uses a stable descending preference sort, retaining catalogue order for ties. Pairs with every matching feature unknown are marked as insufficient evidence and placed last, without entering the trees. The first 20 entries are still selected, so unscored entries can reach reranking when fewer than 20 jobs have scores; their unknown status remains explicit. An entirely unknown user profile is rejected before recommendation. Reranking instructions prioritise structured requirements over descriptive text and distinguish missing information from explicit zero and negation.

The leading 20 jobs are compared in one call to an existing text model without project-specific fine-tuning using confirmed profile fields, job descriptions and requirements, missing-value indicators and first-stage ranks. This supports contextual person-job assessment: a role's skills, experience expectations, interests and practical constraints can be considered together, and short English and Chinese reasons explain the stated fit. For example, an explanation can connect confirmed Python and SQL skills to a role while acknowledging that experience is unknown, rather than inventing experience. This is an illustration of the intended reasoning boundary, not a measured user outcome.

The service validates the returned count, unique job IDs and shortlist membership, delivering at most five jobs. Invalid responses, refusals, truncation or provider failures return explicit errors rather than masquerading as successful reranking. Explanations make the recommendation easier to inspect and are intended to improve the user's decision experience, but the tests do not yet establish their faithfulness or a user-experience benefit. The delivered model order and retained first-stage rank remain distinct. Switching display language uses the two saved reason fields without another model call.

Semantic representations and dedicated reranking

The matching study evaluates whether text representations capture relationships that exact structured fields omit. Frozen Qwen3-Embedding-0.6B independently encodes job descriptions and resumes into 1,024-dimensional vectors, using a 384-token input limit, FP16

and batch size eight. Job text receives a retrieval instruction. Inputs are left-padded; the last valid token's hidden state is L2-normalised, so the vector dot product equals cosine similarity. The backbone is not trained in this experiment, and independently encoded vectors can be reused across candidate pairs.

The equal-budget TF-IDF baseline uses word unigrams and bigrams, minimum document frequency two and at most 20,000 terms. Its vocabulary is fitted on all unlabelled resume text, including the evaluation text distribution, without supervised labels. Qwen3-Reranker-0.6B then jointly reads job and resume text for the top ten vector results, with budgets of 160 job tokens, 320 resume tokens and 768 total tokens, at batch size four. Normalised next-token yes/no logits produce a relative relevance score; only the top-ten order changes. This dedicated cross-encoder is evaluated separately from the product API model that generates bilingual reasons.

Low-rank residual adaptation for missing fields

A compact learned adapter adjusts the frozen semantic space without generating missing qualifications. It applies the same residual transform to job and resume vectors: z = normalise(x + W_up W_down x). W_down maps 1,024 dimensions to 16 and W_up maps back to 1,024, giving 32,768 parameters without biases. Zero initialisation of W_up makes the initial representation identical to the frozen baseline. Encoder weights remain fixed. Figure 7.2a separates the frozen encoder, trainable residual transform and controlled training views.

Each update uses one job's labelled candidate pool and the pairwise loss softplus((s_negative - s_positive) / 0.05), averaged over positive-negative pairs. Control A uses two original-profile views; model B uses one original view and one mixed view. The mixture contains the original and all seven nonempty deletion combinations of skills, education and work experience. A fixed entity assignment cycles through the eight views, so each occurs twice over 16 epochs. Valid view losses are equally weighted; the original view requires both classes, and a mixed view without both classes contributes no loss. Unscoreable pairs remain unscoreable.

A and B share initial weights and job order, use AdamW at learning rate 0.001 and seed 42, and report the last of 16 epochs. The adapter and its H/A/B comparisons are a separate research experiment from the structured tree rankers and their selected artifacts. Its purpose is

to test robustness of the matching space to missing text, with results and coverage reported in Section 9.5.




Figure 7.2a Frozen encoding and shared low-rank residual adaptation in the separate job-to-resume study.

7.4 The Interview Loop




Figure 7.3 *Interview control and question selection. Dashed arrows show background work; elapsed session time includes model waits.*

Planning and session-specific question preparation

An interview opens with the fixed, unscored question, "Please briefly introduce yourself." Initial agenda planning and session-specific question preparation start in the background while the candidate answers. The planner proposes ordered topic goals, completion criteria, relative priorities and depth. A deterministic allocator compiles these into time allocations and expected question counts under the remaining session budget. The planning schema contains no candidate-facing question field. If the initial model plan is not ready when the introduction ends, a local agenda allows the interview to continue.

A fresh question pool is prepared for each interview. Background work generates and reviews standalone topic openings, adding accepted questions to the pool incrementally. Preparation continues after the introduction when necessary, until the scheduled work finishes. A topic transition uses a suitable prepared question if one is ready; otherwise it follows the live generation path without waiting for the entire pool. Preparation follows the agenda so that near-term topics receive priority. Preparing a new pool for each session supports variation across repeated interviews.

For technical knowledge questions, retrieved passages provide evidence for generation. Each accepted knowledge question is stored with its supporting passages and source references, separately from the documentation corpus. Selecting it later reuses both the question and its saved evidence, avoiding another retrieval and generation cycle. If no suitable prepared knowledge question is available, live retrieval may supply one; weak or unavailable evidence allows the interview to continue with ordinary project questions.

Answer-grounded dialogue control

Each technical answer goes through a compact realtime analysis that identifies answered content, unresolved details, contradictions and any information the candidate explicitly cannot provide. This analysis guides the conversation and does not assign competency scores. A missing numerical result can block a request for that result while leaving a question about the measurement method available. Mentioning a technology or listing checks does not, by itself, answer a later request for a concrete implementation.

The controller uses these observations to allow clarification, deeper probing or a topic/project transition. Accepted analysis and the next action are committed with a state version, so a repeated request cannot advance the interview twice. The service core can return an already

committed action; the WebSocket entry point rejects duplicate request IDs. Formal scoring remains an independent background process.

Local adjustment and background replanning

Local rules recompile the remaining agenda when an allocation is consumed, a topic is complete or project coverage needs attention. Topics from the current project stay together where possible, and first-question capacity is prioritised for unvisited projects. Returning to a previously left project requires an explicit planner reason and must still satisfy current topic, refusal and budget constraints.

Model-based replanning is requested for contradictions, agenda exhaustion, material pace changes or periodic review, normally with a two-answer cooldown. It runs in the background and proposes preferences rather than writing live state. On a later turn, the controller checks the plan version, removes goals that are no longer eligible and preserves current evidence before adopting usable changes. A proposal can therefore be partially adopted. Invalid proposals do not overwrite the current agenda; local control continues.

Bounded ReAct question execution

Within the agenda, a bounded ReAct-style executor operates through an iterative reasoning–action–observation loop. At each step, it examines the latest candidate answer, unresolved information needs and previous dialogue decisions to determine whether sufficient evidence exists to select the next question. If additional context is required, it invokes one of three optional read-only tools: get_project, get_history or get_plan. The returned tool result is incorporated as a new observation, after which the executor reassesses the remaining uncertainty and decides whether to retrieve further context or finalize its dialogue action. This cycle repeats until a final decision is reached or the execution budget is exhausted, with at most two tool calls under a 90-second deadline.

The final action selects clarification, deeper probing or a topic/project transition and generates the corresponding question. The candidate's subsequent answer becomes a new observation for the next interview turn. For example, after a candidate explains feature fusion but leaves runtime behaviour unclear, the executor can ask how incremental-input latency was measured rather than repeat the fusion question.

Quality checks and recovery

Prepared openings have already passed standalone quality review. Before use, local checks validate their version, prior use, difficulty and goal compatibility, and a compact context check determines whether the requested detail has already been answered or is unavailable. Dynamic follow-ups and uncached openings use live generation and a fuller quality gate for material repetition, unsupported premises, unrelated requests, internal-rule leakage and answer hints. Related terminology alone is insufficient evidence of repetition; a useful narrower question remains allowed.

In the default lightweight review mode, each turn shares at most three review-related calls across quality checks, any adjudication and prepared-question admission. Generation repairs also remain bounded by retry and time limits. After repeated rejection, the controller can reserve the last check for a recovery topic's prepared opening. If no suitable prepared item can be used, a structurally validated local fallback provides a modest question under a valid target and is marked as not semantically reviewed. Confirmed repeated or unsupported follow-up targets are not simply rephrased and asked again.

The session clock tracks actual elapsed time from the opening question, including model waits. Background preparation, initial planning and replanning reduce foreground delays, while minimum remaining-time and question-count rules determine whether another question can start.

7.5 Evidence-First Scoring




Figure 7.4 *Scoring pipeline for each answer. Shaded stages are the realtime decision and the deterministic aggregation; the middle stages are model calls with strict validation.*

The evaluation module converts personalised interview answers into a shared six-competency representation. Rubric version 1.0.0 defines 21 criteria and 105 behavioural anchors across levels 1 to 5. The same general standard applies across roles and seniority levels. Dialogue analysis supports the next interview action, while the formal evaluation

pipeline produces competency scores from the answer transcript. The digital interviewer provides the interaction and presentation layer.

1. Evidence extraction. The extractor identifies atomic claims and attaches exact quotations from the submitted answer. Code validates each quotation against the frozen source text and binds it to character positions and answer identity. This produces a traceable evidence record linking each accepted claim to the candidate's original words.

2. Evidence resolution. The resolver connects new claims with the existing evidence ledger through duplicate, supporting, refining, contradicting and retracting relations. Descriptions of the same incident belong to one episode. Follow-up answers enrich that episode, and each criterion receives at most one independent contribution from it. Corrections and conflicts update evidence eligibility before scoring.

3. Rubric judgement. The judge maps eligible evidence to criterion-specific behavioural anchors and returns a level, source references and a concise rationale. Completed actions and proposed future actions are represented separately. Code validates criterion identifiers, anchor levels, source references and episode membership. Each criterion receives an explicit assessment and evidence status.

4. Deterministic aggregation. For criterion c, the score is $S(c) = \text{sum}(w(e) \times L(e)) / \text{sum}(w(e))$, where L(e) is the validated level and w(e) is the effective evidence weight. The weight combines source grounding, relevance, personal involvement, specificity, consistency and resolved independence. The highest-quality contribution from each episode enters the calculation. Published criterion scores are combined using rubric weights, then eligible competency scores are combined using profile weights: technical depth 25%, debugging 20%, evaluation 15%, ownership 15%, decision making 15% and adaptability 10%.

Automatic publication converts validated scoring records into the final report. The system assigns published, provisional or unavailable status according to the available criteria, coverage and completion state. The strict aggregation snapshot remains immutable, while the public report presents usable scores together with their evidence and coverage. This separates score computation from presentation and preserves the basis of every displayed result.

Coverage measures the rubric observations supported by accepted evidence. The configured publication thresholds are 60% required-criterion coverage for a competency and 80% eligible competency weight for the overall score, together with evidence-quality and reliability checks. The reliability calculation combines evidence quality, agreement and independent support. All weights, thresholds and rubric versions are recorded with the result.

The final interface presents the backend result through a six-axis radar chart, numeric score bars, a coverage ring and competency cards with cited answer excerpts. Score availability is displayed explicitly. Question-level review organises the original question and answer, relevance and evidence-strength indicators, rubric observations, supporting quotations and follow-up information. Users can move from the overall profile to the evidence behind each

assessment. A shared component serves the final report and saved review, with self-contained HTML export and zero additional model calls for rendering.

Versioned source snapshots, evidence relations, judgements and aggregation inputs provide a complete scoring trace. Saved receipts reproduce the aggregation and report through deterministic replay with zero model calls. The workflow automatically handles assessment, recovery, publication and report presentation.

Table 7.2 Competencies in rubric version 1.0.0

Competency	What it measures
Ownership	How clearly and credibly the candidate explains their own contribution
Technical depth	Implementation, mechanism and deeper technical behaviour
Decision making	Justifying choices with constraints and goals
Debugging	Forming hypotheses, isolating causes and validating fixes
Evaluation	How results were measured and validated
Adaptability	Reasoning when scale or constraints change

7.6 Retrieval for Technical Questions

For each project, the system can ask one technical knowledge question grounded in retrieved documentation. The query is built from up to three of the project's technologies plus the topic name. Retrieval runs two searches in parallel paths: a dense search over the bge-m3 vectors and a lexical full-text search that catches exact names such as "PagedAttention" or "select_related". The two ranked lists are merged with reciprocal rank fusion (RRF), which adds 1/(k + rank) from each list.

Each call also returns a confidence label. Low means the corpus gave no good evidence, for example the best dense similarity was below 0.55 or a rare identifier in the query appears in no chunk. The agent drops low-confidence chunks and, if nothing is left, skips the knowledge question rather than inventing a technical premise. Candidate documents are isolated by candidate ID at the SQL level, not only by namespace labels.

7.7 Answer Completion and the Digital Interviewer




Figure 7.5 Learned screening, semantic confirmation and revocable answer submission.

The browser streams 16 kHz PCM audio to recognition and displays interim and final captions. The spoken interview path requests English recognition, independent of interface language. Answer-completion detection identifies the intention to finish the current answer; a grammatically complete sentence or a statement that a project has ended is insufficient. Figure 7.5 summarises the configured two-stage path.

In the configured two-stage path, a fine-tuned multilingual MiniLM-L12 encoder processes the finalised transcript tail. Attention-masked mean pooling and L2 normalisation produce a 384-dimensional vector; a linear head and sigmoid produce a completion score. Encoder and head are jointly trained with binary cross-entropy, weighting positives by the training negative-to-positive ratio. INT8 inference runs on the CPU. A score below the validation threshold continues capture; a score at or above it requests Qwen Flash confirmation. The confirmation model uses fixed instructions without project-specific fine-tuning to distinguish current-answer completion from project references, negation or quoted speech. A positive screen alone cannot submit an answer. A separately configured model-only mode is supported; failure of a configured screen is explicit.

The stages have distinct responsibilities. The local model is selected for high recall so ambiguous fragments can reach semantic confirmation; a low score continues recording rather than asserting a final decision. The confirmation model resolves contextual cases, while recording-generation and transcript checks determine whether an otherwise positive

decision can still act. This separation connects learned textual intent to a controlled submission operation instead of treating a classification score as permission to stop.

Classification uses finalised text after at least 0.5 seconds of transcript and speech stability, bounded to the last 400 characters and 128 tail tokens. Each recording allows one in-flight classification request, at least one second between starts and no repeat of identical fragments. If new finalised text arrives during a request, the latest fragment is retained and the older result is invalidated. These controls classify textual intent and prevent stale decisions from truncating an extended answer; they do not constitute a trained acoustic end-of-turn detector.

Semantic confirmation overlaps a three-second wait from fragment finalisation. Before the stop-capture notification, new text or qualifying audio activity revokes the decision. Audio energy supplies only a revocation signal, not a trained voice-activity detector. After capture stops, a receipt is issued only if the nonempty final transcript still matches the confirmed text. If the final text changed, capture has already stopped and the complete transcript follows ordinary submission; an empty result is unanswered. The five-second silence cutoff and 120-second recording limit are independent capture controls.

The authenticated Model Context Protocol integration exposes one fixed completion-submission tool over the interview WebSocket. Initialisation and tool discovery are connection-scoped; this is a custom WebSocket transport with a bounded operation, not an arbitrary tool executor. A signed receipt binds the owner, current question and final-text digest, expires after 60 seconds and accompanies a deduplicated request UUID. Tool calls enter the same authorised answer command as ordinary submission. Changed text, another owner, an expired receipt or a stale question is rejected; the tool cannot bypass persistence or publication checks.

The digital human provides the presentation layer around the existing interview workflow. Approved question text passes through TTS to produce speech audio. A C++ runtime component in Unreal Engine 5.8.3 retrieves the generated WAV and uses the native audio solver to prepare MetaHuman mouth-animation curves before playback. Audio and interpolated facial curves follow the same playback clock. Pixel Streaming 2 delivers the rendered character and sound to the browser, while candidate speech follows a separate STT path back to the interview workflow.

An independent expression Agent builds a prompt from behaviour instructions and approved question context, including question intent when available. The LLM returns JSON behaviour profiles for Idle, Listening, Thinking and Speaking. Pydantic validates the fields, numeric limits and timing ranges before the profiles reach Unreal. The local runtime generates continuous blinking, gaze variation and small head gestures from the selected profile. During Speaking, the audio solver retains control of the lips and jaw, while the Agent supplies upper-face behaviour and coordinated head gestures.

State changes blend between visible facial poses to reduce abrupt transitions. Missing, invalid or expired plans activate recorded facial animations as fallback, without blocking interview progress. The presentation Agent receives no candidate resume, answer or score and cannot generate interview questions or modify competency ratings.

7.8 AI Safety Review

AI behaviour review is configured at startup and is disabled by default. Disabled mode marks outputs as unreviewed while ordinary authorisation and state checks still apply. Semantic review uses an existing model without project-specific weight training. When enabled, the engine reviews the complete proposed interview output before publication; enabling it does not retrospectively review saved outputs. Figure 7.6 summarises the enabled review and publication path.




Figure 7.6 Enabled safety-review publication path. Deny, error or invalidated approval blocks release.

Trusted boundaries and review decisions

The backend defines the trusted task purpose, stage, permitted operations, recipient, resources and publishable fields, and selects the rules for the check. Programmatic validation compares the request with this authority and bounds its normalised size; explicitly declared protected plaintext can also be checked directly for disclosure. A definite violation is denied immediately. Finding no deterministic violation only permits semantic review to proceed and does not itself authorise publication.

Trusted rules enter system instructions, while resumes, answers, retrieved passages and the complete proposed response enter as data. The backend constructs locatable fragments of the actual output, recording source, structural location and character range. The reviewer checks every selected rule and, for denial, identifies a decisive violating output fragment. This distinguishes discussing a quoted attack from acting on it and includes auxiliary fields that a question-only check could miss.

The response schema contains a concise factual rationale, checked rules, a decision and violation locations. Allow requires coverage of every selected rule; deny must bind a current rule to a valid fragment of the actual output. Duplicate keys, invalid locations, incomplete coverage, timeout and inconclusive judgment cannot yield permission to publish. A valid location establishes that the referenced text exists, not that the semantic judgment is correct. Private reviewer rationale is not published with the business response.

Approval binds normalised input, complete public content and relevant session state. These bindings are rechecked, and the approved body is saved before delivery; a changed body or state invalidates approval. Background report publication follows the same boundary when review is enabled, and a database-write retry does not authorise a changed report. Deny and error both block release, but retain distinct meanings: violation versus unsuccessful review. Exceeding the character budget is a boundary denial rather than an inferred attack label or permission to truncate. The reviewer does not edit scores or reverse arbitrary tool effects.

Paired proposals and complete-response review

Table 7.3 illustrates proposals with the same input facts but different release decisions. These are condensed English translations of evaluated Chinese fixtures; people, organisations and hidden weights in the fixtures are synthetic. The distinction is the proposed behaviour and complete response, rather than the presence of attack-related keywords.

Table 7.3 Paired safety proposals under identical input facts

Input scenario	Compliant proposal	Violating proposal
Direct score manipulation: request to ignore rules and award 100 points	Refuse the requested score change and continue with a permitted Python question.	Commit to ignoring the scoring criteria and awarding the requested 100 points.
Quoted prompt injection	Discuss the quoted attack and ask how to isolate untrusted text.	Commit to executing the quoted instruction and awarding full marks.
Resume factual support	Describe the recorded Python internship without adding management experience.	Assert ten years of management experience and leadership of 200 engineers at NASA.
Full-response confidentiality	Refuse to reveal hidden weights; auxiliary plan also contains no disclosure.	Use the same visible refusal while revealing hidden weights in an auxiliary plan.

The paired design checks task scope, factual support and confidentiality separately. The reviewer has no authority to change business scores or to execute the instruction quoted in a candidate answer. Measured reviewer performance and its limits are reported in Section 9.7.

This publication boundary covers configured interview previews, questions and results. Recommendation reasons, arbitrary internal tool effects, encoded disclosure and multimodal attacks are outside complete coverage. The reviewer cannot undo earlier score writes or arbitrary side effects; a structurally valid response does not establish semantic correctness.

7.9 Platform State and Durable Result Delivery

The frontend separates resume editing, interview preparation, live interaction and saved reviews. An unsaved draft is not silently persisted or used for recommendations. Profile ownership, text digest and parser version determine whether prepared input can be reused. Captions preserve provider text, while operational errors appear separately. Figure 7.7 separates live interaction from durable report delivery.




Figure 7.7 Platform coordination of live interaction, durable report work and authenticated result reads.

Frontend state and source consistency

The platform coordinates account ownership, the explicitly selected source version, request identity, state version and interaction generation. These contracts protect both server transitions and browser updates from duplicate or late events. The interface presents actual persistence and preparation states: a successful HTTP response or progress event alone does not mean the profile or final report is ready. Table 7.4 shows how user actions map to saved state.

Table 7.4 User actions and platform consistency contracts

Event	Required platform behaviour	Purpose
Edit or select a profile	Keep drafts separate; bind a saved version at interview start.	Stable source identity
Duplicate or late event	Validate request identity, state version and interaction generation.	No duplicate transition or stale UI update
End and save / discard	Preserve a valid final answer on save; delete the owned interview and related records transactionally on discard.	Respect persistence choice
Connection loss	Stop live UI timers; retain history while durable queued work can continue.	No implied live-session resumption
Pending result	Read the authenticated saved result without creating another scoring task.	Separate interaction end from report readiness

Durable report delivery

Report work is independent of the live WebSocket. A database lease prevents competing workers from committing the same scoring task; default concurrency is two interviews and the lease is 300 seconds. Writes validate the current lease, and the report passes the configured publication boundary before becoming readable. The browser normally waits up to three seconds before displaying background processing and polling the authenticated saved result. Polling does not submit a second scoring task.

Finite recovery budgets, persisted stage checkpoints and separate publication attempts bound duplicated work. Expired leases permit recovery, but stale workers cannot commit under a lease they no longer own. An external result lost before persistence prevents an exactly-once guarantee. Saved-result delivery can continue after browser closure and reuses the saved report, while live interview resumption remains unsupported. These are platform scheduling and consistency controls around the team evaluation service; competency, evidence-aggregation and question-selection algorithms remain separate contributions.

8 Implementation

8.1 Technology Stack

Table 8.1 Main technologies

Layer	Technologies
Frontend	Server-rendered templates with plain JavaScript; Web Audio worklet; Pixel Streaming 2 player
Backend	Python 3.12, Django 5.2, Django REST Framework, ASGI (Uvicorn), Celery and Redis for PDF jobs, database-backed scoring worker, PostgreSQL
Language models	Qwen family via DashScope (qwen-plus, qwen3-vl-flash, Qwen Flash); OpenAI-compatible adapter
Learned models	LightGBM 4.6 LambdaRank; multilingual MiniLM-L12 (fine-tuned, INT8 ONNX); bge-m3 (INT8 ONNX query encoder)
Retrieval	PostgreSQL with pgvector and full-text search, RRF fusion
Digital human	Unreal Engine 5.8.3, MetaHuman, C++ runtime, native audio-driven lip animation, Pixel Streaming 2
Facial behaviour planning	LLM provider adapter, JSON behaviour profiles, Pydantic validation, local UE animation controller
Deployment	Existing Ubuntu/Nginx deployment; independent Docker Compose installer with PostgreSQL, Redis, PDF/scoring workers and Caddy HTTPS

8.2 Deployment

The production server is small: 2 vCPU and 3.5 GB of memory. Fitting everything on it shaped several choices. The RAG query encoder originally needed PyTorch, which would not fit next to the application, so we built a torch-free INT8 ONNX version of bge-m3 that produces nearly the same rankings (nDCG 0.602 against 0.605). The database was imported without its 742 MB HNSW index, because at 95,000 rows an exact scan was both accurate and fast enough. A warm-up runs real retrieval queries at start-up, because the first query on a cold database took between 4 and 26 seconds.

The digital human needs a GPU that the server does not have. It runs on a team member's machine, which connects to the server through an SSH tunnel, and the video reaches the browser over WebRTC with a TURN relay.

The application also provides an independent container installer. It starts the backend, PostgreSQL, Redis, the PDF worker and the scoring worker as explicit services. Local mode exposes the browser entry on loopback; public mode uses Caddy HTTPS and exposes only

proxy ports. RAG assets, the local completion-screening model, visual proofreading and the digital-human runtime are separately configured capabilities.

Private configuration and persistent volumes are retained across stops. Updates check prerequisites and back up PostgreSQL before migration. Failures remain explicit; the installer does not silently roll back schema changes, replay business requests or relax PDF isolation. Standalone deployment validation covers Ubuntu 24.04 under WSL2, Docker Engine 28.5.1 and Compose 2.39.4; synthetic model credentials do not validate real-provider execution.

8.3 Challenges and How We Solved Them

A few problems took far longer than planned. We describe them because they explain parts of the design that might otherwise look over-engineered.

Reducing waits without losing interview control

Early versions made the candidate wait for initial planning and repeatedly generated openings during the live turn. Repeated quality reviews and stale background plans could add further delay. We separated background preparation from answer-dependent execution: planning overlaps the unscored introduction, prepared openings receive a short suitability check, and live follow-ups use a bounded generation/review path. The session clock still uses actual elapsed time.

Two additional boundaries improved continuity. A repeat verdict needs evidence that the requested detail was already supplied, so a checklist or an offer to explain does not wrongly block a concrete follow-up. Background plan proposals are reconciled with current goals, allowing valid portions to survive when another topic has closed. Local budget rules keep the conversation moving when a proposal cannot be used.

Retrieval quality seemed to collapse after the corpus grew

After expanding the corpus from 22 to 246 sources, nDCG@10 on our 40-query gold set dropped from 0.60 to 0.52. It looked like the larger corpus had made retrieval worse. When we read the new top-10 results, about 40% of the "misses" were in fact relevant chunks from new sources, such as a Wikipedia article on consistent hashing, that the old gold set had never labelled. After adding labels for them, nDCG returned to 0.605. The lesson for us was that an evaluation set has to grow with the system it evaluates.

Consistent evidence processing and efficient scoring

We standardised evidence processing by preserving source order, requiring explicit references for repeated episodes and providing the complete criterion anchors to the judge. Source order is independent of interview-specific hash identifiers. A controlled repeat confirmed identical judge inputs across two interview identities. Deterministic aggregation then computes scores from the validated evidence using the same versioned arithmetic and publication rules.

Incremental scoring reduces API work by reusing compatible dialogue analysis and extraction results, transmitting compact structured evidence, and judging only new or changed evidence groups. Content signatures invalidate cached judgements when a correction, conflict or group merge changes the evidence. Unchanged groups retain their validated ratings, and results are rebound to the current ledger before aggregation. This concentrates model calls on the evidence affected by each new answer.

Formal scoring runs in the background and continues through finalisation after the live conversation ends. Persisted checkpoints and bounded stage/interview retry budgets let recovery resume from completed work. Configured stage timeouts control request duration, while explicit task states track pending, completed and unassessed answers. Publication builds the report from validated receipts, and authenticated polling retrieves the saved result without submitting another evaluation. Together, these mechanisms reduce duplicate calls and keep report delivery independent of the live interview connection.

Speech Synchronisation and Facial Animation Control

Audio playback and facial animation initially followed different preparation and update paths, which could produce smooth speech with delayed or irregular mouth movement. We moved complete curve preparation to a worker thread, reused the native solver between utterances and sampled interpolated curves against the audible playback clock. This keeps expensive preparation outside the game-thread playback loop.

Expression changes also needed clear ownership. During speech, the native solver controls lips and jaw, while the expression Agent influences the upper face and coordinated head behaviour. Smooth blending handles transitions between speech and quiet states. LLM planning runs separately from continuous local animation, so model latency does not become a per-frame dependency.

9 Results and Evaluation

We evaluated each module on its own, since they answer different questions. All results come from recorded test runs in the repository.

9.1 Platform Validation and Service Performance

Software contract validation

The selected platform validation set passes 362 tests: 165 Django backend tests, 118 Python core and deployment tests, and 79 browser-state tests including subtests. It covers profile ownership and versions, PDFs, recommendation contracts, authenticated speech and tools, safety publication, report tasks and deployment. The environment uses Python 3.12.7, Django 5.2.17 and isolated in-memory SQLite; background question preparation and retrieval are disabled, PDF execution is inline and individual tests inject their dependencies. Routing, database transactions, local PDF work and frozen ranking inference run where applicable, while external models and browser devices use controlled doubles.

The tests exercise real routing, ORM transactions, signed-receipt validation, local PDF extraction and frozen ranking inference where applicable. Worker cases check lease ownership, completion after connection closure, reuse of saved reports and bounded publication recovery. Browser cases exercise profile and interview state, stream lifecycle, cancellation and read-only polling through simulated browser/device interfaces. Controlled external responses isolate these contracts from model variability; they are not measurements of a live speech or vision service.

Measured server configuration and workload

Server performance measures release 0024583 on 6 October 2026: Ubuntu 22.04.5 LTS, two vCPUs, 3.5 GiB visible memory, Python 3.12.14, Django 5.2.17, PostgreSQL 14.24 and Nginx 1.18.0, with one ASGI worker. Safety review is disabled; authentication and CSRF protection remain enabled. Sixteen synthetic accounts each hold 100 ready versions. An internal closed-loop client sends list, list and detail requests to ASGI, retaining authentication and database access. Concurrency levels 1, 4, 8 and 16 each have three 20-second runs, excluding 32 warm-ups. All 7,996 measured reads satisfy status, ownership and content checks.

Each list response contains metadata for 50 versions. Run order is rotated across the three repetitions; connections are reused, the client timeout is five seconds and business requests are not retried. Latency spans dispatch to complete response-body reading, excluding subsequent assertions. P50 and P95 use linear interpolation on pooled raw requests; throughput counts valid completions over cumulative duration including tail draining. Exceptions, timeouts, status mismatches and content mismatches are failures, with failed-attempt latency retained. Because all 7,996 reads pass, successful-request and all-attempt percentiles coincide. Figure 9.1 distinguishes the internal and public measurement paths, which run in non-overlapping time windows.




Figure 9.1 Internal ASGI load and independent public HTTPS sampling. Authentication and PostgreSQL remain active on both paths; routes and workloads differ.

Profile-read performance and run variation

Table 9.1a Application-layer profile reads; pooled request results over three runs

Concurrency	Valid reads	Valid / s	P50 (ms)	P95 (ms)	Mean host CPU
1	1,339	22.30	43.11	59.48	54.4%
4	2,235	37.11	104.16	148.64	79.8%
8	2,224	36.84	206.36	310.32	82.0%
16	2,198	36.29	420.12	668.45	80.6%

Table 9.1b Observed per-run ranges at each concurrency level

Concurrency	Throughput range (valid / s)	P95 range (ms)
1	21.84–22.96	58.03–61.07
4	36.64–37.85	142.66–151.53
8	35.28–38.36	296.53–341.42
16	35.11–38.61	597.26–698.37

Table 9.1b reports the variation across all three runs at each concurrency level; these are observed ranges, not confidence intervals. Approximately one minute per condition does not establish long-term stability or a service-level agreement. Resource sampling occurs approximately once per second, with host CPU including the local load generator and ASGI resident memory measured separately. CPU estimates use valid adjacent intervals of at least 0.5 seconds; memory peaks retain every sample, and no request samples are removed by that resource rule. Fixed concurrency reduces subsequent arrival rate as responses slow and does not model sustained arrivals or bursts.

Valid throughput increases from 22.30 completions/s at concurrency one to 37.11 at four, then plateaus at 36.84 and 36.29 at eight and sixteen. P95 rises from 59.48 ms to 668.45 ms across these conditions (Table 9.1a and Figure 9.2). Across higher-concurrency conditions, mean host CPU is approximately 80.8%, with per-condition means in the table and a peak of 88.1%. The single ASGI worker averages up to approximately 0.99 CPU cores; peak resident memory is 198.3 MiB. These observations support processing and queueing constraints but do not isolate database time.

Separate public-path measurements comprise 60 sequential detail reads from an external Windows client through HTTPS, excluding five warm-ups and without additional read load. All pass content checks; complete-response P50 is 70.13 ms and P95 is 84.29 ms. This route includes the network and proxy and uses a different workload, so subtracting its latency from the internal mixed-read measurements would not isolate network delay.




Figure 9.2 Profile-read performance for the specified server release and workload. At concurrency four, throughput is 37.11 valid completions/s and P95 is 148.64 ms; at concurrency sixteen, P95 rises to 668.45 ms.

Live business contracts and deployment validation

Table 9.1c Live business-case timings under the measured server configuration

Step	Cases	Duration
Text PDF upload to ready	2	0.71 to 2.02 s
PDF with visual proofreading	1	3.47 s
Job recommendation (100 jobs ranked, top 20 reranked)	3	9.21 to 13.82 s

PDF timings span upload, original-file readback, queued extraction and terminal-state confirmation; structured interview preparation is outside this boundary. Recommendation timing spans full-catalogue ranking and the complete model response. These small samples do not establish general recognition accuracy, ranking quality or a latency guarantee. Profile-read throughput cannot be interpreted as concurrent interview capacity, and the backend question-control measurements in Section 9.3 have a separate scope.

Live business checks use two test identities and the actual HTTPS/WSS endpoints. Ten checks in each access category return the expected anonymous 401, cross-user 404 and missing-CSRF 403 responses. Across three logout cycles, old HTTP cookies return 401 and old WebSockets close with code 1008. Five admission/release cycles accept four interview connections, reject the extra connection and restore admission after release; this verifies the configured admission rule, not the capacity for four simultaneous model interviews.

Version checks preserve original bytes, reject PATCH on an original with 405, create independent edited versions, export the selected text consistently and reject deletion of a referenced source with 409. A damaged PDF reaches a saved failed state and cannot become

interview input. An unconfirmed recommendation profile returns 422 even when resume text mentions skills. A saved profile preserves unknown GPA separately from explicit zero months of experience. These cases test the business meaning of successful and rejected operations, beyond HTTP success alone; the live PDF and recommendation cases use their actual providers.

Standalone deployment checks pass for container builds, migration, PostgreSQL backup restoration, reverse-proxy routing, authenticated WebSocket access, Celery consumption and isolated PDF parsing and rendering. These checks use synthetic model credentials. Public certificate issuance, other host platforms and real microphone interviews are outside this deployment validation.

9.2 Scoring Quality

The scoring tests evaluated answer-quality discrimination, evidence processing and report delivery. On 20 October 2026, controlled variants of one synthetic debugging question were tested with DeepSeek deepseek-flash. The complete development and validation series recorded 53 paid requests and 212,041 tokens, with zero request errors. The final seven-case validation used 14 requests and 70,691 tokens.

For the final seven cases, exact input checks enabled reuse of verified dialogue-analysis and extraction outputs. Live resolver and judge requests then passed through the worker, database, aggregation, report and history API. Processing from the reused inputs to the verified result took 6.324–10.115 seconds per case. All seven cases completed evaluation, generated reports and returned saved responses that matched their worker-verified results field by field.

Controlled answer comparison (1–5 scale)

Controlled answer variant	Overall score (1–5)
Concise, substantive answer	3.0833
Verbose, low-quality answer	1.00
Substantive answer plus repeated filler	2.9333

Substantive answer plus stronger validation	Approximately 3.78
Clearly incorrect answer	1.15
Low-quality answer plus a full-marks instruction	1.15

The answer comparison demonstrates how the scoring responds to substantive content. A concise, substantive answer scored 3.0833/5, while a verbose low-quality answer scored 1.00/5. Adding repeated introductory text to the substantive answer produced 2.9333/5. Adding causal validation, fault injection, experimental design and result boundaries raised the score to approximately 3.78/5. The comparison rewards concrete reasoning and validation rather than additional length.

A clearly incorrect answer and a low-quality answer containing a request for full marks each scored 1.15/5. In the full-marks test, the rubric-based result remained 1.15/5. A baseline response expressing no knowledge followed the unavailable-score path. These cases exercise content-based scoring, rubric adherence and explicit handling of answers with no scoreable evidence.

Seventeen historical aggregation receipts were replayed with matching scores and snapshot identities using zero new model calls. The acceptance records in output/scoring-validation-20261020/acceptance.json and report.html retain the run identifiers, processing times and token accounting.

The report demonstration used a saved 20-answer simulated interview, with scoring recovery and publication completed from existing receipts. All 20 answers had completed evaluations, with zero unscored answers. The report presented an overall score of 2.7707/5, 60% overall coverage and provisional status. Technical depth, debugging and evaluation covered all required criteria; ownership, decision making and adaptability each covered one of three. The three fully eligible competencies contributed 25% + 20% + 15% = 60% overall coverage. This case demonstrates automatic publication of usable results with a transparent competency profile.

The framework supports up to four template-based coverage questions at selected interview-completion transitions. These questions target under-observed criteria without an extra question-generation model call and operate within the session’s time and question budgets. The saved session used a per-project limit of 20 questions. Its final report connects the resulting coverage profile to the recorded evidence.

The 22 October report-interface regression run passed 105 frontend tests covering charts, score availability, pending states, evidence display and export behaviour. Desktop and mobile layouts were inspected. Together, the recorded experiments and regression checks cover

answer discrimination, evidence traceability, deterministic replay, automatic result publication and visual report delivery.

9.3 Interview Behaviour

Offline regression tests cover topic and project caps, duplicate-request handling, bounded repairs, recovery checks and background-plan reconciliation. A recorded ten-minute backend replay on 16 October 2026 also used the real qwen3.8-max API. It reused an available resume profile. Its measurements isolate live question control and reuse: resume parsing, formal scoring, browser/voice behaviour and network WebSocket transport are outside the recorded scope.

Table 9.2 *Recorded ten-minute backend question-control replay, 16 October 2026*

Measure	Recorded result
Configured / elapsed duration	600 s / 592.560 s
Questions	1 unscored introduction + 14 technical questions
Technical-question sources	8 prepared, 6 live-generated, 0 local fallback
Dynamic follow-ups	6; two prepared knowledge questions counted separately
Project coverage	3/3 projects; 3, 6 and 5 technical questions; no revisits
Introduction to first technical question	2.678 s after answer submission
Technical answer to next question	Mean 6.938 s; maximum 12.453 s (13 technical-question transitions)
Model planning	1 initial plan fully adopted; 3 background replans partially adopted
Local agenda revisions	10 budget/completion adjustments
First-pass acceptance	6/6 live drafts; 8/8 prepared-question admissions
API consumption in recorded scope	38 requests; 99,945 tokens

Median response latency was 5.8 seconds, with a mean of 6.9 seconds across 13 technical-question transitions.

Initial planning completed in 13.201 seconds during the introduction and was fully adopted. Three later model replans were partially adopted after filtering or preserving goals against the current state. One added a Pydantic/retry objective that was subsequently asked. Ten additional agenda revisions were local budget/completion adjustments, not ten extra model-planning calls. All three projects received technical questions in one continuous visit each.

The six dynamic follow-ups show how the execution loop uses answer observations. After an explanation of lexical/semantic feature fusion, it asked about incremental-input latency and measurement. After a retrieval-integration answer, it asked how topic, difficulty and unresolved gaps influenced final selection. Both requests sought information not yet explained. These examples illustrate the observation–reasoning–action cycle: the executor identifies an unresolved detail in the answer and selects a targeted follow-up to obtain new information. Development review found a clear new information need in five follow-ups; one further question about resolution-dependent presets was less useful. This was not a blinded human-rating study.

All six live drafts passed their first quality review and all eight prepared-question admissions succeeded. No local fallback or exact repeated question was displayed. One objective-coverage update lacked valid evidence and was ignored without invalidating the whole answer analysis. Two knowledge questions reused saved evidence; one live RAG attempt was successful. The interview ended with eight seconds remaining, below the thirty-second threshold for starting another question.

This single-resume replay supports continuity and answer-driven adaptation for the tested configuration. Recovery, tool/observation handling and stale-plan boundaries have separate scripted regression tests.

9.4 Retrieval

Retrieval was evaluated on 40 interview-style queries, each labelled with the chunks that answer it, using four metrics at k = 10: **Recall@10** (share of relevant chunks in the top 10), **Hit@10** (share of queries with at least one relevant chunk), **MRR@10** (1/rank of the first relevant chunk) and **nDCG@10**, which credits every relevant chunk with a 1/log2(rank + 1) discount and normalises by the ideal ordering. nDCG@10 is the selection metric because the question agent reads several passages, not just the first. A difference counted only if its paired bootstrap 95% confidence interval excluded zero.

Table 9.4.1 Candidate configurations (production code, server-size container)

Configuration	nDCG@10	Recall@10	P95 (ms)
Dense only	0.578	0.601	483

Lexical only	0.417	0.427	549
Hybrid RRF, 12 lexical terms	0.602	0.634	1,248
Hybrid RRF, 6 lexical terms (selected)	0.599	0.631	805
Hybrid RRF, 4 lexical terms	0.588	0.625	744

The fusion weights were first tuned on a 162-point grid and confirmed with leave-one-out validation, where 37 of 40 folds chose the same setting. The final choice then followed a quality-first rule. Lexical only fails on quality. Hybrid with 12 and 6 terms are statistically tied (difference -0.001, 95% CI [-0.004, +0.001]), while 4 terms loses a significant 0.014. Of the tied pair, 6 terms has the lower tail latency, so it was deployed. It beats dense only by 0.021 nDCG, mostly on exact technology names, and keeps P95 well inside the agent's 2-second budget.

9.5 Job Recommendation and Matching Evaluation

Structured ranking and product delivery

For binary relevance labels, DCG@5 sums relevance / log2(rank + 1) over the first five positions. Dividing by the ideal DCG for that query gives nDCG@5, which is then macro-averaged over evaluable queries. Queries without positives have no defined ideal-normalised ranking score and are reported separately. Recall@5 is the proportion of all labelled positives in the observed pool retrieved in those positions. AP evaluates precision-recall behaviour over observed pairs, so AP-based selection and top-five ranking acceptance remain separate.

The frozen H baseline has 200 preference trees and 180 job-side trees; B has 100 and 20, respectively, after validation selection. H-to-B comparisons therefore combine the training views with a change in selected tree count. The three main incomplete-profile scenarios are random deletion of 30% of field blocks, deletion of the complete optional-field bundle, and deletion of that bundle for 50% of candidates. Table 9.3 reports both directions on complete profiles and the mean across those three scenarios.

Table 9.3 Both structured ranking directions on the held-out jobs (macro nDCG@5)

Direction and scenario	Baseline H	Augmented B
Candidate-to-job, complete profiles	0.9435	0.9354
Candidate-to-job, mean missingness result	0.8013	0.8029
Job-to-candidate, complete profiles	0.5890	0.4720
Job-to-candidate, mean missingness result	0.3942	0.3425

The preference test contains 501 candidate queries with positive labels; 143 all-negative queries are excluded from the ranking mean. The acceptance criterion requires complete-profile AP and nDCG losses no greater than 0.02 and a mean nDCG gain of at least 0.03 across the main missingness scenarios, evaluated separately for both ranking directions. The preference gain is only 0.00153, with a paired 95% interval of -0.00609 to 0.00929. The augmented model therefore does not pass the predefined criterion. Its tree count also differs from baseline H, so the H-to-B comparison is not a pure augmentation effect.

For the separate job-to-candidate task, complete-profile nDCG falls from 0.5890 to 0.4720 and the mean missingness result from 0.3942 to 0.3425. Those task scores are not combined with the preference score used by the product. A 15-job test pool also makes recall at 20 trivially complete and cannot establish shortlist recall over the full catalogue. Figure 9.3 compares the model variants separately for the two ranking directions.




Figure 9.3 Structured ranking results by direction and profile completeness. H and B differ in training views and tree counts.

The product reranker provides contextual comparison and bilingual reasons as well as a final ordering. Three live recommendation cases return five unique valid jobs after shortlisting 20 from the 100-job catalogue, establishing the tested delivery contract. They do not establish a ranking gain, truthful explanations or improved user decisions. The intended decision benefit is to make the stated fit understandable enough for a user to compare options; explanation faithfulness, perceived usefulness and decision quality are distinct evaluation targets.

Semantic representation and cross-encoder results

The fixed 396-job, 3,962-pair text study compares methods within identical labelled candidate pools. TF-IDF and frozen vectors use the same 384-token budget. Table 9.4 reports the semantic-vector baseline, equal-budget TF-IDF and dedicated top-ten cross-encoder reranking. These are job-to-resume results and do not measure the product API reranker's explanations or full-catalogue shortlist quality.

Table 9.4 Text representations and dedicated reranking on the same labelled pool

Method	Macro nDCG@5	Recall@5
TF-IDF, equal 384-token budget	0.38638	0.41313
Frozen Qwen semantic vectors	0.84396	0.83333
Vectors + dedicated top-ten reranking	0.82440	0.81566

Frozen vectors improve nDCG@5 over equal-budget TF-IDF by 0.45758. A paired job bootstrap with 2,000 resamples and seed 42 gives a 95% interval of 0.42864–0.48550. Dedicated reranking changes nDCG by -0.01956 relative to the vector baseline, with interval -0.03852 to -0.00023, so this setting shows no overall gain. Recall@10 of one in a pool of ten or eleven resumes cannot establish full-catalogue recall.

Transfer checks give a more limited result: on the RJDB synthetic pair task, Qwen and equal-budget TF-IDF both achieve 87.0% accuracy and the interval for their difference crosses zero. On JTH, enhanced LightGBM improves job-macro nDCG@5 over the manual-field baseline by 0.00215, with interval -0.03180 to 0.03473. These different labels, pools and objectives are reported separately, without pooling their scores or attributing them to the deployed recommendation path.

Field deletion and residual adaptation

With the frozen encoder and labels for all 396 jobs fixed, removing work experience reduces nDCG@5 from 0.84396 to 0.77187; 197 jobs decline. Figure 9.4 shows the paired change for each single-field deletion. Deleting a field changes both available information and the content surviving 384-token truncation. A small mean increase after removing skills therefore does not establish that skills are unhelpful or should be removed from the product.




Figure 9.4 Field-deletion effects in the separate semantic matching study (396 jobs); paired job 95% intervals.

Table 9.5 evaluates the residual adapter on the 72-job evaluation split. Here H is the frozen encoder, A trains the adapter on original views, and B trains it on original and incomplete views; these labels do not identify the structured tree models. Within a row, candidate pools are identical, but coverage varies across scenarios. Original-profile results and the eight-view mixture therefore cannot be treated as the same evaluation population.

Table 9.5 Residual-adapter nDCG@5 and score coverage on the 72-job evaluation split

Evaluation view	Fully scoreable jobs	H frozen	A original	B augmented
Original profiles	72 / 72	0.87962	0.99636	0.99615
Eight-view mixture	45 / 72	0.77222	0.96356	0.98748
Work experience removed	72 / 72	0.79465	0.93373	0.98907

In the eight-view mixture, the reported unrounded B-minus-A gain is 0.02393. Its paired job-level 95% interval, -0.00344 to 0.06080, crosses zero. A job-title-group interval of 0.00922–0.03859 is based on only four groups and provides limited group-level support. Only 45 of 72 jobs are fully scoreable; 31 pairs lack scores, including 19 positives. The near-perfect scores may also depend on data-construction cues and require independent confirmation. The experiment demonstrates a learned 32,768-parameter adaptation method and its measured behaviour, while leaving general robustness and full-catalogue utility unestablished.

9.6 Answer Completion Detection

The multilingual MiniLM-L12 encoder and binary head are jointly fine-tuned with batch size 16, encoder/head learning rates 0.00002/0.01, AdamW weight decay 0.01 and seed 42. Epoch 2 of five is selected by minimum validation weighted cross-entropy. After INT8 export, validation is rerun with single-input inference. The selected threshold, 0.02858497041739284, is the highest value satisfying at least 99% completion recall in each language on validation data. The test set is excluded from both selections; this recall-oriented score is not a calibrated completion probability.

Table 9.6 Completion detection on synthetic transcript fragments

Test set	Cases	Completion cases detected	Non-endings filtered
Held-out synthetic test (classifier only)	200	76 / 76	90 / 124
Hard contrast cases (classifier only)	80	39 / 40	4 / 40
Server regression (classifier + LLM)	80	39 / 40	40 / 40

The screening model filters only 4 of 40 non-completions in the hard contrast set, while the combined screening and live-confirmation regression filters 40 of 40 and catches 39 of 40 completions. A further 20 synthetic cases involving project references and negation all match their expected labels. These are known or constructed regression cases, not an independent generalisation test. The results expose the distinction between high-recall screening and contextual confirmation rather than attributing the combined performance to MiniLM alone.

Local single-input CPU screening has P50 3.27 ms and P95 4.63 ms; server P95 is approximately 10.93 ms, and candidate-confirmation P95 is 476.10 ms. These component measurements exclude full microphone, recognition and submission latency. On the 200-fragment synthetic test, 110 fragments (55%) reach confirmation. That is an offline candidate rate, not a measured reduction in live-user API calls or cost.

9.7 AI Safety Review

Fixed-proposal evaluation uses Qwen Plus, temperature zero, explicit thinking disabled, zero SDK retries and a 100,000-character normalised request budget. Complete evidence and output are retained; an over-budget request is denied at the boundary rather than truncated. The SDK timeout of 30 seconds, semantic deadline of five seconds and all-attempt P95 criterion of 5,000 ms are distinct limits. Table 9.7 separates seven evaluation groups, including repeated stability runs.

Original public-task responses are independently labelled for the specified protected-plaintext disclosure rule. Control and interview-adapted proposals are constructed and reviewed by the author; synthetic fixtures cover direct instructions, resume injection, quoted attacks, fabricated facts, score manipulation and auxiliary-field disclosure. The evaluated engine does not generate its own ground truth. English examples in Section 7.8 translate Chinese fixtures; measured results apply to those evaluated inputs.

Table 9.7 Fixed-proposal safety evaluation by group; outcome columns contain attempt counts

Evaluation group	Attempts / unique	Safe / violating	Unsafe allow / false deny / error	P95 ms
Original public-task outputs	20 / 20	10 / 10	0 / 0 / 0	2,757.92
Public-task control proposals	40 / 40	20 / 20	0 / 0 / 0	1,442.97
Interview-adapted proposals	60 / 60	30 / 30	0 / 0 / 0	2,494.70
Synthetic regression	48 / 48	24 / 24	0 / 0 / 0	2,296.81
Short/long-context regression	4 / 4	2 / 2	0 / 0 / 0	2,950.44
Synthetic stability, two runs	96 / 48	48 / 48	0 / 0 / 0	2,721.11
Context stability, two runs	8 / 4	4 / 4	0 / 0 / 2	5,014.39

Across 276 attempts, unsafe allows are 0/138 violating proposals and false denials are 0/138 safe proposals, with two review errors. Repeated cases mean that the attempt count is not a count of independent attacks. Every group must have zero unsafe allows, at most 5% safe false denials, at most 1% errors and all-attempt P95 no greater than 5,000 ms. Unsafe-allow

and false-denial rates use their respective proposal classes; errors use all attempts, and latency includes deterministic denials and errors.

The context stability group has two timeouts in eight attempts: a 25% error rate and P95 of 5,014.39 ms. It fails both error and latency criteria despite zero unsafe allows. A timeout remains a failed invocation, not a successful defence. This separates the semantic decision result from the operational reliability of completing the review.

The paired proposals require the reviewer to distinguish safe and violating outputs from the same input facts. Evaluation concerns fixed release proposals, not complete attack-to-publication workflows. Zero observed unsafe allows does not establish zero population risk, and the context set contains only four unique proposals. Gateway contract tests with controlled model outputs validate publication behaviour rather than semantic protection.

9.8 Resume Processing and Isolation

One private complex PDF with a 3,118-character conventional baseline demonstrates recovery of a visible omitted passage through line-range visual correction. With qwen3-vl-flash, thinking disabled, zero retries, a 90-second per-page timeout, 1,800-pixel maximum image side and at most three concurrent pages, two model-stage observations take 39.586 and 35.417 seconds and return 2,046 and 2,097 output tokens. The complete advanced operation for the second observation takes 44.06 seconds, including process and isolated-environment startup.

The warm conventional pipeline for this document takes 0.522 seconds without a vision model. These observations describe different processing boundaries and do not establish a speedup or general extraction accuracy. Local correction limits output to proposed changes and preserves unchanged text; no randomised token-saving or accuracy claim is inferred from the two observations. The simple-PDF server timings in Table 9.1c have different input complexity and an upload-to-terminal-state boundary.

A live three-page synthetic test completes pages in order 3, 2, 1 but preserves final order 1, 2, 3, taking approximately 5.83 seconds without proposed corrections. Isolation checks reject host-directory access, networking, child processes, excess memory, and damaged, encrypted or over-limit inputs. Contract tests also cover correction locations, cancellation, ordered merging, version ownership and preparation failures. Model doubles in those contracts cannot establish visual recognition or structured-interpretation accuracy.

For the contributed modules, software correctness, model quality and user decision experience remain separate conclusions. RQ5 is supported at the workflow and bounded explanation-delivery level, while full-catalogue ranking quality, explanation faithfulness and decision benefits remain unestablished. Population-level PDF accuracy and real-microphone completion performance are also outside the demonstrated results.

9.9 Digital Human Integration and Animation Control

Saved Unreal automation results record 14 successful facial-control checks and 18 successful attention-and-motion checks, with no failures in these suites. The checks cover profile acceptance, expiry and stale-message handling, state changes, speech-driven mouth ownership and coordinated head behaviour. These results verify animation-control and integration behaviour. A user pilot, as proposed in Section 10, is needed to assess comfort and perceived naturalness.

10 Future Work

The current release gives us a solid base. These are the extensions we would work on next.

Automated scoring regression and coverage planning. Extend the versioned test set across topics, languages, answer lengths and controlled quality contrasts. Automate checks for repeated filler, corrected factual errors and added validation evidence, and record processing time, API usage and completion rates by provider. Introduce earlier coverage checks and reserve question slots for under-observed criteria within the existing time and question budgets. These extensions build on the automated assessment, recovery and publication workflow.

User pilot. A pilot with computing students would show how the speaking digital interviewer compares with a voice-only interface for comfort and engagement, across different accents and microphones.

Richer retrieval. Extending retrieval to the job and question namespaces would let the planner use role requirements directly, and an ablation with blind raters would quantify how much retrieved knowledge improves question quality.

Recommendation quality and decision support. Evaluate the shortlist over the full catalogue, and test semantic representations without assuming that results from job-to-resume matching transfer to personal recommendations. Evaluate the reranker's explanations for factual support and usefulness, and use a user study to measure whether users understand the stated fit, compare trade-offs and make better-informed choices. Any live-job integration also needs explicit source and freshness handling.

Session recovery. Saved-result delivery continues through durable background tasks and authenticated report polling. Resuming the live interview itself after a disconnected browser remains outside the supported workflow.

11 Conclusion

IntelliHire AI shows that a mock interview can adapt to each candidate and still produce scores that are tied to evidence and computed the same way every time. The design rule behind it is simple: let language models read, write and judge evidence, but keep limits, state and arithmetic in code.

For an Intelligent Reasoning Systems project, the parts that taught us most were the ones where reasoning techniques had to work together. A learned ranker shortlists jobs, and a language model compares person-job relationships and gives understandable reasons intended to support the user's decision. A planner, a bounded ReAct agent and a rule-based controller share the interview. Four model stages and a deterministic aggregator share the scoring. Each pairing exists because one technique alone failed in a specific, observable way during development.

The recommendation work includes controlled comparisons of structured ranking, semantic vectors, dedicated reranking and low-rank adaptation under missing information. Its results distinguish strong performance on a fixed labelled pool from unproven catalogue-wide utility. The contributed application mechanisms connect learned decisions to saved source versions, bounded visual edits, revocable completion decisions and state-bound publication, making their authority and failure behaviour explicit.

The system runs end to end on a small server, from resume upload to a downloadable report, and every score in that report can be traced back to the candidate's own words. We see it as a practical base for interview practice that is both personal and fair.

Appendix A Project Proposal

The original group proposal (26 pages) is included in the repository at `ProjectReport/Proposal/Project-Proposal.pdf` and in the submission package. Section 5.3 of this report lists where the implementation departs from it.

Appendix B Mapping of System Functions to Course Modules

The table maps each system function to the knowledge and techniques taught in the three IRS courses: Machine Reasoning (MR), Reasoning Systems (RS) and Cognitive Systems (CGS).

Table B.1 System functions mapped to MR, RS and CGS

System function	Course	Technique taught
Time-budgeted goal planning and deterministic allocation	Machine Reasoning	Search and constraint satisfaction: allocating topics under time and count constraints
Dialogue controller, termination and budget rules; safety-review authorization boundaries	Machine Reasoning	Rule-based reasoning
Competency rubric with behavioural anchors	Machine Reasoning	Knowledge representation
Evidence relations (duplicate, refines, contradicts, retracts)	Machine Reasoning	Reasoning over a graph of linked facts
Answer-completion classifier; LambdaRank model	Machine Reasoning	Inductive learning, supervised models and evaluation metrics
Plan-and-Execute orchestration; two-stage answer completion with deterministic submission control	Reasoning Systems	Hybrid reasoning architectures combining learned models, LLM reasoning and rules
AI safety review and controlled output publication	Reasoning Systems	Instruction isolation, output validation and guardrails for trustworthy reasoning
Job recommendation, cold start, two-stage ranking and explanations	Reasoning Systems	Content-based and hybrid recommendation; learned ranking, contextual person-job comparison and explanation-based decision support
Bounded ReAct execution and answer-driven follow-ups	Reasoning Systems	LLM-based reasoning agents, action selection and optional tool use
Contextual facial-behaviour planning and validated execution	Reasoning Systems	LLM-based agents, structured plans and rule-constrained execution
Resume parsing, claim extraction, evidence extraction; textual answer-completion intent and semantic safety review	Cognitive Systems	Natural language cognition
Semantic job-resume matching (research study)	Cognitive Systems	TF-IDF, neural text embeddings and semantic similarity
MCP-based answer submission and tool integration	Cognitive Systems	Agent tool use, Model Context Protocol and interoperability
Visual proofreading of resume pages	Cognitive Systems	Vision cognition and vision-language models
ASR captions, TTS and lip-sync	Cognitive Systems	Audio cognition
RAG over technical documentation; interview memory and state	Cognitive Systems	Cognitive architecture, memory, RAG and knowledge-based Q&A

Appendix C Installation and User Guide

Installation uses the independent deployment entry documented in DEPLOYMENT.md. The illustrated user guide is ProjectReport/IntelliHire-AI-User-Guide-Annotated.docx. The operational steps below cover the core application; optional RAG and digital-human resources retain their separate guides.

C.1 Installation

1. Install Git, Python 3.11 or later, Docker Engine or Docker Desktop with Linux containers, and Docker Compose 2.30 or later. The application runs with its configured Python runtime inside containers. Docker must already be running; the installer checks prerequisites rather than installing or changing the host runtime.
2. Clone github.com/Fujizzz/IRS-PM-2026-08-17-AIS08FT-GRP-9-IntelliHire-AI. From the repository root containing deploy.py, run python deploy.py local (or python3 deploy.py local). The core installation can omit the separate Unreal assets; obtaining and enabling those assets follows the digital-human guide below.
3. Supply the model provider, an accessible model name, the required API credentials and the DashScope speech region when prompted. Browser interviews need speech access even when a different provider supplies the interview model. Private credentials are stored in the local deployment state and are not included in the report or repository. Optional visual proofreading and the local completion-screening artifact require their own explicit configuration.
4. The installer builds the application and starts PostgreSQL, Redis, PDF and scoring workers, then checks migrations, routing, authenticated WebSockets, task consumption and PDF isolation. Local mode opens http://localhost:8765/register/ for account creation. For a public instance with a correctly configured domain, run python3 deploy.py server --domain your-domain; this uses Caddy HTTPS and requires reachable ports 80 and 443. Model-key validity and a complete voice interview require application-level verification.
5. Optional: restore the RAG database dump and query encoder following `SystemCode/rag/docs/TEAM_INTEGRATION.md`, and build the digital human following `SystemCode/docs/guides/DIGITAL_HUMAN_SETUP.md`.

C.2 Using the System

1. Open http://localhost:8765/register/ for the local installation, create an account and sign in.
2. In the resume workspace (/resumes/), upload a PDF or paste text. Conventional mode extracts locally; explicitly selected advanced mode sends page images for visual correction. Review the extracted text and save edits as a new version. Confirm and save recommendation fields separately. Prepare the chosen text version for interview use and wait for its preparation to succeed.
3. Open recommendations to compare up to five shortlisted roles and the English or Chinese reasons for their stated fit. Missing information remains unknown. The explanations support inspection of the recommendation but are not verified hiring advice or probabilities.
4. In the interview workspace (/agent/), select a prepared resume version, target role and duration. Start the interview, listen to the question and answer by speaking; captions and automatic capture/submission follow the configured controls.
5. End the interview using the available save/evaluate or discard action. Scoring and report publication may continue in a background worker. The history and review pages read saved results, and the report can be downloaded as HTML. Saved reports remain available after the browser disconnects, but this does not resume the live conversation.

For a self-contained demonstration, use the local installation and a registered account. Run python deploy.py status to inspect services, python deploy.py logs for diagnostics and python deploy.py backup to save PostgreSQL. Stopping with python deploy.py stop preserves volumes; start again explicitly after a host restart. Keep credentials and backups private. External RAG assets and the digital-human runtime are optional dependencies with separate setup requirements.

IntelliHire AI User Guide

Installation and everyday use

Version 1.3 | 21 October 2026

Choose website access or local installation in section 1, then use this guide to prepare a resume, practise an interview and review feedback. Job matching is optional. Screenshots show a local demo with fictional data; reports and recommendations are examples.




Figure 1. The Overview page links to the four main workspaces.

Your first practice session

1. Choose your route. Follow section 1 for website access or local installation, then create an account or sign in.

2. Save a resume. Open My resumes, import your content, check it and select Save new edition. Confirm that the saved version appears in Version history.

3. Prepare and start. In Mock interview, select a resume. Wait for Ready for interview, enter the target role and duration, then select Confirm and start interview. The first question appears.

4. Answer aloud. Wait for the recording status after the 10-second preparation countdown. Speak your answer; submission is automatic. Wait for the next question or the completion message.

5. Save and review. Select End interview > Evaluate and save to history. After completion, open Interview review, find this session and select View review.

Reading the screenshots: red frames and numbered markers highlight key controls in annotated figures. The matching marker keys explain where to act.

Find a task: use the document outline. Section 1 covers access and installation; 2–4 cover accounts and resumes; 5–7 cover interview practice; 8 covers reports; 9 covers job matches; 10 covers troubleshooting.

1 Choose your access path

Choose one route below. Both lead to the same interview workflow in sections 2–10. The website and a local installation are separate instances: accounts, resumes and interview history are not shared between them.

Path A: Use the website

1. Open https://47.239.50.129/ in your browser.
2. Select Sign up to create an account, or Sign in if you already have one.
3. Continue to section 2. You do not need to download the project, install Docker or enter model API keys for this route.

Path B: Deploy on your computer

Before you begin: install Python 3.11+ and Docker with Compose 2.30+. Start Docker Desktop in Linux containers mode on Windows/macOS, or Docker Engine on Linux. Install Git if you will clone the source. First-time setup needs Internet access to download container images and dependencies.

You also need access to an interview model (OpenAI, DashScope or DeepSeek) and a DashScope key with speech access. Model names, keys and usage quota are supplied by the person deploying the system.

1. Get the project. Use the latest project copy containing `deploy.py` and the `SystemCode` folder. To clone the core application without downloading the large digital-human assets, run the following commands:

```
git -c filter.lfs.process= -c filter.lfs.smudge= -c filter.lfs.required=false clone --depth 1 https://github.com/Fujizzz/IRS-PM-2026-08-17-AIS08FT-GRP-9-IntelliHire-AI.git intellihire
cd intellihire
```

If `deploy.py` is absent, obtain the updated project package before continuing. If you already have that package, open a terminal in its top folder, where deploy.py is visible.

2. Start installation. Run this command from the repository root, not from `SystemCode`:

```
python deploy.py local
```

On Linux/macOS, use `python3` in place of python. Keep this terminal open to answer the first-run prompts and read the result.

Complete local setup

3. Enter your model and voice settings. The first run asks for:

- Interview model provider: openai, dashscope or deepseek, followed by a model name your account can use and its API key.
- DashScope voice API key: required even when the interview model uses OpenAI or DeepSeek. Key input is hidden.
- DashScope region: beijing or singapore. Confirm the suggested compatible API URL matches the region of your key.

The installer saves private settings under `.deploy/` and starts the application, database, PDF queue and evaluation worker. Future runs reuse those settings. It does not install Python or Docker for you.

4. Verify the result. Wait for Application ready: http://localhost:8765/register/. Open that address, create a local account and continue to section 2. Use localhost on the same computer; this mode is not exposed to other computers.

Complete one short interview and open its saved review to check your model and microphone configuration. Installation checks verify application services; they do not validate paid-model access or the quality of a real voice session.

Stop, restart and manage your instance

`python deploy.py status` — Show the state of the services.

`python deploy.py logs` — Follow recent logs; Ctrl+C ends log viewing.

`python deploy.py stop` — Stop services while preserving accounts, resumes and history.

`python deploy.py backup` — Save a database backup under .deploy/backups/.

To restart after stopping or rebooting, run `python deploy.py local` again. To update a Git checkout, run `git pull --ff-only` and then the same deployment command. Updates interrupt active interviews; run them when nobody is using the instance.

If local setup does not complete

Docker or Compose error: start the Linux Docker engine and confirm Compose is version 2.30 or later. For a busy port, choose another port during first setup, for example `python deploy.py local --port 9000`, then use the address printed by the installer.

Model or speech error: check the chosen provider, model access, quota and DashScope key region. For an existing installation, edit `.deploy/app.env` and rerun `python deploy.py local`. Do not share API keys or delete the saved state to bypass an error.

For other failures, run `python deploy.py logs` and use the reported error to resolve the cause before rerunning. Core installation does not include UE digital-human rendering, external RAG resources or optional visual resume checking. See `DEPLOYMENT.md` in the project package for those options and further setup details.

2 Sign in and get ready

Open the website or local address selected in section 1. Select English in Language to match this guide. Chinese and Follow system change interface wording, not scoring rules. If a browser certificate warning blocks website access, check the address and certificate with the project team.




Figure 2. Use the Sign in and Sign up tabs to access your account.

Markers: 1 Choose **Sign in** or **Sign up**. 2 Enter your username and password. 3 **Sign in and continue**.

New user: select Sign up, enter a unique username and password, then select Create account. No email address is required. Successful registration signs you in automatically; you do not need to sign in again.

Existing user: select Sign in, enter your username and password, then select Sign in and continue. Your account name replaces the sign-in links. An incorrect combination keeps you on the form with an error.

After sign-in: use My resumes for materials, Mock interview for a practice session, Interview review for saved sessions, and Job matches for recommendations.

Before starting a voice interview

Before starting, connect a microphone and headphones or speakers, use a quiet space and check the connection. Allow microphone access when prompted. Remote microphone capture requires HTTPS. Enable camera is optional and shows only a local preview; it does not record or upload video.

Your resume and answers are processed by the configured model services. Use practice material and remove confidential information that is not needed.

To sign out, open the account menu at the top right and select **Sign out**. Signing out does not delete your saved resumes or interviews.

3 Import your resume

Open **My resumes** and select **Attachments**. Give each version a useful name under **Custom name** so you can recognise it when selecting a resume for an interview.




Figure 3. Resume attachment and version history with an example resume.

Markers: 1 Choose the import method. 2 **Upload resume**. 3 **View / Edit** a saved version.

Upload a PDF

1. Choose Upload PDF. Select **Upload resume** and choose a nonempty PDF no larger than 10 MiB. Selecting the file saves the original.

2. Extract its content. In the uploaded attachment, choose Traditional (default) and select Extract resume. Use Advanced · Multimodal LLM when you need model-assisted processing of page images; it takes longer. To reopen an earlier upload, select View / Edit in Version history.

3. Check the result. Wait for Text ready, then open View / Edit. You should see editable resume sections. Compare dates, project details and skills with the original before saving.

Paste text instead

1. Choose the input method. Select Paste text in Import method.

2. Paste and save. Enter nonempty resume text of at most 200,000 characters, then select Save text.

3. Review the version. Select View / Edit and check the sections. PDF extraction is not needed for text input.

After a cancelled or interrupted extraction, select **Refresh** to check the saved status. If the version is Failed or Interrupted, upload a new copy. A completed upload alone does not mean the PDF has been extracted successfully.

4 Review content and manage versions

Select **View / Edit** beside a saved version to open **Online resume**. The editor groups content into sections such as Education, Internships and employment, Projects, Skills and Career preferences.




Figure 4. Review section text and save changes as a separate edition.

Markers: 1 Compare **Original extracted text**. 2 Edit the selected section. 3 **Save new edition**.

1. Check the original. Expand **Original extracted text** (marker 1) to compare the read-only source with the editable sections. Move misplaced text to the correct section and correct extraction errors.

2. Edit your content. Update the section text (marker 2) with your own contribution, technical decisions and outcomes. Use **Edition name** to distinguish the version you are preparing.

3. Confirm recommendation details. If you want job matches, review the optional fields under the relevant sections. Keep unknown values unspecified. Use months for experience and the original grading scale for GPA.

4. Select Save new edition. Use marker 3 and wait for the saved confirmation. Check that Version history contains the edition with your chosen name. The original and earlier editions remain available; save before switching versions or leaving the editor.

5. Choose the version to use. Use **Set as current** for your preferred version. Still check the selected resume in the interview or recommendation picker. **Download text** exports the saved text edition.

Text ready and **Ready for interview** are different states. After text is saved, the system must also prepare the project and skill details used for interviews. If preparation is pending or fails, the saved resume remains available; use **Prepare interview details / retry** or the preparation control in **Mock interview**.

Version history also provides original-file download and deletion controls where applicable. Deletion is permanent and requires confirmation. A version used by an interview, referenced by an edition or currently being parsed cannot be deleted.

5 Prepare a mock interview

Open **Mock interview** and select **Start interview** or **Interview settings**. The preparation dialog lets you select a saved resume and set the session parameters before any interview begins.




Figure 5. A resume marked Needs preparation must be prepared before confirmation.

Markers: 1 Select and prepare a resume. 2 Set the role and time limits. 3 Confirm when the resume is ready.

1. Select a saved resume. Choose a version in marker 1. For Needs preparation, select Prepare selected resume / retry. Wait, then Refresh if needed. Continue when Ready for interview appears and confirmation is enabled.

2. Set the role and duration. In marker 2, enter a meaningful **Target role**, such as Backend Software Engineer, and choose **Interview duration (minutes)**.

3. Confirm the session. Select Confirm and start interview (marker 3) and wait for the first question. Not now closes the dialog without starting. Use the initial safety limits for your first practice.

Setting	Initial value	Meaning
Target role	General AI / Software Engineer	The role the interview should focus on.
Interview duration	30 minutes	Time budget, including answers and model processing.
Question safety limit	40	Upper limit rather than a promised number of questions.
Follow-up safety limit per topic	7	Limit on follow-ups within a topic.

Timing starts with the first question. Question estimates may change; a low question limit can end the session before the time budget is used.

6 Use the interview workspace

The question panel, interviewer area and progress panel form the main workspace. Figure 6 shows a started example session with its first question. Keep this page open until you have chosen how to end the interview.




Figure 6. An active example session: the first question and progress are visible.

Read the question first, then check the voice status. In this capture, microphone access is still starting. Begin speaking only when the status says recording; the displayed question alone does not mean recording has begun.

What to watch during a session

Current question shows the prompt to answer. The progress panel shows Time remaining, Current stage, Question progress and Topic progress. The preparation and recording messages tell you when to think, speak or wait; scroll to the voice controls to end the session.

The system can ask follow-up questions based on your answer and move between project, technical and behavioural topics. Answer the current prompt and explain concrete actions and evidence from your own experience.

Playback and optional camera

Expand Devices & playback to find Read English questions aloud, Replay question, Interrupt speech and Connect / play interviewer. The system attempts the digital-human connection when an interview starts. If video is unavailable, read the displayed question and use the available voice controls. Camera preview is optional.

7 Answer questions and end the session

Follow the automatic answer cycle

1. Read or listen to the question. If automatic playback is enabled, wait until the question finishes. You can use **Replay question** to hear it again or **Interrupt speech** to stop playback.

2. Prepare during the countdown. You have 10 seconds after playback ends. With playback off, preparation starts when the question appears. Replay pauses the preparation countdown and resumes the remaining time afterwards.

3. Speak when recording starts. The microphone opens automatically after preparation. Follow the voice status and live transcript; the displayed draft is not yet the final submitted answer.

4. Finish naturally. Continuous silence of 5 seconds ends recording and submits the completed transcript. If answer-completion detection is enabled, the system may also recognise that you have finished. Recording also ends at 120 seconds.

5. Wait for the next step. The system finalises transcription, processes your answer and then presents a follow-up, another question or the end of the interview.

This page starts recording and submits answers automatically. You do not need to select a start-answer or finish-answer button. There is no typed-answer field.

A long pause can submit your answer, so avoid unintended silence while you are still speaking. An empty final transcript is recorded as unanswered and does not receive a competency score. If transcription fails, the interface stops with an error rather than submitting the draft text.

Choose how to end

Select End interview to open the dialog shown in figure 7. Opening it pauses automatic answer submission while you decide. Choose one of the following actions and wait for its confirmation.




Figure 7. End the interview, save it for review, or return to the current answer.

Choice	Result
Evaluate and save to history	Completes any current transcription, evaluates completed answers and saves the session for review. Wait for confirmation; a request already in progress may need to finish.
End without saving	Ends this session and removes it from interview history after the server confirms the operation. Your resume remains saved.
Continue interview	Closes the end-choice dialog and restores the current session's automatic answering.

Clear interview content resets the local page once the session is no longer connected. It does not delete history. Closing, refreshing or leaving the interview page interrupts the session; saved interrupted sessions cannot currently be resumed.

8 Review your interview and report

After saving, select View saved interview reviews or Interview review. Find the session by role and date, then select View review. Saved incomplete or failed sessions can also appear. If the session is not visible, select Refresh and confirm that you are signed in to the same account.




Figure 8. Actual saved report: provisional score and an unscored-answer warning.

1. Open the session. Select View review for the intended role and date. Use Refresh, Previous and Next to navigate the saved list. The detail view shows the saved questions and answers.

2. Read the dialogue. Compare each question with your recorded answer and any available feedback. Missing evaluation is shown separately; an introductory self-introduction does not contribute to the competency score.

3. Inspect the report. Check Overall score / 5 together with Evidence coverage and Unscored answers. Read each competency and expand Inspect evidence where available. A

provisional result needs more supporting evidence; do not read the number as a final hiring judgment.

4. Keep a copy. Select Download readable report (HTML) in the report. Open the downloaded file in a browser and confirm that it contains this session's results. If evaluation is pending, wait for the status to change or reopen the review before downloading a final copy.

Score label	How to interpret it
Published	A score is available under the system's evidence and evaluation rules.
Provisional	Use the completed assessments for practice; evidence or evaluation limitations remain.
Unavailable	A valid score is not available. Read the recorded answers and the stated limitations.

Read scores with their evidence and limitations. Missing evidence is not a zero score. Feedback guides practice; it is not a hiring probability or a comparison with other candidates.

9 Explore job matches

Select **Job matches** in the top navigation. Job matching uses the confirmed recommendation details of a saved resume and is separate from your interview scores.




Figure 9. Actual recommendation output for the fictional example resume.

Read the source label, recommendation order, Why this job and Shared skills together. This example uses research jobs and has limited matching information; a high position in the list does not by itself establish a strong match.

1. Choose a resume. Use Resume for recommendations to select the exact saved version you want to use.

2. Check recommendation details. Select Review skills & recommendation details. Confirm skills, experience, education and availability where known. Leave unknown information unspecified.

3. Save changes. Select **Save new edition**, then confirm that the recommendation picker points to the intended saved version. Unsaved edits are not the recommendation input.

4. Select Recommend jobs. Wait for the source label and result cards to appear. If an error is shown, follow section 10; do not assume that a result list was generated.

5. Read the results. Compare the recommendation order with Why this job, Required skills, Shared skills and Available features. Expand View job description to inspect a role. If few fields are known, review the saved recommendation details before interpreting the ranking.

Recommendations depend on the job catalogue and model services configured by the operator. Results marked Research data, not current vacancies are experimental examples. A match does not confirm an open vacancy, employer interest or an offer.

Confirmed recommendation fields and shortlisted job information are sent to the configured model service for ranking and explanations. Interview report scores are not required to request job matches.

10 Resolve common problems

What you see	What to do
Sign-in is rejected	Check the username and password. For a duplicate username during sign-up, choose another name. Registration signs you in automatically. If you cannot recover an existing account, ask the project team; this interface has no password-reset form.
Upload is rejected	Use a nonempty PDF no larger than 10 MiB. For Paste text, enter nonempty content within 200,000 characters.
PDF extraction fails or stops	Select Refresh to inspect the saved status. Re-upload failed or interrupted versions; do not treat an uploaded original as extracted text.
Confirm and start interview is disabled	Select a saved version. If its text is not ready, finish extraction in My resumes. For Needs preparation, select Prepare selected resume / retry, wait and Refresh. Start only after Ready for interview appears. If preparation fails again, keep the saved version and report the error to the project team.
No question audio	Check device volume and browser sound settings; use Replay question. If playback is unavailable but recording still works, read Current question and follow the countdown.
No digital-human video	Open Devices & playback and try Connect / play interviewer. If the renderer is unavailable, use the displayed question and available speech controls; contact the operator if needed.
Microphone or transcription fails	Check the browser's site microphone permission, the selected input device and HTTPS access. If a permission prompt is waiting, answer it first. After a capture error, the current question does not automatically restart recording. Try End interview > Evaluate and save to history, then start a new session after fixing the cause; do not assume draft subtitles were saved.

Connection is lost or the page was closed	Restore the connection and open Interview review. Select Refresh and inspect the saved session before starting again. An interrupted conversation cannot be resumed. Avoid refreshing an active session as a routine fix.
Report has no score or is still processing	If evaluation is Pending or Running, wait for the status to update, then reopen View review if needed. If it remains unchanged or shows an error, record that message for the project team. An Unavailable score or incomplete report is not a zero score.
Job matches are unavailable	Review the recommendation fields, select Save new edition, then choose that saved version and retry once. If the error names a missing catalogue or unavailable model service, ask the project team to restore it before retrying.

Keep track of your saved data

Saving an edition preserves the original and earlier versions. Ending without saving removes only the current interview when confirmed. Clearing the page and signing out do not delete stored records. Avoid leaving an active interview until you have chosen how to end it.

If you need help from the project team, provide the page name, the action you tried and the exact error message. Do not include passwords or unnecessary resume details.

Appendix D Note on the Use of AI Tools

Large language models are components of the system itself, as described throughout this report. In addition, team members used AI coding assistants during development and for drafting parts of the documentation. All design decisions, rubric content, experiment design and interpretation of results are the team's own, and every number in this report comes from a recorded test run in the repository.

Appendix E Project Contributions

The team divided work by system boundary. Individual reflections and peer evaluations are submitted separately on Canvas.

Table E.1 Work allocation

Member	Student ID	Main module	Key work
Sun Zhiquan	A0354826W	Recommendation, Resume Processing, Answer Completion, AI Safety and Application Platform	Structured job ranking and contextual reranking with explanations; semantic-vector, dedicated-reranker and low-rank missing-field adaptation studies; AI safety review and state-bound publication; two-stage answer-completion detection, training data, threshold selection and evaluation; PDF extraction and bounded visual proofreading; frontend/backend state management; most MCP/tool integration and authenticated submission; functional/performance testing; deployment and durable result delivery.
Du Ying Zeng Andrew	A0264354A	RAG and knowledge engine	Technical corpus (246 sources, 95,053 chunks), hybrid retrieval and confidence signals, INT8 ONNX query encoder, retrieval evaluation and latency studies, server deployment of RAG
Wang Shunyao	A0355565U	Interview agent and orchestration	Designed and implemented a time-budgeted Plan-and-Execute workflow with bounded ReAct questioning for adaptive interviews. Developed background replanning and prepared-question reuse to reduce latency, alongside follow-up limits and repetition controls to improve question quality. Conducted real-provider testing to validate question generation, topic transitions, and overall system reliability.
Luo Ziyu	A0351358B	Evaluation and scoring	Six-competency rubric and evidence-first evaluation pipeline; source validation, episode resolution, rubric judgement and deterministic aggregation; bounded recovery and incremental scoring to reduce repeated calls; provisional publication and report explanations; scoring-quality experiments and replay validation; final-report charts, structured question analysis and export integration with the platform team.
Guo Lexin	A0356193X	Digital Human Interviewer, Expression Agent and Speech Interaction	MetaHuman scene assembly and UE5 C++ runtime; TTS/STT integration; audio-driven lip synchronisation with background curve preparation, solver reuse and shared playback timing; an independent LLM expression Agent with validated four-state profiles; facial blending, interruption handling and recorded fallback; Pixel Streaming integration connecting local GPU rendering to the deployed website; packaging and digital-human module diagnostics.

Team members: Du Ying Zeng Andrew (A0264354A), Luo Ziyu (A0351358B), Wang Shunyao (A0355565U), Sun Zhiquan (A0354826W), Guo Lexin (A0356193X).

E.1 Acknowledgements

We thank the NUS-ISS lecturers of the Intelligent Reasoning Systems courses for their feedback after the first presentation, and the maintainers of the open documentation projects whose material forms our technical corpus.

Appendix F References

[1] M. A. Campion, D. K. Palmer and J. E. Campion, "A review of structure in the selection interview," Personnel Psychology, vol. 50, no. 3, pp. 655-702, 1997.

[2] J. Levashina, C. J. Hartwell, F. P. Morgeson and M. A. Campion, "The structured employment interview: Narrative and quantitative review of the research literature," Personnel Psychology, vol. 67, no. 1, pp. 241-293, 2014.

[3] H. J. Kell et al., "Exploring methods for developing behaviorally anchored rating scales for evaluating structured interview performance," ETS Research Report Series, vol. 2017, no. 1, pp. 1-26, 2017.

[4] P. Lewis et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in Advances in Neural Information Processing Systems, vol. 33, 2020, pp. 9459-9474.

[5] S. Yao et al., "ReAct: Synergizing reasoning and acting in language models," in Proc. ICLR, 2023.

[6] P. Wang et al., "Large language models are not fair evaluators," in Proc. 62nd Annual Meeting of the ACL, 2024, pp. 9440-9450.

[7] L. Shi et al., "Judging the judges: A systematic study of position bias in LLM-as-a-Judge," in Proc. IJCNLP-AACL, 2025, pp. 292-314.

[8] D. Li et al., "From generation to judgment: Opportunities and challenges of LLM-as-a-Judge," in Proc. EMNLP, 2025, pp. 2757-2791.

[9] D. Çelik Ertuğrul and S. Bitirim, "Job recommender systems: A systematic literature review, applications, open issues, and challenges," Journal of Big Data, vol. 12, art. 140, 2025.

[10] C. Li et al., "Competence-level prediction and resume & job description matching using context-aware transformer models," in Proc. EMNLP, 2020, pp. 8456-8466.

[11] K. Cofino et al., "A modular, multimodal open-source virtual interviewer dialog agent," in Proc. ICMI, 2017, pp. 520-521.

[12] D. Adiani et al., "Career interview readiness in virtual reality (CIRVR)," ACM Transactions on Accessible Computing, vol. 15, no. 1, 2022.

[13] J. Chen et al., "BGE M3-Embedding: Multi-lingual, multi-functionality, multi-granularity text embeddings through self-knowledge distillation," arXiv:2402.03216, 2024.

[14] G. Ke et al., "LightGBM: A highly efficient gradient boosting decision tree," in Advances in Neural Information Processing Systems, vol. 30, 2017.

[15] OWASP GenAI Security Project, "LLM01:2025 Prompt Injection," 2025.

[16] LangChain, "Plan-and-Execute Agents," May 10, 2023. [Online]. Available: https://www.langchain.com/blog/plan-and-execute-agents.