



Developing a parsing algorithm for OpenCMISS to setup a generic simulation based on input file

Waleed Mirza




Road Map Of Presentation

- ☐ State of the art.
- ☐ Motivation / Advantages.
- ☐ Syntax and functionalities of the input file.
- ☐ Different aspects of parsing algorithm.
- ☐ Case studies
- ☐ Future Work



State of the art

- ❑ Different binary for every case study.
- ❑ For each set of simulation parameters, one has to recompile the source code.





Motivation/Advantages

The developed algorithm will allow user to,

- Set up a generic simulation in OpenCMISS by providing instructions in an input file (*just like .inp file in Abaqus or .ans file in Ansys*).
- To change the simulation parameters (for instance in parametric analysis) without recompiling the code.
- Given a binary file (for instance ***GenericCaseStudy.out***) and the input file (*for instance ***input.iron****) , a simulation can be executed by,

\$ <Absolute path to the binary file >/ *GenericCaseStudy*
<Absolute path to the input file file >/ *input.iron*




Project overview

1- Develop layout/structure for the input file.

2- Develop a *GenericFortranExample.f90* file capable of setting up a generic simulation.

3- Develop a parsing algorithm that can pick input instructions from the input file and feeds them in the *GenericFortranExample.f90* file






1- Preliminary Concepts

- ❑ Structure of OPENCMISS involves objects of different derived types. Each derived type object contains different simulation parameters. For instance:
 - Objects of ***CMFE_GeneratedMesh*** Type contain information of mesh parameters such as mesh size , topology etc.
 - Objects of ***CMFE_BoundaryConditions*** Type contains information of the boundary conditions such as location of BCs, prescribed values etc.
- ❑ With instructions provided in the input file, these derived types objects are created and appropriate information is stored in them.



1- Preliminary Concepts (continued)





2- Syntax of the input file

❑ The input file is divided in 18 blocks and each block generates a derived type object and contains information which is later stored in different members of the object.

- BASIS block
- GENERATED_MESH Block
- BOUNDARY_CONDITION Block
- CONTROL_LOOP block
- MATERIAL_FIELD block
- DEPENDENT_FIELD block etc.

Note that each block corresponds to block of routines in FortranExample.f90 file



2 - Syntax of Input file (Continued)

- ❑ Each block starts and ends with the keywords *START_<BLOCK NAME >* and *END_<BLOCK NAME>* respectively.
- ❑ Each block encapsulate set of input arguments.

START_BASIS

BASIS_ID

FLUID

NumberOfGaussXi ! For numerical integration

3 , 3

BASIS_INTERPOLATION_TYPE

LINEAR_LAGRANGE_INTERPOLATION

END_BASIS



2 - Syntax of Input file (Continued)

- ☐ The syntax of input is case insensitive.
- ☐ Comments should be started with exclamation mark !
- ☐ *Blank line can be introduced by the user in the input file for readability.*
- ☐ *The input file should be finished with the keyword
STOP_PARSING*
- ☐ **Please be careful with the spellings . As of now there is no way to deal with typos.**



2 - Syntax of Input file (Continued)

Example of an input file

Governing equation to be solved for domain with volume $1m \times 1m \times 1m$.

□ Case *a* $\nabla^2 \varphi = 0$



$\varphi(x, y, 1) = 1$

□ Case *b*


$\varphi(0, y, z) = 1 \quad \varphi(1, y, z) = 0$

□ Case *c*


$\varphi(x, y, 1) = 1 \quad \varphi(x, y, 0) = 0$



(a)



(b)



(c)



3-Parsing Algorithm


3.1- Nomenclature of data structures

- ❑ The nomenclature of the data structures have been established with an aim to make them **self descriptive** and **clear in terms of readability**.
- ❑ For instance in
all_GeneratedMesh(:)%GeneratedMeshInterpolationType
 - *all_GeneratedMesh(:)* is an array of objects of generated mesh.
 - Size of the array = number of times the GENERATED_MESH block defined in the input file.
 - For example for an FSI study there will be three GENERATED_MESH blocks i.e. for SOLID , FLUID and INTERFACE.”



3.1- Nomenclature Of Data Structures (Conti.)

- ❑ *GeneratedMeshInterpolationType* is a string type member of object *all_GeneratedMesh(:)*.
- ❑ For instance, in an FSI study each domain (Solid, Fluid and Interface) can have a different Interpolation type
- *all_GeneratedMesh(1)%GeneratedMeshInterpolationType = "QUADRATIC_LAGRANGE_INTERPOLATION"*
- *all_GeneratedMesh(2)%GeneratedMeshInterpolationType = "QUADRATIC_LAGRANGE_INTERPOLATION"*
- *all_GeneratedMesh(3)%GeneratedMeshInterpolationType = "LINEAR_LAGRANGE_INTERPOLATION"*



3.1- Nomenclature Of Data Structures (Conti.)

❑ **Question:** In a multidomain problem how will the algorithm recognize which interpolation type belongs to which domain ?

❑ **Answer:** Block Ids will help algorithm with that.

➤ *all_GeneratedMesh(1)%GeneratedMeshId = "SOLID"*

➤ *all_GeneratedMesh(2)%GeneratedMeshId = "FLUID"*


➤ *all_GeneratedMesh(3)%GeneratedMeshId = "INTERFACE"*

❑ Section 4 will explain this feature of the algorithm more in detail.



3.1- Nomenclature Of Data Structures (Conti.)

In a Nutshell





4- GenericFortranExampleFile.f90

- This is the file where simulation is setup using the parameters define in the input file.
- As of now, the *GenericFortranExampleFile.f90* is evolved enough to setup laplace , fluid and solid mechanics problems.
- Nevertheless, *GenericFortranExampleFile.f90* is quite amenable and modifiable for simulations of other classes.




4- GenericFortranExampleFile.f90 (Continued)

- Objects of different data type are linked here. For instance
- Objects of *all_Region(:)%Region* and *all_CoordinateSystem(:)%CoordinateSystem* with similar data types are linked together i.e.
- CALL cmfe_Region_CoordinateSystemSet(*all_Region(RegionIdx)%Region*, & *all_CoordinateSystem(CsysIdx)%CoordinateSystem*, Err)
- The Algorithm has to make sure in the subroutine above , *CoordinateSystemIdx* and *RegionIdx* are such that
all_CoordinateSystem(CsysIdx)%CoordinateSystemId = "SOLID"
all_Region(RegionIdx)%RegionId = "SOLID"



4- GenericFortranExampleFile.f90

- That's where the *MATCH_ID*() subroutine kicks in
- call subroutine *MATCH_ID*(all_Region(RegionIdx)%RegionId, &
- & all_CoordinateSystem(:)%CoordinateSystemId,
- & CoordinateSystemIdx)





4- Case Studies

4.1 Laplace Problem

Governing equation to be solved for domain with volume $1m \times 1m \times 1m$.

$$\nabla^2 \varphi = 0$$

□ Case *a*



$$\varphi(x, y, 1) = 1$$

□ Case *b*

$$\varphi(0, y, z) = 1 \quad \varphi(1, y, z) = 0$$

□ Case *c*

$$\varphi(x, y, 1) = 1 \quad \varphi(x, y, 0) = 0$$







4.1- Laplace Problem (continued)

Case (a): $\varphi(x, y, 1) = 1$


Case (b): $\varphi(0, y, z) = 1$ $\varphi(1, y, z) = 0$






4.1- Laplace Problem (continued)

Case (c): $\varphi(x, y, 1) = 1$ $\varphi(x, y, 0) = 0$





4.2 Case Study # 2


2D Fluid Flow Problem

Governing equation to be solved

$$\underbrace{\rho \left(\frac{\partial \vec{u}}{\partial t} + \vec{u} \cdot \nabla \vec{u} \right)}_{\text{Acceleration}} = \underbrace{-\nabla p}_{\text{Pressure}} + \underbrace{\nu \Delta \vec{u}}_{\text{Viscosity}}$$

Case(a) : $V_x(0, y) = 4$

Case(b) : $V_x(0, y) = 4V_{max} \frac{y}{h} \left(\frac{y}{h} - 1 \right)$




$P(x = L) = 0$




2d Fluid Flow Problem (Conti.)

Case(a) : $V_x(0, y) = 4$



Case(b) : $V_x(0, y) = 4V_{max} \frac{y}{h} (\frac{y}{h} - 1)$





4.3 - Case study # 3

Cube subjected to uniaxial displacement

Governing equation to be solved

$$0 = \frac{1}{\rho} \Delta \cdot \sigma + g$$

Boundary conditions


$$u(0, y, z) = 0$$

$$u(1, y, z) = 1$$

$$u(x, y, 0) = 0$$


Material model

Transverse Isotropic Material model





4.3 Cube subjected to uniaxial displacement (Continued)





5- Conclusion and Future Research

- The developed parsing algorithm can ideally solve Fluid Mechanics , Solid Mechanics and Laplace problems.
- Over the course of following months, the algorithm will be further developed and tested to solve a **fluid solid interaction study**.
- **Please talk to me if you want me to add any feature in my algorithm of your interest.**

