
1 Recursions

1.1 Definitions

 S^1, S^2 target and query sequences i_1, j_1, i_2, j_2 interaction boundaries si_1, sj_1, si_2, sj_2 seed boundaries N the maximum interaction length (~ 150) M the enclosed unpaired positions in one loop (~ 15) General energy computation:



$$E(^{i_1,j_1}_{i_2,j_2}) = E_h^{seed}(^{i_1,j_1}_{i_2,j_2}) + ED_1(^{i_1}_{j_1}) + ED_2(^{i_2}_{j_2})$$

Optimization task:


$$\min_{\substack{seed \\ j_2-i_2 \leq N}} \min_{\substack{j_1-i_1 \leq N \\ j_2-i_2 \leq N}} \left(E_h^{seed}(^{i_1,j_1}_{i_2,j_2}) \right)$$

1.2 Initialization


$$E_h^{seed}(^{si_1,sj_1}_{si_2,sj_2}) = E_{seed}$$

With E_{seed} including E_{init} .

1.3 Recursion 1 $(O(N^4) \text{ space} + \text{time})$



1.4 Recursion 2 $(O(N^2) \text{ space} + O(N^4) \text{ time})$



$$E_h^{seed}(_{i_2,j_2}^{i_1,j_1}) = \begin{cases} \infty \\ : \text{ if } j_1 - i_1 > N \text{ oder } j_2 - i_2 > N \\ \left(E_L(_{i_2}^{i_1}) + E_{seed} + E_R(_{j_2}^{j_1}) \right) \\ : \text{ otherwise.} \end{cases}$$

$$\forall \sum_{\substack{si_1 - N \leq i_1 \leq si_1 \\ si_2 - N \leq i_2 \leq si_2}} E_L(_{i_2}^{i_1}) = \begin{cases} \infty \\ \text{: if no matching base pair} \\ \min_{\substack{l_1 - i_1 - 1 \leq M \\ l_2 - i_2 - 1 \leq M}} \left(E_{loop}(_{i_2, l_2}^{i_1, l_1}) + E_L(_{l_2}^{l_1}) \right) \\ \text{: otherwise.} \end{cases}$$

$$\forall E_{R}(_{j_{2}}^{j_{1}}) = \begin{cases} \infty \\ : \text{ if no matching base pair} \\ \min_{\substack{j_{1}-r_{1}-1 \leq M \\ j_{2}-r_{2}-1 \leq M}} \left(E_{R}(_{r_{2}}^{r_{1}}) + E_{loop}(_{r_{2},j_{2}}^{r_{1},j_{1}}) \right) \\ : \text{ otherwise.} \end{cases}$$