

C++ Iterators and `std::vector`

- ◆ What is an Iterator?
- ◆ Iterators and `std::vector`
 - Basic Syntax:
- ◆ Common Iterator Operations
- ◆ Example: Iterating Over a Vector
- ◆ Const Iterators
- ◆ Reverse Iterators
- ◆ Why Use Iterators?
- ✅ Summary
- 🎯 Quiz!

◆ What is an Iterator?

An **iterator** in C++ is an object that acts like a pointer and allows you to **traverse** (i.e. move through) containers (like `std::vector`, `std::map`, etc.). Think of it as a **generalized pointer** that provides access to elements in a container without exposing the underlying structure.

◆ Iterators and `std::vector`

`std::vector` is a **sequence container** that stores elements in a **contiguous memory block**. It supports **random access iterators**, which means you can move forward, backward, and jump to any position in constant time.

Basic Syntax:

```
std::vector<int>::iterator it;
```

◆ Common Iterator Operations

Operation	Description
<code>begin()</code>	Returns iterator to the first element
<code>end()</code>	Returns iterator to one past the last element
<code>*it</code>	Dereferences iterator to access value
<code>it++</code> / <code>++it</code>	Moves to the next element
<code>it--</code> / <code>--it</code>	Moves to the previous element
<code>it + n</code>	Moves forward by <code>n</code> positions
<code>it - n</code>	Moves backward by <code>n</code> positions

◆ Example: Iterating Over a Vector

```
#include <iostream>
#include <vector>

int main() {
    std::vector<int> nums = {10, 20, 30, 40, 50};

    // Using iterator
    for (std::vector<int>::iterator it = nums.begin(); it != nums.end(); ++it) {
        std::cout << *it << " ";
    }
    // Output: 10 20 30 40 50
}
```

◆ Const Iterators

Use `const_iterator` when you want to **read** but not **modify** the elements.

```
std::vector<int>::const_iterator it;
```

◆ Reverse Iterators

```
for (std::vector<int>::reverse_iterator rit = nums.rbegin(); rit != nums.rend(); ++rit) {
    std::cout << *rit << " ";
}
// Output: 50 40 30 20 10
```

◆ Why Use Iterators?


- **Abstraction:** You don't need to know how the container is implemented.
- **Generic Programming:** Algorithms like `std::sort`, `std::find`, etc., work with iterators.
- **Safety:** Iterators provide bounds-checked access when used with STL algorithms.

✅ Summary

- Iterators are like smart pointers for containers.
- `std::vector` supports **random access iterators**.
- Use `begin()` and `end()` to traverse a vector.
- Prefer `const_iterator` for read-only access.
- STL algorithms rely heavily on iterators.

🎯 Quiz!

Here's a short quiz on the topic: [quiz](#)

Footer Separator

Markdown Viewer

How to view the markdown files in a browser...

- [Markdown Viewer](#)

Lecture Practices

Here are the lecture Practices...

- [Day 1](#)
- [Day 2](#)
- [Day 3](#)

Lecture Quizzes

Here are the lecture quizzes...

- [Day 1](#)
- [Day 2](#)
- [Day 3](#)

Weekly Topics

Here are the topics for the week...

- [Calling Methods](#)
- [Calling Methods 2](#)
- [Creating Methods](#)
- [Iterators](#)
- [Vectors](#)
- [References](#)
- [Const](#)
- [Erasing in a Loop](#)
- [Default Parameters](#)