

# Static vs. Non-Static Member Functions in C++

- ◆ Non-Static Member Functions
  - Definition:
  - Characteristics:
  - Example:
- ◆ Static Member Functions
  - Definition:
  - Characteristics:
  - Example:
- ◆ Key Differences
- ✔ When to Use What?
- 🎮 Quiz!

In C++, member functions of a class can be either **static** or **non-static**. Understanding the difference between them is crucial for designing efficient and logical object-oriented programs.

## ◆ Non-Static Member Functions

### Definition:

Non-static member functions are associated with an **instance** of a class. They can access both **instance variables** and **static variables** of the class.

### Characteristics:

- ❗ Require an object to be called. ❗
- Have access to the `this` pointer (i.e., the current object).
- Can access and modify instance (non-static) data members.

### Example:

```
#include <iostream>
using namespace std;

class Student {
private:
    string name;
    int age;

public:
    void setDetails(string n, int a) {
        name = n; //non-static methods can access and modify the data members of the class
        age = a;
    }

    void display() {
        cout << "Name: " << name << ", Age: " << age << endl;
    }
};

int main() {
    //
    // Step 1. Create an object of the Student class
    Student s1;

    //
    // Step 2. Use the Student variable to call the non-static methods
    s1.setDetails("Alice", 20);
    s1.display(); // Output: Name: Alice, Age: 20

    return 0;
}
```

## ◆ Static Member Functions

### Definition:

Static member functions are associated with the **class itself**, not with any particular object. They can only access **static data members** or other **static member functions**.

### Characteristics:

- Can be called using the class name (no object needed).
- Do not have access to the `this` pointer.
- Cannot access non-static members directly.

### Example:

```
#include <iostream>
using namespace std;

class Counter {
private:
    static int count;

public:
    static void increment() {
        count++;
    }

    static void showCount() {
        cout << "Count: " << count << endl;
    }
};

// Definition of static member
int Counter::count = 0;

int main() {
    //
    // Use ClassName:: to call static methods
    Counter::increment();
    Counter::increment();
    Counter::showCount();

    return 0;
}
```

## ◆ Key Differences

Feature	Non-Static Function	Static Function
Called using	Object	Class name or object
Access to <code>this</code> pointer	Yes	No
Access to instance data	Yes	No
Access to static data	Yes	Yes
Memory allocation	Per object	Shared across all instances

## ✔ When to Use What?

- Use **non-static** functions when behavior depends on object-specific data.
- Use **static** functions for utility operations or when behavior is independent of object state.

## 🎮 Quiz!

Here's a short quiz on the topic: [quiz](#)

🖼️ Footer Separator

## 🖋️ Markdown Viewer

How to view the markdown files in a browser...

- [Markdown Viewer](#)

## 🧠 Lecture Practices

Here are the lecture Practices...

- [Day 1](#)
- [Day 2](#)
- [Day 3](#)

## 🔍 Lecture Quizzes

Here are the lecture quizzes...

- [Day 1](#)
- [Day 2](#)
- [Day 3](#)

## ⚙️ Weekly Topics

Here are the topics for the week...

- [Calling Methods](#)
- [Calling Methods 2](#)
- [Creating Methods](#)
- [Iterators](#)
- [Vectors](#)
- [References](#)
- [Const](#)
- [Erasing in a Loop](#)
- [Default Parameters](#)