

SQL JOINS

SQL

You will be able to...

- ◉ Explain Primary and Foreign keys
- ◉ Use SELECT, FROM, WHERE and JOIN
- ◉ Explain the differences between INNER, OUTER, LEFT and RIGHT joins
- ◉ Alias tables
- ◉ Use ORDER BY and COUNT

Example DB

Students

ID	Name	Age	Gender	Address
1	Nick D.	20	M	2
2	Andy D.	28	M	2
3	Beth M.	23	F	1
4	Lisa N.	20	F	4

Addresses

ID	Street	Zip	City	State
1	423 Main St.	60647	Chicago	IL
2	13 Main St	60655	Barrington	IL
3	15 Main St	60651	Elsewhere	IL
4	14 Main St	60650	Chicago	IL

All 20 Year Old Students

Students

ID	Name	Age	Gender	Address
1	Nick D.	20	M	2
2	Andy D.	28	M	2
3	Beth M.	23	F	1
4	Lisa N.	20	F	4

20 Year Old Students

ID	Name	Age
1	Nick D.	20
4	Lisa N.	20

```
SELECT ID, Name, Age
FROM Students
WHERE Age = 20;
```

Students

ID	Name	Age	Gender	Address
1	Nick D.	20	M	2
2	Andy D.	28	M	2
3	Beth M.	23	F	1
4	Lisa N.	20	F	4

Addresses

ID	Street	Zip	City	State
1	423 Main St.	60647	Chicago	IL
2	13 Main St.	60655	Barrington	IL
3	15 Main St.	60651	Elsewhere	IL
4	14 Main St.	60650	Chicago	IL

```
SELECT Students.ID, Name, Street, Zip, City
FROM Students
JOIN Addresses
ON Students.Address = Addresses.ID;
```

Students with Addresses

Student.ID	Name	Street	Zip	City
1	Nick D.	13 Main St.	60655	Barrington
2	Andy D.	13 Main St.	60655	Barrington
3	Beth M.	423 Main St.	60647	Chicago
4	Lisa N.	14 Main St.	60650	Chicago

Students

ID	Name	Age	Gender	Address
1	Nick D.	20	M	2
2	Andy D.	28	M	2
3	Beth M.	23	F	1
4	Lisa N.	20	F	4

Addresses

ID	Street	Zip	City	State
1	423 Main St.	60647	Chicago	IL
2	13 Main St.	60655	Barrington	IL
3	15 Main St.	60651	Elsewhere	IL
4	14 Main St.	60650	Chicago	IL

```
SELECT Students.ID, Name, Street, Zip, City
FROM Students
JOIN Addresses
ON Students.Address = Addresses.ID
WHERE Addresses.City = 'Chicago';
```

Students with Addresses

Student.ID	Name	Street	Zip	City
3	Beth M.	423 Main St.	60647	Chicago
4	Lisa N.	14 Main St.	60650	Chicago



Some Common SQL Keywords

Keyword	Action
SELECT	Which COLUMNS to include in output table (shrinks the result horizontally!)
FROM	Which TABLE to pull data from
JOIN	Another TABLE to glue / concatenate to the output
ON	What COLUMNS must match when joining two tables
WHERE	Which ROWS to include in the output table (shrinks the result vertically!)

CRUD Operations


SQL is used to create/read/update/delete (CRUD) data from a database

- ◉ INSERT: Insert new rows into a table
- ◉ SELECT: Get data from a database
- ◉ UPDATE: Update existing rows in a table
- ◉ DELETE: Delete rows from a table

- ◉ CREATE / DROP: Make / delete new dbs/tables/views/indexes




Inner Join




```
SELECT *  
FROM A  
INNER JOIN B  
ON A.Key = B.Key
```

Outer Join




```
SELECT *  
FROM A  
FULL OUTER JOIN B  
ON A.Key = B.Key
```

Left Join



```
SELECT *  
FROM A  
LEFT JOIN B  
ON A.Key = B.Key
```

Right Join




```
SELECT *  
FROM A  
RIGHT JOIN B  
ON A.Key = B.Key
```

<http://www.codeproject.com/Articles/33052/Visual-Representation-of-SQL-Joins>



Inner Join



```
SELECT pets.name, owners.name  
FROM owners  
INNER JOIN pets  
ON pets.ownerID = owners.ID
```

OWNERS

ID	name
1	Geordi
2	Janeway
3	Data
4	Spock


PETS

ID	ownerID	type	name
1	4	Monkey	Mittens
2	null	Lizard	Carol
3	1	Dog	Rufus
4	3	Cat	Spot

pets.name	owners.name
Mittens	Spock
Rufus	Geordi
Spot	Data



Left Join



```
SELECT pets.name, owners.name  
FROM owners  
LEFT JOIN pets  
ON pets.ownerID = owners.ID
```


OWNERS

ID	name
1	Geordi
2	Janeway
3	Data
4	Spock

PETS


ID	ownerID	type	name
1	4	Monkey	Mittens
2	null	Lizard	Carol
3	1	Dog	Rufus
4	3	Cat	Spot

pets.name	owners.name
Mittens	Spock
Rufus	Geordi
null	Janeway
Spot	Data





Right Join



```
SELECT pets.name, owners.name  
FROM owners  
RIGHT JOIN pets  
ON pets.ownerID = owners.ID
```


OWNERS

ID	name
1	Geordi
2	Janeway
3	Data
4	Spock

PETS


ID	ownerID	type	name
1	4	Monkey	Mittens
2	null	Lizard	Carol
3	1	Dog	Rufus
4	3	Cat	Spot

pets.name	owners.name
Mittens	Spock
Carol	null
Rufus	Geordi
Spot	Data





Outer Join



```
SELECT pets.name, owners.name  
FROM owners  
FULL OUTER JOIN pets  
ON pets.ownerID = owners.ID
```


OWNERS

ID	name
1	Geordi
2	Janeway
3	Data
4	Spock

PETS

ID	ownerID	type	name
1	4	Monkey	Mittens
2	null	Lizard	Carol
3	1	Dog	Rufus
4	3	Cat	Spot

pets.name	owners.name
Mittens	Spock
Carol	null
Rufus	Geordi
null	Janeway
Spot	Data





AS

Student			Enrollment		School		
ID	Name	Age	StudentID	SchoolID	ID	Name	Level
1	Bart S.	10	1	1	1	Springfield Elementary	E
2	Lisa S.	8	2	1	2	Brook Middle	M
3	Jim F.	13	3	2	3	Springbrook High	H
4	Joan B.	15	4	3	4	Springfield University	U

```
SELECT *
FROM Student AS st
INNER JOIN Enrollment AS e
ON st.ID = e.StudentID
INNER JOIN School AS sc
ON e.SchoolID = sc.ID;
```

Result							
st.ID	st.Name	Age	StudentID	SchoolID	sc.ID	sc.Name	Level
1	Bart S.	10	1	1	1	Springfield Elementary	E
2	Lisa S.	8	2	1	1	Springfield Elementary	E
3	Jim F.	13	3	2	2	Brook Middle	M
4	Joan B.	15	4	3	3	Springbrook High	H



GROUP BY + COUNT

Student		
ID	Name	Age
1	Bart S.	10
2	Lisa S.	8
3	Jim F.	13
4	Joan B.	15

Enrollment	
StudentID	SchoolID
1	1
2	1
3	2
4	3

School		
ID	Name	Level
1	Springfield Elementary	E
2	Brook Middle	M
3	Springbrook High	H
4	Springfield University	U

```
SELECT Name, COUNT(*)
FROM School
INNER JOIN Enrollment
ON School.ID = Enrollment.SchoolID
GROUP BY Name;
```

Result

Name	COUNT(*)
Springfield Elementary	2
Brook Middle	1
Springbrook High	1
Springfield University	0



ORDER BY

```
SELECT *  
FROM Student  
ORDER BY Age DESC;
```

Student		
ID	Name	Age
1	Bart S.	10
2	Lisa S.	8
3	Jim F.	13
4	Joan B.	15

Enrollment	
StudentID	SchoolID
1	1
2	1
3	2
4	3

School		
ID	Name	Level
1	Springfield Elementary	E
2	Brook Middle	M
3	Springbrook High	H
4	Springfield University	U

Result

ID	Name	Age
4	Joan B.	15
3	Jim F.	13
1	Bart S.	10
2	Lisa S.	8



SUB-QUERIES

Student	ID	Name	Age
	1	Bart S.	10
	2	Lisa S.	8
	3	Jim F.	13
	4	Joan B.	15

Enrollment	
StudentID	SchoolID
1	1
2	1
3	2
4	3

School		
ID	Name	Level
1	Springfield Elementary	E
2	Brook Middle	M
3	Springbrook High	H
4	Springfield University	U

```
SELECT ID, Name, Age
FROM Student
INNER JOIN Enrollment
  ON Student.ID = Enrollment.StudentID
INNER JOIN (
  SELECT SchoolID
  FROM Student
  WHERE Student.Name = 'Lisa S.'
  INNER JOIN Enrollment
    ON Student.ID = Enrollment.StudentID
) AS LisaSchools
  ON LisaSchools.SchoolID = Enrollment.SchoolID
WHERE Name != 'Lisa S.';
```

Result

ID	Name	Age
1	Bart S.	10

You will be able to...

- ◉ Explain Primary and Foreign keys
- ◉ Use SELECT, FROM, WHERE and JOIN
- ◉ Explain the differences between INNER, OUTER, LEFT and RIGHT joins
- ◉ Alias tables
- ◉ Use ORDER BY and COUNT

WORKSHOP