

Objects



Overview

```
1  /*
2    - what is an object?
3    - why are objects useful?
4    - typeof object
5    - accessing, adding, changing, deleting values
6    - in operator
7    - for..in loop
8    - Object.keys()
9    - nested arrays and objects
10 */
11
12
13
14
```



value1
value1

What is an object?

```
1  /* an object is a collection of key-value pairs */
2
3  /* like arrays, objects store values, but instead of storing them in
4     numeric "indices", objects store values in string "keys" */
5
6  let myArray = ['value1', 'value2'];
7
8  let myObject = {
9      'aardvark': 'an aardvark lives in such',
10     'key2': 'value2'
11 };
12
13 console.log(myArray[0]);
14 console.log(myObject['aardvark']); // 'an aardvark lives in such',
```



Why are objects useful?

```
1  /* consider representing Pusheen the Cat as an array */
2  let pusheen = ['Pusheen', 7, 'gray and tabby'];
3
4  /* an array is a good place to hold an ordered list of values, but it
5     doesn't store any information about what those values represent */
6
7  /* an object's string keys allows objects to store more information about
8     the values within it */
9
10 let pusheen = {
11   'name': 'Pusheen',
12   'age': 7,
13   'color': 'gray and tabby'
14 };
```



object

typeof object

```
1 console.log(typeof {}); ==> 'object'
```

2

3

4

5

6

7

8

9

10

11

12

13

14



Creating an object

```
1  /* create a new object using curly braces */
2
3  /* an object's keys are always strings; you can omit the quotation
4     marks */
5
6  let pusheen = {
7     name: 'Pusheen',
8     age: 7,
9     color: 'gray and tabby'
10 };
11
12
13
14
```



Pusheen
7
gray and tabby
undefined

Accessing a value

```
/* use bracket notation to access a value */
```

```
/* pass a string into the brackets that corresponds with a key in the  
object */
```

```
let pusheen = {  
  name: 'Pusheen',  
  age: 7,  
  color: 'gray and tabby'  
};
```

```
console.log(pusheen['name']);  
console.log(pusheen['age']);  
console.log(pusheen['color']);  
console.log(pusheen['notAKeyInTheObject']);
```



Accessing a value

```
1  /* any variable or expression that evaluates to a string can be passed
2     into the brackets */
3
4  let pusheen = {
5     name: 'Pusheen',
6     age: 7,
7     color: 'gray and tabby'
8  };
9
10 let keyToCheck = 'name';
11
12 console.log(pusheen[keyToCheck]);
13 console.log(pusheen['col' + 'or']);
14
```




Pusheen
7
gray and tabby
undefined

Accessing a value

```
1  /* you can also use dot notation to access values */
2
3  let pusheen = {
4      name: 'Pusheen',
5      age: 7,
6      color: 'gray and tabby'
7  };
8
9  let keyToCheck = 'name';
10
11 console.log(pusheen.name); // no quotes needed with dot notation
12 console.log(pusheen.age);
13 console.log(pusheen.color);
14 console.log(pusheen.keyToCheck);
```



Adding a key/value pair

```
1  /* use bracket notation or dot notation to add a
2     key/value pair */
3
4  let pusheen = {
5     name: 'Pusheen',
6     age: 7,
7     color: 'gray and tabby'
8  };
9
10 pusheen['sister'] = 'Stormy';
11 pusheen.brother = 'Pip';
12
13 console.log(pusheen);
14
```

```
{
  name: Pusheen,
  age: 7,
  color: gray and tabby,
  sister: Stormy,
  brother: Pip
}
```



Changing a value

```
1  /* use bracket notation or dot notation to change a value */
2
3  let pusheen = {
4    name: 'Pusheen',
5    age: 7,
6    color: 'gray and tabby'
7  };
8
9  pusheen['age'] = 8;
10 pusheen.age = pusheen.age + 1
11
12 console.log(pusheen.age);
13
14
```



```
{ name: Pusheen }
```

Deleting a key/value pair

/ use the delete keyword to delete a key/value pair */*

```
1 let pusheen = {  
2   'Cat is cool': 'Pusheen',  
3   ageOfTheCat: 7,  
4   color: 'gray and tabby'  
5 };  
6  
7 delete pusheen['Cat is Cool'];  
8 delete pusheen.cat is ;  
9  
10 console.log(pusheen);  
11  
12  
13  
14
```



true
false

in operator

```
1  /* use the in operator to check if a key is in the object */
2
3  let pusheen = {
4    name: 'Pusheen',
5    age: 7,
6    color: 'gray and tabby'
7  };
8
9  console.log('name' in pusheen);
10 console.log('sadness' in pusheen);
11
12
13
14
```



name
age
color

for...in loop

```
1  /* use the for...in loop to loop through all of the keys in an object */
2
3  let pusheen = {
4      name: 'Pusheen',
5      age: 7,
6      color: 'gray and tabby'
7  };
8
9  for (let key in pusheen) {. //name
10     console.log(key, Pusheen[key])
11 }
12
13
14
```



Pusheen's name is Pusheen
Pusheen's age is 7
Pusheen's color is gray and tabby

for...in loop

```
1  /* use the for...in loop to loop through all of the keys in an object */
2
3  let pusheen = {
4    name: 'Pusheen',
5    age: 7,
6    color: 'gray and tabby'
7  };
8
9  for (let key in pusheen) {
10    console.log("Pusheen's", key, 'is', pusheen[key]);
11  }
12
13
14
```



Pusheen's name is undefined
Pusheen's age is undefined
Pusheen's color is undefined

for...in loop

```
1  /* use the for...in loop to loop through all of the keys in an object */
2
3  let pusheen = {
4      name: 'Pusheen',
5      age: 7,
6      color: 'gray and tabby'
7  };
8
9  for (let key in pusheen) {
10     console.log("Pusheen's", key, 'is', pusheen[key]);
11 }
12
13
14
```




[name, age, color]

Object.keys()

```
1  /* use Object.keys() to get an array of the keys in the object */
2
3  let pusheen = {
4    name: 'Pusheen',
5    age: 7,
6    color: 'gray and tabby'
7  };
8
9  Object.keys(pusheen)
10 Object.values(pusheen) ==> ['Pusheen', 7, 'gray and tabby']
11
12 console.log(Object.keys(pusheen));
13
14
```



nested arrays

```
1  /* objects can store any type of value, including arrays and other
2     objects */
3
4  let pusheen = {
5     name: 'Pusheen',
6     age: 7,
7     colors: ['gray', 'tabby']
8  };
9
10 Pusheen.colors.shift();
11
12
13 console.log(pusheen.colors[0]);
14 console.log(pusheen.colors[1]);
```



nested objects

```
1  /* objects can store any type of value, including arrays and other
2     objects */
3
4  let pusheen = {
5     name: 'Pusheen',
6     age: 7,
7     siblings: {
8         sister: 'Stormy',
9         brother: 'Pip'
10    }
11 };
12
13 console.log(pusheen['siblings'].sister);
14 console.log(pusheen.siblings.brother);
```



something was logged
something else was logged

```
1 Let obj = [{num:1}, {num:2}, {num:3}]
2 For (let I = 0; I < obj.length; I++){
3   obj[I].num
4 }
5
6
7
8
```



Recap

```
1  /*
2    - what is an object?
3    - why are objects useful?
4    - typeof object
5    - accessing, adding, changing, deleting values
6    - in operator
7    - for..in loop
8    - Object.keys()
9    - nested arrays and objects
10 */
11
12
13
14
```