

# Linux Beginner Guide

Jaewoong Lee

Ulsan National Institute of Science and Technology

*jwlee230@unist.ac.kr*

January 5, 2020

# Introduction

In this guide, I assume that followings are already installed:

- 1 Ubuntu 16.04.2 or Higher
- 2 ZSH 5.0.2 or Higher
- 3 VIM 8.1 or Higher
- 4 We will connect to server via SSH

With this guide, you can use and understand Linux system.

Also, this guide includes as little information about operating system as possible. If you find some fault in the strict sense of the word, that means you are not **beginner**.

# Overview

- 1 Linux?
- 2 Basic Linux Command
- 3 Edit File with VIM
- 4 IO Redirections
- 5 How to Download from Web

# Linux?



**Figure:** Linus Torvalds, Inventor of Linux

Linux is one of the most famous OS as Windows and macOS.  
Linux is open-source project.  
Android, OS for mobile, is based on Linux.

# Ubuntu?



Figure: Logo of Ubuntu

Ubuntu is an OS which is based on Linux.

Ubuntu is the best OS in Linux-like OS, because of convenience of its installation and usage.

# Where we start

```
$ ssh fumire@192.168.
fumire@192.168.0.69's password:
Welcome to Ubuntu 18.04.2 LTS (GNU/Linux 4.15.0-1032-rasp12 armv7l)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

0 packages can be updated.
0 updates are security updates.

Last login: Sun Jan  5 03:49:29 2020 from 192.168.
fumire@fumire-raspberry:~$
```

Figure: Here is where we start

After you connect to server via SSH, you can see like this.

Here is where we start!

*fumire* will be user name, and *fumire-raspberry* will be server name.

```
fumire@fumire-raspberry:~$ pwd  
/home/fumire
```

Figure: Result of *pwd* Command

*pwd* is abbr. of "Print Working Directory".

You can see where you are with *pwd* command.

Also, "/home/username" is your *home folder*, a.k.a. '~'.

```
fumire@fumire-raspberry:~$ ls  
Desktop  Documents  Downloads  Music  Pictures  Public  snap  Templates  Videos
```

Figure: Result of `ls` Command

`ls` stands for "List".

`ls` command lists current directory contents.

If current directory is empty, the result will be nothing.



However, you have not completed configuration. Therefore, finish settings with following command:

## Example

```
$ git clone https://github.com/Fumire/.dotfiles.git
$ cd .dotfiles
$ make
$ chsh -s /usr/bin/zsh
```

Note that you should input command only after '\$'.  
After executing commands, you should restart your shell.

# Configuration (Cont.)

```
$ ssh fumire@192.168.
fumire@192.168.0.69's password:
Welcome to Ubuntu 18.04.2 LTS (GNU/Linux 4.15.0-1032-raspi2 armv7l)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

409 packages can be updated.
238 updates are security updates.

Last login: Sun Jan  5 04:36:48 2020 from 192.168.
04:39:57 fumire@fumire-raspberry ~
```

Figure: ZSH

With successful configuration, you can see like this.

# Tip!

```
04:39:57 fumire@fumire-raspberry ~  
$ ls  
Desktop Documents Downloads Library Music Pictures Public snap Templates Videos  
04:39:59 fumire@fumire-raspberry ~  
$ Is  
zsh: command not found: Is
```

Figure: Right Command vs. Wrong Command

You can easily know this command is right with ZSH as figure.

*mkdir* stands for "Make Directory".

You can make a directory which named 'test' as following:

## Example

```
$ mkdir test
```

or

```
$ md test
```

*mkdir* returns nothing. Literally, *mkdir* command only make directory. You can check that the directory has been made with *ls* command.


*cd* is abbr. of "Change Directory".

You can change your working directory to 'test' as following:

### Example

```
$ pwd  
$ cd test  
$ pwd
```

Also, you can go your home folder at once with *cd*, no matter where you are.



```
05:01:20 fumire@fumire-raspberry ~/test  
$ cd  
05:01:23 fumire@fumire-raspberry ~  
$ pwd  
/home/fumire
```

Figure: *cd* will guide you to home folder

# Tip!

If you hit "Tab" button, ZSH will give proper candidates.  
Following example shows what ZSH gives.



```
07:25:54 fumire@fumire-raspberry ~  
$ cd  
Desktop/ Downloads/ Music/ Public/ Templates/ Videos/  
Documents/ Library/ Pictures/ snap/ test/
```

Figure: Shortcut with Tab

You can get detailed information about command as following:

## Example

```
$ man ls  
and/or  
$ ls --help
```

This guide will give simple information about Linux command. Hence, when you have curiosity about command, use these command.

# Directory Structure


Try following commands:

## Example

```
$ cd test
```

```
$ ls -al
```

Then, you can see like this:



```
05:25:28 ~ fumire@fumire-raspberry ~  
$ cd test  
05:25:30 ~ fumire@fumire-raspberry ~/test  
$ ls -al  
total 8  
drwxrwxr-x 2 fumire fumire 4096 Jan 5 04:53 .  
drwxr-xr-x 22 fumire fumire 4096 Jan 5 05:25 ..
```

Figure: Result of `ls` command

All directory has `'.'` and `'..'`, even though the directory is empty.  
`'.'` means current directory itself; and, `'..'` means parent directory.



# touch

*touch* command make new file or touch the file.

Try following example:

## Example

```
$ cd  
$ touch t  
$ ls
```

Then, you can see that the file which name 't' has been made.



```
06:32:37 funire@funire-raspberry ~  
$ cd  
06:32:40 funire@funire-raspberry ~  
$ touch t  
06:32:42 funire@funire-raspberry ~  
$ ls  
Desktop  Documents  Downloads  Library  Music  Pictures  Public  snap  t  Templates  test  Videos
```

Figure: Result of *touch* Command

*mv* command moves/renames file. *mv* is used as:

### Example

```
$ mv SRC(source) DST(destination)
```

Try following commands:

### Example

```
$ mv t tmp  
$ ls  
$ mv tmp test/  
$ ls
```

Then, you will realize that the file 'tmp' is gone. I hope that you already know where the file goes. :)

*cp* command copies SRC to DST. *cp* is used as:

### Example

```
$ cp SRC DST
```

Try following commands:

### Example

```
$ cd ~/test/  
$ ls  
$ cp tmp tmp2  
$ ls
```

Then, you can realize that a new file 'tmp2' has been made.

*rm* stands for 'Remove'. As its name, you can delete files or directory.

### Example

```
$ rm tmp2
```

When you want delete directory, use '-r' option:

### Example

```
$ rm -r directoryname
```

*sudo* is abbr. of "Substitute User do"; but, many people know as "Super User do".

*sudo* allows a system administrator to delegate authority to give certain user the ability to run some command as another user.




Figure: XKCD: Sandwich

THINK what will happen after *sudo* command!!

There are three major editors in Linux.




Figure: Descriptions of Editor

For this reason, this guide use VIM editor.




Figure: Learning Curves among Editors


# First Meet with VIM

With these commands, you can make/edit file.

## Example

```
$ vi tmp
```

If it is first time to open VIM, then you will see like this.



```
1 Installing plugins (8/24)
2 [
3   ]
4 2 * indentline: Installing ...
5 3 * vim-gnome-code-break: Installing ...
6 4 * tabline-vim: Installing ...
7 5 * php.vim: Installing ...
8 6 * vim-repeat: Installing ...
9 7 * vim-commentary: Installing ...
10 8 * vim-tui: Cloning into '/home/funire/.vim/plugged/vi-
11 9 * nerdtree: Cloning into '/home/funire/.vim/plugged/ne-
12 10 * vim-fugitive: Cloning into '/home/funire/.vim/pluged-
13 11 * singleComite: Cloning into '/home/funire/.vim/pluged-
14 12 * strip.vim: Cloning into '/home/funire/.vim/plugged/c-
15 13 * tagbar: Cloning into '/home/funire/.vim/plugged/tagb-
16 14 * scratch.vim: Cloning into '/home/funire/.vim/plugged-
17 15 * vim-surround: remote: Total 32 (delta 0), reused 20
18 16 * syntastic: Cloning into '/home/funire/.vim/plugged/s-
19 17 * vim-javascript: Cloning into '/home/funire/.vim/plug-
20 18 * vim-autoforamt: Cloning into '/home/funire/.vim/plug-
21 19 * vim-gitter: remote: Compressing objects: 100% (6-
22 20 * vim-bufferline: remote: Total 32 (delta 5), reused 1-
23 21 * vim-airline: remote: Compressing objects: 100% (680/
24 22 * undotree: Resolving deltas: 100% (32/32), done.
25 23 * csv.vim: remote: Total 44 (delta 16), reused 18 (del-
26 24 * merdcommenter: Resolving deltas: 100% (44/44), done.
27 25 * vim-awkdown: remote: Total 75 (delta 12), reused 59
28 26 [21] [All] [vim-plug] 0:1 [All] [No Name]
```

Figure: First Time of VIM



# Modes of VIM




Figure: Three Modes in VIM

# How to Edit with VIM

Editing with VIM is following such steps:

- ➊ Press 'i'
- ➋ Edit the file
- ➌ Press 'ESC'
- ➍ Enter ':w' which means *write*
- ➎ Enter ':q' which means *quit*

## Plugin Setting (Optional)

You might see the error message because the plugin setting is not completed. To solve this, use following commands:

### Example

```
$ cd ~/.vim/plugged/tabnine-vim/  
$ python3 install.py
```

Then, all plugin acts properly without errors.

*cat* stands for **concatenate**. *cat* command reads files, and writing them to standard output.

Consider following example:

### Example

```
$ cd ~/test/  
$ cat tmp
```

You can see contents of file.

# Input/Output to file

If you want redirect output to file, use following example:

## Example

```
$ cat tmp > output
```

However, this method *overwrites* the contents of file.

If you want preserve the file contents, use following:

## Example

```
$ cat tmp >> output
```

Also, < means input from file.

## Output to file *Cont.*

In some cases, you should divide standard output and standard error.  
In these cases, use following commands:

### Example

```
$ commands 1> STDOUT 2> STDERR
```

### Example

```
$ cat tmp 1> ex.stdout 2> ex.stderr
```

*more* and *less* are commands for seeing the contents of file. Consider following examples:

## Example

```
$ more tmp
```

## Example

```
$ less tmp
```

# Pipe

Use pipe (|) to indicate input as output of previous command.

## Example

```
$ command1 | command2
```

The output of command 1 will be the input of command2.  
Consider following example:

## Example

```
$ cat tmp | less
```



# Two Ways for Download

There are two main ways for download.

- 1 curl
- 2 wget

## Example

```
$ curl https://www.naver.com
```

*curl* returns to standard output. If you want to get file, consider following:

## Example

```
$ curl https://www.naver.com -o naver.html
```

*wget* returns a downloaded file as output.

## Example

```
$ wget https://www.naver.com  
$ ls
```

# gzip

*gzip* is used for file compression and decompression.

When compressing:

## Example

```
$ gzip tmp
```

When decompressing:

## Example

```
$ gzip -d tmp.gz
```

However, the examples hereinabove delete the original files. If you want *keep* original file, consider following:

## Example

```
$ gzip -k tmp
```

# TAR Files

*TAR* stands for "Tape Archives".

Originally, it is used for tape; but, in nowadays, it is used for file archiving system. Usually, make a directory to one TAR files.

TAR.GZ file is commonly used for distribution some software. For example:

## Example

```
$ wget https://www.python.org/ftp/python/3.8.1/Python-3.8.1.tgz
```

(TGZ is for TAR.GZ)

# TAR Files (*Cont.*)

You might think decompress TGZ file and make a directory from TAR file. However, you can decompress TGZ file at once:

## Example

```
$ tar -zxvf Python-3.8.1.tgz
```

Then, you can see the directory named 'Python-3.8.1'.