

Linux Beginner Guide

Jaewoong Lee

Ulsan National Institute of Science and Technology

jwlee230@unist.ac.kr

May 27, 2026

Introduction

In this guide, I assume that you can open a Linux shell in one of these ways:

- ❶ A current Ubuntu LTS desktop, WSL, or course-provided Linux server
- ❷ A terminal running bash or zsh
- ❸ A basic terminal editor such as Vim, Neovim, or nano
- ❹ SSH access if the lab uses a remote server

With this guide, you can use and understand a Linux system.

The commands are written for a beginner lab in 2026. Your prompt, user name, host name, or Linux distribution may look different, and that is fine.

Overview

- 1 Linux?
- 2 Basic Linux Command
- 3 Edit File with Vim
- 4 IO Redirections
- 5 How to Download from Web
- 6 User Permissions
- 7 Process Control
- 8 Process Control with Slurm

Linux?



Figure: Linus Torvalds, Inventor of Linux

Linux is a widely used operating system family, alongside Windows and macOS.

Linux is open source and is used on servers, cloud systems, laptops, embedded devices, and phones.

Android, a mobile operating system, is based on Linux.

Ubuntu?



Figure: Logo of Ubuntu

Ubuntu is a beginner-friendly Linux distribution. It is common in classrooms, cloud images, WSL, and personal machines, but most commands in this guide also work on other Linux distributions.

Where we start

```
$ ssh fumire@192.168.
fumire@192.168.0.69's password:
Welcome to Ubuntu 18.04.2 LTS (GNU/Linux 4.15.0-1032-raspi2 armv7l)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

0 packages can be updated.
0 updates are security updates.

Last login: Sun Jan  5 03:49:29 2020 from 192.168.
fumire@fumire-raspberry:~$
```

Figure: Here is where we start

After you open a terminal or connect to a server via SSH, you may see a prompt like this.

Here is where we start!

The text before '@' is the user name, and the text after '@' is the server or computer name.

```
fumire@fumire-raspberry:~$ pwd  
/home/fumire
```

Figure: Result of *pwd* Command

pwd is abbr. of "Print Working Directory".

You can see where you are with *pwd* command.

Also, "/home/username" is your *home folder*, a.k.a. '~'.

```
fumire@fumire-raspberry:~$ ls  
Desktop  Documents  Downloads  Music  Pictures  Public  snap  Templates  Videos
```

Figure: Result of `ls` Command

`ls` stands for "List".

`ls` command lists current directory contents.

If current directory is empty, the result will be nothing.

Configuration

Before starting the lab, make a small working directory. No custom dotfiles, shell theme, or plugin setup is required.

Example

```
$ mkdir -p ~/linux-lab  
$ cd ~/linux-lab  
$ pwd
```

Note that you should input only the command after '\$'.
If you use your own Ubuntu machine and a command is missing, install the basic tools with *sudo apt install vim curl wget screen*.

Configuration (Cont.)

```
$ ssh fumire@192.168.
fumire@192.168.0.69's password:
Welcome to Ubuntu 18.04.2 LTS (GNU/Linux 4.15.0-1032-raspi2 armv7l)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

409 packages can be updated.
238 updates are security updates.

Last login: Sun Jan  5 04:36:48 2020 from 192.168.
04:39:57 fumire@fumire-raspberry ~
```

Figure: Shell Prompt

Your prompt may look different from this image. The important part is that you know which directory you are in.

Tip!

```
04:39:57 fumire@fumire-raspberry ~  
$ ls  
Desktop Documents Downloads Library Music Pictures Public snap Templates Videos  
04:39:59 fumire@fumire-raspberry ~  
$ Is  
zsh: command not found: Is
```

Figure: Right Command vs. Wrong Command

Many shells highlight valid commands or paths. Treat this as a helpful hint, not as a replacement for reading the command before pressing Enter.

mkdir stands for "Make Directory".

You can make a directory which named 'test' as following:

Example

```
$ mkdir test
```

```
$ ls
```

mkdir returns nothing when it succeeds. Literally, *mkdir* command only makes a directory.

You can check that the directory has been made with *ls* command.


cd is abbr. of "Change Directory".

You can change your working directory to 'test' as following:

Example

```
$ pwd  
$ cd test  
$ pwd
```

Also, you can go your home folder at once with *cd*, no matter where you are.



```
05:01:20 fumire@fumire-raspberry ~/test  
$ cd  
05:01:23 fumire@fumire-raspberry ~  
$ pwd  
/home/fumire
```

Figure: *cd* will guide you to home folder

Tip!

If you hit the "Tab" key, bash and zsh can complete file names, directory names, and commands.

Following example shows what tab completion gives.

A terminal window with a black background. The top bar shows the time 07:25:54, the user fumire, and the host fumire-raspberry. The prompt is \$ and the command cd is entered. Below the prompt, a list of directories is displayed in two rows: Desktop/, Downloads/, Music/, Public/, Templates/, Videos/ in the first row, and Documents/, Library/, Pictures/, snap/, test/ in the second row. All directory names are in blue text.

```
07:25:54 fumire@fumire-raspberry ~  
$ cd  
Desktop/ Downloads/ Music/ Public/ Templates/ Videos/  
Documents/ Library/ Pictures/ snap/ test/
```

Figure: Shortcut with Tab

You can get detailed information about command as following:

Example

```
$ man ls  
and/or  
$ ls --help
```

This guide gives simple information about Linux commands. When you want more detail about a command, use these commands.


Directory Structure

Try following commands:

Example

```
$ cd test  
$ ls -al
```

Then, you can see like this:



```
05:25:28 ~ fumire@fumire-raspberry ~  
$ cd test  
05:25:30 ~ fumire@fumire-raspberry ~/test  
$ ls -al  
total 8  
drwxrwxr-x 2 fumire fumire 4096 Jan 5 04:53 .  
drwxr-xr-x 22 fumire fumire 4096 Jan 5 05:25 ..
```

Figure: Result of `ls` command

All directory has `'.'` and `'..'`, even though the directory is empty.
`'.'` means current directory itself; and, `'..'` means parent directory.

touch

touch command make new file or touch the file.
Try following example:

Example

```
$ cd  
$ touch t  
$ ls
```

Then, you can see that the file which name 't' has been made.



```
06:32:37 funire@funire-raspberry ~  
$ cd  
06:32:40 funire@funire-raspberry ~  
$ touch t  
06:32:42 funire@funire-raspberry ~  
$ ls  
Desktop Documents Downloads Library Music Pictures Public snap t Templates test Videos
```

Figure: Result of *touch* Command

mv command moves/renames file. *mv* is used as:

Example

```
$ mv SRC(source) DST(destination)
```

Try following commands:

Example

```
$ mv t tmp  
$ ls  
$ mv tmp test/  
$ ls
```

Then, you will realize that the file 'tmp' is gone. I hope that you already know where the file goes. :)

cp command copies SRC to DST. *cp* is used as:

Example

```
$ cp SRC DST
```

Try following commands:

Example

```
$ cd ~/test/  
$ ls  
$ cp tmp tmp2  
$ ls
```

Then, you can realize that a new file 'tmp2' has been made.

rm stands for 'Remove'. As its name, you can delete files or directories.

Example

```
$ rm tmp2
```

When you want to delete a directory, use '-r' option:

Example

```
$ rm -r directoryname
```

There is no way to restore removed files!! Beware what you remove!!

sudo is abbr. of "Substitute User do"; but, many people know as "Super User do".

sudo allows a system administrator to delegate authority to give certain user the ability to run some command as another user.




Figure: XKCD: Sandwich

THINK what will happen after *sudo* command!!

Editor

Common choices include nano, Vim/Neovim, Emacs, and VS Code Remote SSH.




Figure: Descriptions of Editor

This guide uses Vim because it is available on many servers.

Editor (Cont.)




Figure: Learning Curves among Editors


First Meet with Vim

With these commands, you can make/edit file.

Example

```
$ vim notes.txt
```

If it is your first time to open Vim, then you may see something like this.



```
1 Installing plugins (8/24)
2 [#####]
3
4 * indentline: Installing ...
5 * vim-grepper: Installing ...
6 * tabline-vim: Installing ...
7 * php.vim: Installing ...
8 * vim-repeat: Installing ...
9 * vim-commentary: Installing ...
10 * vim-tmux: Cloning into '/home/fumire/.vim/plugged/vi-
11 * nerdtree: Cloning into '/home/fumire/.vim/plugged/ne-
12 * vim-fugitive: Cloning into '/home/fumire/.vim/plugge-
13 * singleCompile: Cloning into '/home/fumire/.vim/plugg-
14 * ctrlp.vim: Cloning into '/home/fumire/.vim/plugged/c-
15 * tagbar: Cloning into '/home/fumire/.vim/plugged/tagb-
16 * scratch.vim: Cloning into '/home/fumire/.vim/plugged-
17 * vim-surround: remote: Total 32 (delta 7), reused 26
18 * aynstastic: Cloning into '/home/fumire/.vim/plugged/s-
19 * vim-javascript: Cloning into '/home/fumire/.vim/plug-
20 * vim-autofmt: Cloning into '/home/fumire/.vim/plug
21 * vim-gitter: remote: Compressing objects: 100% (26
22 * vim-bufferline: remote: Total 32 (delta 5), reused 1
23 * vim-viml: remote: Compressing objects: 100% (688/6
24 * undotree: Resolving deltas: 100% (32/32), done.
25 * csv.vim: remote: Total 44 (delta 16), reused 18 (del
26 * nerdcommenter: Resolving deltas: 100% (44/44), done.
27 * vim-makdown: remote: Total 79 (delta 12), reused 39
28
29 2:1 [All] [-] [Plugins] 0:1 [All] [No Name]
```

Figure: First Time of Vim

Modes of Vim




Figure: Three Modes in Vim

How to Edit with Vim

Editing with Vim follows these steps:

- ➊ Press 'i'
- ➋ Edit the file
- ➌ Press 'ESC'
- ➍ Enter ':w' which means *write*
- ➎ Enter ':q' which means *quit*

Editor Practice (Optional)

No Vim plugin is required for this lab. If you want a guided practice session, run:

Example

```
$ vimtutor
```

If *vimtutor* is not installed on your own Ubuntu machine, install Vim with:

Example

```
$ sudo apt install vim
```

cat stands for **concatenate**. *cat* command reads files, and writing them to standard output.

Consider following example:

Example

```
$ cd ~/test/  
$ cat tmp
```

You can see contents of file.

Input/Output to file

If you want redirect output to file, use following example:

Example

```
$ cat tmp > output
```

However, this method *overwrites* the contents of file.

If you want preserve the file contents, use following:

Example

```
$ cat tmp >> output
```

Also, < means input from file.

Output to file *Cont.*

In some cases, you should divide standard output and standard error.
In these cases, use following commands:

Example

```
$ commands 1> STDOUT 2> STDERR
```

Example

```
$ cat tmp 1> ex.stdout 2> ex.stderr
```

more and *less* are commands for seeing the contents of file. Consider following examples:

Example

```
$ more tmp
```

Example

```
$ less tmp
```

Also, hit "Q" when you want to leave *more* or *less*.

Pipe

Use pipe (|) to indicate input as output of previous command.

Example

```
$ command1 | command2
```

The output of command 1 will be the input of command2.

Consider following example:

Example

```
$ cat tmp | less
```


Two Ways for Download

There are two main ways for download.

- 1 curl
- 2 wget

Example

```
$ curl https://example.com
```

curl returns to standard output. If you want to get file, consider following:

Example

```
$ curl -L https://example.com -o example.html
```

wget returns a downloaded file as output.

Example

```
$ wget https://example.com -O example.html  
$ ls
```

gzip

gzip is used for file compression and decompression.

When compressing:

Example

```
$ gzip tmp
```

When decompressing:

Example

```
$ gzip -d tmp.gz
```

However, the examples hereinabove delete the original files. If you want *keep* original file, consider following:

Example

```
$ gzip -k tmp
```

TAR stands for "Tape Archives".

Originally, it was used for tape; today, it is used to bundle many files into one archive.

TAR.GZ files are commonly used for source code and lab data. Replace LAB-URL with the URL from your instructor:

Example

```
$ wget LAB-URL -O lab-files.tar.gz
```

(TGZ is for TAR.GZ)

TAR Files (*Cont.*)

You might think you must decompress the GZ file and then extract the TAR file. However, you can extract a TGZ or TAR.GZ file at once:

Example

```
$ tar -xzf lab-files.tar.gz
```

Then, you can see the extracted directory with *ls*.

Permissions

With the following command, we can know how permissions are set:

Example

```
$ ls -al
```

```
08:16:10 fumire@fumire-raspberry ~/test
$ ls -al
total 16
drwxrwxr-x 2 fumire fumire 4096 Jan  5 08:16 .
drwxr-xr-x 23 fumire fumire 4096 Jan  5 09:29 ..
-rw-rw-r-- 1 fumire fumire  0 Jan  5 07:32 ex.stderr
-rw-rw-r-- 1 fumire fumire  9 Jan  5 07:32 ex.stdout
-rw-rw-r-- 1 fumire fumire  9 Jan  5 07:07 tmp
```

Figure: File Permissions

The way to read this result is following:




Figure: How to Read Permissions

chmod stands for "Change Mode". You can modify permissions of files. Before input command, you should calculate simple arithmetic:

Owner	  	rwX $4 + 2 + 1 = 7$
Group	  	rwX $4 + 2 + 1 = 7$
Other	 	rw- $4 + 2 = 6$

File Permission: **rwX** **rwX** **rx-** **776**

Figure: Simple Arithmetic

Then, you will get three digits for permission. Moreover, 660 or 770 are usually used.

Example

```
$ chmod three_digits filename
```


chmod (*Cont.*)

Or, you can do as followings:

Example

```
$ chmod rwx----- tmp
```

Example

```
$ chmod g=rwx tmp
```

Example

```
$ chmod +x tmp
```

chown stands for "change ownership". As its name, you can modify ownership of file.

When you want to change only USER:

Example

```
$ chown USER tmp
```

When you want to change both USER and GROUP:

Example

```
$ chown USER:GROUP tmp
```

When you have started command, but you realize that you should stop the command, then use "Ctrl-C".

Example

```
$ sleep 99999  
$ ^C
```

Ctrl-C sends SIGINT, which stands for "Signal Interruption"; and, the process is going to terminate after receiving SIGINT.

Consider long-time procedure, such as:

Example

```
$ sleep 99999
```

However, with '&', you do not have to wait procedure.

Example

```
$ sleep 99999 &
```

Then, the process is executing on background.

jobs commands shows the background process.

Example

```
$ jobs
```

```
09:55:43 fumire@fumire-raspberry ~/test 7s
$ sleep 99999 &
[1] 18945

10:02:56 fumire@fumire-raspberry ~/test
$ jobs
[1] + running    sleep 99999
```

Figure: Result of *jobs*

You use record the [number] for handle the process.

kill command kills the process.

When you want to kill background process, consider following:

Example

```
$ kill %number
```

The number is from the *jobs* command.

Example

```
$ kill process_number
```

You can kill as above when you know exact process number (PID).

When you lost from SSH connection, all executing process receive SIGHUP, which stands for Signal Hangup, and will be terminate even they runs on background.

To prevent SIGHUP, use *nohup* command.

Example

```
$ nohup sleep 99999 &
```

However, *nohup* command makes 'nohup.out' automatically. You can change output file name with IO redirection.

screen prevents unintentional connection lost.

Make screen session with simple command:

Example

```
$ screen
```

When you want to detach the screen session, use following, instead of *exit*:

Example

```
$ ^a, d
```

When you restore the screen session, use following command:

Example

```
$ screen -r
```


We use a shared server or cluster, not a dedicated machine. Therefore, CPU, memory, GPU, and time should be distributed across all users. Slurm is a job scheduler. It places your job in a queue, starts it when resources are available, and records the result.

Script File

Script file is a text file containing a collection of shell statements and Slurm options.

Make a script file via Vim as:

Example

```
$ vim tmp.sh
```

Also, the file contents should be:

Example

```
#!/bin/bash
#SBATCH --job-name=linux-lab
#SBATCH --time=00:05:00
#SBATCH --cpus-per-task=1
hostname
sleep 30
```

Lines beginning with `#SBATCH` tell Slurm what resources the job needs.

You can submit the script file to the queue with *sbatch* command:

Example

```
$ sbatch tmp.sh
```

When you want to designate the log file names, consider following:

Example

```
$ sbatch --output=outputlog.txt --error=errorlog.txt tmp.sh
```

You can check your jobs with *squeue* command:

Example

```
$ squeue -u $USER
```

If you want to check jobs from all users, consider following:

Example

```
$ squeue
```

Note that you should record the JOBID for further handling.

If you want to cancel submitted jobs, you can use *scancel* command:

Example

```
$ scancel JOBID
```

If you want to cancel all jobs from you, consider following:

Example

```
$ scancel -u $USER
```