

Exercises

You should check your solutions using GHCI or writing a .hs script and running it.

Exercise 1:

Using list comprehension define the following list

```
[1,2,3,4,5,6]
```

Exercise 2:

Using list comprehension define the following list

```
[10,20,30,40,50,60]
```

Exercise 3:

Using list comprehension define the following list

```
[(1,1),(2,2),(3,3),(4,4)]
```

Exercise 4:

Using list comprehension define the following list

```
[(1,2),(2,3),(3,4),(4,5)]
```

Exercise 5:

Using list comprehension define the following list (note that the second element in the 2-tuple is always 1).

```
myConstFunc = [(1,1),(2,1),(3,1),(4,1),(5,1)]
```

Exercise 6:

Using list comprehension define the list of tuples, containing a number (between 1 and 10 inclusive) and its square.

```
squares = [(1,1),(2,4),(3,9),(4,16),(5,25),(6,36),  
           (7,49),(8,64),(9,81),(10,100)]
```

Exercise 7:

Write down the values as defined in the following lists f1, f2, f3. Check your answers.

```
f1 :: [(Int, Int)]
f1 = [(x, y) | x <- [1..3], y <- [4..5]]

f2 :: [(Int, Int)]
f2 = [(x, y) | y <- [4..5], x <- [1..3]]

f3 :: [(Int, Int)]
f3 = [(y, x) | x <- [1..3], y <- [4..5]]
```

Exercise 8:

Given the following definition of

```
isEven :: Integer -> Bool
isEven n = (n `mod` 2 == 0)
```

Write down the values as defined in the following list: Check your solution.

```
[2*n | n <- [2,4,7], isEven n, n>3]
```

Exercise 9:

Give a definition of a function

```
doubleAll :: [Integer] -> [Integer]
```

which doubles all the elements of a list of integers.

Exercise 10:

Give a definition of a function

```
capitalize :: String -> String
```

which converts all small letters in a String into capitals.

Hint: You can use the following function (having imported Data.Char):

```
import Data.Char
toupper :: Char -> Char
```

Exercise 11:

Using a list comprehension, write a function **sigma** that calculates the sum of

$$\sum_{i=1}^{i=100} i^2$$

Exercise 12:

Using a list comprehension, write a function **sigma'**

```
sigma' :: Int -> Int
```

that takes an integer n and calculates

$$\sum_{i=1}^{i=n} i^2$$

Exercise 13:

Define the function

```
matches :: Integer -> [Integer] -> [Integer]
```

which picks out all occurrences of an integer in a list. For instance:

```
*Main> matches 1 [1,2,3,4,1]
[1,1]
*Main> matches 1 [2,3,4]
[]
*Main> 
```

Using matches or otherwise (**Hint:** e.g. the **patterns** functions seen in class), define a function

```
elem' :: Integer -> [Integer] -> Bool --elem is already defined in Prelude
```

which is True if the Integer is an element of the list, and False otherwise.

Exercise 14:

Suppose that a *coordinate grid* of size $m \times n$ is given by the list of all pairs (x, y) of integers such that $0 \leq x \leq m$ and $0 \leq y \leq n$. Using a list comprehension, define a function:

```
grid :: Int -> Int -> [(Int, Int)]
```

that returns a coordinate grid of a given size. For example:

```
*Main> grid 1 2
[(0,0),(0,1),(0,2),(1,0),(1,1),(1,2)]
*Main> █
```

Exercise 15:

Using a list comprehension and the function **grid** above, define a function

```
square :: Int -> [(Int, Int)]
```

that returns a coordinate square of size n , excluding the diagonal from $(0, 0)$ to (n, n) . For example:

```
*Main> square 2
[(0,1),(0,2),(1,0),(1,2),(2,0),(2,1)]
*Main> █
```

Exercise 16:

In a similar way to the function *length*, show how the library function

```
replicate :: Int -> a -> [a]
```

that produces a list of identical elements can be defined using list comprehension. (Call your version **myReplicate**) For example:

```
*Main> myReplicate 3 True
[True,True,True]
  █
```

Exercise 17:

A triple (x, y, z) of positive integers is called pythagorean if $x^2 + y^2 = z^2$. Using a list comprehension, define a function

```
pyths :: Int -> [(Int,Int,Int)]
```

that returns a list of all such triples whose components are at most a given limit. For example

```
*Main> pyths 10
[(3,4,5),(4,3,5),(6,8,10),(8,6,10)]
*Main> █
```

Exercise 18:

A positive integer is perfect if it equals the sum of all of its factors, excluding the number itself. Using a list comprehension and the function **factors**, define a function

```
perfects :: Int -> [Int]
```

that returns the list of all perfect numbers up to a given limit. For example:

```
*Main> perfects 500
[6,28,496]
*Main> █
```

Hint: Note that the list of factors of x includes x ...