Integration testing with TestContainers-Go



Erdem Toraman

Nikolay Kuznetsov

GoDays - Berlin 23 Jan 2020

About us


- Go developers at Zalando in Helsinki
- Project with ~20 microservices in Go
- User perspective of TestContainers-Go library

2 unit tests passed, 0 integration tests





Basic integration test




Getting a database for testing

Local database

- In-memory mock
- Docker!

Docker advantages

- 100% compatible databases
- Same version as production
- Empty DB state



Integration testing with Docker



Easy-peasy!

docker run -d -p 5432:5432 postgres:12.1



What could go wrong?

- Host port conflicts
- Not ready container / service
- Resource leak (the container keeps running)
- Stale data (if reusing the same container)
- Starting mechanism both for CI and a local machine




Solving some issues

```
#!/bin/sh
DB NAME=users
TABLE NAME=users
if [[ ! $(docker ps -q -f name=user-postgres) ]]; then
    if [[ $(docker ps -ag -f status=exited -f name=user-postgres) ]]; then
        # cleanup
        docker rm user-postgres
    fi
    docker run -d --name user-postgres -p 5432:5432 postgres:9.6.13
    sleep 5
    docker exec user-postgres psql --user=postgres -p 5432 -c "CREATE DATABASE $DB_NAME;"
else
    echo "it's already running"
fi
```



Docker API



docs.docker.com/engine/api/latest

Exec example


EXEC

Create an exec instance

Start an exec instance

Resize an exec instance

Inspect an exec instance





TestContainers flavors













TestContainers-Go

github.com/testcontainers/testcontainers-go

- Docker Go client under the hood
- Host port randomization
- Containers clean up at the test shutdown
- Readiness waiting strategies



As simple as

```
pgContainer, err := tc.GenericContainer(ctx,
 tc GenericContainerRequest{
   ContainerRequest: tc.ContainerRequest{
    Image: "postgres:12.1",
    ExposedPorts: []string{"5432/tcp"},
```

Host port randomization

IMAGE PORTS postgres:12.1 0.0.0:32770->5432/tcp

API to get a host port:

port, err := pgContainer.MappedPort(ctx, "5432/tcp")

- Prevents port conflicts
- Enables parallel builds

Containers cleanup: Ryuk

github.com/testcontainers/moby-ryuk

- Ryuk kills containers (networks, volumes) by labels
- TC assigns labels to started containers
- TC keeps a connection to Ryuk open



sessionId 2a0770fa-e

Waiting strategies

- Host port
- HTTP
- Logs
- Custom
- Multi



Host port waiting strategy

```
tc.ContainerRequest{
    Image: "postgres:12.1",
    ExposedPorts: []string{"5432/tcp"},
    WaitingFor: wait.ForListeningPort("5432/tcp"),
},
```

- Default (customizable) timeout is 60 seconds
- Impl checks both from outside and inside container

HTTP waiting strategy

```
WaitingFor: wait.ForHTTP("/health").

WithPort("8080/tcp").

WithStatusCodeMatcher(

func(status int) bool { return status == http.StatusOK }),
```

Demo

Demo I: integration testing

github.com/erdemtoraman/godays-testcontainers-demo

- Testing interaction with a database
- Create and Get users from Postgres

User Repository




What happened?

- Ran a Postgres container
- Mapped a random port to the host machine
- Ran tests against it
- Cleaned up the containers

Demo II: end-to-end testing

github.com/erdemtoraman/godays-testcontainers-demo



Takeaways

- testcontainers.org
- Balance between flexibility, speed and features
- Great for integration tests
- Possible to use for end-to-end tests



Thank you!

- Y
- @erdem_toraman, @nikolayk812
- erdemtoraman