

FundLoop App Summary

One-page product snapshot based only on evidence in this repository.

What It Is

FundLoop is a Next.js and Supabase web app for a revenue-sharing ecosystem where projects pledge part of their revenue and active users receive a recurring citizen salary.

The repo shows a two-sided product with onboarding, project discovery, analytics, support, and admin surfaces.

Who It's For

Primary users are project teams and individual community members/builders. The landing page and onboarding flows explicitly split into 'Join as a Project' and 'Join as a User.'

What It Does

- Guides project and user sign-up through multi-step onboarding flows.
- Stores user profiles, invite codes, interests, occupations, wallets, and contribution skills in Supabase/Postgres.
- Stores project records, categories, payment settings, visibility, and organization links.
- Shows project detail pages with participant lists and payment/citizen-salary summaries.
- Tracks monthly network stats and renders analytics dashboards and charts.
- Accepts support requests and newsletter subscriptions.
- Includes admin and super-admin areas for payments, users, organizations, audit log, and invitation attribution.

How It Works

- Frontend: Next.js 15 App Router in `app/`, React 19 components in `components/`, and Tailwind/shadcn UI.
- Auth and data access: browser Supabase clients in UI components plus Next server actions using `@supabase/ssr` for authenticated account operations.
- Persistence: SQL in `database/` defines `users`, `projects`, `payments`, `monthly\_network\_stats`, `support\_requests`, `newsletter\_subscribers`, organizations, invitations, wallets, and audit tables.
- Data flow: forms/pages read and write Supabase tables directly; some server actions revalidate routes after account changes.
- Repo caveat: several screens are explicitly labeled dummy/mock data. External payment processor or background-job service: **Not found in repo.**

How To Run

- Run `bash setup.sh` to enable Corepack, install dependencies with `pnpm install`, and seed `.env.local` from `.env.example` when missing.
- Set `NEXT\_PUBLIC\_SUPABASE\_URL` and `NEXT\_PUBLIC\_SUPABASE\_ANON\_KEY` in `.env.local`.
- Run the SQL files in `database/` against your Supabase project in order.
- Start the app with `pnpm dev`, then open `http://localhost:3000`.