


Monády – úvod



Phil Wadler: <http://homepages.inf.ed.ac.uk/wadler/topics/monads.html>

- Monads for Functional Programming In *Advanced Functional Programming*, Springer Verlag, LNCS 925, 1995,

- Noel Winstanley: What the hell are Monads?, 1999

<http://web.cecs.pdx.edu/~antoy/Courses/TPFLP/lectures/MONADS/Noel/research/monads.html>

- Jeff Newbern's: All About Monads

https://www.cs.rit.edu/~swm/cs561/All_About_Monads.pdf

- Dan Bensen: A (hopefully) painless introduction to monads,

<http://www.prairienet.org/~dsb/monads.htm>

Monady sú použiteľný nástroj pre programátora poskytujúci:

- modularitu – skladať zložitejšie výpočty z jednoduchších (no side-effects),
- flexibilitu – výsledný kód je ľahšie adaptovateľný na zmeny,
- izoluje side-effect operácie (napr. IO) od čisto funkcionálneho zvyšku.



Maybe Monad

Maybe je podobné Exception (Nothing $\sim\sim$ Raise String, Just a $\sim\sim$ Return a)

```
data Maybe a = Nothing | Just a
```

```
instance Monad Maybe where
```

```
    return v      = Just v  
    fail          = Nothing
```

-- vrát' hodnotu
-- vrát' neúspech

```
    Nothing >>= _ = Nothing  
    (Just x) >>= f = f x
```

-- reťazenie, bind, ...
-- ak už nastal neúspech, trvá do konca
-- ak je zatiaľ úspech, závisí to na výpočte f

```

return v      = Just v
fail          = Nothing
Nothing >>=   = Nothing
(Just x) >>= f = f x

```

Príklady na Maybe Monad

- konšaty: `Just 1, Nothing :: Maybe Int`, `Just "b" :: Maybe String`

- základné operácie:

`(Just 1) >>= (\x -> Nothing)` = Nothing

`(Just 1) >>= (\x -> Just (1+x))` = Just 2

`Nothing >>= (\x -> Just (1+x))` = Nothing

- do-notácia, monad-comprehension:

`do { x<-(Just 1); Nothing } :: Maybe t` = Nothing

`do { x<-(Just 1); return (1+x) } :: Maybe Int` = Just 2

`do { x<-(return 1); return (1+x) } :: (Monad m, Num b) => m b`

`do { x<-(return 1); return (1+x) }` = 2

`do { x<-(return 1); return (Just (1+x)) } :: Maybe Int` = Just 2

`do { x<-(return 1); return [1+x] } :: [Int]` = [2]

`do { x<-Nothing; return (1+x) } :: Maybe Int` = Nothing



Monadic Prelude

```
class Monad m where
```

```
    return  :: a -> m a
```

```
    (>>=)   :: m a -> (a -> m b) -> m b
```

```
    (>>)     :: m a -> m b -> m b
```

```
    p >> q = p >>= \ _ -> q
```

-- definition:(>>=), return

-- zahodíme výsledok prvej monády

-- ak nezáleží na výsledkoch

```
sequence_  :: (Monad m) => [m a] -> m ()
```

```
sequence_  = foldr (>>) (return ())
```

```
sequence_ (c:cs) = do { _ <- c; _ <- sequence cs; return () }
```

```
sequence_ [m1,m2,...mn] = m1 >>= \ _ ->
```

```
    m2 >>= \ _ ->
```

```
    ...
```

```
    mn >>= \ _ ->
```

```
    return ()
```

```
do { m1 ;
```

```
    m2 ;
```

```
    ...
```

```
    mn ;
```

```
    return ()
```



Maybe sequence

```
sequence      :: Monad m => [m a] -> m [a]
sequence []   = return []
sequence (c:cs) = do { x <- c; xs <- sequence cs; return (x:xs) }
```

```
sequence [Just "a", Just "b", Just "d"]      = Just ["a","b","d"]
sequence []                                   = Just []
sequence [Just "a", Just "b", Nothing, Just "d"] = Nothing
```

```
sequence [putStr "ab", putStr "ba", putStrLn "!"] = [(),(),()]
abba!
sequence_ [putStr "ab", putStr "ba", putStrLn "!"] = []
abba!
```



Maybe MonadPlus

```
data Maybe a = Nothing | Just a
```

```
class Monad m => MonadPlus m where – podtrieda, resp. podinterface  
  mzero    :: m a                    --  $\emptyset$   
  mplus     :: m a -> m a -> m a    -- disjunkcia
```

```
instance MonadPlus Maybe where  
  mzero          = Nothing           -- fail...  
  Just x `mplus` y    = Just x       -- or  
  Nothing `mplus` y   = y
```

```
Just "a" `mplus` Just "b"      = Just "a"   !!!  
Just "a" `mplus` Nothing       = Just "a"  
Nothing `mplus` Just "b"      = Just "b"
```



Zákony monád a monády Plus

- vlastnosti return a >>=:

```
return x >>= f           = f x           -- return ako identita zľava
p >>= return             = p             -- return ako identita sprava
p >>= (\x -> (f x >>= g)) = (p >>= (\x -> f x)) >>= g -- "asociativita"
```

- vlastnosti zero a `plus`:

```
zero `plus` p           = p             -- zero ako identita zľava `plus`
p `plus` zero           = p             -- zero ako identita sprava `plus`
p `plus` (q `plus` r)   = (p `plus` q) `plus` r -- asociativita
```

- vlastnosti zero `plus` a >>= :

```
zero >>= f               = zero          -- zero ako identita zľava `>>=`
p >>= (\x->zero)          = zero          -- zero ako identita sprava `>>=`
(p `plus` q) >>= f       = (p >>= f) `plus` (q >>= f) -- distributivita
```



Sheep family

```
adam  = Sheep "Adam"  Nothing Nothing
eve   = Sheep "Eve"   Nothing Nothing
uranus = Sheep "Uranus" Nothing Nothing
gaea  = Sheep "Gaea"  Nothing Nothing
kronos = Sheep "Kronos" (Just gaea) (Just uranus)
holly  = Sheep "Holly" (Just eve) (Just adam)
roger  = Sheep "Roger" (Just eve) (Just kronos)
molly  = Sheep "Molly" (Just holly) (Just roger)
dolly  = Sheep "Dolly" (Just molly) Nothing
```

-- a sheep has its name, and maybe mother and maybe father

```
data Sheep = Sheep {name :: String, mother :: Maybe Sheep, father :: Maybe Sheep}
                  deriving (Eq)
```

starý otec z matkinej strany

```
maternalGrandfather :: Sheep -> Maybe Sheep
```

```
maternalGrandfather' o = if mother o == Nothing then
```

```
    Nothing
```

```
  else
```

```
    father (fromJust (mother o))
```

-- klasicky:

-- o :: Sheep

-- mother o :: Maybe Sheep

-- fromJust ... :: Sheep

```
maternalGrandfather s = do{ m <- mother s ;
                           father m }
```

-- monadicky:

-- m :: Sheep

matky otca otec

maternalGrandfather dolly = Just "Roger"

```
mothersPaternalGrandfather :: Sheep -> Maybe Sheep
```

```
mothersPaternalGrandfather s = do { m <- mother s ;
```

```
    gf <- father m ;
```

```
    father gf }
```

-- m, gf :: Sheep

mothersPaternalGrandfather dolly = Just "Kronos"



List monad

- List monad použijeme, ak simulujeme nedeterministický výpočet
 - ...parsery boli toho príkladom

```
data List a = Null | Cons a (List a) deriving (Show)      -- alias [a]
```

```
instance Functor List where                                -- to je vlastne map
```

```
    fmap f Nil = Nil
```

```
    fmap f (Cons x xs) = Cons (f x) (fmap f xs)
```

```
instance Monad List where
```

```
    return x      = [x]
```

```
    m >>= f       = concatMap f m
```

```
    concatMap     = concat . map f m
```

```
    m >>= f       = concat (map f m)
```

```
:: a -> [a]
```

```
:: [a] -> (a -> [b]) -> [b]
```

```
return :: a -> [a]
>>=   :: [a] -> (a -> [b]) -> [b]
```



List Monad a MonadPlus

```
type List a      = [a]
```

```
instance Functor List where
    fmap = map
```

```
instance Monad List where
    return v      = [x]
    [] >>= f      = []
    (x:xs) >>= f  = f x ++ (xs >>= f)    -- concatMap f (x:xs)
```

```
instance MonadPlus List where
    mzero          = []
    [] `mplus` ys  = ys
    (x:xs) `mplus` ys = x : (xs `plus` ys) -- mplus je klasický append
```

List monad - vlastnosti

Príklad, tzv. listMonad $M\ a = List\ a = [a]$

$return\ x = [x]$ $:: a \rightarrow [a]$

$m\ >>= f = concatMap\ f\ m$ $:: [a] \rightarrow (a \rightarrow [b]) \rightarrow [b]$

$concatMap = concat . map\ f\ m$

Cvičenie: overme platnosť zákonov:

- $return\ c\ >>= (\backslash x \rightarrow g) = g[x/c]$
 - $[c]\ >>= (\backslash x \rightarrow g) = concatMap\ (\backslash x \rightarrow g)\ [c] = concat . map\ (\backslash x \rightarrow g)\ [c] = concat\ [g[x/c]] = g[x/c]$
- $m\ >>= \backslash x \rightarrow return\ x = m$
 - $[c_1, \dots, c_n]\ >>= (\backslash x \rightarrow return\ x) = concatMap\ (\backslash x \rightarrow return\ x)\ [c_1, \dots, c_n] = concat . map\ (\backslash x \rightarrow return\ x)\ [c_1, \dots, c_n] = concat\ [[c_1], \dots, [c_n]] = [c_1, \dots, c_n]$
- $m1\ >>= (\backslash x \rightarrow m2\ >>= (\backslash y \rightarrow m3)) = (m1\ >>= (\backslash x \rightarrow m2))\ >>= (\backslash y \rightarrow m3)$
 - $([c_1, \dots, c_n]\ >>= (\backslash x \rightarrow [d_1, \dots, d_m]))\ >>= (\backslash y \rightarrow m3) = (concat\ [[d_1[x/c_1], \dots, d_m[x/c_1]], \dots, [d_1[x/c_n], \dots, d_m[x/c_n]]])\ >>= (\backslash y \rightarrow m3) = ([d_1[x/c_1], \dots, d_m[x/c_1], \dots, d_1[x/c_n], \dots, d_m[x/c_n]])\ >>= (\backslash y \rightarrow m3) = ([d_1[x/c_1], \dots, d_m[x/c_1], \dots, d_1[x/c_n], \dots, d_m[x/c_n]])\ >>= (\backslash y \rightarrow [e_1, \dots, e_k]) = \dots [e_i[y/d_j[x/c_i]]]$



Zákony monadPlus pre List

- vlastnosti zero a `plus` :

zero `plus` p = p

p `plus` zero = p

p `plus` (q `plus` r) = (p `plus` q) `plus` r

-- preložené do ľudštiny:

-- [] ++ p = p

-- p ++ [] = p

-- asociativita ++

- vlastnosti zero `plus` a >>= :

zero >>= f = zero

p >>= (\x->zero) = zero

(p `plus` q) >>= f = (p >>= f) `plus` (q >>= f)

-- concat . map f [] = []

-- concat . map (\x->[]) p = []

-- concat . map f (p ++ q) =

concat . map f p

++

concat . map f q



List monad vs. comprehension

```
squares lst = do { x <- lst ;  
                  return (x * x) }
```

-- vlastne znamená

```
squares lst =      lst >>= \x -> return (x * x)
```

-- po dosadení >>=, return

```
squares lst = concat . map (\x -> [x * x]) lst
```

-- eta redukcia

```
squares = concat . map (\x -> [x * x])
```

-- takto by sme to napísali


```
squares = map (\x -> x * x)
```

-- iný príklad: kartézsky súčin

```
cart xs ys = do { x <- xs ;  
                 y <- ys ;  
                 return (x,y) }
```



Sheep family



adam = Sheep "Adam" Nothing Nothing
eve = Sheep "Eve" Nothing Nothing
uranus = Sheep "Uranus" Nothing Nothing
gaea = Sheep "Gaea" Nothing Nothing
kronos = Sheep "Kronos" (Just gaea) (Just uranus)
holly = Sheep "Holly" (Just eve) (Just adam)
roger = Sheep "Roger" (Just eve) (Just kronos)
molly = Sheep "Molly" (Just holly) (Just roger)
dolly = Sheep "Dolly" (Just molly) Nothing

```
data Sheep = Sheep {name::String, mother::Maybe Sheep, father::Maybe Sheep}
```

```
parents_ :: Sheep -> [Maybe Sheep]
```

```
parents_ x = [father x, mother x]
```

```
parents_ dolly = [Nothing, Just "Molly"]
```

```
parents :: Sheep -> Maybe [Sheep]
```

```
parents x = sequence [father x, mother x]
```

```
parents dolly = Nothing
```

```
parents roger = Just ["Kronos", "Eve"]
```

```
parents' :: Sheep -> [Sheep]
```

```
parents' x = (if father x == Nothing then [] else [ fromJust (father x) ]) ++  
             (if mother x == Nothing then [] else [ fromJust (mother x) ])
```

```
parents' dolly = ["Molly"]
```

```
parents' roger = ["Kronos", "Eve"]
```

```
parents" :: Sheep -> Maybe [Sheep]
```

```
parents" x = do { o<-father x; return [o] } `mplus` (do m<-mother x; return [m])
```

```
parents" dolly = Just ["Molly"]
```

```
parents" roger = Just ["Kronos"]
```

```
parents"' :: Sheep -> Maybe [Sheep]
```

```
parents"' x = do { o<-father x; m<-mother x; return ([o] `mplus` [m]) }
```

```
parents"' dolly = Nothing
```

```
parents"' roger = Just ["Kronos", "Eve"]
```

Sheep family

```
adam = Sheep "Adam"  Nothing Nothing
eve  = Sheep "Eve"   Nothing Nothing
uranus = Sheep "Uranus" Nothing Nothing
gaea = Sheep "Gaea"  Nothing Nothing
kronos = Sheep "Kronos" (Just gaea) (Just uranus)
holly = Sheep "Holly" (Just eve) (Just adam)
roger = Sheep "Roger" (Just eve) (Just kronos)
molly = Sheep "Molly" (Just holly) (Just roger)
dolly = Sheep "Dolly" (Just molly) Nothing
```

1) Definujte predkov po ženskej línii, teda
 k_mother 1 je mama, k_mother 2 je babka,
 k_mother 3 je prababka, ...

k_mother :: Int -> Sheep -> Maybe Sheep


k_mother 0 dolly = Just "Dolly"

k_mother 1 dolly = Just "Molly"

k_mother 2 dolly = Just "Holly"

k_mother 3 dolly = Just "Eve"

k_mother 4 dolly = Nothing



2) Definujte všetkých predkov k-tej úrovne, opakovať v zozname sa môžu:

k_predecessors :: Int -> Sheep -> [Sheep]

k_predecessors 1 dolly = ["Molly"]

k_predecessors 2 dolly = ["Roger","Holly"]

k_predecessors 3 dolly = ["Kronos","Eve","Adam","Eve"]

k_predecessors 4 dolly = ["Uranus","Gaea"]

k_predecessors 5 dolly = []



Guard

(Control.Monad)

```
pythagoras = [(x, y, z) | z <- [1..],  
                        x <- [1..z],  
                        y <- [x..z],  
                        x*x+y*y == z*z]
```

-- pythagorejské trojuholníky

```
pythagoras' = do z <- [1..]  
               x <- [1..z]  
               y <- [x..z]  
               if x*x+y*y == z*z then return (x,y,z) else return ()
```

-- zlé riešenie, prečo ?

```
pythagoras" ... if x*x+y*y == z*z then return "hogo-fogo" else []  
                return (x,y,z)                resp. ["hogo-fogo"]
```

```
pythagoras"" ... if x*x+y*y == z*z then return () else []  
                  resp. guard (x*x+y*y == z*z)  
                  return (x,y,z)
```




Guard

(Control.Monad)

Kartézsky súčin

```
guard :: (MonadPlus m) => Bool -> m ()
guard True  = return ()
guard False = mzero
> guard (9 > 5) >> return "hogo" :: [String]
["hogo"]
> guard (5 > 9) >> return "fogo" :: [String]
[]
```

```
listComprehension xs ys = [(x,y) | x<-xs, y<-ys ]
```

```
listComprehension [1,2,3] ['a','b','c'] = [(1,'a'),(1,'b'),(1,'c'),(2,'a'),(2,'b'),(2,'c'),(3,'a'),(3,'b'),(3,'c')]
```

```
guardedListComprehension xs ys = [(x,y) | x<-xs, y<-ys, x<=y, x*y == 24 ]
```

```
guardedListComprehension [1..10] [1..10] = [(3,8),(4,6)]
```

```
monadComprehension xs ys = do { x<-xs; y<-ys; return (x,y) }
```


```
monadComprehension [1,2,3] ['a','b','c'] = [(1,'a'),(1,'b'),(1,'c'),(2,'a'),(2,'b'),(2,'c'),(3,'a'),(3,'b'),(3,'c')]
```

```
guardedMonadComprehension xs ys =
```

```
do { x<-xs; y<-ys; guard (x<=y); guard (x*y==24); return (x,y) }
```

```
guardedMonadComprehension [1..10] [1..10] = [(3,8),(4,6)]
```

Backtracking



-- konsistencia riešenia (teraz nepodstatné):

```
check (i,j) (m,n) = (i==m) || (j==n) || (j+i==n+m) || (j+m==i+n)
```

```
safe p n = all (True==) [not (check (i,j) (m+1,n)) | (i,j) <- zip [1..m] p]
               where m=length p
```

-- backtrack

queens size = queens1 size where

```
queens1 n | n==0 = [[]]
```

```
          | otherwise = [cr++[row] | cr<-queens1 (n-1) , row<-[1..size], safe cr row]
```

length \$ queens 10 = 724 (3.16 secs, 1,897,245,320 bytes)

mqueens size = mqueens1 size where

```
mqueens1 n | n==0 = return []
```


```
          | otherwise = do { cr <- mqueens1 (n-1) ;
                             row <- [1..size] ;
                             guard (safe cr row) ;
                             return (cr++[row]) }
```

length \$ mqueens 10 = 724 (3.12 secs, 1,954,471,256 bytes)

súbor:queens.hs

Kôň

zdroj : <http://learnyouahaskell.com/a-fistful-of-monads#the-list-monad>



```
type KnightPos = (Int,Int)
```

```
-- jeden krok koňa na šachovnici
```

```
moveKnight :: KnightPos -> [KnightPos]
```

```
moveKnight (c,r) = do { (c',r') <- [(c+2,r-1),(c+2,r+1),(c-2,r-1),(c-2,r+1),(c+1,r-2),(c+1,r+2),(c-1,r-2),(c-1,r+2)]  
                        guard (c' `elem` [1..8] && r' `elem` [1..8]) ; -- stále na ploche  
                        return (c',r') }
```

```
-- kam sa dostane kôň na k krokov
```

```
ink :: Int -> KnightPos -> [KnightPos]
```

```
ink 0 start = return start
```

```
ink k start = do { m <- moveKnight start ;  
                  mm <- ink (k-1) m ;  
                  return mm }
```

```
length $ ink 7 (1,1) = 45016
```

```
length $ nub $ ink 7 (1,1) = 32
```

súbor:knight.hs



filterM

(Control.Monad)

```
filterM    :: (Monad m) => (a -> m Bool) -> [a] -> m [a]
```

```
> filterM (\x->[True, False]) [1,2,3]           -- potenčná množina, powerset  
[[1,2,3],[1,2],[1,3],[1],[2,3],[2],[3],[]]
```

```
filterM    :: (Monad m) => (a -> m Bool) -> [a] -> m [a]
```

```
filterM _ [] = return []
```

```
filterM p (x:xs) = do
```

```
    flg <- p x
```

```
    ys  <- filterM p xs
```

```
    return (if flg then x:ys else ys)
```



mapM, forM

(Control.Monad)

mapM :: (Monad m) => (a -> m b) -> [a] -> m [b]
mapM f = sequence . map f

forM :: (Monad m) => [a] -> (a -> m b) -> m [b] -- len záměna args.
forM = flip mapM

```
> mapM (\x->[x,11*x]) [1,2,3]
[[1,2,3],[1,2,33],[1,22,3],[1,22,33],[11,2,3],[11,2,33],[11,22,3],[11,22,33]]
```

```
> forM [1,2,3] (\x->[x,11*x])
[[1,2,3],[1,2,33],[1,22,3],[1,22,33],[11,2,3],[11,2,33],[11,22,3],[11,22,33]]
```

```
> mapM print [1,2,3]
1
2
3
[(),(),()]
```

```
> mapM_ print [1,2,3]
1
2
3
```



foldM

(Control.Monad)

```
foldM :: (Monad m) => (a -> b -> m a) -> a -> [b] -> m a
foldM _ a [] = return a
foldM f a (x:xs) = f a x >>= \y -> foldM f y xs
```

```
foldM f a1 [x1, ..., xn] =
  do {
    a2 <- f a1 x1;
    a3 <- f a2 x2;
    ...
    an <- f an-1 xn-1;
    return f an xn }
```

```
> foldM (\y -> \x ->
  do { print (show x++"..."++ show y);
    return (x*y)})
  1 [1..10]
???
```

```
> foldM (\y -> \x -> do print (show x++"..."++ show y); return (x*y)) 1 [1..10]
???
```



Error monad

```
newtype Either a b = Right a | Left b
instance (Error e) => Monad (Either e) where
    return x = Right x
    Right x >>= f = f x
    Left err >>= f = Left err
    fail msg = Left (strMsg msg)
```

```
data Term = Con Int | Div Term Term deriving(Show, Read, Eq)
```

```
eval      :: Term -> Either String Int
```

```
eval(Con a) = return a
```

```
eval(Div t u) = do { valT <- eval t ;
                    valU <- eval u ;
                    if valU == 0 then
                        fail "div by zero"
                    else
                        return (valT `div` valU) }
```

```
> eval (Div (Con 1972) (Con 23))
```

```
Right 85
```

```
> eval (Div (Con 1972) (Con 0))
```

```
*** Exception: div by zero
```

súbor:Error.hs

Writer monad

(Control.Monad.Writer)

```
newtype Writer w a = Writer { runWriter :: (a, w) }
instance (Monoid w) => Monad (Writer w) where
    return x = Writer (x, mempty)
    (Writer (x,v)) >>= f =
        let (Writer (y, v')) = f x in Writer (y, v `mappend` v')
```

```
data Term = Con Int | Div Term Term deriving(Show, Read, Eq)
```

```
out :: Int -> Writer [String] Int
```

```
out x = writer (x, ["number: " ++ show x])
```

```
eval      :: Term -> Writer [String] Int
```

```
eval(Con a) = out a
```

```
eval(Div t u) = do {      valT <- eval t ;
                        valU <- eval u ;
                        out (valT `div` valU) ;
                        return (valT `div` valU) }
```

```
> eval (Div (Con 1972) (Con 23))
```

```
WriterT (Identity (85,["number: 1972","number: 23","number: 85"])))
```

```
> runWriter $ eval (Div (Con 1972) (Con 23))
```

```
(85,["number: 1972","number: 23","number: 85"])
```

súbor:Write.hs



Writer monad

(Control.Monad.Writer)

```
-- tell :: MonadWriter w m => w -> m ()
```

```
gcd' :: Int -> Int -> Writer [String] Int
```

```
gcd' a b | b == 0 = do
```

```
    tell ["result " ++ show a]
```

```
    return a
```

```
  | otherwise = do
```

```
    tell [show a ++ " mod " ++ show b ++ " = " ++ show (a `mod` b)]
```

```
    gcd' b (a `mod` b)
```

```
> gcd' 18 12
```

```
WriterT (Identity (6,["18 mod 12 = 6","12 mod 6 = 0","result 6"]))
```

```
> runWriter (gcd' 2016 48)
```

```
(48,["2016 mod 48 = 0","result 48"])
```

```
> mapM putStrLn (snd $ runWriter (gcd' 2016 48))
```

```
2016 mod 48 = 0
```

```
result 48
```

```
[(),()]
```

súbor:Write.hs

IO Monad

(vstup čísla)



```
type Kopa = Int
```

```
finished :: Kopa -> Bool
```

-- kedy hra končí

```
finished = (== 0)
```

```
valid :: Kopa -> Int -> Bool
```

-- korektný ťah

```
valid kopa beriem = (kopa >= beriem) && beriem < 4 && beriem > 0
```

```
getDigit :: String -> IO Int
```

```
getDigit prompt = do putStr prompt
```

```
    x <- getChar
```

```
    if isDigit x
```

```
        then return (digitToInt x)
```

```
    else
```

```
        getDigit ""
```

súbor:nim1.hs

IO Monad

(dvaja hráči)



```
play2 :: Kopa -> Bool -> IO ()
play2 kopa hrac =
  do putStrLn ("kopa:" ++ (show kopa))
    if finished kopa then
      putStrLn ("Hrac " ++ (show (not $ hrac)) ++ " vyhral!")
    else
      do putStrLn ("Ide hrac " ++ (show hrac))
        beriem <- getDigit "kolko beries : "
        if valid kopa beriem then
          play2 (kopa - beriem) (not $ hrac)
        else
          do putStrLn "zly tah"
            play2 kopa hrac
```

```
nim2 :: IO ()
nim2 = play2 (nextInt 10 20) True
```

-- generujeme náhodnú kopa 10..19

IO Monad

(jeden hráč proti kompu)



```
play1 :: Kopa -> IO ()
play1 kopa =
  do putStrLn ("kopa:" ++ (show kopa))
    if finished kopa then
      putStrLn "prehral si :("
    else
      do beriem <- getDigit "kolko beries : "
        if valid kopa beriem then
          let kopa' = kopa - beriem in
            if finished kopa' then
              putStrLn "vyhral si :)"
            else
              do putStrLn ("ja beriem:" ++ (show (kopa' - (strategia kopa'))))
                play1 (strategia kopa')
        else
          do putStrLn "zly tah"
            play1 kopa
```

```
strategia :: Int -> Int
strategia kopa
  | kopa `mod` 4 == 0 = kopa-1
  | otherwise = kopa - (kopa `mod` 4)

nim1 :: IO ()
nim1 = play1 (nextInt 10 20)
```



State monad

(Control.Monad.State)

```
newtype State s a = State { runState :: (s -> (a,s)) }
```

```
instance Monad (State s) where  
  return a          = State \s -> (a,s)  
  (State x) >>= f = State \s ->  
    let (v,s') = x s in runState (f v) s',
```

```
class (Monad m) => MonadState s m | m -> s where  
  get :: m s                                -- get vrátí stav z monády  
  put :: s -> m ()                          -- put prepíše stav v monáde
```

```
modify :: (MonadState s m) => (s -> s) -> m ()  
modify f = do { s <- get ;  
               put (f s) }
```

Čo je newtype vs. data vs. type

newtype State s a = State { runState :: (s -> (a,s)) }

State s a má rovnakú reprezentáciu ako s -> (a,s), ale nie je to

type State s a = s -> (a,s)

data State s a = State { runState :: (s -> (a,s)) }




State s a je reprezentovaná krabicou State s pointrom na s -> (a,s)

Príklad:

data Book = Book Int Int

newtype Book = Book (Int, Int)

data Book = Book (Int, Int)





State s a

(basics-1)

```
newtype State s a = State { runState :: (s -> (a,s)) }
```

- `runState :: State s a -> (s -> (a, s))` -- vráti funkciu state monády
- `evalState :: State s a -> s -> a` -- vráti výsledok state monády pre stav s
- `execState :: State s a -> s -> s` -- vráti výsledný stav state monády pre vstupný stav s

```
:t runState ((return "hello") :: State Int String)
```

```
runState ((return "hello") :: State Int String) :: Int -> (String, Int)
```

```
runState ((return "hello") :: State Int String) 77 = ("hello",77)
```

```
evalState ((return "hello") :: State Int String) 77 = "hello"
```

```
execState ((return "hello") :: State Int String) 77 = 77
```

```
newtype State s a = State { runState :: (s -> (a,s)) }
```

State s a

(basics-2)

```
return :: a -> State s a      -- monáda s výsledkom x::a, stavom s
return x s = (x,s)            -- return x = \s -> (x,s)

get :: State s s               -- stav state monády je jej výsledkom
get s = (s,s)                 -- get = \s -> (s,s)

runState get 1 = (1,1)

put :: s -> State s ()        -- prepíše stav monády x, výsledok je nezaujímavý
put x s = ((),x)              -- put x = \s -> ((),x)

runState (put 5) 1 = ((),5)

runState (do { put 5; return 'X' }) 1 = ('X',5)

modify :: (s -> s) -> State s ()
modify f = do { x <- get; put (f x) }

runState (modify (+3)) 1 = ((),4)
runState (do { modify (+3); return "hello"}) 1 = ("hello",4)
```



```
newtype State s a = State { runState :: (s -> (a,s)) }
```

State s a

(basics-3)

```
let increment = do { x <- get; put (x+1); return x } in runState increment 77  
= (77,78)
```

```
gets :: (s -> b) -> State s b
```

```
gets f = do { x <- get; return (f x) }
```

```
runState (gets (+1)) 77 = (78,77)
```

```
evalState (gets (+1)) 77 = 78
```

-- vráti výsledok state monády pre
vstupný stav s, po aplikovaní funkcie

```
execState (gets (+1)) 77 = 77
```

-- vráti výsledný stav state monády pre
vstupný stav s, a ten sa nezmenil

```
runState (modify (+1)) 77 = ((),78)
```

State Stack

```
pop :: State Stack Int
pop = state \(x:xs) -> (x,xs))

push :: Int -> State Stack ()
push a = state \(xs -> ((),a:xs))
```

type Stack = [Int]

stav

výsledok

pushAll :: Int -> State Stack String

pushAll 0 = return ""

```
pushAll n = do {
  push n;
  str <- pushAll (n-1);
  nn <- pop;
  return (show nn ++ str)}
```

evalState vráti výslednú hodnotu

```
> evalState (pushAll 10) []
"10987654321"
```

execState vráti výsledný stav

```
> execState (pushAll 10) []
[]
```

type Stack = [Int]

pushAll' :: Int -> State Stack String

pushAll' 0 = return ""

pushAll' n = do

```
stack <- get -- push n
put (n:stack)
```

```
str <- pushAll (n-1)
```

```
(nn:stack') <- get -- nn <- pop
put stack'
```

```
return (show nn ++ str)
```

```
> evalState (pushAll' 10) []
```

```
"10987654321"
```

```
> execState (pushAll' 10) []
```

```
[]
```

súbor:stack.hs

Preorder so stavom

(Control.Monad.State)

```
data Tree a = Nil |  
            Node a (Tree a) (Tree a) deriving (Show, Eq)
```

stav

```
preorder :: Tree a -> State [a] ()  
preorder Nil  
preorder (Node value left right)
```

```
-- stav a výstupná hodnota  
= return ()  
=  
do {
```

```
e :: Tree String  
e = Node "c" (Node "a" Nil Nil) (Node "b" Nil Nil)
```

```
> execState (preorder e) [] -- stav  
["b","a","c"]
```

```
> evalState (preorder e) [] -- výsledok  
( )
```

```
str<-get; -- get state=preorderlist  
put (value:str); -- modify (value:)  
preorder left;  
preorder right;  
return () }
```

súbor:tree.hs

stav

výsledok

Prečíslovanie binárneho stromu

```
reindex :: Tree a -> State Int (Tree Int)
reindex Nil          = return Nil
reindex (Node value left right) =
    do {
```

-- stav a výstupná hodnota

```
        i <- get;
        put (i+1);
        ileft <- reindex left;
        iright <- reindex right;
        return (Node i ileft iright) }
```

> e'

Node "d" (Node "c" (Node "a" Nil Nil) (Node "b" Nil Nil)) (Node "c" (Node "a" Nil Nil) (Node "b" Nil Nil))

> evalState (reindex e') 0

Node 0 (Node 1 (Node 2 Nil Nil) (Node 3 Nil Nil)) (Node 4 (Node 5 Nil Nil) (Node 6 Nil Nil))

> execState (reindex e') 0

7

súbor:tree.hs

Prečíslovanie stromu 2

stav

výsledok

```
type Table a = [a]
```

```
numberTree :: Eq a => Tree a -> State (Table a) (Tree Int)
```

```
numberTree Nil = return Nil
```

```
numberTree (Node x t1 t2) = do
    num <- numberNode x
    nt1 <- numberTree t1
    nt2 <- numberTree t2
    return (Node num nt1 nt2)
```


where

```
numberNode :: Eq a => a -> State (Table a) Int
```

```
numberNode x = do
    table <- get
    (newTable, newPos) <- return (addNode x table)
    put newTable
    return newPos
```

```
addNode :: (Eq a) => a -> Table a -> (Table a, Int)
```

```
addNode x table = case (findIndexInList (== x) table) of
    Nothing -> (table ++ [x], length table)
    Just i -> (table, i)
```



súbor:tree.hs



Prečíslovanie stromu 2

```
numTree :: (Eq a) => Tree a -> Tree Int  
numTree t = evalState (numberTree t) []
```

```
> numTree ( Node "Zero"  
             (Node "One" (Node "Two" Nil Nil)  
               (Node "One" (Node "Zero" Nil Nil) Nil)) Nil)
```

```
Node 0 (Node 1 (Node 2 Nil Nil) (Node 1 (Node 0 Nil Nil) Nil)) Nil
```