

Monády – úvod



Phil Wadler: <http://homepages.inf.ed.ac.uk/wadler/topics/monads.html>

- Monads for Functional Programming In *Advanced Functional Programming*, Springer Verlag, LNCS 925, 1995,

- Noel Winstanley: What the hell are Monads?, 1999

<http://web.cecs.pdx.edu/~antoy/Courses/TPFLP/lectures/MONADS/Noel/research/monads.html>

- Jeff Newbern's: All About Monads

https://www.cs.rit.edu/~swm/cs561/All_About_Monads.pdf

- Dan Bensen: A (hopefully) painless introduction to monads,

<http://www.prairienet.org/~dsb/monads.htm>

Monady sú použiteľný nástroj pre programátora poskytujúci:

- modularitu – skladať zložitejšie výpočty z jednoduchších (no side-effects),
- flexibilitu – výsledný kód je ľahšie adaptovateľný na zmeny,
- izoluje side-effect operácie (napr. IO) od čisto funkcionálneho zvyšku.



Maybe monad

Maybe je podobné Exception (Nothing~~Raise String, Just a ~~Return a)

```
data Maybe a = Nothing | Just a
```

```
instance Monad Maybe where
```

```
    return v      = Just v
```

-- vrát' hodnotu

```
    fail          = Nothing
```

-- vrát' neúspech

```
    Nothing >>= f = Nothing
```

-- ak už nastal neúspech, trvá do konca

```
    (Just x) >>= f = f x
```

-- ak je zatiaľ úspech, závisí to na výpočte f

```
return v      = Just v
fail          = Nothing
Nothing >>= f = Nothing
(Just x) >>= f = f x
```

Príklady na Maybe Monad

- konštaty: Just 1, Nothing :: Maybe Int

- základné operácie:

(Just 1) >>= (\x -> Nothing) = Nothing

(Just 1) >>= (\x -> Just (1+x)) = Just 2

Nothing >>= (\x -> Just (1+x)) = Nothing

do { x<-(Just 1); Nothing } :: Maybe t = Nothing

do { x<-(Just 1); return (1+x) } :: Maybe Int = Just 2

do { x<-(return 1); return (1+x) } :: (Monad m, Num b) => m b

do { x<-(return 1); return (1+x) } = 2

do { x<-(return 1); return (1+x) } :: Maybe Int = Just 2

do { x<-(return 1); return (1+x) } :: [Int] = [2]

do { x<-Nothing; return (1+x) } :: Maybe t = Nothing



Maybe sequence

```
sequence      :: Monad m => [m a] -> m [a]
sequence []    = return []
sequence (c:cs) = do { x <- c; xs <- sequence cs; return (x:xs) }
```

```
sequence [Just "a", Just "b", Just "d"]      = Just ["a","b","d"]
sequence [Just "a", Just "b", Nothing, Just "d"] = Nothing
```



Maybe MonadPlus

```
data Maybe a = Nothing | Just a
```

```
class Monad m => MonadPlus m where – podtrieda, resp. podinterface  
  mzero    :: m a                    -- ∅  
  mplus     :: m a -> m a -> m a    -- disjunkcia
```

```
instance MonadPlus Maybe where  
  mzero          = Nothing           -- fail...  
  Just x `mplus` y    = Just x       -- or  
  Nothing `mplus` y   = y
```

```
Just "a" `mplus` Just "b"           = Just "a"  
Just "a" `mplus` Nothing             = Just "a"  
Nothing `mplus` Just "b"             = Just "b"
```



Zákony monád a monády Plus

- vlastnosti `return a >>=`:

```
return x >>= f           = f x           -- return ako identita zľava
p >>= return             = p             -- return ako identita sprava
p >>= (\x -> (f x >>= g)) = (p >>= (\x -> f x)) >>= g -- "asociativita"
```

- vlastnosti `zero a `plus``:

```
zero `plus` p           = p             -- zero ako identita zľava
p `plus` zero           = p             -- zero ako identita sprava
p `plus` (q `plus` r)   = (p `plus` q) `plus` r -- asociativita
```

- vlastnosti `zero `plus` a >>=`:

```
zero >>= f               = zero          -- zero ako identita zľava
p >>= (\x->zero)          = zero          -- zero ako identita sprava
(p `plus` q) >>= f       = (p >>= f) `plus` (q >>= f) -- distribut.
```



Sheep family

```
adam  = Sheep "Adam"  Nothing Nothing
eve   = Sheep "Eve"   Nothing Nothing
uranus = Sheep "Uranus" Nothing Nothing
gaea  = Sheep "Gaea"  Nothing Nothing
kronos = Sheep "Kronos" (Just gaea) (Just uranus)
holly  = Sheep "Holly" (Just eve) (Just adam)
roger  = Sheep "Roger" (Just eve) (Just kronos)
molly  = Sheep "Molly" (Just holly) (Just roger)
dolly  = Sheep "Dolly" (Just molly) Nothing
```

-- a sheep has its name, and maybe mother and father

```
data Sheep = Sheep {name::String, mother::Maybe Sheep, father::Maybe Sheep}
                  deriving (Eq)
```

starý otec z matkinej strany

```
maternalGrandfather :: Sheep -> Maybe Sheep
```

```
maternalGrandfather' o = if mother o == Nothing then
```

```
    Nothing
```

```
  else
```

```
    father (fromJust (mother o))
```

-- klasicky:

```
maternalGrandfather s = do{ m <- mother s ;
                           father m }
```

-- monadicky:

```
maternalGrandfather dolly = Just "Roger"
```

matky otca otec

```
mothersPaternalGrandfather :: Sheep -> Maybe Sheep
```

```
mothersPaternalGrandfather s = do { m <- mother s ;
```

```
    gf <- father m ;
```

```
    father gf }
```

```
mothersPaternalGrandfather dolly = Just "Kronos"
```



List monad

- List monad použijeme, ak simulujeme nedeterministický výpočet

```
data List a = Null | Cons a (List a) deriving (Show)      -- alias [a]
```

```
instance Functor List where                                -- to je vlastne map
```

```
    fmap f Nil = Nil
```

```
    fmap f (Cons x xs) = Cons (f x) (fmap f xs)
```

```
instance Monad List where
```

```
    return x      = [x]
```

```
    m >>= f       = concatMap f m
```

```
    concatMap     = concat . map f m
```

```
:: a -> [a]
```

```
:: [a] -> (a -> [b]) -> [b]
```



```
return :: a -> [a]  
>>=   :: [a] -> (a -> [b]) -> [b]
```



List monad

```
type List a      = [a]
```

```
instance Functor List where  
    fmap = map
```

```
instance Monad List where  
    return v      = [v]  
    [] >>= f      = []  
    (x:xs) >>= f  = f x ++ (xs >>= f)    -- concatMap f (x:xs)
```

```
instance MonadPlus List where  
    mzero          = []  
    [] `mplus` ys  = ys  
    (x:xs) `mplus` ys = x : (xs `plus` ys) -- mplus je klasický append
```

List monad - vlastnosti

Príklad, tzv. listMonad $M\ a = List\ a = [a]$

$return\ x = [x]$ $:: a \rightarrow [a]$

$m\ >>= f = concatMap\ f\ m$ $:: [a] \rightarrow (a \rightarrow [b]) \rightarrow [b]$

$concatMap = concat . map\ f\ m$

Cvičenie: overme platnosť zákonov:

- $return\ c\ >>= (\backslash x \rightarrow g) = g[x/c]$
 - $[c]\ >>= (\backslash x \rightarrow g) = concatMap\ (\backslash x \rightarrow g)\ [c] = concat . map\ (\backslash x \rightarrow g)\ [c] = concat\ [g[x/c]] = g[x/c]$
- $m\ >>= \backslash x \rightarrow return\ x = m$
 - $[c_1, \dots, c_n]\ >>= (\backslash x \rightarrow return\ x) = concatMap\ (\backslash x \rightarrow return\ x)\ [c_1, \dots, c_n] = concat . map\ (\backslash x \rightarrow return\ x)\ [c_1, \dots, c_n] = concat\ [[c_1], \dots, [c_n]] = [c_1, \dots, c_n]$
- $m1\ >>= (\backslash x \rightarrow m2\ >>= (\backslash y \rightarrow m3)) = (m1\ >>= (\backslash x \rightarrow m2))\ >>= (\backslash y \rightarrow m3)$
 - $([c_1, \dots, c_n]\ >>= (\backslash x \rightarrow [d_1, \dots, d_m]))\ >>= (\backslash y \rightarrow m3) = (concat\ [[d_1[x/c_1], \dots, d_m[x/c_1]], \dots, [d_1[x/c_n], \dots, d_m[x/c_n]]])\ >>= (\backslash y \rightarrow m3) = ([d_1[x/c_1], \dots, d_m[x/c_1], \dots, d_1[x/c_n], \dots, d_m[x/c_n]])\ >>= (\backslash y \rightarrow m3) = ([d_1[x/c_1], \dots, d_m[x/c_1], \dots, d_1[x/c_n], \dots, d_m[x/c_n]])\ >>= (\backslash y \rightarrow [e_1, \dots, e_k]) = \dots [e_i[y/d_j[x/c_i]]]$



Zákony monadPlus pre List

- vlastnosti zero a `plus` :

zero `plus` p	= p	-- [] ++ p = p
p `plus` zero	= p	-- p ++ [] = p
p `plus` (q `plus` r)	= (p `plus` q) `plus` r	-- asociativita ++

- vlastnosti zero `plus` a >>= :

zero >>= f	= zero	-- concat . map f [] = []
p >>= (\x->zero)	= zero	-- concat . map (\x->[]) p = []
(p `plus` q) >>= f	= (p >>= f) `plus` (q >>= f)	-- concat . map f (p ++ q) = concat . map f p ++ concat . map f q



List monad vs. comprehension

```
squares lst = do    x <- lst  
                  return (x * x)
```

-- vlastne znamená

```
squares lst =      lst >>= \x -> return (x * x)
```

-- po dosadení

```
squares lst = concat . map (\x -> [x * x]) lst
```

-- eta redukcia

```
squares = concat . map (\x -> [x * x])
```

-- a takto by sme to napísali bez všetkého

```
squares = map (\x -> x * x)
```

-- iný príklad: kartézsky súčin

```
cart xs ys = do x <- xs  
               y <- ys  
               return (x,y)
```



Sheep family

```
adam = Sheep "Adam"  Nothing Nothing
eve  = Sheep "Eve"   Nothing Nothing
uranus = Sheep "Uranus" Nothing Nothing
gaea = Sheep "Gaea"  Nothing Nothing
kronos = Sheep "Kronos" (Just gaea) (Just uranus)
holly = Sheep "Holly" (Just eve) (Just adam)
roger = Sheep "Roger" (Just eve) (Just kronos)
molly = Sheep "Molly" (Just holly) (Just roger)
dolly = Sheep "Dolly" (Just molly) Nothing
```

```
data Sheep = Sheep {name::String, mother::Maybe Sheep, father::Maybe Sheep}
```

```
parents_ :: Sheep -> [Maybe Sheep]
```

```
parents_ x = [father x, mother x]
```

```
parents_ dolly = [Nothing, Just "Molly"]
```

```
parents :: Sheep -> Maybe [Sheep]
```

```
parents x = sequence [father x, mother x]
```

```
parents dolly = Nothing
```

```
parents roger = Just ["Kronos", "Eve"]
```

```
parents' :: Sheep -> [Sheep]
```

```
parents' x = (if father x == Nothing then [] else [ fromJust (father x) ]) ++
              (if mother x == Nothing then [] else [ fromJust (mother x) ])
```

```
parents' dolly = ["Molly"]
```

```
parents'' :: Sheep -> Maybe [Sheep]
```

```
parents' roger = ["Kronos", "Eve"]
```

```
parents'' x = do { o<-father x; return [o] } `mplus` (do m<-mother x; return [m])
```

```
parents'' dolly = Just ["Molly"]
```

```
parents''' :: Sheep -> Maybe [Sheep]
```

```
parents'' roger = Just ["Kronos"]
```

```
parents''' x = do { o<-father x; m<-mother x; return ([o] `mplus` [m]) }
```

```
parents''' dolly = Nothing
```

```
parents''' roger = Just ["Kronos", "Eve"]
```



Guard

(Control.Monad)

```
pythagoras = [(x, y, z) | z <- [1..],           -- pythagorejské trojuholníky
                        x <- [1..z],
                        y <- [x..z],
                        x*x+y*y == z*z]
```

```
pythagoras' = do z <- [1..]
                x <- [1..z]
                y <- [x..z]                      -- zlé riešenie, prečo ?
                if x*x+y*y == z*z then return (x,y,z) else return ()
```

```
pythagoras" ... if x*x+y*y == z*z then return "hogo-fogo" else []
                return (x,y,z)                      resp. ["hogo-fogo"]
```

```
pythagoras"" ... if x*x+y*y == z*z then return () else []
                  resp. guard (x*x+y*y == z*z)
                  return (x,y,z)
```



Guard

(Control.Monad)

Kartézsky súčin

```
guard :: (MonadPlus m) => Bool -> m ()
guard True  = return ()
guard False = mzero
> guard (9 > 5) >> return "hogo" :: [String]
["hogo"]
> guard (5 > 9) >> return "fogo" :: [String]
[]
```

```
listComprehension xs ys = [(x,y) | x<-xs, y<-ys ]
```

```
listComprehension [1,2,3] ['a','b','c'] = [(1,'a'),(1,'b'),(1,'c'),(2,'a'),(2,'b'),(2,'c'),(3,'a'),(3,'b'),(3,'c')]
```

```
guardedListComprehension xs ys = [(x,y) | x<-xs, y<-ys, x<=y, x*y == 24 ]
```

```
guardedListComprehension [1..10] [1..10] = [(3,8),(4,6)]
```

```
monadComprehension xs ys = do { x<-xs; y<-ys; return (x,y) }
```


```
monadComprehension [1,2,3] ['a','b','c'] = [(1,'a'),(1,'b'),(1,'c'),(2,'a'),(2,'b'),(2,'c'),(3,'a'),(3,'b'),(3,'c')]
```

```
guardedMonadComprehension xs ys =
```

```
do { x<-xs; y<-ys; guard (x<=y); guard (x*y==24); return (x,y) }
```

```
guardedMonadComprehension [1..10] [1..10] = [(3,8),(4,6)]
```

Backtracking



```
check (i,j) (m,n) = (i==m) || (j==n) || (j+i==n+m) || (j+m==i+n)
```

```
safe p n = all (True==) [not (check (i,j) (m+1,n)) | (i,j) <- zip [1..m] p]
               where m=length p
```

-- backtrack

```
queens n = queens1 n n
```

```
queens1 n v | n==0 = [[]]
```

```
            | otherwise = [y++[p] | y <- queens1 (n-1) v, p <- [1..v], safe y p]
```

```
length $ queens 10 = 724 (3.16 secs, 1,897,245,320 bytes)
```

```
mqueens n = mqueens1 n n
```

```
mqueens1 n v | n==0 = return []
```

```
            | otherwise = do y <- mqueens1 (n-1) v
```

```
                          p <- [1..v]
```


```
                          guard (safe y p)
```

```
                          return (y++[p])
```

```
length $ mqueens 10 = 724 (3.12 secs, 1,954,471,256 bytes)
```


Kôň

zdroj : <http://learnyouahaskell.com/a-fistful-of-monads#the-list-monad>



```
type KnightPos = (Int,Int)
```

```
moveKnight :: KnightPos -> [KnightPos]
```

```
moveKnight (c,r) = do (c',r') <- [(c+2,r-1),(c+2,r+1),(c-2,r-1),(c-2,r+1),(c+1,r-2),(c+1,r+2),(c-1,r-2),(c-1,r+2)]
                        guard (c' `elem` [1..8] && r' `elem` [1..8])
                        return (c',r')
```

kam sa dostane kôň na k krokov

```
ink :: Int -> KnightPos -> [KnightPos]
```

```
ink 0 start = return start
```

```
ink k start = do m <- moveKnight start
```

```
                mm <- ink (k-1) m
```

```
                return mm
```

```
length $ ink 7 (0,0) = 45016
```

```
length $ nub $ ink 7 (0,0) = 32
```



filterM

(Control.Monad)

```
filterM    :: (Monad m) => (a -> m Bool) -> [a] -> m [a]
```

```
> filterM (\x->[True, False]) [1,2,3]           -- potenčná množina, powerset  
[[1,2,3],[1,2],[1,3],[1],[2,3],[2],[3],[]]
```

```
filterM    :: (Monad m) => (a -> m Bool) -> [a] -> m [a]
```

```
filterM _ [] = return []
```

```
filterM p (x:xs) = do
```

```
    flg <- p x
```

```
    ys  <- filterM p xs
```

```
    return (if flg then x:ys else ys)
```



mapM, forM

(Control.Monad)

mapM :: (Monad m) => (a -> m b) -> [a] -> m [b]
mapM f = sequence . map f

forM :: (Monad m) => [a] -> (a -> m b) -> m [b] -- len záměna args.
forM = flip mapM

```
> mapM (\x->[x,11*x]) [1,2,3]
[[1,2,3],[1,2,33],[1,22,3],[1,22,33],[11,2,3],[11,2,33],[11,22,3],[11,22,33]]
```

```
> forM [1,2,3] (\x->[x,11*x])
[[1,2,3],[1,2,33],[1,22,3],[1,22,33],[11,2,3],[11,2,33],[11,22,3],[11,22,33]]
```

```
> mapM print [1,2,3]
1
2
3
[(),(),()]
```

```
> mapM_ print [1,2,3]
1
2
3
```



foldM

(Control.Monad)

```
foldM :: (Monad m) => (a -> b -> m a) -> a -> [b] -> m a
foldM _ a [] = return a
foldM f a (x:xs) = f a x >>= \y -> foldM f y xs
```

```
foldM f a1 [x1, ..., xn] =
  do {
    a2 <- f a1 x1;
    a3 <- f a2 x2;
    ...
    an <- f an-1 xn-1;
    return f an xn }
```

```
> foldM (\y -> \x ->
  do { print (show x++"..."++ show y);
        return (x*y)})
  1 [1..10]
???
```

```
> foldM (\y -> \x -> do print (show x++"..."++ show y); return (x*y)) 1 [1..10]
???
```

```
newtype Either a b = Right a | Left b
instance (Error e) => Monad (Either e) where
    return x = Right x
    Right x >>= f = f x
    Left err >>= f = Left err
    fail msg = Left (strMsg msg)
```



Error monad

```
data Term = Con Int | Div Term Term deriving(Show, Read, Eq)
```

```
eval      :: Term -> Either String Int
```

```
eval(Con a) = return a
```

```
eval(Div t u) = do
```

```
    valT <- eval t
```

```
    valU <- eval u
```

```
    if valU == 0 then
```

```
        fail "div by zero"
```

```
    else
```

```
        return (valT `div` valU)
```

```
> eval (Div (Con 1972) (Con 23))
```

```
Right 85
```

```
> eval (Div (Con 1972) (Con 0))
```

```
*** Exception: div by zero
```



Writer monad

(Control.Monad.Writer)

```
newtype Writer w a = Writer { runWriter :: (a, w) }  
instance (Monoid w) => Monad (Writer w) where  
    return x = Writer (x, mempty)  
    (Writer (x,v)) >>= f =  
        let (Writer (y, v')) = f x in Writer (y, v `mappend` v')
```

```
data Term = Con Int | Div Term Term deriving(Show, Read, Eq)
```

```
out :: Int -> Writer [String] Int
```

```
out x = writer (x, ["number: " ++ show x])
```

```
eval      :: Term -> Writer [String] Int
```

```
eval(Con a) = out a
```

```
eval(Div t u) = do
```

```
    valT <- eval t
```

```
    valU <- eval u
```

```
    out (valT `div` valU)
```

```
    return (valT `div` valU)
```

```
> eval (Div (Con 1972) (Con 23))
```

```
WriterT (Identity (85,["number: 1972","number: 23","number: 85"]))
```

```
> runWriter $ eval (Div (Con 1972) (Con 23))
```

```
(85,["number: 1972","number: 23","number: 85"])
```



Writer monad

(Control.Monad.Writer)

```
-- tell :: MonadWriter w m => w -> m ()
```

```
gcd' :: Int -> Int -> Writer [String] Int
```

```
gcd' a b | b == 0 = do
```

```
    tell ["result " ++ show a]
```

```
    return a
```

```
  | otherwise = do
```

```
    tell [show a ++ " mod " ++ show b ++ " = " ++ show (a `mod` b)]
```

```
    gcd' b (a `mod` b)
```

```
> gcd' 18 12
```

```
WriterT (Identity (6,["18 mod 12 = 6","12 mod 6 = 0","result 6"]))
```

```
> runWriter (gcd' 2016 48)
```

```
(48,["2016 mod 48 = 0","result 48"])
```


```
> mapM putStrLn (snd $ runWriter (gcd' 2016 48))
```

```
2016 mod 48 = 0
```

```
result 48
```

```
[(),()]
```

IO Monad



```
type Kopa = Int
```


```
finished :: Kopa -> Bool           -- kedy hra konci  
finished = (== 0)
```

```
valid :: Kopa -> Int -> Bool  -- korektny tah  
valid kopa num = (kopa >= num) && num < 4
```

```
getDigit :: String -> IO Int  
getDigit prompt = do putStr prompt  
                    x <- getChar  
                    if isDigit x  
                      then return (digitToInt x)  
                      else  
                        getDigit ""
```


IO Monad

(dvaja hráči)




```
play2 :: Kopa -> Bool -> IO ()
play2 kopa hrac =
  do putStrLn ("kopa:" ++ (show kopa))
  if finished kopa then
    putStrLn ("Hrac " ++ (show (not $ hrac)) ++ " vyhral!")
  else
    do putStrLn ("Ide hrac " ++ (show hrac))
    num <- getDigit "kolko beries : "
    if valid kopa num then
      play2 (kopa - num) (not $ hrac)
    else
      do putStrLn "zly tah"
      play2 kopa hrac
```

```
nim2 :: IO ()
nim2 = play2 (nextInt 10 20) True
```

IO Monad

(jeden hráč proti kompu)



```
play1 :: Kopa -> IO ()
play1 kopa =
  do putStrLn ("kopa:" ++ (show kopa))
    if finished kopa then
      putStrLn "prehral si :("
    else
      do num <- getDigit "kolko beries : "
        if valid kopa num then
          let kopa' = kopa - num in
            if finished kopa' then
              putStrLn "vyhral si :)"
            else
              do putStrLn ("ja beriem:" ++ (show (kopa' - (strategia kopa'))))
                play1 (strategia kopa')
        else
          do putStrLn "zly tah"
            play1 kopa
```

```
strategia :: Int -> Int
strategia kopa
  | kopa `mod` 4 == 0 = kopa-1
  | otherwise = kopa - (kopa `mod` 4)

nim1 :: IO ()
nim1 = play1 (nextInt 10 20)
```



State monad

(Control.Monad.State)

```
newtype State s a = State { runState :: (s -> (a,s)) }
```

```
instance Monad (State s) where
  return a      = State \s -> (a,s)
  (State x) >>= f = State \s ->
    let (v,s') = x s in runState (f v) s',
```

```
class (Monad m) => MonadState s m | m -> s where
  get :: m s                -- get vrátí stav z monády
  put :: s -> m ()          -- put prepíše stav v monáde
```

```
modify :: (MonadState s m) => (s -> s) -> m ()
modify f = do  s <- get
              put (f s)
```

newtype

```
newtype State s a = State { runState :: (s -> (a,s)) }
```




State s a má rovnakú reprezentáciu ako (s -> (a,s))

```
data State s a = State { runState :: (s -> (a,s)) }
```

State s a je reprezentovaná krabicou State s pointrom na (s -> (a,s))

Príklad:

```
data Book = Book Int Int    newtype Book = Book (Int, Int)    data Book = Book (Int, Int)
```





State Stack

```
pop :: State Stack Int
pop = state(\(x:xs) -> (x,xs))
```

```
push :: Int -> State Stack ()
push a = state(\xs -> ((),a:xs))
```

```
type Stack = [Int]
```

```
type Stack = [Int]
```

```
pushAll :: Int -> State Stack String
pushAll 0 = return ""
pushAll n = do
  push n
  str <- pushAll (n-1)
  nn <- pop
  return (show nn ++ str)
```

```
pushAll' :: Int -> State Stack String
pushAll' 0 = return ""
pushAll' n = do
```

```
  stack <- get -- push n
  put (n:stack)
```

```
  str <- pushAll (n-1)
```

```
  (nn:stack') <- get -- nn <- pop
  put stack'
```

```
  return (show nn ++ str)
```

```
> evalState (pushAll 10) []
"10987654321"
> execState (pushAll 10) []
[]
```

```
> evalState (pushAll' 10) []
"10987654321"
> execState (pushAll' 10) []
[]
```



Preorder so stavom

(Control.Monad.State)

```
data Tree a = Nil |
             Node a (Tree a) (Tree a)
             deriving (Show, Eq)
```

```
preorder :: Tree a -> State [a] ()
```

```
preorder Nil
```

```
preorder (Node value left right)
```

```
= return ()
```

```
=
do {
```

-- stav a výstupná hodnota

```
str<-get; -- get state=preorderlist
put (value:str); -- modify (value:)
preorder left;
preorder right;
return () }
```

```
e :: Tree String
```

```
e = Node "c" (Node "a" Nil Nil) (Node "b" Nil Nil)
```

```
> execState (preorder e) []
["b","a","c"]
```

```
> evalState (preorder e) []
()
```



Prečíslovanie binárneho stromu

```
index :: Tree a -> State Int (Tree Int)      -- stav a výstupná hodnota
index Nil          = return Nil
index (Node value left right) =
    do {
        i <- get;
        put (i+1);
        ileft <- index left;
        iright <- index right;
        return (Node i ileft iright) }
```

> e'

```
Node "d" (Node "c" (Node "a" Nil Nil) (Node "b" Nil Nil)) (Node "c" (Node "a" Nil
Nil) (Node "b" Nil Nil))
```

> evalState (index e') 0

```
Node 0 (Node 1 (Node 2 Nil Nil) (Node 3 Nil Nil)) (Node 4 (Node 5 Nil Nil) (Node 6
Nil Nil))
```

> execState (index e') 0

7

Prečíslovanie stromu 2

```
type Table a = [a]
```

```
numberTree :: Eq a => Tree a -> State (Table a) (Tree Int)
```

```
numberTree Nil = return Nil
```

```
numberTree (Node x t1 t2) = do  num <- numberNode x
                                nt1 <- numberTree t1
                                nt2 <- numberTree t2
                                return (Node num nt1 nt2)
```


where

```
numberNode :: Eq a => a -> State (Table a) Int
```

```
numberNode x = do  table <- get
                   (newTable, newPos) <- return (nNode x table)
                   put newTable
                   return newPos
```

```
nNode :: (Eq a) => a -> Table a -> (Table a, Int)
```

```
nNode x table = case (findIndexInList (== x) table) of
                  Nothing -> (table ++ [x], length table)
                  Just i -> (table, i)
```





Prečíslovanie stromu 2

```
numTree :: (Eq a) => Tree a -> Tree Int  
numTree t = evalState (numberTree t) []
```

```
> numTree ( Node "Zero"  
             (Node "One" (Node "Two" Nil Nil)  
             (Node "One" (Node "Zero" Nil Nil) Nil)) Nil)
```

```
Node 0 (Node 1 (Node 2 Nil Nil) (Node 1 (Node 0 Nil Nil) Nil)) Nil
```